



Salesforce Field Reference Guide

Salesforce, Winter '18



CONTENTS

| | |
|---|----|
| Salesforce Fields Reference | 1 |
| Account | 2 |
| AccountContactRole | 3 |
| AccountPartner | 4 |
| AccountTeamMember | 5 |
| AccountTerritoryAssignmentRule | 5 |
| AccountTerritoryAssignmentRuleItem | 6 |
| AccountTerritorySharingRule | 6 |
| ActivityHistory | 7 |
| Announcement | 8 |
| ApexLog | 9 |
| ApexTestQueueItem | 10 |
| ApexTestResult | 10 |
| AppMenuItem | 11 |
| Asset | 12 |
| AttachedContentDocument | 13 |
| Attachment | 14 |
| AuthConfig | 14 |
| AuthConfigProviders | 15 |
| AuthProvider | 16 |
| AuthSession | 16 |
| Bookmark | 17 |
| BrandTemplate | 18 |
| Campaign | 18 |
| CampaignMember | 20 |
| CampaignMemberStatus | 21 |
| Case | 21 |
| CaseContactRole | 22 |
| CaseMilestone | 23 |
| ChatterActivity | 24 |
| ChatterConversation | 24 |
| ChatterConversationMember | 25 |
| ChatterMessage | 25 |
| ClientBrowser | 25 |
| CollaborationGroup | 26 |
| CollaborationGroupMember | 27 |
| CollaborationGroupMemberRequest | 27 |
| CollaborationGroupRecord | 28 |
| CollaborationInvitation | 28 |

Contents

| | |
|----------------------------|----|
| CombinedAttachment | 29 |
| Contact | 30 |
| ContentDistribution | 32 |
| ContentDistributionView | 32 |
| ContentDocument | 33 |
| ContentDocumentLink | 34 |
| ContentWorkspace | 34 |
| ContentWorkspaceDoc | 35 |
| ContentVersion | 36 |
| Contract | 37 |
| ContractContactRole | 39 |
| ContractLineItem | 39 |
| CronJobDetail | 40 |
| CurrencyType | 40 |
| CustomPermission | 41 |
| CustomPermissionDependency | 42 |
| Dashboard | 42 |
| DashboardComponent | 43 |
| DatedConversionRate | 44 |
| Division | 44 |
| Document | 45 |
| Domain | 46 |
| DomainSite | 46 |
| EmailMessage | 47 |
| EmailTemplate | 48 |
| Entitlement | 49 |
| EntitlementContact | 50 |
| EntitlementTemplate | 51 |
| EntitySubscription | 51 |
| Event | 52 |
| EventLogFile | 53 |
| ExternalDataSource | 54 |
| ExternalDataUserAuth | 55 |
| FeedComment | 55 |
| FeedItem | 56 |
| FeedTrackedChange | 57 |
| FieldPermissions | 57 |
| Folder | 58 |
| GoogleDoc | 58 |
| Group | 59 |
| Idea | 60 |
| Lead | 61 |
| ListView | 63 |
| ListViewChart | 63 |

Contents

| | |
|--------------------------------|----|
| LoginHistory | 64 |
| LoginIp | 65 |
| LookedUpFromActivity | 65 |
| MailmergeTemplate | 67 |
| MilestoneType | 67 |
| NamedCredential | 68 |
| Note | 69 |
| NoteAndAttachment | 69 |
| OauthToken | 70 |
| ObjectPermissions | 70 |
| OpenActivity | 71 |
| Opportunity | 72 |
| OpportunityCompetitor | 74 |
| OpportunityContactRole | 74 |
| OpportunityHistory | 75 |
| OpportunityLineItem | 75 |
| OpportunityLineItemSchedule | 76 |
| OpportunityPartner | 77 |
| OpportunitySplit | 78 |
| OpportunitySplitType | 78 |
| OpportunityStage | 79 |
| OpportunityTeamMember | 80 |
| OwnedContentDocument | 80 |
| Partner | 81 |
| PartnerNetworkConnection | 82 |
| PartnerNetworkRecordConnection | 82 |
| PartnerRole | 83 |
| Period | 84 |
| PermissionSet | 84 |
| PermissionSetAssignment | 85 |
| PermissionSetLicense | 86 |
| PermissionSetLicenseAssign | 86 |
| PlatformAction | 87 |
| Pricebook2 | 88 |
| PricebookEntry | 89 |
| Product2 | 89 |
| ProductEntitlementTemplate | 90 |
| Question | 90 |
| Quote | 91 |
| RecentlyViewed | 93 |
| Reply | 94 |
| Report | 95 |
| SelfServiceUser | 95 |
| ServiceContract | 96 |

Contents

| | |
|-----------------------------|-----|
| SetupEntityAccess | 98 |
| Site | 98 |
| SlaProcess | 99 |
| Solution | 100 |
| TagDefinition | 100 |
| Task | 101 |
| Territory | 102 |
| Topic | 103 |
| TopicAssignment | 104 |
| TwoFactorInfo | 104 |
| User | 105 |
| UserAccountTeamMember | 107 |
| UserLogin | 108 |
| UserRecordAccess | 108 |
| UserRole | 108 |
| UserProfile | 109 |
| UserTeamMember | 110 |
| UserTerritory | 111 |
| Vote | 111 |
| WebLink | 112 |

SALESFORCE FIELDS REFERENCE

This is a list of the standard fields for the major objects in Salesforce. For details about using each object, see the Salesforce online help. For more technical details, see the *SOAP API Developer's Guide*.

Fields display in a variety of places in the Salesforce user interface, including page layouts, related lists, search layouts, list views, and reports. For the majority of the fields, you can also use them as *merge fields* within custom formula fields, Visualforce pages, custom links, and custom buttons. Merge fields serve as placeholders for data that will be replaced with information from your records, user information, or company information. For more information about using merge fields, see "Generate Emails From Records" in the Salesforce online help.

Depending on your organization settings and Salesforce Edition, some of these fields may not be available. Not all fields have information in every column. For example, a picklist field does not have a length or precision. The columns in the following tables include:

| | |
|----------------|--|
| Field Label | How the field is displayed in the user interface in areas such as record detail pages, search results, and list views. |
| API Field Name | The name of the field, as represented in the SOAP API. |
| Type | <p>Indicates the data type of a field. With the exception of boolean and division, the types refer to standard Salesforce data types, such as number or picklist.</p> <p>A boolean data type is represented within Salesforce as a checkbox.</p> <p>A division data type is used for the Division picklist available to organizations that have enabled divisions.</p> <p>Note that Lookup fields are both manually assigned and system-generated references to other records. Not all of the Picklist fields listed below have values that can be modified.</p> <p>For more information on data types, see Primitive Data Types in the <i>SOAP API Developer's Guide</i>.</p> |
| Length | The maximum number of characters in the field. For example, the Shipping Zip/Postal Code has a length of 20. You cannot set it to a value longer than 20 characters. |
| Precision | <p>The precision describes the order of magnitude for the field, in other words, the complete length of the number, including digits both to the left and right of the decimal point.</p> <p>For example, 10234.56 has a precision of seven, five for the numbers to the left of the decimal place and two for the numbers to the right.</p> <p>Note that this is different from the <code>Length</code> value in number fields in Salesforce. The <code>Length</code> is the number of digits to the left of the decimal place.</p> |

Scale

The scale is the number of digits used to describe the fractional value of the field, in other words, the number of digits to the right of the decimal place. A scale of two means that two digits to the right of the decimal place will be displayed.

Account

Represents an individual account, which is an organization or person involved with your business (such as customers, competitors, and partners).

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|-------------------|-----------|--------|-----------|-------|
| Account | MasterRecordId | reference | 15 | | |
| Account ID | Id | id | 15 | | |
| Account Number | AccountNumber | string | 40 | | |
| Account Owner | OwnerId | reference | 15 | | |
| Account Site | Site | string | 80 | | |
| Account Source | AccountSource | picklist | 40 | | |
| Annual Revenue | AnnualRevenue | currency | | 18 | 0 |
| Billing Address | BillingStreet | textarea | 255 | | |
| Billing Address | BillingCity | string | 40 | | |
| Billing Address | BillingState | string | 80 | | |
| Billing Address | BillingPostalCode | string | 20 | | |
| Billing Address | BillingCountry | string | 80 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Data.com Key | Jigsaw | string | 20 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Employees | NumberOfEmployees | int | | 8 | 0 |
| Fax | Fax | phone | 40 | | |
| Industry | Industry | picklist | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Jigsaw Company Id | JigsawCompanyId | string | 20 | | |
| Last Activity | LastActivityDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Ownership | Ownership | picklist | 40 | | |
| Parent Account | ParentId | reference | 15 | | |
| Phone | Phone | phone | 40 | | |
| Photo URL | PhotoUrl | url | 255 | | |
| Rating | Rating | picklist | 40 | | |
| SIC Code | Sic | string | 20 | | |
| SIC Description | SicDesc | string | 80 | | |
| Shipping Address | ShippingStreet | textarea | 255 | | |
| Shipping Address | ShippingCity | string | 40 | | |
| Shipping Address | ShippingState | string | 80 | | |
| Shipping Address | ShippingPostalCode | string | 20 | | |
| Shipping Address | ShippingCountry | string | 80 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Ticker Symbol | TickerSymbol | string | 20 | | |
| Type | Type | picklist | 40 | | |
| Website | Website | url | 255 | | |

AccountContactRole

Represents the role that a Contact plays on an Account.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Contact | ContactId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Contact Role ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Primary | IsPrimary | boolean | | | |
| Role | Role | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

AccountPartner

This read-only object represents a partner relationship between two Account objects. It is automatically created when a Partner object is created for a partner relationship between two accounts.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Account From | AccountFromId | reference | 15 | | |
| Account Partner ID | Id | id | 15 | | |
| Account To | AccountToId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity | OpportunityId | reference | 15 | | |
| Primary | IsPrimary | boolean | | | |
| Reverse Partner | ReversePartnerId | reference | 15 | | |
| Role | Role | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

AccountTeamMember

Represents a User who is a member of an Account team.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|--------------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Account Access | AccountAccessLevel | picklist | 40 | | |
| Account Team Member ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Division | Division | picklist | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Team Role | TeamMemberRole | picklist | 40 | | |
| User | UserId | reference | 15 | | |

AccountTerritoryAssignmentRule

An account assignment rule that assigns accounts to territories based on account fields. Only available if territory management has been enabled for your organization.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------------|----------------|-----------|--------|-----------|-------|
| Account Territory Assignment Rule ID | Id | id | 15 | | |
| Active | IsActive | boolean | | | |
| Apply to child territories | IsInherited | boolean | | | |
| Boolean Filter | BooleanFilter | string | 120 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Rule Name | Name | string | 80 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Territory | TerritoryId | reference | 15 | | |

AccountTerritoryAssignmentRuleItem

A row of selection criteria for an AccountTerritoryAssignmentRule object. Only available if territory management has been enabled for your organization.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---|----------------|-----------|--------|-----------|-------|
| Account Territory Assignment Rule | RuleId | reference | 15 | | |
| Account Territory Assignment Rule Item ID | Id | id | 15 | | |
| Custom Field Definition | Field | picklist | 40 | | |
| Operation | Operation | picklist | 40 | | |
| Sort Order | SortOrder | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |
| Value | Value | string | 1000 | | |

AccountTerritorySharingRule

Represents the rules for sharing an Account within a Territory.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------------|--------------------|----------|--------|-----------|-------|
| Account Access | AccountAccessLevel | picklist | 40 | | |
| Account Territory Rule ID | Id | id | 15 | | |
| Case Access | CaseAccessLevel | picklist | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------------|-----------|--------|-----------|-------|
| Contact Access | ContactAccessLevel | picklist | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | textarea | 1000 | | |
| Developer Name | DeveloperName | string | 80 | | |
| Group | GroupId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | Name | string | 80 | | |
| Opportunity Access | OpportunityAccessLevel | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| User/Group | UserOrGroupId | reference | 15 | | |

ActivityHistory

This read-only object is displayed in a related list of closed activities—past events and closed tasks—related to an object. It includes activities for all contacts related to the object. ActivityHistory fields for phone calls are only available if your organization uses Salesforce CRM Call Center.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|-----------------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Activity ID | Id | id | 15 | | |
| All-Day Event | IsAllDayEvent | boolean | | | |
| Assigned To | OwnerId | reference | 15 | | |
| Call Duration | CallDurationInSeconds | int | | 8 | 0 |
| Call Object Identifier | CallObject | string | 255 | | |
| Call Result | CallDisposition | string | 255 | | |
| Call Type | CallType | picklist | 40 | | |
| Closed | IsClosed | boolean | | | |
| Comments | Description | textarea | 32000 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Date | ActivityDate | date | | | |
| Deleted | IsDeleted | boolean | | | |
| Duration | DurationInMinutes | int | | 9 | 0 |
| End | EndDateTime | datetime | | | |
| High Priority | IsHighPriority | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Location | Location | string | 80 | | |
| Name | Whold | reference | 15 | | |
| Priority | Priority | picklist | 40 | | |
| Public | IsVisibleInSelfService | boolean | | | |
| Related To | WhatId | reference | 15 | | |
| Reminder Date/Time | ReminderDateTime | datetime | | | |
| Reminder Set | IsReminderSet | boolean | | | |
| Start | StartDateTime | datetime | | | |
| Status | Status | picklist | 40 | | |
| Subject | Subject | combobox | 80 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Task | IsTask | boolean | | | |
| Type | ActivityType | picklist | 40 | | |

Announcement

Represents a Chatter group announcement. This object is available in API version 30.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|-----------|--------|-----------|-------|
| Announcement ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Expiration Date | ExpirationDate | datetime | | | |
| Feed Item | FeedItemId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Parent | ParentId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

ApexLog

Represents a debug log, containing information about a transaction, including information about Apex, Visualforce, workflow and validation rules. This object is available in API version 19.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------|----------------------|-----------|--------|-----------|-------|
| Application | Application | string | 64 | | |
| Date | LastModifiedDate | datetime | | | |
| Duration (ms) | DurationMilliseconds | int | | 9 | 0 |
| Location | Location | picklist | 40 | | |
| Log ID | Id | id | 15 | | |
| Log Size (bytes) | LogLength | int | | 9 | 0 |
| Log User | LogUserId | reference | 15 | | |
| Operation | Operation | string | 128 | | |
| Request Type | Request | string | 16 | | |
| Start Time | StartTime | datetime | | | |
| Status | Status | string | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |

ApexTestQueueItem

Represents a single Apex class in the Apex job queue. This object is available in API version 23.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|----------------|-----------|--------|-----------|-------|
| Apex Class | ApexClassId | reference | 15 | | |
| Apex Test Queue Item ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Parent Job | ParentJobId | reference | 15 | | |
| Status | Status | picklist | 40 | | |
| Status Detail | ExtendedStatus | string | 1000 | | |
| System Modstamp | SystemModstamp | datetime | | | |

ApexTestResult

Represents the result of an Apex test method execution.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|----------------|-----------|--------|-----------|-------|
| Apex Class | ApexClassId | reference | 15 | | |
| Apex Debug Log | ApexLogId | reference | 15 | | |
| Apex Job | AsyncApexJobId | reference | 15 | | |
| Apex Test Result ID | Id | id | 15 | | |
| Error Message | Message | string | 4000 | | |
| Method Name | MethodName | string | 255 | | |
| Pass/Fail | Outcome | picklist | 40 | | |
| Queue Item | QueueItemId | reference | 15 | | |
| Stack Trace | StackTrace | string | 4000 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Time Started | TestTimestamp | datetime | | | |

AppMenuItem

Represents the organization's default settings for items in the Force.com app menu or App Launcher.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---|---------------------------|-----------|--------|-----------|-------|
| App Type | Type | picklist | 255 | | |
| App requires a registered mobile device | IsRegisteredDeviceOnly | boolean | | | |
| AppMenuItem ID | Id | id | 15 | | |
| Application ID | ApplicationId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Date the mobile app was most recently installed | MobileAppInstalledDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | string | 250 | | |
| Developer Name | Name | string | 80 | | |
| ID for the related mobile app binary | MobileAppBinaryId | string | 255 | | |
| Icon Url | IconUrl | url | 255 | | |
| Info URL | InfoUrl | url | 255 | | |
| Is this a canvas-enabled application | CanvasEnabled | boolean | | | |
| IsUsingAdminAuthorization | IsUsingAdminAuthorization | boolean | | | |
| Label | Label | string | 250 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Logo Image URL | LogoUrl | url | 255 | | |
| Minimum required mobile device OS version | MobileMinOsVer | string | 255 | | |
| Mobile Start Url | MobileStartUrl | url | 255 | | |
| Mobile device OS platform | MobilePlatform | picklist | 255 | | |
| Most recently installed version of the mobile app | MobileAppInstalledVersion | string | 255 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--|-------------------------|----------|--------|-----------|-------|
| Namespace Prefix | NamespacePrefix | string | 80 | | |
| Sort Order | SortOrder | int | | 9 | 0 |
| Start Url | StartUrl | url | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| The canvas url for the canvas application | CanvasUrl | url | 255 | | |
| The configured access method for the canvas application | CanvasAccessMethod | picklist | 255 | | |
| The identifier used to render the canvas application. | CanvasReferenceId | string | 18 | | |
| The selected/supported locations of the canvas application | CanvasSelectedLocations | string | 255 | | |
| Type of mobile device | MobileDeviceType | string | 255 | | |
| URL to install the mobile app | MobileAppInstallUrl | url | 255 | | |
| Version of the mobile app | MobileAppVer | string | 255 | | |

Asset

Represents an item of commercial value, such as a product sold by your company or a competitor, that a customer has purchased and installed.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------|---------------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Asset ID | Id | id | 15 | | |
| Asset Name | Name | string | 255 | | |
| Competitor Asset | IsCompetitorProduct | boolean | | | |
| Contact | ContactId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Install Date | InstallDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Price | Price | currency | | 18 | 0 |
| Product | Product2Id | reference | 15 | | |
| Purchase Date | PurchaseDate | date | | | |
| Quantity | Quantity | double | | 12 | 2 |
| Serial Number | SerialNumber | string | 80 | | |
| Status | Status | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

AttachedContentDocument

This read-only object contains all `ContentDocument` objects associated with an object.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|------------------------|-----------|--------|-----------|-------|
| Content Document Link Id | Id | id | 15 | | |
| Content Modified By | LastModifiedById | reference | 15 | | |
| Content Modified Date | LastModifiedDate | datetime | | | |
| Content Size | ContentSize | int | | 9 | 0 |
| Content URL | ContentUrl | url | 255 | | |
| Created | CreatedDate | datetime | | | |
| Created by | CreatedById | reference | 15 | | |
| Deleted | IsDeleted | boolean | | | |
| Document | ContentDocumentId | reference | 15 | | |
| External Data Source | ExternalDataSourceName | string | 80 | | |
| File Extension | FileExtension | string | 40 | | |
| File Type | FileType | string | 20 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|-----------|--------|-----------|-------|
| Parent | LinkedEntityId | reference | 15 | | |
| Title | Title | string | 255 | | |

Attachment

Represents a file that a User has uploaded and attached to a parent object.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Attachment ID | Id | id | 15 | | |
| Body | Body | base64 | | | |
| Body Length | BodyLength | int | | 8 | 0 |
| Content Type | ContentType | string | 120 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 500 | | |
| File Name | Name | string | 255 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Owner Name | OwnerId | reference | 15 | | |
| Parent | ParentId | reference | 15 | | |
| Private | IsPrivate | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |

AuthConfig

Represents authentication options for a community or custom domain that was created by using My Domain. This object is available in API version 32.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------------|------------------|-----------|--------|-----------|-------|
| Authentication Configuration ID | Id | id | 15 | | |
| Authentication Configuration Type | Type | picklist | 255 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Is Active | IsActive | boolean | | | |
| Label | MasterLabel | string | 80 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Language | Language | picklist | 40 | | |
| Name | DeveloperName | string | 80 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| URL | Url | string | 240 | | |

AuthConfigProviders

Represents an authentication provider that's configured in an organization. This object is a child of the AuthConfig object. This object is available in API version 32.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|------------------|-----------|--------|-----------|-------|
| Auth Config | AuthConfigId | reference | 15 | | |
| Auth Config Provider ID | Id | id | 15 | | |
| Authentication Provider | AuthProviderId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|----------|--------|-----------|-------|
| Last Modified Date | LastModifiedDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |

AuthProvider

Represents an authentication provider in your org.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|-----------------------|-----------|--------|-----------|-------|
| Auth. Provider ID | Id | id | 15 | | |
| Authorize Endpoint URL | AuthorizeUrl | url | 1024 | | |
| Consumer Key | ConsumerKey | string | 256 | | |
| Consumer Secret | ConsumerSecret | string | 100 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom Error URL | ErrorUrl | string | 500 | | |
| Custom Logout URL | LogoutUrl | url | 1500 | | |
| Default Scopes | DefaultScopes | string | 256 | | |
| Execute Registration As | ExecutionUserId | reference | 15 | | |
| Icon URL | IconUrl | url | 1024 | | |
| Name | FriendlyName | string | 32 | | |
| Options | Options | int | | 9 | 0 |
| Provider Type | ProviderType | picklist | 40 | | |
| Registration Handler | RegistrationHandlerId | reference | 15 | | |
| Token Endpoint URL | TokenUrl | url | 1024 | | |
| Token Issuer | IdTokenIssuer | string | 1024 | | |
| URL Suffix | DeveloperName | string | 32 | | |
| User Info Endpoint URL | UserInfoUrl | url | 1024 | | |

AuthSession

The AuthSession object represents an individual user session in your organization. This object is available in versions 29.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|----------------------|-----------|--------|-----------|-------|
| Auth Session | ParentId | reference | 15 | | |
| Auth Session ID | Id | id | 15 | | |
| Created | CreatedDate | datetime | | | |
| Login | LoginType | picklist | 1 | | |
| Login History | LoginHistoryId | reference | 15 | | |
| Logout URL | LogoutUrl | string | 1500 | | |
| Session Security Level | SessionSecurityLevel | picklist | 40 | | |
| Session Type | SessionType | picklist | 40 | | |
| Source IP | SourceIp | string | | | |
| Updated | LastModifiedDate | datetime | | | |
| User | UserId | reference | 15 | | |
| User Type | UserType | picklist | 40 | | |
| Valid For | NumSecondsValid | int | | 9 | 0 |

Bookmark

Represents a link between opportunities that share common information.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Bookmark ID | Id | id | 15 | | |
| Bookmarked From | FromId | reference | 15 | | |
| Bookmarked To | ToId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |

BrandTemplate

Letterhead for HTML EmailTemplate.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Brand Template Name | Name | string | 255 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | string | 1000 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Letterhead ID | Id | id | 15 | | |
| Letterhead Unique Name | DeveloperName | string | 80 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Value | Value | textarea | 32000 | | |

Campaign

Represents and tracks a marketing campaign, such as a direct mail promotion, webinar, or trade show.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|----------------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Actual Cost | ActualCost | currency | | 18 | 0 |
| Budgeted Cost | BudgetedCost | currency | | 18 | 0 |
| Campaign ID | Id | id | 15 | | |
| Campaign Member Type | CampaignMemberRecordTypeId | reference | 15 | | |
| Campaign Name | Name | string | 80 | | |
| Campaign Owner | OwnerId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------------------|---------------------------------|-----------|--------|-----------|-------|
| Contacts in Campaign | NumberOfContacts | int | | 9 | 0 |
| Converted Leads in Campaign | NumberOfConvertedLeads | int | | 9 | 0 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| End Date | EndDate | date | | | |
| Expected Response (%) | ExpectedResponse | percent | | 10 | 2 |
| Expected Revenue | ExpectedRevenue | currency | | 18 | 0 |
| Last Activity | LastActivityDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Leads in Campaign | NumberOfLeads | int | | 9 | 0 |
| Num Sent | NumberSent | double | | 18 | 0 |
| Opportunities in Campaign | NumberOfOpportunities | int | | 9 | 0 |
| Parent Campaign | ParentId | reference | 15 | | |
| Responses in Campaign | NumberOfResponses | int | | 9 | 0 |
| Start Date | StartDate | date | | | |
| Status | Status | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Total Actual Cost in Hierarchy | HierarchyActualCost | currency | | 18 | 0 |
| Total Budgeted Cost in Hierarchy | HierarchyBudgetedCost | currency | | 18 | 0 |
| Total Contacts in Hierarchy | HierarchyNumberOfContacts | int | | 9 | 0 |
| Total Converted Leads in Hierarchy | HierarchyNumberOfConvertedLeads | int | | 9 | 0 |
| Total Expected Revenue in Hierarchy | HierarchyExpectedRevenue | currency | | 18 | 0 |
| Total Leads in Hierarchy | HierarchyNumberOfLeads | int | | 9 | 0 |
| Total Num Sent in Hierarchy | HierarchyNumberSent | double | | 18 | 0 |
| Total Opportunities in Hierarchy | HierarchyNumberOfOpportunities | int | | 9 | 0 |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--|-----------------------------------|----------|--------|-----------|-------|
| Total Value Opportunities in Hierarchy | HierarchyAmountAllOpportunities | currency | | 18 | 0 |
| Total Value Won Opportunities in Hierarchy | HierarchyAmountWonOpportunities | currency | | 18 | 0 |
| Total Won Opportunities in Hierarchy | HierarchyNumberOfWonOpportunities | int | | 9 | 0 |
| Type | Type | picklist | 40 | | |
| Value Opportunities in Campaign | AmountAllOpportunities | currency | | 18 | 0 |
| Value Won Opportunities in Campaign | AmountWonOpportunities | currency | | 18 | 0 |
| Won Opportunities in Campaign | NumberOfWonOpportunities | int | | 9 | 0 |

CampaignMember

Represents the association between a campaign and either a lead or a contact.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Campaign | CampaignId | reference | 15 | | |
| Campaign Member ID | Id | id | 15 | | |
| Contact | ContactId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| First Responded Date | FirstRespondedDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Lead | LeadId | reference | 15 | | |
| Responded | HasResponded | boolean | | | |
| Status | Status | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

CampaignMemberStatus

One or more member status values defined for a campaign.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------------|------------------|-----------|--------|-----------|-------|
| Campaign | CampaignId | reference | 15 | | |
| Campaign Member Status ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Is Default | IsDefault | boolean | | | |
| Label | Label | string | 765 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Responded | HasResponded | boolean | | | |
| Sort Order | SortOrder | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |

Case

Represents a case, which is a customer issue or problem.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------|-----------------|-----------|--------|-----------|-------|
| Account Name | AccountId | reference | 15 | | |
| Asset | AssetId | reference | 15 | | |
| Business Hours | BusinessHoursId | reference | 15 | | |
| Case ID | Id | id | 15 | | |
| Case Number | CaseNumber | string | 30 | | |
| Case Origin | Origin | picklist | 40 | | |
| Case Owner | OwnerId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Case Reason | Reason | picklist | 40 | | |
| Closed | IsClosed | boolean | | | |
| Closed When Created | IsClosedOnCreate | boolean | | | |
| Contact Name | ContactId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Date/Time Closed | ClosedDate | datetime | | | |
| Date/Time Opened | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Escalated | IsEscalated | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Parent Case | ParentId | reference | 15 | | |
| Priority | Priority | picklist | 40 | | |
| Status | Status | picklist | 40 | | |
| Subject | Subject | string | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |
| Web Company | SuppliedCompany | string | 80 | | |
| Web Email | SuppliedEmail | email | 80 | | |
| Web Name | SuppliedName | string | 80 | | |
| Web Phone | SuppliedPhone | string | 40 | | |

CaseContactRole

Represents the role that a given Contact plays on a Case.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Case | CasesId | reference | 15 | | |
| Contact | ContactId | reference | 15 | | |
| Contact Role ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Role | Role | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

CaseMilestone

Represents a milestone (required step in a customer support process) on a Case. This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|-------------------|-----------|--------|-----------|-------|
| Business Hours | BusinessHoursId | reference | 15 | | |
| Case | CaseId | reference | 15 | | |
| Case Milestone ID | Id | id | 15 | | |
| Completed | IsCompleted | boolean | | | |
| Completion Date | CompletionDate | datetime | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Elapsed Time (Days) | ElapsedTimeInDays | double | | 6 | 2 |
| Elapsed Time (Hours) | ElapsedTimeInHrs | double | | 6 | 2 |
| Elapsed Time (Mins) | ElapsedTimeInMins | int | | 9 | 0 |
| Last Modified By | LastModifiedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------|-----------------------|-----------|--------|-----------|-------|
| Last Modified Date | LastModifiedDate | datetime | | | |
| Milestone | MilestoneTypeld | reference | 15 | | |
| Start Date | StartDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Target Date | TargetDate | datetime | | | |
| Target Response (Days) | TargetResponseInDays | double | | 6 | 2 |
| Target Response (Hours) | TargetResponseInHrs | double | | 6 | 2 |
| Target Response (Mins) | TargetResponseInMins | int | | 9 | 0 |
| Time Remaining (Min:Sec) | TimeRemainingInMins | string | 10 | | |
| Time Since Target (Min:Sec) | TimeSinceTargetInMins | string | 10 | | |
| Violation | IsViolated | boolean | | | |

ChatterActivity

ChatterActivity represents the number of posts and comments made by a user and the number of comments and likes on posts and comments received by the same user. This object is available in API version 23.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|----------------------|-----------|--------|-----------|-------|
| Chatter Activity ID | Id | id | 15 | | |
| Comment Count | CommentCount | int | | 9 | 0 |
| Comment Received Count | CommentReceivedCount | int | | 9 | 0 |
| Influence Raw Rank | InfluenceRawRank | int | | 9 | 0 |
| Like Received Count | LikeReceivedCount | int | | 9 | 0 |
| Parent | ParentId | reference | 15 | | |
| Post Count | PostCount | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |

ChatterConversation

Represents a private conversation in Chatter, consisting of messages that conversation members have sent or received. This object is available in API version 23.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|------|--------|-----------|-------|
| Conversation ID | Id | id | 15 | | |

ChatterConversationMember

Represents a member of a private conversation in Chatter. A member has either sent messages to or received messages from other conversation participants. This object is available in API version 23.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|----------------|-----------|--------|-----------|-------|
| Chatter Conversation | ConversationId | reference | 15 | | |
| Conversation Member ID | Id | id | 15 | | |
| Member | MemberId | reference | 15 | | |

ChatterMessage

Represents a message sent as part of a private conversation in Chatter. This object is available in API version 23.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|----------------|-----------|--------|-----------|-------|
| Body | Body | textarea | 10000 | | |
| Chatter Conversation | ConversationId | reference | 15 | | |
| Chatter Message ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Date Message Was Sent | SentDate | datetime | | | |
| Sender | SenderId | reference | 15 | | |

ClientBrowser

Represents a cookie added to the browser upon login, and also includes information about the browser application where the cookie was inserted.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------|----------------|-----------|--------|-----------|-------|
| Client Browser ID | Id | id | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Full User Agent | FullUserAgent | string | 1024 | | |
| Last Update | LastUpdate | datetime | | | |
| Proxy Info | ProxyInfo | string | 1024 | | |
| User | UsersId | reference | 15 | | |

CollaborationGroup

Represents a Chatter group. This object is available in API version 19.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------|------------------------|-----------|--------|-----------|-------|
| Access Type | CollaborationType | picklist | 40 | | |
| Allow Customers | CanHaveGuests | boolean | | | |
| Announcement | AnnouncementId | reference | 15 | | |
| Archive | IsArchived | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | textarea | 1000 | | |
| Disable Automatic Archiving | IsAutoArchiveDisabled | boolean | | | |
| Group Id | Id | id | 15 | | |
| Has Private Fields Access | HasPrivateFieldsAccess | boolean | | | |
| Information | InformationBody | textarea | 1000 | | |
| Information Title | InformationTitle | string | 30 | | |
| Last Feed Modified Date | LastFeedModifiedDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------------|----------------|-----------|--------|-----------|-------|
| Last Viewed Date | LastViewedDate | datetime | | | |
| Member Count | MemberCount | int | | 9 | 0 |
| Name | Name | string | 40 | | |
| Owner | OwnerId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Url for Thumbnail sized Photo | SmallPhotoUrl | url | 1024 | | |
| Url for full-sized Photo | FullPhotoUrl | url | 1024 | | |

CollaborationGroupMember

Represents a member of a Chatter group. This object is available in API version 19.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|-----------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Group | CollaborationGroupId | reference | 15 | | |
| Group Member Id | Id | id | 15 | | |
| Group Member Role | CollaborationRole | picklist | 40 | | |
| Last Feed Access Date | LastFeedAccessDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Member | MemberId | reference | 15 | | |
| Notification Frequency | NotificationFrequency | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

CollaborationGroupMemberRequest

Represents a request to join a private Chatter group. This object is available in API version 21.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|----------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Group | CollaborationGroupId | reference | 15 | | |
| Group Member Request Id | Id | id | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Requester | RequesterId | reference | 15 | | |
| Response Message | ResponseMessage | string | 255 | | |
| Status | Status | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

CollaborationGroupRecord

Represents the records associated with Chatter groups.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|----------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Group | CollaborationGroupId | reference | 15 | | |
| Group Record ID | Id | id | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Record | RecordId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

CollaborationInvitation

Represents an invitation to join Chatter, either directly or through a group. This object is available in API version 21.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------------|----------------------------|-----------|--------|-----------|-------|
| Chatter Invitation Id | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Invitation Status | Status | picklist | 40 | | |
| Invited Email | InvitedUserEmail | string | 240 | | |
| Invited Email (Normalized) | InvitedUserEmailNormalized | email | 80 | | |
| Inviter | InviterId | reference | 15 | | |
| Modified By | LastModifiedById | reference | 15 | | |
| Modified Date | LastModifiedDate | datetime | | | |
| Optional Message | OptionalMessage | string | 255 | | |
| Parent | ParentId | reference | 15 | | |
| Shared Entity | SharedEntityId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

CombinedAttachment

This read-only object contains all notes, attachments, Google Docs, documents uploaded to libraries in Salesforce CRM Content, and files added to Chatter that are associated with a record.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------|-----------|--------|-----------|-------|
| Combined Attachment Id | Id | id | 15 | | |
| Content Modified By | LastModifiedById | reference | 15 | | |
| Content Modified Date | LastModifiedDate | datetime | | | |
| Content Size | ContentSize | int | | 9 | 0 |
| Content URL | ContentUrl | url | 255 | | |
| Created | CreatedDate | datetime | | | |
| Created by | CreatedById | reference | 15 | | |
| Deleted | IsDeleted | boolean | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|------------------------|-----------|--------|-----------|-------|
| External Data Source | ExternalDataSourceName | string | 80 | | |
| File Extension | FileExtension | string | 40 | | |
| File Type | FileType | string | 30 | | |
| Parent | ParentId | reference | 15 | | |
| Title | Title | string | 255 | | |
| Type | RecordType | string | 30 | | |

Contact

Represents a contact, which is an individual associated with an account.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Account Name | AccountId | reference | 15 | | |
| Assistant | AssistantName | string | 40 | | |
| Asst. Phone | AssistantPhone | phone | 40 | | |
| Birthdate | Birthdate | date | | | |
| Contact | MasterRecordId | reference | 15 | | |
| Contact ID | Id | id | 15 | | |
| Contact Owner | OwnerId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Data.com Key | Jigsaw | string | 20 | | |
| Deleted | IsDeleted | boolean | | | |
| Department | Department | string | 80 | | |
| Description | Description | textarea | 32000 | | |
| Do Not Call | DoNotCall | boolean | | | |
| Email | Email | email | 80 | | |
| Email Bounced Date | EmailBouncedDate | datetime | | | |
| Email Bounced Reason | EmailBouncedReason | string | 255 | | |
| Email Opt Out | HasOptedOutOfEmail | boolean | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Fax | Fax | phone | 40 | | |
| Fax Opt Out | HasOptedOutOffax | boolean | | | |
| Home Phone | HomePhone | phone | 40 | | |
| Is Email Bounced | IsEmailBounced | boolean | | | |
| Jigsaw Contact Id | JigsawContactId | string | 20 | | |
| Last Activity | LastActivityDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Lead Source | LeadSource | picklist | 40 | | |
| Mailing Address | MailingStreet | textarea | 255 | | |
| Mailing Address | MailingCity | string | 40 | | |
| Mailing Address | MailingState | string | 80 | | |
| Mailing Address | MailingPostalCode | string | 20 | | |
| Mailing Address | MailingCountry | string | 80 | | |
| Mobile | MobilePhone | phone | 40 | | |
| Name | Salutation | picklist | 40 | | |
| Name | FirstName | string | 40 | | |
| Name | LastName | string | 80 | | |
| Other Address | OtherStreet | textarea | 255 | | |
| Other Address | OtherCity | string | 40 | | |
| Other Address | OtherState | string | 80 | | |
| Other Address | OtherPostalCode | string | 20 | | |
| Other Address | OtherCountry | string | 80 | | |
| Other Phone | OtherPhone | phone | 40 | | |
| Phone | Phone | phone | 40 | | |
| Photo URL | PhotoUrl | url | 255 | | |
| Reports To | ReportsToId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|--------|--------|-----------|-------|
| Title | Title | string | 128 | | |

ContentDistribution

Represents information about sharing a document externally. This object is available in API version 32.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|-----------------------|-----------|--------|-----------|-------|
| Content Delivery ID | Id | id | 15 | | |
| Content Delivery Name | Name | string | 100 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Document | ContentDocumentId | reference | 15 | | |
| Expiration Date | ExpiryDate | datetime | | | |
| External Link | DistributionPublicUrl | string | 256 | | |
| First Viewed | FirstViewDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Viewed | LastViewDate | datetime | | | |
| Owner Name | OwnerId | reference | 15 | | |
| Password | Password | string | 36 | | |
| Preferences | Preferences | int | | 9 | 0 |
| Related To | RelatedRecordId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Version | ContentVersionId | reference | 15 | | |
| View Count | ViewCount | int | | 9 | 0 |

ContentDistributionView

Represents information about views of a shared document. This read-only object is available in API version 32.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|----------------|-----------|--------|-----------|-------|
| Content Delivery | DistributionId | reference | 15 | | |
| Content Delivery View | ParentViewId | reference | 15 | | |
| Content Delivery View ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Deleted | IsDeleted | boolean | | | |
| File Downloaded | IsDownload | boolean | | | |
| Internal View | IsInternal | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| View Date | CreatedDate | datetime | | | |

ContentDocument

Represents a document that has been uploaded to a library in Salesforce CRM Content or Salesforce Files. This object is available in versions 17.0 and later for Salesforce CRM Content. This object is available in API version 21.0 and later for Salesforce Files.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|---------------------|-----------|--------|-----------|-------|
| Archived By | ArchivedById | reference | 15 | | |
| Archived Date | ArchivedDate | date | | | |
| Content Modified Date | ContentModifiedDate | datetime | | | |
| ContentDocument ID | Id | id | 15 | | |
| Created | CreatedDate | datetime | | | |
| Created By | CreatedById | reference | 15 | | |
| Description | Description | textarea | 1000 | | |
| File Extension | FileExtension | string | 40 | | |
| File Type | FileType | string | 20 | | |
| Is Archived | IsArchived | boolean | | | |
| Is Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|--------------------------|-----------|--------|-----------|-------|
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Latest Published Version | LatestPublishedVersionId | reference | 15 | | |
| Owner | OwnerId | reference | 15 | | |
| Publish Status | PublishStatus | picklist | 40 | | |
| Size | ContentSize | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |
| Title | Title | string | 255 | | |

ContentDocumentLink

Represents the link between a Salesforce CRM Content document or Salesforce file and where it's shared. A file can be shared with other users, groups, records, and Salesforce CRM Content libraries. This object is available in versions 21.0 and later for Salesforce CRM Content documents and Salesforce Files.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|-------------------|-----------|--------|-----------|-------|
| ContentDocumentLink ID | Id | id | 15 | | |
| Document | ContentDocumentId | reference | 15 | | |
| Is Deleted | IsDeleted | boolean | | | |
| Linked Entity | LinkedEntityId | reference | 15 | | |
| Share Type | ShareType | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Visibility | Visibility | picklist | 40 | | |

ContentWorkspace

Represents a content library.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------------|------------------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Default Content Type | DefaultRecordTypeId | reference | 15 | | |
| Description | Description | textarea | 500 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Library ID | Id | id | 15 | | |
| Name | Name | string | 255 | | |
| Restrict Content Types | IsRestrictContentTypes | boolean | | | |
| Restrict Linked Content Types | IsRestrictLinkedContentTypes | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Tag Model | TagModel | picklist | 40 | | |

ContentWorkspaceDoc

Represents a link between a document and a public library in Salesforce CRM Content.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|--------------------|-----------|--------|-----------|-------|
| Created Date | CreatedDate | datetime | | | |
| Document | ContentDocumentId | reference | 15 | | |
| Is Deleted | IsDeleted | boolean | | | |
| Is Owning Library | IsOwner | boolean | | | |
| Library | ContentWorkspaceId | reference | 15 | | |
| Library Document ID | Id | id | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

ContentVersion

Represents a specific version of a document in Salesforce CRM Content or Salesforce Files. This object is available in versions 17.0 and later for Salesforce CRM Content documents. This object is available in versions 20.0 and later for Salesforce Files.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|------------------------|-----------|--------|-----------|-------|
| Checksum | Checksum | string | 50 | | |
| Content Location | ContentLocation | picklist | 40 | | |
| Content Modified By | ContentModifiedById | reference | 15 | | |
| Content Modified Date | ContentModifiedDate | datetime | | | |
| Content Origin | Origin | picklist | 40 | | |
| Content URL | ContentUrl | url | 1333 | | |
| ContentVersion ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | textarea | 1000 | | |
| Document | ContentDocumentId | reference | 15 | | |
| External Data Source | ExternalDataSourceId | reference | 15 | | |
| External Document Info1 | ExternalDocumentInfo1 | string | 1000 | | |
| External Document Info2 | ExternalDocumentInfo2 | string | 1000 | | |
| Featured Content Boost | FeaturedContentBoost | int | | 9 | 0 |
| Featured Content Date | FeaturedContentDate | date | | | |
| File Extension | FileExtension | string | 40 | | |
| File Type | FileType | string | 20 | | |
| First Publish Location | FirstPublishLocationId | reference | 15 | | |
| Is Deleted | IsDeleted | boolean | | | |
| Is Latest | IsLatest | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Major Version | IsMajorVersion | boolean | | | |
| Negative Rating Count | NegativeRatingCount | int | | 9 | 0 |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|---------------------|-----------|--------|-----------|-------|
| Owner | OwnerId | reference | 15 | | |
| Path On Client | PathOnClient | string | 500 | | |
| Positive Rating Count | PositiveRatingCount | int | | 9 | 0 |
| Publish Status | PublishStatus | picklist | 40 | | |
| Rating Count | RatingCount | int | | 9 | 0 |
| Reason For Change | ReasonForChange | string | 1000 | | |
| Size | ContentSize | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |
| Tags | TagCsv | textarea | 2000 | | |
| Title | Title | string | 255 | | |
| Version Data | VersionData | base64 | | | |
| Version Number | VersionNumber | string | 20 | | |

Contract

Represents a contract (a business agreement) associated with an Account.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|-------------------|-----------|--------|-----------|-------|
| Account Name | AccountId | reference | 15 | | |
| Activated By | ActivatedById | reference | 15 | | |
| Activated Date | ActivatedDate | datetime | | | |
| Billing Address | BillingStreet | textarea | 255 | | |
| Billing Address | BillingCity | string | 40 | | |
| Billing Address | BillingState | string | 80 | | |
| Billing Address | BillingPostalCode | string | 20 | | |
| Billing Address | BillingCountry | string | 80 | | |
| Company Signed By | CompanySignedId | reference | 15 | | |
| Company Signed Date | CompanySignedDate | date | | | |
| Contract End Date | EndDate | date | | | |
| Contract ID | Id | id | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|-----------------------|-----------|--------|-----------|-------|
| Contract Name | Name | string | 80 | | |
| Contract Number | ContractNumber | string | 30 | | |
| Contract Owner | OwnerId | reference | 15 | | |
| Contract Start Date | StartDate | date | | | |
| Contract Term (months) | ContractTerm | int | | 4 | 0 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Customer Signed By | CustomerSignedId | reference | 15 | | |
| Customer Signed Date | CustomerSignedDate | date | | | |
| Customer Signed Title | CustomerSignedTitle | string | 40 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Last Activity | LastActivityDate | date | | | |
| Last Approved Date | LastApprovedDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Owner Expiration Notice | OwnerExpirationNotice | picklist | 40 | | |
| Shipping Address | ShippingStreet | textarea | 255 | | |
| Shipping Address | ShippingCity | string | 40 | | |
| Shipping Address | ShippingState | string | 80 | | |
| Shipping Address | ShippingPostalCode | string | 20 | | |
| Shipping Address | ShippingCountry | string | 80 | | |
| Special Terms | SpecialTerms | textarea | 4000 | | |
| Status | Status | picklist | 40 | | |
| Status Category | StatusCode | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

ContractContactRole

Represents the role that a given Contact plays on a Contract.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Contact | ContactId | reference | 15 | | |
| Contact Role ID | Id | id | 15 | | |
| Contract | ContractId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Primary | IsPrimary | boolean | | | |
| Role | Role | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

ContractLineItem

Represents a Product2 in a ServiceContract (customer support agreement). This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|-----------------|-----------|--------|-----------|-------|
| Asset Name | AssetId | reference | 15 | | |
| Contract Line Item ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency | CurrencyIsoCode | picklist | 3 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Discount | Discount | percent | | 5 | 2 |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| End Date | EndDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Line Item Number | LineItemNumber | string | 255 | | |
| List Price | ListPrice | currency | | 18 | 2 |
| Price Book Entry | PricebookEntryId | reference | 15 | | |
| Quantity | Quantity | double | | 12 | 2 |
| Sales Price | UnitPrice | currency | | 18 | 2 |
| Service Contract | ServiceContractId | reference | 15 | | |
| Start Date | StartDate | date | | | |
| Status | Status | picklist | 255 | | |
| Subtotal | Subtotal | currency | | 18 | 2 |
| System Modstamp | SystemModstamp | datetime | | | |
| Total Price | TotalPrice | currency | | 18 | 2 |

CronJobDetail

Contains details about the associated scheduled job, such as the job's name and type.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|----------|--------|-----------|-------|
| Job ID | Id | id | 15 | | |
| Job Name | Name | string | 255 | | |
| Type | JobType | picklist | 40 | | |

CurrencyType

Represents the currencies used by an organization for which the multicurrency feature is enabled.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Conversion Rate | ConversionRate | double | | 18 | 6 |
| Corporate Currency | IsCorporate | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency ISO Code | IsoCode | picklist | 40 | | |
| Currency Type ID | Id | id | 15 | | |
| Decimal Places | DecimalPlaces | int | | 9 | 0 |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |

CustomPermission

Represents a permission created to control access to a custom process or app, such as sending email.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom Permission ID | Id | id | 15 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 255 | | |
| Label | MasterLabel | string | 80 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Language | Language | picklist | 40 | | |
| Name | DeveloperName | string | 80 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|----------|--------|-----------|-------|
| System Modstamp | SystemModstamp | datetime | | | |

CustomPermissionDependency

Represents the dependency between two custom permissions when one custom permission requires that you enable another custom permission.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------------------|----------------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom Permission | CustomPermissionId | reference | 15 | | |
| Custom Permission Dependency ID | Id | id | 15 | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Required Custom Permission | RequiredCustomPermissionId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

Dashboard

Represents a dashboard, which shows data from custom reports as visual components. Access is read-only. This object is available in API version 20.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------------|---------------------|-----------|--------|-----------|-------|
| Background Fade Direction | BackgroundDirection | picklist | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Dashboard ID | Id | id | 15 | | |
| Dashboard Running User | Type | picklist | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------------|------------------------------|-----------|--------|-----------|-------|
| Dashboard Unique Name | DeveloperName | string | 80 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | string | 255 | | |
| Ending Color | BackgroundEnd | int | | 9 | 0 |
| Folder | FolderId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Last refreshed for this user | DashboardResultRefreshedDate | string | 256 | | |
| Left Size | LeftSize | picklist | 40 | | |
| Middle Size | MiddleSize | picklist | 40 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Right Size | RightSize | picklist | 40 | | |
| Running User | RunningUserId | reference | 15 | | |
| Running as | DashboardResultRunningUser | string | 256 | | |
| Starting Color | BackgroundStart | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |
| Text Color | TextColor | int | | 9 | 0 |
| Title | Title | string | 80 | | |
| Title Color | TitleColor | int | | 9 | 0 |
| Title Size | TitleSize | int | | 9 | 0 |

DashboardComponent

Represents a dashboard component, which can be a chart, metric, table, or gauge on a dashboard. Access is read-only. This object is available in API version 21.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|-----------|--------|-----------|-------|
| Dashboard | DashboardId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|----------------|--------|--------|-----------|-------|
| Dashboard Component ID | Id | id | 15 | | |
| Dashboard Component Name | Name | string | 80 | | |

DatedConversionRate

Represents the dated exchange rates used by an organization for which the multicurrency and the effective dated currency features are enabled.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency Code | IsoCode | picklist | 40 | | |
| Date | StartDate | date | | | |
| DatedConversion Rate ID | Id | id | 15 | | |
| Exchange Rate | ConversionRate | double | | 18 | 6 |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Next Start Date | NextStartDate | date | | | |
| System Modstamp | SystemModstamp | datetime | | | |

Division

A logical segment of your organization's data. For example, if your company is organized into different business units, you could create a division for each business unit, such as "North America," "Healthcare," or "Consulting." Available only if the organization has the Division permission enabled.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------|----------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Division ID | Id | id | 15 | | |
| Global Division | IsGlobalDivision | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | Name | string | 80 | | |
| Sort Order | SortOrder | int | | 8 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |

Document

Represents a file that a user has uploaded. Unlike Attachment records, documents are not attached to a parent object.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------|-------------------|-----------|--------|-----------|-------|
| Author | AuthorId | reference | 15 | | |
| Body | Body | base64 | | | |
| Body Length | BodyLength | int | | 8 | 0 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 255 | | |
| Document Content Searchable | IsBodySearchable | boolean | | | |
| Document ID | Id | id | 15 | | |
| Document Name | Name | string | 255 | | |
| Document Unique Name | DeveloperName | string | 80 | | |
| Externally Available | IsPublic | boolean | | | |
| File Extension | Type | string | 40 | | |
| Folder | FolderId | reference | 15 | | |
| Internal Use Only | IsInternalUseOnly | boolean | | | |
| Keywords | Keywords | string | 255 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|----------|--------|-----------|-------|
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| MIME Type | ContentType | string | 120 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Url | Url | string | 255 | | |

Domain

Read-only object that represents a custom Web address assigned to a site in your organization. This object is available in API version 26.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Domain ID | Id | id | 15 | | |
| Domain Name | Domain | string | 765 | | |
| Domain Type | DomainType | picklist | 40 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Options | Options | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |

DomainSite

Read-only junction object that joins together the Site and Domain objects.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom URL ID | Id | id | 15 | | |
| Domain | DomainId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Path | PathPrefix | string | 255 | | |
| Site | SiteId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

EmailMessage

Represents an email in Salesforce.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|-----------|--------|-----------|-------|
| Activity | ActivityId | reference | 15 | | |
| BCC Address | BccAddress | string | 4000 | | |
| CC Address | CcAddress | string | 4000 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Division | Division | picklist | 15 | | |
| EmailMessage ID | Id | id | 15 | | |
| From Address | FromAddress | email | 1000 | | |
| From Name | FromName | string | 1000 | | |
| HTML Body | HtmlBody | textarea | 32000 | | |
| Has Attachment | HasAttachment | boolean | | | |
| Headers | Headers | textarea | 32000 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|-----------------------|-----------|--------|-----------|-------|
| Is Incoming | Incoming | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Message Date | MessageDate | datetime | | | |
| Parent Case | ParentId | reference | 15 | | |
| Reply-to Email Message | ReplyToEmailMessageId | reference | 15 | | |
| Status | Status | picklist | 40 | | |
| Subject | Subject | string | 3000 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Text Body | TextBody | textarea | 32000 | | |
| To Address | ToAddress | string | 4000 | | |

EmailTemplate

Represents a template for mass email, or email sent when the activity history related list of a record is modified.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|------------------|-----------|--------|-----------|-------|
| API Version | ApiVersion | double | | 18 | 1 |
| Author | OwnerId | reference | 15 | | |
| Available For Use | IsActive | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | string | 4000 | | |
| Email Body | Body | textarea | 384000 | | |
| Email Template ID | Id | id | 15 | | |
| Email Template Name | Name | string | 80 | | |
| Encoding | Encoding | picklist | 40 | | |
| Folder | FolderId | reference | 15 | | |
| HTML Value | HtmlValue | textarea | 384000 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|------------------|-----------|---------|-----------|-------|
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Used Date | LastUsedDate | datetime | | | |
| Letterhead | BrandTemplateId | reference | 15 | | |
| Markup | Markup | textarea | 1048576 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Style | TemplateStyle | picklist | 40 | | |
| Subject | Subject | string | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Template Type | TemplateType | picklist | 40 | | |
| Template Unique Name | DeveloperName | string | 80 | | |
| Times Used | TimesUsed | int | | 9 | 0 |

Entitlement

Represents the customer support an Account or Contact is eligible to receive. This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|---------------------|-----------|--------|-----------|-------|
| Account Name | AccountId | reference | 15 | | |
| Asset Name | AssetId | reference | 15 | | |
| Business Hours | BusinessHoursId | reference | 15 | | |
| Cases Per Entitlement | CasesPerEntitlement | int | | 9 | 0 |
| Contract Line Item | ContractLineItemId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency | CurrencyIsoCode | picklist | 3 | | |
| Deleted | IsDeleted | boolean | | | |
| Division | Division | picklist | 15 | | |
| End Date | EndDate | date | | | |
| Entitlement ID | Id | id | 15 | | |
| Entitlement Name | Name | string | 255 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Entitlement Process | SlaProcessId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Per Incident | IsPerIncident | boolean | | | |
| Remaining Cases | RemainingCases | int | | 9 | 0 |
| Service Contract | ServiceContractId | reference | 15 | | |
| Start Date | StartDate | date | | | |
| Status | Status | picklist | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |

EntitlementContact

Represents a Contact eligible to receive customer support via an Entitlement. This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------|-----------|--------|-----------|-------|
| Contact Name | ContactId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency | CurrencyIsoCode | picklist | 3 | | |
| Deleted | IsDeleted | boolean | | | |
| Division | Division | picklist | 15 | | |
| Entitlement Contact | Name | string | 255 | | |
| Entitlement Contact ID | Id | id | 15 | | |
| Entitlement Name | EntitlementId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |

EntitlementTemplate

Represents predefined terms of customer support for a product (Product2). This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------------|---------------------|-----------|--------|-----------|-------|
| Business Hours | BusinessHoursId | reference | 15 | | |
| Cases Per Entitlement | CasesPerEntitlement | int | | 9 | 0 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Entitlement Process | SlaProcessId | reference | 15 | | |
| Entitlement Template ID | Id | id | 15 | | |
| Entitlement Template Name | Name | string | 120 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Per Incident | IsPerIncident | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Term (Days) | Term | int | | 9 | 0 |
| Type | Type | picklist | 40 | | |

EntitySubscription

Represents a subscription for a user following a record or another user. This object is available in API version 34.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|----------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Entity Subscription ID | Id | id | 15 | | |
| Parent | ParentId | reference | 15 | | |
| Subscriber | SubscriberId | reference | 15 | | |

Event

Represents an event in the calendar. In the user interface, event and task records are collectively referred to as activities.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------------|-------------------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Activity ID | Id | id | 15 | | |
| All-Day Event | IsAllDayEvent | boolean | | | |
| Archived | IsArchived | boolean | | | |
| Assigned To | OwnerId | reference | 15 | | |
| Create Recurring Series of Events | IsRecurrence | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Date | ActivityDate | date | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Duration | DurationInMinutes | int | | 8 | 0 |
| End | EndDateTime | datetime | | | |
| End Date | RecurrenceEndDateOnly | date | | | |
| Group Event Type | GroupEventType | picklist | 40 | | |
| Is Child | IsChild | boolean | | | |
| Is Group Event | IsGroupEvent | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Location | Location | string | 255 | | |
| Name | WhoId | reference | 15 | | |
| Private | IsPrivate | boolean | | | |
| Recurrence Activity | RecurrenceActivityId | reference | 15 | | |
| Recurrence Day of Month | RecurrenceDayOfMonth | int | | 9 | 0 |
| Recurrence Day of Week Mask | RecurrenceDayOfWeekMask | int | | 9 | 0 |
| Recurrence Instance | RecurrenceInstance | picklist | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|--------------------------|-----------|--------|-----------|-------|
| Recurrence Interval | RecurrenceInterval | int | | 9 | 0 |
| Recurrence Month of Year | RecurrenceMonthOfYear | picklist | 40 | | |
| Recurrence Time Zone | RecurrenceTimeZoneSidKey | picklist | 40 | | |
| Recurrence Type | RecurrenceType | picklist | 40 | | |
| Related To | WhatId | reference | 15 | | |
| Reminder Date/Time | ReminderDateTime | datetime | | | |
| Reminder Set | IsReminderSet | boolean | | | |
| Show Time As | ShowAs | picklist | 40 | | |
| Start | StartDateTime | datetime | | | |
| Start Date | RecurrenceStartDateTime | datetime | | | |
| Subject | Subject | combobox | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Time | ActivityDateTime | datetime | | | |
| Type | Type | picklist | 40 | | |

EventLogFile

Represents event log files for event monitoring. The event monitoring product gathers information about your Salesforce org's operational events, which you can use to analyze usage trends and user behavior. This object is available in API version 32.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| API Version | ApiVersion | double | | 18 | 1 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Event Log File ID | Id | id | 15 | | |
| Event Type | EventType | picklist | 255 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Log Date | LogDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|--------------------|----------|--------|-----------|-------|
| Log File | LogFile | base64 | | | |
| Log File Content Type | LogFileContentType | string | 255 | | |
| Log File Field Names | LogFileFieldNames | string | 1333 | | |
| Log File Field Types | LogFileFieldTypes | string | 1333 | | |
| Log File Length | LogFileLength | double | | 18 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |

ExternalDataSource

Represents an external data source, which defines connection details for integration with data and content that are stored outside the Salesforce org.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------|---------------------|-----------|--------|-----------|-------|
| API Key | ApiKey | string | 128 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom Configuration | CustomConfiguration | textarea | 4000 | | |
| Default External Repository | Repository | string | 255 | | |
| Deleted | IsDeleted | boolean | | | |
| External Data Source | MasterLabel | string | 80 | | |
| External Data Source ID | Id | id | 15 | | |
| Identity Type | PrincipalType | picklist | 255 | | |
| Large Icon | LargeIconId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Language | Language | picklist | 40 | | |
| Name | DeveloperName | string | 80 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Small Icon | SmallIconId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|----------|--------|-----------|-------|
| Type | Type | picklist | 255 | | |
| URL | Endpoint | textarea | 1000 | | |

ExternalDataUserAuth

Stores authentication settings for a Salesforce user to access an external system. The external system must be defined in an external data source or a named credential that's configured to use per-user authentication.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------------|----------------------|-----------------|--------|-----------|-------|
| Authentication Protocol | Protocol | picklist | 255 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| External Data Source | ExternalDataSourceId | reference | 15 | | |
| External Data User Authentication ID | Id | id | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Password | Password | encryptedstring | 175 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| User | UserId | reference | 15 | | |
| Username | Username | string | 255 | | |

FeedComment

Represents a comment added to a feed by a user.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------|----------------|----------|--------|-----------|-------|
| Comment Body | CommentBody | textarea | 5000 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|-----------------|-----------|--------|-----------|-------|
| Comment Type | CommentType | picklist | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Feed Comment ID | Id | id | 15 | | |
| Feed Item | FeedItemId | reference | 15 | | |
| Inserted By | InsertedById | reference | 15 | | |
| Parent | ParentId | reference | 15 | | |
| Related Record | RelatedRecordId | reference | 15 | | |

FeedItem

FeedItem represents an entry in the feed, such as changes in a record feed, including text posts, link posts, and content posts.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|--------------------|-----------|--------|-----------|-------|
| Best Comment | BestCommentId | reference | 15 | | |
| Body | Body | textarea | 5000 | | |
| Comment Count | CommentCount | int | | 9 | 0 |
| Content Data | ContentData | base64 | | | |
| Content Description | ContentDescription | textarea | 1000 | | |
| Content File Name | ContentFileName | string | 255 | | |
| Content File Type | ContentType | string | 120 | | |
| Content Size | ContentSize | int | | 9 | 0 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Feed Item ID | Id | id | 15 | | |
| Feed Item Type | Type | picklist | 40 | | |
| Has Content | HasContent | boolean | | | |
| Has Link | HasLink | boolean | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Inserted By | InsertedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Like Count | LikeCount | int | | 9 | 0 |
| Link Url | LinkUrl | url | 1000 | | |
| Parent | ParentId | reference | 15 | | |
| Related Record | RelatedRecordId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Title | Title | string | 255 | | |

FeedTrackedChange

Represents an individual field change or set of field changes. A FeedTrackedChange is a child object of a record feed, such as AccountFeed. This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|----------------|-----------|--------|-----------|-------|
| Feed Item | FeedItemId | reference | 15 | | |
| Feed Tracked Change ID | Id | id | 15 | | |
| Field | FieldName | string | 120 | | |
| New Value | NewValue | anyType | 255 | 18 | 0 |
| Old Value | OldValue | anyType | 255 | 18 | 0 |

FieldPermissions

Represents the enabled field permissions for the parent PermissionSet. This object is available in API version 24.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|-----------------|----------|--------|-----------|-------|
| | PermissionsRead | boolean | | | |
| Editable | PermissionsEdit | boolean | | | |
| Entity | SubjectType | picklist | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------------------|----------------|-----------|--------|-----------|-------|
| Field Permissions ID | Id | id | 15 | | |
| Parent Entity | ParentId | reference | 15 | | |
| Standard Field Name or Custom Field | Field | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

Folder

Represents a repository for a Document, EmailTemplate, Report, or Dashboard. Only one type of item can be contained in a folder.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Access Type | AccessType | picklist | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Folder ID | Id | id | 15 | | |
| Folder Unique Name | DeveloperName | string | 80 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | Name | string | 40 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Read Only | IsReadOnly | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |

GoogleDoc

Represents a link to a Google Document. This object is available in API version 14.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Division | Division | picklist | 15 | | |
| Google Doc Id | Id | id | 15 | | |
| Google Doc Name | Name | string | 80 | | |
| Google Doc Owner | OwnerId | reference | 15 | | |
| Google Doc URL | Url | string | 255 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Parent | ParentId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

Group

A set of User records.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|-------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Developer Name | DeveloperName | string | 80 | | |
| Email | Email | email | 255 | | |
| Group ID | Id | id | 15 | | |
| Include Bosses | DoesIncludeBosses | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | Name | string | 40 | | |
| Owner Name | OwnerId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|------------------------|-----------|--------|-----------|-------|
| Related | RelatedId | reference | 15 | | |
| Send Email to Members | DoesSendEmailToMembers | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |

Idea

Represents an idea on which users are allowed to comment and vote, for example, a suggestion for an enhancement to an existing product or process. This object is available in API version 12 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|--------------------|---------------|--------|-----------|-------|
| Categories | Categories | multipicklist | 765 | 7 | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Idea Body | Body | textarea | 32000 | | |
| Idea ID | Id | id | 15 | | |
| Is Merged | IsMerged | boolean | | | |
| IsHtml | IsHtml | boolean | | | |
| Last Idea Comment | LastCommentId | reference | 15 | | |
| Last Idea Comment Date | LastCommentDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Name of Creator | CreatorName | string | 121 | | |
| Number of Comments | NumComments | int | | 9 | 0 |
| Parent Idea | ParentIdeaId | reference | 15 | | |
| Record Type | RecordTypeId | reference | | | |
| Status | Status | picklist | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------------------|----------------------|-----------|--------|-----------|-------|
| System Modstamp | SystemModstamp | datetime | | | |
| Title | Title | string | 255 | | |
| Url of Creator's Profile Photo | CreatorFullPhotoUrl | string | 255 | | |
| Url of Creator's Thumbnail Photo | CreatorSmallPhotoUrl | string | 255 | | |
| Vote Score | VoteScore | double | | 18 | 4 |
| Vote Total | VoteTotal | double | | 18 | 0 |
| Zone | CommunityId | reference | 15 | | |

Lead

Represents a prospect or potential Opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|------------------------|-----------|--------|-----------|-------|
| Address | Street | textarea | 255 | | |
| Address | City | string | 40 | | |
| Address | State | string | 80 | | |
| Address | PostalCode | string | 20 | | |
| Address | Country | string | 80 | | |
| Annual Revenue | AnnualRevenue | currency | | 18 | 0 |
| Company | Company | string | 255 | | |
| Converted | IsConverted | boolean | | | |
| Converted Account | ConvertedAccountId | reference | 15 | | |
| Converted Contact | ConvertedContactId | reference | 15 | | |
| Converted Date | ConvertedDate | date | | | |
| Converted Opportunity | ConvertedOpportunityId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Data.com Key | Jigsaw | string | 20 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Do Not Call | DoNotCall | boolean | | | |
| Email | Email | email | 80 | | |
| Email Bounced Date | EmailBouncedDate | datetime | | | |
| Email Bounced Reason | EmailBouncedReason | string | 255 | | |
| Email Opt Out | HasOptedOutOfEmail | boolean | | | |
| Fax | Fax | phone | 40 | | |
| Fax Opt Out | HasOptedOutOfFax | boolean | | | |
| Industry | Industry | picklist | 40 | | |
| Jigsaw Contact Id | JigsawContactId | string | 20 | | |
| Last Activity | LastActivityDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Transfer Date | LastTransferDate | date | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Lead | MasterRecordId | reference | 15 | | |
| Lead ID | Id | id | 15 | | |
| Lead Owner | OwnerId | reference | 15 | | |
| Lead Source | LeadSource | picklist | 40 | | |
| Lead Status | Status | picklist | 40 | | |
| Mobile | MobilePhone | phone | 40 | | |
| Name | Salutation | picklist | 40 | | |
| Name | FirstName | string | 40 | | |
| Name | LastName | string | 80 | | |
| No. of Employees | NumberOfEmployees | int | | 8 | 0 |
| Phone | Phone | phone | 40 | | |
| Photo URL | PhotoUrl | url | 255 | | |
| Rating | Rating | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Title | Title | string | 128 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|-----------------|---------|--------|-----------|-------|
| Unread By Owner | IsUnreadByOwner | boolean | | | |
| Website | Website | url | 255 | | |

ListView

Represents a list view. A list view specifies a set of records for an object, based on specific criteria. This object is available in API version 32.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|--------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom Object Definition | SubjectType | picklist | 40 | | |
| Is SOQL Compatible | IsSoqlCompatible | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| List View ID | Id | id | 15 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| View Name | Name | string | 40 | | |
| View Unique Name | DeveloperName | string | 80 | | |

ListViewChart

Represents a graphical chart that's displayed on Salesforce for Android, iOS, and mobile web list views. The chart aggregates data that is filtered based on the list view that's currently displayed. This object is available in API version 33.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|------------------|-----------|--------|-----------|-------|
| API Name | DeveloperName | string | 80 | | |
| Aggregate Field | AggregateField | picklist | 255 | | |
| Aggregate Type | AggregateType | picklist | 255 | | |
| Chart Type | ChartType | picklist | 255 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom Object Definition | SubjectType | picklist | 40 | | |
| Deleted | IsDeleted | boolean | | | |
| Grouping Field | GroupingField | picklist | 255 | | |
| Label | MasterLabel | string | 80 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| List View Chart ID | Id | id | 15 | | |
| Master Language | Language | picklist | 40 | | |
| Owner | OwnerId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

LoginHistory

Represents the login history for all successful and failed login attempts for organizations and enabled portals. This object is available in API version 21.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------|----------------|--------|--------|-----------|-------|
| API Type | ApiType | string | 64 | | |
| API Version | ApiVersion | string | 32 | | |
| Application | Application | string | 64 | | |
| Browser | Browser | string | 64 | | |
| Client Version | ClientVersion | string | 64 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------|----------------|-----------|--------|-----------|-------|
| Login History Id | Id | id | 15 | | |
| Login Time | LoginTime | datetime | | | |
| Login Type | LoginType | picklist | 1 | | |
| Login URL | LoginUrl | string | 255 | | |
| Platform | Platform | string | 64 | | |
| Source IP | SourceIp | string | | | |
| Status | Status | string | 128 | | |
| UserId | UserId | reference | 15 | | |

LoginIp

Represents a validated IP address. This object is available in version 28.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|-------------------|-----------|--------|-----------|-------|
| Challenge Method | ChallengeMethod | picklist | 40 | | |
| Challenge SentDate | ChallengeSentDate | datetime | | | |
| Created Date | CreatedDate | datetime | | | |
| IsAuthenticated | IsAuthenticated | boolean | | | |
| Login IP ID | Id | id | 15 | | |
| Source IP | SourceIp | string | | | |
| User | UserId | reference | 15 | | |

LookedUpFromActivity

This read-only object is displayed as a related list on an activity record (an event or a task); the list contains records that have custom lookup relationships from the activity to another object. This object is not queryable.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------------|-----------|--------|-----------|-------|
| Activity ID | Id | id | 15 | | |
| All-Day Event | IsAllDayEvent | boolean | | | |
| Assigned To | OwnerId | reference | 15 | | |
| Call Duration | CallDurationInSeconds | int | | 8 | 0 |
| Call Object Identifier | CallObject | string | 255 | | |
| Call Result | CallDisposition | string | 255 | | |
| Call Type | CallType | picklist | 40 | | |
| Closed | IsClosed | boolean | | | |
| Comments | Description | textarea | 32000 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Date | ActivityDate | date | | | |
| Deleted | IsDeleted | boolean | | | |
| Duration | DurationInMinutes | int | | 9 | 0 |
| End | EndDateTime | datetime | | | |
| High Priority | IsHighPriority | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Location | Location | string | 80 | | |
| Name | WhoId | reference | 15 | | |
| Priority | Priority | picklist | 40 | | |
| Public | IsVisibleInSelfService | boolean | | | |
| Related To | WhatId | reference | 15 | | |
| Reminder Date/Time | ReminderDateTime | datetime | | | |
| Reminder Set | IsReminderSet | boolean | | | |
| Start | StartDateTime | datetime | | | |
| Status | Status | picklist | 40 | | |
| Subject | Subject | combobox | 80 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Task | IsTask | boolean | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|----------|--------|-----------|-------|
| Type | ActivityType | picklist | 40 | | |

MailmergeTemplate

Represents a mail merge template (a Microsoft Word document) used for performing mail merges for your organization.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------|-----------|--------|-----------|-------|
| Body | Body | base64 | | | |
| Body Length | BodyLength | int | | 8 | 0 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | string | 255 | | |
| Document Type | Category | picklist | 40 | | |
| File | Filename | string | 255 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Used Date | LastUsedDate | datetime | | | |
| Mail Merge Template ID | Id | id | 15 | | |
| Name | Name | string | 80 | | |
| System Modstamp | SystemModstamp | datetime | | | |

MilestoneType

Represents a milestone (required step in a customer support process). This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------|----------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Description | Description | textarea | 255 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Milestone Type ID | Id | id | 15 | | |
| Name | Name | string | 80 | | |
| Recurrence Type | RecurrenceType | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

NamedCredential

Represents a named credential, which specifies the URL of a callout endpoint and its required authentication parameters in one definition. A named credential can be specified as an endpoint to simplify the setup of authenticated callouts.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Identity Type | PrincipalType | picklist | 255 | | |
| Label | MasterLabel | string | 80 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Language | Language | picklist | 40 | | |
| Name | DeveloperName | string | 80 | | |
| Named Credential ID | Id | id | 15 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| URL | Endpoint | textarea | 1000 | | |

Note

Represents a note, which is text associated with a custom object or a standard object, such as a Contact, Contract, or Opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Body | Body | textarea | 32000 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Note Id | Id | id | 15 | | |
| Note Owner | OwnerId | reference | 15 | | |
| Parent | ParentId | reference | 15 | | |
| Private | IsPrivate | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Title | Title | string | 80 | | |

NoteAndAttachment

This read-only object contains all notes and attachments associated with an object.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Is Note | IsNote | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Note or Attachment Id | Id | id | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|-----------|--------|-----------|-------|
| Owner Name | OwnerId | reference | 15 | | |
| Parent | ParentId | reference | 15 | | |
| Private | IsPrivate | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Title | Title | string | 80 | | |

OauthToken

Represents an OAuth access token for connected app authentication and can be used to create a user interface for token management. This object is available in API version 32.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------|----------------|-----------|--------|-----------|-------|
| Access Token | AccessToken | string | 255 | | |
| AppMenuItem | AppMenuItemId | reference | 15 | | |
| Application Name | AppName | string | 255 | | |
| Created Date | CreatedDate | datetime | | | |
| Delete Token | DeleteToken | string | 255 | | |
| Last Used Date | LastUsedDate | datetime | | | |
| Oauth Token ID | Id | id | 15 | | |
| Request Token | RequestToken | string | 255 | | |
| Use Count | UseCount | int | | 9 | 0 |
| User | UserId | reference | 15 | | |

ObjectPermissions

Represents the enabled object permissions for the parent PermissionSet. This object is available in API version 24.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|------|--------|-----------|-------|
| | Permissions | int | | 9 | 0 |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Entity Name | SubjectType | picklist | 40 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| ObjectPermissions ID | Id | id | 15 | | |
| Parent Entity | ParentId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

OpenActivity

This read-only object is displayed in a related list of open activities—future events and open tasks—related to an object. It includes activities for all contacts related to the object. OpenActivity fields for phone calls are only available if your organization uses Salesforce CRM Call Center.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|-----------------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Activity ID | Id | id | 15 | | |
| All-Day Event | IsAllDayEvent | boolean | | | |
| Assigned To | OwnerId | reference | 15 | | |
| Call Duration | CallDurationInSeconds | int | | 8 | 0 |
| Call Object Identifier | CallObject | string | 255 | | |
| Call Result | CallDisposition | string | 255 | | |
| Call Type | CallType | picklist | 40 | | |
| Closed | IsClosed | boolean | | | |
| Comments | Description | textarea | 32000 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Date | ActivityDate | date | | | |
| Deleted | IsDeleted | boolean | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------------|-----------|--------|-----------|-------|
| Duration | DurationInMinutes | int | | 9 | 0 |
| End | EndDateTime | datetime | | | |
| High Priority | IsHighPriority | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Location | Location | string | 80 | | |
| Name | WhoId | reference | 15 | | |
| Priority | Priority | picklist | 40 | | |
| Public | IsVisibleInSelfService | boolean | | | |
| Related To | WhatId | reference | 15 | | |
| Reminder Date/Time | ReminderDateTime | datetime | | | |
| Reminder Set | IsReminderSet | boolean | | | |
| Start | StartDateTime | datetime | | | |
| Status | Status | picklist | 40 | | |
| Subject | Subject | combobox | 80 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Task | IsTask | boolean | | | |
| Type | ActivityType | picklist | 40 | | |

Opportunity

Represents an opportunity, which is a sale or pending deal.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------|----------------|-----------|--------|-----------|-------|
| Account Name | AccountId | reference | 15 | | |
| Amount | Amount | currency | | 18 | 2 |
| Close Date | CloseDate | date | | | |
| Closed | IsClosed | boolean | | | |
| Contract | ContractId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------|--------------------------|-----------|--------|-----------|-------|
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Expected Revenue | ExpectedRevenue | currency | | 18 | 2 |
| Fiscal Period | FiscalYear | int | | 8 | 0 |
| Fiscal Period | FiscalQuarter | int | | 8 | 0 |
| Forecast Category | ForecastCategory | picklist | 40 | | |
| Forecast Category | ForecastCategoryName | picklist | 40 | | |
| Has Line Item | HasOpportunityLineItem | boolean | | | |
| Last Activity | LastActivityDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Lead Source | LeadSource | picklist | 40 | | |
| Next Step | NextStep | string | 255 | | |
| Opportunity ID | Id | id | 15 | | |
| Opportunity Name | Name | string | 120 | | |
| Opportunity Owner | OwnerId | reference | 15 | | |
| Price Book | Pricebook2Id | reference | 15 | | |
| Primary Campaign Source | CampaignId | reference | 15 | | |
| Private | IsPrivate | boolean | | | |
| Probability (%) | Probability | percent | | 3 | 0 |
| Quantity | TotalOpportunityQuantity | double | | 18 | 2 |
| Stage | StageName | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |
| Won | IsWon | boolean | | | |

OpportunityCompetitor

Represents a competitor on an Opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------------|------------------|-----------|--------|-----------|-------|
| Competitor Name | CompetitorName | combobox | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity | OpportunityId | reference | 15 | | |
| Opportunity: Competitor ID | Id | id | 15 | | |
| Strengths | Strengths | string | 1000 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Weaknesses | Weaknesses | string | 1000 | | |

OpportunityContactRole

Represents the role that a Contact plays on an Opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Contact | ContactId | reference | 15 | | |
| Contact Role ID | Id | id | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity | OpportunityId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|----------|--------|-----------|-------|
| Primary | IsPrimary | boolean | | | |
| Role | Role | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

OpportunityHistory

Represents the stage history of an Opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------|-----------|--------|-----------|-------|
| Amount | Amount | currency | | 18 | 2 |
| Close Date | CloseDate | date | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Expected Revenue | ExpectedRevenue | currency | | 18 | 2 |
| Opportunity | OpportunityId | reference | 15 | | |
| Opportunity History ID | Id | id | 15 | | |
| Probability | Probability | percent | | 3 | 0 |
| Stage Name | StageName | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| To ForecastCategory | ForecastCategory | picklist | 40 | | |

OpportunityLineItem

Represents an opportunity line item, which is a member of the list of Product2 products associated with an Opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------|----------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|------------------|-----------|--------|-----------|-------|
| Date | ServiceDate | date | | | |
| Deleted | IsDeleted | boolean | | | |
| Discount | Discount | percent | | 5 | 2 |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Line Description | Description | string | 255 | | |
| Line Item ID | Id | id | 15 | | |
| List Price | ListPrice | currency | | 18 | 2 |
| Opportunity | OpportunityId | reference | 15 | | |
| Opportunity Product Name | Name | string | 376 | | |
| Price Book Entry | PricebookEntryId | reference | 15 | | |
| Product | Product2Id | reference | 15 | | |
| Product Code | ProductCode | string | 255 | | |
| Quantity | Quantity | double | | 12 | 2 |
| Sales Price | UnitPrice | currency | | 18 | 2 |
| Sort Order | SortOrder | int | | 9 | 0 |
| Subtotal | Subtotal | currency | | 18 | 2 |
| System Modstamp | SystemModstamp | datetime | | | |
| Total Price | TotalPrice | currency | | 18 | 2 |

OpportunityLineItemSchedule

Represents information about the quantity, revenue distribution, and delivery dates for a particular OpportunityLineItem.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------|-----------------|-----------|--------|-----------|-------|
| Comments | Description | string | 80 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency ISO Code | CurrencyIsoCode | picklist | 3 | | |
| Deleted | IsDeleted | boolean | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|-----------------------|-----------|--------|-----------|-------|
| Division | Division | picklist | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Line Item | OpportunityLineItemId | reference | 15 | | |
| Quantity | Quantity | double | | 18 | 2 |
| Revenue | Revenue | currency | | 18 | 2 |
| Schedule Date | ScheduleDate | date | | | |
| Schedule ID | Id | id | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |

OpportunityPartner

This read-only object represents a partner relationship between an Account and an Opportunity. This object is automatically created when a Partner object is created for a partner relationship between an account and an opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------|-----------|--------|-----------|-------|
| Account To | AccountToId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity | OpportunityId | reference | 15 | | |
| Opportunity Partner ID | Id | id | 15 | | |
| Primary | IsPrimary | boolean | | | |
| Reverse Partner | ReversePartnerId | reference | 15 | | |
| Role | Role | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

OpportunitySplit

OpportunitySplit credits one or more opportunity team members with a portion of the opportunity amount. This object is available in API version 16.0 and later for pilot customers, and version 28.0 and later for others.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|------------------|-----------|--------|-----------|-------|
| Amount | SplitAmount | currency | | 18 | 2 |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | Split | string | 255 | | |
| Note | SplitNote | string | 255 | | |
| Opportunity Name | OpportunityId | reference | 15 | | |
| Opportunity Split ID | Id | id | 15 | | |
| Opportunity Split Type | SplitTypeId | reference | 15 | | |
| Percent (%) | SplitPercentage | percent | | 5 | 2 |
| System Modstamp | SystemModstamp | datetime | | | |
| Team Member | SplitOwnerId | reference | 15 | | |

OpportunitySplitType

OpportunitySplitType provides unique labels and behavior for each split type.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------|------------------|-----------|--------|-----------|-------|
| 100% Validated | IsTotalValidated | boolean | | | |
| Active | IsActive | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------------|------------------|-----------|--------|-----------|-------|
| Data Status | SplitDataStatus | picklist | 255 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 255 | | |
| Developer Name | DeveloperName | string | 80 | | |
| Entity | SplitEntity | picklist | 255 | | |
| Field | SplitField | picklist | 255 | | |
| Label | MasterLabel | string | 80 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Language | Language | picklist | 40 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Opportunity Split Type ID | Id | id | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

OpportunityStage

Represents the stage of an Opportunity in the sales pipeline, such as New Lead, Negotiating, Pending, Closed, and so on.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|----------------------|-----------|--------|-----------|-------|
| Closed | IsClosed | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | string | 255 | | |
| Forecast Category | ForecastCategory | picklist | 40 | | |
| Forecast Category Name | ForecastCategoryName | picklist | 40 | | |
| Is Active | IsActive | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Label | MasterLabel | string | 255 | | |
| Opportunity Stage ID | Id | id | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|--------------------|----------|--------|-----------|-------|
| Probability (%) | DefaultProbability | percent | | 3 | 0 |
| Sort Order | SortOrder | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |
| Won | IsWon | boolean | | | |

OpportunityTeamMember

Represents a User on the opportunity team of an Opportunity.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------------|------------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency ISO Code | CurrencyIsoCode | picklist | 3 | | |
| Deleted | IsDeleted | boolean | | | |
| Division | Division | picklist | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity | OpportunityId | reference | 15 | | |
| Opportunity Access | OpportunityAccessLevel | picklist | 40 | | |
| Opportunity Team Member ID | Id | id | 15 | | |
| Opportunity Team Member Name | Name | string | 361 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Team Role | TeamMemberRole | picklist | 40 | | |
| User | UserId | reference | 15 | | |

OwnedContentDocument

Represents a file owned by a user. This object is available in version 30.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------|------------------------|-----------|--------|-----------|-------|
| Content Modified By | LastModifiedById | reference | 15 | | |
| Content Modified Date | LastModifiedDate | datetime | | | |
| Content Size | ContentSize | int | | 9 | 0 |
| Content URL | ContentUrl | url | 255 | | |
| Created | CreatedDate | datetime | | | |
| Created By | OwnerId | reference | 15 | | |
| Created by | CreatedById | reference | 15 | | |
| Deleted | IsDeleted | boolean | | | |
| Document | ContentDocumentId | reference | 15 | | |
| External Data Source | ExternalDataSourceName | string | 80 | | |
| File Extension | FileExtension | string | 40 | | |
| File Type | FileType | string | 20 | | |
| Title | Title | string | 255 | | |
| User Owned Content Document Id | Id | id | 15 | | |

Partner

Represents a partner relationship between two Account records or between an Opportunity and an Account.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Account From | AccountFromId | reference | 15 | | |
| Account To | AccountToId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity | OpportunityId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|------------------|-----------|--------|-----------|-------|
| Partner ID | Id | id | 15 | | |
| Primary | IsPrimary | boolean | | | |
| Reverse Partner | ReversePartnerId | reference | 15 | | |
| Role | Role | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

PartnerNetworkConnection

Represents a Salesforce to Salesforce connection between Salesforce organizations.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------------|------------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Connection Name | ConnectionName | string | 295 | | |
| Connection Owner | PrimaryContactId | reference | 15 | | |
| Connection Status | ConnectionStatus | picklist | 40 | | |
| Contact | ContactId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Decision Date | ResponseDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Partner Network Connection ID | Id | id | 15 | | |

PartnerNetworkRecordConnection

Represents a record shared between Salesforce organizations using Salesforce to Salesforce.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|-----------|--------|-----------|-------|
| Connection | ConnectionId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------------|-----------------|-----------|--------|-----------|-------|
| Local Record | LocalRecordId | reference | 15 | | |
| Parent Record | ParentRecordId | reference | 15 | | |
| Partner Network Record Connection ID | Id | id | 15 | | |
| Partner Record | PartnerRecordId | reference | 15 | | |
| Related Records | RelatedRecords | string | 1000 | | |
| Send Closed Tasks | SendClosedTasks | boolean | | | |
| Send Emails | SendEmails | boolean | | | |
| Send Open Tasks | SendOpenTasks | boolean | | | |
| Start Date | StartDate | datetime | | | |
| Status | Status | picklist | 40 | | |
| Stop Date | EndDate | datetime | | | |

PartnerRole

Represents a role for an account Partner, such as consultant, supplier, and so on.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Label | MasterLabel | string | 255 | | |
| Partner Role Value ID | Id | id | 15 | | |
| Reverse Role | ReverseRole | picklist | 40 | | |
| Sort Order | SortOrder | int | | 9 | 0 |
| System Modstamp | SystemModstamp | datetime | | | |

Period

Represents a fiscal period defined in FiscalYearSettings.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|----------------------|-----------|--------|-----------|-------|
| End Date | EndDate | date | | | |
| Fiscal Year Settings | FiscalYearSettingsId | reference | 15 | | |
| Is Forecast Period | IsForecastPeriod | boolean | | | |
| Number | Number | int | | 9 | 0 |
| Period ID | Id | id | 15 | | |
| Period Name | PeriodLabel | picklist | 40 | | |
| Quarter Name | QuarterLabel | picklist | 40 | | |
| Start Date | StartDate | date | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |

PermissionSet

Represents a set of permissions that's used to grant additional access to one or more users without changing their profile or reassigning profiles. This object is available in API version 22.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | string | 255 | | |
| Is Owned By Profile | IsOwnedByProfile | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Permission Set Label | Label | string | 80 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|----------------|-----------|--------|-----------|-------|
| Permission Set Name | Name | string | 80 | | |
| PermissionSet ID | Id | id | 15 | | |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Permissions | Permissions | int | | 9 | 0 |
| Profile | ProfileId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| User License | UserLicenseId | reference | 15 | | |

PermissionSetAssignment

Represents the association between a User and a PermissionSet. This object is available in API version 22.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------------|-----------------|-----------|--------|-----------|-------|
| Date Assigned | SystemModstamp | datetime | | | |
| Permission Set | PermissionSetId | reference | 15 | | |
| PermissionSetAssignment ID | Id | id | 15 | | |
| User | AssigneeId | reference | 15 | | |

PermissionSetLicense

Represents a license that's used to enable one or more users to receive a specified permission without changing their profile or reassigning profiles. You can use permission set licenses to grant access, but not to deny access. This object is available in API version 29.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------------|-------------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Developer Name | DeveloperName | string | 80 | | |
| Expiration Date | ExpirationDate | date | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Master Language | Language | picklist | 40 | | |
| Permission Set License ID | Id | id | 15 | | |
| Permission Set License Key | PermissionSetLicenseKey | string | 81 | | |
| Permission Set License Label | MasterLabel | string | 80 | | |
| Status | Status | picklist | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Total Licenses | TotalLicenses | int | | 9 | 0 |
| Used Licenses | UsedLicenses | int | | 9 | 0 |

PermissionSetLicenseAssign

Represents the association between a User and a PermissionSetLicense. This object is available in API version 29.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------|----------------|-----------|--------|-----------|-------|
| Assignee | AssigneeId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------------|-------------------------|-----------|--------|-----------|-------|
| Date Assigned | SystemModstamp | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Permission Set License | PermissionSetLicensesId | reference | 15 | | |
| Permission Set License Assignment ID | Id | id | 15 | | |

PlatformAction

PlatformAction is a virtual read-only object. It enables you to query for actions displayed in the UI, given a user, a context, device format, and a record ID. Examples include standard and custom buttons, quick actions, and productivity actions.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|---------------------|-----------|--------|-----------|-------|
| API Name | ApiName | string | 255 | | |
| Action List Context | ActionListContext | picklist | 255 | | |
| Action Target Type | ActionTargetType | picklist | 255 | | |
| Action Target URL | ActionTargetUrl | url | 255 | | |
| Category | Category | picklist | 255 | | |
| Confirmation Message | ConfirmationMessage | string | 255 | | |
| Device Format | DeviceFormat | picklist | 255 | | |
| Group ID | GroupId | reference | 15 | | |
| Icon Content Type | IconContentType | string | 255 | | |
| Icon Height | IconHeight | int | | 9 | 0 |
| Icon URL | IconUrl | url | 255 | | |
| Icon Width | IconWidth | int | | 9 | 0 |
| Invocation Status | InvocationStatus | picklist | 255 | | |
| Invoked By | InvokedById | reference | 15 | | |
| Is Group Default | IsGroupDefault | boolean | | | |
| Label | Label | string | 255 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|---------------------|----------|--------|-----------|-------|
| Last Modified Date | LastModifiedDate | datetime | | | |
| Not used ID | Id | id | 15 | | |
| Platform Action ID | ExternalId | string | 255 | | |
| Primary Color | PrimaryColor | string | 255 | | |
| Related Source Entity | RelatedSourceEntity | string | 255 | | |
| Source Entity | SourceEntity | string | 255 | | |
| Subtype | Subtype | string | 255 | | |
| Type | Type | picklist | 255 | | |

Pricebook2

Represents a price book that contains the list of products that your org sells.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|--------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | string | 255 | | |
| Is Standard Price Book | IsStandard | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Price Book ID | Id | id | 15 | | |
| Price Book Name | Name | string | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |

PricebookEntry

Represents a product entry (an association between a Pricebook2 and Product2) in a price book.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| List Price | UnitPrice | currency | | 18 | 2 |
| Price Book | Pricebook2Id | reference | 15 | | |
| Price Book Entry ID | Id | id | 15 | | |
| Product | Product2Id | reference | 15 | | |
| Product Code | ProductCode | string | 255 | | |
| Product Name | Name | string | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Use Standard Price | UseStandardPrice | boolean | | | |

Product2

Represents a product that your org sells.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------|------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|------------------|----------|--------|-----------|-------|
| Last Modified Date | LastModifiedDate | datetime | | | |
| Product Code | ProductCode | string | 255 | | |
| Product Description | Description | textarea | 4000 | | |
| Product Family | Family | picklist | 40 | | |
| Product ID | Id | id | 15 | | |
| Product Name | Name | string | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |

ProductEntitlementTemplate

Represents predefined terms of customer support (Entitlement) that users can add to products (Product2).

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------------------|-----------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Entitlement Template | EntitlementTemplateId | reference | 15 | | |
| Product | Product2Id | reference | 15 | | |
| Product Entitlement Template ID | Id | id | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

Question

Represents a question in a community that users can view and reply to.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------|-----------------|-----------|--------|-----------|-------|
| Best Reply | BestReplyId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency ISO Code | CurrencyIsoCode | picklist | 3 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------------|--------------------------|-----------|--------|-----------|-------|
| Deleted | IsDeleted | boolean | | | |
| Has Single Field For Content | HasSingleFieldForContent | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Reply | LastReplyId | reference | 15 | | |
| Last Reply Date | LastReplyDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Number of Replies | NumReplies | int | | 9 | 0 |
| Question Body | Body | textarea | 32000 | | |
| Question ID | Id | id | 15 | | |
| Question Title | Title | string | 255 | | |
| Record Type | RecordTypeId | reference | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Up Votes | UpVotes | int | | 9 | 0 |
| Vote Score | VoteScore | double | | 18 | 4 |
| Zone | CommunityId | reference | 15 | | |

Quote

The Quote object represents a quote, which is a record showing proposed prices for products and services. Available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------|----------------------|-----------|--------|-----------|-------|
| Account Name | AccountId | reference | 15 | | |
| Additional To | AdditionalStreet | textarea | 255 | | |
| Additional To | AdditionalCity | string | 40 | | |
| Additional To | AdditionalState | string | 80 | | |
| Additional To | AdditionalPostalCode | string | 20 | | |
| Additional To | AdditionalCountry | string | 80 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Additional To Name | AdditionalName | string | 255 | | |
| Bill To | BillingStreet | textarea | 255 | | |
| Bill To | BillingCity | string | 40 | | |
| Bill To | BillingState | string | 80 | | |
| Bill To | BillingPostalCode | string | 20 | | |
| Bill To | BillingCountry | string | 80 | | |
| Bill To Name | BillingName | string | 255 | | |
| Contact Name | ContactId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Discount | Discount | percent | | 5 | 2 |
| Email | Email | email | 80 | | |
| Expiration Date | ExpirationDate | date | | | |
| Fax | Fax | phone | 40 | | |
| Grand Total | GrandTotal | currency | | 18 | 2 |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Line Items | LineItemCount | int | | 9 | 0 |
| Opportunity Name | OpportunityId | reference | 15 | | |
| Phone | Phone | phone | 40 | | |
| Pricebook | Pricebook2Id | reference | 15 | | |
| Quote ID | Id | id | 15 | | |
| Quote Name | Name | string | 255 | | |
| Quote Number | QuoteNumber | string | 30 | | |
| Quote To | QuoteToStreet | textarea | 255 | | |
| Quote To | QuoteToCity | string | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|--------------------|----------|--------|-----------|-------|
| Quote To | QuoteToState | string | 80 | | |
| Quote To | QuoteToPostalCode | string | 20 | | |
| Quote To | QuoteToCountry | string | 80 | | |
| Quote To Name | QuoteToName | string | 255 | | |
| Ship To | ShippingStreet | textarea | 255 | | |
| Ship To | ShippingCity | string | 40 | | |
| Ship To | ShippingState | string | 80 | | |
| Ship To | ShippingPostalCode | string | 20 | | |
| Ship To | ShippingCountry | string | 80 | | |
| Ship To Name | ShippingName | string | 255 | | |
| Shipping and Handling | ShippingHandling | currency | | 18 | 2 |
| Status | Status | picklist | 40 | | |
| Subtotal | Subtotal | currency | | 18 | 2 |
| Syncing | IsSyncing | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Tax | Tax | currency | | 18 | 2 |
| Total Price | TotalPrice | currency | | 18 | 2 |

RecentlyViewed

Represents records that the current user has recently viewed or referenced (by viewing a related record).

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Alias | Alias | string | 8 | | |
| E-mail | Email | email | 80 | | |
| Language | Language | picklist | 40 | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Phone | Phone | phone | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|----------------|-----------|--------|-----------|-------|
| Profile | ProfileId | reference | 15 | | |
| Recently Viewed ID | Id | id | 15 | | |
| Record Type ID | RecordTypeId | reference | 15 | | |
| Role | UserRoleId | reference | 15 | | |
| Title | Title | string | 80 | | |
| Type | Type | picklist | 40 | | |

Reply

Represents a reply that a user has submitted to a question in an answers community.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency ISO Code | CurrencyIsoCode | picklist | 3 | | |
| Deleted | IsDeleted | boolean | | | |
| Down Votes | DownVotes | int | | 9 | 0 |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | Name | string | 255 | | |
| Question | QuestionId | reference | 15 | | |
| Reply Body | Body | textarea | 32000 | | |
| Reply ID | Id | id | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Up Votes | UpVotes | int | | 9 | 0 |
| Vote Total | VoteTotal | double | | 18 | 0 |
| Zone | CommunityId | reference | 15 | | |

Report

Represents a report, a set of data that meets certain criteria, displayed in an organized way. Access is read-only. This object is available in API version 20.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|--------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | string | 255 | | |
| Folder | OwnerId | reference | 15 | | |
| Format | Format | picklist | 40 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Run | LastRunDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Report ID | Id | id | 15 | | |
| Report Name | Name | string | 40 | | |
| Report Unique Name | DeveloperName | string | 80 | | |
| System Modstamp | SystemModstamp | datetime | | | |

SelfServiceUser

Represents a Contact who has been enabled to use your organization's Self-Service portal, where he or she can obtain online support.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Contact | ContactId | reference | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|-------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Email | Email | email | 80 | | |
| LanguageLocaleKey | LanguageLocaleKey | picklist | 40 | | |
| Last Login | LastLoginDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| LocaleSidKey | LocaleSidKey | picklist | 40 | | |
| Super User | SuperUser | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| TimeZoneSidKey | TimeZoneSidKey | picklist | 40 | | |
| User ID | Id | id | 15 | | |
| Username | Username | string | 80 | | |

ServiceContract

Represents a customer support contract (business agreement). This object is available in API version 18.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|-------------------|-----------|--------|-----------|-------|
| Account Name | AccountId | reference | 15 | | |
| Activation Date | ActivationDate | datetime | | | |
| Approval Status | ApprovalStatus | picklist | 40 | | |
| Billing Address | BillingStreet | textarea | 255 | | |
| Billing Address | BillingCity | string | 40 | | |
| Billing Address | BillingState | string | 80 | | |
| Billing Address | BillingPostalCode | string | 20 | | |
| Billing Address | BillingCountry | string | 80 | | |
| Contact Name | ContactId | reference | 15 | | |
| Contract Name | Name | string | 255 | | |
| Contract Number | ContractNumber | string | 30 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------|--------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Currency | CurrencyIsoCode | picklist | 3 | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 32000 | | |
| Discount | Discount | percent | | 5 | 2 |
| End Date | EndDate | date | | | |
| Grand Total | GrandTotal | currency | | 18 | 2 |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Line Items | LineItemCount | int | | 9 | 0 |
| Price Book | Pricebook2Id | reference | 15 | | |
| Service Contract ID | Id | id | 15 | | |
| Service Contract Owner | OwnerId | reference | 15 | | |
| Shipping Address | ShippingStreet | textarea | 255 | | |
| Shipping Address | ShippingCity | string | 40 | | |
| Shipping Address | ShippingState | string | 80 | | |
| Shipping Address | ShippingPostalCode | string | 20 | | |
| Shipping Address | ShippingCountry | string | 80 | | |
| Shipping and Handling | ShippingHandling | currency | | 18 | 2 |
| Special Terms | SpecialTerms | textarea | 32000 | | |
| Start Date | StartDate | date | | | |
| Status | Status | picklist | 255 | | |
| Subtotal | Subtotal | currency | | 18 | 2 |
| System Modstamp | SystemModstamp | datetime | | | |
| Tax | Tax | currency | | 18 | 2 |
| Term (months) | Term | int | | 9 | 0 |
| Total Price | TotalPrice | currency | | 18 | 2 |

SetupEntityAccess

Represents the enabled setup entity access settings (such as for Apex classes) for the parent PermissionSet. This object is available in API version 25.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------|-----------------|-----------|--------|-----------|-------|
| Parent Entity | ParentId | reference | 15 | | |
| Setup Entity | SetupEntityId | reference | 15 | | |
| Setup Entity Type | SetupEntityType | picklist | 40 | | |
| SetupEntityAccess ID | Id | id | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |

Site

Represents a public website that is integrated with an org. This object is available in API version 16.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------|-----------------------------|-----------|--------|-----------|-------|
| Analytics Tracking Code | AnalyticsTrackingCode | string | 40 | | |
| Clickjack Protection Level | ClickjackProtectionLevel | picklist | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Daily Bandwidth Limit (MB) | DailyBandwidthLimit | int | | 9 | 0 |
| Daily Bandwidth Used | DailyBandwidthUsed | int | | 9 | 0 |
| Daily Request Time Limit (min) | DailyRequestTimeLimit | int | | 9 | 0 |
| Daily Request Time Used | DailyRequestTimeUsed | int | | 9 | 0 |
| Default Web Address | UrlPathPrefix | string | 40 | | |
| Guest User | GuestUserId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Monthly Page Views Allowed | MonthlyPageViewsEntitlement | int | | 9 | 0 |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|----------------|-----------|--------|-----------|-------|
| Options | Options | int | | 9 | 0 |
| Site Contact | AdminId | reference | 15 | | |
| Site Description | Description | textarea | 1000 | | |
| Site ID | Id | id | 15 | | |
| Site Label | MasterLabel | string | 255 | | |
| Site Name | Name | string | 80 | | |
| Site Status | Status | picklist | 40 | | |
| Site Subdomain Prefix | Subdomain | string | 80 | | |
| Site Type | SiteType | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

SlaProcess

Represents an entitlement process associated with an Entitlement. This object is available in API version 19.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Business Hours | BusinessHoursId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Description | Description | textarea | 255 | | |
| Entitlement Process ID | Id | id | 15 | | |
| Entitlement Process Name | Name | string | 120 | | |
| Entry Date Field | StartDateField | picklist | 40 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | NameNorm | string | 240 | | |
| System Modstamp | SystemModstamp | datetime | | | |

Solution

Represents a detailed description of a customer issue and the resolution of that issue.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------------------|-----------------------|-----------|--------|-----------|-------|
| Author | OwnerId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Is Html | IsHtml | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Num Related Cases | TimesUsed | int | | 9 | 0 |
| Public | IsPublished | boolean | | | |
| Reviewed | IsReviewed | boolean | | | |
| Solution Details | SolutionNote | textarea | 32000 | | |
| Solution ID | Id | id | 15 | | |
| Solution Number | SolutionNumber | string | 30 | | |
| Solution Title | SolutionName | string | 255 | | |
| Status | Status | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Visible in Public Knowledge Base | IsPublishedInPublicKb | boolean | | | |

TagDefinition

Defines the attributes of child Tag objects.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------|------------------|-----------|--------|-----------|-------|
| Deleted | IsDeleted | boolean | | | |
| Display Tag Text | Name | string | 765 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Tag Definition ID | Id | id | 15 | | |
| Tag Type | Type | picklist | 40 | | |

Task

Represents a business activity such as making a phone call or other to-do items. In the user interface, Task and Event records are collectively referred to as activities.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|----------------------------------|-----------------------|-----------|--------|-----------|-------|
| Account | AccountId | reference | 15 | | |
| Activity ID | Id | id | 15 | | |
| Archived | IsArchived | boolean | | | |
| Assigned To | OwnerId | reference | 15 | | |
| Call Duration | CallDurationInSeconds | int | | 8 | 0 |
| Call Object Identifier | CallObject | string | 255 | | |
| Call Result | CallDisposition | string | 255 | | |
| Call Type | CallType | picklist | 40 | | |
| Closed | IsClosed | boolean | | | |
| Comments | Description | textarea | 32000 | | |
| Create Recurring Series of Tasks | IsRecurrence | boolean | | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Due Date | ActivityDate | date | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------|---------------------------|-----------|--------|-----------|-------|
| End Date | RecurrenceEndDateOnly | date | | | |
| High Priority | IsHighPriority | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Name | WhoId | reference | 15 | | |
| Priority | Priority | picklist | 40 | | |
| Recurrence Activity | RecurrenceActivityId | reference | 15 | | |
| Recurrence Day of Month | RecurrenceDayOfMonth | int | | 9 | 0 |
| Recurrence Day of Week Mask | RecurrenceDayOfWeekMask | int | | 9 | 0 |
| Recurrence Instance | RecurrenceInstance | picklist | 40 | | |
| Recurrence Interval | RecurrenceInterval | int | | 9 | 0 |
| Recurrence Month of Year | RecurrenceMonthOfYear | picklist | 40 | | |
| Recurrence Time Zone | RecurrenceTimeZoneSidKey | picklist | 40 | | |
| Recurrence Type | RecurrenceType | picklist | 40 | | |
| Related To | WhatId | reference | 15 | | |
| Reminder Date/Time | ReminderDateTime | datetime | | | |
| Reminder Set | IsReminderSet | boolean | | | |
| Repeat This Task | RecurrenceRegeneratedType | picklist | 40 | | |
| Start Date | RecurrenceStartDateOnly | date | | | |
| Status | Status | picklist | 40 | | |
| Subject | Subject | combobox | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Type | Type | picklist | 40 | | |

Territory

Represents a flexible collection of accounts and users where the users have at least read access to the accounts, regardless of who owns the accounts. Only available if territory management has been enabled for your organization.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------|-----------------------------|-----------|--------|-----------|-------|
| Account Access Level | AccountAccessLevel | picklist | 40 | | |
| Case Access Level | CaseAccessLevel | picklist | 40 | | |
| Confine Opportunity Assignment | RestrictOpportunityTransfer | boolean | | | |
| Contact Access Level | ContactAccessLevel | picklist | 40 | | |
| Currency | CurrencyIsoCode | picklist | 3 | | |
| Description | Description | string | 1000 | | |
| Developer Name | DeveloperName | string | 80 | | |
| Forecast Manager | ForecastUserId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| May Forecast Manager Share | MayForecastManagerShare | boolean | | | |
| Opportunity Access Level | OpportunityAccessLevel | picklist | 40 | | |
| Parent Territory | ParentTerritoryId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Territory ID | Id | id | 15 | | |
| Territory Name | Name | string | 80 | | |

Topic

Represents a topic on a Chatter post or record. This object is available in API version 28.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Description | Description | string | 1000 | | |
| Name | Name | string | 99 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Talking About | TalkingAbout | int | | 9 | 0 |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|------|--------|-----------|-------|
| Topic ID | Id | id | 15 | | |

TopicAssignment

Represents the assignment of a topic to a specific feed item, record, or file. This object is available in API version 28.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|-----------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Object Type | EntityType | string | 80 | | |
| Record | EntityId | reference | 15 | | |
| Record Key Prefix | EntityKeyPrefix | string | 3 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Topic | TopicId | reference | 15 | | |
| Topic Assignment Id | Id | id | 15 | | |

TwoFactorInfo

Stores a user's secret for two-factor operations. Use this object when customizing two-factor authentication in your organization.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Algorithm Type | Type | picklist | 255 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--|----------------|-----------|--------|-----------|-------|
| Shared key between User and authentication service | SharedKey | string | 255 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Two Factor ID | Id | id | 15 | | |
| User | UserId | reference | 15 | | |

User

Represents a user in your organization.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|------------------------------------|-------------------------|-----------|--------|-----------|-------|
| | EmailPreferences | int | | 9 | 0 |
| About Me | AboutMe | textarea | 1000 | | |
| Account | AccountId | reference | 15 | | |
| Active | IsActive | boolean | | | |
| Address | Street | textarea | 255 | | |
| Address | City | string | 40 | | |
| Address | State | string | 80 | | |
| Address | PostalCode | string | 20 | | |
| Address | Country | string | 80 | | |
| Admin Info Emails | ReceivesAdminInfoEmails | boolean | | | |
| Alias | Alias | string | 8 | | |
| Allow Forecasting | ForecastEnabled | boolean | | | |
| Call Center | CallCenterId | reference | 15 | | |
| Cell | MobilePhone | phone | 40 | | |
| Chatter Email Highlights Frequency | DigestFrequency | picklist | 40 | | |
| Company Name | CompanyName | string | 80 | | |
| Contact | ContactId | reference | 15 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--|-----------------------------------|-----------|--------|-----------|-------|
| Default Notification Frequency when Joining Groups | DefaultGroupNotificationFrequency | picklist | 40 | | |
| Delegated Approver | DelegatedApproverId | reference | 15 | | |
| Department | Department | string | 80 | | |
| Division | Division | string | 80 | | |
| E-mail | Email | email | 128 | | |
| Email Encoding | EmailEncodingKey | picklist | 40 | | |
| Email Sender Address | SenderEmail | email | 80 | | |
| Email Sender Name | SenderName | string | 80 | | |
| Email Signature | Signature | string | 1333 | | |
| Employee Number | EmployeeNumber | string | 20 | | |
| Extension | Extension | phone | 40 | | |
| Fax | Fax | phone | 40 | | |
| Info Emails | ReceivesInfoEmails | boolean | | | |
| Language | LanguageLocaleKey | picklist | 40 | | |
| Last Login | LastLoginDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Last Password Change or Reset | LastPasswordChangeDate | datetime | | | |
| Last Referenced Date | LastReferencedDate | datetime | | | |
| Last Viewed Date | LastViewedDate | datetime | | | |
| Locale | LocaleSidKey | picklist | 40 | | |
| Manager | ManagerId | reference | 15 | | |
| Nickname | CommunityNickname | string | 40 | | |
| Offline Edition Trial Expiration Date | OfflineTrialExpirationDate | datetime | | | |
| Phone | Phone | phone | 40 | | |
| Profile | ProfileId | reference | 15 | | |
| Role | UserRoleId | reference | 15 | | |
| Sales Anywhere Trial Expiration Date | OfflinePdaTrialExpirationDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Time Zone | TimeZoneSidKey | picklist | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------------------------|----------------|----------|--------|-----------|-------|
| Title | Title | string | 80 | | |
| Url for Thumbnail sized Photo | SmallPhotoUrl | url | 1024 | | |
| Url for full-sized Photo | FullPhotoUrl | url | 1024 | | |
| User ID | Id | id | 15 | | |
| User Photo badge text overlay | BadgeText | string | 80 | | |
| User Type | UserType | picklist | 40 | | |
| Username | Username | string | 80 | | |

UserAccountTeamMember

Represents a User on the default account team of another User.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------------|------------------------|-----------|--------|-----------|-------|
| Account Access | AccountAccessLevel | picklist | 40 | | |
| Case Access | CaseAccessLevel | picklist | 40 | | |
| Contact Access | ContactAccessLevel | picklist | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity Access | OpportunityAccessLevel | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Team Role | TeamMemberRole | picklist | 40 | | |
| User | OwnerId | reference | 15 | | |
| User | UserId | reference | 15 | | |
| User Account Team Member ID | Id | id | 15 | | |

UserLogin

Represents the settings that affect a user's ability to log into an organization. To access this object, you need the `UserPermissions.ManageUsers` permission. This object is available in API version 29.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Is Frozen | IsFrozen | boolean | | | |
| Is Password Locked | IsPasswordLocked | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| User | UserId | reference | 15 | | |
| User Login ID | Id | id | 15 | | |

UserRecordAccess

Represents a user's access to a set of records. This object is read only and is available in API version 24.0 and later.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------------|-------------------|-----------|--------|-----------|-------|
| Has All Access | HasAllAccess | boolean | | | |
| Has Delete Access | HasDeleteAccess | boolean | | | |
| Has Edit Access | HasEditAccess | boolean | | | |
| Has Read Access | HasReadAccess | boolean | | | |
| Has Transfer Access | HasTransferAccess | boolean | | | |
| Maximum Access Level | MaxAccessLevel | picklist | 40 | | |
| Record | RecordId | picklist | 40 | | |
| User | UserId | reference | 15 | | |
| User Record Access ID | Id | id | 15 | | |

UserRole

Represents a user role in your organization.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--|----------------------------------|-----------|--------|-----------|-------|
| Case Access Level for Account Owner | CaseAccessForAccountOwner | picklist | 40 | | |
| Contact Access Level for Account Owner | ContactAccessForAccountOwner | picklist | 40 | | |
| Description | RollupDescription | string | 80 | | |
| Developer Name | DeveloperName | string | 80 | | |
| Forecast Manager | ForecastUserId | reference | 15 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| May Forecast Manager Share | MayForecastManagerShare | boolean | | | |
| Name | Name | string | 80 | | |
| Opportunity Access Level for Account Owner | OpportunityAccessForAccountOwner | picklist | 40 | | |
| Parent Role | ParentRoleId | reference | 15 | | |
| Partner Account | PortalAccountId | reference | 15 | | |
| Portal Type | PortalType | picklist | 40 | | |
| Role ID | Id | id | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| User | PortalAccountOwnerId | reference | 15 | | |

UserProfile

Represents a Chatter user profile.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|----------|--------|-----------|-------|
| About Me | AboutMe | textarea | 1000 | | |
| Active | IsActive | boolean | | | |
| Address | Street | textarea | 255 | | |
| Address | City | string | 40 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------------|------------------|-----------|--------|-----------|-------|
| Address | State | string | 80 | | |
| Address | PostalCode | string | 20 | | |
| Address | Country | string | 80 | | |
| Cell | MobilePhone | phone | 40 | | |
| Company Name | CompanyName | string | 80 | | |
| E-mail | Email | email | 128 | | |
| Fax | Fax | phone | 40 | | |
| Information Currency | CurrencyIsoCode | picklist | 3 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Manager | ManagerId | reference | 15 | | |
| Phone | Phone | phone | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Title | Title | string | 80 | | |
| Url for Thumbnail sized Photo | SmallPhotoUrl | url | 1024 | | |
| Url for full-sized Photo | FullPhotoUrl | url | 1024 | | |
| User ID | Id | id | 15 | | |
| User Photo has a badge overlay | IsBadged | boolean | | | |

UserTeamMember

Represents a single User on the default opportunity team of another User.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Opportunity Access | OpportunityAccessLevel | picklist | 40 | | |
| System Modstamp | SystemModstamp | datetime | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|---------------------|----------------|-----------|--------|-----------|-------|
| Team Role | TeamMemberRole | picklist | 40 | | |
| User | OwnerId | reference | 15 | | |
| User | UserId | reference | 15 | | |
| User Team Member ID | Id | id | 15 | | |

UserTerritory

Represents a User who has been assigned to a Territory.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|------------------|-----------|--------|-----------|-------|
| Active | IsActive | boolean | | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Territory | TerritoryId | reference | 15 | | |
| User | UserId | reference | 15 | | |
| UserTerritory ID | Id | id | 15 | | |

Vote

Represents a vote that a user has made on an Idea or a Reply.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-----------------|----------------|-----------|--------|-----------|-------|
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Deleted | IsDeleted | boolean | | | |
| Parent | ParentId | reference | 15 | | |
| System Modstamp | SystemModstamp | datetime | | | |
| Vote ID | Id | id | 15 | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|-------------|----------------|----------|--------|-----------|-------|
| Vote Type | Type | picklist | 40 | | |

WebLink

Represents a custom link to a URL or Scontrol.

Fields

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------------|---------------------|-----------|--------|-----------|-------|
| Behavior | OpenType | picklist | 40 | | |
| Content Source | LinkType | picklist | 40 | | |
| Created By | CreatedById | reference | 15 | | |
| Created Date | CreatedDate | datetime | | | |
| Custom Link ID | Id | id | 15 | | |
| Custom Object Definition | PageOrSubjectType | picklist | 40 | | |
| Description | Description | textarea | 1000 | | |
| Display Type | DisplayType | picklist | 40 | | |
| Height (in pixels) | Height | int | | 9 | 0 |
| Label | MasterLabel | string | 240 | | |
| Last Modified By | LastModifiedById | reference | 15 | | |
| Last Modified Date | LastModifiedDate | datetime | | | |
| Link Encoding | EncodingKey | picklist | 40 | | |
| Name | Name | string | 240 | | |
| Namespace Prefix | NamespacePrefix | string | 15 | | |
| Protected Component | IsProtected | boolean | | | |
| Require Row Selection | RequireRowSelection | boolean | | | |
| Resizable | IsResizable | boolean | | | |
| Scontrol | ScontrolId | reference | 15 | | |
| Show Address Bar | ShowsLocation | boolean | | | |
| Show Menu Bar | HasMenuBar | boolean | | | |
| Show Scrollbars | HasScrollbars | boolean | | | |
| Show Status Bar | ShowsStatus | boolean | | | |

| Field Label | API Field Name | Type | Length | Precision | Scale |
|--------------------|-----------------------|-------------|---------------|------------------|--------------|
| Show Toolbars | HasToolbar | boolean | | | |
| System Modstamp | SystemModstamp | datetime | | | |
| URL | Url | textarea | 1048576 | | |
| Width (in pixels) | Width | int | | 9 | 0 |
| Window Position | Position | picklist | 40 | | |