
Object Reference for Salesforce and Force.com

Version 34.0, Summer '15



CONTENTS

Chapter 1: Object Basics	1
Primitive Data Types	2
Field Types	3
Compound Fields	9
Address Compound Fields	9
Geolocation Compound Field	11
Compound Field Considerations and Limitations	12
API Data Types and Salesforce Field Types	14
Required Fields	14
System Fields	15
API Field Properties	16
Custom Fields	17
Custom Objects	18
External Objects	21
Relationships Among Objects	22
Factors that Affect Data Access	23
REFERENCE	26
Chapter 2: Standard Objects	26
AcceptedEventRelation	50
Account	52
AccountCleanInfo	71
AccountContactRole	92
AccountFeed	93
AccountHistory	100
AccountOwnerSharingRule	101
AccountPartner	104
AccountShare	106
AccountTag	109
AccountTeamMember	110
AccountTerritoryAssignmentRule	112
AccountTerritoryAssignmentRuleItem	114
AccountTerritorySharingRule	115
ActionLinkGroupTemplate	118
ActionLinkTemplate	121
ActivityHistory	125
AdditionalNumber	133
AgentWork	134

Contents

AllowedEmailDomain	136
Announcement	137
ApexClass	138
ApexComponent	140
ApexLog	143
ApexPage	145
ApexTestQueueItem	148
ApexTestResult	150
ApexTrigger	152
AppMenuItem	156
Approval	160
Article Type__DataCategorySelection	163
Article Type__Feed	164
Asset	170
AssetFeed	173
AssetOwnerSharingRule	179
AssetShare	181
AssetTag	183
AssignmentRule	184
AsyncApexJob	185
AttachedContentDocument	188
Attachment	190
AuraDefinition	194
AuraDefinitionBundle	195
AuthConfig	197
AuthConfigProviders	199
AuthProvider	200
AuthSession	205
Bookmark	208
BrandTemplate	209
BusinessHours	212
BusinessProcess	215
CallCenter	217
Campaign	219
CampaignFeed	227
CampaignMember	234
CampaignMemberStatus	237
CampaignOwnerSharingRule	238
CampaignShare	240
CampaignTag	242
Case	243
CaseArticle	252
CaseComment	253
CaseContactRole	256

Contents

CaseFeed	257
CaseHistory	263
CaseMilestone	265
CaseOwnerSharingRule	268
CaseShare	270
CaseSolution	271
CaseStatus	272
CaseTag	274
CaseTeamMember	275
CaseTeamRole	276
CaseTeamTemplate	277
CaseTeamTemplateMember	277
CaseTeamTemplateRecord	278
CategoryData	279
CategoryNode	280
CategoryNodeLocalization	281
ChatterActivity	286
ChatterAnswersActivity	288
ChatterAnswersReputationLevel	292
ChatterConversation	293
ChatterConversationMember	294
ChatterMessage	294
ClientBrowser	296
CollaborationGroup	297
CollaborationGroupFeed	302
CollaborationGroupMember	309
CollaborationGroupMemberRequest	311
CollaborationGroupRecord	312
CollaborationInvitation	313
CombinedAttachment	316
Community (Zone)	318
ConnectedApplication	319
Contact	322
ContactCleanInfo	333
ContactFeed	342
ContactHistory	348
ContactOwnerSharingRule	349
ContactShare	351
ContactTag	353
ContentDistribution	354
ContentDistributionView	359
ContentDocument	360
ContentDocumentFeed	365
ContentDocumentHistory	372

Contents

ContentDocumentLink	373
ContentFolder	376
ContentFolderLink	376
ContentFolderMember	377
ContentHubItem	378
ContentHubRepository	381
ContentNote	383
ContentVersion	385
ContentVersionHistory	395
ContentWorkspace	397
ContentWorkspaceDoc	399
Contract	401
ContractContactRole	409
ContractFeed	411
ContractHistory	417
ContractLineItem	418
ContractLineItemHistory	422
ContractStatus	424
ContractTag	425
CronJobDetail	426
CronTrigger	427
CurrencyType	430
CustomBrand	432
CustomBrandAsset	432
Custom Metadata Type__mdt	435
Custom Object__Feed	437
CustomPermission	443
CustomPermissionDependency	445
DandBCompany	447
Dashboard	465
DashboardComponent	470
DashboardComponentFeed	470
DashboardFeed	477
DashboardTag	483
DatacloudCompany	484
DatacloudContact	492
DatacloudDandBCompany	496
DatacloudOwnedEntity	516
DatacloudPurchaseUsage	517
DatacloudSocialHandle	519
DatedConversionRate	520
DcSocialProfile	522
DcSocialProfileHandle	524
DeclinedEventRelation	525

Contents

Division	526
DivisionLocalization	527
Document	529
DocumentAttachmentMap	533
DocumentTag	535
Domain	536
DomainSite	537
DuplicateRecordItem	538
DuplicateRecordSet	539
DuplicateRule	541
EmailDomainKey	543
EmailMessage	545
EmailServicesAddress	549
EmailServicesFunction	551
EmailStatus	556
EmailTemplate	557
Entitlement	562
EntitlementContact	565
EntitlementFeed	566
EntitlementHistory	572
EntitlementTemplate	574
EntityHistory	576
EntitySubscription	577
EnvironmentHubMember	579
Event	583
EventFeed	596
EventLogFile	602
EventRelation	679
EventTag	683
EventWhoRelation	685
ExternalDataSource	686
ExternalDataUserAuth	688
FeedComment	689
FeedItem	693
FeedLike	702
FeedPollChoice	703
FeedPollVote	704
FeedPost	705
FeedRevision	709
FeedTrackedChange	710
FieldHistoryArchive	713
FieldPermissions	716
FiscalYearSettings	719
FlowInterview	722

Contents

Folder	723
ForecastingAdjustment	726
ForecastingFact	730
ForecastingItem	732
ForecastingOwnerAdjustment	738
ForecastingQuota	742
ForecastingType	744
ForecastShare	746
Goal	748
GoalFeed	750
GoalHistory	755
GoalLink	756
GoalShare	757
GoogleDoc	758
Group	759
GroupMember	762
HashtagDefinition	763
Holiday	764
Idea	768
IdeaComment	774
IdeaReputation	776
IdeaReputationLevel	778
IdeaTheme	779
KnowledgeableUser	781
KnowledgeArticle	782
KnowledgeArticleVersion	784
KnowledgeArticleVersionHistory	791
KnowledgeArticleViewStat	794
KnowledgeArticleVoteStat	795
Lead	797
LeadCleanInfo	813
LeadFeed	827
LeadHistory	833
LeadOwnerSharingRule	835
LeadShare	836
LeadStatus	838
LeadTag	839
LimitAllocationPerApp	841
LineitemOverride	843
ListView	845
ListViewChart	847
ListViewChartInstance	849
LiveAgentSession	853
LiveAgentSessionHistory	856

Contents

LiveAgentSessionOwnerSharingRule	857
LiveAgentSessionShare	859
LiveChatBlockingRule	860
LiveChatButton	862
LiveChatButtonDeployment	870
LiveChatButtonSkill	871
LiveChatDeployment	872
LiveChatTranscript	874
LiveChatTranscriptEvent	881
LiveChatTranscriptHistory	883
LiveChatTranscriptOwnerSharingRule	884
LiveChatTranscriptShare	886
LiveChatTranscriptSkill	887
LiveChatUserConfig	888
LiveChatUserConfigProfile	894
LiveChatUserConfigUser	895
LiveChatVisitor	896
LoginGeo	897
LoginHistory	899
LoginIp	903
LookedUpFromActivity	904
MailmergeTemplate	910
Metric	912
MetricDataLink	916
MetricDataLinkHistory	917
MetricFeed	918
MetricHistory	922
MetricsDataFile	923
MetricShare	926
MilestoneType	927
Name	928
NamedCredential	932
Network	934
NetworkActivityAudit	940
NetworkMember	943
NetworkMemberGroup	948
NetworkModeration	949
NetworkPageOverride	951
NetworkSelfRegistration	952
NewsFeed	953
Note	959
OauthToken	961
NoteAndAttachment	963
NoteTag	965

Contents

ObjectPermissions	966
ObjectTerritory2AssignmentRule	969
ObjectTerritory2AssignmentRuleItem	971
ObjectTerritory2Association	973
OpenActivity	974
Opportunity	981
OpportunityCompetitor	991
OpportunityContactRole	992
OpportunityFeed	993
OpportunityFieldHistory	1000
OpportunityHistory	1001
OpportunityLineItem	1003
OpportunityLineItemSchedule	1010
OpportunityOverride	1013
OpportunityOwnerSharingRule	1016
OpportunityPartner	1018
OpportunityShare	1020
OpportunitySplit	1021
OpportunitySplitType	1023
OpportunityStage	1025
OpportunityTag	1028
OpportunityTeamMember	1029
Order	1031
OrderFeed	1041
OrderHistory	1046
OrderItem	1048
OrderItemFeed	1050
OrderItemHistory	1056
OrderOwnerSharingRule	1057
Organization	1060
OrgWideEmailAddress	1078
OwnedContentDocument	1079
PackageLicense	1081
Partner	1083
PartnerNetworkConnection	1086
PartnerNetworkRecordConnection	1088
PartnerNetworkSyncLog	1092
PartnerRole	1093
Period	1095
PermissionSet	1096
PermissionSetAssignment	1102
PermissionSetLicense	1103
PermissionSetLicenseAssign	1106
PlatformAction	1107

Contents

PresenceUserConfig	1112
PresenceUserConfigProfile	1114
PresenceUserConfigUser	1115
Pricebook2	1115
Pricebook2History	1119
PricebookEntry	1120
ProcessDefinition	1123
ProcessInstance	1125
ProcessInstanceHistory	1127
ProcessInstanceStep	1130
ProcessInstanceNode	1132
ProcessInstanceWorkitem	1134
ProcessNode	1136
Product2	1138
Product2Feed	1143
ProductEntitlementTemplate	1150
Profile	1150
ProfileSkill	1153
ProfileSkillEndorsement	1155
ProfileSkillEndorsementFeed	1156
ProfileSkillEndorsementHistory	1160
ProfileSkillFeed	1161
ProfileSkillHistory	1165
ProfileSkillShare	1166
ProfileSkillUser	1168
ProfileSkillUserFeed	1169
ProfileSkillUserHistory	1173
PushTopic	1174
QuantityForecast	1176
QuantityForecastHistory	1183
QueueRoutingConfig	1186
Question	1188
QuestionDataCategorySelection	1193
QuestionReportAbuse	1195
QuestionSubscription	1195
QueueSubject	1197
QuickText	1198
QuickTextHistory	1200
QuickTextOwnerSharingRule	1201
QuickTextShare	1203
Quote	1204
QuoteDocument	1217
QuoteLineItem	1218
RecentlyViewed	1222

Contents

RecordType	1226
RecordTypeLocalization	1229
Reply	1230
ReplyReportAbuse	1233
Report	1234
ReportFeed	1237
ReportTag	1243
ReputationLevel	1244
ReputationPointsRule	1246
RevenueForecast	1247
RevenueForecastHistory	1255
RuleTerritory2Association	1258
SamlSsoConfig	1259
Scontrol	1264
ScontrolLocalization	1267
SearchPromotionRule	1272
SelfServiceUser	1273
ServiceChannel	1276
ServiceChannelStatus	1278
ServiceContract	1279
ServiceContractFeed	1286
ServiceContractHistory	1293
ServiceContractOwnerSharingRule	1294
ServiceContractShare	1296
ServicePresenceStatus	1297
SetupEntityAccess	1298
SignupRequest	1300
Site	1307
SiteDomain	1312
SiteHistory	1313
Skill	1314
SkillProfile	1315
SkillUser	1316
SlaProcess	1317
Solution	1320
SolutionFeed	1323
SolutionHistory	1330
SolutionStatus	1331
SolutionTag	1333
SOSDeployment	1334
SOSSession	1336
SOSSessionActivity	1339
SOSSessionHistory	1340
SOSSessionOwnerSharingRule	1341

Contents

SOSSessionShare	1343
StaticResource	1344
StreamingChannel	1347
TagDefinition	1348
Task	1350
TaskFeed	1361
TaskPriority	1367
TaskRelation	1369
TaskStatus	1371
TaskTag	1372
TaskWhoRelation	1373
TenantSecret	1375
Territory	1377
Territory2	1379
Territory2Model	1382
Territory2ModelHistory	1384
Territory2Type	1385
ThirdPartyAccountLink	1387
Topic	1389
TopicAssignment	1390
TopicFeed	1392
TopicLocalization—Beta	1398
TwoFactorInfo	1403
UndecidedEventRelation	1404
User	1405
UserAccountTeamMember	1443
UserConfigTransferButton	1446
UserConfigTransferSkill	1447
UserFeed	1447
UserLicense	1454
UserLogin	1457
UserMembershipSharingRule	1458
UserPackageLicense	1460
UserPreference	1461
UserProfile	1462
UserProfileFeed	1480
UserProvAccount	1487
UserProvAccountStaging	1490
UserProvMockTarget	1493
UserProvisioningConfig	1495
UserProvisioningLog	1498
UserProvisioningRequest	1500
UserProvisioningRequestOwnerSharingRule	1505
UserProvisioningRequestShare	1506

Contents

UserRecordAccess	1508
UserRole	1510
UserServicePresence	1514
UserShare	1515
UserTeamMember	1516
UserTerritory	1518
UserTerritory2Association	1519
Vote	1520
WebLink	1522
WebLinkLocalization	1527
WorkAccess	1532
WorkAccessShare	1533
WorkBadge	1534
WorkBadgeDefinition	1536
WorkBadgeDefinitionHistory	1540
WorkBadgeDefinitionShare	1541
WorkCoaching	1542
WorkCoachingFeed	1544
WorkCoachingHistory	1549
WorkCoachingShare	1550
WorkFeedback	1551
WorkFeedbackHistory	1553
WorkFeedbackQuestion	1554
WorkFeedbackQuestionHistory	1556
WorkFeedbackQuestionSet	1557
WorkFeedbackQuestionSetHistory	1558
WorkFeedbackQuestionSetShare	1559
WorkFeedbackQuestionShare	1561
WorkFeedbackRequest	1562
WorkFeedbackRequestFeed	1568
WorkFeedbackRequestHistory	1572
WorkFeedbackRequestShare	1573
WorkFeedbackShare	1574
WorkFeedbackTemplate	1576
WorkFeedbackTemplateShare	1576
WorkGoal	1576
WorkGoalCollaborator	1582
WorkGoalCollaboratorHistory	1583
WorkGoalFeed	1584
WorkGoalHistory	1589
WorkGoalLink	1590
WorkGoalShare	1591
WorkPerformanceCycle	1593
WorkPerformanceCycleFeed	1595

Contents

WorkPerformanceCycleHistory	1600
WorkPerformanceCycleShare	1601
WorkReward	1602
WorkRewardFund	1604
WorkRewardFundHistory	1607
WorkRewardFundShare	1608
WorkRewardFundType	1609
WorkRewardFundTypeHistory	1611
WorkRewardFundTypeShare	1612
WorkRewardHistory	1614
WorkRewardShare	1615
WorkThanks	1616
WorkThanksShare	1617
Chapter 3: Data Model	1619
Sales Objects	1620
Task and Event Objects	1621
Support Objects	1622
Document, Note, and Attachment Objects	1622
User, Sharing, and Permission Objects	1623
Profile and Permission Objects	1624
Record Type Objects	1625
Product and Schedule Objects	1626
Sharing and Team Selling Objects	1627
Customizable Forecasting Objects	1627
Forecasts Objects	1628
Territory Management 2.0 Objects	1628
Territory Management	1630
Process Objects	1631
Content Objects	1632
Chatter Objects	1632
Chatter Feed Objects	1634
Salesforce Knowledge Objects	1635
Work.com Badge and Reward Objects	1636
INDEX	1637

CHAPTER 1 Object Basics

In this chapter ...

- [Primitive Data Types](#)
- [Field Types](#)
- [Compound Fields](#)
- [API Data Types and Salesforce Field Types](#)
- [Required Fields](#)
- [System Fields](#)
- [API Field Properties](#)
- [Custom Fields](#)
- [Custom Objects](#)
- [External Objects](#)
- [Relationships Among Objects](#)
- [Factors that Affect Data Access](#)

Generally speaking, API objects represent database tables that contain your organization's information. For example, the central object in the Salesforce data model represents accounts—companies and organizations involved with your business, such as customers, partners, and competitors. The term “record” describes a particular occurrence of an object (such as a specific account like “IBM” or “United Airlines” that is represented by an Account object). A record is analogous to a row in a database table.

Objects already created for you by Salesforce are called standard objects. Objects you create in your organization are called custom objects. Objects you create that map to data stored outside your organization are called external objects.

While this document describes all of the objects available in the API, your applications work with only the objects that you are authorized to access. Programmatic access to objects is determined by the objects defined in your organization, your organization configuration, your user permissions and access settings (which are configured by your organization's system administrator), your data sharing model, and other factors related specifically to the object.

Most of the objects accessible through the API are read-write objects. However, there are a few objects that are read-only. This fact is noted in the description for the object.



Note: The objects Pricebook and Product are no longer available, and have been removed from this document.

Primitive Data Types

The API uses the following primitive data types:

Value	Details
base64	Base 64-encoded binary data. Fields of this type are used for storing binary files in Attachment records, Document records, and Scontrol records. In these objects, the <code>Body</code> or <code>Binary</code> field contains the (base64 encoded) data, while the <code>BodyLength</code> field defines the length of the data in the <code>Body</code> or <code>Binary</code> field. In the Document object, you can specify a URL to the document instead of storing the document directly in the record.
boolean	Boolean fields have one of these values: <code>true</code> (or 1), or <code>false</code> (or 0).
byte	A set of bits.
date	Date data. Fields of this type contain date values, such as <code>ActivityDate</code> in the Event object. Unlike <code>dateTime</code> fields, date fields contain no time value—the time portion of a date field is not relevant and is always set to midnight in the Coordinated Universal Time (UTC) time zone. If you specify a date value in a query, you can filter on date fields only.
dateTime	Date/time values (timestamps). Fields of this type handle date/time values (timestamps), such as <code>ActivityDateTime</code> in the Event object or the <code>CreatedDate</code>, <code>LastModifiedDate</code>, or <code>SystemModstamp</code> in many objects. Regular <code>dateTime</code> fields are full timestamps with a precision of one second. They are always transferred in the Coordinated Universal Time (UTC) time zone. In your client application, you might need to translate the timestamp to or from a local time zone. If you specify a <code>dateTime</code> value in a query, you can filter on <code>dateTime</code> fields only. Development tools differ in the way that they handle time data. Some development tools report the local time, while others report only the Coordinated Universal Time (UTC) time zone. To determine how your development tool handles time values, refer to its documentation.  Note: The Event object has a <code>DurationInMinutes</code> field that specifies the number of minutes for an event. Even though this is a temporal value, it is an integer type—not a <code>dateTime</code> type.
double	Double values. Fields of this type can contain fractional portions (digits to the right of the decimal place), such as <code>ConversionRate</code> in <code>CurrencyType</code>. In the API, all non-integer values (such as Currency Field Type and Percent Field Type) contain values of type double. Some restrictions may be applied to double values: • <code>scale</code>: Maximum number of digits to the right of the decimal place. • <code>precision</code>: Total number of digits, including those to the left and the right of the decimal place The maximum number of digits to the left of the decimal place is equal to <code>precision</code> minus <code>scale</code>. In the online application, <code>precision</code> is defined differently—it is the maximum number of digits allowed to the left of the decimal place. Values can be stored in scientific notation if the number is large enough (or, for negative numbers, small enough), as indicated by the W3C XML Schema Part 2: Datatypes Second Edition specification.  Warning: When the user sets the precision in custom fields in the Salesforce application, it displays the precision set by the user, even if the user enters a more precise value than defined for those

Value	Details
	fields. However, when you set the precision in custom fields using the API, no rounding occurs when the user retrieves the number field.
int	Fields of this type contain numbers with no fractional portion (digits to the right of a decimal place), such as the <code>NumberOfEmployees</code> in an <code>Account</code> . For integer fields, the <code>digits</code> field specifies the maximum number of digits that an integer can have.
string	Character strings. Fields that are of data type <code>string</code> contain text and some have length restrictions depending on the data being stored. For example, in the <code>Contact</code> object, the <code>FirstName</code> field is 40 characters, the <code>LastName</code> field is 80 characters, the <code>MailingStreet</code> is 255 characters.  Note: For fields that contain strings, behavior is different beginning with API version 15.0. In API versions previous to 15.0, if you specify a value for a field, and that value is too large, the value is truncated. For API version 15.0 and later, if a value is specified that is too large, the operation fails and the fault code <code>STRING_TOO_LONG</code> is returned. <code>AllowFieldTruncationHeader</code> allows you to specify that the previous behavior, truncation, be used instead of the new behavior in API versions 15.0 and later. This header has no effect in versions 14.0 and earlier. The affected fields are: <code>anyType</code>, <code>email</code>, <code>encryptedstring</code>, <code>multipicklist</code>, <code>phone</code>, <code>picklist</code>, <code>string</code>, and <code>textarea</code>.
time	Time values. Fields of this type handle time values, such as <code>FridayEndTime</code> in the <code>BusinessHours</code> object. Development tools differ in the way that they handle time data. Some development tools report the local time, while others report only the Coordinated Universal Time (UTC) time zone. To determine how your development tool handles time values, refer to its documentation.

These data types are used in the SOAP messages that are exchanged between your client application and the API. When writing your client application, follow the data typing rules defined for your programming language and development environment. Your development tool handles the mapping of typed data in your programming language with these SOAP data types.

The primitive data types are:

- specified in the World Wide Web Consortium's publication *XML Schema Part 2: Data Types* at the following URL: <http://www.w3.org/TR/xmlschema-2/>.
- enumerated in the `SOAPType` field of the Field type, which is described in the `fields` property of the `DescribeObjectResult`.

Primitive types are used as a standardized way to define, send, receive, and interpret basic data types in the SOAP messages exchanged between client applications and the API. In addition, primitive data types are interpreted in a Salesforce-specific way, which is useful for display formatting and for numeric conversion (adding values of different currencies).

For example, Salesforce chooses to interpret a double value passed via SOAP as a `double` in a number of possible ways, depending on the field definition. If the field type for that data is currency, Salesforce handles the display of the data by prepending it with a currency symbol and inserting a decimal for precision. Similarly, if the field type is percent, Salesforce handles the display of the data by appending a percent sign (%). Regardless of the field type, however, the value is sent in the SOAP message as a double.

The API uses data types called field types that are defined in the WSDLs. For more information, see [Field Types](#).

Field Types

In addition to the primitive data types, the API defines the following data types for fields:

 **Note:** For fields that contain strings, behavior is different beginning with API version 15.0. In API versions previous to 15.0, if you specify a value for a field, and that value is too large, the value is truncated. For API version 15.0 and later, if a value is specified that is too large, the operation fails and the fault code `STRING_TOO_LONG` is returned. `AllowFieldTruncationHeader` allows you to specify that the previous behavior, truncation, be used instead of the new behavior in API versions 15.0 and later. This header has no effect in versions 14.0 and earlier. The affected fields are: `anyType`, `email`, `encryptedstring`, `multipicklist`, `phone`, `picklist`, `string`, and `textarea`.

Field Type	What the Field Contains
address	A compound data type that contains address field data. See Address Compound Fields .
anyType	Polymorphic data type that returns string, picklist, reference, Boolean, currency, int, double, percent, ID, date, datetime, url, or email data depending on the kind of field involved. See AnyType Field Type .
calculated	Fields that are defined by a formula. See Calculated Field Type .
combobox	A combobox, which includes a set of enumerated values and allows the user to specify a value not in the list. See ComboBox Field Type .
currency	Currency values. See Currency Field Type .
DataCategoryGroupReference	Reference to a data category group or a category unique name. See DataCategoryGroupReference Field Type .
email	Email addresses. See Email Field Type .
encryptedstring	Encrypted text fields contain any combination of letters, numbers, or symbols that are stored in encrypted form. You can set a maximum length of up to 175 characters. Available in API versions 11.0 and later.
ID	Primary key field for the object. See ID Field Type. Note that most Web services tools, including .NET and WSC, map the ID simple type defined in the API WSDL (Enterprise or Partner) to a string. However, other tools generate a specific ID class to represent the ID simple type. Please consult your Web services toolkit documentation for more information.
JunctionIdList	A string array of referenced ID values that represent the many-to-many relationship of an underlying junction entity. Query and manipulate the string array to query and manipulate the underlying junction entities in a single API call. See: JunctionIdList Field Type  Warning: Adding a <code>JunctionIdList</code> field name to the <code>fieldsToNull</code> property deletes all related junction records. This action can't be undone.
location	A compound data type that contains latitude and longitude values for geolocation fields. See Geolocation Compound Field .
masterrecord	When records are merged, the ID of the record that is saved (the other records are deleted).
multipicklist	Multi-select picklists, which include a set of enumerated values from which multiple values can be selected. See Multi-Select Picklist Field Type .
percent	Percentage values. See Percent Field Type .

Field Type	What the Field Contains
phone	Phone numbers. Values can include alphabetic characters. Client applications are responsible for phone number formatting. See Phone Field Type .
picklist	Picklists, which include a set of enumerated values from which one value can be selected. See Picklist Field Type .
reference	Cross-references to a different object. Analogous to a foreign key field in SQL. See Reference Field Type .
textarea	String that is displayed as a multiline text field. See Textarea Field Type .
url	URL values. Client applications should commonly display these as hyperlinks. See URL Field Type .

These field types extend [primitive data types](#). While many of these field types follow common data typing conventions that are made explicit in their metadata, certain field types have unique characteristics that you need to understand before using them in your client application.

These field types apply to both standard and custom fields. They are enumerated in the `type` field of the `Field` type, which is described in the `fields` property of the `DescribeObjectResult`.



Note: Some numeric fields have precision and scale limits. In addition, certain text fields have length restrictions. These restrictions are enforced when you `create()` or `update()` objects. However, the API may return data that does not meet these restrictions.

AnyType Field Type

The `anyType` field type is dynamic and returns `string`, `date`, `number`, or `boolean` data depending on the kind of field involved. For example, the element in a SOAP message has an `xsi:type="xsd:string"` attribute if the field is of type `string`. This field type is used in history objects for the `NewValue` and `OldValue` fields. It is also a valid field type for `fieldType` and `soapType`.



Note: Most SOAP toolkits automatically deserialize this element into the correct native type.

Calculated Field Type

Calculated fields are read-only fields in the API. These are fields defined by a formula, which is an algorithm that derives its value from other fields, expressions, or values. You can filter on these fields in SOQL, but you should not replicate these fields. The length of text calculated fields is 3900 characters or less—anything longer will be truncated.

Calculated fields are called formula fields in the Salesforce user interface.

ComboBox Field Type

A combobox is a picklist that also allows users to type a value that is not already specified in the list. A combobox is defined as a string value.

Currency Field Type

Currency fields contain currency values, such as the `ExpectedRevenue` field in a Campaign, and are defined as type `double`.

For organizations that have the multicurrency option enabled, the `CurrencyIsoCode` field is defined for any object that can have currency fields. The `CurrencyIsoCode` field and currency fields are linked in a special way. On any specific record, the `CurrencyIsoCode` field defines the currency of that record, and thus, the values of all currency fields on that record will be expressed in that currency.

For most cases, clients do not need to consider the linking of the `CurrencyIsoCode` field and the currency fields on an object. However, clients may need to consider the following:

- The `CurrencyIsoCode` field exists only for those organizations that have enabled multicurrency support.
- When displaying the currency values in a user interface, it is preferred to prepend each currency value with its `CurrencyIsoCode` value and a space separator.
- The `CurrencyIsoCode` field is a restricted picklist field. The set of allowable values, defined in the `CurrencyType` object, can vary from organization to organization. Attempting to set it to a value that is not defined for an organization causes the operation to be rejected.
- If you update the `CurrencyIsoCode` field on an object, it implicitly converts all currency values on that object to the new currency code, using the conversion rates that are defined for that organization in the Salesforce user interface. If you specify currency values in that same `update()` call, the new currency values you specify are interpreted in the new `CurrencyIsoCode` field value, without conversion.
- The picklist values in a `CurrencyIsoCode` field do not exactly match the labels displayed in Salesforce.

To perform currency conversions, client applications can look up the `CurrencyIsoCode` in the `CurrencyType` object.

DataCategoryGroupReference Field Type

A data category group has categories that classify articles in Salesforce Knowledge and questions in the Answers feature. Every article and question object has two fields of type `DataCategoryGroupReference` which contain the category group and category unique name. You can use the `describeDataCategoryGroups()` and `describeDataCategoryGroupStructures()` calls to retrieve the category groups and categories associated to these objects.

Email Field Type

Email fields contain email addresses. Client applications are responsible for specifying valid and properly formatted email addresses in `create()` and `update()` calls.

ID Field Type

With rare exceptions, all objects in the API have a field of type ID that is named `Id` and contains a unique identifier for each record in the object. It is analogous to a primary key in relational databases. When you `create()` a new record, the Web service generates an ID value for the record, ensuring that it is unique within your organization's data. You cannot use the `update()` call on ID fields. Because the ID value stays constant over the lifetime of the record, you can refer to the record by its ID value in subsequent API calls. Also, the ID value contains a three-character code that identifies the object type, which client applications can retrieve via the `describeSObjects()` call.

In addition, certain objects, including custom objects, have one or more fields of type `reference` that contain the ID value for a related record. These fields have names that end in the suffix "-Id", for example, `OwnerId` in the account object. `OwnerId` contains the ID of the user who owns that object. Unlike the field named `Id`, `reference` fields are analogous to foreign keys and can be changed via the `update()` call. For more information, see [Reference Field Type](#).

Some API calls, such as `retrieve()` and `delete()`, accept an array of IDs as parameters—each array element uniquely identifies the row to retrieve or delete. Similarly, the `update()` call accepts an array of sObject records—each sObject contains an `Id` field that uniquely identifies the sObject.

ID fields in the Salesforce user interface contain 15-character, base-62, case-sensitive strings. Each of the 15 characters can be a numeric digit (0-9), a lowercase letter (a-z), or an uppercase letter (A-Z). Two unique IDs may only be different by a change in case.

Because there are applications like Access which do not recognize that 50130000000014c is a different ID from 50130000000014C, an 18-digit, case-safe version of the ID is returned by all API calls. The 18 character IDs have been formed by adding a suffix to each ID in the Force.com API. 18-character IDs can be safely compared for uniqueness by case-insensitive applications, and can be used in all API calls when creating, editing, or deleting data.

If you need to convert the 18-character ID to a 15-character version, truncate the last three characters. Salesforce recommends that you use the 18-character ID.



Note: Most Web services tools, including .NET and WSC, map the ID simple type defined in the API WSDL (Enterprise or Partner) to a string. However, other tools generate a specific ID class to represent the ID simple type. Please consult your web services toolkit documentation for more information.

JunctionIdList Field Type

Starting in API version 34.0, the `JunctionIdList` field type lets you manipulate the many-to-many relationship of an entity directly. You no longer need to manipulate underlying junction entity records. `JunctionIdList` fields can be queried and updated like any other field on the entity. Queries or updates to `JunctionIdList` fields act as queries or updates to the underlying junction entity records. Fields of type `JunctionIdList` appear in the WSDL as an unbounded array of type ID.

Multi-Select Picklist Field Type

Multi-select picklist fields contain a list of one or more items from which a user can choose multiple items. One of the items can be configured as the default item. Selections are maintained as a string containing a series of attributes delimited by semicolons. For example, a query might return the values of a multivalue picklist as “first value; second value; third value”. For information on querying multi-select picklists, see [Querying Multi-Select Picklists in the Salesforce SOQL and SOSL Reference Guide](#).

Percent Field Type

Percent fields contain percent values. Percent fields are defined as type double.

Phone Field Type

Phone fields contain phone numbers, which can include alphabetic characters. Client applications are responsible for phone number formatting.

Picklist Field Type

Picklist fields contain a list of one or more items from which a user chooses a single item. They display as drop-down lists in the Salesforce user interface. One of the items can be configured as the default item.

In the Field object associated with the DescribeObjectResult, the `restrictedPicklist` field defines whether the field is a restricted picklist or not. The API does not enforce the list of values for advisory (unrestricted) picklist fields on `create()` or `update()`. When inserting an unrestricted picklist field that does not have a PicklistEntry, the system creates an “inactive” picklist value. This value can be promoted to an “active” picklist value by adding the picklist value in the Salesforce user interface.

When creating new, inactive picklists, the API checks to see if there is a match. This check is case-insensitive.

In the `Field` object associated with the `DescribeObjectResult`, the `picklistValues` field contains an array of items (`PicklistEntry` objects). Each `PicklistEntry` defines the item's label, value, and whether it is the default item in the picklist (a picklist has no more than one default value).

Enumerated fields support localization of the labels to the language of the user. For example, for the `Industry` field on an `Account`, the value "Agriculture" may be translated to various languages. The enumerated field values are fixed and do not change with a user's language. However, each value may have a specified "label" field that provides the localized label for that value. You must always use the value when inserting or updating a field. The `query()` call always returns the value, not the label. The corresponding label for a value in the `DescribeObjectResult` should be used when displaying the value to the user in any user interface.

The API supports the retrieval of the certain picklists in the following objects: `CaseStatus`, `ContractStatus`, `LeadStatus`, `OpportunityStage`, `PartnerRole`, `SolutionStatus`, `TaskPriority`, and `TaskStatus`. Each object represents a value in the respective picklist. These picklist entries always specify some other piece of information, such as whether the status is converted, and so on. Your client application can invoke the `query()` call on any of these objects (such as `CaseStatus`) to retrieve the set of values in the picklist, and then use that information while processing other objects (such as `Case` objects) to find more information about those objects (such as a given case). These objects are read-only via the API. To modify items in picklists, you must use the Salesforce user interface.

Reference Field Type

A reference field contains an `Id` value that points to a unique record (usually the parent record) on another object. This is analogous to the concept of a foreign key in relational databases. The name of a reference field ends, by convention, with the letters `Id` (such as `CaseId` or `OpportunityId`). For example, in the `OpportunityCompetitor` object, the `OpportunityId` field is a reference field that points to the `Opportunity` object. It contains an ID value that uniquely identifies an `Opportunity` record.

In some cases, an object can refer to another object of its same type. For example, an `Account` can have a parent link that points to another `Account`.

The `Event` and `Task` objects both have `whoId` and `whatId` cross-reference ID fields. Each of these cross-reference fields can point to one of several other objects. The `whoId` field can point to a `Contact` or `Lead`, and the `whatId` field can point to an `Account`, `Opportunity`, `Campaign`, or `Case`. In addition, if the `whoId` field refers to a `Lead`, then the `whatId` field must be empty.

You can describe and query each cross-referenced object. When you query a cross-reference ID field, it returns an object ID of the appropriate type. You can then query that ID to get additional information about the object, using the ID in the `id` field for that query.

The cross-reference ID field value is either:

- a valid record in your organization, or
- an empty value, which indicates an empty reference

The cross-reference ID field value, if non-`null`, is guaranteed to be an object in your organization. However, it is not guaranteed that you can query that object. Users with the "View All Data" permission can always query that object. Other users may be restricted from viewing or editing the referenced object.

When specifying a value for a cross-reference ID field in a `create()` or `update()` call, the value must be a valid value of type ID, and the user must have appropriate access to that object. The exact requirements vary from field to field.

Textarea Field Type

Textarea fields contain text that can be longer than 4000 bytes. Unlike string fields, textarea fields cannot be specified in the `WHERE` clause of a `queryString` of a `query()` call. To filter records on this field, you must do so while processing records in the `QueryResult`. For fields with this restriction, its `filterable` field in the `Field` type (described in the `fields` property of the `DescribeObjectResult`) is `false`.

URL Field Type

URL fields contain URLs. Client applications are responsible for specifying valid and properly formatted URLs in `create()` and `update()` calls.

Compound Fields

Compound fields group together multiple elements of primitive data types, such as numbers or strings, to represent complex data types, such as a location or an address. Compound fields are an abstraction that can simplify application code that handles the values, leading to more concise, understandable code.

Address compound fields are available in the SOAP and REST APIs in API version 30.0 and later. Geolocation fields are available in the SOAP and REST APIs in API version 26.0 and later, with some limitations on SOAP for API versions below 30.0.

Compound fields are accessible as a single, structured field, or as individual component fields. The values contained within the compound field and the values in individual fields both map to the same underlying data stored in Salesforce; they always have identical values. Code that references individual component fields is unaffected by the new compound fields.

Compound fields are read-only. Changes are performed by writing to the individual component fields. This maintains a single, consistent method for performing updates, and avoids the possibility of conflicts. For example, if both the `BillingAddress` compound field and `BillingCity` individual component field were updated in the same API call, it would be unclear which value should be saved.

Compound fields are available only through the SOAP and REST APIs. Compound fields are described in both the Enterprise and Partner WSDLs. Update your WSDL to at least API 30.0 to access the new compound data types.

Address Compound Fields

Standard addresses—addresses built into standard objects in Salesforce—are accessible in the SOAP and REST APIs as an `Address`, a structured compound data type, as well as individual address elements.

Using API 30.0 and later, standard addresses are available in the SOAP and REST APIs as a compound field of type `Address`, a structured data type that combines the following fields.

- `City`
- `Country`
- `CountryCode`
- `Latitude`
- `Longitude`
- `PostalCode`
- `State`
- `StateCode`
- `Street`



Note: `StateCode` and `CountryCode` are always available on compound address fields, whether or not state and country picklists are enabled in your organization.

The `Address` type extends the `Location` type, the data type used for compound geolocation fields.

Address fields are provided on many standard objects, such as `Account`, `Contact`, `Quote`, and `User`. Some objects provide fields for multiple addresses. For example, `Account` provides for four different addresses. In this case, address field names are prefixed with the type of address, for example, `BillingCity`, `BillingState`, and so on.

 **Note:** Standard address compound fields are read-only, and are only accessible using the SOAP and REST APIs. See [Compound Field Considerations and Limitations](#) on page 12 for additional details of the restrictions this imposes.

Retrieving Compound Address Fields

Using compound fields can simplify code that works with addresses, especially for SOQL queries. SOQL `SELECT` clauses can reference addresses directly, instead of all of the individual component fields.

```
SELECT Name, BillingAddress
FROM Account
```

To write code that's compatible with API versions before 30.0, as well as API 30.0 and above, use the individual fields:

```
SELECT Name, BillingStreet, BillingCity, BillingState, BillingPostalCode,
       BillingCountry, BillingLatitude, BillingLongitude
FROM Account
```

Compound address field values are returned as a structured data type, `Address`. Code that works with compound address fields needs to reference the individual components of the returned value. See the code sample below.

Example: Retrieve a Standard Address Compound Field with the SOAP API

The following Java method uses the Salesforce SOAP API to retrieve and display the Mailing Address for a list of contacts.

```
// Modified version of code in the SOAP API QuickStart
private void querySample() {
    String soqlQuery = "SELECT FirstName, LastName, MailingAddress FROM Contact";
    try {
        QueryResult qr = connection.query(soqlQuery);
        boolean done = false;

        if (qr.getSize() > 0) {
            System.out.println("\nLogged-in user can see "
                               + qr.getRecords().length + " contact records.");

            while (!done) {
                System.out.println("");
                Object[] records = qr.getRecords();
                for (int i = 0; i < records.length; ++i) {
                    Contact con = (Contact) records[i];
                    String fName = con.getFirstName();
                    String lName = con.getLastName();

                    // Access the compound address field MailingAddress
                    Address addr = (Address) con.getMailingAddress();
                    String streetAddr = "";
                    if (null != addr) streetAddr = addr.getStreet();

                    if (fName == null) {
                        System.out.println("Contact " + (i + 1) + ": " + lName +
                                           " -- " + streetAddr);
                    } else {
                        System.out.println("Contact " + (i + 1) + ": " + fName +
                                           " " + lName +
                                           " -- " + streetAddr);
                    }
                }
            }
        }
    }
}
```

```

        }
    }

    if (qr.isDone()) {
        done = true;
    } else {
        qr = connection.queryMore(qr.getQueryLocator());
    }
}
} else {
    System.out.println("No records found.");
}
} catch (ConnectionException ce) {
    ce.printStackTrace();
}
}

```

Using Compound Address Fields as Locations

Compound address fields include a geolocation field, and can be used as locations in SOQL `WHERE` and `ORDER BY` clauses. For example, here's a SOQL query to retrieve the ten accounts closest to San Francisco.

```

SELECT Id, Name, BillingAddress
FROM Account
WHERE DISTANCE(BillingAddress, GEOLOCATION(37.775,-122.418), 'mi') < 20
ORDER BY DISTANCE(BillingAddress, GEOLOCATION(37.775,-122.418), 'mi')
LIMIT 10

```

 **Note:** The geolocation component of address fields isn't set automatically. Set values for latitude and longitude on your addresses by using SOQL, Workbench, the SOAP or REST API, or a geocoding service. You can then use address fields as locatable values. Search the AppExchange for “geocode” to find some possible solutions.

Geolocation Compound Field

Geolocation fields are accessible in the SOAP and REST APIs as a `Location`—a structured compound data type—or as individual latitude and longitude elements.

In API versions 26.0 and later, geolocation fields are available in the SOAP and REST APIs as a compound field of type `Location`. This structured data type contains the following fields.

- `latitude`
- `longitude`

 **Note:** SOAP calls that use API versions earlier than 30.0 return geolocation compound values as strings. See “Returned Geolocation Data Types” later in this topic.

Geolocation fields are provided on many standard objects, such as `Account`, `Contact`, `Quote`, and `User`, as part of their address field or fields. Geolocation fields can also be added as custom fields to standard or custom objects.

 **Note:**

- A geolocation compound field is read-only, although its `latitude` and `longitude` subfields are editable. You can only access compound fields using the SOAP or REST API. For more information about working with compound fields and their subfields, see [Compound Field Considerations and Limitations](#) on page 12.

- Although geolocation fields appear as a single field in the user interface, custom geolocation fields count as *three* custom fields towards your organization's limits: one for latitude, one for longitude, and one for internal use.

Retrieving Compound Geolocation Fields

Using compound fields can simplify code that works with geolocations, especially for SOQL queries. SOQL `SELECT` clauses can reference geolocations directly, instead of the individual component fields.

```
SELECT location__c
FROM Warehouse__c
```

To write code that's compatible with API versions earlier than 26.0 and with API versions 26.0 and later, use the individual latitude and longitude fields.

```
SELECT location__latitude__s, location__longitude__s
FROM Warehouse__c
```

Returned Geolocation Data Types

A compound geolocation field value is returned as the structured data type `Location`. Code that works with compound geolocation fields must reference the individual components of the returned value. See the sample code in [Address Compound Fields](#) on page 10.

In API versions earlier than 30.0, SOAP calls return compound geolocation field values as strings, instead of as a structured data type, for backward compatibility. If you plan to display your latitude and longitude values or pass them to a service that expects strings, use the values that are returned. If you plan to use the values in mathematical calculations or pass them to a map service that expects numbers, cast the results to numbers.

The string value format is:

```
API location: [latitudeValue longitudeValue]
```

An example of a regular expression to parse out the latitude and longitude values is:

```
API location: \([[-+]?[0-9]{1,2}([.]\d+)?\)[[-+]?[0-9]{1,3}([.]\d+)?\]
```

The first capture is the latitude, and the third is the longitude.

Compound Field Considerations and Limitations

Address and geolocation compound fields are convenient and result in more concise, clear code. Here are some things to consider when using them in your apps.

Both address and geolocation compound fields have the following limitations.

- Compound fields are read-only. To update field values, modify the individual field components.
- Compound fields are accessible only through the SOAP and REST APIs. The compound versions of fields aren't accessible anywhere in the Salesforce user interface.
- Although compound fields can be queried with the `Location` and `Address` Apex classes, they're editable only as components of the actual field. Read and set geolocation field components by appending "`__latitude__s`" or "`__longitude__s`" to the field name, instead of the usual "`__c`." For example:

```
Double theLatitude = myObject__c.aLocation__latitude__s;
myObject__c.aLocation__longitude__s = theLongitude;
```

You can't access or set the compound value.

- You can't use compound fields in Visualforce—for example, in an `<apex:outputField>`. To access or update field values, use the individual field components.
- If you select compound fields for export in the Data Loader, they cause error messages. To export values, use individual field components.
- Geolocation fields and latitude and longitude on standard addresses aren't supported in the Data Import Wizard. Use the SOAP or REST APIs to import these fields. If you don't have a preferred tool for working with Salesforce APIs, Workbench is an easy way to get started.
- You can't use compound fields in lookup filters, except to filter distances that are within or not within given ranges. You can use distance lookup filters only in the Metadata API.
- The only formula functions that you can use with compound fields are `ISBLANK`, `ISCHANGED`, and `ISNULL`. You can't use `BLANKVALUE`, `CASE`, `NULLVALUE`, `PRIORVALUE`, or the equality and comparison operators with compound fields. The equality and comparison operators include `=` and `==` (equal), `<>` and `!=` (not equal), `<` (less than), `>` (greater than), `<=` (less than or equal), `>=` (greater than or equal), `&&` (AND), and `||` (OR).

Address compound fields have the following limitations.

- Compound address fields are available only for address fields that exist as part of the standard objects included in Salesforce. You can't create custom compound address fields.
- The geolocation component of address fields isn't set automatically. Set values for latitude and longitude on your addresses by using SOQL, Workbench, the SOAP or REST API, or a geocoding service. You can then use address fields as locatable values. Search the AppExchange for "geocode" to find some possible solutions.
- Address fields can't be used in `WHERE` statements in SOQL. Address fields aren't filterable, but the `isFilterable()` method of the `DescribeFieldResult` Apex class erroneously returns `true` for address fields.

Geolocation compound fields have the following limitations.

- Geolocation fields aren't supported in custom settings.
- Geolocation fields aren't available in dashboards or Schema Builder.
- Geolocation fields are available in Visual Workflow and in formula-based workflow and approvals, but they can't be used in filter-based workflow updates and approvals.
- `DISTANCE` formulas are supported in:
 - Entry criteria for workflow rules and approval processes
 - Field update actions in workflow rules and approval processes
 - Custom validation rules
 - Lookup filters (in the Metadata API only)
- Geolocation fields and latitude and longitude on standard addresses aren't supported in Salesforce to Salesforce.
- The geolocation component of address fields isn't set automatically. Set values for latitude and longitude on your addresses by using SOQL, Workbench, the SOAP or REST API, or a geocoding service. You can then use address fields as locatable values. Search the AppExchange for "geocode" to find some possible solutions.
- Geolocation fields are supported in SOQL with the following limitations.
 - `DISTANCE` and `GEOLOCATION` are supported in `WHERE` and `ORDER BY` clauses in SOQL, but not in `GROUP BY` or `SELECT`.
 - `DISTANCE` supports only the logical operators `>` and `<`, returning values within (`<`) or beyond (`>`) a specified radius.
 - When using the `GEOLOCATION` function in SOQL queries, the geolocation field must precede the latitude and longitude coordinates. For example, `DISTANCE(warehouse_location__c, GEOLOCATION(37.775,-122.418),`

'km') works but `DISTANCE(GEOLocation(37.775,-122.418), warehouse_location__c, 'km')` doesn't work.

- Apex bind variables aren't supported for the units parameter in `DISTANCE` or `GEOLocation` functions. This query doesn't work.

```
String units = 'mi';
List<Account> accountList =
    [SELECT ID, Name, BillingLatitude, BillingLongitude
     FROM Account
     WHERE DISTANCE(My_Location_Field__c, GEOLocation(10,10), :units) < 10];
```

For more information and examples, see the [Force.com SOQL and SOSL Reference](#).

API Data Types and Salesforce Field Types

Generally, API data types and field types in the user interface have the same names. For example, a date field is represented by a date data type in the API. However, some field types are represented differently depending on whether you are inspecting an object via the API or the user interface. The following table contains the mapping for field types and data types that are different:

API Data Type	Corresponding Field Types in the User Interface
ID	Lookup relationship, master-detail relationship
string	Auto number, email, phone, picklist, multi-select picklist, text, text area, long text area, rich text area, data category group reference and URL. Different maximum lengths are specified in the WSDL for text, text area, and long text area.
boolean	Checkbox
double	Currency, formula, number, percent, and roll-up summary
Varies by type	When formula fields are created in the user interface, a type must be specified. This type corresponds to the API data type of the same name: currency, date, date/time, number, percent, or text.

All other fields that you can create in the user interface fall into one of the following categories:

- The field is not available in both the user interface and the API. For example, the `BusinessHours` object has fields of API data type time, but you cannot create a custom field of this type.
- Field types are the same as their corresponding API data type. For example, if you create a date field in the user interface, that field is the date data type in the API.

For more information about API data types, see [Primitive Data Types](#) and [Field Types](#).

Required Fields

Required fields must have a non-null value. This rule affects the create and update calls:

- In a create call, the system automatically populates the data for certain required fields (such as system fields and the object ID fields). Similarly, if a required field has a default value (its `defaultedOnCreate` attribute is set to `true`, as described in `Field` in a describe result, then the system implicitly assigns a value for this field when the object is created, even if a value for this field is

not explicitly passed in on the create call. For all other required fields, such as ID fields that are analogous to foreign keys in SQL, a client application must explicitly assign a value when the object is created (it cannot be `null`).

- In updates, a required field cannot be set to `null`, and many required fields can't be changed.

Any field not specified as required in the object description is optional, that is, it can be `null` when updated or created.

Some required fields for some objects require special handling.

System Fields

The following fields are read-only fields found on most objects. These fields are automatically updated during API operations. For example, the ID field is automatically generated during a create operation and the `LastModifiedDate` is automatically updated during any operation on an object.

Field	Field Type	Description
<code>Id</code>	ID	Globally unique string that identifies a record. For information on IDs, see ID Field Type . Because this field exists in every object, it is not listed in the field table for each object. <code>Id</code> fields have Defaulted on create and Filter access.
<code>IsDeleted</code>	boolean	Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Because this field does not appear in all objects, it is listed in the field table for each object.
Audit Fields		
<code>CreatedById</code>	reference	ID of the User who created this record. <code>CreatedById</code> fields have Defaulted on create and Filter access.
<code>CreatedDate</code>	dateTime	Date and time when this record was created. <code>CreatedDate</code> fields have Defaulted on create and Filter access.
<code>LastModifiedById</code>	reference	ID of the User who last updated this record. <code>LastModifiedById</code> fields have Defaulted on create and Filter access.
<code>LastModifiedDate</code>	dateTime	Date and time when this record was last modified by a user. <code>LastModifiedDate</code> fields have Defaulted on create and Filter access.
<code>SystemModstamp</code>	dateTime	Date and time when this record was last modified by a user or by an automated process (such as a trigger). <code>SystemModstamp</code> fields have Defaulted on create and Filter access.

If you import data into Salesforce and need to set the value for an audit field, contact Salesforce. Once Salesforce enables this capability for your organization, you can set audit field values for the following objects: [Account](#), [Attachment](#), [CampaignMember](#), [Case](#), [CaseComment](#), [Contact](#), [FeedComment](#), [FeedItem](#), [Idea](#), [IdeaComment](#), [Lead](#), [Opportunity](#), and [Vote](#). The only audit field you cannot set a value for is `systemModstamp`.

For information on setting audit fields for custom objects, see [Audit Fields for Custom Objects](#).

Not all standard objects have all audit fields. Check the Enterprise WSDL to verify which audit fields are available for a given object.

Parent Reference Fields

If an object has a relationship to a parent object, two fields are added:

- *Parent_Name* contains the object name of the parent. For example, Case has a `Contact` field that contains a reference to the contact parent of the case.
- *Parent_NameId* contains the ID of the parent. For example, Case has a `ContactId` field that refers to the contact parent of the case. This field is used in SOQL relationship queries such as the following:

```
SELECT Case.ContactId, Case.Contact.Name FROM Case
```

Even if the object can parent itself, these fields occur. For example, the Campaign object has a `Campaign` and `CampaignId` field for referencing the parent Campaign.

API Field Properties

Fields on objects represent the details of each object and are analogous to columns in a database table. Each field on each object has one or more of the following properties:

Property	Description
Autonumber	The API creates an autonumber.
Create	Value for the field can be specified during create using the API.
Defaulted on create	When created, a default value is supplied if no other value is specified.
Delete	Value for the field can be deleted using the API.
Filter	Can be used as filter criteria in a SOQL query FROM or WHERE clause.
Group	Can be included in the GROUP BY clause of a SOQL query (<code>true</code>) or not (<code>false</code>). Available in API version 18.0 and later.
idLookup	Can be used to specify a record in an upsert call. The <code>Id</code> field of each object has this property and some <code>Name</code> fields. There are exceptions, so check for the property in any object you wish to upsert.
Nullable	The field can contain a null value.
Query	The field can be queried with SOQL using the API.
Replicate	The value of the field can be replicated using the API.
Restricted picklist	A picklist that depends on the value of another picklist for the values it displays.
Retrieve	Value of the field can be retrieved using the API.
Search	Can be searched with SOSL using the API.
Sort	Indicates whether a query can sort on this field (<code>true</code>) or not (<code>false</code>).
Update	Can be updated using the API.

Custom Fields

Salesforce administrators can define custom fields for standard or custom objects in their organization using the user interface. During creation, the `custom` flag—a Boolean field in the Field object—is set to `true`. Client applications cannot define custom fields via the API. Usually, client applications do not need to know whether a field is a standard field or a custom field.

Note that all numeric custom fields are handled as type `double`.

Use the following topics to understand custom fields:

- [Objects That Support Custom Fields](#)
- [Naming Conventions for Custom Fields](#)
- [External ID Attribute on Custom Fields](#)
- [Uniqueness for Custom Fields](#)
- [Default Values in Custom Fields](#)
- [Managed Packages and API Names](#)

Objects That Support Custom Fields

To identify the standard objects that support custom fields, see the table in [Relationships Among Custom Objects](#).

Naming Conventions for Custom Fields

Custom objects have an associated name field that is defined by your Salesforce administrator. Custom fields must have unique names within the same object.

In the API, the names of custom fields are identified by a suffix of two underscores immediately followed by a lowercase “c” character. For example, a custom object labeled “Issue” in the user interface is seen as `Issue__c` in that organization's WSDL. Similarly, a custom field labeled “Hire Date” in the user interface is seen as `Hire_Date__c` in that organization's WSDL. For example, a custom field labeled “Hire Date” in the user interface is seen as `Hire_Date__c` in that organization's WSDL.

Relationships change the naming convention, see [Relationships Among Custom Objects](#) for more information.

External ID Attribute on Custom Fields

In the user interface, you can identify one custom field on an object as being an external ID field. The field type must be a text, number, or email field. An external ID contains record IDs from a system outside of Salesforce. You can match against this field during import or integration, or when upserting records.

Uniqueness for Custom Fields

In the user interface, you can specify that a custom field on a custom object contain unique values across all the records of that custom object type. The uniqueness can be either case sensitive or case insensitive. In the API, you can find out if a field is unique by issuing a `describe` call against the custom object and inspecting two attribute values:

- If the `unique` field is set to `true`, the custom field values must be unique across all records of that custom object type in the organization. A value of `false` means the field can have the same value in different records of that custom object type.
- If the `caseSensitive` field is set to `true`, the uniqueness (if enabled) is case sensitive. For example “ABC” and “abc” are considered two unique values. If the value is `false`, then “ABC” and “abc” are considered the same value.

These values cannot be set or modified using API calls. If a custom field on a custom object has `unique` set to `true`, and you try to insert a duplicate value, a `DUPLICATE_VALUE` exception code is returned.

Default Values in Custom Fields

You can set a default value on a custom field using a formula field:

- The user logged in for API activity must have the “Customize Application” permission.
- The field must have a data type of currency, date, datetime, int, double, percent, string, textarea, email, phone, or url. You cannot use composite fields like Address, Person, Names, nor Fiscal Periods. Note that you can set a checkbox as checked or unchecked by default using the user interface, but you cannot set it using a formula field.
- Default formulas run on fields, and the results are saved, even if the fields are hidden by field-level security.
- Default values are not used for lead conversion, importing, or merging records.

Managed Packages and API Names

If you have an unmanaged package and a managed package version becomes available, the API names of custom fields, custom objects, and Scontrol objects in the package changes, because a namespace prefix is added to each of these components to make them unique: `name__c` becomes `prefix__name__c`. To move from an unmanaged package to a managed package version of the same application, we advise that you export the data, uninstall the old package, install the new package, review the name changes, and import with the relevant mapping. For details, see the [ISVforce Guide](#).

Custom Objects

In the user interface, you can extend your organization's data by defining custom objects. Custom objects are custom database tables that allow you to store information unique to your organization. For custom objects, the `custom` flag—a Boolean field in the describe results—is `true`.

Client applications with sufficient permissions can invoke API calls on existing custom objects. You can create new custom objects with the user interface, or by using the metadata WSDL with a client application or using the Force.com IDE. For more information about using the metadata WSDL to create new custom objects, see the [Force.com Metadata API Developer's Guide](#). For more information about the Force.com IDE, see [Salesforce Developers](#).

Use the following topics to understand how the API interacts with custom objects and fields:

- [Naming Conventions for Custom Objects](#)
- [Relationships Among Custom Objects](#)
- [Audit Fields for Custom Objects](#)
- [Sharing and Custom Objects](#)
- [Required Fields in Custom Objects](#)
- [Managed Packages and API Names](#)

Naming Conventions for Custom Objects

Custom objects have an associated name field that is defined by your Salesforce administrator during setup. Custom objects must have unique names within your organization.

In the API, the names of custom objects are identified by a suffix of two underscores immediately followed by a lowercase “c” character. For example, a custom object labeled “Issue” in the Salesforce user interface is seen as `Issue__c` in that organization's WSDL.

Relationships change the naming convention, see [Relationships Among Custom Objects](#) for more information.

In order for a custom object record to appear in the Salesforce user interface, its name field must be populated. If you use the API to create a custom object record that does not have a name, then the ID of that record will be used as its name.

Relationships Among Custom Objects

Custom objects relate to other objects and behave just like standard objects, as described in [Relationships Among Objects](#). For example, cascading deletes are supported in custom objects in a Master-Detail relationship.

Custom objects require special treatment so that they can participate in Relationship Queries. For the relationship field name of a custom object, `__r` is appended to the name to create the ID, and `__c` is appended to the name to create the parent object pointer. For example, if the relationship field name is `MyRel`, the name of the ID becomes `MyRelId__r`, and the parent object pointer becomes `MyRel__c`, and the relationship name is `MyRel__r`. For more information, see Understanding Relationship Names, Custom Objects, and Custom Fields in the [Salesforce SOQL and SOSL Reference Guide](#).

The following table summarizes whether a standard object can be:

- The master in a master-detail relationship with a custom object. Master-detail relationships involve cascading deletes and sharing rules that are controlled by the parent.
- The lookup in a lookup relationship on a custom object. In other words, whether a custom object can have a lookup to the standard object.
- Extended with custom fields.

Standard Object	Master-Detail	Lookup	Custom Fields
Account	Yes	Yes	Yes
Campaign	Yes	Yes	Yes
Case	Yes	Yes	Yes
Contact	Yes	Yes	Yes
Contract	Yes	Yes	Yes
Event	No	No	Yes
Lead	No	No	Yes
Opportunity	Yes	Yes	Yes
Product2	No	Yes	Yes
Solution	Yes	Yes	Yes
Task	No	No	Yes
User	No	Yes	Yes

Custom objects can also have many-to-many relationships with other custom objects or standard objects. A many-to-many relationship allows each record of one object to be linked to multiple records from another object and vice versa. For more information, see [Relationships Among Objects](#).

Audit Fields for Custom Objects

Custom objects can have the same audit fields as standard objects. Your organization must be API enabled and have the ability to create audit fields enabled, and you must have the “Modify All Data” permission.

When you create a custom object, the four audit fields `CreatedById`, `CreatedDate`, `LastModifiedById` and `LastModifiedDate` are automatically created and populated for the object. These fields are read only.

Note these restrictions:

- `CreatedDate` can't be greater than the `LastModifiedDate`.
- You can't set any date field to be greater than the current time.

For more information about audit fields, see [System Fields](#).

Sharing and Custom Objects

A sharing rule object is created for each custom object that does not have a master-detail relationship to another object. They are similar to standard object sharing rules, for example `AccountOwnerSharingRule`. If the user creating the custom object has the “Manage Sharing” permission, a sharing rule object is automatically created for it.

Apex sharing reasons can be retrieved describing the custom object's sharing object, and examining the information in the `rowCause` field. The name of a sharing object for each custom object is of the form: `MyObjectName__Share`, similar to `AccountShare` and other standard object sharing objects.

Tags and Custom Objects

When a custom object is created, a Tag object related to it is also created. These object names are of the form: `MyObjectName__Tag`, similar to `AccountTag` and other standard object tag objects.

Required Fields in Custom Objects

In the user interface, you can mark a custom field as required, and this is also enforced in the API. Every custom field has a field `isRequired`, with a data type boolean. The default value is `false`. If set to `true`, every request must supply a value (or leave the current value) to this field. Otherwise, the request will fail. Once the value is set to `true`, the next time the field is edited or created, the validation applies, and if there is no value supplied or default value specified, the request fails.

To edit the `isRequired` field, you must log in as a user with the “Customize Application” permission.

If you change a custom object field to be required in an existing client application or integration, be sure that a value is always supplied for that field. For example, if the custom picklist field `Education Level` on the contact object is required, supply a default value for that custom field. If a required field does not have a specified or default value, an error with the status code `REQUIRED_FIELD_MISSING` is returned.

Managed Packages and API Names

If you have an unmanaged package and a managed package version becomes available, the API names of custom fields, custom objects, and Scontrol objects in the package changes, because a namespace prefix is added to each of these components to make them unique: `name__c` becomes `prefix__name__c`. To move from an unmanaged package to a managed package version of the same application, we advise that you export the data, uninstall the old package, install the new package, review the name changes, and import with the relevant mapping. For details, see the [ISVforce Guide](#).

External Objects

External objects are supported in API version 32.0 and later. External objects are similar to custom objects, but external object record data is stored outside your Salesforce organization. For example, perhaps you have data that's stored on premises in an enterprise resource planning (ERP) system. Instead of copying the data into your organization, use external objects to access the data in real time via Web service callouts.

External objects are available with Lightning Connect and Files Connect. Each external object is associated with an external data source definition in your Salesforce organization.

An external data source specifies how to access an external system. Lightning Connect uses external data sources to access data that's stored outside your Salesforce organization. Files Connect uses external data sources to access third-party content systems. External data sources have associated external objects, which your users and the Force.com platform use to interact with the external data and content.

By accessing record data on demand, external objects always reflect the current state of the external data. You don't have to manage a copy of that data in Salesforce, so you're not wasting storage and resources keeping data in sync.

External objects are best used when you have a large amount of data that you can't or don't want to store in your Salesforce organization, and you only need to use a small amount of data at any one time.

See "Define External Objects" in the Salesforce Help for how to create and modify external objects.

Naming Conventions for External Objects

Object names must be unique across all standard, custom, and external objects in the organization.

In the API, the names of external objects are identified by a suffix of two underscores immediately followed by a lowercase "x" character. For example, an external object named "ExtraLogInfo" in the Salesforce user interface is seen as `ExtraLogInfo__x` in that organization's WSDL.

External Object Relationships

External objects support standard lookup relationships. However, data that's stored outside your Salesforce organization often doesn't contain the 18-character Salesforce record IDs that standard lookup relationships use to associate related records with each other. Therefore, two special types of lookup relationships are also available for external objects: external lookups and indirect lookups. See "External Object Relationships" in the Salesforce Help for details.

Feature Support for External Objects

Most of the Salesforce features that support custom objects also support external objects. However, there are exceptions, and some features have special limitations and considerations for external objects. See the following topics in the Salesforce Help.

- Salesforce Compatibility Considerations for Lightning Connect—All Adapters
- Considerations for Lightning Connect—All Adapters

Lightning Connect Adapters

Lightning Connect uses a protocol-specific adapter to connect to an external system and access its data. This table describes the available adapters.

Lightning Connect Adapter	Description
OData 2.0	Uses Open Data Protocol Version 2.0 to access data that's stored outside Salesforce. The external data must be exposed via OData producers.
Salesforce	Uses the Force.com REST API to access data that's stored in other Salesforce organizations.
Custom adapter created via Apex	You use the Apex Connector Framework to develop your own custom adapter when the other available adapters aren't suitable for your needs. A custom adapter can obtain data from anywhere. For example, some data can be retrieved from anywhere in the Internet via callouts, while other data can be manipulated or even generated programmatically.

For more information about Lightning Connect, see "Lightning Connect Overview" in the Salesforce Help.

For details on using the Apex Connector Framework, see "Lightning Connect" and "DataSource Namespace" in the [Force.com Apex Code Developer's Guide](#).

Relationships Among Objects

Relationships associate objects with other objects. For example, a relationship can link a custom object to standard object in a related list, such as linking a custom object called Bugs to cases to track product defects associated with customer cases. To view the parent and child relationships among standard objects, see the ERD diagrams in [Data Model](#).



Note:

- You can use parent-child relationships in SOQL queries. For more information, see Relationship Queries in the [Salesforce SOQL and SOSL Reference Guide](#).
- Only lookup, external lookup, and indirect lookup relationships are available for external objects. No other relationship types are supported. See "External Object Relationships" in the Salesforce Help.

You can define different types of relationships by creating custom relationship fields on an object. The differences between relationship types include how they handle data deletion, record ownership, security, and required fields in page layouts:

- Master-Detail (1:n)** — A parent-child relationship in which the master object controls certain behaviors of the detail object:
 - When a record of the master object is deleted, its related detail records are also deleted.
 - The `Owner` field on the detail object is not available and is automatically set to the owner of its associated master record. Custom objects on the detail side of a master-detail relationship cannot have sharing rules, manual sharing, or queues, as these require the `Owner` field.
 - The detail record inherits the sharing and security settings of its master record.
 - The master-detail relationship field is required on the page layout of the detail record.
 - By default, records can't be reparented in master-detail relationships. Administrators can, however, allow child records in master-detail relationships on custom objects to be reparented to different parent records by selecting the `Allow reparenting` option in the master-detail relationship definition.

You can define master-detail relationships between custom objects or between a custom object and a standard object. However, the standard object cannot be on the detail side of a relationship with a custom object. In addition, you cannot create a master-detail relationship in which the User or Lead objects are the master.

When you define a master-detail relationship, the custom object on which you are working is the detail side. Its data can appear as a custom related list on page layouts for the other object.

- **Many-to-many** — You can use master-detail relationships to model *many-to-many* relationships between any two objects. A many-to-many relationship allows each record of one object to be linked to multiple records from another object and vice versa. For example, you may have a custom object called “Bug” that relates to the standard case object such that a bug could be related to multiple cases and a case could also be related to multiple bugs. To create a many-to-many relationship, simply create a custom junction object with two master-detail relationship fields, each linking to the objects you want to relate. See the Salesforce online help for details.

Custom objects with two master-detail relationships are supported in API version 11 and later.

Starting in API version 34.0, the `JunctionIdList` field type lets you manipulate the many-to-many relationship of an entity directly. You no longer need to manipulate underlying junction entity records. `JunctionIdList` fields can be queried and updated like any other field on the entity. Queries or updates to `JunctionIdList` fields act as queries or updates to the underlying junction entity records. Fields of type `JunctionIdList` appear in the WSDL as an unbounded array of type ID.

`JunctionIdList` is implemented in the `Task` and `Event` objects.

- **Lookup (1:n)** — This type of relationship links two objects together, but has no effect on deletion or security. Unlike master-detail fields, lookup fields are not automatically required. When you define a lookup relationship, data from one object can appear as a custom related list on page layouts for the other object. See the Salesforce online help for details.

To create relationships, use the user interface or Salesforce Metadata API.

Factors that Affect Data Access

When using the API, the following factors affect access to your organization’s data:

Access

Your organization must be enabled for API access.

Objects may not be available until you contact Salesforce and request access. For example Territory is visible only if territory management has been enabled in the application. Such requirements are in the “Usage” section for each object.

Sometimes a feature must be used once before objects related to it can be accessed with the API. For example, the `recordTypeIds` is available only after at least one record type has been created for your organization in the user interface.

To investigate data access issues, you can start by inspecting the WSDL:

- **Enterprise WSDL:** The generated enterprise WSDL file contains all of the objects that are available to your organization. By using the API, a client application can access objects that are defined in your enterprise WSDL file.
- **Partner WSDL:** When using the generated partner WSDL file, a client application can access objects that are returned in the `describeGlobal()` call.

Object-Level and Field-Level Security

The API respects object-level and field-level security configured in the user interface. You can access objects and fields only if the logged-in user’s permissions and access settings allow such access. For example, fields that are not visible to a given user are not returned in a `query()` or `describeObjects()` call. Similarly, read-only fields can’t be updated.

User Permissions

A user attempting to access the API must have the permission “API Enabled” selected. It’s selected by default.

Your client application logs in as a user called a *logged-in* user. The logged-in user’s permissions grant or deny access to specific objects and fields in your organization:

- **Read**—Users can only view objects of this type.
- **Create**—Users can read and create objects of this type.

- **Edit**—Users can read and update objects of this type.
- **Delete**—Users can read, edit, and delete objects of this type.

User permissions do not affect field-level security. If field-level security specifies that a field is hidden, users with “Read” on that object can view only those fields that are not hidden on the record. In addition, users with “Read” on an object can view only those records that sharing settings allow. The one exception is the “Edit Read Only Fields” permission, which gives users the ability to edit fields marked as read only via field-level security.

Sharing

For most API calls, data that is outside of the logged-in user’s sharing model is not returned. Users are granted the most permissive access that is available to them, either through organization-wide defaults or manual record sharing, just as in the application.

User Permissions that Override Sharing

- **View All**—Users can view all records associated with this object, regardless of sharing settings.
- **Modify All**—Users can read, edit, delete, transfer, and approve all records associated with this object, regardless of sharing settings.
- **Modify All Data**—users can read, edit, delete, transfer, and approve all records regardless of sharing settings. This permission is not an object-level permission, unlike “View All” and “Modify All.”

To protect the security of your data, give the logged-in user only the permissions needed to successfully execute all the calls made by the application. For large integration applications, “Modify All Data” may speed up call response times. If you are loading a large number of records, use the [Bulk API](#) instead.

Related Objects

Some objects depend on other objects for permission. For example, AccountTeamMember follows sharing on the associated permission-assigned object such as the Account record. Similarly, a Partner depends on the permissions in the associated .

Ownership changes to a record do not automatically cascade to related records. For example, if ownership changes for a given Account, ownership does not then automatically change for any Contract associated with that Account—each ownership change must be made separately and explicitly by the client application.

Object Properties

To create an object with the `create()` call, the object’s `createable` attribute must be set to `true`. To determine what operations are allowed on a given object, your client application can invoke the `describeObjects()` call on the object and inspect the properties in the `DescribeObjectResult`.



Note: `replicable` allows `getUpdated()` and `getDeleted()` calls.

Page Layouts and Record Types

Requirements defined in the Salesforce user interface for page layouts and record types are not enforced by the API:

- Page layouts can specify whether a given field is required, but the API does not enforce such layout-specific field restrictions or validations in `create()` and `update()` calls. It’s up to the client application to enforce any such constraints, if applicable.
- Record types can control which picklist values can be chosen in a given record and which page layouts users with different profiles can see. However, such rules that are configured and enforced in the user interface are not enforced in the API. For example, the API does not validate whether the value in a picklist field is allowed per any record type restrictions associated with the profile of the logged-in user. Similarly, the API does not prevent a client application from adding data to a particular field simply because that field does not appear in a layout associated with the profile of the logged-in user.

Referential Integrity

To ensure referential integrity, the API forces or prevents certain behaviors:

- ID values in [reference fields](#) are validated in `create()` and `update()` calls.
- If a client application deletes a record, then its children are automatically deleted as part of the call if the `cascadeDelete` property on `ChildRelationship` for that child has a value of `true`. For example, if a client application deletes an Opportunity,

then any associated OpportunityLineItem records are also deleted. However, if an OpportunityLineItem is not deletable or is currently being used, then deletion of the parent Opportunity fails. For example, if a client application deletes an Invoice_Statement, then any associated Line_Item records are also deleted. However, if a Line_Item is not deletable or is currently being used, then deletion of the parent Invoice_Statement fails. Use DescribeObjectResult to view the ChildRelationship value if you want to be sure what will be deleted.

There are certain exceptions that prevent the execution of a `cascadeDelete`. For example, you can't delete an account if it has associated cases, if it has related opportunities that are owned by other users, or if associated contacts are enabled for the Customer Portal. In addition, if you attempt to delete an account that has closed/won opportunities owned by you or has active contracts, then the delete request for that record will fail.

REFERENCE

CHAPTER 2 Standard Objects

This section provides a list of standard objects and their standard fields. Some fields may not be listed for some objects.

To see the system fields for each object, see [System Fields](#).

To verify the complete list of fields for an object, you can use a describe call from the API, or inspect with an appropriate tool, for example, inspecting the WSDL or using a schema viewer.

Object	Description
AcceptedEventRelation	Represents invitees with the status <code>Accepted</code> for a given event.
Account	An individual account, which is an organization involved with your business (such as customers, competitors, and partners).
AccountContactRole	The role that a given Contact plays on an Account.
AccountFeed	Represents a single feed item on an account record detail page. This object is available in API version 18.0 and later.
AccountHistory	Represents the history of changes to the values in the fields of an account. This object is available in versions 11.0 and later.
AccountOwnerSharingRule	A rule that grants access to an account to users other than the owner.
AccountPartner	A relationship between two Account objects, such as partnerships or subsidiaries.
AccountShare	A sharing entry on an Account.
AccountTag	Associates a word or short phrase with an Account.
AccountTeamMember	A User who is a member of an Account team.
AccountTerritoryAssignmentRule	A rule that assigns accounts to territories.
AccountTerritoryAssignmentRuleItem	A field-specific criteria row for an AccountTerritoryAssignmentRule.
AccountTerritorySharingRule	Rules for sharing an account within a territory.
ActionLinkGroupTemplate	Action link templates let you reuse action link definitions and package and distribute action links. An action link is a button on a feed element. Clicking on an action link can take a user to another Web page, initiate a file download, or invoke an API call to an external server or Salesforce. Use action links to integrate Salesforce and third-party services into the feed. Every action link belongs to an action link group and action links within the group are mutually exclusive.
ActionLinkTemplate	Action link templates let you reuse action link definitions and package and distribute action links. An action link is a button on a feed element. Clicking an action link can take a user to another Web page, initiate a file download, or invoke

Standard Objects

Object	Description
	an API call to an external server or Salesforce. Use action links to integrate Salesforce and third-party services into the feed.
ActivityHistory	Contains information about events and tasks related to an object.
AdditionalNumber	An additional phone number for a CallCenter.
AllowedEmailDomain	Represents an allowed email domain for users in your organization. You can define a whitelist to restrict the email domains allowed in a user's <code>Email</code> field. This object is available in API version 29.0 and later.
ApexClass	Represents an Apex class.
ApexComponent	A Visualforce custom component that can be used in a Visualforce page alongside standard components such as <code><apex:relatedList></code> and <code><apex:dataTable></code> .
ApexLog	A debug log, containing information about a transaction, including information about Apex, Visualforce, workflow and validation rules. This object is available in API version 19.0 and later.
ApexPage	A Visualforce page, containing Visualforce markup, HTML, Javascript, and other Web-enabled code.
ApexTestQueueItem	Represents a single Apex class in the Apex job queue. This object is available in API version 23.0 and later.
ApexTestResult	Represents the result of an Apex test method execution. This object is available in API version 23.0 and later.
ApexTrigger	Represents an Apex trigger.
Approval	An approval request for a Contract.
Article Type__DataCategorySelection	A data category selection represents a data category that classifies an article. This object can be used to associate an article with data categories from a data category group or to query the category selections for an article. This object is available in API version 19.0 and later.
Article Type__Feed	Represents a single feed item in the feed displayed on the detail page for an article. This object is available in API version 20.0 and later.
Asset	An Asset is a product from your company or from a competitor that a customer has purchased and installed.
AssetFeed	Represents a single feed item in the feed displayed on the detail page for an asset record. This object is available in API version 18.0 and later.
AssetOwnerSharingRule	A rule that grants access to an Asset to users other than the owner.
AssetShare	A sharing entry on an Asset.
AssetTag	Associates a word or short phrase with an Asset.
AssignmentRule	An assignment rule associated with a Case or Lead.

Standard Objects

Object	Description
AsyncApexJob	Represents an individual Apex sharing recalculation job, a batch Apex job, a method with the <code>future</code> annotation, or a job that implements <code>Queueable</code> .
AttachedContentDocument	This read-only object contains all <code>ContentDocument</code> objects associated with an object.
Attachment	A file that a User has uploaded and attached to a parent object.
AuraDefinition	Represents a Lightning definition, such as component markup, a client-side controller, or an event. Lightning components is a beta feature.
AuraDefinitionBundle	Represents a Lightning definition bundle, such as a component or application bundle. A bundle contains a Lightning definition and all its related resources. Lightning components is a beta feature.
AuthConfig	Represents authentication options for a community or custom domain that was created by using My Domain.
AuthConfigProviders	Represents an authentication provider that's configured in an organization. This object is a child of the <code>AuthConfig</code> object.
AuthProvider	An Auth Provider enables users to log into your Salesforce organization using their login credentials from an external service provider such as Facebook® or Janrain®.
AuthSession	The <code>AuthSession</code> object represents an individual user session in your organization.
Bookmark	A link between two opportunities.
BrandTemplate	Letterhead for email templates.
BusinessHours	Specifies the business hours of your support organization. Escalation rules are run only during these hours.
BusinessProcess	A business process.
CallCenter	A single computer-telephony integration (CTI) system instance in an organization.
Campaign	A marketing campaign, such as a direct mail promotion, webinar, or trade show.
CampaignFeed	Represents a single feed item in the feed on a campaign record detail page. This object is available in API version 18.0 and later.
CampaignMember	The association between a Campaign and either a Lead or Contact.
CampaignMemberStatus	A status value associated with a Campaign.
CampaignOwnerSharingRule	Represents the rules for sharing a Campaign with User records other than the owner.
CampaignShare	Represents a list of access levels to a Campaign along with an explanation of the access level. For example, if you have access to a record because you own it, the Access Level value is <code>Full</code> and Reason for Access value is <code>Owner</code> .
CampaignTag	Associates a word or short phrase with a Campaign.
Case	A customer issue such as a customer's feedback, problem, or question.

Object	Description
CaseArticle	Represents the association between a Case and a KnowledgeArticle. This object is available in API version 20.0 and later.
CaseComment	A comment that provides additional information about the associated Case.
CaseContactRole	The role that a given Contact plays on a Case.
CaseFeed	Represents a single feed item in the feed displayed on the detail page for a case record. This object is available in API version 18.0 and later.
CaseHistory	Historical information about changes that have been made to the associated Case.
CaseMilestone	Represents a milestone (required step in a customer support process) on a Case. This object is available in API version 18.0 and later.
CaseOwnerSharingRule	A rule that grants access to a case to users other than the owner.
CaseShare	A sharing entry on a Case.
CaseSolution	The association between a particular Case and a particular Solution .
CaseStatus	The status of a Case, such as New, On hold, In Process, and so on.
CaseTag	Associates a word or short phrase with a Case
CaseTeamMember	Represents a case team member, who works with a team of other users to help resolve a case.
CaseTeamRole	Represents a case team role. Every case team member has a role on a case, such as "Customer Contact" or "Case Manager."
CaseTeamTemplate	Represents a predefined case team, which is a group of users that helps resolve a case.
CaseTeamTemplateMember	Represents a member on a predefined case team, which is a group of users that helps resolve cases.
CaseTeamTemplateRecord	The CaseTeamTemplateRecord object is a linking object between the Case and CaseTeamTemplate objects. To assign a predefined case team to a case (customer inquiry), create a CaseTeamTemplateRecord record and point the <code>ParentId</code> to the case and the <code>TeamTemplateId</code> to the predefined case team.
CategoryData	A logical grouping of Solution records.
CategoryNode	A tree of Solution categories.
CategoryNodeLocalization	The translated value of the label for a category.
ChatterActivity	ChatterActivity represents the number of posts and comments made by a user and the number of comments and likes on posts and comments received by the same user. This object is available in API version 23.0 and later.
ChatterAnswersActivity	Represents the reputation of a User in Chatter Answers communities. This object is available in API version 25.0 and later.

Object	Description
ChatterAnswersReputationLevel	Represents a reputation level within a Chatter Answers zone. This object is available in API version 26.0 and later.
ChatterConversation	Represents a private conversation in Chatter, consisting of messages that conversation members have sent or received. This object is available in API version 23.0 and later.
ChatterConversationMember	Represents a member of a private conversation in Chatter. A member has either sent messages to or received messages from other conversation participants. This object is available in API version 23.0 and later.
ChatterMessage	Represents a message sent as part of a private conversation in Chatter. This object is available in API version 23.0 and later.
CollaborationGroup	Represents a Chatter group. This object is available in API version 19.0 and later.
CollaborationGroupFeed	A group feed shows posts and comments about the group. This object is available in API version 19.0 and later.
CollaborationGroupMember	Represents a member of a Chatter group. This object is available in API version 19.0 and later.
CollaborationGroupMemberRequest	Represents a request to join a private Chatter group.
CollaborationGroupRecord	Represents the records associated with Chatter groups.
CollaborationInvitation	Represents an invitation to join Chatter, either directly or through a group. This object is available in API version 21.0 and later.
CombinedAttachment	This read-only object contains all notes, attachments, Google Docs, documents uploaded to libraries in Salesforce CRM Content, and files added to Chatter that are associated with a record.
Community (Zone)	Represents a zone within Ideas, Chatter Answers, or Answers. .
ConnectedApplication	Represents a connected app and its details; all fields are read-only.
Contact	A contact, which is an individual associated with an Account.
ContactFeed	Represents a single feed item in the feed on a contact record detail page. This object is available in API version 18.0 and later.
ContactHistory	Represents the history of changes to the values in the fields of a contact. This object is available in versions 11.0 and later.
ContactOwnerSharingRule	Represents the rules for sharing a contact with User records other than the owner.
ContactShare	Represents a list of access levels to a Contact along with an explanation of the access level. For example, if you have access to a record because you own it, the Access Level value is <code>Full</code> and Reason for Access value is <code>Owner</code> .
ContactTag	Associates a word or short phrase with a Contact.
ContentDocument	Represents a document that has been uploaded to a library in Salesforce CRM Content.

Object	Description
ContentDocumentFeed	Represents a single feed item associated with ContentDocument.
ContentDocumentHistory	Represents the history of a document in Salesforce CRM Content.
ContentDocumentLink	Represents the link between a Salesforce CRM Content document or Chatter file and where it's shared. A file can be shared with other users, Chatter groups, records, and Salesforce CRM Content libraries.
ContentFolder	Represents a folder in a content library for adding files. This object is available in API version 34.0 and later.
ContentFolderLink	Defines the association between a library and its root folder. This object is available in API version 34.0 and later.
ContentFolderMember	Defines the association between a file and a folder. This object is available in API version 34.0 and later.
ContentHubItem	Represents a file or folder in a Files Connect external data source, such as Microsoft SharePoint or OneDrive for Business.
ContentHubRepository	Represents a Files Connect external data source such as Microsoft SharePoint or OneDrive for Business.
ContentNote	Represents a note in Salesforce.
ContentVersion	Represents a specific version of a document in Salesforce CRM Content.
ContentVersionHistory	Represents the history of a specific version of a document in Salesforce CRM Content.
ContentWorkspace	Represents a public library in Salesforce CRM Content.
ContentWorkspaceDoc	Represents a link between a document and a library in Salesforce CRM Content.
Contract	A contract (a business agreement) associated with an Account.
ContractContactRole	The role that a given Contact plays on a Contract.
ContractFeed	Represents a single feed item in the feed on the contract record detail page. This object is available in API version 18.0 and later.
ContractHistory	Information about changes to a contract.
ContractLineItem	Represents a Product2 in a ServiceContract (customer support agreement). This object is available in API version 18.0 and later.
ContractLineItemHistory	Represents the history of changes to the values in the fields on a ContractLineItem (items in a customer support agreement). This object is available in API version 18.0 and later.
ContractStatus	The status of a Contract, such as Draft, In Approval, Activated, Terminated, or Expired.
ContractTag	Associates a word or short phrase with a Contract.

Object	Description
CronTrigger	Contains schedule information for a scheduled job. CronTrigger is similar to a cron job on UNIX systems. This object is available in API version 17.0 and later.
CronJobDetail	Contains details about the associated scheduled job, such as the job's name and type.
CurrencyType	The currencies used by an organization for which the multicurrency feature is enabled.
CustomBrand	Represents a custom branding and color scheme. This object is available in API version 28.0 and later.
CustomBrandAsset	Represents a branding element in a custom branding scheme. For example, a color, logo image, header image, or footer text. This object is available in API version 28.0 and later.
Custom Metadata Type__mdt	Represents a custom metadata record. This object is available in API version 34.0 and later.
Custom Object__Feed	Represents a single feed item on a custom object detail page. This object is available in API version 18.0 and later.
CustomPermission	Represents a permission that grants access to custom features. This object is available in API version 31.0 and later.
CustomPermissionDependency	Represents the dependency between two custom permissions when one custom permission requires that you enable another custom permission.
DandBCompany	Represents a D&B Company record, which is associated with an account. This object is available in API version 25.0 and later.
Dashboard	Represents a dashboard, which shows data from custom reports as visual components. Access is read-only. This object is available in API version 20.0 and later.
DashboardComponent	Represents a dashboard component, which can be a chart, metric, table, or gauge on a dashboard. Access is read-only. This object is available in API version 21.0 and later.
DashboardComponentFeed	Represents a single feed item in the feed displayed on a dashboard component. This object is available in API version 21.0 and later.
DashboardFeed	Represents a single feed item in the feed displayed on a dashboard. This object is available in API version 20.0 and later.
DashboardTag	Associates a word or short phrase with a Dashboard. This object is available in API version 20.0 and later.
DatacloudCompany	Represents the fields for Data.com company records. This object is available in API version 30.0 or later.
DatacloudContact	The fields and properties for Data.com contact records. This object is available in API version 30.0 or later.

Object	Description
DatacloudDandBCompany	Represents a set of read-only fields that are used to return D&B company data from Data.com API calls.
DatacloudOwnedEntity	Represents fields in the DatacloudOwnedEntity object. The DatacloudOwnedEntity object tracks user-purchased records. This object is available in API version 30.0 or later.
DatacloudPurchaseUsage	Represents an object used to identify and track Data.com record purchases. This object is available in API version 30.0 or later.
DatacloudSocialHandle	Returns normalized URLs with userids for different social media used by Data.com contacts. The DatacloudSocialHandle object is a child object of the DatacloudContact object. This object is available in API version 30.0 or later.
DatedConversionRate	The effective dated exchange rates used by an organization for which advanced currency management is enabled.
DcSocialProfile	The <code>DcSocialProfile</code> object is a read-only object accessible only through the Data.com Social Key API.
DcSocialProfileHandle	The <code>DcSocialProfileHandle</code> object, a child object to <code>DcSocialProfile</code> , is a read-only object accessible only through the Data.com Social Key API.
DeclinedEventRelation	Represents invitees with the status <code>Declined</code> for a given event.
Division	A logical segment of your organization's data. Available only if the organization has the Division permission enabled.
DivisionLocalization	The translated value of a label for a division.
Document	A file that a user has uploaded. Unlike Attachment objects, Documents are not attached to a parent object.
DocumentAttachmentMap	Maps the relationship between an EmailTemplate and its attachment, which is stored as a Document.
DocumentTag	Associates a word or short phrase with a Document.
DuplicateRecordItem	Represents an individual record that's part of a duplicate record set. Use this object to create custom report types.
DuplicateRecordSet	Represents a group of records that have been identified as duplicates. Each duplicate record set contains one or more duplicate record items. Use this object to create custom report types.
EmailDomainKey	Represents a domain key for an organization's domain, used to authenticate outbound email that Salesforce sends on the organization's behalf.
EmailMessage	An email message related to Email-to-Case.
EmailServicesAddress	An email service address.
EmailServicesFunction	An email service.

Object	Description
EmailStatus	The status of an email sent via Salesforce.
EmailTemplate	A template for sending email via Salesforce.
Entitlement	Represents the customer support an Account or Contact is eligible to receive. Entitlements may be based on an Asset, Product2, or ServiceContract. This object is available in API version 18.0 and later.
EntitlementContact	Represents a Contact eligible to receive customer support via an Entitlement. This object is available in API version 18.0 and later.
EntitlementFeed	An entitlement feed shows recent changes to an entitlement record for any fields that are tracked in feeds, as well as comments and posts about the record. This object is available in API version 23.0 and later.
EntitlementHistory	Represents the changes to field values on an Entitlement. This object is available in API version 18.0 and later.
EntitlementTemplate	Represents predefined terms of customer support for a product (Product2). This object is available in API version 18.0 and later.
EntityHistory	Removed as of 8.0. Use the history object corresponding to the object you are working with.
EntitySubscription	Represents a subscription for a user following a record or another user. This object is available in versions 18.0 and later.
EnvironmentHubMember	Represents a member organization in the Environment Hub. This object is available in API version 29.0 and later.
Event	A calendar appointment event.
EventFeed	Represents a single feed item in the feed on an Event. This object is available in API version 20.0 and later.
EventRelation	Represents people (a user, a lead, or contacts) or a resource (such as a conference room) invited to an event. This object lets you add or remove invitees from an event and use the API to manage invitees' responses to invitations. If Shared Activities is enabled, this object doesn't support triggers, workflow, or data validation rules.
EventTag	Associates a word or short phrase with an Event.
EventWhoRelation	Represents the relationship between an event and a lead or contacts. This derived object is a filtered version of the EventRelation on page 679 object; that is, IsParent is <i>true</i> and IsWhat is <i>false</i> . It doesn't represent relationships to invitees or to accounts, opportunities, or other objects.
ExternalDataSource	Represents an external data source, such as SharePoint®. This object is available in API version 27 and later.
ExternalDataUserAuth	Stores authentication settings for a specific user to access an external system. The external system can be an external data source or a callout endpoint that's defined in a named credential. The external data source or named credential must be

Object	Description
	configured to use per-user authentication. This object is available in API version 27 and later.
FeedComment	Represents a comment added to a feed by a user. Represents a comment added to a feed by a user. This object is available in API version 18.0 and later.
FeedItem	FeedItem represents an entry in the feed, such as changes in a record feed, including text posts, link posts, and content posts. This object is available in API version 21.0 and later.
FeedLike	Indicates that a user has liked a feed item. This object is available in API version 21.0 and later.
FeedPollChoice	Shows the choices for a poll posted in the feed. This object is available in API version 29.0 and later.
FeedPollVote	Shows how users voted on a poll posted in the feed. This object is available in API version 29.0 and later.
FeedPost	FeedPost represents the following types of changes in a record feed, such as AccountFeed: text posts, link posts, and content posts. This object is available in API version 18.0 through 21.0. FeedPost is no longer available in later versions. Starting with API version 21.0, use FeedItem to represent text posts, link posts, and content posts in feeds.
FeedTrackedChange	Represents an individual field change or set of field changes. This object is available in API version 18.0 and later.
FieldPermissions	Represents the enabled field permissions for the parent PermissionSet. This object is available in API version 24.0 and later.
FiscalYearSettings	Fiscal year settings.
FlowInterview	Represents a flow interview. A <i>flow interview</i> is a running instance of a flow.
Folder	A repository for a Document, MailmergeTemplate, email template, or report. Only one type of item can be contained in a particular Folder.
ForecastingAdjustment	This object represents an individual sales manager's adjustment for a subordinate's forecast via a ForecastingItem. Available in API versions 26 and greater. This object is separate from the ForecastingOwnerAdjustment object, which represents forecast users' adjustments of their <i>own</i> forecasts.
ForecastingFact	This is a read-only object linking a ForecastingItem with its opportunities, such as opportunities that share the same owner or forecast category and have a closing date within the period of the forecasting item. Available in API versions 26 and greater.
ForecastingItem	This is a read-only object used for individual forecast amounts. Users see amounts based on their perspectives and forecast roles. The amounts users see include one of the following when forecasting in revenue: AmountWithoutAdjustments, AmountWithoutManagerAdjustment, ForecastAmount,

Object	Description
	<code>OwnerOnlyAmount</code> . The amounts users see include one of the following when forecasting in quantity: <code>QuantityWithoutAdjustments</code> , <code>QuantityWithoutManagerAdjustments</code> , <code>ForecastQuantity</code> , <code>OwnerOnlyQuantity</code> .
ForecastingOwnerAdjustment	This object represents an individual forecast user's adjustment of their <i>own</i> forecast via a <code>ForecastingItem</code> . Available in API versions 33 and greater. This object is separate from the <code>ForecastingAdjustment</code> object, which represents managers' adjustments of <i>subordinates'</i> forecasts.
ForecastingQuota	This object represents an individual user's quota for a specified time period.
ForecastingType	This object is used to identify the forecast type associated with <code>ForecastingAdjustment</code> , <code>ForecastingOwnerAdjustment</code> , <code>ForecastingQuota</code> , <code>ForecastingFact</code> , and <code>ForecastingItem</code> objects.
ForecastShare	Represents the sharing of a customizable forecast at a given role and territory.
Goal	The <code>Goal</code> object represents the components of a goal such as its name, description, and status.
GoalFeed	Represents a single feed item in the feed displayed for a <code>Goal</code> record. The goal feed shows changes to a goal for fields that are tracked in feeds, posts, and comments about the goal.
GoalHistory	This read-only object contains historical information about changes that have been made to the <code>Goal</code> object.
GoalLink	Represents the relationship between two goals. This is a many-to-many relationship, meaning that each goal can link to many other goals.
GoalShare	Represents a sharing entry on a <code>Goal</code> object.
Group	A set of <code>User</code> records.
GroupMember	A <code>User</code> or <code>Group</code> that is a member of a public group.
HashtagDefinition	<code>HashtagDefinition</code> represents hashtag (#) topics in public <code>Chatter</code> posts and comments. This object is available in API version 26.0 and later.
Holiday	Represents a period of time during which your customer support team is unavailable. Business hours and escalation rules associated with business hours are suspended during any holidays with which they are affiliated.
Idea	Represents an idea on which users are allowed to comment and vote, for example, a suggestion for an enhancement to an existing product or process.
IdeaComment	Represents a comment that a user has submitted in response to an idea.
IdeaTheme	Represents an invitation to community members to submit ideas that are focused on a specific topic. This object is available in API version 26 and later.

Object	Description
KnowledgeableUser	Represents a user identified as knowledgeable about a specific topic, and ranks them relative to other knowledgeable users. This object is available in API version 31.0 and later.
KnowledgeArticle	Provides read-only access to an article and the ability to delete the master article. This object is available in API version 19.0 and later.
KnowledgeArticleVersion	Provides a global view of standard article fields across all article types depending on their version. This object is available in API version 18.0 and later.
KnowledgeArticleVersionHistory	Enables read-only access to the full history of an article. This object is available in API version 25.0 and later.
KnowledgeArticleViewStat	Provides statistics on the number of views for the specified article across all article types. This object is available in API version 20.0 and later.
KnowledgeArticleVoteStat	Provides the weighted rating for the specified article on a scale of 1 to 5 across all article types. This object is available in API version 20.0 and later.
Lead	A lead, which is a prospect or potential Opportunity.
LeadFeed	Represents a single feed item in the feed displayed on the detail page for a lead record. This object is available in API version 18.0 and later.
LeadHistory	Represents the history of changes to the values in the fields of a lead.
LeadOwnerSharingRule	Rules that assign an owner to a lead.
LeadShare	A sharing entry on a Lead.
LeadStatus	The status of a Lead, such as Open, Qualified, or Converted.
LeadTag	Associates a word or short phrase with a Lead.
LimitAllocationPerApp	Represents a connected app quota for an API limit. This object is available in API version 30.0 and later.
LineitemOverride	Customizable forecast data for an opportunity line item.
ListView	Represents a list view. A list view specifies a set of records for an object, based on specific criteria. This object is available in API version 32.0 and later.
ListViewChart	Represents a graphical chart that's displayed on Salesforce1 list views. The chart aggregates data that is filtered based on the list view that's currently displayed. This object is available in API version 33.0 and later.
ListViewChartInstance	Retrieves metadata for all standard and custom charts for a given entity in context of a given list view. This object is available in API versions 34.0 and later.
LoginHistory	Represents the login history for all successful and failed login attempts for organizations and enabled portals. This object is available in API version 21.0 and later.
LookedUpFromActivity	Contains information about events and tasks related to an object through a custom lookup relationship.

Object	Description
MailmergeTemplate	A mail merge template (a Microsoft Word document) used for performing mail merges for your organization.
Metric	The Metric object represents the components of a goal metric such as its name, metric type, and current value.
MetricDataLink	The link between the metric and the data source, such as a report.
MetricDataLinkHistory	This read-only object contains historical information about changes that have been made to the MetricDataLink object.
MetricFeed	Represents a single feed item in the feed displayed on a Metric record.
MetricHistory	This read-only object contains historical information about changes that have been made to the Metric object.
MetricShare	Represents a sharing entry on a Metric object.
MilestoneType	Represents a milestone (required step in a customer support process). This object is available in API version 18.0 and later.
Name	Non-queryable object that provides information about foreign key traversals when the foreign key has more than one parent.
NamedCredential	Represents a named credential, which specifies the URL of a callout endpoint and its required authentication parameters in one definition. A named credential can be specified as an endpoint to simplify the setup of authenticated callouts. This object is available in API version 33.0 and later.
Network	Represents a community, which is a customizable public or private space where employees, end-customers, and partners can collaborate on best practices and business processes. Communities give you the opportunity to share information, records, and files with coworkers and related external stakeholders all in one place. This object is available in API version 26.0 and later.
NetworkActivityAudit	Represents an audit trail of moderation actions in Communities. This object is available in API version 30.0 and later.
NetworkMember	Represents a member of a community. Members can be either users in your company or external users with portal profiles. This object is available in API version 26.0 and later.
NetworkMemberGroup	Represents a group of members in a community. Members can be either users in your internal organization or external users assigned portal profiles. An administrator adds members to a community by adding a profile or a permission set, and any user with the profile or permission set becomes a member of the community. This object is available in API version 26.0 and later. Prior to API version 27.0, this object was called NetworkProfile.
NetworkModeration	Represents a flag on an item in a community. This object is available in API version 30.0 and later.

Object	Description
NetworkPageOverride	Represents information about custom pages used to override the default pages in communities. You can create Community Builder (Site.com Studio) or Visualforce pages and override the default pages in a community. Using custom pages allows you to create a more personalized experience for your users.
NetworkSelfRegistration	Represents the account that self-registering community members are associated with by default. Self-registering users in a community are required to be associated with an account, which the administrator must specify while setting up self-registration for the community. If an account isn't specified, Salesforce creates person accounts (when enabled) for self-registering users.
NewsFeed	Represents a single feed item on a user's home tab. A Chatter feed shows recent changes to records that the user is following. NewsFeed is available in API version 18.0 through API version 26.0. In API version 27.0 and later, NewsFeed is no longer available in the SOAP API.
Note	A note, which is text associated with an Attachment, Contact, Contract, Opportunity, or custom object.
NoteAndAttachment	Information about the notes and attachments for an object.
NoteTag	Associates a word or short phrase with a Note.
OAuthToken	Represents an OAuth access token for connected app authentication and can be used to create a user interface for token management. Each time a user grants access to an application, the application obtains a new access token.
ObjectPermissions	Represents the enabled object permissions for the parent PermissionSet. This object is available in API version 24.0 and later.
ObjectTerritory2AssignmentRule	Represents a territory assignment rule that's associated with an object, such as Account. ObjectTerritory2AssignmentRuleItem can only be created or deleted if the BooleanFilter field on its corresponding ObjectTerritory2AssignmentRule is null. Available only if Enterprise Territory Management has been enabled for your organization.
ObjectTerritory2AssignmentRuleItem	A single row of selection criteria for an ObjectTerritory2AssignmentRule object. ObjectTerritory2AssignmentRuleItem can only be created or deleted if the BooleanFilter field on its corresponding ObjectTerritory2AssignmentRule object is a null value. Available only if Enterprise Territory Management has been enabled for your organization.
ObjectTerritory2Association	Represents an association (by assignment) between a territory and an object record, such as an account. Available only if Enterprise Territory Management has been enabled for your organization.
OpenActivity	Contains information about events and tasks related to an object.
Opportunity	An opportunity, which is a sale or pending deal.
OpportunityCompetitor	A competitor on an Opportunity.
OpportunityContactRole	The role that a Contact plays on an Opportunity.

Object	Description
OpportunityFeed	Represents a single feed item in the feed displayed on the detail page for an opportunity record. This object is available in API version 18.0 and later.
OpportunityFieldHistory	The history of changes to the field values of an Opportunity. This object is available in versions 13.0 and later.
OpportunityHistory	The stage history of an Opportunity.
OpportunityLineItem	An opportunity line item, which is a member of the list of Product2 records associated with an Opportunity, along with other information about those products on that opportunity.
OpportunityLineItemSchedule	Information about the quantity, revenue distribution, and delivery dates for a particular OpportunityLineItem.
OpportunityOverride	Customizable forecast data for an opportunity.
OpportunityOwnerSharingRule	A rule that grants access to an opportunity to users other than the owner.
OpportunityPartner	A partner relationship between an Account and an Opportunity.
OpportunityShare	A sharing entry on an Opportunity.
OpportunitySplit	A related list for an Opportunity, which lets you divide sales credit across opportunity team members.
OpportunitySplitType	A customized label for one of the two default split types: revenue splits, which must total 100%, and overlay splits, which can total any percentage.
OpportunityStage	The stage of an Opportunity in the sales pipeline, such as New Lead, Negotiating, Pending, Closed, and so on.
OpportunityTag	Associates a word or short phrase with an Opportunity.
OpportunityTeamMember	An individual User on the opportunity team of a particular Opportunity.
Order	Represents an order associated with a contract or an account.
OrderFeed	Represents a single feed item in the feed displayed on an order.
OrderHistory	Represents historical information about changes that have been made to the standard fields of the associated order, or to any custom fields with history tracking enabled.
OrderItem	Represents an order product that your organization sells.
OrderItemFeed	Represents a single feed item in the feed displayed on the detail page for an order product record. An order product feed shows changes to an order product for fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to order products in Salesforce.
OrderItemHistory	Represents the history of changes to the values in the fields of an order product.
Organization	A business, company, or other organization.

Object	Description
OrgWideEmailAddress	Represents an organization-wide email address for user profiles.
OwnedContentDocument	Represents a file owned by a user. This object is available in API version 30.0 and later.
PackageLicense	Represents a license for an installed managed package.
Partner	The association between two particular accounts or between a particular Opportunity and an Account.
PartnerNetworkConnection	A connection in Salesforce to Salesforce.
PartnerNetworkRecordConnection	A record that is shared with a connection using Salesforce to Salesforce.
PartnerNetworkSyncLog	A log listing the status of record inserts and updates being replicated in Organization Sync.
PartnerRole	A role for an account Partner, such as a consultant or supplier.
Period	A fiscal period.
PermissionSet	A set of permissions that's used to grant additional permissions to one or more users without changing their profile. This object is available in API version 22.0 and later.
PermissionSetAssignment	Represents the association between a User and a PermissionSet. This object is available in API version 22.0 and later.
PlatformAction on page 1107	PlatformAction is a virtual read-only object that enables you to query for actions—such as standard and custom buttons, quick actions, and productivity actions—that should be displayed in a UI, given a user, a context, device format, and a record ID.
Pricebook2	A price book that contains the list of products (Product2 records) that your organization sells.
Pricebook2History	Represents historical information about changes that have been made to the standard fields of the associated Pricebook2, or to any custom fields with history tracking enabled. This object is available in API version 34.0 and later.
PricebookEntry	A product entry (an association between a Pricebook2 and Product2) in a price book.
ProcessDefinition	Represents the definition of a single approval process.
ProcessInstance	Represents an instance of a single, end-to-end approval process. Use this and the node, step, and workitem process instance objects to create approval history reports.
ProcessInstanceHistory	This read-only object shows all steps and pending approval requests associated with an approval process (ProcessInstance).
ProcessInstanceNode	Represents a step in an instance of an approval process. Compare to ProcessNode, which describes the step in a process definition. Use this object to retrieve approval history.

Standard Objects

Object	Description
ProcessInstanceStep	Represents one work item in an approval process (ProcessInstance).
ProcessInstanceWorkitem	Represents a user's pending approval request.
ProcessNode	Describes a step in a process definition. Compare to ProcessInstanceNode, which describes the step in a running process.
Product2	A product that your organization sells. A product is member of the list of items in a Pricebook2.
Product2Feed	Represents a single feed item in the feed displayed on the detail page for a product record. This object is available in API version 18.0 and later.
ProductEntitlementTemplate	Represents predefined terms of customer support (Entitlement) that users can add to products (Product2).
Profile	A profile, which defines a set of user permissions for performing different operations, such as querying, adding, updating, or deleting information.
ProfileSkill	Represents a profile skill, which describes a user's professional knowledge. This is a global record for the organization, and users are associated through the ProfileSkillUser object.
ProfileSkillEndorsement	Represents a detail relationship of ProfileSkillUser. An endorsement of a profile skill shows approval and support of another user's publicly declared skill.
ProfileSkillEndorsementFeed	Represents a single feed item in the feed displayed on the detail page for a ProfileSkillEndorsement record.
ProfileSkillEndorsementHistory	Represents the history of changes to the fields of a ProfileSkillEndorsement.
ProfileSkillFeed	Represents a single feed item in the feed displayed on the detail page for a profile skill.
ProfileSkillHistory	Represents the history of changes to the fields of a ProfileSkill.
ProfileSkillShare	Represents a sharing entry on a ProfileSkill.
ProfileSkillUser	Represents a detail relationship of User. The object connects profile skills with users.
ProfileSkillUserFeed	Represents a single feed item in the feed displayed on the detail page for a ProfileSkillUser record.
ProfileSkillUserHistory	Represents the history of changes to the fields of a ProfileSkillUser.
PushTopic	Represents a query that is the basis for notifying listeners of changes to records in an organization.
QuantityForecast	A quantity-based customizable forecast.
QuantityForecastHistory	Historical information about a quantity-based customizable forecast.
Question	Represents a question in a community that users can view and reply to.

Object	Description
QuestionDataCategorySelection	A data category selection represents a data category that classifies a question. This object can be used to associate a question with a data category from a data category group or to query the categorization for a question. It is available in API version 19.0 and later.
QuestionReportAbuse	Represents a user-reported abuse on a Question in a Chatter Answers community. This object is available in API version 24.0 and later.
QuestionSubscription	Represents a subscription for a user following a Question. This object is available in API version 24.0 and later.
QueueSubject	Associates sObject records with a specified queue.
Quote	Represents a quote, which is a record showing proposed prices for products and services. Quotes can be created from and synced with opportunities, and emailed as PDFs to customer. Available in API version 18.0 and later.
QuoteDocument	Represents a Quote in document format. Available in API version 18.0 and later.
QuoteLineItem	Represents a quote line item, which is a member of the list of Product2 products associated with a Quote, along with other information about those line items on that quote. Available in API version 18.0 and later.
RecentlyViewed	Represents a record that the current user has recently viewed or referenced (by viewing a related record).
RecordType	A record type.
RecordTypeLocalization	The translated value of a label for a record type.
Reply	Represents a reply that a user has submitted to a question in an answers community.
ReplyReportAbuse	Represents a user-reported abuse on a Reply in a Chatter Answers community. This object is available in API version 24.0 and later.
Report	Represents a report, a set of data that meets certain criteria, displayed in an organized way. Access is read-only. This object is available in API version 20.0 and later.
ReportFeed	Represents a single feed item in the feed displayed on a report. This object is available in API version 20.0 and later.
ReportTag	Associates a word or short phrase with a Report. This object is available in API version 20.0 and later.
ReputationLevel	Represents a reputation level defined for a community. This object is available in API version 32.0 and later.
ReputationPointsRule	Represents the reputation point rules for a community. Each rule specifies an action that community members can earn points from and the points associated with those actions in a particular community. This object is available in API version 32.0 and later.
RevenueForecast	A revenue-based customizable forecast.

Object	Description
RevenueForecastHistory	Historical information about a revenue-based customizable forecast.
RuleTerritory2Association	Represents a record-assignment rule and its association to an object, such as Account. Available only if Enterprise Territory Management has been enabled for your organization.
SamlSsoConfig	Represents a SAML Single Sign-On configuration. This object is available in API version 32.0 and later.
SearchPromotionRule	Represents a promoted search term, which is one or more keywords that you associate with a Salesforce Knowledge article. When a user's search query includes these keywords, the associated article is returned first in search results.
Scontrol	A custom s-control, which is custom content that is hosted by the system but executed by the client application.
ScontrolLocalization	The translated value of the field label for an s-control.
SelfServiceUser	A Contact who has been enabled to use your organization's Self-Service portal, where he or she can obtain online support.
ServiceContract	Represents a customer support contract (business agreement). This object is available in API version 18.0 and later.
ServiceContractFeed	Represents a single feed item in the feed displayed on the detail page for a service contract record. A service contract feed shows recent changes to a service contract for any fields that are tracked in feeds, as well as comments and posts about the record. This object is available in API version 23.0 and later.
ServiceContractHistory	Represents the history of changes to the values in the fields on a ServiceContract (customer support agreement). This object is available in API version 18.0 and later.
ServiceContractOwnerSharingRule	Represents the rules for sharing a ServiceContract (customer service agreement) with users other than the owner. This object is available in API version 18.0 and later.
ServiceContractShare	Represents a sharing entry on a ServiceContract (customer support agreement). This object is available in API version 18.0 and later.
SetupEntityAccess	Represents the enabled setup entity access settings (such as for Apex classes) for the parent PermissionSet. This object is available in API version 25.0 and later.
SignupRequest	Represents a request for a new Trialforce signup. This object is available in API version 27.0 and later.
Site	Represents a public website that is integrated with an Organization. This object is available in API version 18.0 and later. To access this object, Force.com Sites or Site.com must be enabled for your organization.
SiteHistory	Represents the history of changes to the values in the fields of a site. This object is available in API version 18.0 and later. To access this object, Force.com Sites or Site.com must be enabled for your organization.

Object	Description
SlaProcess	Represents an entitlement process associated with an Entitlement. This object is available in API version 19.0 and later.
Solution	A detailed description of a customer issue and the resolution of that issue.
SolutionFeed	Represents a single feed item in the feed displayed on the detail page for a solution record. This object is available in API version 18.0 and later.
SolutionHistory	History of changes to a solution.
SolutionStatus	The status of a Solution, such as Draft, Reviewed, and so on.
SolutionTag	Associates a word or short phrase with a Solution.
StaticResource	A static resource that can be used in Visualforce markup.
StreamingChannel	Represents a channel that is the basis for notifying listeners of generic Streaming API events. This is available from API version 29.0 or later.
TagDefinition	Defines the attributes of child Tag objects.
Task	An activity or to-do item to perform or that has been performed.
TaskFeed	Represents a single feed item in the feed on an Task. This object is available in API version 20.0 and later.
TaskPriority	The priority (importance) of a Task, such as High, Normal, or Low.
TaskRelation	Represents the relationship between a task and a lead, contacts, and other objects related to the task. If Shared Activities is enabled, this object doesn't support triggers, workflow, or data validation rules.
TaskStatus	The status of a Task, such as Not Started, Completed, or Closed.
TaskTag	Associates a word or short phrase with a Task.
TaskWhoRelation	TaskWhoRelation represents the relationship between a task and a lead or contacts. This derived object is a filtered version of the TaskRelation on page 1369 object; that is, IsParent is <i>true</i> and IsWhat is <i>false</i> . It doesn't represent relationships to accounts, opportunities, or other objects.
Territory	A territory to which users and accounts are assigned.
Territory2	Represents a sales territory. Available only if Enterprise Territory Management has been enabled for your organization.
Territory2Model	Represents a territory model. Available only if Enterprise Territory Management has been enabled for your organization.
Territory2ModelHistory	Represents the history of changes to the values in the fields on a territory model. Available only if Enterprise Territory Management has been enabled for your organization.
Territory2Type	Represents a category for territories (Territory2). Every Territory2 must have a Territory2Type. Available only if Enterprise Territory Management has been enabled for your organization.

Object	Description
ThirdPartyAccountLink	A list of third-party account links is generated when users of an organization authenticate using an external Auth. Provider. Use this object to list and revoke a given user's social sign-on connections (such as Facebook®).
Topic	Represents a topic on a Chatter post or record. This object is available in API version 28.0 and later.
TopicAssignment	Represents the assignment of a topic to a specific feed item or record. This object is available in API version 28.0 and later.
TopicFeed	Represents a single feed tracked change for a topic. This object is available in API version 29.0 and later.
TopicLocalization	Represents the translated version of a topic name. Topic localization applies only to navigational and featured topics in communities.
TwoFactorInfo	Stores a user's secret for all two-factor operations.
UndecidedEventRelation	Represents invitees with the status <code>Not Responded</code> for a given event.
User	A user in your organization.
UserAccountTeamMember	A single User on the default account team of another user.
UserConfigTransferButton	Represents the association between a Live Agent configuration and a live chat button. This association allows users associated with a specific configuration to transfer chats to a button queue.
UserConfigTransferSkill	Represents the association between a Live Agent configuration and a skill. This association allows users associated with a specific configuration to transfer chats to agents who have that skill.
UserFeed	Represents a single feed item in the feed displayed on a Chatter user profile feed. A user profile feed shows changes to a user record for fields that are tracked in feeds, as well as posts and comments about the record. This object is available in API version 18.0 and later.
UserLicense	A user license in your organization.
UserLogin	Represents the settings that affect a user's ability to log into an organization. This object is available in API version 29.0 and later.
UserMembershipSharingRule	Represents the rules for sharing user records from a source group to a target group. A user record contains details about a user. Users who are members of the source group can be shared with members of the target group.
UserPackageLicense	Represents a license for an installed managed package, assigned to a specific user.
UserPreference	A functional preference for a user in your organization.
UserProfile	Represents a Chatter user profile.
UserProfileFeed	Represents a user profile feed, which tracks all actions by a user on records that can be tracked in a feed. This feed is displayed on the user profile page.

Object	Description
	UserProfileFeed is available in API version 18.0 through API 26.0. In API version 27.0 and later, UserProfileFeed is no longer available in the SOAP API.
UserProvAccount	Represents information that links a Salesforce user account with an account in a third-party (target) system, such as Google, for users of connected apps with Salesforce user provisioning enabled.
UserProvAccountStaging	Temporarily stores user account information while a user completes the User Provisioning Wizard. This information that is stored in the UserProvAccount object when you click the button to collect and analyze accounts on the target system.
UserProvMockTarget	Represents an entity for testing user data before committing the data to a third-party system for user provisioning.
UserProvisioningConfig	Represents information for a flow to use during a user provisioning request process, such as the attributes for an update. The values of this object are read-only.
UserProvisioningLog	Represents messages generated during the process of provisioning users for third-party applications.
UserProvisioningRequest	Represents an individual provisioning request to create, update or delete a user account in a third-party service system (or another Salesforce organization).
UserProvisioningRequestOwnerSharingRule	Represents a rule for sharing a UserProvisioningRequest object with users other than the owner.
UserProvisioningRequestShare	Represents a sharing entry on a UserProvisioningRequest record.
UserRecordAccess	Represents a user's access to a set of records. This object is available in API version 24.0 and later.
UserRole	A role in your organization.
UserShare	Represents a sharing entry on a user record. This object is available in API version 26.0 and later.
UserTeamMember	A single User on the default opportunity team of another user.
UserTerritory	A single user who has been assigned to a territory.
UserTerritory2Association	Represents an association (by assignment) between a territory and a user record. Available only if Enterprise Territory Management has been enabled for your organization.
Vote	Represents a vote that a user has made on an Idea or a Reply.
WebLink	A Web link to an URL or Scontrol.
WebLinkLocalization	The translated value of the field label for a custom link to a URL or s-control.
WorkAccess	Used to grant or restrict user access to give badge definitions. Each badge definition record must have one WorkAccess record.
WorkAccessShare	WorkAccessShare is used to control Givers of WorkBadgeDefinition records.

Object	Description
WorkBadge	A WorkBadge record is created for each recipient of a WorkBadgeDefinition. Contains information about who the badge was given to and which badge was given.
WorkBadgeDefinition	The attributes of a badge including the badge name, description, and image. Each WorkBadge record must have a lookup to a WorkBadgeDefinition as badge attributes, such as badge name, badge description, and badge image, are derived from the WorkBadgeDefinition object.
WorkBadgeDefinitionHistory	Represents the history of changes to the values in the fields of a WorkBadgeDefinition object.
WorkBadgeDefinitionShare	Represents a sharing entry on a WorkBadgeDefinition object.
WorkCoaching	Represents a single coaching relationship between two users. One of the users is defined as the coach and the other is defined as a coachee. WorkCoaching is feed-enabled so there is a private feed available to the coach and coachee.
WorkCoachingFeed	Represents a single feed item in the feed on the detail page for a coaching record. A coaching feed shows recent changes to a lead record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to coaching in Salesforce.
WorkCoachingHistory	Represents the history of changes to the values in the fields of a WorkCoaching object.
WorkCoachingShare	Represents a sharing entry on a WorkCoaching object.
WorkFeedback	Answer to a specific question that the person was asked via a request for feedback. Also used to store offered feedback without linking it to a particular question.
WorkFeedbackHistory	This read-only object contains historical information about changes that have been made to the WorkFeedback object.
WorkFeedbackQuestion	Represents a question within a set of questions of either a free form text type, or a multiple choice.
WorkFeedbackQuestionHistory	Represents the history of changes to the values in the fields of a WorkFeedbackQuestion.
WorkFeedbackQuestionSet	Represents a set of questions that are being asked. The question set is used to link all the individual requests where different recipients were asked the same set of questions on the same subject.
WorkFeedbackQuestionSetHistory	This read-only object contains historical information about changes that have been made to the WorkFeedbackQuestionSet object.
WorkFeedbackQuestionSetShare	Represents a sharing entry on a WorkFeedbackQuestionSet.
WorkFeedbackQuestionShare	Represents a sharing entry on a WorkFeedbackQuestion.
WorkFeedbackRequest	In the feedback application, WorkFeedbackRequest represents a single feedback request on a subject or topic (question) to a single recipient. In the case of offered feedback, WorkFeedbackRequest represents feedback that is offered about a

Object	Description
	subject. In the performance application, WorkFeedbackRequest represents a request for feedback on a set of questions from a question set, on a subject—for the recipient to complete and submit.
WorkFeedbackRequestFeed	Represents a single feed item in the feed displayed on the feedback request detail page. The feedback request feed shows changes to a request for fields that are tracked in feeds, posts and comments about the request.
WorkFeedbackRequestHistory	Represents the history of changes to the values in the fields of a WorkFeedbackRequest.
WorkFeedbackRequestShare	Represents a sharing entry on a WorkFeedbackRequest.
WorkFeedbackShare	Represents a sharing entry on a WorkFeedback object.
WorkFeedbackTemplate	This object is reserved for future use.
WorkFeedbackTemplateShare	This object is reserved for future use.
WorkGoal	The WorkGoal object represents the components of a goal such as its description and associated metrics.
WorkGoalCollaborator	The WorkGoalCollaborator object represents collaborators on a WorkGoal object. Note that this doesn't include WorkGoal followers, which is handled by Chatter Feed Follow functionality.
WorkGoalCollaboratorHistory	This read-only object contains historical information about changes that were made to the WorkGoalCollaborator object.
WorkGoalFeed	Represents a single feed item in the feed displayed on the goal page for a Goal record. The goal feed shows changes to a goal for fields that are tracked in feeds, posts, and comments about the goal, as well as updates on metrics.
WorkGoalHistory	This read-only object contains historical information about changes that have been made to the WorkGoal object.
WorkGoalLink	Represents the relationship between two goals (many to many relationship).
WorkGoalShare	Represents a sharing entry on a WorkGoal object.
WorkPerformanceCycle	WorkPerformanceCycle represents feedback that is gathered for the purpose of assessing the performance of a specific set of employees.
WorkPerformanceCycleFeed	Represents a single feed item in the feed that is displayed on a Work.com Performance detail page.
WorkPerformanceCycleHistory	Represents the history of changes to the values in the fields of a WorkPerformanceCycle.
WorkPerformanceCycleShare	Represents a sharing entry on a WorkPerformanceCycle object.
WorkReward	Used to store reward codes tied to a Reward Fund. Reward Funds must have at least one WorkReward record.
WorkRewardFund	Represents a Reward Fund and describes the Reward Fund attributes.

Object	Description
WorkRewardFundHistory	Represents the history of changes to the values in the fields of a WorkRewardFund object.
WorkRewardFundShare	Share records for WorkRewardFund.
WorkRewardFundType	Represents the type of WorkRewardFund object.
WorkRewardFundTypeHistory	Represents the history of changes to the values in the fields of a WorkRewardFundType object.
WorkRewardFundTypeShare	Represents a sharing entry on a WorkRewardFundType.
WorkRewardHistory	Represents the history of changes to the fields of a WorkReward.
WorkRewardShare	Share records for WorkReward object.
WorkThanks	Represents the source and message of a thanks post.
WorkThanksShare	Share records for WorkThanks object.

 **Note:** The Product and Pricebook objects are no longer available and have been removed. Requests containing them are refused, and responses do not contain them. Use Product2 and Pricebook2 instead.

 **Note:** Force.com includes the following standard objects: AcceptedEventRelation, Account, AccountContactRole, AccountFeed, AccountHistory, AccountPartner, AccountShare, ActivityHistory, AdditionalNumber, AggregateResult, Announcement, ApexClass, ApexComponent, ApexPage, ApexTestQueueItem, ApexTestResult, ApexTrigger, AppMenuItem, AssignmentRule, AsyncApexJob, AttachedContentDocument, Attachment, AuthSession, BrandTemplate, BusinessHours, BusinessProcess, CallCenter, CategoryNode, ChatterActivity, ClientBrowser, CollaborationGroup, CollaborationGroupFeed, CollaborationGroupMember, CollaborationGroupMemberRequest, CollaborationInvitation, CombinedAttachment, Community, Contact, ContactFeed, ContactHistory, ContactShare, ContentDocument, ContentDocumentFeed, ContentDocumentHistory, ContentDocumentLink, ContentNote, ContentVersion, ContentVersionHistory, CronJobDetail, CronTrigger, Dashboard, DashboardComponent, DashboardComponentFeed, DashboardFeed, DeclinedEventRelation, Document, DocumentAttachmentMap, Domain, DomainSite, EmailServicesAddress, EmailServicesFunction, EmailStatus, EmailTemplate, EntitySubscription, Event, EventFeed, EventRelation, FeedComment, FeedItem, FeedLike, FeedTrackedChange, FieldPermissions, FiscalYearSettings, Folder, ForecastShare, Group, GroupMember, HashtagDefinition, Holiday, Idea, IdeaComment, LoginIp, MailmergeTemplate, MobileDeviceRegistrar, Name, Note, NoteAndAttachment, ObjectPermissions, OpenActivity, OrgWideEmailAddress, OwnedContentDocument, Period, PermissionSet, PermissionSetAssignment, PermissionSetLicense, PermissionSetLicenseAssign, ProcessDefinition, ProcessInstance, ProcessInstanceHistory, ProcessInstanceNode, ProcessInstanceStep, ProcessInstanceWorkitem, ProcessNode, Profile, PushTopic, QueueSubject, RecentlyViewed, RecordType, Report, ReportFeed, Scontrol, SetupEntityAccess, Site, SiteFeed, SiteHistory, StaticResource, Task, TaskFeed, TaskPriority, TaskStatus, Topic, TopicAssignment, TopicFeed, UndecidedEventRelation, User, UserFeed, UserLicense, UserPreference, UserProfile, UserRecordAccess, UserRole, UserShare, Vote.

AcceptedEventRelation

Represents invitees with the status `Accepted` for a given event.

This object is available in API versions 29.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
EventId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the event.
RelationId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the invitee.
RespondedDate	Type dateTime Properties Filter, Nillable, Sort Description Indicates the most recent date and time when the invitee accepted an invitation to the event.
Response	Type string Properties Filter, Group, Nillable, Sort Description Indicates the content of the response field. Label is <code>Comment</code>.
Type	Type string Properties Filter, Group, Nillable, Sort Description Indicates whether the invitee is a user, lead or contact, or resource.

Usage

Query invitees who have accepted an invitation to an event

```
SELECT eventId, type, response FROM AcceptedEventRelation WHERE eventId='00UTD000000ZH5LA'
```

Account

Represents an individual account, which is an organization or person involved with your business (such as customers, competitors, and partners).

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `merge()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can access their own accounts and any account shared with them.

Fields

Field Name	Details
AccountNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Account number assigned to this account (not the unique, system-generated ID assigned during creation). Maximum size is 40 characters.
AccountSource	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The source of the account record. For example, <i>Advertisement</i>, <i>Data.com</i>, or <i>Trade Show</i>. The source is selected from a picklist of available values, which are set by an administrator. Each picklist value can have up to 40 characters.
AnnualRevenue	Type currency Properties Create, Filter, Nillable, Sort, Update

Field Name	Details
	Description Estimated annual revenue of the account.
BillingAddress	Type address Properties Filter, Nillable Description The compound form of the billing address. Read-only. See Address Compound Fields for details on compound address fields.
BillingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the billing address of this account. Maximum size is 40 characters.
BillingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the billing address of this account. Maximum size is 80 characters.
BillingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the account's billing address.
BillingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLongitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
BillingLongitude	Type double

Field Name	Details
	Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLatitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
BillingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the billing address of this account. Maximum size is 20 characters.
BillingState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the billing address of this account. Maximum size is 80 characters.
BillingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the account's billing address.
BillingStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Street address for the billing address of this account.
CleanStatus	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates the record's clean status as compared with Data.com. Values are: <code>Matched</code>, <code>Different</code>, <code>Acknowledged</code>, <code>NotFound</code>, <code>Inactive</code>, <code>Pending</code>, <code>SelectMatch</code>, or <code>Skipped</code>.

Field Name	Details
	Several values for <code>CleanStatus</code> display with different labels on the account record detail page. • Matched displays as <code>In Sync</code> • Acknowledged displays as <code>Reviewed</code> • Pending displays as <code>Not Compared</code>
<code>ConnectionReceivedId</code>	Type reference Properties Filter, Nillable Description ID of the <code>PartnerNetworkConnection</code> that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
<code>ConnectionSentId</code>	Type reference Properties Filter, Nillable Description ID of the <code>PartnerNetworkConnection</code> that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the <code>ConnectionSentId</code> field is no longer supported. The <code>ConnectionSentId</code> field is still visible, but the value is null. You can use the new <code>PartnerNetworkRecordConnection</code> object to forward records to connections.
<code>Description</code>	Type textarea Properties Create, Nillable, Update Description Text description of the account. Limited to 32,000 KB.
<code>DunsNumber</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The Data Universal Numbering System (D-U-N-S) number is a unique, nine-digit number assigned to every business location in the Dun & Bradstreet database that has a unique, separate, and distinct operation. D-U-N-S numbers are used by industries and organizations around the world as a global standard for business identification and tracking. Maximum size is 9 characters.

Field Name	Details
	 Note: This field is only available to organizations that use Data.com Prospector or Data.com Clean.
Fax	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Fax number for the account.
Industry	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description An industry associated with this account. Maximum size is 40 characters.
IsCustomerPortal	Type boolean Properties Defaulted on create, Filter, Update Description Indicates whether the account has at least one contact enabled to use the organization's Customer Portal (<code>true</code>) or not (<code>false</code>). This field is available if Customer Portal is enabled OR Communities is enabled and you have Customer Portal licenses. If you change this field's value from <code>true</code> to <code>false</code>, you can disable up to 100 Customer Portal users associated with the account and permanently delete all of the account's Customer Portal roles and groups. You can't restore deleted Customer Portal roles and groups. This field can be updated in API version 16.0 and later.  Tip: We recommend that you only update up to 50 contacts simultaneously when changing the accounts on contacts enabled for a Customer Portal or partner portal. We also recommend that you make this update during times outside of your organization's business hours.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.

Field Name	Details
IsPartner	Type boolean Properties Defaulted on create, Filter, Update Description Indicates whether the account has at least one contact enabled to use the organization's partner portal (<code>true</code>) or not (<code>false</code>). This field is available if partner relationship management (partner portal) is enabled OR Communities is enabled and you have partner portal licenses. If you change this field's value from <code>true</code> to <code>false</code>, you can disable up to 15 partner portal users associated with the account and permanently delete all of the account's partner portal roles and groups. You can't restore deleted partner portal roles and groups. Disabling a partner portal user in the Salesforce user interface or the API does not change this field's value from <code>true</code> to <code>false</code>. Even if this field's value is <code>false</code>, you can enable a contact on an account as a partner portal user via the API. This field can be updated in API version 16.0 and later.  Tip: We recommend that you only update up to 50 contacts simultaneously when changing the accounts on contacts enabled for a Customer Portal or partner portal. We also recommend that you make this update during times outside of your organization's business hours.
IsPersonAccount	Type boolean Properties Defaulted on create, Filter Description Read only. Label is Is Person Account. Indicates whether this account has a record type of Person Account (<code>true</code>) or not (<code>false</code>).
Jigsaw	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description References the ID of a company in Data.com. If an account has a value in this field, it means that the account was imported from Data.com. If the field value is <code>null</code>, the account was not imported from Data.com. Maximum size is 20 characters. Available in API version 22.0 and later. Label is Data.com Key.  Important: The <code>Jigsaw</code> field is exposed in the API to support troubleshooting for import errors and reimporting of corrected data. Do not modify the value in the <code>Jigsaw</code> field.

Field Name	Details
LastActivityDate	Type date Properties Filter, Group, Nillable, Sort Description Value is one of the following, whichever is the most recent: • Due date of the most recent event logged against the record. • Due date of the most recently closed task associated with the record.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
MasterRecordId	Type reference Properties Filter, Group, Nillable, Sort Description If this object was deleted as the result of a merge, this field contains the ID of the record that was kept. If this object was deleted for any other reason, or has not been deleted, the value is <code>null</code>.
NaicsCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The six-digit North American Industry Classification System (NAICS) code is the standard used by business and government to classify business establishments into industries, according to their economic activity for the purpose of collecting, analyzing, and publishing statistical data related to the U.S. business economy. Maximum size is 8 characters.

Field Name	Details
	 Note: This field is only available to organizations that use Data.com Prospector or Data.com Clean.
NaicsDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on its NAICS code. Maximum size is 120 characters.  Note: This field is only available to organizations that use Data.com Prospector or Data.com Clean.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Label is Account Name. Name of the account. Maximum size is 255 characters. If the account has a record type of Person Account: • This value is the concatenation of the <code>FirstName</code>, <code>MiddleName</code>, <code>LastName</code>, and <code>Suffix</code> of the associated person contact. • You can't modify this value.
NumberOfEmployees	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Label is Employees. Number of employees working at the company represented by this account. Maximum size is eight digits.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The ID of the user who currently owns this account. Default value is the user logged in to the API to perform the create. If you have set up account teams in your organization, updating this field has different consequences depending on your version of the API:

Field Name	Details
	- For API version 12.0 and later, sharing records are kept, as they are for all objects. - For API version before 12.0, sharing records are deleted. - For API version 16.0 and later, users must have the “Transfer Record” permission in order to update (transfer) account ownership using this field.
Ownership	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Ownership type for the account, for example Private, Public, or Subsidiary.
ParentId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the parent object, if any.
Phone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Phone number for this account. Maximum size is 40 characters.
PhotoUrl	Type url Properties Filter, Group, Nillable, Sort Description Path to be combined with the URL of a Salesforce instance (for example, https://na1.salesforce.com/) to generate a URL to request the social network profile image associated with the account. Generated URL returns an HTTP redirect (code 302) to the social network profile image for the account. Blank if Social Accounts and Contacts isn't enabled for the organization or if Social Accounts and Contacts is disabled for the requesting user.
Rating	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The account's prospect rating, for example Hot, Warm, or Cold.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object.
Salutation	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Honorific added to the name for use in letters, etc.
ShippingAddress	Type address Properties Filter, Nillable Description The compound form of the shipping address. Read-only. See Address Compound Fields for details on compound address fields.
ShippingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details of the shipping address for this account. City maximum size is 40 characters
ShippingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details of the shipping address for this account. Country maximum size is 80 characters.
ShippingCountryCode	Type picklist

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the account's shipping address.
ShippingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLongitude</code> to specify the precise geolocation of a shipping address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
ShippingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLatitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
ShippingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details of the shipping address for this account. Postal code maximum size is 20 characters.
ShippingState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details of the shipping address for this account. State maximum size is 80 characters.
ShippingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the account's shipping address.

Field Name	Details
ShippingStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description The street address of the shipping address for this account. Maximum of 255 characters.
Sic	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Standard Industrial Classification code of the company's main business categorization, for example, 57340 for Electronics. Maximum of 20 characters.
SicDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on its SIC code. Maximum length is 80 characters.
Site	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Name of the account's location, for example <code>Headquarters</code> or <code>London</code>. Label is Account Site. Maximum of 80 characters.
TickerSymbol	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The stock market symbol for this account. Maximum of 20 characters.
Tradestyle	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description A name, different from its legal name, that an organization may use for conducting business. Similar to “Doing business as” or “DBA”. Maximum length is 255 characters.  Note: This field is only available to organizations that use Data.com Prospector or Data.com Clean.
Type	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Type of account, for example, Customer, Competitor, or Partner.
Website	Type url Properties Create, Filter, Group, Nillable, Sort, Update Description The website of this account. Maximum of 255 characters.
YearStarted	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The date when an organization was legally established. Maximum length is 4 characters.  Note: This field is only available to organizations that use Data.com Prospector or Data.com Clean.

IsPersonAccount Fields

These fields are the subset of person account fields that are contained in the child person contact record of each person account. If the `IsPersonAccount` field has the value `false`, the following fields have a null value and can't be modified. If `true`, the fields contain the value indicated in the Description column in the following table and can be modified.

Person accounts are not enabled by default.

Field Name	Details
FirstName	Type string

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description First name of the person for a person account. Maximum size is 40 characters.
LastName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Last name of the person for a person account. Required if the record type is a person account record type. Maximum size is 80 characters.
MiddleName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Middle name of the person for a person account. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.
PersonAssistantName	Type string Properties Create, Filter, Nillable, Update Description The person account's assistant name. Label is Assistant. Maximum size is 40 characters.
PersonAssistantPhone	Type phone Properties Create, Filter, Nillable, Update Description The person account's assistant phone. Label is Asst. Phone. Maximum size is 40 characters.
PersonBirthDate	Type date Properties Create, Filter, Nillable, Update Description The assistant name. Label is Birthdate.

Field Name	Details
	 Note: The year portion of the <code>PersonBirthDate</code> field is ignored in filter criteria, including report filters, list view filters, and SOQL queries. For example, the following SOQL query returns person accounts with birthdays later in the year than today: <pre>SELECT FirstName, LastName, PersonBirthDate FROM Account WHERE Birthdate > TODAY</pre>
PersonContactId	Type reference Properties Filter, Nillable, Update Description The ID for the contact associated with this person account. Label is Contact ID.
PersonDepartment	Type string Properties Create, Filter, Nillable, Update Description The department. Label is Department. Maximum size is 80 characters.
PersonEmail	Type email Properties Create, Filter, Nillable, Update Description Email address for thisperson account. Label is Email.
PersonEmailBouncedDate	Type dateTime Properties Create, Filter, Nillable, Update Description If bounce management is activated and an email sent to the person account bounces, the date and time the bounce occurred.
PersonEmailBouncedDate	Type string Properties Create, Filter, Nillable, Update

Field Name	Details
	Description If bounce management is activated and an email sent to the person account bounces, the reason the bounce occurred
PersonHasOptedOutOfEmail	Type boolean Properties Create, Filter, Nillable, Update Description Indicates whether the person account has opted out of email (<code>true</code>) or not (<code>false</code>). Label is Email Opt Out .
PersonHomePhone	Type phone Properties Create, Filter, Nillable, Update Description The home phone number for this person account. Label is Home Phone .
PersonLastCURequestDate	Type dateTime Properties Create, Filter, Nillable, Update Description The last date that this person account was requested. Label is Last Stay-in-Touch Request Date .
PersonLastCUUpdateDate	Type dateTime Properties Create, Filter, Nillable, Update Description The last date a person account was updated. Label is Last Stay-in-Touch Save Date .
PersonLeadSource	Type picklist Properties Create, Filter, Nillable, Update Description The person account's lead source. Label is Lead Source .

Field Name	Details
PersonMailingAddress	Type address Properties Filter, Nillable Description The compound form of the person account mailing address. Read-only. See Address Compound Fields for details on compound address fields.
PersonMailingCity	Type string Properties Create, Filter, Nillable, Update Description Details about the person account's mailing city. Labels are Mailing City, Mailing Country, Postal Code, and State. Maximum size for city and country is 40 characters. Maximum size for postal code and state is 20 characters.
PersonMailingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>PersonMailingLongitude</code> to specify the precise geolocation of a person account's mailing address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
PersonMailingLongitude	Type double Properties Create, Filter, , Nillable, Sort, Update Description Used with <code>PersonMailingLatitude</code> to specify the precise geolocation of a person account's mailing address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
PersonMailingStreet	Type textarea Properties Create, Filter, Nillable, Update Description The mailing street address for this person account. Label is Mailing Street. Maximum size is 255 characters.

Field Name	Details
PersonMobilePhone	Type phone Properties Create, Filter, Nillable, Update Description The mobile phone number for this person account. Label is Mobile.
- PersonOtherCity - PersonOtherCountry - PersonOtherPostalCode - PersonOtherState	Type string Properties Create, Filter, Nillable, Update Description Details about the alternate address for this person account. Labels are Other City, Other Country, Other Zip/Postal Code, and Other State.
- PersonOtherCountryCode - PersonOtherStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country or state code for the alternate address of the person account.
PersonOtherLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>PersonOtherLongitude</code> to specify the precise geolocation of a person account's alternate address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
PersonOtherLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>PersonOtherLatitude</code> to specify the precise geolocation of a person account's alternate address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
PersonOtherPhone	Type phone

Field Name	Details
	Properties Create, Filter, Nillable, Update Description The alternate phone number for this person account. Label is Other Phone .
PersonOtherStreet	Type textarea Properties Create, Filter, Nillable, Update Description The person account's alternate street address. Label is Other Street .
PersonTitle	Type string Properties Create, Filter, Nillable, Update Description The person account's title. Label is Title . Maximum size is 80 characters.
Suffix	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Name suffix of the person for a person account. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.

 **Note:** If you are importing Account data into Salesforce and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself.

Usage

Use this object to query and manage accounts in your organization. Client applications can create, update, delete, or query Attachment records associated with an account via the API.

Client applications can also create or update account objects by converting a Lead via the `convertLead()` call.

If the values in the `IsPersonAccount` Fields are not null, you can't change `IsPersonAccount` to `false`, or an error occurs.

AccountCleanInfo

Stores the metadata Data.com Clean uses to determine an account record's clean status. Helps you automate the cleaning or related processing of account records. AccountCleanInfo includes a number of bit vector fields.

- `CleanedBy` indicates who (a user) or what (a Clean job) cleaned the account record.
- `IsDifferent` indicates whether or not a field on the account record has a value that differs from the corresponding field on the matched Data.com record.
- `IsFlaggedWrong` indicates whether or not a field on the account record has a value that is flagged as wrong to Data.com.
- `IsReviewed` indicates whether or not a field on the account record is in a `Reviewed` state, which means that the value was reviewed by a user but not accepted.

Their individual bits are defined here.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
<code>AccountId</code>	Type reference Properties Filter, Group, Sort Description The unique, system-generated ID assigned when the account record was created.
<code>AccountSite</code>	Type string Properties Filter, Group, Nillable, Sort Description Information about the account's location, such as single location, headquarters, or branch.
<code>Address</code>	Type address Properties Filter, Nillable Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.

Field Name	Details
AnnualRevenue	Type currency Properties Filter, Nillable, Sort Description Estimated annual revenue of the account.
City	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the account.
CleanedByJob	Type boolean Properties Filter Description Indicates whether the account record was cleaned by a Data.com Clean job (<code>true</code>) or not (<code>false</code>).
CleanedByUser	Type boolean Properties Filter Description Indicates whether the account record was cleaned by a Salesforce user (<code>true</code>) or not (<code>false</code>).
CompanyName	Type string Properties Filter, Group, Nillable, Sort Description The name of the company.
CompanyStatusDataDotCom	Type picklist Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description The status of the company per Data.com. Values are: Company is In Business per Data.com or Company is Out of Business per Data.com.
Country	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the account.
DandBCompanyDunsNumber	Type string Properties Filter, Group, Nillable, Sort Description The D-U-N-S Number on the D&B Company record (if any) that is linked to the account.
DataDotComId	Type string Properties Filter, Group, Nillable, Sort Description The ID Data.com maintains for the company.
Description	Type textarea Properties Nillable Description A description of the account.
DunsNumber	Type string Properties Filter, Group, Nillable, Sort Description The Data Universal Numbering System (D-U-N-S) number is a unique, nine-digit number assigned to every business location in the Dun & Bradstreet database that has a unique, separate, and distinct operation. D-U-N-S numbers are used

Field Name	Details
	by industries and organizations around the world as a global standard for business identification and tracking.
DunsRightMatchConfidence	Type int Properties Filter, Group, Nillable, Sort Description The account's DUNSRight confidence code.
DunsRightMatchGrade	Type string Properties Filter, Group, Nillable, Sort Description The account's DUNSRight match grade.
Fax	Type phone Properties Filter, Group, Nillable, Sort Description The account's fax number.
Industry	Type picklist Properties Filter, Group, Nillable, Sort Description The industry the account belongs to.
IsDifferentAccountSite	Type boolean Properties Filter Description Indicates whether the account's <code>AccountSite</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentAnnualRevenue	Type boolean

Field Name	Details
	Properties Filter
	Description Indicates whether the account's <code>AnnualRevenue</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentCity</code>	Type boolean
	Properties Filter
	Description Indicates whether the account's <code>City</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentCompanyName</code>	Type boolean
	Properties Filter
	Description Indicates whether the account's <code>AccountName</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentCountry</code>	Type boolean
	Properties Filter
	Description Indicates whether the account's <code>Country</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentCountryCode</code>	Type boolean
	Properties Filter
	Description Indicates whether the account's <code>Country Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentDandBCompanyDunsNumber</code>	Type boolean
	Properties Filter

Field Name	Details
	Description Indicates whether the account's <code>DandBCompanyID</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentDescription</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Description</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentDunsNumber</code>	Type boolean Properties Filter Description Indicates whether the account's <code>DunsNumber</code> field value is different from the D-U-N-S Number on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentFax</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Fax</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentIndustry</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Industry</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentNaicsCode</code>	Type boolean Properties Filter

Field Name	Details
	Description Indicates whether the account's <code>NaicsCode</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentNaicsDescription</code>	Type boolean Properties Filter Description Indicates whether the account's <code>NaicsDescription</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentNumberOfEmployees</code>	Type boolean Properties Filter Description Indicates whether the account's <code>NumberOf Employees</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentOwnership</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Ownership</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentPhone</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Phone</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentPostalCode</code>	Type boolean Properties Filter

Field Name	Details
	Description Indicates whether the account's <code>PostalCode</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentSic</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Sic</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentSicDescription</code>	Type boolean Properties Filter Description Indicates whether the account's <code>SicDescription</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentState</code>	Type boolean Properties Filter Description Indicates whether the account's <code>State</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentStateCode</code>	Type boolean Properties Filter Description Indicates whether the account's <code>State Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentStreet</code>	Type boolean Properties Filter

Field Name	Details
	Description Indicates whether the account's <code>State</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentTickerSymbol</code>	Type boolean Properties Filter Description Indicates whether the account's <code>TickerSymbol</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentTradestyle</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Tradestyle</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentWebsite</code>	Type boolean Properties Filter Description Indicates whether the account's <code>Website</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentYearStarted</code>	Type boolean Properties Filter Description Indicates whether the account's <code>YearStarted</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongAccountSite</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>AccountSite</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongAddress</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Address</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongAnnualRevenue</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>AnnualRevenue</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongCompanyName</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>CompanyName</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongDescription</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Description</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongDunsNumber</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>DunsNumber</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongFax</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Fax</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongIndustry</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Industry</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongNaicsCode</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>NaicsCode</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongNaicsDescription</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>NaicsDescription</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongNumberOfEmployees</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>NumberOfEmployees</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongOwnership</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Ownership</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongPhone</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Phone</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongSic</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Sic</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongSicDescription</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>SicDescription</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongTickerSymbol</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>TickerSymbol</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongTradestyle</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Tradestyle</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongWebsite</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Website</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongYearStarted</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>YearStarted</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsInactive</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the account has been reported to Data.com as <i>Inactive</i> (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedAccountSite</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>AccountSite</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedAddress</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Address</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedAnnualRevenue</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>AnnualRevenue</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedCompanyName</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>CompanyName</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedDandBCompanyDunsNumber</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>DandBCompanyID</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedDescription</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>Description</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedDunsNumber</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>DunsNumber</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedFax</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Fax</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedIndustry</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Industry</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedNaicsCode</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>NaicsCode</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedNaicsDescription</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>NaicsDescription</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedNumberOfEmployees</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>NumberOfEmployees</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedOwnership</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Ownership</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedPhone</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Phone</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedSic</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Sic</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedSicDescription</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the account's <code>SicDescription</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedTickerSymbol</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>TickerSymbol</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedTradestyle</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Tradestyle</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedWebsite</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>Website</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedYearStarted</code>	Type boolean Properties Filter, Update Description Indicates whether the account's <code>YearStarted</code> field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
<code>LastMatchedDate</code>	Type dateTime Properties Filter, Sort Description The date the account record was last matched and linked to a Data.com record.

Field Name	Details
LastStatusChangedById	Type reference Properties Filter, Group, Nillable, Sort Description The ID of who or what last changed the record's <code>Clean Status</code> field value: a Salesforce user or a Clean job.
LastStatusChangedDate	Type dateTime Properties Filter, Nillable, Sort Description The date on which the record's <code>Clean Status</code> field value was last changed.
Latitude	Type double Properties Filter, Nillable, Sort Description Used with <code>Longitude</code> to specify the precise geolocation of a billing address. Data not currently provided.
Longitude	Type double Properties Filter, Nillable, Sort Description Used with <code>Latitude</code> to specify the precise geolocation of a billing address. Data not currently provided.
NaicsCode	Type string Properties Filter, Group, Nillable, Sort Description The six-digit North American Industry Classification System (NAICS) code is the standard used by business and government to classify business establishments into industries, according to their economic activity for the purpose of collecting, analyzing, and publishing statistical data related to the U.S. business economy.

Field Name	Details
NaicsDescription	Type string Properties Filter, Group, Nillable, Sort Description A brief description of an organization's line of business, based on its NAICS code.
Name	Type string Properties Filter, Group, Sort, Update Description Field label is Account Clean Info Name. The name of the account. Maximum size is 255 characters.
NumberOfEmployees	Type int Properties Filter, Group, Nillable, Sort Description The number of employees working at the account.
Ownership	Type picklist Properties Filter, Group, Nillable, Sort Description Ownership type for the account, for example Private, Public, or Subsidiary.
Phone	Type phone Properties Filter, Group, Nillable, Sort Description The phone number for the account.
PostalCode	Type string Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description Details for the billing address of the account.
Sic	Type string Properties Filter, Group, Nillable, Sort Description Standard Industrial Classification code of the company's main business categorization, for example, 57340 for Electronics.
SicDescription	Type string Properties Filter, Group, Nillable, Sort Description A brief description of an organization's line of business, based on its SIC code.
State	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the account.
Street	Type textarea Properties Filter, Group, Nillable, Sort Description Details for the billing address of the account.
TickerSymbol	Type string Properties Filter, Group, Nillable, Sort Description The stock market symbol for the account.
Tradestyle	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description A name, different from its legal name, that an organization can use for conducting business. Similar to “Doing business as” (DBA).
Website	Type url Properties Filter, Group, Nillable, Sort Description The website of the account.
YearStarted	Type string Properties Filter, Group, Nillable, Sort Description The year the company was established or the year when current ownership or management assumed control of the company.

Usage

Create triggers that read AccountCleanInfo fields to help automate the cleaning or related processing of account records. For example:

- Keep account records' status `InSync` if the only difference from matched records is the `Phone` format (for example, `(415) 353-8000` on the account record versus `415 353 8000` on the matched Data.com record).

```
trigger AccountPhoneTrigger on Account (before update) {

    for (Account account: Trigger.new) {
        Account oldAccount = Trigger.oldMap.get(account.ID);
        if (account.CleanStatus == 'Different') {
            List cleanInfo = [Select Id, IsDifferentPhone, IsReviewedPhone, Phone from
AccountCleanInfo where AccountId = :account.Id];
            if (cleanInfo.size() > 0 && cleanInfo[0].IsDifferentPhone &&
cleanInfo[0].Phone.StartsWith('+')) {
                // if Data.com phone number is marked Different but starts with '+',
ignore this
                // and set the status to "Reviewed"
                AccountCleanInfo cleanInfoToUpdate = new AccountCleanInfo();
                cleanInfoToUpdate.Id = cleanInfo[0].Id;
                cleanInfoToUpdate.IsReviewedPhone = true;
                update cleanInfoToUpdate;
                account.CleanStatus = 'Reviewed';
            }
        }
    }
}
```

```
}  
  }  
}
```

- Create a customized set of `Industry` field values for accounts. Use triggers to map values from fields on imported or cleaned records onto a standard set of values.
- Read the `CleanStatus` field value on the Account object. If that value is `Different`, but a Salesforce record has no street address value, update the record's status to `Not Compared`.

AccountContactRole

Represents the role that a Contact plays on an Account.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>AccountId</code>	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Account.
<code>ContactId</code>	Type reference Properties Create, Filter, Group, Sort, Update Description Required. ID of the Contact associated with this account.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter

Field	Details
	Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
<code>IsPrimary</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Specifies whether the Contact plays the primary role on the Account (<code>true</code>) or not (<code>false</code>). Note that each account has only one primary contact role. Label is Primary . Default value is <code>false</code> .
<code>Role</code>	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Name of the role played by the Contact on this Account, such as Decision Maker, Approver, Buyer, and so on. Must be unique—there can't be multiple records in which the <code>AccountId</code> , <code>ContactId</code> , and <code>Role</code> values are identical. Different contacts can play the same role on the same account. A contact can play different roles on the same account.

Usage

Use this object to define the role that a Contact plays on a given Account within the context of a specific Opportunity.

AccountFeed

Represents a single feed item on an account record detail page.

An account feed shows changes to an account record for fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to accounts in Salesforce. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"

- “Modify All” on the Account object
- “Moderate Chatter”



Note: Users with the “Moderate Chatter” permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of AccountFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.

Field	Details
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference

Field	Details
	Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an FeedItem: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort

Field	Details
	Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code> .
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community , a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: • <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. • <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code> : • Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. • For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. • You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the account record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort

Field	Details
	Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed.

Field	Details
	• ProfileSkillPost—generated when a skill is added to a user’s Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for an account record.

AccountHistory

Represents the history of changes to the values in the fields of an account. This object is available in versions 11.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
AccountId	Type reference Properties Filter, Group, Sort Description ID of the Account. Label is Account ID.
NewValue	Type anyType Properties Nillable, Sort

Field	Details
	Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this object to identify changes to an account.

This object respects field level security on the parent object.

AccountOwnerSharingRule

Represents the rules for sharing an account with a User other than the owner.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
AccountAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Update Description A value that represents the type of sharing being allowed. The possible values are: • Read

Field	Details
	- Edit - All (This value isn't valid for creating or updating.)
CaseAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of access granted to the target Group for all child cases. The possible values are: - None - Read - Edit
ContactAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A value that represents the type of access granted to the target Group, UserRole, or User for any associated contacts. The possible values are: - None - Read - Edit  Note: When DefaultContactAccess is set to Controlled by Parent, you can't create or update this field.
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Details
	Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. An Account owned by a User in the source Group triggers the rule to give access.
OpportunityAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of access granted to the target Group for any associated Opportunity. The possible values are: • None • Read • Edit
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.
UserOrGroupId	Type reference

Field	Details
	Properties Create, Filter, Group, Sort
	Description The ID representing the User or Group being granted access.

Usage

Use this object to manage the sharing rules for accounts. General sharing and territory management-related sharing use this object. For example, the following code creates an account owner sharing rule between two public groups, which can also contain portal users.

```
AccountOwnerSharingRule rule = new AccountOwnerSharingRule();
rule.setName("RuleName"); // Set the sharing rule name
rule.setDeveloperName("RuleDeveloperName"); // Set the sharing rule developer name
rule.setGroupId("00Gx000000000000"); // Set the group of users to share records from
rule.setUserOrGroupId("00Gx000000000001"); // Set the group of users to share records to
rule.setAccountAccessLevel("Edit");
rule.setOpportunityAccessLevel("Read");
rule.setCaseAccessLevel("None");
connection.create(rule);
```

AccountPartner

This read-only object represents a partner relationship between two Account objects. It is automatically created when a Partner object is created for a partner relationship between two accounts.

 **Note:** This object is completely distinct and independent of Account records that have been enabled for the partner portal.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
AccountFromId	Type reference
	Properties Filter, Group, Sort

Field	Details
	Description ID of the main Account in the partner relationship.
AccountToId	Type reference Properties Filter, Group, Nillable, Sort, Description ID of the partner Account in the partner relationship.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
IsPrimary	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the AccountPartner is the main account's primary partner (<code>true</code>) or not (<code>false</code>).
OpportunityId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the opportunity in a partner relationship with the related account.
Role	Type picklist Properties Filter, Group, Nillable, Sort Description The UserRole that the partner Account has on the main Account. For example, Consultant or Distributor.

Creating an Account-Account Partner Relationship

When you create a partner relationship between two accounts (when you create a Partner object and specify the `AccountFromId`), the API automatically creates two AccountPartner objects, one for the forward relationship and one for the reverse. For example, if you create a Partner object with "Acme, Inc." as the `AccountFromId` and "Acme Consulting" as the `AccountToId`, the API automatically creates two AccountPartner objects:

- The forward relationship AccountPartner with "Acme, Inc." as the `AccountFromId` and "Acme Consulting" as the `AccountToId`.
- The reverse relationship AccountPartner with "Acme Consulting" as the `AccountFromId` and "Acme, Inc." as the `AccountToId`.
- The value of the `Role` field in the reverse relationship AccountPartner is set to the PartnerRole object `ReverseRole` value associated with the value of the `Role` field in the forward relationship AccountPartner.

This mapping allows the API to manage the objects and their relationship efficiently.

AccountShare

Represents a sharing entry on an Account.

Supported Calls

`describeSObjects()`, `create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>AccountAccessLevel</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to the Account. The possible values are: • Read • Edit • All (This value isn't valid for create or update calls.) This field must be set to an access level that is at least equal to the organization's default Account access level. In addition, either this field, the <code>OpportunityAccessLevel</code> field, or the <code>CaseAccessLevel</code> field must be set higher than the organization's default access level.

Field	Details
AccountId	Type reference Properties Filter, Group, Sort Description ID of the Account associated with this sharing entry. This field can't be updated.
CaseAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to cases associated with the account. The possible values are: • None • Read • Edit This field must be set to an access level that is at least equal to the organization's default <code>CaseAccessLevel</code>. This field can't be updated via the API if the <code>AccountAccessLevel</code> field is set to <code>All</code>. You can't update this field for the associated account owner via the API. You must update the account owner's <code>CaseAccessLevel</code> via the Salesforce user interface.
ContactAccessLevel	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Level of access that the User or Group has to contacts associated with the account. The possible values are: • None • Read • Edit This field must be set to an access level that is at least equal to the organization's default <code>ContactAccessLevel</code>. This field can't be updated via the API if the <code>ContactAccessLevel</code> field is set to "Controlled by Parent." You can't update this field for the associated account owner using the API. You must update the account owner's <code>ContactAccessLevel</code> via the Salesforce user interface.
IsDeleted	Type boolean

Field	Details
	Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
OpportunityAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to opportunities associated with the Account. The possible values are: • None • Read • Edit This field must be set to an access level that is at least equal to the organization's default opportunity access level. This field can't be updated via the API if the <code>AccountAccessLevel</code> field is set to <code>All</code>. You can't use the API to update this field for the associated Account owner. You must update the Account owner's opportunityAccessLevel via the Salesforce user interface.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to <code>Manual</code> (default). There are many possible values, including: • <code>Manual</code>—The User or Group has access because a User with "All" access manually shared the Account with them. • <code>Owner</code>—The User is the owner of the Account • <code>Team</code>—The User or Group has team access (is an <code>AccountTeamMember</code>). • <code>Rule</code>—The User or Group has access via an Account sharing rule.
UserOrGroupId	Type reference Properties Filter, Group, Sort Description ID of the User or Group that has been given access to the Account. This field can't be updated.

Usage

This object allows you to determine which users and groups can view or edit Account records owned by other users.

If you attempt to create an AccountShare record that matches an existing record, the request updates any modified fields and returns the existing record.

For example, the following code finds all accounts owned by a user and manually shares them to a portal user.

```
QueryResult result = conn.query("SELECT Id FROM Account WHERE OwnerId = '005D0000001LPFB'");
// Create a new AccountShare object
List<AccountShare> shares = new ArrayList<AccountShare>();
for (SObject rec : result.getRecords()) {
    AccountShare share = new AccountShare();
    share.setAccountId(rec.getId());
    //Set the portal user Id to share the accounts with
    share.setUserOrGroupId("003D000000QA8T1");
    share.setAccountAccessLevel("Edit");
    share.setOpportunityAccessLevel("Read");
    share.setCaseAccessLevel("Edit");
    shares.add(share);
}
conn.create(shares.toArray(new AccountShare[shares.size()]));
```

This code shares the accounts that the user owns at the time, but not those that are owned at a later time. For these types of shares, use an owner-based sharing rule such as [AccountOwnerSharingRule](#).

AccountTag

Associates a word or short phrase with an Account.

Supported Calls

create(), delete(), describeSObjects(), query(), retrieve()

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string

Field Name	Details
	Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • Public—The tag can be viewed and manipulated by all users in an organization. • Personal—The tag can be viewed or manipulated only by a user with a matching OwnerId.

Usage

AccountTag stores the relationship between its parent TagDefinition and the Account being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

AccountTeamMember

Represents a User who is a member of an Account team. See also UserAccountTeamMember, which represents a User who is on the default account team of another user.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- This object is available only for Enterprise, Unlimited, and Performance Edition users who have enabled the account team functionality.
- Customer Portal users can't access this object.

Fields

Field Name	Details
AccountAccessLevel	Type picklist Properties Filter, Group, Nillable, Sort Description Level of access that the User or Group has to the Account. The possible values are: • None • Read • Edit • All This field must be set to an access level that is at least equal to the organization's default Account access level. In addition, the AccountAccountAccessLevel, OpportunityAccessLevel, or CaseAccessLevel field must be set higher than the organization's default access level.
AccountId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Account to which this user is a team member. Must be a valid account ID.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.  Note: Any AccountTeamMember record that is deleted is not moved to the Recycle Bin, and cannot be undeleted, unless the record was cascade-deleted when deleting a related Account. For directly deleted AccountTeamMember records, don't use the isDeleted field

Field Name	Details
	to detect deleted records in SOQL queries or <code>queryAll()</code> calls. Instead, use <code>getDeleted()</code> .
TeamMemberRole	Type picklist Properties Create, Filter, Nillable, Update Description Role associated with this team member. One of the valid team member roles defined for your organization. Label is Team Role.
UserId	Type reference Properties Create, Filter Description Required. ID of the User who is a member of this account team. Must be a valid User ID.

Usage

Use this object to manage the team members of a particular Account and to specify team member roles for those users on that account.

AccountTerritoryAssignmentRule

An account assignment rule that assigns accounts to territories based on account fields. Only available if territory management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
BooleanFilter	Type string Properties Create, Filter, Nillable, Update Description Advanced filter conditions that were specified for the rule in the online application. For example, "(1 AND 2) OR 3."
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates whether the rule is active (<code>true</code>) or inactive (<code>false</code>). Via the API, active rules run automatically when new accounts are created and existing accounts are edited. The exception is when the <code>IsExcludedFromRealign</code> field on an account is <code>true</code>, which prevents account assignment rules from evaluating that account.
IsInherited	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates whether the rule is an inherited rule (<code>true</code>) or a local rule (<code>false</code>). An inherited rule also acts upon territories below it in the territory hierarchy. A local rule is created at the immediate territory and only impacts the immediate territory.
Name	Type string Properties Create, Filter, Update Description A name for the rule. Limit is 80 characters.
TerritoryId	Type reference Properties Create, Filter, Update Description ID of the territory where accounts that satisfy this rule are assigned.

Usage

A territory will not have any accounts (with the exception of manually assigned accounts) unless at least one account assignment rule is active for the territory.

AccountTerritoryAssignmentRuleItem

A row of selection criteria for an AccountTerritoryAssignmentRule object. Only available if territory management has been enabled for your organization. AccountTerritoryAssignmentRuleItem can be created or deleted if the BooleanFilter field on its corresponding AccountTerritoryAssignmentRule object is a null value.

Supported Calls

create(), delete(), describeSObjects(), getDeleted(), getUpdated(), query(), retrieve(), update(), upsert()

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
Field	Type picklist Properties Create, Filter, Group, Sort, Update Description The standard or custom account field to use as a criteria.
Operation	Type picklist Properties Create, Filter, Group, Sort, Update Description The criteria to apply, such as “equals” or “starts with.”
RuleID	Type reference Properties Create, Filter, Update Description ID of the associated AccountTerritoryAssignmentRule.

Field	Details
SortOrder	Type int Properties Create, Filter, Update Description The order in which this row is evaluated compared to other AccountTerritoryAssignmentRuleItem objects for the given AccountTerritoryAssignmentRule.
Value	Type string Properties Create, Filter, Nillable, Update Description The field value(s) to evaluate, such as 94105 if the Field is Billing Zip/Postal Code.

Usage

- Both standard and custom account fields can be used as criteria for account assignment rules.
- A territory will not have any accounts (with the exception of manually assigned accounts) unless at least one account assignment rule is active for the territory.

AccountTerritorySharingRule

Represents the rules for sharing an Account within a Territory.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
AccountAccessLevel	Type picklist

Field	Details
	Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing being allowed. The possible values are: • Read • Edit • All
CaseAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of access granted to the target group for all child cases of the account. The possible values are: • None • Read • Edit
ContactAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A value that represents the type of access granted to the target group for all related contacts on the account. The possible values are: • None • Read • Edit  Note: This field is read only.
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.

Field	Details
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. Accounts owned by users in the source territory trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.
OpportunityAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of access granted to the target group for all opportunities associated with the account. The possible values are: • None • Read

Field	Details
	Edit
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the user or group being given access, or, if a territory ID, the users assigned to that territory.

Usage

Use this object to manage the sharing rules for a particular object. General sharing and Territory-related sharing use this object.

ActionLinkGroupTemplate

Action link templates let you reuse action link definitions and package and distribute action links. An action link is a button on a feed element. Clicking on an action link can take a user to another Web page, initiate a file download, or invoke an API call to an external server or Salesforce. Use action links to integrate Salesforce and third-party services into the feed. Every action link belongs to an action link group and action links within the group are mutually exclusive. This object is available in API version 33.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Only users with the “Customize Application” permission can modify or delete this object.

Fields

Field Name	Details
Category	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The location of the action link group within the feed element. Values are: <code>Primary</code>—The action link group is displayed in the body of the feed element.

Field Name	Details
	Overflow—The action link group is displayed in the overflow menu of the feed element.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The name of the action link group template to use in code.
ExecutionsAllowed	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The number of times an action link can be executed. Values are: Once—An action link can be executed only once across all users. OncePerUser—An action link can be executed only once for each user. Unlimited—An action link can be executed an unlimited number of times by each user. If the action link's <code>actionType</code> is <code>Api</code> or <code>ApiAsync</code>, you can't use this value.
HoursUntilExpiration	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of hours from when the action link group is created until it's removed from associated feed elements and can no longer be executed. The maximum value is 8,760.
IsPublished	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, the action link group template is published. Action link group templates shouldn't be published until at least one ActionLinkTemplate is associated with it. Once set to <code>true</code>, this can't be set back to <code>false</code>.
Language	Type picklist

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the <code>MasterLabel</code>.
<code>MasterLabel</code>	Type string Properties Create, Filter, Group, Sort, Update Description The name of the action link group template.
<code>NamespacePrefix</code>	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.

Usage

Define action link templates in Setup and use `ConnectApi` in Apex or Chatter REST API to instantiate action links from the templates and to post feed elements with the action links.

If you delete a published action link group template, you delete all related action link information which includes deleting all action links that were instantiated using the template from feed items.

ActionLinkTemplate

Action link templates let you reuse action link definitions and package and distribute action links. An action link is a button on a feed element. Clicking an action link can take a user to another Web page, initiate a file download, or invoke an API call to an external server or Salesforce. Use action links to integrate Salesforce and third-party services into the feed. This object is available in API version 33.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Only users with the “Customize Application” permission can modify or delete this object.

Fields

Field Name	Details
<code>ActionLinkGroupTemplateId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the ActionLinkGroupTemplate with which this action link template is associated.
<code>ActionUrl</code>	Type textarea Properties Create, Update Description The action link URL. For example, a <code>Ui</code> action link URL is a Web page. A <code>Download</code> action link URL is a link to the file to download. <code>Ui</code> and <code>Download</code> action link URLs are provided to clients. An <code>Api</code> or <code>ApiAsync</code> action link URL is a REST resource. <code>Api</code> and <code>ApiAsync</code> action link URLs aren't provided to clients. Links to Salesforce can be relative. All other links must be absolute and start with <code>https://</code>. Links to resources hosted on Salesforce servers can be relative, starting with a <code>/</code>. All other links must be absolute and start with <code>https://</code>. This field can contain context variables and binding variables in the form <code>{!Bindings.key}</code>, for example, <code>https://www.example.com/{!Bindings.itemId}</code>. Set the binding variable's value when you instantiate the action link group from the template.

Field Name	Details
Headers	Type textarea Properties Create, Nillable, Update Description Template for the HTTP headers sent when corresponding action links are invoked. This field can be used only for <code>Api</code> and <code>ApiAsync</code> action links. This field can contain context variables and binding variables in the form <code>{!Bindings.<i>key</i>}</code>.
IsConfirmationRequired	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, a confirmation dialog appears before the action is executed.
IsGroupDefault	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, action links derived from this template are the default or primary action in their action groups. There can be only one default action per action group.
Label	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A custom label to display on the action link button. If none of the <code>LabelKey</code> values make sense for an action link, use a custom label. Set the <code>LabelKey</code> field to <code>None</code> and enter a label name in the <code>Label</code> field. Action links have four states: new, pending, success, and failed. These strings are appended to the label for each state: • <i>Label</i> • <i>Label Pending</i> • <i>Label Success</i> • <i>Label Failed</i> For example, if the value of <code>Label</code> is "Call Home," the values of the four action link states are: Call Home, Call Home Pending, Call Home Success, and Call Home Failed.

Field Name	Details
	If <code>LabelKey</code> has any value other than <code>None</code> , the <code>Label</code> field is empty.
<code>LabelKey</code>	Type string Properties Create, Filter, Group, Sort, Update Description Key for the set of labels to display for these action link states: new, pending, success, failed. For example, the Approve set contains these labels: Approve, Pending, Approved, Failed. For a complete list of keys and labels, see Action Links Labels in <i>Chatter REST API Developer's Guide</i> or <i>Apex Code Developer's Guide</i>. If none of the label key values make sense for an action link, set this field to <code>None</code> and enter a custom label name in the <code>Label</code> field.
<code>LinkType</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of action link. One of these values: • <code>Api</code>—The action link calls a synchronous API at the action URL. Salesforce sets the status to <code>SuccessfulStatus</code> or <code>FailedStatus</code> based on the HTTP status code returned by your server. • <code>ApiAsync</code>—The action link calls an asynchronous API at the action URL. The action remains in a <code>PendingStatus</code> state until a third party makes a request to <code>/connect/action-links/actionLinkId</code> to set the status to <code>SuccessfulStatus</code> or <code>FailedStatus</code> when the asynchronous operation is complete. • <code>Download</code>—The action link downloads a file from the action URL. • <code>Ui</code>—The action link takes the user to a web page at the action URL.
<code>Method</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description HTTP method for the action URL. One of these values: • <code>HttpDelete</code>—Returns HTTP 204 on success. Response body or output class is empty. • <code>HttpGet</code>—Returns HTTP 200 on success. • <code>HttpHead</code>—Returns HTTP 200 on success. Response body or output class is empty.

Field Name	Details
	<code>HttpPatch</code>—Returns HTTP 200 on success or HTTP 204 if the response body or output class is empty. <code>HttpPost</code>—Returns HTTP 201 on success or HTTP 204 if the response body or output class is empty. Exceptions are the batch posting resources and methods, which return HTTP 200 on success. <code>HttpPut</code>—Return HTTP 200 on success or HTTP 204 if the response body or output class is empty. <code>Ui</code> and <code>Download</code> action links must use <code>HttpGet</code>.
Position	Type int Properties Create, Filter, Group, Sort, Update Description An integer specifying the position of the action link template relative to other action links in the group. 0 is the first position.
RequestBody	Type textarea Properties Create, Nillable, Update Description Template for the HTTP request body sent when corresponding action links are invoked. This field can be used only for <code>Api</code> and <code>ApiAsync</code> action links. This field can contain context variables and binding variables in the form <code>{!Bindings.key}</code>.
UserAlias	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description If you selected <code>CustomUser</code> or <code>CustomExcludedUser</code> for <code>UserVisibility</code>, this field is the alias for the custom user. Use the alias in a template binding to specify the custom user when an action link group is created using the template.
UserVisibility	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update

Field Name	Details
	Description Who can see the action link. This value is set per action link, not per action link group. One of these values: • Creator—Only the creator of the action link can see the action link. • Everyone—Everyone can see the action link. • EveryoneButCreator—Everyone but the creator of the action link can see the action link. • Manager—Only the manager of the creator of the action link can see the action link. • CustomUser—Only the custom user can see the action link. • CustomExcludedUser—Everyone but the custom user can see the action link.

Usage

Create action link templates in Setup. Use Apex classes in the `ConnectApi` namespace or Chatter REST API to instantiate action links from templates and to post feed elements with the action links.

For information about action links, see “Working with Action Links” in *Apex Code Developer’s Guide* or *Chatter REST API Developer’s Guide*.

ActivityHistory

This read-only object is displayed in a related list of closed activities—past events and closed tasks—related to an object. It includes activities for all contacts related to the object. ActivityHistory fields for phone calls are only available if your organization uses Salesforce CRM Call Center.

Supported Calls

`describeSObjects()`

Fields

Field	Details
<code>AccountId</code>	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the related account, which is determined as follows: • The account associated with the <code>WhatId</code>, if it exists; or

Field	Details
	- The account associated with the <code>WhoId</code>, if it exists; otherwise <code>null</code> For information on IDs, see ID Field Type.
ActivityDate	Type date Properties Filter, Group, Nillable, Sort Description Indicates one of the following: - The due date of a task - The due date of an event if <code>IsAllDayEvent</code> is set to <code>true</code> This field has a time stamp that is always set to midnight in the Universal Time Coordinated (UTC) time zone. The time stamp doesn't represent the time of the activity; don't attempt to alter it to accommodate time zone differences. Label is <code>Date</code>.
ActivityType	Type picklist Properties Filter, Group, Nillable, Sort Description Represents one of the following values: <code>Call</code>, <code>Meeting</code>, or <code>Other</code>. Label is <code>Type</code>.
CallDisposition	Type string Properties Filter, Group, Nillable, Sort Description Represents the result of a given call, for example, "we'll call back," or "call unsuccessful." Limit is 255 characters.
CallDurationInSeconds	Type int Properties Filter, Group, Nillable, Sort Description Duration of the call in seconds.
CallObject	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description Name of a call center. Limit is 255 characters.
CallType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of call being answered: Inbound, Internal, or Outbound.
ConnectionReceivedId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the PartnerNetworkConnection that shared this record with your organization. This field is available only if your organization has enabled Salesforce to Salesforce and only in API versions 28.0 and later.
ConnectionSentId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the PartnerNetworkConnection that your organization shared this record with. This field is available only if your organization has enabled Salesforce to Salesforce, and only in API versions 28.0 and later. The value is always <code>null</code> . You can use the PartnerNetworkRecordConnection object to forward records to connections.
Description	Type textarea Properties Nillable Description Contains a description of the event or task. Limit is 32 KB.
Division	Type picklist

Field	Details
	Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization's data. Available only if the organization has the Division permission enabled.
DurationInMinutes	Type int Properties Filter, Group, Nillable, Sort Description Indicates the duration of the event or task.
EndTime	Type dateTime Properties Filter, Nillable, Sort Description Indicates the end date and time of the event or task. Available in versions 27.0 and later. This field is optional, depending on the following: • If <code>IsAllDayEvent</code> is true, you can supply a value for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time. If both fields are <code>null</code>, the duration defaults to one day. • If <code>IsAllDayEvent</code> is false, a value must be supplied for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time.
IsAllDayEvent	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If the value of this field is set to <code>true</code>, then the activity is an event spanning a full day, and the <code>ActivityDate</code> defines the date of the event. If the value of this field is set to <code>false</code>, then the activity may be an event spanning less than a full day, or it may be a task. Label is <code>All-Day Event</code>.
IsClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description Indicates whether a task is closed; value is always <code>true</code>. This field is set indirectly by setting the <code>Status</code> field on the task—each picklist value has a corresponding <code>IsClosed</code> value. Label is <code>Closed</code>.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the activity has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is <code>Deleted</code>.
<code>IsHighPriority</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates a high-priority task. This field is derived from the <code>Priority</code> field.
<code>IsOnlineMeeting</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the activity represents an online meeting (<code>true</code>) or not (<code>false</code>).  Note: This field is not available in API version 16.0 or later.
<code>IsReminderSet</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a reminder is set for an activity (<code>true</code>) or not (<code>false</code>).
<code>IsTask</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description If the value of this field is set to <code>true</code>, then the activity is a task. If the value is set to <code>false</code>, then the activity is an event. Label is <code>Task</code>.
IsVisibleInSelfService	Type boolean Properties Defaulted on create, Filter Description If the value of this field is set to <code>true</code>, then the activity can be viewed in the self-service portal. Label is <code>Visible in Self-Service</code>.
Location	Type string Properties Filter, Group, Nillable, Sort Description If the activity is an event, then this field contains the location of the event. If the activity is a task, then the value is <code>null</code>.
OwnerId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the user who owns the activity.
PrimaryAccountId	Type reference Properties Filter, Group, Nillable, Sort Description Contains the <code>AccountId</code> value from the activity record. Available in API versions 30.0 and later to organizations that use Shared Activities.
PrimaryWhoId	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description Contains the <code>whoId</code> value from the activity record. Available in API versions 30.0 and later to organizations that have enabled Shared Activities.
Priority	Type picklist Properties Filter, Group, Nillable, Sort Description Indicates the priority of a task, such as high, normal, or low.
ReminderDateTime	Type dateTime Properties Filter, Nillable, Sort Description Represents the time when the reminder is scheduled to fire, if <code>IsReminderSet</code> is set to <code>true</code> . If <code>IsReminderSet</code> is set to <code>false</code> , then the user may have deselected the reminder checkbox in the Salesforce user interface, or the reminder has already fired at the time indicated by the value.
Status	Type picklist Properties Filter, Group, Nillable, Sort Description Indicates the current status of a task, such as in progress or complete. Each predefined status field sets a value for <code>IsClosed</code> . To obtain picklist values, query <code>TaskStatus</code> .
Subject	Type combobox Properties Filter, Nillable, Sort Description Contains the subject of the task or event.
WhatId	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description The <code>WhatId</code> represents nonhuman objects such as accounts, opportunities, campaigns, cases, or custom objects. <code>WhatIds</code> are polymorphic. Polymorphic means a <code>WhatId</code> is equivalent to the ID of a related object. The label is <code>Related To ID</code>.
<code>WhoId</code>	Type reference Properties Filter, Group, Nillable, Sort Description The <code>WhoId</code> represents a human such as a lead or a contact. <code>WhoIds</code> are polymorphic. Polymorphic means a <code>WhoId</code> is equivalent to a contact's ID or a lead's ID. The label is <code>Name ID</code>. If Shared Activities is enabled, the value of this field is the ID of the related lead or primary contact. If you add, update, or remove the <code>WhoId</code> field, you might encounter problems with triggers, workflows, and data validation rules that are associated with the record. The label is <code>Name ID</code>. If your organization uses Shared Activities, when you query activities in API version 30.0 or later, the returned value of the <code>WhoId</code> field matches the value in the queried object, not necessarily in the activity record itself.

Usage

Query activities that are related to an object

1. Optionally, issue a describe call against the object whose activities you wish to query, to get a suggestion of the correct SOQL to use.
2. Issue a SOQL relationship query with a main clause that references the object, and an inner clause that references the activity history; for example:

```
SELECT
  (SELECT ActivityDate, Description
   FROM ActivityHistories)
FROM Account
WHERE Name Like 'XYZ%'
```

The user interface enforces sharing rules, filtering out related-list items that a user doesn't have permission to see.

The following constraints on users who don't have the "View All Data" permission help prevent performance issues.

- In the main clause of the relationship query, you can reference only one record. For example, you can't filter on all records where the account name starts with "A." Instead, you must reference a single account record.

```
SELECT
  (SELECT ActivityDate, Description
   FROM ActivityHistory
```

```
ORDER BY ActivityDate DESC NULLS LAST, LastModifiedDate DESC
LIMIT 500)
FROM Account
WHERE Name = 'Acme'
LIMIT 1
```

- In the inner clause of the query, you can't use `WHERE`.
- In the inner clause of the query, you must specify a limit of 500 or fewer on the number of rows that are returned in the list.
- In the inner clause of the query, you must sort on `ActivityDate` in descending order and `LastModifiedDate` in descending order. You can optionally display nulls last. For example: `ORDER BY ActivityDate DESC NULLS LAST, LastModifiedDate DESC`.

AdditionalNumber

This object represents an optional additional number for a call center. This additional number is visible in the call center's phone directory.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
CallCenterId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description System field that contains the ID of the user who created the call center associated with this additional number. If value is null, this additional number is displayed in every call center's phone directory.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Description of the additional number, such as Conference Room B. Limit: 255 characters.

Field	Details
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the additional number. Limit: 80 characters.
Phone	Type phone Properties Create, Filter, Nillable, Group, Sort, Update Description The phone number that corresponds to this additional number.

Usage

Create an additional number for a call center directory. Use this object if the number is not easily categorized as a User, Contact, Lead, Account, or the other object. Examples include phone queues or conference rooms.

AgentWork

Represents a work assignment that has been routed to an agent. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `upsert()`, `query()`, `getDeleted()`, `getUpdated()`, `retrieve()`, `update()`

Fields

Field	Details
CapacityPercentage	Type percent Properties Filter, Nillable, Sort Description The percentage of an agent's capacity for work items that's consumed by a specific type of work item from this service channel.

Field	Details
	For example, you might give phone calls a capacity percentage of <i>100</i>. If an agent receives a phone call, the agent doesn't receive new work items until the call ends, because at that point the agent's capacity will have reached 100%.
CapacityWeight	Type double Properties Filter, Nillable, Sort Description The amount of an agent's capacity for work items that's consumed by a work item from this service channel. For example, if an agent has a capacity of <i>6</i>, and cases are assigned a capacity weight of <i>2</i>, an agent can be assigned up to 3 cases before the agent is at capacity and can't receive new work items.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description An automatically generated ID number that identifies the record.
OriginalQueueId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the queue to which the work assignment was originally routed to.
ServiceChannelId	Type reference Properties Create, Filter, Group, Sort Description The ID of the service channel that's associated with the work assignment.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The working status of the work item. Valid values are:

Field	Details
	- Assigned - Unavailable - Declined - Opened - Closed
UserId	Type reference Properties Create, Filter, Group, Sort Description The ID of the user that the work item was assigned to.
WorkItemId	Type reference Properties Create, Filter, Group, Sort Description The ID of the object that's routed to the agent through Omni-Channel.

AllowedEmailDomain

Represents an allowed email domain for users in your organization. You can define a whitelist to restrict the email domains allowed in a user's `Email` field. This object is available in API version 29.0 and later.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

You must have the "Manage Internal Users" user permission to use this object.



Note: If you don't see this object, contact your Salesforce representative to enable it.

Fields

Field	Details
Domain	Type string

Field	Details
	Properties Create, Filter, Group, idLookup, Sort, Update
	Description An allowed email domain for users.

Announcement

Represents a Chatter group announcement. This object is available in API version 30.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>ExpirationDate</code>	Type dateTime
	Properties Create, Filter, Sort, Update
	Description Required. The date on which the announcement expires. Announcements display on the group UI until 11:59 p.m. local time on the selected date.
<code>FeedItemId</code>	Type reference
	Properties Create, Filter, Group, Sort
	Description Required. The ID of the FeedItem that contains the content of the announcement. Announcements are stored as text posts.
<code>ParentId</code>	Type reference
	Properties Filter, Group, Nillable, Sort
	Description The ID of the parent CollaborationGroup that the announcement belongs to. An announcement can belong only to a single Chatter group.

Usage

Group owners, managers, and users with the “Modify All Data” permission can use the Announcement object to create, edit, and delete group announcements. Creating a group announcement is a three-step process:

- 1. Use the FeedItem object to create a text post with the announcement’s content. Use the CollaborationGroup record you want to post the announcement to as the parent of this feed item.
- 2. Next, use the feed item ID and an expiration date to create the announcement record.
- 3. Finally, update the AnnouncementId field in the CollaborationGroup record with the ID of the announcement you created.

To delete the group announcement, simply delete the AnnouncementId value in the CollaborationGroup record. To restore a group announcement, update the AnnouncementId field for a group with the announcement’s ID. The expiration date for the announcement should be in the future and the feed item used to create the announcement should be parented by the same group.

ApexClass

Represents an Apex class.

 **Note:** Although Apex classes and triggers have the Create and Update field properties, a runtime exception occurs if you try to create or update them using the API. Instead, use the Force.com Migration Tool, the Salesforce user interface, or the Force.com IDE to create or update Apex classes or triggers.

Supported Calls

create(), delete(), describeSObjects(), getDeleted(), getUpdated(), query(), retrieve(), update(), upsert()

Fields

Field	Details
ApiVersion	Type double Properties Create, Filter, Sort, Update Description The API version for this class. Every class has an API version specified at creation.
Body	Type textarea Properties Create, Nillable, Update Description The Apex class definition. Limit: 1 million characters.

Field	Details
bodyCrc	Type double Properties Create, Defaulted on create, Filter, Nillable, Sort, Update Description The CRC (cyclic redundancy check) of the class or trigger file.
IsValid	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether any dependent metadata has changed since the class was last compiled (<code>true</code>) or not (<code>false</code>).
LengthWithoutComments	Type int Properties Create, Filter, Group, Sort, Update Description Length of the class without comments.
Name	Type string Properties Group, Sort, Create, Filter, Update Description Name of the class. Limit: 255 characters
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values:

Field	Details
	- In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. - In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
Status	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The current status of the Apex class. The following string values are valid: <code>Active</code>—The class is active. <code>Deleted</code>—The class is marked for deletion. This is useful for managed packages, because it allows a class to be deleted when a managed package is updated.  Note: The ApexTrigger <code>Status</code> field includes an <code>Inactive</code> option, but it is only supported for ApexTrigger. For more information, see the Force.com Metadata API Developer's Guide.

Usage

For information, see the [Force.com Apex Code Developer's Guide](#).

ApexComponent

Represents a definition for a custom component that can be used in a Visualforce page alongside standard components such as `<apex:relatedList>` and `<apex:dataTable>`. For information, see the [Visualforce Developers Guide](#).

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
ApiVersion	Type double Properties Create, Filter, Sort, Update Description The API version for this custom component. Every custom component has an API version specified at creation. If the API version is less than 15.0 and <code>ApiVersion</code> is not specified, <code>ApiVersion</code> defaults to 15.0.
ControllerKey	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The identifier for the controller associated with this custom component: • If the <code>ControllerType</code> parameter is set to <code>Standard</code> or <code>StandardSet</code>, this value is the name of the sObject that defines the controller. • If the <code>ControllerType</code> parameter is set to <code>Custom</code>, this value is the name of the Apex class that defines the controller.
ControllerType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of controller associated with this Visualforce custom component. Possible values include: • <code>Not Specified</code>, for custom components defined without a value for the <code>controller</code> attribute on the <code><apex:component></code> tag • <code>Standard</code>, a value that can't be used with custom components or errors may occur • <code>StandardSet</code>, a value that can't be used with custom components or errors may occur • <code>Custom</code>, for components that have a value for the <code>controller</code> attribute on the <code><apex:component></code> tag
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update

Field	Details
	Description Description of the Visualforce custom component.
Markup	Type textarea Properties Create, Update Description The Visualforce markup, HTML, Javascript, and any other Web-enabled code that defines the content of the custom component.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The text used to identify the Visualforce custom component in the Setup area of Salesforce. The Label for this field is Label.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of this Visualforce custom component.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer.

Field	Details
	In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.

Usage

Use custom components to encapsulate a common design pattern and then reuse that pattern several times in one or more Visualforce pages. All users who can view Visualforce pages can view custom components, but the “Customize Application” permission is required to create or update custom components.

ApexLog

Represents an Apex debug log.

This object is available in API version 19.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
Application	Type string Properties Filter, Group, Sort Description This value depends on the client type that triggered the log. - For API clients, this value is the client ID - For browser clients, this value is <code>Browser</code>
DurationMilliseconds	Type int Properties Filter, Group, Sort Description Duration of the transaction in milliseconds.
Location	Type picklist

Field	Details
	Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies the location of the origin of the log. Values are: • Monitoring—log is generated as part of debug log monitoring. These types of logs are maintained until the user or the system overwrites them. • SystemLog—log is generated from the Developer Console. These types of logs are only maintained for 60 minutes or until the user clears them.
LogLength	Type int Properties Filter, Group, Sort Description Length of the log in bytes.
LogUserId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user whose actions triggered the debug log.
Operation	Type string Properties Filter, Group, Sort Description Name of the operation that triggered the debug log, such as Apex SOAP, Apex Sharing Recalculation, and so on.
Request	Type string Properties Filter, Group, Sort Description Request type. Values are: • API—request came from the API • Application—request came from the Salesforce user interface

Field	Details
StartTime	Type dateTime Properties Filter, Sort Description Start time of the transaction.
Status	Type string Properties Filter, Group, Sort Description Status of the transaction. This value is either <code>Success</code> , or the text of an unhandled Apex exception.

Usage

You can read information about this object, as well as delete it: you can't update or insert. For information, see the [Force.com Apex Code Developer's Guide](#).

ApexPage

Represents a single Visualforce page.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
ApiVersion	Type double Properties Create, Filter, Sort, Update Description The API version for this page. Every page has an API version specified at creation. If the API version is less than 15.0 and <code>ApiVersion</code> is not specified, <code>ApiVersion</code> defaults to 15.0.

Field	Details
ControllerKey	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The identifier for the controller associated with this page: • If the <code>ControllerType</code> parameter is set to <code>Standard</code> or <code>StandardSet</code>, this value is the name of the sObject that defines the controller. • If the <code>ControllerType</code> parameter is set to <code>Custom</code>, this value is the name of the Apex class that defines the controller.
ControllerType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of controller associated with this Visualforce page. Possible values include: • <code>Not Specified</code>, for pages defined with neither a <code>standardController</code> nor a <code>controller</code> attribute on the <code><apex:page></code> tag • <code>Standard</code>, for pages defined with the <code>standardController</code> attribute on the <code><apex:page></code> tag • <code>StandardSet</code>, for pages defined using the <code>standardController</code> and <code>recordSetVar</code> attribute on the <code><apex:page></code> tag • <code>Custom</code>, for pages defined with the <code>controller</code> attribute on the <code><apex:page></code> tag
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Description of the Visualforce page.
isAvailableInTouch	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates if Visualforce tabs associated with the Visualforce page can be used in the Salesforce1 app (<code>true</code>) or not (<code>false</code>). (Use of this field for Salesforce Touch is deprecated.) This field is available in API version 27.0 and later.

Field	Details
	Standard object tabs that are overridden with a Visualforce page aren't supported in Salesforce1, even if you set this field for the page. The default Salesforce1 page for the object is displayed instead of the Visualforce page.
IsConfirmationTokenRequired	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether <code>GET</code> requests for the page require a CSRF confirmation token (<code>true</code>) or not (<code>false</code>). This field is available in API version 28.0 and later. If you change this field's value from <code>false</code> to <code>true</code>, links to the page require a CSRF token to be added to them, or the page will be inaccessible.
Markup	Type textarea Properties Create, Update Description The Visualforce markup, HTML, Javascript, and any other Web-enabled code that defines the content of the page.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The text used to identify the Visualforce page in the Setup area of Salesforce. The Label is Label.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of this Visualforce page.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort

Field	Details
	Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: - In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. - In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.

Usage

Use Visualforce pages to add custom content that extends the base Salesforce application functionality. All users in Visualforce-enabled organizations can view Visualforce pages, but the "Customize Application" permission is required to create or update them.

For information, see the [Visualforce Developers Guide](#).

ApexTestQueueItem

 **Note:** The API for asynchronous test runs is a Beta release.

Represents a single Apex class in the Apex job queue. This object is available in API version 23.0 and later.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Description
<code>ApexClassId</code>	Type reference Properties Create, Filter, Group, Sort Description The Apex class whose tests are to be executed.

Field Name	Description
	This field can't be updated.
ExtendedStatus	Type string Properties Filter, Nillable, Sort Description The pass rate of the test run. For example: "(4/6)". This means that four out of a total of six tests passed. If the class fails to execute, this field contains the cause of the failure.
ParentJobId	Type reference Properties Filter, Group, Nillable, Sort Description Read-only. Points to the AsyncApexJob that represents the entire test run. If you insert multiple Apex test queue items in a single bulk operation, the queue items will share the same parent job. This means that a test run can consist of the execution of the tests of several classes if all the test queue items are inserted in the same bulk operation.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description The status of the job. Valid values are: • Holding¹ • Queued • Preparing • Processing • Aborted • Completed • Failed ¹ This status applies to batch jobs in the Apex flex queue.

Usage

Insert an `ApexTestQueueItem` object to place its corresponding Apex class in the Apex job queue for execution. The Apex job executes the test methods in the class.

To abort a class that is in the Apex job queue, perform an update operation on the `ApexTestQueueItem` object and set its `Status` field to `Aborted`.

If you insert multiple Apex test queue items in a single bulk operation, the queue items will share the same parent job. This means that a test run can consist of the execution of the tests of several classes if all the test queue items are inserted in the same bulk operation.

ApexTestResult

 **Note:** The API for asynchronous test runs is a Beta release.

Represents the result of an Apex test method execution. This object is available in API version 23.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>ApexClassId</code>	Type reference Properties Filter, Group, Sort Description The Apex class whose test methods were executed.
<code>ApexLogId</code>	Type reference Properties Filter, Group, Nillable, Sort Description Points to the <code>ApexLog</code> for this test method execution if debug logging is enabled; otherwise, <code>null</code> .
<code>AsyncApexJobId</code>	Type reference Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description Read-only. Points to the AsyncApexJob that represents the entire test run. This field points to the same object as ApexTestQueueItem.ParentJobId .
Message	Type string Properties Filter, Nillable, Sort Description The exception error message if a test failure occurs; otherwise, null.
MethodName	Type string Properties Filter, Group, Nillable, Sort Description The test method name.
Outcome	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The result of the test method execution. Can be one of these values: • Pass • Fail • CompileFail
QueueItemId	Type reference Properties Filter, Group, Nillable, Sort Description Points to the ApexTestQueueItem which is the class that this test method is part of.
StackTrace	Type string

Field Name	Details
	Properties Filter, Nillable, Sort Description The Apex stack trace if the test failed; otherwise, null.
TestTimestamp	Type dateTime Properties Filter, Sort Description The start time of the test method.

Usage

You can query the fields of the `ApexTestResult` record that corresponds to a test method executed as part of an Apex class execution.

Each test method execution is represented by a single `ApexTestResult` record. For example, if an Apex test class contains six test methods, six `ApexTestResult` records are created. These records are in addition to the `ApexTestQueueItem` record that represents the Apex class.

ApexTrigger

Represents an Apex trigger.



Note: Although Apex classes and triggers have the Create and Update field properties, a runtime exception occurs if you try to create or update them using the API. Instead, use the Force.com Migration Tool, the Salesforce user interface, or the Force.com IDE to create or update Apex classes or triggers.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
ApiVersion	Type double Properties Create, Filter, Sort, Update

Field	Details
	Description The API version for this trigger. Every trigger has an API version specified at creation.
Body	Type textarea Properties Create, Nillable, Update Description The Apex trigger definition. Limit: 1 million characters.
bodyCrc	Type double Properties Create, Defaulted on create, Filter, Nillable, Sort, Update Description The CRC (cyclic redundancy check) of the class or trigger file.
IsValid	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether any dependent metadata has changed since the trigger was last compiled (<code>true</code>) or not (<code>false</code>).
LengthWithoutComments	Type int Properties Create, Filter, Group, Sort, Update Description Length of the trigger without comments
Name	Type string Properties Create, Filter, Group, Sort, Update Description Name of the trigger. Limit: 255 characters

Field	Details
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
Status	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The current status of the Apex trigger. The following string values are valid: • <code>Active</code>—The trigger is active. • <code>Inactive</code>—The trigger is inactive, but not deleted. • <code>Deleted</code>—The trigger is marked for deletion. This is useful for managed packages, because it allows a class to be deleted when a managed package is updated.  Note: <code>Inactive</code> is not valid for <code>ApexClass</code>. For more information, see the Force.com Metadata API Developer's Guide.
TableEnumOrId	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Specifies the object associated with the trigger, such as Account or Contact.
UsageAfterDelete	Type boolean

Field	Details
	Properties Create, Filter, Update Description Specifies whether the trigger is an <code>after delete</code> trigger (<code>true</code>) or not (<code>false</code>).
UsageAfterInsert	Type boolean Properties Create, Filter, Update Description Specifies whether the trigger is an <code>after insert</code> trigger (<code>true</code>) or not (<code>false</code>).
UsageAfterUndelete	Type boolean Properties Create, Filter, Update Description Specifies whether the trigger is an <code>after undelete</code> trigger (<code>true</code>) or not (<code>false</code>).
UsageAfterUpdate	Type boolean Properties Create, Filter, Update Description Specifies whether the trigger is an <code>after update</code> trigger (<code>true</code>) or not (<code>false</code>).
UsageBeforeDelete	Type boolean Properties Create, Filter, Update Description Specifies whether the trigger is a <code>before delete</code> trigger (<code>true</code>) or not (<code>false</code>).
UsageBeforeInsert	Type boolean Properties Create, Filter, Update Description Specifies whether the trigger is a <code>before insert</code> trigger (<code>true</code>) or not (<code>false</code>).

Field	Details
UsageBeforeUpdate	Type boolean Properties Create, Filter, Update Description Specifies whether the trigger is a <code>before update</code> trigger (<code>true</code>) or not (<code>false</code>).
UsageIsBulk	Type boolean Properties Create, Filter, Update Description Specifies whether the trigger is defined as a bulk trigger (<code>true</code>) or not (<code>false</code>).  Note: This field is not used for Apex triggers saved using Salesforce API version 10.0 or higher: all triggers starting with that version are automatically considered bulk, and this field will always return <code>true</code>.

Usage

For more information about Apex triggers, see the [Force.com Apex Code Developer's Guide](#).

AppMenuItem

Represents an item in the App Picker menu.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
CanvasAccessMethod	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The access method for the canvas app. Values can be: • OAuth Webflow (GET)

Field	Details
	Signed Request (POST)
CanvasEnabled	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates if the app menu item is a canvas app (<code>true</code>) or not (<code>false</code>).
CanvasOptions	Type string Properties Filter, Group, Nillable, Sort Description Represents the options enabled for a canvas connected app. The options are: - PersonalEnabled—The app is enabled as a canvas personal app. - HideHeader—The publisher header, which contains the “What are you working on?” text, is hidden. - HideShare—The publisher Share button is hidden. This field is available in API version 34.0 and later.
CanvasReferenceId	Type string Properties Filter, Group, Nillable, Sort Description The canvas app unique identifier.
CanvasSelectedLocations	Type string Properties Filter, Group, Nillable, Sort Description The selected locations for the canvas app which define where the canvas app can appear in the user interface. For example: Chatter, ChatterFeed, Publisher, ServiceDesk
CanvasUrl	Type url Properties Filter, Group, Nillable, Sort

Field	Details
	Description The URL of the canvas app.
Description	Type string Properties Filter, Group, Nillable, Sort Description A description of this menu item.
IconUrl	Type string Properties Filter, Group, Nillable, Sort Description The icon for the menu item's application.
InfoUrl	Type string Properties Filter, Group, Nillable, Sort Description The URL for more information about the application.
IsUsingAdminAuthorization	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If <code>true</code> , the app is pre-authorized for certain users by the administrator.
Label	Type string Properties Group, Nillable Description The app's name.
LogoUrl	Type string Properties Filter, Group, Nillable, Sort

Field	Details
	Description The logo for the menu item's application. The default is a cloud.
MobileStartUrl	Type string Properties Filter, Group, Nillable, Sort Description The location mobile users are directed to after they've authenticated. This is only used with connected apps.
Name	Type string Properties Filter, Group, Nillable, Sort Description The API name of the item.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, NamespacePrefix is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.
SortOrder	Type int

Field	Details
	Properties Filter, Group, idLookup, Sort Description The index value that controls where this item appears in the menu. For example, a menu item with a sort order of 5 will appear between items with sort order values of 3 and 9.
StartUrl	Type string Properties Filter, Group, Nillable, Sort Description The location users are directed to after they've authenticated. For a connected app, this is the location specified by the <code>StartUrl</code> . Otherwise it's the application's default start page.
Type	Type string Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of application represented by this item. The types are: • ConnectedApplication • ServiceProvider • TabSet

Usage

Use this read-only object to view an entry in the Force.com App Menu. You can create a SOQL query to retrieve all items, even those a user does not see from the user interface.

There are many ways you can use AppMenuItem. Here are some examples:

- Build your own App Launcher or App Menu in Salesforce. Create a custom page showing all the apps you have access to and that lets you run them using single sign-on.
- Build your own App Launcher or App Menu on a tablet or mobile app. You can have your own app for launching applications on a variety of mobile devices.
- Build an app launcher into your company's intranet. There's no need to have it run on Salesforce because there's a Web service API to let you build an app launcher.

Approval

Represents an approval request for a Contract.



Note: This object is read-only and is specific to approvals on the Contract object. It isn't equal to or involved in the approval processes represented by the ProcessInstance, which is more powerful.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
ApproveComment	Type string Properties Filter, Nillable, Sort Description Text entered by the user when they approved or rejected this approval request. Required. Limit: 4,000 characters.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
OwnerId	Type reference Properties Filter, Group, Sort Description Required. ID of the User being asked to approve or reject the approval request. Must be a valid User ID. Required.
ParentId	Type reference Properties Filter, Group, Sort

Field	Details
	Description Required. ID of the Contract associated with this approval request. Must be a valid contract ID.
RequestComment	Type string Properties Filter, Nillable, Sort Description Text entered by the User who created the approval request. Optional. This field can't be updated after the Approval has been created. Limit: 4,000 characters.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Required. Status of this approval request. One of the following picklist values: • Pending—Specified only when the Approval request is created (<code>create()</code> call) • Approved—Specified only when the Approval request is approved (<code>update()</code> call) • Rejected—Specified when the Approval request is rejected (<code>update()</code> call) or when it is created (<code>create()</code> call) and immediately rejected for archival/historical purposes.

Usage

This object allows client applications to programmatically handle approval requests for a Contract. Initially, to request a Contract approval, a client application might create a new Approval request record, specifying the `ParentId`, `OwnerId` (user approving or rejecting the request), `Status` (Pending), and (optionally) `RequestComment` fields. Note that when a client application creates the first approval request, if the value of the Contract `Status` field is Draft, then the Approval `Status` for this record is automatically changed to In Approval Process (see `ContractStatus` for more information).

A client application might subsequently update an existing Approval request, specifying the `Status` (Approved or Rejected) and an `ApproveComment` (required); the `RequestComment` field can't be updated. Updating an Approval record (either to approve or reject) requires the client application to be logged in with "Approve Contract" permission. To update an Approval request, its `Status` must be Pending—a client application can't update an Approval that has already been Approved or Rejected. To re-submit an approval request for a given Contract, a client application must create a new, separate Approval record and repeat the approval process.

Once a Contract has been approved (not rejected), the Contract `LastApprovedDate` field is automatically updated, however the Contract `Status` field isn't updated, it keeps the value InApproval.

An approved Contract must be activated explicitly. Client applications can activate a Contract by setting the value in its `Status` field to Activated, or a User can activate a Contract via the Salesforce user interface.

A Contract can have multiple approval requests in various states (Pending, Approved, and Rejected). In addition, one User can have multiple approval requests associated with the same Contract.

Client applications can't explicitly delete Approval records. Approval records are deleted automatically if the parent Contract is deleted.

*Article Type*__DataCategorySelection

A data category selection represents a data category that classifies an article. This object can be used to associate an article with data categories from a data category group or to query the category selections for an article.

The object name is variable and has a syntax of *Article Type*__DataCategorySelection, where *Article Type* is the Object Name for the article type associated with the article. For example, Offer__DataCategorySelection represents the association between the Offer article type and its data categories. Every article is associated with an article type.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `getDeleted()`, `retrieve()`

Special Access Rules

Users can only access, create or delete data category selection visible to their role, permission set, or profile. If a user has partial visibility on an article's categorization, only the visible categories are returned.

Fields

Field Name	Details
DataCategoryGroupName	Type DataCategoryGroupReference Properties Create Description Unique name of the data category group which has categories associated with the article.
DataCategoryName	Type DataCategoryGroupReference Properties Create Description Unique name of the data category associated with the article.
ParentId	Type reference Properties Create, Filter

Field Name	Details
	Description ID of the article associated with the data category selection.

Usage

Every article in Salesforce Knowledge can be categorized. A data category selection represents a category that has been selected to classify an article. You can use the *Article Type__DataCategorySelection* object to query and manage article categorization in your organization. Client applications can create a categorization for an article with a Draft status. They can also delete and query article categorizations.



Note: When using *Article Type__DataCategorySelection* to classify an article, you can't select both a category (for example USA) and one of its descendants (California) or ascendant categories (North America). In this case, only the first category is selected.

Answer communities use *QuestionDataCategorySelection* to classify questions.

SOQL Sample

The following SOQL query returns the data category selections used to classify the article whose ID is `ka0D000000005ApIAI`.

```
SELECT Id,DataCategoryName, ParentId
FROM Offer__DataCategorySelection WHERE ParentId='ka0D000000005ApIAI'
```

This clause only returns category unique names. To retrieve category labels use the following clause:

```
SELECT Id,toLabel(DataCategoryName), ParentId
FROM Offer__DataCategorySelection WHERE ParentId='ka0D000000005ApIAI'
```



Tip: You can also use relationship queries to retrieve categorizations from an article type.

Article Type__Feed

Represents a single feed item in the feed displayed on the detail page for an article. An article feed shows recent changes to an article record for any fields that are tracked in feeds, as well as posts and comments about the article. It is a useful way to stay up-to-date with changes made to articles in Salesforce Knowledge. This object is available in API version 20.0 and later. The object name is variable and has a syntax of *Article Type__Feed*, where *Article Type* is the *Object Name* for the article type associated with the article. For example, *Offer__Feed* represents a feed item on an article based on the *Offer* article type.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Body	Type textarea Properties Create, Nillable, Sort, Update on page 16 Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Create, Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Create, Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Create, Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.

Field	Details
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDate DESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.

Field	Details
<code>IsDeleted</code>	Type <code>boolean</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
<code>LastModifiedDate</code>	Type <code>dateTime</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Sort</code> Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
<code>LikeCount</code>	Type <code>int</code> Properties <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description The number of <code>FeedLikes</code> associated with this feed item.
<code>LinkUrl</code>	Type <code>url</code> Properties <code>Create</code>, <code>Nullable</code>, <code>Sort</code> Description The URL of a <code>LinkPost</code>.
<code>ParentId</code>	Type <code>reference</code> Properties <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description ID of the article that is tracked in the feed. The feed is displayed on the detail page for this record.

Field	Details
RelatedRecordId	Type reference Properties Create, Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of Type ContentPost.
Title	Type string Properties Create, Group, Nillable, Sort Description The title of the FeedItem. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name. The Title field can be updated on posts of Type QuestionPost.
Type	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The type of FeedItem. Except for ContentPost, LinkPost, and TextPost, don't create FeedItem types directly from the API. • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file.

Field	Details
	• CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case. • CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • CaseCommentPost—generated event when a user adds a case comment for a case object. • ChangeStatusPost—generated event when a user changes the status of a case. • ChatTranscriptPost—generated event when Live Agent transcript is saved to a case. • EmailMessageEvent—generated event when an email related to a case object is sent or received. • FacebookPost—generated when a Facebook post is created from a case. Deprecated. • MilestoneEvent—generated when a case milestone is completed or reaches violation status. • SocialPost—generated when a social post is created from a case.  Note: If you set Type to ContentPost, also specify ContentData and ContentFileName.

Usage

Use this object to track changes for an article. You can only delete a feed if you created it, or if you have the “Modify All Data” permission or “Modify All” permission on the KnowledgeArticle object.

Asset

Represents an item of commercial value (such as a product sold by your company or by a competitor) that a customer has purchased and installed.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AccountId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Required. ID of the Account associated with this asset. Must be a valid account ID. Required if <code>ContactId</code> is not specified.
ContactId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Required if <code>AccountId</code> is not specified. ID of the Contact associated with this asset. Must be a valid contact ID that has an account parent (but does not need to match the asset's <code>AccountId</code>).
Description	Type textarea Properties Create, Nillable, Update Description Description of this asset.
InstallDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date on which this asset was installed.

Field	Details
IsCompetitorProduct	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this Asset represents a product sold by a competitor (<code>true</code>) or not (<code>false</code>). Default value is <code>false</code>. Label is Competitor Asset.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of the asset. Label is Asset Name.
Price	Type currency Properties Create, Filter, Nillable, Sort, Update Description Price paid for this asset.
Product2Id	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the Product2 associated with this asset. Must be a valid Product2 ID. Optional.
PurchaseDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date on which this asset was purchased.
Quantity	Type double Properties Create, Filter, Nillable, Sort, Update

Field	Details
	Description Quantity purchased or installed.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this asset.
SerialNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Serial number for this asset.
Status	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Customizable picklist of values. The default picklist includes the following values: • Purchased • Shipped • Installed • Registered • Obsolete
UsageEndDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date when usage for this asset ends or expires.

Usage

Use this object to track assets previously sold into customer accounts. With asset tracking, a client application can quickly determine which products were previously sold or are currently installed at a specific account.

For example, your organization might want to renew and up-sell opportunities on products sold in the past. Similarly, your organization might want to track competitive products that exist in a customer environment that could potentially be replaced or swapped out.

Asset tracking is also useful for product support, providing detailed information to assist with product-specific support issues. For example, the `PurchaseDate` or `SerialNumber` could indicate whether a given product has certain maintenance requirements, including product recalls. Similarly, the `UsageEndDate` might indicate when the asset was removed from service or when a license or warranty expires.

If an application creates a new Asset record, it must at least specify a `Name` and either an `AccountId`, `ContactId`, or both.

AssetFeed

Represents a single feed item in the feed displayed on the detail page for an asset record. An asset feed shows recent changes to an asset record for any fields that are tracked in feeds, as well as comments and posts about the record. It is a useful way to stay up-to-date with changes to assets. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Asset object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the AssetFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int

Field Name	Details
	Properties Filter , Group , Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter , Group , Nillable , Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the CreatedBy field contains the ID of the system administrator while the ConnectionId contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable , Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group , Nillable , Sort Description The file uploaded to the feed. Required if Type is ContentPost. Setting AssetFeed automatically sets Type to ContentPost.
ContentSize	Type int

Field Name	Details
	Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
FeedPostId	Type reference Properties Filter. Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. Use FeedItem instead. The ID of the associated FeedPost. A FeedPost represents the following types of changes in an AssetFeed: status updates, changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description The ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into the feed, <code>InsertedById</code> is set to the ID of the logged-in user.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description This is a standard system field.

Field Name	Details
	When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on the feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for the <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type <code>int</code> Properties <code>Filter, Group, Sort</code> Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type <code>url</code> Properties <code>Nillable, Sort</code> Description The URL of the <code>LinkPost</code>.
NetworkScope	Type <code>picklist</code> Properties <code>Create, Filter, Group, Nillable, Sort</code> Description Specifies whether this feed item is available in the default <code>community</code>, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a <code>Group</code> or <code>User</code> parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.

Field Name	Details
ParentId	Type reference Properties Filter, Group, Sort Description ID of the asset record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion article associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a new AssetFeed object of Type ContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the AssetFeed. When the Type is LinkPost, the LinkUrl is the URL, and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of AssetFeed item: • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement.

Field Name	Details
	• <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received.

Field Name	Details
	- FacebookPost—generated when a Facebook post is created from a case. Deprecated. - MilestoneEvent—generated when a case milestone is completed or reaches violation status. - SocialPost—generated when a social post is created from a case.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: - AllUsers—The feed item is available to all users who have permission to see the feed item. - InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: - For record posts, Visibility is set to InternalUsers for all internal users by default. - External users can set Visibility only to AllUsers. - On user and group posts, only internal users can set Visibility to InternalUsers. - Visibility can be updated on record posts.

Usage

Use this object to track changes for an asset record.

AssetOwnerSharingRule

Represents the rules for sharing an Asset with users other than the owner. This object is available in API version 33.0 and later.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
AssetAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing being allowed. The possible values are: • Read • Edit
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description The ID representing the source group. Cases owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the target user or group. Target users or groups are given access.

Usage

Use this object to manage the sharing rules for assets. General sharing uses this object.

AssetShare

Represents a sharing entry on an Asset. This object is available in API version 33.0 and later.

Supported Calls

`describeSObjects()`, `create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
AssetAccessLevel	Type picklist

Field	Details
	Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to the Asset. The possible values are: • Read • Edit • All This value is not valid for creating or deleting records. This field must be set to an access level that is higher than the organization's default access level for cases.
AssetId	Type reference Properties Filter, Group, Sort Description ID of the Asset associated with this sharing entry. This field can't be updated.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to <code>Manual</code> (default). Values may include: • <code>Manual</code>—The User or Group has access because a user with "All" access manually shared the Asset with them. • <code>Owner</code>—The User is the owner of the Asset. • <code>Rule</code>—The User or Group has access via an Asset sharing rule.
UserOrGroupId	Type reference Properties Filter, Group, Sort

Field	Details
	Description ID of the User or Group that has been given access to the Asset. This field can't be updated.

Usage

This object allows you to determine which users and groups can view and edit Asset records owned by other users.

If you attempt to create a new record that matches an existing record, request updates any modified fields and returns the existing record.

AssetTag

Associates a word or short phrase with an Asset.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter

Field Name	Details
	Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization. • <code>Personal</code>—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

AssetTag stores the relationship between its parent TagDefinition and the Asset being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

AssignmentRule

Represents an assignment rule associated with a Case or Lead.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `search()`

Special Access Rules

- This object is read only. Assignment rules are created, configured, and deleted in the user interface.
- Customer Portal users can't access this object.

Fields

Field	Details
Active	Type boolean

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this assignment rule is active (<code>true</code>) or not (<code>false</code>).
Name	Type string Properties Filter, Group, Nillable, Sort Description Name of this assignment rule.
SubjectType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Type of assignment rule—Case or Lead.

Usage

Before creating or updating a new Case or Lead, a client application can query (by name) the AssignmentRule to obtain the ID of the assignment rule to use, and then assign that ID to the `assignmentRuleId` field of the AssignmentRuleHeader. The AssignmentRuleHeader can be set using either SOAP API or REST API.

AsyncApexJob

Represents an individual Apex sharing recalculation job, a batch Apex job, a method with the `future` annotation, or a job that implements `Queueable`.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ApexClassID	Type reference,

Field Name	Details
	Properties Filter, Group, Sort Description The ID of the Apex class executing the job. Label is <code>Class ID</code>.
CompletedDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time when the job was completed.
ExtendedStatus	Type string Properties Filter, Group, Nillable, Sort Description If one or more errors occurred during the batch processing, this contains a short description of the first error. A more detailed description of that error, along with any subsequent errors, is emailed to the user who started the running batch class. This field is available in API version 19.0 and later.
JobItemsProcessed	Type int Properties Filter, Group, Sort Description Number of job items processed. Label is <code>Batches Processed</code>.
JobType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of job being processed. Valid values are: • <code>Future</code> • <code>SharingRecalculation</code> • <code>ScheduledApex</code> • <code>BatchApex</code> • <code>BatchApexWorker</code> • <code>TestRequest</code>

Field Name	Details
	• TestWorker • ApexToken • Queueable
MethodName	Type string Properties Filter, Group, Nillable, Sort Description The name of the Apex method being executed. Label is <code>Apex Method</code>.
NumberOfErrors	Type int Properties Filter, Group, Nillable, Sort Description Total number of batches with a failure. A batch is considered transactional, so any unhandled exceptions constitute an entire failure of the batch. Label is <code>Failures</code>.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The status of the job. Valid values are: • Holding¹ • Queued • Preparing • Processing • Aborted • Completed • Failed ¹ This status applies to batch jobs in the Apex flex queue.
TotalJobItems	Type int Properties Filter, Group, Nillable, Sort Description Total number of batches processed. Each batch contains a set of records. Label is <code>Total Batches</code>.

Usage

Use this object to query Apex batch jobs in your organization.

AttachedContentDocument

This read-only object contains all `ContentDocument` objects associated with an object.

Supported Calls

`describeSObjects()`

Fields

Field Name	Details
<code>ContentDocumentId</code>	Type reference Properties Filter, Group, Nillable, Sort Description ID of the attached <code>ContentDocument</code> .
<code>ContentSize</code>	Type int Properties Filter, Group, Nillable, Sort Description Size of the document in bytes.
<code>ContentUrl</code>	Type url Properties Filter, Group, Nillable, Sort Description URL for links and Google Docs. This field is set only for links and Google Docs, and is one of the fields that determine the <code>FileType</code> . This field is available in API version 31.0 and later.
<code>ExternalDataSourceName</code>	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description Name of the external data source in which the document is stored. This field is set only for external documents that are connected to Salesforce. This field is available in API version 32.0 and later.
FileExtension	Type string Properties Filter, Group, Nillable, Sort Description File extension of the attached <code>ContentDocument</code>. This field is available in API version 31.0 and later.
FileType	Type string Properties Filter, Group, Nillable, Sort Description Type of document, determined by the file extension.
LinkedEntityId	Type reference Properties Filter, Group, Sort Description ID of the record the <code>ContentDocument</code> is attached to.
Title	Type string Properties Filter, Group, Sort Description Title of the attached <code>ContentDocument</code>.

Usage

Use this object to list all `ContentDocument` objects attached to an object via a feed post.

To retrieve `ContentDocument` objects, issue a `describe` call on an object, which returns a query result for each activity since the record was created. You can't directly query this object.

Attachment

Represents a file that a User has uploaded and attached to a parent object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Body	Type base64 Properties Create, Update Description Required. Encoded file data.
BodyLength	Type int Properties Filter, Group, Nillable, Sort Description Size of the file (in bytes).
ConnectionReceivedId	Type reference Properties Filter, Nillable Description ID of the <code>PartnerNetworkConnection</code> that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
ConnectionSentId	Type reference Properties Filter, Nillable

Field	Details
	Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the <code>ConnectionSentId</code> field is no longer supported. The <code>ConnectionSentId</code> field is still visible, but the value is null. You can use the new <code>PartnerNetworkRecordConnection</code> object to forward records to connections.
ContentType	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The content type of the attachment. If the Don't allow HTML uploads as attachments or document records security setting is enabled for your organization, you cannot upload files with the following file extensions: <code>.htm</code>, <code>.html</code>, <code>.htt</code>, <code>.htx</code>, <code>.mhtm</code>, <code>.mhtml</code>, <code>.shtm</code>, <code>.shtml</code>, <code>.acgi</code>, <code>.svg</code>.
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Description of the attachment. This field is available in API version 18.0 and later.
IsEncrypted	 Note: This information applies to Platform Encryption and not to Classic Encryption. See the Salesforce Online Help for more information. Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the attachment is encrypted using Platform Encryption (<code>true</code>) or not (<code>false</code>). This field is available in API version 34.0 and later.
IsPartnerShared	Type boolean Properties Defaulted on create, Filter, Update Description Indicates whether this record is shared with a connection using Salesforce to Salesforce. Label is <code>Is Shared With Partner</code>.

Field	Details
IsPrivate	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this record is viewable only by the owner and administrators (<code>true</code>) or viewable by all otherwise-allowed users (<code>false</code>). During a create or update call, it is possible to mark an Attachment record as private even if you are not the owner. This can result in a situation in which you can no longer access the record that you just inserted or updated. Label is Private. Attachments on tasks or events can't be marked private.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of the attached file. Label is File Name.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the User who owns the attachment. This field was required previous to release 9.0. Beginning with release 9.0, it can be null on create. The owner of an attachment on a task or event must be the same as the owner of the task or event.
ParentId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the parent object of the attachment. The following objects are supported as parents of attachments: • Account • Asset • Campaign • Case • Contact

Field	Details
	• Contract • Custom objects • EmailMessage • EmailTemplate • Event • Lead • Opportunity • Product2 • Solution • Task

 **Note:** If you are importing Attachment data and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. For example, for compliance reasons, you may prefer to set the `CreatedDate` to the date the record was originally created in your system, rather than the date it was imported into Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself.

Usage

The API sends and receives the binary file attachment data encoded as a `base64Binary` data type. Prior to creating a record, client applications must encode the binary attachment data as base64. Upon receiving a response, client applications must decode the base64 data to binary (this conversion is usually handled for you by the SOAP client).

The create call restricts these files to a maximum size of 25 MB. For a file attached to a Solution, the limit is 1.5 MB. The maximum email attachment size is 3 MB.

The API supports attachments on email in create, delete, or update calls. The query call does not return attachments parented by email, unless the user performing the query has the “Modify All Data” permission.

 **Note:**

- Attachment records are not searched during text searches.
- When issued by an administrator, the query results include Attachment records from the Recycle Bin.
- When issued by a non-administrator, the `queryAll()` call results do not include Attachment records from the Recycle Bin.

Access to fields depends on the method being used:

- All of the fields are accessible using the `describeObjects()` and `query()` calls. With the `create()` call, you can insert the `Name`, `ParentId`, `Body`, `IsPrivate`, and `OwnerId` fields.
- To modify existing records, the `update()` call gives you access to change the `Name`, `Body`, `IsPrivate`, and `OwnerId` fields.
- You can access all of the fields using a `query()` call. However, you can't receive the `Body` field for multiple records in a single `query()` call. If your query returns the `Body` field, your client application must ensure that only one row with one Attachment is returned; otherwise, an error occurs. A more effective approach is to return IDs (but not Attachment records in the `Body` field) from a `query()` call and then pass them into `retrieve()` calls that return the `Body` field.
- For information about accessing the attachments of archived activities, see Archived Activities.

AuraDefinition

Represents a Lightning definition, such as component markup, a client-side controller, or an event. Lightning components is a beta feature. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AuraDefinitionBundleId</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of the bundle containing the definition. A bundle contains a Lightning definition and all its related resources.
<code>DefType</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The definition type, such as <code>COMPONENT</code> for component markup, or <code>CONTROLLER</code> for a client-side controller.
<code>Format</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The format of the definition. Valid values are: • <code>XML</code> for component markup • <code>JS</code> for JavaScript code • <code>CSS</code> for styles
<code>Source</code>	Type textarea Properties Create, Update

Field Name	Details
	Description The contents of the Lightning definition. This is all the markup or code for the definition.

Usage

For more information, see the [Lightning Components Developer's Guide](#).

AuraDefinitionBundle

Represents a Lightning definition bundle, such as a component or application bundle. A bundle contains a Lightning definition and all its related resources. Lightning components is a beta feature. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>ApiVersion</code>	Type double Properties Create, Filter, Sort, Update Description The API version for this bundle. Every bundle has an API version specified at creation.
<code>Description</code>	Type textarea Properties Create, Filter, Group, Sort, Update Description The text description of the bundle. Maximum size of 255 characters.
<code>DeveloperName</code>	Type string Properties Create, Filter, Group, Sort, Update

Field Name	Details
	Description The unique name of the record in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. This field is automatically generated but you can supply your own value if you create the record using the API.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the <code>MasterLabel</code>.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description Master label for the Lightning bundle. This internal label doesn't get translated.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.

Usage

For more information, see the [Lightning Components Developer's Guide](#).

AuthConfig

Represents authentication options for a community or custom domain that was created by using My Domain.

The fields for this object control the login options that show up on the login page for users of a community or custom domain.

- Logging in with a username and password
- Using SAML for single sign-on
- Authentication provider logins from a third-party service, such as Facebook or Twitter

This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

You must have "View Setup and Configuration" permission to view the settings.

Fields

Field Name	Details
<code>AuthOptionsAuthProvider</code>	Type boolean Properties Filter Description If <code>true</code>, at least one Auth. Provider is selected to show up on the login page, and this object has child <code>AuthConfigProvider</code> objects for each provider.
<code>AuthOptionsSaml</code>	Type boolean Properties Filter Description If <code>true</code>, at least one SAML configuration is selected to show up on the login page. If the organization has only one SAML configuration, this value indicates whether that configuration is selected to show up on the login page. If the organization has multiple SAML configurations, see the child <code>AuthConfigProvider</code> objects for each configuration.

Field Name	Details
AuthOptionsUsernamePassword	Type boolean Properties Filter Description If <code>true</code>, the login option for a username and password appears on the login page.
DeveloperName	Type string Properties Filter, Group, Sort Description The name of the domain created using My Domain or, for communities, a concatenated string of <i>community name_community prefix</i>.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Whether this configuration is in use.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language for the organization.
MasterLabel	Type string Properties Filter, Group, Sort Description The text that's used to identify the Visualforce page in Setup.
NamespacePrefix	Type string Properties Filter, Group, Sort

Field Name	Details
	Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
Type	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The organization type for this object. • <code>Org</code> (includes custom domains) • <code>Community</code> • <code>Site</code> • <code>Portal</code>
Url	Type string Properties Filter, Group, idLookup, Sort Description The login URL of the organization for this AuthConfig object. Each URL has only one associated AuthConfig object.

AuthConfigProviders

Represents an authentication provider that's configured in an organization. This object is a child of the AuthConfig object.

This object links the authentication configuration for an organization to the Auth.Provider through the `AuthOptionsAuthProvider` field of the AuthConfig object. The login page of a Community or custom domain that was created by using My Domain can allow

multiple SAML configurations and multiple authentication providers. These configurations can be set to show up as buttons on the login page. Each configuration has an AuthConfigProvider object. This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

You must have “View Setup and Configuration” permission to view the settings.

Fields

Field Name	Details
AuthConfigId	Type reference Properties Filter, Group, Sort Description The ID for this configuration.
AuthProviderId	Type reference Properties Filter, Group, Sort Description The ID of the Auth. Provider or SAML configuration.

AuthProvider

Represents an Authentication Provider (or Auth Provider) in your organization.

An Auth Provider enables users to log into your Salesforce organization using their login credentials from an external service provider such as Facebook[®] or Janrain[®].

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Only users with the “Customize Application” and “Manage AuthProviders” permissions can access this object.

Fields

Field Name	Details
<code>AuthorizeUrl</code>	Type url Properties Create, Filter, Nillable, Sort, Update Description Required, but only if <code>ProviderType</code> is <code>OpenIdConnect</code>. The OAuth authorization endpoint URL. Used only with OpenID Connect authentication providers. Available in API version 29.0 and later.
<code>ConsumerKey</code>	Type string Properties Create, Filter, Nillable, Sort, Update Description Required. The app's key that is registered at the third-party Single Sign-On provider.
<code>ConsumerSecret</code>	Type string Properties Create, Nillable Description Required. The consumer secret of the app that is registered at the third-party Single Sign-On provider. This field cannot be updated. When using <code>create()</code> this field must be encrypted. To create an encrypted form of the consumer secret from plain text: 1. Create an Auth Provider with the <code>ConsumerSecret</code> plain text value. 2. Save the Auth Provider. 3. Create an outbound change set that includes the Auth Provider component. The new change set .xml file will have an entry in the form <code><consumerSecret>++XYZ++</consumerSecret></code> where <code>++XYZ++</code> is the encrypted secret.
<code>DefaultScopes</code>	Type string Properties Create, Filter, Nillable, Sort, Update

Field Name	Details
	Description Required, but only if <code>ProviderType</code> is <code>OpenIdConnect</code>. The scopes to be sent with the authorization request, if not specified when a flow is started. Used only with OpenID Connect authentication providers. Available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description Required. Used when referring to the Auth Provider from a program.
ErrorUrl	Type string Properties Create, Filter, Nillable, Sort, Update Description A custom error URL for the provider to use to report any errors.
ExecutionUserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The user that runs the Apex handler class. The user must have the “Manage Users” permission. A user is required if you specify a registration handler class.
FriendlyName	Type string Properties Create, Filter, Group, Sort, Update Description Required. A user-friendly name for the provider.
IconUrl	Type url Properties Create, Filter, Nillable, Sort, Update

Field Name	Details
	Description The path to an icon to use as a button on the login page. Users click the button to log in with the associated Auth. Provider.
IdTokenIssuer	Type string Properties Create, Filter, Nillable, Sort, Update Description Only available if <code>ProviderType</code> is <code>OpenIdConnect</code>. This value identifies the source of the authentication token in the form <code>https: URI</code>. Used only with OpenID Connect authentication providers. If provided, Salesforce validates the returned <code>id_token</code> value. The OpenID Connect specification requires an <code>id_token</code> value to be returned with the <code>access_token</code> value. Available in API version 30.0 and later.
LogoutUrl	Type url Properties Create, Filter, Nillable, Sort, Update Description Provides a specific destination for users after they log out if they authenticated using social sign-on. The URL must be fully qualified with an <code>http</code> or <code>https</code> prefix, such as <code>https://acme.my.salesforce.com</code>. Available in API version 33.0 and later.
OptionsIncludeOrgIdInId	Type boolean Properties Create, Filter, Update Description Includes the organization ID to differentiate between users with the same user ID from two sources (such as two sandboxes). Only available for Salesforce authentication providers. Once set to <code>true</code>, it can't be set to <code>false</code>. Available in API version 32.0 and later.
OptionsSendAccessTokenInHeader	Type boolean Properties Create, Filter, Update

Field Name	Details
	Description Required only if <code>ProviderType</code> is <code>OpenIdConnect</code>. When <code>true</code>, the access token is sent to the <code>UserInfoUrl</code> in a header instead of a query string. Used only with OpenID Connect authentication providers. Available in API version 30.0 and later.
<code>OptionsSendClientCredentialsInHeader</code>	Type boolean Properties Create, Filter, Update Description Required only if <code>ProviderType</code> is <code>OpenIdConnect</code>. When <code>true</code>, the client credentials are sent in a header, instead of a query string, to the <code>tokenUrl</code>. The credentials are in the standard OpenID Connect Basic Credentials header form, which is <code>Basic <token></code>, where <code><token></code> is the base64-encoded string <code>"clientkey:clientsecret"</code>. Used only with OpenID Connect authentication providers. Available in API version 30.0 and later.
<code>ProviderType</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. The third-party Single Sign-On provider to use. Valid values are: - Facebook - Salesforce - Janrain - LinkedIn (Available in API version 32.0 and later.) - Twitter (Available in API version 32.0 and later.) - OpenIdConnect (Available in API version 29.0 and later.)  Note: This type requires values for the following fields: - AuthorizeUrl - DefaultScopes - TokenUrl - UserInfoUrl - MicrosoftACS Microsoft Access Control Service typically provides authentication for a Microsoft Office 365 service like SharePoint® Online. (Available in API version 31.0 and later.)

Field Name	Details
RegistrationHandlerId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description An existing Apex class that implements the <code>Auth.RegistrationHandler</code> interface.
TokenUrl	Type url Properties Create, Filter, Nillable, Sort, Update Description Required, but only if <code>ProviderType</code> is <code>OpenIdConnect</code> . The OAuth token endpoint URL. Used only with OpenID Connect authentication providers. Available in API version 29.0 and later.
UserInfoUrl	Type url Properties Create, Filter, Nillable, Sort, Update Description Required, but only if <code>Provider-type</code> is <code>OpenIdConnect</code> . The OpenID Connect endpoint URL. Used only with OpenID Connect authentication providers. Available in API version 29.0 and later.

AuthSession

The AuthSession object represents an individual user session in your organization. This object is available in versions 29.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
CreatedDate	Type dateTime

Field Name	Details
	Properties Defaulted on create, Filter, Sort Description The date and time this session was created. This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description The date and time this session was last updated, A session expires when the current date and time equals LastModifiedDate + NumSecondsValid. This is a standard system field.
LoginGeoId	Type reference Properties Filter, Group, Nillable, Sort Description The 18-character ID for the record of the geographic location of the user for a login event. Due to the nature of geolocation technology, the accuracy of geolocation fields (for example, country, city, postal code) may vary. This field is available in API version 34.0 and later.
LoginHistoryId	Type reference Properties Filter, Group, Nillable, Sort Description The 18-character ID for a successful login event. When a session is reused, Salesforce updates the LoginHistoryId with the value from the most recent login. This field is available in API version 33.0 and later.
LoginType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of login, for example, Application.
LogoutUrl	Type string

Field Name	Details
	Properties Filter, Nillable, Sort Description The page or view to display after users log out of a community, or an organization if they authenticated using SAML. This field is available in API version 32.0 and later.
NumSecondsValid	Type int Properties Filter, Group, Sort Description The number of seconds before the session expires, starting from the last update time.
ParentId	Type reference Properties Filter, Group, Sort Description The 18-character ID for the parent session, if one exists (for example, if the current session is for a canvas app). If the current session doesn't have a parent, this value is the current session's own ID.
SessionSecurityLevel	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Standard or High, depending upon the authentication method used.
SessionType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of session. Common ones are UI, Content, API, and Visualforce.
SourceIp	Type string Properties Filter, Group, Sort

Field Name	Details
	Description IP address of the end user's device from which the session started. This can be an IPv4 or IPv6 address.
UserType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The kind of user for this session. Types include Standard, Partner, Customer Portal Manager, High Volume Portal, and CSN Only.
UsersId	Type reference Properties Filter, Group, Nillable, Sort Description The user's Salesforce user ID.

Usage

The AuthSession object exposes session data and enables read and delete operations on that data. For example, use this object to create a report showing who is signed in to your organization, or to create a tool to delete a session, ending that user's session. For a user, only their own sessions are available, while administrators can see all sessions.

You can't change user sessions with this object; only read and delete them.

Bookmark

Represents a link between opportunities that share common information.

This object is available to organizations with the Similar Opportunities feature enabled.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
ID	Type ID

Field	Details
	Properties Defaulted on create, Filter Description ID of the bookmark. Label is Bookmark ID .
FromId	Type ID Properties Filter Description The originating opportunity. Label is Bookmarked From ID
ToId	Type ID Properties Filter Description The opportunity to which the originating opportunity is linked. Label is Bookmarked To ID .
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .

Usage

The Bookmark object works with the Opportunity object only.

Use this read-only object to query the bookmarks between opportunities in your organization. In the online application, users can search for opportunities that share attributes with their opportunity. The user can then bookmark the appropriate opportunities for future reference.

BrandTemplate

Letterhead for HTML EmailTemplate.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
Description	Type string Properties Create, Filter, Nillable, Sort, Update Description Description of the letterhead. Limited to 1000 characters.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is Letterhead Unique Name.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the letterhead is available for use (<code>true</code>) or not (<code>false</code>). Label is Active.

Field	Details
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the template as it appears in the user interface. Limited to 255 characters. Label is Brand Template Name.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.
Value	Type textarea Properties Create, Update Description The contents of the letterhead, in HTML, including any logos.

Usage

Use this object to brand EmailTemplate records with your letterhead. You can also set a brand template to active or inactive. For example, if you have five different marketing brands, you can maintain each different brand in one template, and assign to the appropriate EmailTemplate.

BusinessHours

This object is used to specify the business hours of your support organization. Escalation rules are run only during these hours. If business hours are associated with any Holiday records, then business hours and escalation rules associated with business hours are suspended during the dates and times specified as holidays.

Supported Calls

`create()`, `getUpdated()`, `query()`, `retrieve()`, `update()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
BusinessHoursId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the BusinessHours associated with the SlaProcess.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the business hours is active (<code>true</code>) or not active (<code>false</code>).
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the business hours.
IsDefault	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Details
	Description Indicates whether the business hours are set as the default business hours (<code>true</code>) or not (<code>false</code>).
FridayEndTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business closes.
FridayStartTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business opens.
MondayEndTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business closes.
MondayStartTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business opens.
SaturdayEndTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business closes.
SaturdayStartTime	Type time

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description Time that business opens.
SundayEndTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business closes.
SundayStartTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business opens.
ThursdayEndTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business closes.
ThursdayStartTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business opens.
TimeZoneSidKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The time zone of the business hours.
TuesdayEndTime	Type time

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description Time that business closes.
TuesdayStartTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business opens.
WednesdayEndTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business closes.
WednesdayStartTime	Type time Properties Create, Filter, Nillable, Sort, Update Description Time that business opens.

Usage

Use this object to specify the business hours at which your support team operates. Escalation rules only run during the business hours with which they are associated. To set business hours to 24-hours a day, set the times from midnight to midnight (00:00:00 ~ 00:00:00) on each day.

By default, business hours are set from 12:00 AM to 12:00 AM in the default time zone specified in your organization's profile.

BusinessProcess

Represents a business process.

Supported Calls

`create()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users cannot access this object.

Fields

Field	Details
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Description of this business process. Limit: 255 characters.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this business process can be presented to users in the Salesforce user interface (<code>true</code>) or not (<code>false</code>) when creating a new record type or changing the business process of an existing record type.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of this business process. Limit: 80 characters.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the

Field	Details
	installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
<code>TableEnumOrId</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Required. One of the following values: Case, Opportunity, or Solution. Label is Entity Enumeration Or ID.

Usage

Use the `BusinessProcess` object to offer different subsets of picklist values to different users for the `LeadStatus`, `CaseStatus`, and `OpportunityStage` fields. Similar to a `RecordType`, a `BusinessProcess` identifies the type of a row in a Case, Lead, or Opportunity and implies a subset of picklist values for these three fields. The values for the remaining picklist fields are driven off of `RecordType`.

CallCenter

This object represents a call center, which is a logical representation of a single computer-telephony integration (CTI) system instance in an organization.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>AdapterURL</code>	Type string Properties Create, Filter, Group, Nillable, Sort

Field	Details
	Description An optional field that specifies the location of where the CTI adapter is hosted. For example, <code>http://localhost:11000</code>. This field is available for call centers using CTI Toolkit version 4.0 and API version 23.0 or later.
CustomSettings	Type string Properties Create, Filter, Group, Nillable, Sort Description Specifies settings in the call center definition file, such as whether the call center uses the Open CTI, and SoftPhone properties, such as height in pixels. This field is available for Open CTI and in API version 25.0 or later.
Id	Type ID Properties Defaulted on create, Filter Description System field that uniquely identifies this call center. Label is Call Center ID. This ID is created automatically when the call center is created.
InternalName	Type string Properties Create, Filter, Group, Sort Description The internal name of the call center. Limit is 80 characters.
Name	Type string Properties Create, Filter, Group, Sort Description The name of the call center. Limit is 80 characters.
Version	Type double

Field	Details
	Properties Create, Filter, Nillable, Sort
	Description The version of the CTI Developer's Toolkit used to create the call center (for versions 2.0 and later). This field is available in API version 18.0 and later.

Usage

Create a call center or query an existing call center.

Campaign

Represents and tracks a marketing campaign, such as a direct mail promotion, webinar, or trade show.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
ActualCost	Type currency
	Properties Create, Filter, Nillable, Sort, Update
	Description Amount of money spent to run the campaign.
AmountAllOpportunities	Type currency
	Properties Filter, Sort

Field	Details
	Description Amount of money in all opportunities associated with the campaign, including closed/won opportunities. Label is Total Value Opportunities .
AmountWonOpportunities	Type currency Properties Filter, Sort Description Amount of money in closed or won opportunities associated with the campaign. Label is Total Value Won Opportunities .
BudgetedCost	Type currency Properties Create, Filter, Nillable, Sort, Update Description Amount of money budgeted for the campaign.
CampaignMemberRecordTypeId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record type ID for CampaignMember records associated with the campaign.
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Nillable, Restricted picklist, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
Description	Type textarea Properties Create, Nillable, Update Description Description of the campaign. Limit: 32 KB. Only the first 255 characters display in reports.

Field	Details
EndDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Ending date for the campaign. Responses received after this date are still counted.
ExpectedResponse	Type percent Properties Create, Filter, Nillable, Sort, Update Description Percentage of responses you expect to receive for the campaign.
ExpectedRevenue	Type currency Properties Create, Filter, Nillable, Sort, Update Description Amount of money you expect to generate from the campaign.
HierarchyActualCost	Type currency Properties Filter, Nillable, Sort Description Calculated field for the total amount of money spent to run the campaigns in a campaign hierarchy. Label is Total Actual Cost in Hierarchy.
HierarchyBudgetedCost	Type currency Properties Filter, Nillable, Sort Description Calculated field for the total amount of money budgeted for the campaigns in a campaign hierarchy. Label is Total Budgeted Cost in Hierarchy.
HierarchyExpectedRevenue	Type currency Properties Filter, Nillable, Sort

Field	Details
	Description Calculated field for the total amount of money you expect to generate from the campaigns in a campaign hierarchy. Label is Total Expected Revenue in Hierarchy.
HierarchyNumberSent	Type int Properties Filter Description Calculated field for the total number of individuals targeted by the campaigns in a campaign hierarchy. For example, the number of email messages sent. Label is Total Num Sent in Hierarchy.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this campaign is active (<code>true</code>) or not (<code>false</code>). Default value is <code>false</code>. Label is Active.
LastActivityDate	Type date Properties Filter, Group, Nillable, Sort Description Value is one of the following, whichever is the most recent: • Due date of the most recent event logged against the record. • Due date of the most recently closed task associated with the record.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update

Field	Details
	Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of the campaign. Limit: is 80 characters.
NumberOfContacts	Type int Properties Filter, Group, Sort Description Number of contacts associated with the campaign. Label is Total Contacts.
NumberOfConvertedLeads	Type int Properties Filter, Group, Sort Description Number of leads that were converted to an account and contact due to the marketing efforts in the campaign. Label is Converted Leads.
NumberOfLeads	Type int Properties Filter, Group, Sort Description Number of leads associated with the campaign. Label is Total Leads.
NumberOfOpportunities	Type int Properties Filter, Group, Sort Description Number of opportunities associated with the campaign. Label is Num Total Opportunities.
NumberOfResponses	Type int

Field	Details
	Properties Filter, Group, Sort Description Number of contacts and unconverted leads with a Member Status equivalent to “Responded” for the campaign. Label is Total Responses .
NumberOfWonOpportunities	Type int Properties Filter, Group, Sort Description Number of closed or won opportunities associated with the campaign. Label is Num Won Opportunities .
NumberSent	Type double Properties Create, Filter, Nillable, Sort, Update Description Number of individuals targeted by the campaign. For example, the number of emails sent. Label is Num Sent .
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the user who owns this campaign. Default value is the user logging in to the API to perform the create.
ParentCampaign	Type reference Properties Create, Filter Nillable, Update Description The campaign above the selected campaign in the campaign hierarchy.
ParentId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description ID of the parent Campaign record, if any.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object.
StartDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Starting date for the campaign.
Status	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Status of the campaign, for example, Planned, In Progress. Limit: 40 characters.
TotalAmountAllOpportunities	Type currency Properties Filter Description Calculated field for total amount of all opportunities associated with the campaign hierarchy, including closed/won opportunities. Label is Total Value Opportunities in Hierarchy .
TotalAmountAllWonOpportunities	Type currency Properties Filter Description Calculated field for amount of all closed/won opportunities associated with the campaign hierarchy. Label is Total Value Won Opportunities in Hierarchy .
TotalNumberOfContacts	Type int

Field	Details
	Properties Filter
	Description Calculated field for number of contacts associated with the campaign hierarchy. Label is Total Contacts in Hierarchy .
TotalNumberOfConvertedLeads	Type int
	Properties Filter
	Description Calculated field for the total number of leads associated with the campaign hierarchy that were converted into accounts, contacts, and opportunities. Label is Total Converted Leads in Hierarchy .
TotalNumberOfLeads	Type int
	Properties Filter
	Description Calculated field for total number of leads associated with the campaign hierarchy. This number also includes converted leads. Label is Total Leads in Hierarchy .
TotalNumberOfOpportunities	Type int
	Properties Filter
	Description Calculated field for the total number of opportunities associated with the campaign hierarchy. Label is Total Opportunities in Hierarchy .
TotalNumberOfResponses	Type int
	Properties Filter
	Description Calculated field for number of contacts and unconverted leads that have a <code>Member Status</code> equivalent to "Responded" for the campaign hierarchy. Label is Total Responses in Hierarchy .
TotalNumberOfWonOpportunities	Type int

Field	Details
	Properties Filter
	Description Calculated field for the total number of won opportunities associated with the campaign hierarchy. Label is Total Won Opportunities in Hierarchy .
Type	Type picklist
	Properties Create, Filter, Group, Nillable, Sort, Update
	Description Type of campaign, for example, Direct Mail or Referral Program. Limit: 40 characters.

Usage

Client applications can create, update, delete, and query Attachment records associated with a campaign via the API.

The Campaign object is defined only for those organizations that have the marketing feature enabled and valid marketing licenses. In addition, it is accessible only to those users that are enabled as marketing users. If the organization does not have the marketing feature or valid marketing licenses, this object does not appear in the `describeGlobal()` call, and you can't use `describeObjects()` or `query()` with the Campaign object.



Note: The main constituent of a campaign is a CampaignMember. You will commonly need to update campaigns with CampaignMember.

CampaignFeed

Represents a single feed item in the feed on a campaign record detail page.

A campaign feed shows recent changes to a campaign record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to campaigns. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Campaign object
- "Moderate Chatter"



Note: Users with the “Moderate Chatter” permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of CampaignFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea

Field	Details
	Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
<code>ContentFileName</code>	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
<code>ContentSize</code>	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
<code>ContentType</code>	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
<code>CreatedDate</code>	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
<code>FeedPostId</code>	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
<code>InsertedById</code>	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
<code>LastModifiedDate</code>	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
<code>LikeCount</code>	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.

Field	Details
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the campaign record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.

Field	Details
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com.

Field	Details
	• TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for a campaign record.

CampaignMember

Represents the association between a campaign and either a lead or a contact.

Supported Calls

For API version 15.0 and earlier: `create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

For API version 16.0 and later: `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
CampaignId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Campaign to which this Lead or Contact is associated.
ContactId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required. ID of the Contact who is associated with a Campaign.
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Nillable, Restricted picklist, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
FirstRespondedDate	Type date

Field	Details
	Properties Filter, Group, Nillable, Sort Description Indicates the date on which the campaign member was first given a responded status.
HasResponded	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the campaign member has responded to the campaign (<code>true</code>) or not (<code>false</code>). Label is Responded.
LeadId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required. ID of the Lead who is associated with a Campaign.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object. To change the record type, modify the <code>CampaignMemberRecordTypeId</code> field on the associated Campaign.
Name	Type string Properties Filter, Group, Nillable, Sort Description First and last name of the contact or lead with which the campaign member is associated.
Status	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Controls the <code>HasResponded</code> flag on this object. You can't directly set the <code>HasResponded</code> flag, as it is read-only, but you can set it indirectly by setting this field in

Field	Details
	a create or update call. Each predefined value implies a <code>HasResponded</code> flag value. Each time you update this field, you implicitly update the <code>HasResponded</code> flag. In the Salesforce user interface, Marketing users can define valid status values for the <code>Status</code> picklist. They can choose one status as the default status. For each <code>Status</code> field value, they can also select which values should be counted as “Responded,” meaning that the <code>HasResponded</code> flag will be set to <code>true</code> for those values. 40 character limit.  Note: When creating or updating campaign members, use the text value for <code>Status</code> instead of the ID from the <code>CampaignMemberStatus</code> object.

 **Note:** If you are importing CampaignMember data into Salesforce and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself..

Usage

Each record has a unique ID, and must contain either a `ContactId` or a `LeadId`, but can't contain both. Any attempt to create a single record with both results in a successful insert but only the `ContactId` will be inserted. However, you can create two separate records on a Campaign—one for the Lead and one for the Contact.

Standard fields from a Contact or Lead are associated with the CampaignMember object but you can't query them directly. To include a lead's `Phone` in your query, for example, query the field from the Lead object.

```
SELECT Id, (SELECT Phone FROM Lead)
FROM CampaignMember
```

This object is defined only for those organizations that have the marketing feature and valid marketing licenses. In addition, the object is accessible only to those users that are enabled as marketing users. If the organization does not have the marketing feature or valid marketing licenses, this object does not appear in the `describeGlobal()` call, and you can't use `describeObjects()` or `query()` with the CampaignMember object.

In API version 16.0 and later, a `create()` call only creates a new record; in earlier versions, a `create()` call creates and updates records. The API determines whether a record exists with the specified `CampaignId` and either `ContactId` or `LeadId`.

 **Note:** Only use a `ContactId` or `LeadId`, but not both, unless you want to track lead-based campaign members you convert to contacts.

If the record does not exist for the given `ContactId` or `LeadId`, then a new record is created. If the record exists, an error is returned and no update is made. To update an existing record, specify the ID of the CampaignMember record to update.

In API versions 15.0 and earlier, if you submit multiple records using a single create request, and if more than one record matches an existing record, only the first record submitted updates the existing record. If any of the submitted records match each other but do not match existing records, only the last record submitted is created.

The `upsert()` call is not supported in API version 16.0 and later. To use the `upsert()` call on this object, you must first delete all data in ID fields except the record ID.

To delete a record, specify the ID of the CampaignMember record to delete.

When creating or updating records, the `Status` field value specified in the call is verified as a valid status for the given Campaign:

- If the specified `Status` value is a valid status, the value is updated, and the `HasResponded` field is updated to either `true` or `false`, depending on the `Status` value association with `HasResponded`.
- If the specified `Status` value is not a valid status, the API assigns the default status to the `Status` field and updates the `HasResponded` field with the associated value. However, if the given Campaign does not have a default status, the API assigns the value specified in the call to the `Status` field, and the `HasResponded` field is set to `false`.

CampaignMemberStatus

One or more member status values defined for a campaign.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

You can't delete a `CampaignMemberStatus` if that status is designated as the default status or if the status is currently used in a Campaign.

Fields

Field	Details
<code>CampaignId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the campaign associated with this member status.
<code>HasResponded</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this status is equivalent to "Responded" (<code>true</code>) or not (<code>false</code>).
<code>IsDefault</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Details
	Description Indicates whether this status is the default status (<code>true</code>) or not (<code>false</code>).
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
Label	Type string Properties Create, Filter, Sort Description Label for the status in the picklist. Limited to 765 characters.
SortOrder	Type int Properties Create, Filter, Group, Sort, Update Description Order where this campaign member status appears in the picklist.

Usage

Use this object to create picklist items for the member status in a campaign.

This object is defined only for those organizations that have the marketing feature and valid marketing licenses. In addition, the object is accessible only to those users that are enabled as marketing users. If the organization does not have the marketing feature or valid marketing licenses, this object does not appear in a `describeGlobal()` call, and you can't use `describeObjects()` or `query()` with the CampaignMember object.

CampaignOwnerSharingRule

Represents the rules for sharing a campaign with User records other than the owner or anyone above the owner in the role hierarchy.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
CampaignAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of access granted to the target Group, or UserRole. The possible values are: • Read • Edit • All
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.

Field	Details
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. ACampaign owned by a User in the source Group triggers the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the User or Group being granted access.

Usage

Use this object to manage the sharing rules for campaigns.

CampaignShare

Represents a sharing entry on a Campaign.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
CampaignId	Type reference

Field	Details
	Properties Filter, Group, Sort Description ID of the Campaign associated with this sharing entry. This field can't be updated.
CampaignAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to the Campaign. The possible values are: • Read • Edit • All (This value is not valid for creating or updating records.) This field must be set to an access level that is higher than the organization's default access level for Campaign.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to Manual (default). There are many possible values, including: • Rule—The User or Group has access via a Campaign sharing rule. • Manual—The User or Group has access because a User with "All" access manually shared the Campaign with them. • Owner—The User is the owner of the Campaign.
UserOrGroupId	Type reference Properties Filter, Group, Sort Description ID of the User or Group that has been given access to the Campaign. This field can't be updated.

Usage

This object allows you to determine which users and groups can view or edit Campaign records owned by other users.

CampaignTag

Associates a word or short phrase with a Campaign.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization.

Field Name	Details
	Personal—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

CampaignTag stores the relationship between its parent TagDefinition and the Campaign being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

Case

Represents a case, which is a customer issue or problem.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
<code>AccountId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the account associated with this case.
<code>CaseNumber</code>	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description Assigned automatically when each case is inserted. It can't be set directly, and it can't be modified after the case is created.
<code>ClosedDate</code>	Type dateTime

Field	Details
	Properties Filter, Nillable, Sort Description The date and time when the case was closed.
CommunityId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the Community (Zone) associated with this case. This field is available in API version 24.0 and later.
ConnectionReceivedId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
ConnectionSentId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the ConnectionSentId field is no longer supported. The ConnectionSentId field is still visible, but the value is null. You can use the new PartnerNetworkRecordConnection object to forward records to connections.
ContactId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the associated Contact.
CreatorFullPhotoUrl	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description URL of the user's profile photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
CreatorName	Type string Properties Filter, Group, Nillable, Sort Description Name of the user who posted the question or reply. Only the first name of internal users (agents) appears to portal users in the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
CreatorSmallPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's thumbnail photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
Description	Type textarea Properties Create, Nillable, Update Description A text description of the case. Limit: 32 KB.
FeedItemId	Type reference Properties Create, Group, Nillable, Sort Description ID of the question in Chatter associated with the case. This field is available in API version 33.0 and later, and is only accessible in organizations where Question-to-Case is enabled.
HasCommentsUnreadByOwner	Type boolean

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a case has comments that have not yet been read by the owner (<code>true</code>) or not (<code>false</code>).
HasSelfServiceComments	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a case has comments added by a Self-Service user (<code>true</code>) or not (<code>false</code>).
IsClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the case is closed (<code>true</code>) or open (<code>false</code>). This field is controlled by the <code>Status</code> field; it can't be set directly. Label is Closed.
IsClosedOnCreate	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the case was closed at the same time that it was created (<code>true</code>) or not (<code>false</code>). This flag is read-only and is automatically set when a record is created. It can't be set to <code>true</code> unless the <code>IsClosed</code> flag is also <code>true</code>.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsEscalated	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Details
	Description Indicates whether the case has been escalated (<code>true</code>) or not. A case's escalated state does not affect how you can use a case, or whether you can query, delete, or update it. However, you can't set this flag via the API. Label is Escalated.
IsSelfServiceClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the case is closed for Self-Service users (<code>true</code>) or not (<code>false</code>).
IsStopped	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether an entitlement process on a case is stopped (<code>true</code>) or not (<code>false</code>).
IsVisibleInSelfService	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the case can be viewed in the Customer Service Portal, Partner Service Portal, and Self-Service Portal (<code>true</code>) or not (<code>false</code>). This field is applied for case visibility in the Partner Relationship Management, Customer Service Portal, and the earlier version of Self Service Portal. The field does not alter sharing and will not prevent usage of a direct URL to a case if a portal user has read or write access.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update

Field	Details
	Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Origin	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The source of the case, such as <code>Email</code>, <code>Phone</code>, or <code>Web</code>. Label is Case Origin.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the contact who owns the case.
ParentId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the parent case in the hierarchy. The label is Parent Case.
Priority	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The importance or urgency of the case, such as <code>High</code>, <code>Medium</code>, or <code>Low</code>.
QuestionId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The question in the answers community that is associated with the case. This field does not appear if you don't have an answers community enabled.
Reason	Type picklist

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The reason why the case was created, such as <code>Instructions not clear</code>, or <code>User didn't attend training</code>.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object.
SlaStartDate	Type dateTime Properties Create, Filter, Nillable, Update Description Shows the time the case entered an entitlement process. You can update or reset the time if you have the "Edit" permission on cases. This field is available in API version 18.0 and later.
Status	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Sort, Update Description The status of the case, such as "New," "Closed," or "Escalated." This field directly controls the <code>IsClosed</code> flag. Each predefined <code>Status</code> value implies an <code>IsClosed</code> flag value. For more information, see <code>CaseStatus</code>.
StopStartDate	Type dateTime Properties Filter, Nillable Description The date and time an entitlement process was stopped on the case. This field is available in API version 18.0 and later.
Subject	Type string

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The subject of the case. Limit: 255 characters.
SuppliedCompany	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The company name that was entered when the case was created. can't be updated after the case has been created. Label is Company.
SuppliedEmail	Type email Properties Create, Filter, Group, Nillable, Sort, Update Description The email address that was entered when the case was created. can't be updated after the case has been created. Label is Email. If your organization has an active auto-response rule, <code>SuppliedEmail</code> is required when creating a case via the API. Auto-response rules use the email in the contact specified by <code>ContactId</code>. If no email address is in the contact record, the email specified here is used.
SuppliedName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The name that was entered when the case was created. can't be updated after the case has been created. Label is Name.
SuppliedPhone	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The phone number that was entered when the case was created. can't be updated after the case has been created. Label is Phone.
Type	Type picklist

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update
	Description The type of case, such as <code>Feature Request</code> or <code>Question</code> .

 **Note:** If you are importing Case data and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself.

Usage

Use the Case object to manage cases for your organization. Client applications can query, update, and delete Attachment records associated with a case via the API.

Assignment Rules

When you query or update a case, your client application can have the case automatically assigned to one or more User records based on assignment rules that have been configured in the user interface. To use this feature, your client application needs to set either of the following options (but not both) in the `AssignmentRuleHeader` used in the create or update:

Field	Field Type	Details
<code>assignmentRuleId</code>	reference	ID of the assignment rule to use. Can be an inactive assignment rule. If unspecified and <code>useDefaultRule</code> is <code>true</code> , then the default assignment rule is used. To find the ID for a given assignment rule, query the <code>AssignmentRule</code> object (specifying <code>RuleType="caseAssignment"</code>), iterate through the returned <code>AssignmentRule</code> objects, find the one you want to use, retrieve its ID, and then specify its ID in this field in the <code>AssignmentRuleHeader</code> .
<code>useDefaultRule</code>	boolean	Specifies whether to use the default rule for rule-based assignment (<code>true</code>) or not (<code>false</code>). The default rule is assigned by users in the Salesforce user interface.

For a code example that shows setting the `AssignmentRuleHeader` for a Lead (which is similar to setting the `AssignmentRuleHeader` for a Case), see [Lead](#).

Separating Accounts from Contacts in Cases

In releases before 8.0, the `AccountId` could not be specified, it was derived from the contact's account. This behavior will continue to be supported in future releases, but you can also now specify an `AccountId`. If you do not specify the `AccountId` during the creation of a case, the value will default to the contact's `AccountId`.



Note: When a record is updated, if the `ContactId` has not changed, then the `AccountId` is not regenerated. This prevents the API from overwriting a value previously changed in the Salesforce user interface. However, if an API call changes the `ContactId` and the `AccountId` field is empty, then the `AccountId` is generated using the contact's account.

Using `_case` with Java

Depending on the development tool you use, you may need to write your application using `_case` instead of `Case`. This is because `case` is a reserved word in Java.

CaseArticle

Represents the association between a `Case` and a `KnowledgeArticle`.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`

Special Access Rules

Access to this object is controlled by the parent `Case` and `KnowledgeArticle`. However, when querying, access is only controlled by the parent `Case`.

Customer Portal users can't access this object.

Fields

Field	Details
<code>ArticleLanguage</code>	Type picklist Properties Filter, Restricted picklist Description The language of the article associated with the case.
<code>ArticleVersionNumber</code>	Type int Properties Create, Group, Nillable Description The number assigned to a version of an article. This field is available in API version 24.0 and later.
<code>CaseId</code>	Type reference

Field	Details
	Properties Create, Filter, Group, Sort
	Description ID of the Case associated with the KnowledgeArticle.
IsSharedByEmail	Type int
	Properties Create, Group, Nillable
	Description Indicates that the article has been shared with the customer through an email.
KnowledgeArticleId	Type reference
	Properties Create, Filter, Group, Sort
	Description ID of the KnowledgeArticle associated with the Case.

Usage

This object lets you send emails with case-article associations and include case-article associations in Apex and Visualforce.

You can't update this object via the API. If you attempt to create a record that matches an existing record, the create request simply returns the existing record.

CaseComment

Represents a comment that provides additional information about the associated Case.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
CommentBody	Type textarea

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description Text of the CaseComment. The maximum size of the comment body is 4,000 bytes. Label is Body.
ConnectionReceivedId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
ConnectionSentId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the ConnectionSentId field is no longer supported. The ConnectionSentId field is still visible, but the value is null. You can use the new PartnerNetworkRecordConnection object to forward records to connections.
CreatorFullPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's profile photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
CreatorName	Type string Properties Filter, Group, Nillable, Sort Description Name of the user who posted the question or reply. Only the first name of internal users (agents) appears to portal users in the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.

Field	Details
CreatorSmallPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's thumbnail photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsPublished	Type boolean Properties Defaulted on create, Create, Filter, Group, Sort, Update Description Indicates whether the CaseComment is visible to customers in the Self-Service portal (<code>true</code>) or not (<code>false</code>). Label is Published. This is the only CaseComment field that can be updated via the API.
ParentId	Type reference Properties Create, Filter, Group, Sort, Description Required. ID of the parent Case of the CaseComment.



Note: If you are importing CaseComment data and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself..

Usage

In the Salesforce user interface, comments are generally entered by a User working on a Case. All users have access to create and view CaseComment in the Salesforce user interface and when using the API. In the API, CaseComment records can't be modified after insertion unless the user has the "Modify All" object-level permission for Cases or the "Modify All Data" permission. If not, users can only update the `IsPublished` field, and can't delete CaseComment.

CaseContactRole

Represents the role that a given Contact plays on a Case.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
CasesId	Type reference Properties Create, Filter, Group, Sort Description ID of the cases associated with this contact.
ContactId	Type reference Properties Create, Filter, Group, Sort, Update Description Required. ID of the contact.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
Role	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Name of the role played by the contact on this contract, such as Decision Maker, Approver, Buyer, and so on. Must be unique—there can't be multiple records in which the <code>ContractId</code>, <code>ContactId</code>, and <code>Role</code> values are identical. Different contacts can play the same role on the same contract. A contact can play different roles on the same contract.

Usage

Use this object to define the role that a given Case plays on a given Contact. For example, you can use this object to be able to see all contacts who are associated to a case, or, given a contact, be able to query all cases that they are associated with, even if they are not the primary contact on the case.

CaseFeed

Represents a single feed item in the feed displayed on the detail page for a case record. A case feed shows recent changes to a case record for any fields that are tracked in feeds, as well as comments and posts about the record. It is a useful way to stay up-to-date with changes to cases. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Case object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nullable, Sort Description The content of the CaseFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.

Field	Details
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection changes a tracked record, the CreatedBy field contains the ID of the system administrator. The ConnectionId contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if Type is ContentPost. Setting ContentFileName automatically sets Type to ContentPost.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.

Field	Details
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
FeedPostId	Type reference Properties Filter. Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. Use FeedItem instead. The ID of the associated FeedPost. A FeedPost represents the following types of changes in a CaseFeed: status updates, changes to tracked fields, text posts, link posts, and content posts. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
InsertById	Type reference Properties Group, Nillable, Sort Description The ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into the feed, <code>InsertById</code> is set to the ID of the logged-in user.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on the feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for the <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>.

Field	Details
	Ordering by <code>LastModifiedDate</code> <code>DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter , Group , Sort Description The number of FeedLikes associated with this feed item.
LinkURL	Type url Properties Nillable, Sort Description The URL of the <code>LinkPost</code> .
NetworkScope	Type picklist Properties Create , Filter , Group , Nillable , Sort Description Specifies whether this feed item is available in the default community , a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: • <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. • <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code> : • Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. • For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. • You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter , Group , Sort

Field	Details
	Description ID of the case record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordID	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion article associated with a <code>ContentPost</code> . This field is null for all posts except <code>ContentPost</code> . For example, set this field to an existing <code>ContentVersion</code> and post it to a feed as a <code>CaseFeed</code> object of <code>Type ContentPost</code> .
Title	Type string Properties Group, Nillable, Sort Description The title of the CaseFeed. When the <code>Type</code> is <code>LinkPost</code> , the <code>LinkURL</code> is the URL, and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of CaseFeed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed.

Field	Details
	• <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.
Visibility	Type picklist

Field	Details
	Properties Create , Filter , Group , Nillable , Sort
	Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>. • <code>Visibility</code> can be updated on record posts.

Usage

Use this object to track changes for a case record.

CaseHistory

Represents historical information about changes that have been made to the associated Case.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

This object is always read-only.

Fields

Field	Details
<code>CaseId</code>	Type reference

Field	Details
	Properties Filter, Group, Sort Description ID of the Case associated with this record.
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Name of the case field that was modified, or a special value to indicate some other modification to the case. The possible values, in addition to the case field names, are: • ownerAssignment—The owner of the case was changed. • ownerAccepted—A user took ownership of a case from a queue. • ownerEscalated—The owner of the case was changed due to case escalation. • external—A user made the case visible to customers in the Customer Self-Service Portal.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
NewValue	Type anyType Properties Nillable, Sort Description New value of the modified case field. Maximum of 255 characters.
OldValue	Type anyType Properties Nillable, Sort Description Previous value of the modified case field. Maximum of 255 characters.

Usage

Case history entries are indirectly created each time a case is modified.

Two rows are added to this record when foreign key fields change. One row contains the foreign key object names that display in the online application. For example, Jane Doe is recorded as the name of a Contact. The other row contains the actual foreign key ID that is only returned to and visible from the API.

This object respects field level security on the parent object.

CaseMilestone

Represents a milestone (required step in a customer support process) on a Case.

Supported Calls

`describeObjects()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
BusinessHoursId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the BusinessHours associated with the CaseMilestone.
CaseId	Type reference Properties Filter Description ID of the case.
CompletionDate	Type dateTime Properties Filter, Nillable, Update Description The date and time the milestone was completed.
ElapsedTimeInDays	Type double

Field	Details
	Properties Filter, Nillable Description The time required to complete a milestone in days.
ElapsedTimeInHrs	Type double Properties Filter, Nillable Description The time required to complete a milestone in hours.
ElapsedTimeInMins	Type int Properties Filter, Nillable Description The time required to complete a milestone in minutes.
IsCompleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the milestone is completed (<code>true</code>) or not (<code>false</code>).
IsViolated	Type boolean Properties Defaulted on create, Filter Description Indicates whether the milestone is violated (<code>true</code>) or not (<code>false</code>).
MilestoneTypeId	Type reference Properties Filter, Nillable Description The ID of the milestone on the case.
StartDate	Type dateTime

Field	Details
	Properties Filter, Nillable, Update Description The date and time the milestone started on the case.
TargetDate	Type dateTime Properties Filter Description The date and time the milestone must be completed.
TargetResponseInDays	Type double Properties Filter, Nillable Description The time to complete the milestone in days.
TargetResponseInHrs	Type double Properties Filter, Nillable Description The time to complete the milestone in hours.
TargetResponseInMins	Type int Properties Filter, Nillable Description The time to complete the milestone in minutes.
TimeSinceTargetInMins	Type text Properties Nillable Description The time elapsed since the milestone target. The format is minutes and seconds.
TimeRemainingInMins	Type text

Field	Details
	Properties Nillable
	Description Time remaining to reach the milestone target. The format is minutes and seconds.

Usage

This object lets you view a milestone on a case. It also lets you view if the milestone was completed and when it must be completed.

CaseOwnerSharingRule

Represents the rules for sharing a case with users other than the owner.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
CaseAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing being allowed. The possible values are: • Read • Edit
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update

Field	Details
	Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. Cases owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description The ID representing the target user or group. Target users or groups are given access.

Usage

Use this object to manage the sharing rules for cases. General sharing and territory management-related sharing use this object.

CaseShare

Represents a sharing entry on a Case.

Supported Calls

`describeSObjects()`, `create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>CaseAccessLevel</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to the Case. The possible values are: • <code>Read</code> • <code>Edit</code> • <code>All</code> This value is not valid for creating or deleting records. This field must be set to an access level that is higher than the organization's default access level for cases.
<code>CaseId</code>	Type reference Properties Filter, Group, Sort

Field	Details
	Description ID of the Case associated with this sharing entry. This field can't be updated.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to <code>Manual</code> (default). Values may include: • <code>Manual</code>—The User or Group has access because a user with “All” access manually shared the Case with them. • <code>Owner</code>—The User is the owner of the Case. • <code>ImplicitChild</code>—User or Group has access to the Case on the Account associated with this Case. • <code>Rule</code>—The User or Group has access via a Case sharing rule.
UserOrGroupId	Type reference Properties Filter, Group, Sort Description ID of the User or Group that has been given access to the Case. This field can't be updated.

Usage

This object allows you to determine which users and groups can view and edit Case records owned by other users.

If you attempt to create a new record that matches an existing record, request updates any modified fields and returns the existing record.

CaseSolution

Represents the association between a Case and a Solution.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
CaseId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Case associated with the Solution.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
SolutionId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Solution associated with the case.

Usage

You can't update this object via the API. If you attempt to create a record that matches an existing record, the request simply returns the existing record.

CaseStatus

Represents the status of a Case, such as New, On Hold, or In Process.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
IsClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this case status value represents a closed Case (<code>true</code>) or not (<code>false</code>). Multiple case status values can represent a closed Case.
IsDefault	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this is the default case status value (<code>true</code>) or not (<code>false</code>) in the picklist.
MasterLabel	Type string Properties Filter, Group, Nillable, Sort Description Master label for this case status value. This display value is the internal label that does not get translated.
SortOrder	Type int Properties Filter, Group, Nillable, Sort Description Number used to sort this value in the case status picklist. These numbers are not guaranteed to be sequential, as some previous case status values might have been deleted.

Usage

This object represents a value in the case status picklist. The case status picklist provides additional information about the status of a Case, such as whether a given `Status` value represents an open or closed case. Query the `CaseStatus` object to retrieve the set of values in the case status picklist, and then use that information while processing Case records to determine more information about a given case. For example, the application could test whether a given case is open or closed based on its `Status` value and the value of the `IsClosed` property in the associated `CaseStatus` object.

CaseTag

Associates a word or short phrase with a Case

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization.

Field Name	Details
	• Personal—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

CaseTag stores the relationship between its parent TagDefinition and the Case being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

CaseTeamMember

Represents a case team member, who works with a team of other users to help resolve a case.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>MemberId</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of the user or contact who is a member on a case team.
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of the case with which the case team member is associated.
<code>TeamRoleId</code>	Type reference Properties Create, Filter, Group, Sort, Update

Field	Details
	Description The ID of the case team role with which the case team member is associated.
TeamTemplateMemberId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the team member included in a predefined case team.

CaseTeamRole

Represents a case team role. Every case team member has a role on a case, such as “Customer Contact” or “Case Manager.”

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of access granted to the target Group for cases. The possible values are: • None • Read • Edit
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the case team role.

Field	Details
PreferencesVisibleInCSP	Type boolean Properties Create, Filter, Update Description Indicates whether or not the case team role is visible to Customer Portal users.

CaseTeamTemplate

Represents a predefined case team, which is a group of users that helps resolve a case.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A text description of the predefined case team.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the predefined case team.

CaseTeamTemplateMember

Represents a member on a predefined case team, which is a group of users that helps resolve cases.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
MemberId	Type reference Properties Create, Filter, Group, Sort Description The ID of the user or contact who is a team member on a predefined case team.
TeamRoleId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the predefined case team member's case team role.
TeamTemplateId	Type reference Properties Create, Filter, Group, Sort Description The ID of the predefined case team's template.

CaseTeamTemplateRecord

The CaseTeamTemplateRecord object is a linking object between the Case and CaseTeamTemplate objects. To assign a predefined case team to a case (customer inquiry), create a CaseTeamTemplateRecord record and point the `ParentId` to the case and the `TeamTemplateId` to the predefined case team.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
ParentId	Type reference Properties Create, Filter, Group, Sort Description The ID of the case with which the case team template record is associated.
TeamTemplateId	Type reference Properties Create, Filter, Group, Sort Description The ID of the predefined case team with which the case team template record is associated.

CategoryData

Represents a logical grouping of Solution records.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
CategoryNodeId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the CategoryNode associated with the solution.

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
RelatedSubjectId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the solution related to the category.

Usage

This object allows you to assign one or more categories to a Solution. It is an intermediate data table with two foreign keys that defines the relationship between a `CategoryNode` and a Solution record.

`CategoryData` has two foreign keys:

- The first foreign key, `CategoryNodeId`, refers to the ID of a `CategoryNode`.
- The other foreign key, `RelatedSubjectId`, refers to a Solution ID.

This is a many-to-many relationship, so there can be multiple rows returned with a `CategoryNodeId`. A Solution can be associated with multiple categories.

CategoryNode

Represents a tree of Solution categories.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Customer Portal users can't access this object.
- Attempting to delete a `CategoryNode` that has children (referred by `CategoryNode.Parent`), or is referred to elsewhere, causes a failure.

Fields

Field	Details
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description Label for the category node.
ParentId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the parent of this node, if any.
SortOrder	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Indicates the sort order of child CategoryNode objects.
SortStyle	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Indicates whether the sort order is alphabetical or custom.

Usage

A CategoryNode defines a category of solutions. In the user interface, you can edit category definitions from Setup by clicking **Customize > Solution > Solution Categories**.

CategoryNodeLocalization

When the Translation Workbench is enabled for your organization, the CategoryNodeLocalization object provides the translation of the label of a solution category.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Your organization must be using Professional, Enterprise, Developer, Unlimited, or Performance Edition and be enabled for the Translation Workbench.
- To view this object, you must have the “View Setup and Configuration” permission.

Fields

Field	Details
<code>CategoryNodeId</code>	Type reference Properties Create, Filter, Nillable Description The ID of the solution <code>CategoryNode</code> that is being translated.
<code>LanguageLocaleKey</code>	Type picklist Properties Create, Filter, Nillable, Restricted picklist Description This field is available in API version 16.0 and earlier. It is the same as the <code>Language</code> field.
<code>Language</code>	Type picklist Properties Create, Filter, Nillable, Restricted picklist Description This field is available in API version 17.0 and later. The combined language and locale ISO code, which controls the language for labels displayed in an application. This picklist contains the following fully-supported languages: • Chinese (Simplified): <code>zh_CN</code> • Chinese (Traditional): <code>zh_TW</code> • Danish: <code>da</code> • Dutch: <code>n1_NL</code> • English: <code>en_US</code>

Field	Details
	• Finnish: <code>fi</code> • French: <code>fr</code> • German: <code>de</code> • Italian: <code>it</code> • Japanese: <code>ja</code> • Korean: <code>ko</code> • Norwegian: <code>no</code> • Portuguese (Brazil): <code>pt_BR</code> • Russian: <code>ru</code> • Spanish: <code>es</code> • Spanish (Mexico): <code>es_MX</code> • Swedish: <code>sv</code> • Thai: <code>th</code> The following end-user only languages are available. • Arabic: <code>ar</code> • Bulgarian: <code>bg</code> • Croatian: <code>hr</code> • Czech: <code>cs</code> • English (UK): <code>en_GB</code> • Greek: <code>el</code> • Hebrew: <code>iw</code> • Hungarian: <code>hu</code> • Indonesian: <code>in</code> • Polish: <code>pl</code> • Portuguese (Portugal): <code>pt_PT</code> • Romanian: <code>ro</code> • Slovak: <code>sk</code> • Slovenian: <code>sl</code> • Turkish: <code>tr</code> • Ukrainian: <code>uk</code> • Vietnamese: <code>vi</code> The following platform languages are available for organizations that use Salesforce exclusively as a platform. • Albanian: <code>sq</code> • Arabic (Algeria): <code>ar_DZ</code> • Arabic (Bahrain): <code>ar_BH</code> • Arabic (Egypt): <code>ar_EG</code> • Arabic (Iraq): <code>ar_IQ</code>

Field**Details**

-
- Arabic (Jordan): `ar_JO`
 - Arabic (Kuwait): `ar_KW`
 - Arabic (Lebanon): `ar_LB`
 - Arabic (Libya): `ar_LY`
 - Arabic (Morocco): `ar_MA`
 - Arabic (Oman): `ar_OM`
 - Arabic (Qatar): `ar_QA`
 - Arabic (Saudi Arabia): `ar_SA`
 - Arabic (Sudan): `ar_SD`
 - Arabic (Syria): `ar_SY`
 - Arabic (Tunisia): `ar_TN`
 - Arabic (United Arab Emirates): `ar_AE`
 - Arabic (Yemen): `ar_YE`
 - Armenian: `hy`
 - Basque: `eu`
 - Bosnian: `bs`
 - Bengali: `bn`
 - Chinese (Simplified—Singapore): `zh_SG`
 - Chinese (Traditional—Hong Kong): `zh_HK`
 - English (Australia): `en_AU`
 - English (Canada): `en_CA`
 - English (Hong Kong): `en_HK`
 - English (India): `en_IN`
 - English (Ireland): `en_IE`
 - English (Malaysia): `en_MY`
 - English (Philippines): `en_PH`
 - English (Singapore): `en_SG`
 - English (South Africa): `en_ZA`
 - Estonian: `et`
 - French (Belgium): `fr_BE`
 - French (Canada): `fr_CA`
 - French (Luxembourg): `fr_LU`
 - French (Switzerland): `fr_CH`
 - Georgian: `ka`
 - German (Austria): `de_AT`
 - German (Luxembourg): `de_LU`
 - German (Switzerland): `de_CH`
 - Hindi: `hi`
-

Field**Details**

- Icelandic: `is`
- Irish: `ga`
- Italian (Switzerland): `it_CH`
- Latvian: `lv`
- Lithuanian: `lt`
- Luxembourgish: `lb`
- Macedonian: `mk`
- Malay: `ms`
- Maltese: `mt`
- Romanian (Moldova): `ro_MD`
- Montenegrin: `sh_ME`
- Romansh: `rm`
- Serbian (Cyrillic): `sr`
- Serbian (Latin): `sh`
- Spanish (Argentina): `es_AR`
- Spanish (Bolivia): `es_BO`
- Spanish (Chile): `es_CL`
- Spanish (Colombia): `es_CO`
- Spanish (Costa Rica): `es_CR`
- Spanish (Dominican Republic): `es_DO`
- Spanish (Ecuador): `es_EC`
- Spanish (El Salvador): `es_SV`
- Spanish (Guatemala): `es_GT`
- Spanish (Honduras): `es_HN`
- Spanish (Nicaragua): `es_NI`
- Spanish (Panama): `es_PA`
- Spanish (Paraguay): `es_PY`
- Spanish (Peru): `es_PE`
- Spanish (Puerto Rico): `es_PR`
- Spanish (United States): `es_US`
- Spanish (Uruguay): `es_UY`
- Spanish (Venezuela): `es_VE`
- Tagalog: `tl`
- Tamil: `ta`
- Urdu: `ur`
- Welsh: `cy`

The values in this field are not related to the default locale selection.

Field	Details
NamespacePrefix	Type string Properties Filter, Nillable Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
Value	Type string Properties Create, Filter, Nillable, Update Description The actual translated label for the solution category. Label is Translation.

Usage

Use this object to translate the labels of your solution categories into a supported language. Users with the Translation Workbench enabled can view category node translations, but either the “Customize Application,” “Manage Translation,” or “Manage Categories” permission is required to create or update category node translations.

ChatterActivity

ChatterActivity represents the number of posts and comments made by a user and the number of comments and likes on posts and comments received by the same user. This object is available in API version 23.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments made by the ParentId.
CommentReceivedCount	Type int Properties Filter, Group, Sort Description The number of FeedComments received by the ParentId.
InfluenceRawRank	Type int Properties Filter, Group, Sort Description Number indicating the ParentId's Chatter influence rank, which is calculated based on the ParentId's ChatterActivity statistics, relative to the other users in the organization. This field is available in API version 26.0 and later.
LikeReceivedCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes received by the ParentId.
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description Identifier of the community to which the ChatterActivity belongs. This field is available only if Salesforce Communities is enabled in your organization. This field is available in API version 26.0 and later.

Field Name	Details
ParentId	Type reference Properties Filter, Group, Nillable, Sort Description Identifier of the object type to which the ChatterActivity is related. In API version 34.0, the ParentId must be a UserId or SelfServiceUser ID.
PostCount	Type int Properties Filter, Group, Sort Description The number of FeedItems made by the ParentId.

Usage

- Use this object to reference the Chatter activity statistics, which include the number of posts and comments made by a user and the number of comments and likes on posts and comments received by the same user.
- You can directly query for ChatterActivity.

```
SELECT Id, PostCount, LikeReceivedCount
FROM ChatterActivity
WHERE ParentId = UserId
```



Note: To query ChatterActivity, you must provide the ParentId. In API version 34.0, the ParentId must be a UserId or SelfServiceUser ID.

- A ChatterActivity record is created for users the first time they post or comment. Users who have never posted or commented don't have ChatterActivity records. If users make only one post and then delete it, they do have ChatterActivity records. In both cases, the user interface displays zeros for their Chatter activity.
- Use the InfluenceRawRank field to reference a user's Chatter influence rank. This field is available in API version 26.0 and later.

ChatterAnswersActivity

Represents the reputation of a User in Chatter Answers communities. This object is available in API version 25.0 and later.

Supported Calls

describeSObjects(), query(), retrieve()

Fields

Field Name	Details
BestAnswerReceivedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of best answers the User has received from other users.
BestAnswerSelectedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of best answers the User has selected.
QuestionsCount	Type int Properties Filter, Group, Nillable, Sort Description The number of Question records posted by the User.
QuestionSubscrCount	Type int Properties Filter, Group, Nillable, Sort Description The number of Question records the User has selected to follow.
QuestionSubscrReceivedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of users following Question records posted by the User.
QuestionUpVotesCount	Type int

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description The number of up votes the User has marked on Question records posted by other users.
QuestionUpVotesReceivedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of up votes the User has received from other users on the Question records he or she has posted.
RepliesCount	Type int Properties Filter, Group, Nillable, Sort Description The number of Reply records posted by the User.
ReplyDownVotesCount	Type int Properties Filter, Group, Nillable, Sort Description The number of down votes the User has marked on Reply records posted by other users.
ReplyDownVotesReceivedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of down votes the User has received from other users on the Reply records he or she has posted.
ReplyUpVotesCount	Type int Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description The number of up votes the User has marked on the Reply records posted by other users.
ReplyUpVotesReceivedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of up votes the User has received from other users on the Reply records he or she has posted.
ReportAbuseOnQuestionsCount	Type int Properties Filter, Group, Nillable, Sort Description The number of abuses that the User has reported on Question records posted by other users.
ReportAbuseOnRepliesCount	Type int Properties Filter, Group, Nillable, Sort Description The number of abuses that the User has reported on Reply records posted by other users.
ReportAbuseReceivedOnQnCount	Type int Properties Filter, Group, Nillable, Sort Description The number of abuses reported by other users on the Question records posted by the User.
ReportAbuseReceivedOnReCount	Type int Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description the number of abuses reported by other users on the Reply records posted by the User.
UserId	Type reference Properties Filter, Group, Nillable, Sort Description The User ID associated with this reputation.
CommunityId	Type reference Properties Filter, Group, Nillable, Sort Description The ID for the zone associated with this reputation.

Usage

Use this object to view metrics on User activity in Chatter Answers. For example, you can use the ChatterAnswersActivity object to view the number of Question records a user is following in Chatter Answers communities.

ChatterAnswersReputationLevel

Represents a reputation level within a Chatter Answers zone. This object is available in API version 26.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
CommunityID	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description ID of the zone for which you're creating the reputation level.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Name of the reputation level.
Value	Type int Properties Create, Filter, Group, Sort, Update Description Minimum number of points for this level.

Usage

Use to create or edit reputation levels for the zone.

ChatterConversation

Represents a private conversation in Chatter, consisting of messages that conversation members have sent or received. This object is available in API version 23.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
Id	Type ID Properties Defaulted on create, Filter, Group, Sort Description ID of the conversation.

Usage

Use this object to identify private conversations in Chatter. Users can access this object if they have the “Manage Chatter Messages” permission. This object is read-only via the API and is provided only to allow administrators to view users' Chatter messages; for example, for compliance purposes.

ChatterConversationMember

Represents a member of a private conversation in Chatter. A member has either sent messages to or received messages from other conversation participants. This object is available in API version 23.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ConversationId	Type reference Properties Filter, Group, Sort Description ID of the associated ChatterConversation.
MemberId	Type reference Properties Filter, Group, Sort Description ID of the conversation member.

Usage

Use this object to view members of private conversations in Chatter. Users can access this object if they have the “Manage Chatter Messages” permission. This object is read-only via the API and is provided only to allow administrators to view users' Chatter messages; for example, for compliance purposes.

ChatterMessage

Represents a message sent as part of a private conversation in Chatter. This object is available in API version 23.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties None Description Text of the message.
ConversationId	Type reference Properties Filter, Group, Sort Description ID of the conversation that the ChatterMessage is associated with.
SenderId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the sender.
SenderNetworkId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the community from which the message was sent. This field is available only if Salesforce Communities is enabled in your organization. This field is available in API version 32.0 and later.
SentDate	Type dateTime Properties Filter, Sort

Field Name	Details
	Description Date the message was sent.

Usage

Use this object to view and delete messages sent or received via private conversations in Chatter. Users can access this object if they have the “Manage Chatter Messages” permission. This object is provided to allow administrators to view and delete users' Chatter messages; for example, for compliance purposes.

Messages are hard deleted. They aren't sent to the Recycle Bin.

ClientBrowser

Represents a cookie added to the browser upon login, and also includes information about the browser application where the cookie was inserted. This object is available in version 28.0 and later.

Supported Calls

`describeSObjects()`, `delete()`, `query()`, `retrieve()`

Fields

Field	Details
<code>FullUserAgent</code>	Type string Properties Filter, Nillable, Sort Description Detailed information about the client (browser). For example, <code>Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.9.0.1) Gecko/2008070208 Firefox/3.0.1</code>
<code>LastUpdate</code>	Type dateTime Properties Filter, Nillable, Sort Description Represents the last time the cookie was changed.
<code>ProxyInfo</code>	Type string

Field	Details
	Properties Filter, Nillable, Sort Description The browser's current proxy information.
UserId	Type reference Properties Nillable, Group, Sort Description The ID of the user associated with this item.

Usage

At every login, the device the login request is from is checked against the known devices using ClientBrowser. A match means a cookie was found on the browser that matches an entry in the ClientBrowser table, so the device is known. No match means that no matching cookie was found, so the device is unknown, and the user is asked to confirm their identity.

CollaborationGroup

Represents a Chatter group. This object is available in API version 19.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

The visibility of information in groups depends on the type of group and the user's permissions.

- **Members:** Any user with the "Create and Own New Chatter Groups" permission can create public, private, and unlisted groups, including in any communities they belong to.
- **Owners and managers:** Users can modify group details for any group they own or manage. Owners can also delete groups they own.
- **Nonmembers:** These user permissions allow group access regardless of group membership.
 - "View All Data"—Allows users to view all public and private groups across their organization and its communities. Users with this permission can't view unlisted group information, unless they have the "Modify Unlisted Groups" permission as well.
 - "Modify All Data"—Allows users to view, modify, and delete all public and private groups across their organization and its communities. Users with this permission can't view or modify unlisted group information, unless they have the "Manage Unlisted Groups" permission as well.
 - "Create and Customize Communities"—Allows users to view, modify, and delete all public and private groups in communities.

- “Manage Unlisted Groups”—Allows users to search for, access, and modify any unlisted group in an organization and its communities.
- “Data Export”—Allows users to export any data from Salesforce, including private and unlisted group data from an organization and its communities.
- **Apex and Visualforce:** Apex code runs in system mode, which means that the permissions of the current user aren’t taken into account.
 - Visualforce pages that display groups might expose unlisted or private group data to users who aren’t members.
 - Because system mode disregards the user’s permissions, all users who are accessing a Visualforce page that’s showing a group can act as an owner of that group.
 - AppExchange apps that are written in Apex and that access all groups will expose unlisted groups to users who aren’t members.

To limit and manage access to the unlisted and private groups in your organization:

- Explicitly filter out unlisted and private group information from SOQL queries in all Apex code.
- Use permission sets, profile-level permissions, and sharing checks in your code to further limit group access.
- Use Apex triggers on the CollaborationGroup object to monitor and manage the creation of groups. In Setup, go to **Chatter > Groups > Group Triggers** to add triggers.

Fields

Field	Details
AnnouncementId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Contains the ID of the Announcement last associated with the group. This field is available in API version 30.0 and later.
CanHaveGuests	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If set to <code>true</code>, indicates that a group allows customers. Chatter customers are users outside your company's email domains who can only see groups they're invited to and interact with members of those groups; they can't see any Salesforce information. This field is available starting in API version 23.0, but groups that allow customers are accessible from earlier API versions. However, when accessed from earlier API versions, groups that allow customers aren't distinguishable from private groups. We strongly recommend that you upgrade to the latest API version. If you must use an earlier version, name groups that allow customers to indicate that they include customers.

Field	Details
CollaborationType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of Chatter group. Available values are: • Public—Anyone can see and post updates. Anyone can join a public group. • Private—Only members can see the group feed and post updates. Non-members can only see the group name and a few other details in list views, search, and on the group page. The group's owner or managers must add members who request to join the group. • Unlisted—Only members and users with the “Manage Unlisted Groups” permission can see the group and post updates. Other users can’t access the group or see it in lists, search, and feeds.
Description	Type string Properties Create, Filter, Nillable, Sort, Update Description Description of the group.
FullPhotoUrl	Type url Properties Filter, Nillable, Sort Description The URL for the group's profile photo. The URL is updated every time a photo is uploaded and reflects the most recent photo. The URL returned for an older photo is not guaranteed to return a photo if a newer photo has been uploaded. You should always query this field for the URL of the most recent photo. This field is available in API version 20.0 and later.
GroupEmail	Type email Properties Group, Nillable, Sort Description The email address for posting to the group. For private groups, only visible to members and users with “Modify All Data” or “View All Data” permissions. This field is available in API version 29.0 and later.

Field	Details
HasPrivateFieldsAccess	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If set to <code>true</code>, indicates that a user can see the <code>InformationBody</code> and <code>InformationTitle</code> fields in a private group. This field is set to <code>true</code> for members of a private group and users with “Modify All Data” or “View All Data” permissions.
InformationBody	Type textarea Properties Create, Nillable, Update Description The text of the Information section. For private groups, only visible to members and users with “Modify All Data” or “View All Data” permissions.
InformationTitle	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The title of the Information section. For private groups, only visible to members and users with “Modify All Data” or “View All Data” permissions.
IsArchived	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the group is archived (<code>true</code>) or not (<code>false</code>).
IsAutoArchiveDisabled	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether automatic archiving is enabled for the group (<code>true</code>) or not (<code>false</code>).
LastFeedModifiedDate	Type dateTime

Field	Details
	Properties Filter, Sort Description The date of the last post or comment on the group.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (LastReferencedDate) and not viewed.
MemberCount	Type int Properties Filter, Group, Nillable, Sort Description The number of members in the group.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Name of the group. Group names must be unique across public and private groups. Unlisted groups don't require unique names.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the community that this group is part of. This field is available only if Salesforce Communities is enabled in your organization.

Field	Details
	You can only add a <code>NetworkId</code> when creating a group. You can't change or add a <code>NetworkId</code> for an existing group. This field is available in API version 26.0 and later.
<code>OwnerId</code>	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the group. Only the current group owner or people with the "Modify All Data" permission can update the <code>OwnerId</code>.
<code>SmallPhotoUrl</code>	Type url Properties Filter, Nillable, Sort Description The URL for a thumbnail of the group's profile photo. The URL is updated every time a photo is uploaded and reflects the most recent photo. The URL returned for an older photo is not guaranteed to return a photo if a newer photo has been uploaded. You should always query this field for the URL of the most recent photo. This field is available in API version 20.0 and later.

Usage

Use this object to create, edit, or delete groups in an organization or in a community. Deleting a group permanently deletes all posts and comments to the group. It also deletes all files and links posted to the group and removes the files from other locations where they were shared.

As a Chatter group member, you can post to the group using the `CollaborationGroupFeed` object. As a Chatter group owner or manager, you can add or remove group members using the `CollaborationGroupMember` object, post announcements to the group using the `Announcement` object, and accept or decline requests to join private groups using the `CollaborationGroupMemberRequest` object. Additionally, the group owner, manager, or your Salesforce system administrator can invite people to join the group using the [CollaborationInvitation](#) object.

The Salesforce system administrator doesn't need to be a member of the group in order to send invitations using the API.

CollaborationGroupFeed

Represents a single feed item on a Chatter group feed.

A group feed shows posts and comments about the group. This object is available in API version 19.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

- "Manage Unlisted Groups"
Only users with this permission can delete items in unlisted groups.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of CollaborationGroupFeed. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the CreatedBy field contains the ID of the system administrator while the ConnectionId contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.

Field	Details
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.

Field	Details
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDate DESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field.

Field	Details
	When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference

Field	Details
	Properties Filter, Group, Sort Description ID of the group that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of ContentPost, LinkPost, and TextPost, feed item types should not be created directly from the API. • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed.

Field	Details
	• CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case. • CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • CaseCommentPost—generated event when a user adds a case comment for a case object. • ChangeStatusPost—generated event when a user changes the status of a case. • ChatTranscriptPost—generated event when Live Agent transcript is saved to a case. • EmailMessageEvent—generated event when an email related to a case object is sent or received. • FacebookPost—generated when a Facebook post is created from a case. Deprecated. • MilestoneEvent—generated when a case milestone is completed or reaches violation status. • SocialPost—generated when a social post is created from a case.  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort

Field	Details
	Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>.

Usage

Use this object to track changes for a group.

CollaborationGroupMember

Represents a member of a Chatter group. This object is available in API version 19.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `describeLayout()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
<code>CollaborationGroupId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the associated <code>CollaborationGroup</code>.
<code>CollaborationRole</code>	Type picklist

Field	Details
	Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The role of a group member. Group owners and managers can change roles for members of their groups. The valid values are: • Standard—Indicates that a user is a group member. Members can post and comment in the group. • Admin—Indicates that a user is a group manager. Managers can post and comment, change member roles, edit group settings, add and remove members, delete posts and comments, and edit the group information field.  Note: To change the group owner, use the <code>OwnerId</code> field on the <code>CollaborationGroup</code> object.
<code>LastFeedAccessDate</code>	Type dateTime Properties Filter, Nillable, Sort Description Date and time when a group member last accessed the group's feed. The value is only updated when a member explicitly consumes the group's feed, not when the member sees group posts in other feeds, like the profile feed.
<code>MemberId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the group member.
<code>NotificationFrequency</code>	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort Description Required. The frequency at which Salesforce sends Chatter group email digests to this member. Can only be set by the member or users with the "Modify All Data" permission. The valid values are: • D—Daily • W—Weekly • N—Never • P—On each post

Field	Details
	The default value is specified by the member in their Chatter email settings. In Communities, the Email on Each Post option is disabled once a group exceeds 10,000 members. All members who had this option selected are automatically switched to Daily digests.

Usage

Use this object to view, create, and delete Chatter group members. You must be a group owner or manager to create members for private Chatter groups.

CollaborationGroupMemberRequest

Represents a request to join a private Chatter group. This object is available in API version 21.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
CollaborationGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the private Chatter group.
RequesterId	Type reference Properties Create, Filter, Group, Sort Description ID of the user requesting to join the group; must be the ID of the context user.
ResponseMessage	Type string Properties Filter, Group, Nillable, Sort, Update Description Optional message to be included in the notification email when <code>Status</code> is <code>Declined</code> .

Field	Details
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description The status of the request. Available values are: - Accepted - Declined - Pending

Usage

This object represents a request to join a private Chatter group, and can be used to accept or decline requests to join private groups you own or manage. On create, an email is sent to the owner and managers of the private group to be accepted or declined. When the `Status` is `Accepted` or `Declined`, an email is sent to notify the requester. When the `Status` is `Declined`, a `ResponseMessage` is optionally included to provide additional details.

Note the following when working with requests:

- Users with the “Modify All Data” or “View All Data” permission can view records for all groups, regardless of membership.
- A user can be a member of 100 groups. Requests to join groups count against this limit.
- `Status` can't be specified on create.
- You can only update a request when the `Status` is `Pending`.
- You can't delete or update a request with a `Status` of `Accepted` or `Declined`.

CollaborationGroupRecord

Represents the records associated with Chatter groups.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`, `undelete()`

Fields

Field	Details
CollaborationGroupId	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description Required. ID of the Chatter group.
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description Optional. The ID of the community that the group belongs to. Available from API version 34.0.
RecordId	Type reference Properties Create, Filter, Group, Sort Description Required. The ID of the record associated with the Chatter group.

CollaborationInvitation

Represents an invitation to join Chatter, either directly or through a group. This object is available in API version 21.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Invitations are available if “Allow Invitations” is enabled for your organization.

Invitations are limited to your allowed domain(s) unless the invite is sent from a private group that allows customers. Allowed domains are set by the administrator.

Invitations to customers are available if “Allow Customer Invitations” is enabled for your organization. Users must have the “Invite Customers to Chatter” permission to send invitations to people outside their Chatter domain.

Fields

Field	Details
InvitedUserEmail	Type string

Field	Details
	Properties Create, Filter, Group, Sort Description The email address for the user invited to join Chatter. Label is <code>Invited Email</code> .
InvitedUserEmailNormalized	Type email Properties Filter, Group, Sort Description A normalized version of the <code>InvitedUserEmail</code> entered. Label is <code>Invited Email (Normalized)</code> .
InviterId	Type reference Properties Filter, Group, Sort Description The person that initiated the invitation.
OptionalMessage	Type string Properties Create, Filter, Group, Nillable, Sort Description An optional message from the person sending the invitation to the person receiving it.
ParentId	Type reference Properties Filter, Group, Nillable, Sort Description Used when the email address on the invitation is different than the one entered when the invitee accepts the invitation.
SharedEntityId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group associated with this invitation.

Field	Details
	• If the invitation is to join Chatter, the <code>SharedEntityId</code> is the ID of the User that created the invitation. The invitee will auto-follow the inviter. • If the invitation is to join a group within Chatter, the <code>SharedEntityId</code> is the ID of the Chatter CollaborationGroup. • To invite a customer, set <code>SharedEntityId</code> to the ID of the private CollaborationGroup with Allow Customers turned on.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The status of the invitation. Possible values are: • Sent • Accepted • Canceled

Usage

Use this object to create or delete (cancel) invitations to join Chatter. You can either invite a user to join Chatter directly or as part of a CollaborationGroup.

 **Note:** To invite someone to join a CollaborationGroup, you must be either the owner or a manager of the group or a Salesforce system administrator.

The Salesforce system administrator doesn't need to be a member of the group in order to send invitations using the API.

When the person accepts your CollaborationGroup invitation, they join the CollaborationGroup and Chatter as well.

 **Note:** You can't send invitations to users of the organization the invite was sent from.

Invited users can view profiles, post on their feed, and join groups, but can't see your Salesforce data or records.

If your organization allows groups with customers, owners and managers of private groups with the "Allow Customers" setting, as well as system administrators, can use this object to invite customers.

Java Samples

The following example shows how to send an invitation to join Chatter:

```
public void invitePeople(String inviterUserId, String invitedEmail) throws Exception {
    CollaborationInvitation invitation = new CollaborationInvitation();
    invitation.setSharedEntityId(inviterUserId); //pass the userId of the inviter
    invitation.setInvitedUserEmail(invitedEmail); //email of the invited user
    insert(invitation);
}
```

The following example shows how to send an invitation to a customer user from a group that allows customers:

```
public void inviteToGroup(String GroupName, String invitedEmail) throws Exception {
    QueryResult qr = query("select id from collaborationgroup where name = '" +
        GroupName); //pass the group name
    String groupId = qr.getRecords()[0].getId();
    CollaborationInvitation invitation = new CollaborationInvitation();
    invitation.setSharedEntityId(groupId); //pass the groupId
    invitation.setInvitedUserEmail(invitedEmail); //email of the invited user
    insert(invitation);
}
```

Apex Samples

```
String emailAddress = 'bob@external.com';
CollaborationGroup chatterGroup = [SELECT Id
    FROM CollaborationGroup
    WHERE Name='All acme.com'
    LIMIT 1];
CollaborationInvitation inv = New CollaborationInvitation();
inv.SharedEntityId = chatterGroup.id;
inv.InvitedUserEmail = emailAddress;

try {
    Insert inv;
} catch(DMLException e){
    System.debug('There was an error with the invite: '+e);
}
```

CombinedAttachment

This read-only object contains all notes, attachments, Google Docs, documents uploaded to libraries in Salesforce CRM Content, and files added to Chatter that are associated with a record.

Supported Calls

describeSObjects()

Fields

Field Name	Details
ContentSize	Type int
	Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description Size of the document in bytes.
ContentUrl	Type url Properties Filter, Group, Nillable, Sort Description URL for links and Google Docs. This field is set only for links and Google Docs, and is one of the fields that determine the <code>FileType</code> . This field is available in API version 31.0 and later.
ExternalDataSourceName	Type string Properties Filter, Group, Nillable, Sort Description Name of the external data source in which the document is stored. This field is set only for external documents that are connected to Salesforce. This field is available in API version 32.0 and later.
FileExtension	Type string Properties Filter, Group, Nillable, Sort Description File extension of the document. This field is available in API version 31.0 and later.
FileType	Type string Properties Filter, Group, Nillable, Sort Description Type of document, determined by the file extension.
ParentId	Type reference Properties Filter, Group, Sort

Field Name	Details
	Description The ID of the parent object.
RecordType	Type string Properties Filter, Group, Nillable, Sort Description The parent object type.
Title	Type string Properties Filter, Group, Nillable, Sort Description Title of the attached file.

Usage

Use this object to list all notes, attachments, documents uploaded to libraries in Salesforce CRM Content, and files added to Chatter for a record, such as a related list on a detail page.

To determine if an object supports the CombinedAttachment object, call `describeSObject()` on the object. For example, `describeSObject('Account')` returns all the child relationships of the Account object, including `CombinedAttachment`. You can then query the `CombinedAttachment` child relationship.

```
SELECT Name, (SELECT Title FROM CombinedAttachments)
FROM Account
```

You can't directly query `CombinedAttachment`.

Community (Zone)

Represents a zone that contains Idea or Question objects.



Note: Starting with the Summer '13 release, Chatter Answers and Ideas "communities" have been renamed to "zones." In API version 28, the API object label has changed to `zone`, but the API type is still `Community`.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	Type textarea Properties Filter, Nillable, Sort Description Text description of the zone.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the zone is active or inactive. An idea or question can only be posted to an active zone.
Name	Type string Properties Filter, Group, Sort Description The name of the zone.
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the Chatter community that this zone is associated with. This field is available only if Salesforce Communities is enabled in your organization. This field is available in API version 34.0 and later.

Usage

Use this object to create a zone in Ideas, Chatter Answers, or Answers. Zones help organize ideas and questions into logical groups and are shared by the Ideas, Answers, and Chatter Answers.

ConnectedApplication

Represents a connected app and its details; all fields are read-only.

Connected apps link client applications, third-party services, other Salesforce organizations, apps and resources to your organization. The connected app configuration specifies authorization and security settings for these resources. This object exposes the settings for a specified connected app.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
MobileSessionTimeout	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Length of time after which the system logs out inactive mobile users.
MobileStartUrl	Type url Properties Filter, idLookup, Nillable, Sort Description Users are directed to this URL after they've authenticated when the app is accessed from a mobile device.
Name	Type string Properties Filter, Group, Sort Description The unique name for this object.
OptionsAllowAdminApprovedUsersOnly	Type boolean Properties Filter Description Indicates whether access is limited to users granted approval to use the connected app by an administrator. Manage profiles for the app by editing each profile's Access list.

Field Name	Details
OptionsHasSessionLevelPolicy	Type boolean Properties Filter Description Specifies whether the connected app requires a High Assurance level session.
OptionsRefreshTokenValidityMetric	Type boolean Properties Filter Description Specifies whether the refresh token validity is based on duration or inactivity. If <code>true</code>, the token validity is measured based on the last use of the token; otherwise, it is based on the token duration.
PinLength	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description For mobile apps, this is the PIN length requirement for users of the connected app. Valid values are 5, 6, 7, 8 or 9.
RefreshTokenValidityPeriod	Type int Properties Filter, Group, Nillable, Sort Description The duration of an authorization token until it expires in hours, months or days as set in the connected app management page.
StartUrl	Type url Properties Filter, Nillable, Sort Description If the app is not accessed from a mobile device, users are directed to this URL after they've authenticated.

Contact

Represents a contact, which is an individual associated with an account.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `merge()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can access only portal-enabled contacts.

Fields

Field	Details
AccountId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the account that is the parent of this contact. We recommend that you only update up to 50 contacts simultaneously when changing the accounts on contacts enabled for a Customer Portal or partner portal. We also recommend that you make this update during times outside of your organization's business hours.
AssistantName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The name of the assistant.
AssistantPhone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description The telephone number of the assistant.
Birthdate	Type date

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The birthdate of the contact. The year portion of the <code>Birthdate</code> field is ignored in filter criteria, including report filters, list view filters, and SOQL queries. For example, the following SOQL query returns contacts with birthdays later in the year than today: <pre>SELECT Name, Birthdate FROM Contact WHERE Birthdate > TODAY</pre>
<code>CanAllowPortalSelfReg</code>	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates whether this contact can self-register for your organization's Customer Portal (<code>true</code>) or not (<code>false</code>).
<code>CleanStatus</code>	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates the record's clean status as compared with Data.com. Values are: <code>Matched</code>, <code>Different</code>, <code>Acknowledged</code>, <code>NotFound</code>, <code>Inactive</code>, <code>Pending</code>, <code>SelectMatch</code>, or <code>Skipped</code>. Several values for <code>CleanStatus</code> display with different labels on the contact record detail page. • <code>Matched</code> displays as <code>In Sync</code> • <code>Acknowledged</code> displays as <code>Reviewed</code> • <code>Pending</code> displays as <code>Not Compared</code>
<code>ConnectionReceivedId</code>	Type reference Properties Filter, Nillable Description ID of the <code>PartnerNetworkConnection</code> that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.

Field	Details
ConnectionSentId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the <code>ConnectionSentId</code> field is no longer supported. The <code>ConnectionSentId</code> field is still visible, but the value is null. You can use the new <code>PartnerNetworkRecordConnection</code> object to forward records to connections.
Department	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The department of the contact.
Description	Type textarea Properties Create, Nillable, Update Description A description of the contact. Label is Contact Description. Limit: 32 KB.
DoNotCall	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates that the contact does not wish to be called.
Email	Type email Properties Create, Filter, Group, Nillable, Sort, Update Description Email address for the contact.
EmailBouncedDate	Type dateTime

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description If bounce management is activated and an email sent to the contact bounces, the date and time the bounce occurred.
EmailBouncedReason	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description If bounce management is activated and an email sent to the contact bounces, the reason the bounce occurred.
Fax	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Fax number for the contact. Label is Business Phone.
FirstName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description First name of the contact. Maximum size is 40 characters.
HasOptedOutOfEmail	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates whether the contact would prefer not to receive email from Salesforce (<code>true</code>) or not (<code>false</code>). Label is Email Opt Out.
HasOptedOutOfFax	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates that the contact does not wish to receive faxes.

Field	Details
HomePhone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Home telephone number for the contact.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsEmailBounced	Type boolean Properties Filter, Group, Sort Description If bounce management is activated and an email is sent to a contact, indicates whether the email bounced (<code>true</code>) or not (<code>false</code>).
IsPersonAccount	Type boolean Properties Defaulted on create, Filter Description Read only. Label is Is Person Account. Indicates whether this account has a record type of Person Account (<code>true</code>) or not (<code>false</code>).
Jigsaw	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description References the ID of a company in Data.com. If an account has a value in this field, it means that the account was imported from Data.com. If the field value is <code>null</code>, the account was not imported from Data.com. Maximum size is 20 characters. Available in API version 22.0 and later. Label is Data.com Key.  Important: The <code>Jigsaw</code> field is exposed in the API to support troubleshooting for import errors and reimporting of corrected data. Do not modify this value.

Field	Details
LastActivityDate	Type date Properties Filter, Group, Nillable, Sort Description Value is one of the following, whichever is the most recent: • Due date of the most recent event logged against the record. • Due date of the most recently closed task associated with the record.
LastCURequestDate	Type dateTime Properties Filter, Nillable, Sort Description The last date that a Stay-in-Touch request was sent to the contact.
LastCUUpdateDate	Type dateTime Properties Filter, Nillable, Sort Description The last time a Stay-in-Touch update was processed for the contact.
LastName	Type string Properties Create, Filter, Group, Sort, Update Description Required. Last name of the contact. Maximum size is 80 characters.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update

Field	Details
	Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
LeadSource	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The source of the lead.
MailingAddress	Type address Properties Filter, Nillable Description The compound form of the mailing address. Read-only. See Address Compound Fields for details on compound address fields.
- MailingCity - MailingState - MailingCountry - MailingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the mailing address.
- MailingStateCode - MailingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO codes for the mailing address's state and country.
MailingStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Street address for mailing address.
MailingLatitude	Type double

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description Used with <code>MailingLongitude</code> to specify the precise geolocation of a mailing address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
<code>MailingLongitude</code>	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>MailingLatitude</code> to specify the precise geolocation of a mailing address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
<code>MasterRecordId</code>	Type reference Properties Filter, Group, Nillable, Sort Description If this object was deleted as the result of a merge, this field contains the ID of the record that was kept. If this object was deleted for any other reason, or has not been deleted, the value is <code>null</code>.
<code>MiddleName</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Middle name of the contact. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.
<code>MobilePhone</code>	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Contact's mobile phone number.
<code>Name</code>	Type string Properties Filter, Group, Sort

Field	Details
	Description Concatenation of <code>FirstName</code> , <code>MiddleName</code> , <code>LastName</code> , and <code>Suffix</code> . Maximum size is 121 characters.
<code>OtherAddress</code>	Type address Properties Filter, Nillable Description The compound form of the other address. Read-only. See Address Compound Fields for details on compound address fields.
• <code>OtherCity</code> • <code>OtherCountry</code> • <code>OtherPostalCode</code> • <code>OtherState</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for alternate address.
• <code>OtherCountryCode</code> • <code>OtherStateCode</code>	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO codes for the alternate address's state and country.
<code>OtherLatitude</code>	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>OtherLongitude</code> to specify the precise geolocation of an alternate address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
<code>OtherLongitude</code>	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>OtherLatitude</code> to specify the precise geolocation of an alternate address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.

Field	Details
OtherPhone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Telephone for alternate address.
OtherStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Street for alternate address.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The ID of the owner of the account associated with this contact.
Phone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Telephone number for the contact. Label is Business Phone.
PhotoUrl	Type url Properties Filter, Group, Nillable, Sort Description Path to be combined with the URL of a Salesforce instance (for example, https://na1.salesforce.com/) to generate a URL to request the social network profile image associated with the contact. Generated URL returns an HTTP redirect (code 302) to the social network profile image for the contact. Blank if Social Accounts and Contacts isn't enabled for the organization or if Social Accounts and Contacts is disabled for the requesting user.

Field	Details
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object.
ReportsToId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description This field is not visible if <code>IsPersonAccount</code> is <code>true</code>.
Salutation	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Honorific abbreviation, word, or phrase to be used in front of name in greetings, such as Dr. or Mrs.
Suffix	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Name suffix of the contact. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.
Title	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Title of the contact such as CEO or Vice President.



Note: If you are importing Contact data and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself..

Usage

Use this object to manage individuals who are associated with an Account in your organization. You can create, query, delete, or update any Attachment associated with a contact.

Create or update contacts by converting a Lead with the `convertLead()` call.

ContactCleanInfo

Stores the metadata Data.com Clean uses to determine a contact record's clean status. Helps you automate the cleaning or related processing of contact records. ContactCleanInfo includes a number of bit vector fields.

- `CleanedBy` indicates who (a user) or what (a Clean job) cleaned the contact record.
- `IsDifferent` indicates whether or not a field on the contact record has a value that differs from the corresponding field on the matched Data.com record.
- `IsFlaggedWrong` indicates whether or not a field on the contact record has a value that is flagged as wrong to Data.com.
- `IsReviewed` indicates whether or not a field on the contact record is in a `Reviewed` state, which means that the value was reviewed by a user but not accepted.

Their individual bits are defined here

Fields

Field Name	Details
Address	Type address Properties Filter, Nillable Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.
City	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the contact.
CleanedByJob	Type boolean Properties Filter

Field Name	Details
	Description Indicates whether the contact record was cleaned by a Data.com Clean job (<code>true</code>) or not (<code>false</code>).
CleanedByUser	Type boolean Properties Filter Description Indicates whether the contact record was cleaned by a Salesforce user (<code>true</code>) or not (<code>false</code>).
ContactId	Type reference Properties Filter, Group, Sort Description The unique, system-generated ID assigned when the contact record was created.
ContactStatusDataDotCom	Type picklist Properties Filter, Group, Nillable, Sort Description The status of the contact per Data.com. Values are: Contact is Active per Data.com, Phone is Wrong per Data.com , Email is Wrong per Data.com, Phone and Email are Wrong per Data.com, Contact Not at Company per Data.com, Contact is Inactive per Data.com, Company this contact belongs to is out of business per Data.com, Company this contact belongs to never existed per Data.com or Email address is invalid per Data.com.
Country	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the contact.
DataDotComID	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description The ID Data.com maintains for the contact.
Email	Type email Properties Filter, Group, Nillable, Sort Description The email address for the contact.
FirstName	Type string Properties Filter, Group, Nillable, Sort Description The contact's first name.
IsDifferentCity	Type boolean Properties Filter Description Indicates whether the contact's <code>City</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentCountry	Type boolean Properties Filter Description Indicates whether the contact's <code>Country</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentCountryCode	Type boolean Properties Filter Description Indicates whether the contact's <code>Country Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).

Field Name	Details
IsDifferentEmail	Type boolean Properties Filter Description Indicates whether the contact's <code>Email</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentFirstName	Type boolean Properties Filter Description Indicates whether the contact's <code>First Name</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentLastName	Type boolean Properties Filter Description Indicates whether the contact's <code>Last Name</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentPhone	Type boolean Properties Filter Description Indicates whether the contact's <code>Phone</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentPostalCode	Type boolean Properties Filter Description Indicates whether the contact's <code>Postal Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentState	Type boolean

Field Name	Details
	Properties Filter Description Indicates whether the contact's <code>State</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentStateCode</code>	Type boolean Properties Filter Description Indicates whether the contact's <code>State Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentStreet</code>	Type boolean Properties Filter Description Indicates whether the contact's <code>Street</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsDifferentTitle</code>	Type boolean Properties Filter Description Indicates whether the contact's <code>Title</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongAddress</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Address</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongEmail</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the contact's <code>Email</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongName</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Name</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongPhone</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Phone</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongTitle</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Title</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsInactive</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the contact has been reported to Data.com as <i>Inactive</i> (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedAddress</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the contact's <code>Address</code> field value is in a <code>Reviewed</code> state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedEmail</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Email</code> field value is in a <code>Reviewed</code> state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedName</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Name</code> field value is in a <code>Reviewed</code> state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedPhone</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Phone</code> field value is in a <code>Reviewed</code> state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedTitle</code>	Type boolean Properties Filter, Update Description Indicates whether the contact's <code>Title</code> field value is in a <code>Reviewed</code> state (<code>true</code>) or not (<code>false</code>).
<code>LastMatchedDate</code>	Type dateTime Properties Filter, Sort Description The date the contact record was last matched and linked to a Data.com record.

Field Name	Details
<code>LastName</code>	Type string Properties Filter, Group, Nillable, Sort Description The contact's last name.
<code>LastStatusChangedById</code>	Type reference Properties Filter, Group, Nillable, Sort Description The ID of who or what last changed the record's <code>Clean Status</code> field value: a Salesforce user or a Clean job.
<code>LastStatusChangedDate</code>	Type dateTime Properties Filter, Nillable, Sort Description The date on which the record's <code>Clean Status</code> field value was last changed.
<code>Latitude</code>	Type double Properties Filter, Nillable, Sort Description Used with <code>Longitude</code> to specify the precise geolocation of a billing address. Data not currently provided.
<code>Longitude</code>	Type double Properties Filter, Nillable, Sort Description Used with <code>Latitude</code> to specify the precise geolocation of a billing address. Data not currently provided.
<code>Name</code>	Type string Properties Filter, Group, Sort, Update

Field Name	Details
	Description Field label is Contact Clean Info Name. The name of the contact. Maximum size is 255 characters.
Phone	Type phone Properties Filter, Group, Nillable, Sort Description The phone number for the contact.
PostalCode	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the contact.
State	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the contact.
Street	Type textarea Properties Filter, Group, Nillable, Sort Description Details for the billing address of the contact.
Title	Type string Properties Filter, Group, Nillable, Sort Description The contact's title.

Usage

Create a customized set of `Title` field values. Use triggers to map values from fields on imported or cleaned records onto a standard set of values.

ContactFeed

Represents a single feed item in the feed on a contact record detail page.

A contact feed shows recent changes to a contact record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to Contact records. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Contact object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of ContactFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.

Field	Details
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.

Field	Details
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an FeedItem: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.

Field	Details
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, LastModifiedDate is the same as CreatedDate. If a FeedComment is inserted on that feed item, then LastModifiedDate becomes the CreatedDate for that FeedComment. Deleting the FeedComment does not change the LastModifiedDate. Ordering by LastModifiedDate DESC sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope:

Field	Details
	- Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the contact record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging).

Field	Details
	For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user’s Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.

Field	Details
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for a contact record.

ContactHistory

Represents the history of changes to the values in the fields of a contact. This object is available in versions 11.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field	Details
	Description The name of the field that was changed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
ContactId	Type reference Properties Filter, Group, Sort Description ID of the Contact. Label is Contact ID .
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this object to identify changes to a contact.

This object respects field level security on the parent object.

ContactOwnerSharingRule

Represents the rules for sharing a contact with a User other than the owner.

 **Note:** Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
ContactAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of access granted to the target Group, UserRole, or User for Contacts. The possible values are: • Read • Edit
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.

Field	Details
	 Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. A Contact owned by a User in the source Group triggers the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the User or Group being granted access.

Usage

Use this object to manage the sharing rules for contacts.

ContactShare

Represents a list of access levels to a Contact along with an explanation of the access level. For example, if you have access to a record because you own it, the `ContactAccessLevel` is `All` and `RowCause` is `Owner`.

Supported Calls

`describeSObjects()`, `create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
ContactId	Type reference Properties Filter, Group, Sort Description ID of the Contact associated with this sharing entry. This field can't be updated.
ContactAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to cases associated with the account Contact. The possible values are: • Read • Edit • All This value is not valid for create or update. This field must be set to an access level that is higher than the organization's default access level for contacts.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to <code>Manual</code> (default). There are many possible values, including:

Field	Details
	• <code>Rule</code>—The User or Group has access via a Contact sharing rule. • <code>ImplicitChild</code>—The User or Group has access to the Contact via sharing access on the associated Account. • <code>Manual</code>—The User or Group has access because a User with “All” access manually shared the Contact with them. • <code>Owner</code>—The User is the owner of the Contact.
<code>UserOrGroupId</code>	Type reference Properties Filter, Group, Sort Description ID of the User or Group that has been given access to the Contact. This field can't be updated.

Usage

This object allows you to determine which users and groups can view or edit Contact records owned by other users.

ContactTag

Associates a word or short phrase with a Contact.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>ItemId</code>	Type reference Properties Create, Filter Description ID of the tagged item.
<code>Name</code>	Type string Properties Create, Filter

Field Name	Details
	Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • Public—The tag can be viewed and manipulated by all users in an organization. • Personal—The tag can be viewed or manipulated only by a user with a matching OwnerId.

Usage

ContactTag stores the relationship between its parent TagDefinition and the Contact being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

ContentDistribution

Represents information about sharing a document. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

- Salesforce CRM Content or Chatter must be enabled to query shared documents. To query content deliveries, content deliveries must be enabled.
- Users (including users with the “View All Data” permission) can query only the files that they have access to. If the file is managed by a Content Library, the user must have “Deliver Content” enabled in the library permission definition and be a member of the library. If the file isn’t managed by a Content Library, the user must have the “Create and Share Content Deliveries for Chatter Files” permission.
- Users can query the `DistributionPublicUrl` and `Password` fields only if they are the file owner, if the file is shared with them, or if the `RelatedRecordId` specifies a record that the users can access.
- If the shared document is deleted, the delete cascades to any associated `ContentDistribution`. The `ContentDistribution` is still queryable by using the `QueryAll` verb.
- If the shared document is archived, the only fields that users can edit are `ExpiryDate` and `PreferencesExpires`.
- Customer Portal users can’t access this object.
- Chatter Free users can’t access this object.

Fields

Field Name	Details
<code>ContentDocumentId</code>	Type reference Properties Filter, Group, Nillable, Sort Description ID of the shared document.
<code>ContentVersionId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the shared document version.
<code>DistributionPublicUrl</code>	Type string Properties Nillable, Sort Description URL of the link to the shared document.
<code>ExpiryDate</code>	Type dateTime

Field Name	Details
	Properties Create, Filter, Nillable, Sort, Update Description Date when the shared document becomes inaccessible.
FirstViewDate	Type dateTime Properties Filter, Nillable, Sort Description Date when the shared document is first viewed.
LastViewDate	Type dateTime Properties Filter, Nillable, Sort Description Date when the shared document was last viewed.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Name of the content delivery.
OwnerId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the user who owns the shared document.
Password	Type string Properties Group, Nillable, Sort Description The password that's needed to access a shared document.
PreferencesAllowOriginalDownload	Type boolean

Field Name	Details
	Properties Create, Filter, Update Description When <code>true</code>, the shared document can be downloaded as the file type that it was uploaded as. When <code>false</code>, download availability depends on whether a preview of the file exists. If a preview exists, the file can't be downloaded. If a preview doesn't exist, the file can still be downloaded. If the shared document is a link, it can't be downloaded.
PreferencesAllowPDFDownload	Type boolean Properties Create, Filter, Update Description When <code>true</code>, the shared document can be downloaded as a PDF if the original file type is PDF or if a PDF preview has been generated.
PreferencesAllowViewInBrowser	Type boolean Properties Create, Filter, Update Description When <code>true</code>, a preview of the shared document can be viewed in a Web browser.
PreferencesExpires	Type boolean Properties Create, Filter, Update Description When <code>true</code>, access to the shared document expires on the date that's specified by <code>ExpiryDate</code>.
PreferencesLinkLatestVersion	Type boolean Properties Create, Filter, Update Description When <code>true</code>, users see the most recent version of a shared document. When <code>false</code>, users see the version of the document that's shared, even if it isn't the most recent version.

Field Name	Details
PreferencesNotifyOnVisit	Type boolean Properties Create, Filter, Update Description When <code>true</code>, the owner of the shared document is emailed the first time that someone views or downloads the shared document.
PreferencesNotifyRndtnComplete	Type boolean Properties Create, Filter, Update Description When <code>true</code>, the owner of the shared document is emailed when renditions of the shared document that can be previewed in a Web browser are generated.
PreferencesPasswordRequired	Type boolean Properties Create, Filter, Update Description When <code>true</code>, a password, specified by <code>Password</code>, is required to access the shared document.
RelatedRecordId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the record, such as an Account, Campaign, or Case, that the shared document is related to.
ViewCount	Type int Properties Filter, Group, Nillable, Sort Description The number of times that the shared document has been viewed.

Usage

Use this object to create, update, delete, or query information about sharing a document by sharing via link in Chatter or by sending as a Salesforce CRM Content delivery.

ContentDistributionView

Represents information about views of a shared document. This read-only object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

- Salesforce CRM Content or Chatter must be enabled to query shared documents. To query content deliveries, content deliveries must be enabled.
- Users (including users with the “View All Data” permission) can query only the files that they have access to. If the file is managed by a Content Library, the user must have “Deliver Content” enabled in the library permission definition and be a member of the library. If the file isn’t managed by a Content Library, the user must have the “Create and Share Content Deliveries for Chatter Files” permission.
- If the shared document is deleted, the delete cascades to any associated ContentDistributionView. The ContentDistributionView is still queryable by using the `QueryAll` verb.
- Customer Portal users can’t access this object.
- Chatter Free users can’t access this object.

Fields

Field Name	Details
DistributionId	Type reference Properties Filter, Group, Sort Description ID of the content delivery that the document is part of.
IsDownload	Type boolean Properties Defaulted on create, Filter, Group, Sort Description <code>true</code> if the shared document is downloaded; <code>false</code> if the shared document is viewed.

Field Name	Details
<code>IsInternal</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description <code>true</code> if the shared document is viewed by a user in the same organization; <code>false</code> if viewed by an external user.
<code>ParentViewId</code>	Type reference Properties Filter, Group, Nillable, Sort Description ID of this instance of accessing the shared document.

Usage

Use this read-only object to query information about users who are accessing shared documents.

ContentDocument

Represents a document that has been uploaded to a library in Salesforce CRM Content or a file in Chatter. This object is available in API versions 17.0 and later for Salesforce CRM Content. The maximum number of documents that can be published is 2,000,000. Archived files count towards this limit and towards storage usage limits..

- Contact Manager, Group, Professional, Enterprise, Unlimited, and Performance Edition customers can publish a maximum of 36,000 new versions per 24-hour period.
- Developer Edition and trial users can publish a maximum of 2,500 new versions per 24-hour period.

This object is available in API version 21.0 and later for Chatter files.

Supported Calls

`delete()`, `describeLayout()` `describeSObjects()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`

Special Access Rules

- Customer and Partner Portal users must have the “View Content in Portal” permission in order to query content in libraries where they have access.
- Users (including users with the “View All Data” permission) can only query files they have access to, including:
 - All Salesforce CRM Content files in libraries they're a member of and in their personal library, regardless of library permissions (API version 17.0 and later).

- All Chatter files they own, posted on their profile, posted on groups they can see, and shared directly with them (API version 21.0 and later).
- A Salesforce CRM Content document can be deleted if any of the following are true:
 - The document is published into a personal library or is in the user's upload queue.
 - The document is published into a public library, the user is a member of that library with the “Add Content” library privilege enabled, and the user trying to delete the document is the owner.
 - The document is published into a public library that has the “Delete Content” or “Manage Library” permission enabled, and the user trying to delete the document is not the owner.

For API version 25.0 and later, you can change ownership of Chatter files and Salesforce CRM Content documents. Note the following:

- To change ownership of a Chatter file, Chatter must be enabled.
- The following must be true to change ownership of a Salesforce CRM Content document:
 - The Salesforce CRM Content app must be enabled.
 - The user who is becoming the owner of the document must have a Salesforce CRM Content feature license.
- A user can change ownership of a Salesforce CRM Content document or Chatter file if any of the following are true:
 - The user is the current owner, or has either the “Modify All Data” or “Manage Salesforce CRM Content” permission enabled.
 - The user has the “Manage Library” permission enabled for the library containing the document.



Note:

- The user who is becoming the owner of the document must be a visible user who is active, but the original owner can be inactive.
- A document's owner can be changed to a user who doesn't have access to the library that contains the document. Library administrators may need to give the new owner membership to the library.

Fields

Field	Details
ArchivedById	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the user who archived the document. This field is available in API version 24.0 and later.
ArchivedDate	Type date Properties Filter, Group, Nillable, Sort Description The date when the document was archived.

Field	Details
	This field is available in API version 24.0 and later.
ContentModifiedDate	Type dateTime Properties Filter, Nillable, Sort Description Date the document was modified. ContentModifiedDate updates when, for example, the document is renamed or a new document version is uploaded. When you're uploading the first version of a document, ContentModifiedDate can be set to the current time or any time in the past. This field is available in API version 32.0 and later.
ContentSize	Type int Properties Filter, Group, Nillable, Sort Description The size of the document in bytes. This field is available in API version 31.0 and later.
Description	Type textarea Properties Filter, Nillable, Sort Description A description of the document. This field is available in API version 31.0 and later.
Division	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization's data. Available only if the organization has the Division permission enabled.
FileExtension	Type string Properties Filter, Group, Nillable, Sort

Field	Details
	Description File extension of the document. This field is available in API version 31.0 and later.
FileType	Type string Properties Filter, Group, Nillable, Sort Description Type of document, determined by the file extension. This field is available in API version 31.0 and later.
IsArchived	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the document has been archived (<code>true</code>) or not (<code>false</code>).
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
LatestPublishedVersionId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the latest document version.

Field	Details
OwnerId	Type reference Properties Filter, Group, Sort, Update Description ID of the owner of this document.
ParentId	Type reference Properties Filter, Group, Nillable, Sort, Update Description ID of the library that owns the document. Created automatically when inserting a ContentVersion via the API for the first time. This field is available in API version 24.0 and later when Salesforce CRM Content is enabled.
PublishStatus	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Indicates if and how the document is published. Valid values are: • P—The document is published to a public library and is visible to other users. Label is Public. • R—The document is published to a personal library and is not visible to other users. Label is Personal Library. • U—The document is not published because publishing was interrupted. Label is Upload Interrupted.
Title	Type string Properties Filter, Group, Sort Description The title of a document.

Usage

- Use this object to retrieve, query, update, and delete the latest version of a document, but not a content pack, in a library or a file in Chatter. Use the `ContentVersion` object to create, query, retrieve, search, edit, and update a specific version of a Salesforce CRM Content document or Chatter file.
 - The `query()` call doesn't return archived documents. The `queryAll()` call returns archived documents.
 - You can't add new versions of archived documents.
 - If Chatter isn't enabled, Chatter files aren't included in query results.
 - You can't query files that are only on records, whether they're public or not.
 - To create a document, create a new version via the `ContentVersion` object without setting the `ContentDocumentId`. This automatically creates a parent document record. When adding a new version of the document, you must specify an existing `ContentDocumentId` which initiates the revision process for the document. When the latest version is published, the title, owner, and publish status fields are updated in the document.
 - When you delete a document, all versions of that document are deleted, including ratings, comments, and tags.
 - You can't create, edit, or delete content packs via the API.
-  **Note:** Content metadata, such as tags, custom fields, and content owners are tracked at the version level rather than at the document level.
- If you query versions in the API, versions with a `PublishStatus` of `Upload Interrupted` are not returned.
 - A document record is a container for multiple version records. You create a new version to add a document to the system. The new version contains the actual file data which allows the document to have multiple versions. The version stores the body of the uploaded document.

ContentDocumentFeed

Represents a single feed item associated with `ContentDocument`. A content document feed shows these content document changes: creating a `ContentDocument` file and uploading a new `ContentDocument`. This object is available in versions 20.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the `ContentDocument` object
- "Moderate Chatter"

 **Note:** Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Create, Nillable, Sort, Update on page 16 Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Create, Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Create, Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Create, Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.

Field	Details
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDate DESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.

Field	Details
<code>IsDeleted</code>	Type <code>boolean</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
<code>LastModifiedDate</code>	Type <code>dateTime</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Sort</code> Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
<code>LikeCount</code>	Type <code>int</code> Properties <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description The number of <code>FeedLikes</code> associated with this feed item.
<code>LinkUrl</code>	Type <code>url</code> Properties <code>Create</code>, <code>Nillable</code>, <code>Sort</code> Description The URL of a <code>LinkPost</code>.
<code>NetworkScope</code>	Type <code>picklist</code> Properties <code>Create</code>, <code>Filter</code>, <code>Group</code>, <code>Nillable</code>, <code>Sort</code>

Field	Details
	Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the document that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Create, Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing ContentVersion and post it to a feed as a <code>FeedItem</code> object of Type <code>ContentPost</code>.
Title	Type string Properties Create, Group, Nillable, Sort Description The title of the <code>FeedItem</code>. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name. The <code>Title</code> field can be updated on posts of Type <code>QuestionPost</code>.

Field	Details
Type	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The type of FeedItem. Except for ContentPost, LinkPost, and TextPost, don't create FeedItem types directly from the API. • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case.

Field	Details
	• CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • CaseCommentPost—generated event when a user adds a case comment for a case object. • ChangeStatusPost—generated event when a user changes the status of a case. • ChatTranscriptPost—generated event when Live Agent transcript is saved to a case. • EmailMessageEvent—generated event when an email related to a case object is sent or received. • FacebookPost—generated when a Facebook post is created from a case. Deprecated. • MilestoneEvent—generated when a case milestone is completed or reaches violation status. • SocialPost—generated when a social post is created from a case.  Note: If you set Type to ContentPost, also specify ContentData and ContentFileName.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers. • Visibility can be updated on record posts.

Usage

Use this object to track changes for a ContentDocument object.

ContentDocumentHistory

Represents the history of a document. This object is available in versions 17.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

- Customer and Partner Portal users must have the “View Content in Portal” permission to query content in libraries where they have access.
- A user can query all versions of a document from their personal library and any version that is part of or shared with a library where they are a member, regardless of library permissions.

Fields

Field	Details
ContentDocumentId	Type reference Properties Filter, Group, Sort Description ID of the document.
Division	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization’s data. Available only if the organization has the Division permission enabled.
Field	Type picklist Properties Filter, Group, Sort, Restricted picklist Description The name of the field that was changed. Possible values include: • <code>contentDocPublished</code>—The document is published into a library. • <code>contentDocUnpublished</code>—The document is archived or removed from a library, either directly or when the owning library is changed.

Field	Details
	• <code>contentDocRepublished</code>—The document is removed from the archive. • <code>contentDocFeatured</code>—The document is featured. • <code>contentDocSubscribed</code>—The document is subscribed to. • <code>contentDocUnsubscribed</code>—The document is no longer subscribed to.
<code>NewValue</code>	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
<code>OldValue</code>	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this read-only object to query the history of a document.

ContentDocumentLink

Represents the link between a Salesforce CRM Content document or Chatter file and where it's shared. A file can be shared with other users, Chatter groups, records, and Salesforce CRM Content libraries. This object is available in versions 21.0 and later for Salesforce CRM Content documents and Chatter files.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `update()`

Special Access Rules

- Customer and Partner Portal users must have the “View Content in Portal” permission to query content in libraries where they have access.
- Users (including users with the “View All Data” permission) can only query files they have access to, including:
 - All Salesforce CRM Content files in libraries they're a member of and in their personal library, regardless of library permissions (API version 17.0 and later).

- All Chatter files they own, posted on their profile, posted on groups they can see, and shared directly with them (API version 21.0 and later).
- In API versions 33.0 and later, you can create and delete ContentDocumentLink objects with a `LinkedEntityId` of any record type that can be tracked in the feed, even if feed tracking is disabled for that record type. Chatter must be enabled for the organization.
- In API versions 25.0 and later, you can create ContentDocumentLink objects with a `LinkedEntityId` of type `User`, `CollaborationGroup`, or `Organization`.
- In API versions 21.0 and later, users with explicit Viewer access (the file has been directly shared with the user) to a file can delete ContentDocumentLink objects between the file and other users who have Viewer access. In the same API versions, any user with Viewer access to a file can delete ContentDocumentLink objects between the file and organizations or groups of which they are a member.
- For organizations with Communities enabled, a document can only be shared with users and groups that are a part of the [community](#) the file was created in.

Fields

Field	Details
ContentDocumentId	Type reference Properties Create, Filter, Group, Sort Description ID of the document.
LinkedEntityId	Type reference Properties Create, Filter, Group, Sort Description ID of the linked object. Can include Chatter users, groups, records (any that support Chatter feed tracking including custom objects), and Salesforce CRM Content libraries.
ShareType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Required. The permission granted to the user of the shared file in a library. This is determined by the permission the user already has in the library. This field is available in API version 25.0 and later. Viewer The user can explicitly view but not edit the shared file. Collaborator The user can explicitly view and edit the shared file.

Field	Details
	Inferred The user's permission is determined by the related record. For shares with a library, this is defined by the permissions the user has in that library.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users, internal users, or shared users. This field is available in API version 26.0 and later. Visibility can have the following values. • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. • SharedUsers—The feed item is available to all users who can see the feed to which the feed item is posted. The SharedUsers value is available in API version 32.0 and later. Note the following exceptions for Visibility. • For posts to a record feed, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers. • For posts to a user feed, if the organization-wide default for user sharing is set to private, Visibility is set to SharedUsers. The visibility of a ContentDocumentLink on a record post is derived from the highest level of visibility of the link on that record.

Usage

Use this object to query the locations where a file is shared or query which files are linked to a particular location. For example, the following query returns a particular document shared with a Chatter group:

```
SELECT ContentDocument.title FROM ContentDocumentLink WHERE ContentDocumentId =
'069D00000000so2' AND LinkedEntityId = '0D5000000089123'
```

- You can't run a query without filters against ContentDocumentLink.
- You can't filter on ContentDocument fields if you're filtering by ContentDocumentId. You can only filter on ContentDocument fields if you're filtering by LinkedEntityId.
- You can't filter on the related object fields. For example, you can't filter on the properties of the account to which a file is linked. You can filter on the properties of the file, such as the title field.

A SOQL query must filter on one of `Id`, `ContentDocumentId`, or `LinkedEntityId`.

ContentFolder

Represents a folder in a content library for adding files. This object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

- Salesforce CRM Content or Chatter must be enabled to access ContentFolder.
- All users with a content feature license can modify folders in their personal library.
- To modify a folder, the user must be a member of the library and have permission to modify folders.

Fields

Field Name	Details
Name	Type string Properties Create, Filter, Group, Sort, Update Description Name of the folder.
ParentContentFolderId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the ParentFolder.

ContentFolderLink

Defines the association between a library and its root folder. This object is available in API version 34.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

- Salesforce CRM Content must be enabled to access ContentFolderLink.
- ContentFolderLink is read-only in the context of a library.

Fields

Field Name	Details
ContentFolderId	Type reference Properties Filter, Group, Sort Description ID of the folder.
ParentEntityId	Type reference Properties Filter, Group, Sort Description Name of the entity the folder hierarchy is linked to.

ContentFolderMember

Defines the association between a file and a folder. This object is available in API version 34.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `update()`

Special Access Rules

- Salesforce CRM Content or Chatter must be enabled to access ContentFolderMember.
- All users with a content feature license can modify folders in their personal library.
- To modify ContentFolderMember, the user must be a member of the library and have permission to modify folders.

Fields

Field Name	Details
ChildRecordId	Type reference Properties Filter, Group, Sort Description ID of the file.
ParentContentFolderId	Type reference Properties Filter, Group, Sort, Update Description ID of the folder the file is in.

ContentHubItem

Represents a file or folder in a Files Connect external data source, such as Microsoft SharePoint or OneDrive for Business. This object is available in API version 33.0 and later.

Special Access Rules

Chatter and Files Connect must be enabled for the organization.

Supported Calls

`describeSObjects()`, `query()`, `search()`



Important: Queries or searches on ContentHubItem must be filtered with the ContentHubRepositoryId field; for example, `SELECT ID from ContentHubItem WHERE ContentHubRepositoryID = <ID of external data source>`.

Fields

Field Name	Details
ContentHubRepositoryId	Type reference Properties Filter, Group, Nillable

Field Name	Details
	Description The ID for the related external data source described by the ContentHubRepository object.
ContentModifiedDate	Type dateTime Properties Nillable Description Date the file or folder content last changed.
ContentSize	Type int Properties Group, Nillable Description File or folder size.
Description	Type string Properties Filter, Group, Nillable Description Explanation of item in external data source.
ExternalContentUrl	Type url Properties Group, Nillable Description The URL of the document content in the external data source.
ExternalDocumentUrl	Type url Properties Group, Nillable Description The URL of the detail page in the external data source.
ExternalId	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description ID for the file or folder in the external data source.
FileExtension	Type string Properties Group, Nillable Description File format extension, such as .doc or .pdf
FileType	Type string Properties Group, Nillable Description Complete file type, such as "Microsoft Word Document."
IsFolder	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether item is a folder or file.
MimeType	Type string Properties Filter, Group, Nillable Description MIME type of the content.
Name	Type string Properties Filter, Nillable, Sort Description Name of the file or folder in the external data source.
Owner	Type string

Field Name	Details
	Properties Filter, Group, Nillable Description Username of the content owner in the external data source.
ParentId	Type string Properties Filter, Group, Nillable Description The ID of the parent folder for the record. This field isn't returned in queries or searches of the ContentHubItem object. It supports only WHERE clauses, such as the following: <pre>WHERE ContentHubRepositoryId = <ID of external source> and ParentId = <ID of parent folder or record>.</pre> Or specify WHERE ParentId = <name of root folder> to return the children of the root folder.  Tip: The ParentId field supports both Salesforce IDs (in the format "0CHxxx") and external IDs.
Title	Type string Properties Group, Nillable Description The title that appears in the content, which often differs from the Name of the containing file or folder.
UpdatedBy	Type string Properties Group, Nillable Description Username for the person who last updated the file.

ContentHubRepository

Represents a Files Connect external data source such as Microsoft SharePoint or OneDrive for Business. This object is available in API version 33.0 and later.

Special Access Rules

Chatter and Files Connect must be enabled for the organization.

Supported Calls

`describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
DeveloperName	Type string Properties Filter, Group, Sort Description The unique name of the record in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. This field is automatically generated but you can supply your own value if you create the record using the API.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
MasterLabel	Type string Properties Filter, Group, Nillable, Sort Description Master label for the external data source. This display value is the internal label and does not get translated.
Type	Type string Properties Filter, Group, Nillable, Sort Description The data source type. Possible values are: - contenthubGoogleDrive - contenthubOffice365 - contenthubOneDrive - contenthubSharepoint

ContentNote

Represents a note in Salesforce. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

- Notes must be enabled.
- Chatter must be enabled.

Fields

Field	Details
Content	Type base64 Properties Create, Nillable, Update Description The content or body of the note. This can include HTML or plain text.
ContentSize	Type int Properties Filter, Group, Nillable, Sort Description Size of the note in bytes.
CreatedById	Type reference Properties Defaulted on createFilter, Group, Sort Description ID of the user who created the note.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort

Field	Details
	Description Date the note was created.
FileExtension	Type string Properties Filter, Group, Nillable, Sort Description File extension of the note.
FileType	Type string Properties Filter, Group, Nillable, Sort Description Type of file for the note. All notes have a file type of <code>SNOTE</code> .
Id	Type id Properties Defaulted on createFilter, Group, Nillable, Sort Description ID of the note.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the note has been deleted.
IsReadOnly	Type boolean Properties Defaulted on create, Group, Sort Description Indicates whether the note is read only.
LastModifiedById	Type reference Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description The ID of the user who last modified the note.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date the note was last modified. Updates when the <code>Title</code> or <code>Content</code> of the note are updated.
OwnerId	Type reference Properties Filter, Group, , Sort Description ID of the owner of the note.
Title	Type string Properties Create, Filter, Group, idLookup, Namefield, Sort, Update Description Title of the note.

Usage

- Use `ContentNote` to create, query, retrieve, search, edit, and update notes.
- `ContentNote` is built on `ContentVersion`, and so it has many of the same usages.
- Not all fields can be set for notes. Only the `Content` and `Title` fields can be updated.
- The maximum file size you can upload via the SOAP API must be less than 50 MB. When a document is uploaded or downloaded via the API, it is converted to base64. This conversion increases the document size by approximately 37%. You must account for the base64 conversion increase so that the file you plan to upload is less than 50 MB.
- SOQL and SOSL queries on the `ContentNote` return only the most recent version of the note.

ContentVersion

Represents a specific version of a document in Salesforce CRM Content or file in Chatter. The maximum number of versions that can be published in a 24-hour period is 36,000. This object is available in versions 17.0 and later for Salesforce CRM Content documents. This object is available in versions 20.0 and later for Chatter files.

Supported Calls

`create()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

- Customer and Partner Portal users must have the “View Content in Portal” permission to query content in libraries where they have access.
- Customer and Partner Portal users can only publish, version, or edit documents if they have a Salesforce CRM Content feature license.
- All users with a content feature license can create versions in their personal library.
- Users (including users with the “View All Data” permission) can only query files they have access to, including:
 - All Salesforce CRM Content files in libraries they're a member of and in their personal library, regardless of library permissions (API version 17.0 and later).
 - All Chatter files they own, posted on their profile, posted on groups they can see, and shared directly with them (API version 21.0 and later).
- All users can update versions in their personal library.
- The owner of a version or document can update the document if they are a member of the library, regardless of library permissions.
- To update a Salesforce CRM Content document, the user must be a member of the library with one of these library privileges enabled:
 - “Add Content”
 - “Add Content On Behalf of Others”
 - “Manage Library”
- `FileType` is defined by either `ContentUrl` for links or `PathOnClient` for documents, but not both.
- In API version 34.0 and later, any file can be shared with libraries, whether the file originated in Chatter or in Salesforce CRM Content.

Fields

Field	Details
Checksum	Type string Properties Filter, Group, Nillable, Sort Description MD5 checksum for the file.
ContentDocumentId	Type reference Properties Create, Filter, Group, Sort Description ID of the document.

Field	Details
ContentLocation	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Origin of the document. Valid values are: • S—This is a document located within Salesforce. Label is Salesforce. • E—This is a document located outside of Salesforce. Label is External.
ContentModifiedById	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user who modified the document.
ContentModifiedDate	Type dateTime Properties Create, Filter, Nillable, Sort Description Date the document was modified. ContentModifiedDate updates when, for example, the document is renamed or a new document version is uploaded. When uploading the first version of a document, ContentModifiedDate can be set to the current time or any time in the past.
ContentSize	Type int Properties Filter, Group, Nillable, Sort Description Size of the document in bytes. Always zero for links.
ContentUrl	Type url Properties Create, Filter, Group, Nillable, Sort, Update Description URL for links. This is only set for links. One of the fields that determines the FileType. The character limit in API versions 34.0 and later is 1,300. The character limit in API versions 32.0 and earlier was 255.

Field	Details
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Description of the content version.
Division	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization's data. Available only if the organization has the Division permission enabled.
ExternalDataSourceId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the external document referenced in the <code>ExternalDataSource</code> object.
ExternalDocumentInfo1	Type string Properties Create, Filter, Nillable, Sort, Update Description The content for this string is determined by the integration from the external source.
ExternalDocumentInfo2	Type string Properties Create, Filter, Nillable, Sort, Update Description The content for this string is determined by the integration from the external source.
FeaturedContentBoost	Type int Properties Filter, Group, Nillable, Sort

Field	Details
	Description Read only. Designates a document as featured.
FeaturedContentDate	Type date Properties Filter, Group, Nillable, Sort Description Date the document was featured.
FileExtension	Type string Properties Filter, Group, Nillable, Sort Description File extension of the document. This field is available in API version 31.0 and later.
FileType	Type string Properties Filter, Group, Sort Description Type of content determined by <code>ContentUrl</code> for links or <code>PathOnClient</code> for documents.
FirstPublishLocationId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the location where the version was first published. If the version is first published into a user's personal library or My Files, the field will contain the ID of the user who owns the personal library or My Files. If the first version is published into a public library, the field will contain the ID of that library. This field is only set the first time a version is published via the API. It isn't set when a version is published in Salesforce CRM Content or uploaded in Chatter. After the version is published, it is a read-only field. If you don't set a <code>FirstPublishLocationId</code> via the API, this field defaults to the user's personal library, unless <code>Origin</code> is set to H, then this field defaults to My Files.

Field	Details
IsEncrypted	 Note: This information applies to Platform Encryption and not to Classic Encryption. See the Salesforce Online Help for more information. Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether files are encrypted using Platform Encryption (<code>true</code>) or not (<code>false</code>). This field is available in API version 34.0 and later.
IsLatest	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this is the latest version of the document (<code>true</code>) or not (<code>false</code>).
IsMajorVersion	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description <code>true</code> if the document is a major version; <code>false</code> if the document is a minor version. Major versions can't be replaced.
Language	Type picklist Properties Create, Filter, Nillable, Restricted picklist, Update Description The language for this document. This field defaults to the user's language unless the organization is multi-language enabled. Specifies the language of the labels returned. The value must be a valid user locale (language and country), such as <code>de_DE</code> or <code>en_GB</code>. For more information on locales, see the Language field on the <code>CategoryNodeLocalization</code> object.
NegativeRatingCount	Type int Properties Filter, Group, Nillable, Sort

Field	Details
	Description Read only. The number of times different users have given the document a thumbs down. Rating counts for the latest version are not version-specific. If Version 1 receives 10 thumbs-down votes, and Version 2 receives 2 thumbs-down votes, the <code>NegativeRatingCount</code> on Version 2 is 12. However, rating counts are not retroactive for prior versions. The <code>NegativeRatingCount</code> on Version 1 is 10.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the community that this file originated from. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. You can only add a <code>NetworkId</code> when creating a file. You can't change or add a <code>NetworkId</code> for an existing file.
Origin	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The source of the content version. Valid values are: • C—This is a Content document from the user's personal library. Label is Content. The <code>FirstPublishLocationId</code> must be the user's ID. If <code>FirstPublishLocationId</code> is left blank, it defaults to the user's ID. • H—This is a Chatter file from the user's My Files. Label is Chatter. The <code>FirstPublishLocationId</code> must be the user's ID. If <code>FirstPublishLocationId</code> is left blank, it defaults to the user's ID. Origin can only be set to H if Chatter is enabled for your organization. This field defaults to C. Label is Content Origin.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of this document.
PathOnClient	Type string

Field	Details
	Properties Create, Filter, Nillable, Sort Description The complete path of the document. One of the fields that determines the <code>FileType</code>.  Note: You must specify a complete path including the path extension in order for the document to be visible in the Preview tab.
<code>PositiveRatingCount</code>	Type int Properties Filter, Group, Nillable, Sort Description Read only. The number of times different users have given the document a thumbs up. Rating counts for the latest version are not version-specific. If Version 1 receives 10 thumbs-up votes, and Version 2 receives 2 thumbs-up votes, the <code>PositiveRatingCount</code> on Version 2 is 12. However, rating counts are not retroactive for prior versions. The <code>PositiveRatingCount</code> on Version 1 is 10.
<code>PublishStatus</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Indicates if and how the document is published. Valid values are: • <code>P</code>—The document is published to a public library and is visible to other users. Label is Public. • <code>R</code>—The document is published to a personal library and is not visible to other users. Label is Personal Library. • <code>U</code>—The document is not published because publishing was interrupted. Label is Upload Interrupted.
<code>RatingCount</code>	Type int Properties Filter, Group, Nillable, Sort Description Read only. Total number of positive and negative ratings.
<code>ReasonForChange</code>	Type string

Field	Details
	Properties Create, Filter, Nillable, Sort Description The reason why the document was changed. This field can only be set when inserting a new version (revising) a document.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type of the version. Custom fields are restricted in <code>RecordTypeId</code>. When an administrator creates a custom field via the API it must be added to at least one page layout: • If the custom field is added to the page layout associated with the General record type, the <code>RecordTypeId</code> that corresponds to that record type does not have to be set on the version record. • If the custom field is added to the page layout associated with a custom record type, the <code>RecordTypeId</code> that corresponds to that record type must be set on the version record.
TagCsv	Type textarea Properties Create, Nillable, Sort, Update Description Text used to apply tags to a content version via the API.
Title	Type string Properties Create, Filter, Group, Sort, Update Description The title of a document.
VersionData	Type base64 Properties Create, Nillable

Field	Details
	Description Encoded file data. This field can't be set for links. The maximum file size you can upload via the SOAP API must be less than 50 MB. When a document is uploaded or downloaded via the API, it is converted to base64 and stored in <code>VersionData</code> . This conversion increases the document size by approximately 37%. You must account for the base64 conversion increase so that the file you plan to upload is less than 50 MB.
VersionNumber	Type string Properties Filter, Group, Nillable, Sort Description The version number. The number increments with each version of the document, for example, 1, 2, 3.

Usage

- Use this object to create, query, retrieve, search, edit, and update a specific version of a Salesforce CRM Content document or Chatter file. Use the `ContentDocument` object to retrieve, query, update, and delete the latest version of a document, but not a content pack, in a library or a file in Chatter.
- Use this object to create, query, retrieve, search, edit, and update a specific version of a Chatter file. Use the `ContentDocument` object to retrieve, query, update, and delete the latest version of a file in Chatter.
- If Chatter isn't enabled, Chatter files aren't included in query results.
- You can't query files that are only on records, whether they're public or not.
- Not all fields can be set for Chatter files.
- You can only update a version if it is the latest version and if it is published.
- You can't archive versions.
- Using API version 32.0 and later, you can update record types on versions.
- You can't delete a version via the API.
- The maximum file size you can upload via the SOAP API must be less than 50 MB. When a document is uploaded or downloaded via the API, it is converted to base64 and stored in `VersionData`. This conversion increases the document size by approximately 37%. You must account for the base64 conversion increase so that the file you plan to upload is less than 50 MB.
- To download a document via the API, you must export the `VersionData` of the document. This does not increase the download count.
- When you upload a document from your local drive using the Data Loader, you must specify the actual path in both `VersionData` and `PathOnClient`. `VersionData` identifies the location and extracts the format and `PathOnClient` identifies the type of document being uploaded.
- SOQL queries on the `ContentVersion` object return all versions of the document. SOSL searches on the `ContentVersion` object return only the most recent version of the document.
- If you query versions in the API, versions with a `PublishStatus` of `Upload Interrupted` are not returned.

- Documents published into a personal library assume the default record type that is set for the user profile of the person publishing the document (General, if no default is set for the user profile).



Note: An administrator can rename the default (*Content Version Layout*) page layout.

- Contact Manager, Group, Professional, Enterprise, Unlimited, and Performance Edition customers can publish a maximum of 36,000 new versions per 24-hour period. Developer Edition and trial users can publish a maximum of 2,500 new versions per 24-hour period.
- Custom validation rules can prevent an update of documents published into a personal library via the API.

Applying Tags to ContentVersion Records

Tags can be applied to ContentVersion records using either Enterprise or Partner API.

To apply tags to a ContentVersion record, set a value in the `TagCsv` field. For example, setting this field to `one, two, three` creates and associates three tags to that version.

- The maximum length of the `TagCsv` field is 2,000 characters.
- The maximum length of an individual tag is 100 characters.
- When tags are applied to a version, the content is indexed automatically and the tags are searchable.
- You can't apply tags to a `TagCsv` that is published into a personal library.
- You can't apply tags using the `ContentDocument` object.
- You can't change or delete tag names. You can remove tags from a document, but that doesn't delete the tag.
- Tags are case insensitive. You can't have two tags with the same name even if they use different uppercase and lowercase letters. The case of the original tag is always used.

To delete tags from a ContentVersion record, perform a standard API update, and remove any values from the `TagCsv` field that you want to delete. For example, if the original `TagCsv` is `one, two, three`, perform an API update specifying `one, three` in the `TagCsv` field to delete `two`. To delete all tags from a ContentVersion you perform a standard API update by setting the field to `null`.

If you create a ContentVersion record and want to revise it via the API, you insert another ContentVersion record but associate it to the same ContentDocument record as the original. This has an impact on tagging:

- If you insert the revision and do not set any value in the `TagCsv` field, any tags applied to the previous version are automatically applied to the new version.
- If you insert the revision and specify a new `TagCsv` field, no tags transfer over and the tags you specify are applied instead.

When you perform a SOQL query for a ContentVersion record and select the `TagCsv` field, all the tags associated with that record are returned. The tags in the string are always ordered alphabetically even if they were inserted in a different order. You can't use the `TagCsv` field as part of a filter in a SOQL query. You can't query all tags in your organization.

Library tagging rules:

- API tagging respects the tagging restrictions that exist on any library that the document is published into. For example, if the library is in restricted tagging mode and only allows tags `one, three`, you can't save a version with a `TagCsv` of `one, two, three`.
- If the library is in guided tagging mode, you can apply tags to the ContentVersion. You can't query the value of guided tags on a library, but you can query the tagging model of a library.

ContentVersionHistory

Represents the history of a specific version of a document. This object is available in versions 17.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

- Customer and Partner Portal users must have the “View Content in Portal” permission to query content in libraries where they have access.
- A user can query all versions of a document from their personal library and any version that is part of or shared with a library where they are a member, regardless of library permissions.

Fields

Field	Details
ContentVersionId	Type reference Properties Filter, Group, Sort Description ID of the version.
Division	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization’s data. Available only if the organization has the Division permission enabled.
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed. Possible values include: • <code>contentVersionCreated</code>—A new version is created. • <code>contentVersionUpdated</code>—The title, description, or any custom field on the version is changed. • <code>contentVersionDownloaded</code>—A version is downloaded. • <code>contentVersionViewed</code>—The version details are viewed. • <code>contentVersionRated</code>—The version is rated. • <code>contentVersionCommented</code>—The version receives a comment.

Field	Details
	• <code>contentVersionDataReplaced</code>—The new version replaces the previous version, which can happen only when the new version is uploaded immediately after the previous version.
<code>NewValue</code>	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
<code>OldValue</code>	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this read-only object to query the history of a document version.

ContentWorkspace

Represents a public library in Salesforce CRM Content. This object is available in versions 17.0 and later.

 **Note:** This object does not apply to personal libraries.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

- Customer and Partner Portal users can only edit the library document object if they have a Salesforce CRM Content feature license.
- Customer and Partner Portal users can query this object if they have the “View Content in Portal” permission. A user can query all public libraries where they are members, regardless of library permissions.

Fields

Field	Details
DefaultRecordTypeId	Type reference Properties Filter, Nillable Description ID of the default content type for the library. Content types are the containers for custom fields in Salesforce CRM Content.
Description	Type textarea Properties Filter, Nillable Description Text description of the content library.
IsRestrictContentTypes	Type boolean Properties Defaulted on create, Filter Description Read only. Indicates whether content types have been restricted (<code>true</code>) or not (<code>false</code>).
IsRestrictLinkedContentTypes	Type boolean Properties Defaulted on create, Filter Description Read only. Indicates whether linked content types have been restricted (<code>true</code>) or not (<code>false</code>).
Name	Type string Properties Filter, idLookup Description Name of the library.
TagModel	Type picklist

Field	Details
	Properties Filter, Nillable, Restricted picklist
	Description The type of tagging assigned to a library. Valid values are: • U — Unrestricted. No restrictions on tagging. Users can enter any tag when publishing or editing content. • G — Guided. Users can enter any tag when publishing or editing content, but they are also offered a list of suggested tags. • R — Restricted. Users must choose from a list of suggested tabs.

Usage

Use this object to query libraries to find out where documents can be published.

If the content type is not specified when publishing a new version into a library, it will be determined by the `DefaultRecordTypeId` of the primary library.

You can't create, update, or delete a library via the API.

ContentWorkspaceDoc

Represents a link between a document and a public library in Salesforce CRM Content. This object is available in versions 17.0 and later.



Note: This object does not apply to documents and versions in a personal library.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Customer and Partner Portal users must have the “View Content in Portal” permission in order to query and obtain content in libraries where they have access.
- Customer and Partner Portal users can only edit documents if they have a Salesforce CRM Content feature license.
- To create a `ContentWorkspaceDoc`, you must be a member of the library with one of these library privileges enabled:
 - “Add Content”
 - “Add Content On Behalf of Others”
 - “Manage Library”
- To query all library documents in a library, a user must be a member of that library, regardless of library permissions.

Fields

Field	Details
ContentDocumentId	Type reference Properties Create, Filter Description Read only. ID of the library document.
ContentWorkspaceId	Type reference Properties Create, Filter Description Read only. ID of the library.
IsOwner	Type boolean Properties Defaulted on create, Filter Description Read only. Indicates whether the library owns the document and determines permissions for that document (<code>true</code>) or not (<code>false</code>). Documents can belong to more than one library, but only one library owns the document and determines its permissions.

Usage

- Use this object to link a document to one or more libraries.
- To share a document with additional libraries, create additional ContentWorkspaceDoc records which join the document to the additional libraries.
- Inserting a ContentWorkspaceDoc triggers the publish process for public libraries.
- A document can be published into many public libraries, but it will always be owned by one library which controls the security of the document.
- A document can only be published into the document owner's personal library. You can't publish into another user's personal library. Personal libraries are not visible via the API.
- To publish a document into a personal library, you must specify your user ID as the first publish location ID. If you leave the first publish location ID blank, it defaults to the current user's ID.
- A document can be published from a personal library into a public library, but once it has been published into the public library, it can't be published into the personal library again.
- You can't publish a document from a personal library into a public library that has restricted content types.

- You can't update or delete a library document via the API.

Contract

Represents a contract (a business agreement) associated with an Account.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AccountId	Type reference Properties Create, Filter, Group, Sort, Update Description Required. ID of the Account associated with this contract.
ActivatedById	Type reference Properties Filter, Group, Nillable, Sort, Update Description ID of the User who activated this contract.
ActivatedDate	Type dateTime Properties Filter, Nillable, Sort, Update Description Date and time when this contract was activated.
BillingAddress	Type address Properties Filter, Nillable Description The compound form of the billing address. Read-only. See Address Compound Fields for details on compound address fields.

Field	Details
BillingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the billing address. Maximum size is 40 characters.
BillingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the billing address of this account. Maximum size is 80 characters.
BillingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the contract's billing address.
BillingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLongitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
BillingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLatitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
BillingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description Details for the billing address of this account. Maximum size is 20 characters.
BillingState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Details for the billing address. Maximum size is 80 characters.
BillingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the contract's billing address.
BillingStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Street address for the billing address.
CompanySignedDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date on which the contract was signed by your organization.
CompanySignedId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the User who signed the contract.
ContractNumber	Type string Properties Autonumber, Defaulted on create, Filter, Sort

Field	Details
	Description Number of the contract.
ContractTerm	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Number of months that the contract is valid.
CustomerSignedDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date on which the customer signed the contract.
CustomerSignedId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the Contact who signed this contract.
CustomerSignedTitle	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Title of the customer who signed the contract.
Description	Type textarea Properties Create, Nillable, Update Description Description of the contract.
EndDate	Type date Properties Filter, Group, Nillable, Sort,

Field	Details
	Description Read-only. Calculated end date of the contract. This value is calculated by adding the <code>ContractTerm</code> to the <code>StartDate</code> .
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
<code>LastActivityDate</code>	Type date Properties Filter, Group, Nillable, Sort Description Value is one of the following, whichever is the most recent: • Due date of the most recent event logged against the record. • Due date of the most recently closed task associated with the record.
<code>LastApprovedDate</code>	Type dateTime Properties Filter, Nillable, Sort Description Last date the contract was approved.
<code>LastReferencedDate</code>	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
<code>LastViewedDate</code>	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.

Field	Details
OwnerExpirationNotice	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Number of days ahead of the contract end date (15, 30, 45, 60, 90, and 120). Used to notify the owner in advance that the contract is ending.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the user who owns the contract.
Pricebook2Id	Type reference Properties Create, Filter, Nillable, Update Description ID of the pricebook, if any, associated with this contract.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object.
ShippingAddress	Type address Properties Filter, Nillable Description The compound form of the shipping address. Read-only. See Address Compound Fields for details on compound address fields.
ShippingCity	Type string Properties Create, Filter, Nillable, Update

Field	Details
	Description Details of the shipping address. City maximum size is 40 characters.
ShippingCountry	Type string Properties Create, Filter, Nillable, Update Description Details of the shipping address. Country maximum size is 80 characters.
ShippingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the contract's shipping address.
ShippingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLongitude</code> to specify the precise geolocation of a shipping address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
ShippingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLatitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
ShippingPostalCode	Type string Properties Create, Filter, Nillable, Update Description Details of the shipping address. Postal code maximum size is 20 characters.
ShippingState	Type string

Field	Details
	Properties Create, Filter, Nillable, Update Description Details of the shipping address. State maximum size is 80 characters.
ShippingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the contract's shipping address.
ShippingStreet	Type string Properties Create, Filter, Nillable, Update Description The street address of the shipping address. Maximum of 255 characters.
SpecialTerms	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Special terms that apply to the contract.
StartDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Start date for this contract. Label is Contract Start Date.
Status	Type picklist Properties Create, Defaulted on create, Filter, Group, Restricted picklist, Sort, Update Description The picklist of values that indicate order status. Each value is within one of two status categories defined in <code>StatusCode</code>. For example, the status picklist may contain: Ready to Ship, Shipped, Received as values within the Activated <code>StatusCode</code>.

Field	Details
StatusCode	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The status category for the order. An order can be either Draft, InApproval, or Activated. Label is Status Category.

Usage

The Contract object represents a business agreement.

The `Status` field specifies the current state of a contract. Status strings (defined in the `ContractStatus` object) represent its current state (Draft, InApproval, or Activated).

Client applications must initially create a Contract in a non-Activated state. Client applications can subsequently activate a Contract by updating it and setting the value in its `Status` field to Activated; however, the `Status` field is the only field you can update when activating the Contract.

Once a Contract has been activated, your client application can't change its status; however, prior to activation, your client application can change the status value from Draft to InApproval via the API. Also, your client application can delete contracts whose status is Draft or InApproval but not when a contract status is Activated.

Client applications can use the API to create, update, delete, and query any Attachment associated with a contract.

ContractContactRole

Represents the role that a given Contact plays on a Contract.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
ContactId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the Contact associated with this Contract.

Field	Details
ContractId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Contract.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsPrimary	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Specifies whether this Contact plays the primary role on this Contract (<code>true</code>) or not (<code>false</code>). Note that each contract has only one primary contact role. Default is <code>false</code>. Label is Primary.
Role	Type picklist Properties Create, Filter, Nillable, Group, Sort, Update Description Name of the role played by the Contact on this Contract, such as Decision Maker, Approver, Buyer, and so on. Must be unique—there can't be multiple records in which the <code>ContractId</code>, <code>ContactId</code>, and <code>Role</code> values are identical. Different contacts can play the same role on the same contract. A contact can play different roles on the same contract.

Usage

Use the `ContractContactRole` object to define the role that a given Contact plays on a given Contract within the context of a specific Opportunity.

ContractFeed

Represents a single feed item in the feed on the contract record detail page.

A contract feed shows recent changes to a contract record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to contracts in Salesforce. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Contract object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of ContractFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description When a PartnerNetworkConnection makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nullable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nullable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nullable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nullable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string

Field	Details
	Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an FeedItem: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.

Field	Details
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, LastModifiedDate is the same as CreatedDate. If a FeedComment is inserted on that feed item, then LastModifiedDate becomes the CreatedDate for that FeedComment. Deleting the FeedComment does not change the LastModifiedDate. Ordering by LastModifiedDate DESC sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope:

Field	Details
	- Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the contract record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging).

Field	Details
	For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user’s Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Field	Details
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for a contract record.

ContractHistory

Represents the history of changes to the values in the fields of a contract.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
ContractId	Type reference Properties Filter, Group, Sort

Field	Details
	Description ID of the Contract. Label is Contract ID.
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this object to identify changes to a contract.

This object respects field level security on the parent object.

ContractLineItem

Represents a Product2 in a ServiceContract (customer support agreement).

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AssetId	Type reference Properties Create, Filter, Nillable, Update Description Required. ID of the Asset associated with the contract line item. Must be a valid asset ID.
Description	Type textarea Properties Create, Nillable, Update Description Description of the contract line item.
Discount	Type percent Properties Create, Filter, Nillable, Update Description The discount for the product as a percentage. When updating, if you specify <code>Discount</code> without specifying <code>TotalPrice</code>, the <code>TotalPrice</code> will be adjusted to accommodate the new <code>Discount</code> value, and the <code>UnitPrice</code> will be held constant. If you specify both <code>Discount</code> and <code>Quantity</code>, you must also specify either <code>TotalPrice</code> or <code>UnitPrice</code> so the system can determine which one to automatically adjust.
EndDate	Type date Properties Create, Filter, Nillable, Update Description The last day the contract line item is in effect.

Field	Details
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
LineItemNumber	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Update Description Automatically-generated number that identifies the contract line item.
ListPrice	Type currency Properties Filter, Nillable Description Corresponds to the <code>UnitPrice</code> on the PricebookEntry that is associated with this line item, which can be in the standard pricebook or a custom pricebook. A client application can use this information to show whether the unit price (or sales price) of the line item differs from the pricebook entry list price.
PricebookEntryId	Type reference Properties Create, Filter Description Required. ID of the associated PricebookEntry. Only exists if Product2 is enabled.
Quantity	Type double

Field	Details
	Properties Create, Filter, Update Description Number of units of the contract line item (product) included in the associated service contract.
ServiceContractId	Type reference Properties Create, Filter Description Required. ID of the ServiceContract associated with the contract line item. Must be a valid asset ID.
StartDate	Type date Properties Create, Filter, Nillable, Update Description The first day the contract line item is in effect.
Status	Type picklist Properties Filter, Nillable Description Status of the contract line item.
Subtotal	Type currency Properties Filter, Nillable Description Contract line item's sales price multiplied by the <code>Quantity</code> .
TotalPrice	Type currency Properties Filter, Nillable Description This field is available only for backward compatibility. It represents the total price of the ContractLineItem

Field	Details
	If you specify <code>Discount</code> and <code>Quantity</code>, this field or <code>UnitPrice</code> is required. This field is nillable, but you can't set both <code>TotalPrice</code> and <code>UnitPrice</code> to null in the same update request. To insert the <code>TotalPrice</code> for a contract line item via the API (given only a unit price and the quantity), calculate this field as the unit price multiplied by the quantity.
<code>UnitPrice</code>	Type currency Properties Create, Filter, Update Description The unit price for the contract line item. In the user interface, this field's value is calculated by dividing the total price of the contract line item by the quantity listed for that line item. Label is Sales Price. This field or <code>TotalPrice</code> is required. You can't specify both. If you specify <code>Discount</code> and <code>Quantity</code>, this field or <code>TotalPrice</code> is required.

Usage

Use this object to query and manage contract line items.

ContractLineItemHistory

Represents the history of changes to the values in the fields on a `ContractLineItem` (items in a customer support agreement).

Supported Calls

`create()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
<code>ContractLineItemId</code>	Type reference Properties Filter, Group, Sort Description Required. ID of the <code>ContractLineItem</code>.

Field	Details
Division	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization's data. Available only if the organization has the Division permission enabled.
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this object to identify changes to a contract line item.

This object respects field level security on the parent object.

ContractStatus

Represents the status of a Contract, such as Draft, InApproval, Activated, Terminated, or Expired.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
<code>IsDefault</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this is the default contract status value (<code>true</code>) or not (<code>false</code>) in the picklist.
<code>MasterLabel</code>	Type string Properties Filter, Group, Nillable, Sort Description Master label for this contract status value. This display value is the internal label that does not get translated.
<code>SortOrder</code>	Type int Properties Filter, Group, Nillable, Sort Description Number used to sort this value in the contract status picklist. These numbers are not guaranteed to be sequential, as some previous contract status values might have been deleted.
<code>StatusCode</code>	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Code indicating the status of a contract. One of the following values:

Field	Details
	• Draft • InApproval • Activated Two other values (Terminated and Expired) are defined but are not available for use via the API.

Usage

This object represents a value in the contract status picklist. The contract status picklist provides additional information about the status of a Contract, such as its current state (Draft, InApproval, or Activated). You can query these records to retrieve the set of values in the contract status picklist, and then use that information while processing Contract objects to determine more information about a given contract. For example, the application could test whether a given contract is activated based on its Status value and the value of the StatusCode property in the associated ContractStatus object.

ContractTag

Associates a word or short phrase with a Contract.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.

Field Name	Details
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization. • <code>Personal</code>—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

ContractTag stores the relationship between its parent TagDefinition and the Contract being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

CronJobDetail

Contains details about the associated scheduled job, such as the job's name and type. This object is available in API version 29.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
JobType	Type picklist

Field	Details
	Properties Filter, Group, Nillable, Restricted picklist, Sort
	Description The type of the associated scheduled job. The following are the available job types. Each job type label is listed with its value in parenthesis. Use the job type value when querying for a specific job type. • Data Export (0) • Dashboard Refresh (3) • Reporting Snapshot (4) • Scheduled Apex (7) • Report Run (8) • Batch Job (9)
Name	Type string
	Properties Filter, Group, idLookup, Sort,
	Description The name of the associated scheduled job.

Usage

Use this object to query additional information about a scheduled job, such as the job's name and type.

CronTrigger

Contains schedule information for a scheduled job. CronTrigger is similar to a cron job on UNIX systems. This object is available in API version 17.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
CronExpression	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description The cron expression used to initiate the schedule. Syntax: Minutes, Hours, Day of month, Month, Day of week, optional Year See Using the System.Schedule Method in the <i>Force.com Apex Code Developer's Guide</i>.
CronJobDetailId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the CronJobDetail record containing more details about this scheduled job.
EndTime	Type dateTime Properties Filter, Nillable, Sort Description The date and time when the job either finished or will finish.
NextFireTime	Type dateTime Properties Filter, Nillable, Sort Description The next date and time the job is scheduled to run. null if the job is not scheduled to run again.
OwnerId	Type reference Properties Filter, Group, Nillable, Sort Description Owner of the job.
PreviousFireTime	Type dateTime

Field	Details
	Properties Filter, Nillable, Sort Description The most recent date and time the job ran. <code>null</code> if the job has not run before current local time.
StartTime	Type dateTime Properties Filter, Nillable, Sort Description The date and time when the most recent iteration of the scheduled job started.
State	Type string Properties Filter, Group, Nillable, Sort Description The current state of the job. The job state is managed by the system. Possible values are: • <code>WAITING</code>—The job is waiting for execution. • <code>ACQUIRED</code>—The job has been picked up by the system and is about to execute. • <code>EXECUTING</code>—The job is executing. • <code>COMPLETE</code>—The trigger has fired and is not scheduled to fire again. • <code>ERROR</code>—The trigger definition has an error. • <code>DELETED</code>—The job has been deleted. • <code>PAUSED</code>—A job can have this state during patch and major releases. After the release has finished, the job state is automatically set to <code>WAITING</code> or another state. • <code>BLOCKED</code>—Execution of a second instance of the job is attempted while one instance is running. This state lasts until the first job instance is completed. • <code>PAUSED_BLOCKED</code>—A job has this state due to a release occurring. When the release has finished and no other instance of the job is running, the job's status is set to another state.
TimesTriggered	Type int Properties Filter, Group, Nillable, Sort Description The number of times this job has been triggered.

Field	Details
TimeZoneSidKey	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Returns the timezone ID. For example, <code>America/Los_Angeles</code> .

Usage

Use this object to query scheduled jobs in your organization.

CurrencyType

Represents the currencies used by an organization for which the multicurrency feature is enabled.

Supported Calls

`create()`, `describeSObjects()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`

Special Access Rules

- This object is not available in single-currency organizations.
- You need the “Customize Application” permission to edit this object.
- Your client application can't delete this object.
- Customer Portal users can't access this object.

Fields

Field	Details
ConversionRate	Type double Properties Filter Description Required. Conversion rate of this currency type against the corporate currency.
DecimalPlaces	Type int

Field	Details
	Properties Filter Description Required. For this currency, specifies the number of digits to the right of the decimal point, such as zero (0) for JPY or 2 for USD.
IsActive	Type boolean Properties Defaulted on create, Filter Description Indicates whether this currency type is active (<code>true</code>) or not (<code>false</code>). Inactive currency types do not appear in picklists in the user interface. Label is Active. This field defaults to <code>false</code> if no value is provided when updating or inserting a record.
IsCorporate	Type boolean Properties Defaulted on create, Filter Description Indicates whether this currency type is the corporate currency (<code>true</code>) or not (<code>false</code>). Label is Corporate Currency. All other currency conversion rates are applied against this corporate currency. If a currency is already defined as the corporate currency in the user interface, it can't be unset. When a non-corporate currency is set to a corporate currency, the system reconfigures all conversion rates based on the new corporate currency.
IsoCode	Type picklist Properties Filter, Restricted picklist Description Required. ISO code of the currency. Must be one of the valid alphabetic, three-letter currency ISO codes defined by the ISO 4217 standard, such as <code>USD</code>, <code>GBP</code>, or <code>JPY</code>. Must be unique within your organization. Label is Currency ISO Code.

Usage

This object is for multicurrency organizations only. Use this object to define the currencies your organization uses.

When updating an existing record, make sure to provide values for all fields to avoid undesired changes to the `CurrencyType`. For example, if a value for `IsActive` is not provided, the default (`false`) is used, which could result in a currently active `CurrencyType` becoming inactive.

CustomBrand

Represents a custom branding and color scheme. This object is available in API version 28.0 and later.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization.

Fields

Field Name	Details
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the parent entity that this branding applies to. The parent entity can be either a network, organization, topic, or reputation level. The branding applies to the entity that the <code>ParentId</code> references. For example, if the <code>ParentId</code> references a network ID, the branding applies to that network (community) only, and if the <code>ParentId</code> references an organization ID, the branding applies to the organization that it is accessed through, and so on. Label is <code>Branded Entity ID</code>.

Usage

Use this object along with [CustomBrandAsset](#) to apply a custom branding scheme to your community. The branding scheme for the community shows in both the user interface and in Salesforce1. You must have “Create and Manage Communities” to customize community branding.

You can also use this object to apply a custom branding scheme to your organization when it is accessed through Salesforce1.

CustomBrandAsset

Represents a branding element in a custom branding scheme. For example, a color, logo image, header image, or footer text. A `CustomBrandAsset` can apply to a community or to an organization using Salesforce1. This object is available in API version 28.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization.

Fields

Field Name	Details
AssetCategory	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Values include: MotifZeronyColor—The background color for the header. Label is <code>Zerony motif color</code>. If this CustomBrandAsset is for a network, this is the header color for the network. If it is for an organization, this is the header color when users access Salesforce1. MotifPrimaryColor—The color used for the active tab. Label is <code>Primary motif color</code>. Not used for Salesforce1 branding. MotifSecondaryColor—The color used for the top borders of lists and tables. Label is <code>Secondary motif color</code>. Not used for Salesforce1 branding. MotifTertiaryColor—The background color for section headers on edit and detail pages. Label is <code>Tertiary motif color</code>. Not used for Salesforce1 branding. MotifQuaternaryColor—If this CustomBrandAsset is for a network, this is the background color for network pages. If it is for an organization, this is the background color on a splash page. Label is <code>Quaternary motif color</code>. MotifZeronyComplementColor—Font color used with <code>zeronyColor</code>. Label is <code>Zerony motif colors complement color</code>. MotifPrimaryComplementColor—Font color used with <code>primaryColor</code>. Label is <code>Primary motif colors complement color</code>.

Field Name	Details
	Not used for Salesforce1 branding. • MotifTertiaryComplementColor—Font color used with <code>tertiaryColor</code>. Label is <code>Tertiary motif colors complement color</code>. Not used for Salesforce1 branding. • MotifQuaternaryComplementColor—Font color used with <code>quaternaryColor</code>. Label is <code>Quaternary motif colors complement color</code>. Not used for Salesforce1 branding. • PageHeader—An image that appears on the header of the community pages. Can be an .html, .gif, .jpg, or .png file. Label is <code>Page Header</code>. Not used for Salesforce1 branding. • PageFooter—An image that appears on the footer of the community pages. Must be an .html file. Label is <code>Page Footer</code>. Not used for Salesforce1 branding. • LoginFooterText—The text that appears in the footer of the community login page. Label is <code>Footer text displayed on the login page</code>. Not used for Salesforce1 branding. • LoginLogoImageId—The logo that appears on the community login page for external users. In Salesforce1, this logo also appears on the community splash page. Label is <code>Logo image displayed on the login page</code>. • LargeLogoImageId—Only used for Salesforce1. The logo that appears on the splash page when you start Salesforce1. Label is <code>Large logo image</code>. • SmallLogoImageId—Only used for Salesforce1. The logo that appears on the publisher in Salesforce1. Label is <code>Small logo image</code>.
CustomBrandId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the associated CustomBrand.
ForeignKeyAssetId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description ID of the document used if the <code>AssetCategory</code> is <code>PageHeader</code> , <code>PageFooter</code> , or <code>LoginLogoImageId</code> .
<code>TextAsset</code>	Type string Properties Create, Filter, Nillable, Sort, Update Description Text used if the <code>AssetCategory</code> is <code>LoginFooterText</code> .

Usage

Use this object to add basic branding elements—color scheme, header or footer images, login page logo, or footer text—to the branding scheme ([CustomBrand](#)) for your Network. You must have “Create and Manage Communities” to customize community branding.

If you’re using communities in Salesforce1, the loading page shows the logo.

Custom Metadata Type__mdt

Represents a custom metadata record.

The object name is a variable with the syntax *Custom Metadata Type__mdt*, where *Custom Metadata Type* is the `Object Name` for the custom metadata type associated with the custom metadata record. For example, `PicklistUsage__mdt` represents a custom metadata record based on the `PicklistUsage` custom metadata type.

This object is available in API version 34.0 and later.

Supported Calls

`describeSObjects()`, `describeLayout()`, `query()`, `retrieve()`

Fields

Field	Details
<i>Custom Field__c</i>	Type Any Type Properties Filter, Group, Nillable, Sort Description A custom field on the record.

Field	Details
DeveloperName	Type string Properties Defaulted on create, Filter, Group, Sort Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.
Label	Type picklist Properties Filter, Group, Nillable, Sort Description The custom metadata record label. This label value is always the same as the <code>MasterLabel</code> value.
Language	Type string Properties Filter, Group, restrictedPicklist, Sort Description The language of the custom metadata record. This value is always the default language of the developing organization.
MasterLabel	Type string Properties Filter, Group, Sort Description The master label for the custom metadata record.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can

Field	Details
	refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation.
QualifiedApiName	Type string Properties Filter, Group, Nillable, Sort Description A concatenation of the namespace prefix and developer name. The format is <i>NamespacePrefix__DeveloperName</i>.

Custom Object__Feed

Represents a single feed item on a custom object detail page.

A custom object feed shows recent changes to a custom object record for any fields that are tracked in feeds, as well as posts and comments about the object. It is a useful way to stay up-to-date with changes made to a custom object. This object is available in API version 18.0 and later. The object name is variable and has a syntax of *Custom Object__Feed*, where *Custom Object* is the `ObjectName` for the custom object. For example, *Offer__Feed* represents a feed object for the custom object named Offer.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort

Field	Details
	Description The content of <i>Custom Object__Feed</i>. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the CreatedBy field contains the ID of the system administrator while the ConnectionId contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group, Nillable, Sort

Field	Details
	Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code> .
ContentSize	Type int Properties Group , Nillable , Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group , Nillable , Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter , Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDate DESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter , Group , Nillable , Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost . A FeedPost represents the following types of changes in an <code>FeedItem</code> : changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference

Field	Details
	Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
<code>IsDeleted</code>	Type <code>boolean</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
<code>LastModifiedDate</code>	Type <code>dateTime</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Sort</code> Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
<code>LikeCount</code>	Type <code>int</code> Properties <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description The number of <code>FeedLikes</code> associated with this feed item.
<code>LinkUrl</code>	Type <code>url</code> Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.

Field	Details
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope: • Only feed items with a Group or User parent can set a NetworkId or a null value for NetworkScope. • For feed items with a record parent, users can set NetworkScope only to AllNetworks. • You can't filter a FeedItem on the NetworkScope field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the custom object that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost.
Title	Type string Properties Group, Nillable, Sort

Field	Details
	Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • <code>TrackedChange</code>—a change or group of changes to a tracked field • <code>UserStatus</code>—automatically generated when a user adds a post • <code>TextPost</code>—a direct text entry on a feed • <code>LinkPost</code>—a URL posting on a feed • <code>ContentPost</code>—an uploaded file on a feed • <code>PollPost</code>—a poll posted on a feed • <code>DashboardComponentSnapshot</code>—a posting of a dashboard snapshot on a feed. • <code>ApprovalPost</code>—automatically generated by a feed query on an approval item • <code>CollaborationGroupCreated</code>—automatically generated post on a user's feed when the user creates a public group • <code>ActivityEvent</code>—generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases) or when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with <code>CaseFeed</code> disabled, one event is generated for the series only. For a recurring Task with <code>CaseFeed</code> enabled, events are generated for the series and each occurrence. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to <code>CaseFeed</code>: • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Usage

Use this object to track changes for a custom object. A record of this object type is automatically created when a user enables feed tracking for a custom object.

CustomPermission

Represents a permission created to control access to a custom process or app, such as sending email. This object is available in API version 31.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
Description	Type textarea Properties Filter, Group, Nillable, Sort Description A description of the custom permission. Limit: 255 characters.
DeveloperName	Type string Properties Filter, Group, Sort Description The unique name of the custom permission in the API. This name can contain only underscores and alphanumeric characters and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. The label corresponds to Name in the user interface. Limit: 80 characters.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field Name	Details
	Description The language of the custom permission. Valid values are: - Chinese (Simplified): zh_CN - Chinese (Traditional): zh_TW - Danish: da - Dutch: nl_NL - English: en_US - Finnish: fi - French: fr - German: de - Italian: it - Japanese: ja - Korean: ko - Norwegian: no - Portuguese (Brazil): pt_BR - Russian: ru - Spanish: es - Spanish (Mexico): es_MX - Swedish: sv - Thai: th
MasterLabel	Type string Properties Filter, Group, Sort Description The custom permission label, which corresponds to Label in the user interface. Limit: 80 characters.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values:

Field Name	Details
	- In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. - In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.

Usage

Use the CustomPermission object to determine users' access to custom permissions.

For example, to query all permission sets where the Button1 permission is enabled:

```
SELECT Id, DeveloperName,
(select Id, Parent.Name, Parent.Profile.Name from SetupEntityAccessItems)
FROM CustomPermission
WHERE DeveloperName = 'Button1'
```

To query all permission sets and profiles with custom permissions:

```
SELECT Assignee.Name, PermissionSet.Id,
PermissionSet.Profile.Name,
PermissionSet.isOwnedByProfile,
PermissionSet.Label
FROM PermissionSetAssignment
WHERE PermissionSetId
IN (SELECT ParentId
FROM SetupEntityAccess
WHERE SetupEntityType =
'CustomPermission')
```

To query for all SetupEntityAccess rows with custom permissions:

```
SELECT Id, ParentId, Parent.Name, SetupEntityId
FROM SetupEntityAccess
WHERE SetupEntityType='CustomPermission'
AND ParentId
IN (SELECT Id
FROM PermissionSet
WHERE isOwnedByProfile = false)
```

CustomPermissionDependency

Represents the dependency between two custom permissions when one custom permission requires that you enable another custom permission. This object is available in API version 32.0 and later.

Supported Calls

`describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
CustomPermissionId	Type reference Properties Filter, Group, Sort Description The ID of the custom permission that requires the permission that's specified in RequiredCustomPermissionId.
RequiredCustomPermissionId	Type reference Properties Filter, Group, Sort Description The ID of the custom permission that must be enabled when CustomPermissionId is enabled.

Usage

The following Apex class contains a method that returns the IDs of all custom permissions that are required for the given custom permission ID. To use this class, save it in your organization.

```
public class CustomPermissionUtil {
    public String[] getAllRequiredCustomPermissions(String customPermId) {
        return getAllRequiredHelper(new String[]{customPermId});
    }

    private String[] getAllRequiredHelper(String[] customPermIds) {
        CustomPermissionDependency[] requiredPerms = [SELECT RequiredCustomPermissionId
                                                    FROM CustomPermissionDependency
                                                    WHERE CustomPermissionId
                                                    IN :customPermIds];

        String[] requiredPermIds = new String[]{};
        for (CustomPermissionDependency cpd : requiredPerms) {
            requiredPermIds.add(cpd.RequiredCustomPermissionId);
        }
        if (requiredPermIds.size() > 0) {
            customPermIds.addAll(getAllRequiredHelper(requiredPermIds));
            return customPermIds;
        } else {
            return customPermIds;
        }
    }
}
```

```
    }
  }
}
```

For more information about using Apex classes, see the [Force.com Apex Code Developer's Guide](#).

DandBCompany

Represents a D&B Company record, which is associated with an account. This object is available in API version 25.0 and later.

 **Warning:** You can update fields in the DandBCompagny object; however, field changes may be overwritten by Data.com Clean jobs or by using the Data.com Clean button.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

Only organizations with Data.com Premium Prospector or Data.com Premium Clean can access this object.

Fields

Field Name	Details
Address	Type address Properties Filter, Nillable Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.
City	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The city where a company is physically located. Maximum size is 40 characters.
CompanyCurrencyIsoCode	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field Name	Details
	Description The code used to represent a company's local currency. This data is provided by the International Organization for Standardization (ISO) and is based on their three-letter currency codes. For example, USD is the ISO code for United States Dollar. Maximum size is 3 characters.
Country	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The country where a company is physically located. Maximum size is 40 characters.
CountryAccessCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The required code for international calls. Maximum size is 4 characters.
CurrencyCode	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The currency in which the company's sales volume is expressed. The full list of values can be found at the Optimizer Resources page maintained by D&B. Maximum size is 4 characters.
Description	Type textarea Properties Create, Nillable, Update Description A brief description of the company, which may include information about its history, its products and services, and its influence on a particular industry. Maximum size is 32000 characters.
DomesticUltimateBusinessName	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The primary name of the Domestic Ultimate, which is the highest ranking subsidiary, specified by country, within an organization's corporate structure. Maximum size is 255 characters.
DomesticUltimateDunsNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The D-U-N-S Number for the Domestic Ultimate, which is the highest ranking subsidiary, specified by country, within an organization's corporate structure. Maximum size is 9 characters.
DunsNumber	Type string Properties Create, Filter, Group, Sort, Update Description The Data Universal Numbering System (D-U-N-S) number is a unique, nine-digit number assigned to every business location in the D&B database that has a unique, separate, and distinct operation. D-U-N-S numbers are used by industries and organizations around the world as a global standard for business identification and tracking. Maximum size is 9 characters.
EmployeesHere	Type double Properties Create, Filter, Nillable, Sort, Update Description The number of employees at a specified location, such as a branch location. Maximum size is 15 characters.
EmployeesHereReliability	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The reliability of the <code>EmployeesHere</code> figure. Available values are <i>Actual number</i>, <i>Low</i>, <i>Estimated (for all records)</i>, <i>Modeled (for non-US records)</i>. A blank value indicates this data is unavailable.

Field Name	Details
EmployeesTotal	Type double Properties Create, Filter, Nillable, Sort, Update Description The total number of employees in the company, including all subsidiary and branch locations. This data is only available on records that have a value of <i>Headquarters/Parent</i> in the <code>LocationStatus</code> field. Maximum size is 15 characters.
EmployeesTotalReliability	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The reliability of the <code>EmployeesTotal</code> figure. Available values are <i>Actual number, Low, Estimated (for all records), Modeled (for non-US records)</i>. A blank value indicates this data is unavailable.
FamilyMembers	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The total number of family members, worldwide, within an organization, including the Global Ultimate, its subsidiaries (if any), and its branches (if any). Maximum size is 5 characters.
Fax	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description The company's facsimile number.
FifthNaics	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional NAICS code used to further classify an organization by industry. Maximum size is 6 characters.

Field Name	Details
FifthNaicsDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding NAICS code. Maximum size is 120 characters.
FifthSic	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional SIC code used to further classify an organization by industry. Maximum size is 4 characters.
FifthSicDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding SIC code. Maximum size is 80 characters.
FipsMsaCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The Federal Information Processing Standards (FIPS) and the Metropolitan Statistical Area (MSA) codes identify the organization's location. The MSA codes are defined by the US Office of Management and Budget. Maximum size is 5 characters.
FipsMsaDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's FIPS MSA code. Maximum size is 255 characters.

Field Name	Details
FourthNaics	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional NAICS code used to further classify an organization by industry. Maximum size is 6 characters.
FourthNaicsDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding NAICS code. Maximum size is 120 characters.
FourthSic	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional SIC code used to further classify an organization by industry. Maximum size is 4 characters.
FourthSicDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding SIC code. Maximum size is 80 characters.
GeoCodeAccuracy	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The level of accuracy of a location's geographical coordinates compared with its physical address. Available values include: • <i>A – Non-US rooftop accuracy</i> • <i>B – Block level</i> • <i>C – Places the address in the correct city</i>

Field Name	Details
	• D – Rooftop level • I – Street intersection • M – Mailing address level • N – Not matched • P – PO BOX location • S – Street level • T – Census tract level • Z – ZIP code level • 0 (zero) – Geocode could not be assigned
GlobalUltimateBusinessName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The primary name of the Global Ultimate, which is the highest entity within an organization's corporate structure and may oversee branches and subsidiaries. Maximum size is 255 characters.
GlobalUltimateDunsNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The D-U-N-S Number of the Global Ultimate, which is the highest entity within an organization's corporate structure and may oversee branches and subsidiaries. Maximum size is 9 characters.
GlobalUltimateTotalEmployees	Type double Properties Create, Filter, Nillable, Sort, Update Description The total number of employees at the Global Ultimate, which is the highest entity within an organization's corporate structure and may oversee branches and subsidiaries. Maximum size is 15 characters.
ImportExportAgent	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field Name	Details
	Description Identifies whether a business imports goods or services, exports goods or services, and/or is an agent for goods.
Latitude	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Used with longitude to specify a precise location, which is then used to assess the Geocode Accuracy. Maximum size is 11 characters.
LegalStatus	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Identifies the legal structure of an organization. Available values include <i>Cooperative, Nonprofit organization, Local government body, Partnership of unknown type,</i> and <i>Foreign company</i> .
LocationStatus	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Identifies the organizational status of a company. Available values are <i>Single location, Headquarters/Parent,</i> and <i>Branch</i> .
Longitude	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Used with latitude to specify a precise location, which is then used to assess the Geocode Accuracy. Maximum size is 11 characters.
MailingAddress	Type address Properties Filter, Nillable

Field Name	Details
	Description The compound form of the mailing address. Read-only. See Address Compound Fields for details on compound address fields.
MailingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The city where a company has its mail delivered. Maximum size is 40 characters.
MailingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The country where a company has its mail delivered. Maximum size is 40 characters.
MailingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The postal code that a company uses on its mailing address. Maximum size is 20 characters.
MailingState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The state where a company has its mail delivered. Maximum size is 20 characters.
MailingStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description The street address where a company has its mail delivered. Maximum size is 255 characters.

Field Name	Details
MarketingPreScreen	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The probability that a company will pay with a significant delay compared to the agreed terms. The risk level is based on the standard Commercial Credit Score, and ranges from low risk to high risk. Available values are <i>High risk of delinquency</i>, <i>Low risk of delinquency</i>, and <i>Moderate risk of delinquency</i>.  Important: Use this information for marketing pre-screening purposes only.
MarketingSegmentationCluster	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Twenty-two distinct, mutually exclusive profiles, created as a result of cluster analysis of D&B data for US organizations. Available values include <i>High-Tension Branches of Insurance/Utility Industries</i>, <i>Rapid-Growth Large Businesses</i>, <i>Labor-Intensive Giants</i>, <i>Spartans</i>, <i>Main Street USA</i>.
MinorityOwned	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates whether an organization is owned or controlled by a member of a minority group.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The primary or registered name of a company. Maximum size is 255 characters.
NationalId	Type string

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The identification number used in some countries for business registration and tax collection. Maximum size is 255 characters.
NationalIdType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description A code value that identifies the type of national identification number used. The full list of values can be found at the Optimizer Resources page maintained by D&B. Maximum size is 5 characters.
OutOfBusiness	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates whether the company at the specified address has discontinued operations.
OwnOrRent	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates whether a company owns or rents the building it occupies.
ParentOrHqBusinessName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The primary name of the parent or headquarters company. Maximum size is 255 characters.
ParentOrHqDunsNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The D-U-N-S Number for the parent or headquarters. Maximum size is 9 characters.
Phone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description A company's primary telephone number.
PostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The postal code that corresponds to a company's physical location. Maximum size is 20 characters.
PrimaryNaics	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The six-digit North American Industry Classification System (NAICS) code is the standard used by business and government to classify business establishments according to their economic activity for the purpose of collecting, analyzing, and publishing statistical data related to the US business economy. The full list of values can be found at the Optimizer Resources page maintained by D&B. Maximum size is 6 characters.
PrimaryNaicsDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on its NAICS code. Maximum size is 120 characters.
PrimarySic	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The four-digit Standard Industrial Classification (SIC) code is used to categorize business establishments by industry. The full list of values can be found at the Optimizer Resources page maintained by D&B. Maximum size is 4 characters.
PrimarySicDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on its SIC code. Maximum size is 80 characters.
PublicIndicator	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates whether ownership of the company is public or private.
SalesVolume	Type double Properties Create, Filter, Nillable, Sort, Update Description The total annual sales revenue in local currency. D&B tracks revenue data for publicly traded companies, Global Ultimates, Domestic Ultimates, and some headquarters.
SalesVolumeReliability	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The reliability of the <code>SalesVolume</code> figure.
SecondNaics	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description An additional NAICS code used to further classify an organization by industry. Maximum size is 6 characters.
SecondNaicsDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding NAICS code. Maximum size is 120 characters.
SecondSic	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional SIC code used to further classify an organization by industry. Maximum size is 4 characters.
SecondSicDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding SIC code. Maximum size is 80 characters.
SixthNaics	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional NAICS code used to further classify an organization by industry. Maximum size is 6 characters.
SixthNaicsDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description A brief description of an organization's line of business, based on the corresponding NAICS code. Maximum size is 120 characters.
SixthSic	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional SIC code used to further classify an organization by industry. Maximum size is 4 characters.
SixthSicDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding SIC code. Maximum size is 80 characters.
SmallBusiness	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates whether the company is designated a small business as defined by the Small Business Administration of the US government.
State	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The state where a company is physically located. Maximum size is 20 characters.
StockExchange	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The corresponding exchange for a company's stock symbol. For example: NASDAQ or NYSE. Maximum size is 16 characters.

Field Name	Details
StockSymbol	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The abbreviation used to identify publicly traded shares of a particular stock. Maximum size is 6 characters.
Street	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description The street address where a company is physically located. Maximum size is 255 characters.
Subsidiary	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates whether a company is more than 50 percent owned by another organization.
ThirdNaics	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional NAICS code used to further classify an organization by industry. Maximum size is 6 characters.
ThirdNaicsDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding NAICS code. Maximum size is 120 characters.
ThirdSic	Type string

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description An additional SIC code used to further classify an organization by industry. Maximum size is 4 characters.
ThirdSicDesc	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A brief description of an organization's line of business, based on the corresponding SIC code. Maximum size is 80 characters.
TradeStyle1	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description A name, different from its legal name, that an organization may use for conducting business. Similar to "Doing business as" or "DBA". Maximum size is 255 characters.
TradeStyle2	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional tradestyle used by the organization. Maximum size is 255 characters.
TradeStyle3	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional tradestyle used by the organization. Maximum size is 255 characters.
TradeStyle4	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional tradestyle used by the organization. Maximum size is 255 characters.

Field Name	Details
TradeStyle5	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An additional tradestyle used by the organization. Maximum size is 255 characters.
URL	Type url Properties Create, Filter, Group, Nillable, Sort, Update Description An organization's primary website address. Maximum size is 104 characters.
UsTaxId	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The identification number for the company used by the Internal Revenue Service (IRS) in the administration of tax laws. Also referred to as Federal Taxpayer Identification Number. Maximum size is 9 characters.
WomenOwned	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates whether a company is more than 50 percent owned or controlled by a woman.
YearStarted	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The year the company was established or the year when current ownership or management assumed control of the company. Maximum size is 4 characters.

Usage

Use this object to manage D&B Company records in your organization.

Dashboard

Represents a dashboard, which shows data from custom reports as visual components. Access is read-only. This object is available in API version 20.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `search()`

Fields

Field	Details
BackgroundDirection	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Returns the direction of the background fade. Available values are: • Top to Bottom • Left to Right • Diagonal (default value) Label is Background Fade Direction.
BackgroundEnd	Type int Properties Filter, Group, Sort Description Returns the ending fade color in hexadecimal. Label is Ending Color.
BackgroundStart	Type int Properties Filter, Group, Sort Description Returns the starting fade color in hexadecimal. Label is Starting Color.

Field	Details
Description	Type string Properties Filter, Group, Nillable, Sort Description Returns the description of the dashboard. Limit: 255 characters.
DeveloperName	Type string Properties Filter, Group, Sort Description Required. The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is <code>Dashboard Unique Name</code>.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
FolderId	Type reference Properties Filter, Group, Sort Description Required. Returns the ID of the Folder that contains the dashboard. See <code>Folder</code>.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is <code>Deleted</code>.
LastReferencedDate	Type date

Field	Details
	Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (LastReferencedDate) and not viewed.
LeftSize	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Returns the size of the left column of the dashboard. Available values are: • Narrow • Medium • Wide
MiddleSize	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Returns the size of the middle column of the dashboard. Available values are: • Narrow • Medium • Wide
NamespacePrefix	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
RightSize	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Returns the size of the right column in the dashboard. Available values are: • Narrow • Medium • Wide
RunningUserId	Type reference Properties Filter, Group, Sort Description Returns the ID of the running user specified for the dashboard. If the dashboard is dynamic, it returns the user ID of the viewing user.
TextColor	Type int Properties Filter, Group, Sort

Field	Details
	Description Returns the body text color in hexadecimal. Label is <code>Text Color</code> .
<code>Title</code>	Type string Properties Filter, Group, Sort Description Returns the title of the dashboard. Limit: 80 characters.
<code>TitleColor</code>	Type int Properties Filter, Group, Sort Description Returns the title text color in hexadecimal. Label is <code>Title Color</code> .
<code>TitleSize</code>	Type int Properties Filter, Group, Sort Description Returns the title font size in points. Label is <code>Title Size</code> .
<code>Type</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Returns the dashboard type. Available values are: • <code>SpecificUser</code>—The dashboard displays data according to the access level of one specific running user. • <code>LoggedInUser</code>—The dashboard displays data according to the access level of the logged-in user. • <code>MyTeamUser</code>—The dashboard displays data according to the access level of the logged-in user, and managers can view dashboards from the point of view of users beneath them in the role hierarchy.

Usage

Provides read only access to the current values in the dashboard fields.

DashboardComponent

Represents a dashboard component, which can be a chart, metric, table, or gauge on a dashboard. Access is read-only. This object is available in API version 21.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
DashboardId	Type reference Properties Filter, Group, Sort Description Returns the ID of the dashboard that contains the component. See Dashboard.
Name	Type string Properties Filter, Group, Nillable, Sort Description Returns the name of the dashboard component.

Usage

Provides read only access to the current values in dashboard component fields.

DashboardComponentFeed

Represents a single feed item in the feed displayed on a dashboard component. This object is available in API version 21.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Body	Type textarea Properties Create, Nillable, Sort, Update on page 16 Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Create, Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Create, Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Create, Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.

Field	Details
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDate DESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.

Field	Details
<code>IsDeleted</code>	Type <code>boolean</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
<code>LastModifiedDate</code>	Type <code>dateTime</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Sort</code> Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
<code>LikeCount</code>	Type <code>int</code> Properties <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description The number of <code>FeedLikes</code> associated with this feed item.
<code>LinkUrl</code>	Type <code>url</code> Properties <code>Create</code>, <code>Nillable</code>, <code>Sort</code> Description The URL of a <code>LinkPost</code>.
<code>NetworkScope</code>	Type <code>picklist</code> Properties <code>Create</code>, <code>Filter</code>, <code>Group</code>, <code>Nillable</code>, <code>Sort</code>

Field	Details
	Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the dashboard that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Create, Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing ContentVersion and post it to a feed as a <code>FeedItem</code> object of Type <code>ContentPost</code>.
Title	Type string Properties Create, Group, Nillable, Sort Description The title of the <code>FeedItem</code>. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name. The <code>Title</code> field can be updated on posts of Type <code>QuestionPost</code>.

Field	Details
Type	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The type of FeedItem. Except for ContentPost, LinkPost, and TextPost, don't create FeedItem types directly from the API. • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case.

Field	Details
	• CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • CaseCommentPost—generated event when a user adds a case comment for a case object. • ChangeStatusPost—generated event when a user changes the status of a case. • ChatTranscriptPost—generated event when Live Agent transcript is saved to a case. • EmailMessageEvent—generated event when an email related to a case object is sent or received. • FacebookPost—generated when a Facebook post is created from a case. Deprecated. • MilestoneEvent—generated when a case milestone is completed or reaches violation status. • SocialPost—generated when a social post is created from a case.  Note: If you set Type to ContentPost, also specify ContentData and ContentFileName.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers. • Visibility can be updated on record posts.

Usage

Use this to retrieve the current contents of the feed fields, such as type of feed or feed ID.

DashboardFeed

Represents a single feed item in the feed displayed on a dashboard.

Shows changes to dashboard fields tracked in feeds, as well as posts and comments about the dashboard. This object is available in API version 20.0 and later.

Supported Calls

`delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of DashboardFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description When a PartnerNetworkConnection makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nullable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nullable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nullable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nullable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string

Field	Details
	Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.

Field	Details
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, LastModifiedDate is the same as CreatedDate. If a FeedComment is inserted on that feed item, then LastModifiedDate becomes the CreatedDate for that FeedComment. Deleting the FeedComment does not change the LastModifiedDate. Ordering by LastModifiedDate DESC sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope:

Field	Details
	- Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the dashboard that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging).

Field	Details
	For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.

Field	Details
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this to retrieve the current contents of the feed fields, such as type of feed or feed ID.

DashboardTag

Associates a word or short phrase with a Dashboard. This object is available in API version 20.0 and later.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter

Field Name	Details
	Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization. • <code>Personal</code>—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

DashboardTag stores the relationship between its parent TagDefinition and the Dashboard being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

DatacloudCompany

Represents the fields for Data.com company records. This object is available in API version 30.0 or later.

Supported Calls

`describeSObjects(), query()`

Fields

Field Name	Details
ActiveContacts	Type int Properties Nillable Description The number of active contacts that are associated with a company.
AnnualRevenue	Type currency Properties Filter, Nillable Description The amount of money that the company makes in one year. Annual revenue is measured in US dollars.
City	Type string Properties Filter, Nillable, Sort Description The name of the city where the company is located.
CompanyId	Type string Properties Filter, Nillable Description A unique numerical identifier for the company and theData.com identifier for a company.
Country	Type string Properties Filter, Nillable, Sort

Field Name	Details
	Description A string that represents the standard abbreviation for the country where the company is located.
Description	Type string Properties Nillable Description A brief synopsis of the company that provides a general overview of the company and what it does.
DunsNumber	Type string Properties Filter, Nillable Description A randomly generated nine-digit number that's assigned by Dun & Bradstreet (D&B) to identify unique business establishments.
EmployeeQuantityGrowthRate	Type double Properties Nillable Description The yearly growth rate of the number of employees in a company expressed as a decimal percentage. The data includes the total employee growth rate for the past two years.
ExternalId	Type string Properties Filter, Nillable, Sort Description A unique numerical identifier for the company. The <code>ExternalId</code> is a system-generated number.
Fax	Type phone Properties Nillable

Field Name	Details
	Description The telephone number that's used to send and receive faxes.
FortuneRank	Type int Properties Defaulted on create, Group, Nillable Description The numeric value of the company's Fortune 1000 ranking. A null or blank value means that the company isn't ranked as a Fortune 1000 company.
IncludedInSnP500	Type string Properties Group, Nillable Description A true or false value. If <code>true</code> , the company is listed in the S&P 500 Index. If <code>false</code> , the company isn't listed in the S&P 500 Index.
Industry	Type string Properties Nillable Description A description of the type of industry such as "Telecommunications," "Agriculture," or "Electronics."
IsInactive	Type boolean Properties Defaulted on create, Filter Description A true or false response. True, the company record is not active. False, the company record is active.
IsOwned	Type boolean Properties Defaulted on create

Field Name	Details
	Description A true or false value. True, your organization owns the record. False, your organization doesn't own the record.
NaicsCode	Type string Properties Filter, Nillable Description A value that represents the North American Industry Classification System (NAICS) code. NAICS was created to provide details about a business's service orientation. The code descriptions are focused on what a business does.
NaicsDesc	Type string Properties Nillable Description A description of the NAICS classification.
Name	Type string Properties Filter, Nillable, Sort Description The company's name.
NumberOfEmployees	Type int Properties Filter, Nillable Description The number of employees working for the company.
Ownership	Type string Properties Filter, Nillable Description The type of ownership of the company:

Field Name	Details
	• Public • Private • Government • Other
Phone	Type phone Properties Nillable Description A numeric string containing the primary telephone number for the company.
PremisesMeasure	Type int Properties Group, Nillable Description A numeric value for the measurement of the premises.
PremisesMeasureReliability	Type string Properties Group, Nillable Description A descriptive accuracy of the measurement such as actual, estimated, or modeled.
PremisesMeasureUnit	Type string Properties Group, Nillable Description A descriptive measurement unit such as acres, square meters, or square feet.
SalesTurnoverGrowthRate	Type double Properties Nillable Description The increase in annual revenue from the previous value for an equivalent period expressed as a decimal percentage.

Field Name	Details
Sic	Type string Properties Filter, Nillable Description A numeric value that represents the Standard Industrial Codes (SIC). SIC is a numbering convention that indicates what type of service a business provides. It is a four-digit value.
SicDesc	Type string Properties Nillable Description A description of the SIC classification.
Site	Type string Properties Filter, Nillable Description An organizational status of the company. • Branch: a secondary location to a headquarter location • Headquarter: a parent company with branches or subsidiaries • Single Location: a single business with no subsidiaries or branches
State	Type string Properties Filter, Nillable, Sort Description The two-letter standard abbreviation for a state.
Street	Type string Properties Nillable Description A postal address for the company.

Field Name	Details
TickerSymbol	Type string Properties Nillable Description The symbol that uniquely identifies companies that are traded on public stock exchanges.
TradeStyle	Type string Properties Nillable Description A legal name under which a company conducts business.
UpdatedDate	Type dateTime Properties Nillable Description The last date and time when the information for this company was updated.
Website	Type url Properties Nillable Description The standard URL for the company's home page.
YearStarted	Type string Properties Nillable Description The year when the company was founded.
Zip	Type string Properties Filter, Nillable

Field Name	Details
	Description A numeric postal code that's designated for the address.

Usage

Use the DatacloudCompany object to search the Data.com database for companies with the specific criteria that you enter. Use this object to find company records that you are interested in purchasing for your organization. Data.com APIs use the term "company," which is similar to Salesforce term "accounts."

DatacloudContact

The fields and properties for Data.com contact records. This object is available in API version 30.0 or later.

Supported Calls

`describeSObjects()`, `query()`

Fields

Field Name	Details
City	Type string Properties Filter, Nillable, Sort Description The city where the company is located.
CompanyId	Type string Properties Filter, Nillable Description The unique numerical identifier for the company and the Data.com company identification number or Data.com Key.
CompanyName	Type string Properties Filter, Sort

Field Name	Details
	Description The name of the company.
ContactId	Type string Properties Filter, Nillable Description The unique numeric identifier for this contact.
Country	Type string Properties Filter, Nillable, Sort Description The standard abbreviation or name for the country where the company is located.  Note: You can enter a comma-separated list of countries; however, for a country that uses a comma in its name, leave out the comma. For example, enter "Taiwan, ROC" as Taiwan ROC.
Department	Type string Properties Filter, Nillable Description The department in the company that the contact is affiliated with.
Email	Type email Properties Filter, Nillable Description A business email address for the contact.
ExternalId	Type string Properties Filter, Nillable, Sort

Field Name	Details
	Description A unique system-generated numerical identifier for the contact.
FirstName	Type string Properties Filter, Nillable Description The first name of the contact.
IsInactive	Type boolean Properties Defaulted on create, Filter Description Whether the record is active (false) or not (true).
IsOwned	Type boolean Properties Defaulted on create Description • True: You own this record. • False: You do not own this record.
LastName	Type string Properties Filter, Nillable, Sort Description The last name of the contact.
Level	Type string Properties Filter, Nillable Description A human resource label that designates a person's level in the company.

Field Name	Details
Phone	Type phone Properties Nillable Description The direct-dial telephone number for the contact.
SocialHandles	Type string Properties The social handles for this contact. Social handles are a normalized URL and user name for social media accounts such as, LinkedIn, Facebook, and Twitter. This is a response-only field. The DatacloudSocialHandles object is a child of the DatacloudContact object.
State	Type string Properties Filter, Nillable, Sort Description The state where the company is located, which can also be a province or other equivalent to a state, depending on the country where the company is located.
Street	Type string Properties Nillable Description The street address for the company where the contact works.
Title	Type string Properties Filter, Nillable, Sort Description Title of the contact such as CEO or Vice President.
UpdatedDate	Type dateTime

Field Name	Details
	Properties Nillable Description The last date and time when the information for a contact was updated.
Zip	Type string Properties Filter, Nillable Description The postal or zip code for the address.

Usage

This object searches the Data.com database for contacts with the specific criteria that you enter. Use this object to find contact records that you are interested in purchasing for your organization.

DatacloudDandBCompany

Represents a set of read-only fields that are used to return D&B company data from Data.com API calls. This object is available in API version 30.0 or later.

Supported Calls

`describeSObjects()`, `query()`

Fields

Field Name	Details
City	Type string Properties Nillable Description The name of the city where the company is physically located.
CompanyCurrencyIsoCode	Type picklist

Field Name	Details
	Properties Nillable, Restricted picklist Description The code used to represent a company's local currency. This data is provided by the International Organization for Standardization (ISO) and is based on their three-letter currency codes. For example, USD is the ISO code for United States Dollar.
CompanyId	Type string Properties Filter, Nillable, Sort Description A unique numeric identifier for a company.
Country	Type string Properties Nillable Description The country where a company is physically located.
CountryAccessCode	Type string Properties Nillable Description The required code for international calls.
CurrencyCode	Type picklist Properties Nillable, Restricted picklist Description The currency in which the company's sales volume is expressed.
Description	Type string Properties Nillable

Field Name	Details
	Description A brief description of the company, which may include information about its history, its products and services, and its influence on a particular industry.
DomesticUltimateBusinessName	Type string Properties Nillable Description The primary name of the Domestic Ultimate, which is the highest ranking subsidiary, specified by country, within an organization's corporate structure.
DomesticUltimateDunsNumber	Type string Properties Nillable Description The D-U-N-S number for the Domestic Ultimate, which is the highest-ranking subsidiary, specified by country, within an organization's corporate structure.
DunsNumber	Type string Properties Filter, Nillable Description The Data Universal Numbering System (D-U-N-S) number is a unique, nine-digit number assigned to every business location in the D&B database that has a unique, separate, and distinct operation. D-U-N-S numbers are used by industries and organizations around the world as a global standard for business identification and tracking.
EmployeeQuantityGrowthRate	Type double Properties Nillable Description The yearly growth rate of the number of employees in a company expressed as a decimal percentage. The data includes the total employee growth rate for the past two years.

Field Name	Details
EmployeesHere	Type double Properties Nillable Description The number of employees at a specified location, such as a branch location.
EmployeesHereReliability	Type picklist Properties Nillable, Restricted picklist Description The reliability of the <code>EmployeesHere</code> figure. Available values are <i>Actual number, Low, Estimated (for all records), Modeled (for non-US records)</i>. A blank value indicates this data is unavailable.
EmployeesTotal	Type double Properties Nillable Description The total number of employees in the company, including all subsidiary and branch locations. This data is available only on records that have a value of <i>Headquarters/Parent</i> in the <code>LocationStatus</code> field.
EmployeesTotalReliability	Type picklist Properties Nillable, Restricted picklist Description The reliability of the <code>EmployeesTotal</code> figure. Available values are <i>Actual number, Low, Estimated (for all records), Modeled (for non-US records)</i>. A blank value indicates this data is unavailable.
ExternalId	Type string Properties Filter, Nillable, Sort Description A system generated numeric identification.

Field Name	Details
FamilyMembers	Type int Properties Nillable Description The total number of family members, worldwide, within an organization, including the Global Ultimate, its subsidiaries (if any), and its branches (if any).
Fax	Type phone Properties Nillable Description The company's facsimile number.
FifthNaics	Type string Properties Nillable Description A NAICS code that's used to further classify an organization by industry.
FifthNaicsDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on the corresponding NAICS code.
FifthSic	Type string Properties Nillable Description A Standard Industrial Classification (SIC) code that's used to further classify an organization by industry.
FifthSicDesc	Type string

Field Name	Details
	Properties Nillable Description A brief description of an organization's line of business, based on the corresponding SIC code.
FipsMsaCode	Type string Properties Nillable Description The Federal Information Processing Standards (FIPS) and the Metropolitan Statistical Area (MSA) codes identify the organization's location. The MSA codes are defined by the US Office of Management and Budget.
FipsMsaDesc	Type string Properties Nillable Description A brief description of an organization's FIPS MSA code.
FortuneRank	Type int Properties Defaulted on create, Group, Nillable Description The numeric value of the company's Fortune 1000 ranking. A null or blank value means that the company isn't ranked as a Fortune 1000 company.
FourthNaics	Type string Properties Nillable Description A NAICS code used to further classify an organization by industry.
FourthNaicsDesc	Type string Properties Nillable

Field Name	Details
	Description A brief description of an organization's line of business, based on the corresponding NAICS code.
FourthSic	Type string Properties Group, Nillable Description A SIC code used to further classify an organization by industry.
FourthSicDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on the corresponding SIC code.
GeoCodeAccuracy	Type picklist Properties Nillable, Restricted picklist Description The level of accuracy of a location's geographical coordinates compared with its physical address. Available values include <i>Rooftop level, Street level, Block level, Census tract level, Mailing address level, ZIP code level, Geocode could not be assigned, Places the address in the correct city, Not matched, Not matched, Street intersection, PO BOX location, and Non-US rooftop accuracy.</i>
GlobalUltimateBusinessName	Type string Properties Nillable Description The primary name of the Global Ultimate, which is the highest entity within an organization's corporate structure and may oversee branches and subsidiaries.

Field Name	Details
GlobalUltimateDunsNumber	Type string Properties Filter, Nillable Description The D-U-N-S number of the Global Ultimate, which is the highest-ranking entity within an organization's corporate structure and can oversee branches and subsidiaries.
GlobalUltimateTotalEmployees	Type double Properties Nillable Description The total number of employees at the Global Ultimate, which is the highest entity within an organization's corporate structure and may oversee branches and subsidiaries.
ImportExportAgent	Type picklist Properties Nillable, Restricted picklist Description Identifies whether a business imports goods or services, exports goods or services, and/or is an agent for goods.
IncludedInSnP500	Type string Properties Group, Nillable Description A true or false value. If <code>true</code>, the company is listed in the S&P 500 Index. If <code>false</code>, the company isn't listed in the S&P 500 Index.
IsOwned	Type boolean Properties Defaulted on create Description A true or false value. True, your organization owns the record. False, your organization doesn't own the record.

Field Name	Details						
IsParent	Type boolean Properties Defaulted on create, Description A true or false value. True, the company is a parent company. False, the company isn't a parent company. A parent company owns other companies.						
Latitude	Type string Properties Nillable Description Used with longitude to specify a precise location, which is used to assess the Geocode Accuracy.						
LegalStatus	Type picklist Properties Nillable, Restricted picklist Description Identifies the legal structure of an organization. Available values include <i>Cooperative, Nonprofit organization, Local government body, Partnership of unknown type,</i> and <i>Foreign company</i>.						
LocationStatus	Type picklist Properties Filter, Nillable, Restricted picklist Description Identifies the organizational status of a company. A numeric value represents each value. <table border="1"> <thead> <tr> <th>Organizational status</th><th>Numeric value</th></tr> </thead> <tbody> <tr> <td><i>Single location:</i> The business has no branches or subsidiaries.</td><td>0</td></tr> <tr> <td><i>Headquarters/Parent:</i> A parent company that owns more than 50 percent of another company. When the company also has branches, it's the headquarters.</td><td>1</td></tr> </tbody> </table>	Organizational status	Numeric value	<i>Single location:</i> The business has no branches or subsidiaries.	0	<i>Headquarters/Parent:</i> A parent company that owns more than 50 percent of another company. When the company also has branches, it's the headquarters.	1
Organizational status	Numeric value						
<i>Single location:</i> The business has no branches or subsidiaries.	0						
<i>Headquarters/Parent:</i> A parent company that owns more than 50 percent of another company. When the company also has branches, it's the headquarters.	1						

Field Name

Details

Organizational status **Numeric value**

Branch: A secondary location of a business. 2



Note: Only the numeric value is accepted in an API request.

Longitude

Type

string

Properties

Nillable

Description

Used with latitude to specify a precise location, which is used to assess the Geocode Accuracy.

MailingCity

Type

string

Properties

Nillable

Description

The city where a company has its mail delivered.

MailingCountry

Type

string

Properties

Nillable

Description

The country where a company has its mail delivered.

MailingState

Type

string

Properties

Nillable

Description

The state where a company has its mail delivered.

MailingStreet

Type

string

Properties

Nillable

Field Name	Details
	Description The street address where a company has its mail delivered.
MailingZip	Type string Properties Nillable Description The postal zip code for the company.
MarketingPreScreen	Type picklist Properties Nillable, Restricted picklist Description The probability that a company pays with a significant delay compared to the agreed terms. The risk level is based on the standard Commercial Credit Score, and ranges from low risk to high risk. Available values are <i>High risk of delinquency</i> , <i>Low risk of delinquency</i> , and <i>Moderate risk of delinquency</i> .  Important: Use this information for marketing pre-screening purposes only.
MarketingSegmentationCluster	Type picklist Properties Nillable, Restricted picklist Description Twenty-two distinct, mutually exclusive profiles, created as a result of cluster analysis of D&B data for US organizations. Available values include <i>High-Tension Branches of Insurance/Utility Industries</i> , <i>Rapid-Growth Large Businesses</i> , <i>Labor-Intensive Giants</i> , <i>Spartans</i> , <i>Main Street USA</i> .
MinorityOwned	Type picklist Properties Nillable, Restricted picklist Description Indicates whether an organization is owned or controlled by a member of a minority group.

Field Name	Details
Name	Type string Properties Filter, Nillable Description The primary or registered name of a company.
NationalId	Type string Properties Nillable Description The identification number used in some countries for business registration and tax collection.
NationalIdType	Type picklist Properties Nillable, Restricted picklist Description A code value that identifies the type of national identification number that's used.
OutOfBusiness	Type picklist Properties Nillable, Restricted picklist Description Indicates whether the company at the specified address has discontinued operations.
OwnOrRent	Type picklist Properties Nillable, Restricted picklist Description Indicates whether a company owns or rents the building it occupies.
ParentOrHqBusinessName	Type string

Field Name	Details
	Properties Nillable Description The primary name of the parent or headquarters company.
ParentOrHqDunsNumber	Type string Properties Filter, Nillable Description The D-U-N-S number for the parent or headquarters.
Phone	Type phone Properties Nillable Description A company's primary telephone number.
PremisesMeasure	Type int Properties Group, Nillable Description A numeric value for the measurement of the premises.
PremisesMeasureReliability	Type string Properties Group, Nillable Description A descriptive accuracy of the measurement such as actual, estimated, or modeled.
PremisesMeasureUnit	Type string Properties Group, Nillable Description A descriptive measurement unit such as acres, square meters, or square feet.

Field Name	Details
PrimaryNaics	Type string Properties Nillable Description The six-digit North American Industry Classification System (NAICS) code is the standard used by business and government to classify business establishments according to their economic activity for the purpose of collecting, analyzing, and publishing statistical data related to the US business economy.
PrimaryNaicsDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on its NAICS code.
PrimarySic	Type string Properties Nillable Description The four-digit SIC code that's used to categorize business establishments by industry.
PrimarySicDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on its SIC code.
PublicIndicator	Type picklist Properties Nillable, Restricted picklist Description Indicates whether ownership of the company is public or private.

Field Name	Details
SalesTurnoverGrowthRate	Type double Properties Nillable Description The increase in annual revenue from the previous value for an equivalent period expressed as a decimal percentage.
SalesVolume	Type double Properties Nillable Description The total annual sales revenue in local currency. D&B tracks revenue data for publicly traded companies, Global Ultimates, Domestic Ultimates, and some headquarters.
SalesVolumeReliability	Type picklist Properties Nillable, Restricted picklist Description The reliability of the SalesVolume figure.
SecondNaics	Type string Properties Nillable Description A NAICS code used to further classify an organization by industry.
SecondNaicsDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on the corresponding NAICS code.
SecondSic	Type string

Field Name	Details
	Properties Nillable Description A SIC code used to further classify an organization by industry.
SecondSicDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on the corresponding SIC code.
SixthNaics	Type string Properties Nillable Description A NAICS code used to further classify an organization by industry.
SixthNaicsDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on the corresponding SIC code.
SixthSic	Type string Properties Nillable Description A SIC code used to further classify an organization by industry.
SixthSicDesc	Type string Properties Nillable

Field Name	Details
	Description A brief description of an organization's line of business, based on the corresponding SIC code.
SmallBusiness	Type picklist Properties Nillable, Restricted picklist Description Indicates whether the company is designated a small business as defined by the Small Business Administration of the US government.
State	Type string Properties Nillable Description The state where a company is physically located.
StockExchange	Type string Properties Nillable Description The corresponding exchange for a company's stock symbol, for example, NASDAQ or NYSE.
StockSymbol	Type string Properties Nillable Description The abbreviation that's used to identify publicly traded shares of a particular stock.
Street	Type string Properties Nillable

Field Name	Details
	Description The street address where a company is physically located.
Subsidiary	Type picklist Properties Nillable, Restricted picklist Description Indicates whether a company is more than 50 percent owned by another organization.
ThirdNaics	Type string Properties Nillable Description A NAICS code used to further classify an organization by industry.
ThirdNaicsDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on the corresponding NAICS code.
ThirdSic	Type string Properties Nillable Description A SIC code used to further classify an organization by industry.
ThirdSicDesc	Type string Properties Nillable Description A brief description of an organization's line of business, based on the corresponding SIC code.

Field Name	Details
TradeStyle1	Type string Properties Nillable Description A name, different from its legal name, that an organization may use for conducting business. Similar to “Doing business as” or “DBA”.
TradeStyle2	Type string Properties Nillable Description A tradestyle used by the organization.
TradeStyle3	Type string Properties Nillable Description A tradestyle used by the organization.
TradeStyle4	Type string Properties Nillable Description A tradestyle used by the organization.
TradeStyle5	Type string Properties Nillable Description A tradestyle used by the organization.
URL	Type url Properties Nillable

Field Name	Details
	Description An organization's primary website address.
UsTaxId	Type string Properties Nillable Description The identification number for the company used by the Internal Revenue Service (IRS) in the administration of tax laws. Also referred to as Federal Taxpayer Identification Number.
WomenOwned	Type picklist Properties Nillable, Restricted picklist Description Indicates whether a company is more than 50 percent owned or controlled by a woman.
YearStarted	Type string Properties Nillable Description The year when the company was established or the year when current ownership or management assumed control of the company.
Zip	Type string Properties Nillable Description A five or nine-digit code that's used to help sort mail.

Usage

Use this object to return D&B Company information. These fields are read-only.

DatacloudOwnedEntity

Represents fields in the DatacloudOwnedEntity object. The DatacloudOwnedEntity object tracks user-purchased records. This object is available in API version 30.0 or later.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
DataDotComKey	Type string Properties Create, Filter, Sort Description The Data.com contact or company record identification number used by the DatacloudPurchaseUsage object to keep track of purchased records. This is equivalent to the Data.com record ID for a contact or company.
DatacloudEntityType	Type picklist Properties Create, Filter, Restricted picklist, Sort Description The type of Data.com record you want to purchase. • 0—contact • 1—company
Name	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description An optional field used to name your record.
PurchaseType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort

Field Name	Details
	Description A read only field set by the API to identify the purchase type. • Added • Export • API
PurchaseUsageId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The unique identification number for the DatacloudPurchaseUsage object created by making a REST POST request. • 0—contact • 1—company
UserId	Type reference Properties Filter, Group, Sort Description A unique identifier for the user making the purchase.

Usage

The Datacloud object that tracks records that are purchased and owned by a specific user.

DatacloudPurchaseUsage

Represents an object used to identify and track Data.com record purchases. This object is available in API version 30.0 or later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
DatacloudEntityType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of Data.com record you want to purchase. 0—indicates contact entity type. 1—indicates company entity type.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description An optional field. You can add a description for your purchase.
Name	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description An optional field used to name your record.
PurchaseType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A read only field set by the API to identify the purchase type. - Added - Export - API
Usage	Type double Properties Filter, Sort

Field Name	Details
	Description A read only field set by the API. It is used to track the points used to purchase records.
UserId	Type reference Properties Filter, Group, Sort Description A read only field set by the API that identifies the user purchasing the records.
UserType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A read only field set by the API with 2 user types. - Monthly Usage - List Pool User

Usage

The DatacloudPurchaseUsage object allows you to track Data.com record purchases for CRM users.

DatacloudSocialHandle

Returns normalized URLs with userids for different social media used by Data.com contacts. The DatacloudSocialHandle object is a child object of the DatacloudContact object. This object is available in API version 30.0 or later.

Supported Calls

`describeSObjects()`, `query()`

Fields

Field Name	Details
DatacloudContactId	Type string

Field Name	Details
	Properties Filter, Nillable, Sort Description The unique numeric identifier for a Data.com contact record.
ProviderName	Type string Properties Filter, Nillable, Sort Description The name of the social media provider.
SocialId	Type string Properties Filter, Nillable, Sort Description The normalized userid for the user on this social media.
Url	Type url Properties Filter, Nillable, Sort Description A normalized URL and userid for the website of the social media provider.

Usage

Returns social handles with Data.com contacts from the DatacloudContact object. Social handle fields are read only fields and can't be used to filter results.

DatedConversionRate

Represents the dated exchange rates used by an organization for which the multicurrency and the effective dated currency features are enabled.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`,

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
ConversionRate	Type double Properties Filter, Update Description Required. Conversion rate of this currency type against the corporate currency.
IsoCode	Type picklist Properties Filter, Restricted picklist Description Required. ISO code of the currency. Must be one of the valid alphabetic, three-letter currency ISO codes defined by the ISO 4217 standard, such as USD, GBP, or JPY. Must be unique within your organization. Label is Currency ISO Code.
NextStartDate	Type date Properties Filter, Nillable Description Read only. The date on which the next effective dated exchange rate will start. Effectively the day after the end date for this exchange rate.
StartDate	Type date Properties Filter Description The date on which the effective dated exchange rate starts.

Usage

This object is for multicurrency organizations with advanced currency management enabled. Use this object to define the exchange rates your organization uses for a date range. This object is not available in single-currency organizations, nor is it available if the organization does not have advanced currency management enabled.

DcSocialProfile

The `DcSocialProfile` object is a read-only object accessible only through the Data.com Social Key API.

This object is available in API version 32.0 or later.

Supported Calls

`describeSObjects()`, `query()`

Special Access Rules

This is a read-only object that is accessed by only the Data.com Social Key API

.

Fields

Field Name	Details
City	Type string Properties Filter, Group, Nillable, Sort Description The name of the city where the company is located.
CompanyName	Type string Properties Filter, Group, Sort Description The name of the company at which the contact works.
ContactId	Type string Properties Filter, Group, Nillable, Sort Description The unique numerical identifier for a contact.
Country	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description A string that represents the standard abbreviation for the country where the contact works.
Email	Type email Properties Filter, Group, Nillable, Sort Description An email address for this contact.
FirstName	Type string Properties Filter, Group, Nillable, Sort Description The first name of a contact.
LastName	Type string Properties Filter, Group, Nillable, Sort Description The last name of a contact.
State	Type string Properties Filter, Group, Nillable, Sort Description The two-letter standard abbreviation for a state.

Usage

Provides social handle information to the Data.com Social Key API.

DcSocialProfileHandle

The `DcSocialProfileHandle` object, a child object to `DcSocialProfile`, is a read-only object accessible only through the Data.com Social Key API.

The `DcSocialProfileHandle` object is a child object of the `DcSocialProfile` object. This object is available in API version 32.0 or later.

Supported Calls

`describeObjects()`, `query()`

Special Access Rules

This is a read-only object that is accessed by only the Data.com Social Key API

Fields

Field Name	Details
<code>DcSocialProfileId</code>	Type string Properties Filter, Group, Nillable, Sort Description A unique identifier for a contacts social handles.
<code>Handle</code>	Type string Properties Filter, Group, Nillable, Sort Description A normalized social handle for a contact.
<code>ProviderName</code>	Type string Properties Filter, Group, Nillable, Sort Description The name of the social media provider.

Usage

Provides social handle information to the Data.com Social Key API.

DeclinedEventRelation

Represents invitees with the status `Declined` for a given event.

This object is available in API versions 29.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
EventId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the event.
RelationId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the invitee.
RespondedDate	Type dateTime Properties Filter, Nillable, Sort Description Indicates the most recent date and time when the invitee declined an invitation to the event.
Response	Type string Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description Indicates the content of the response field. Label is Comment.
Type	Type string
	Properties Filter, Group, Nillable, Sort
	Description Indicates whether the invitee is a user, lead or contact, or resource.

Usage

Query invitees who have declined an invitation to an event

```
SELECT eventId, type, response FROM DeclinedEventRelation WHERE eventId='00UTD000000ZH5LA'
```

Division

A logical segment of your organization's data. For example, if your company is organized into different business units, you could create a division for each business unit, such as "North America," "Healthcare," or "Consulting."

Supported Calls

`create()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Divisions must be enabled for your organization to access this object. To discover whether divisions have been enabled for an organization, inspect the User or Group object for the `DefaultDivision` field—if it is present, then divisions have been enabled, and this field (the field is named `Division` in objects other than User and Group) will be available in all relevant objects.
- Customer Portal users can't access this object.

Fields

Field	Details
IsActive	Type boolean
	Properties Create, Defaulted on create, Filter, Update

Field	Details
	Description Indicates whether the division is active (<code>true</code>) or not (<code>false</code>). Label is Active .
<code>IsGlobalDivision</code>	Type boolean Properties Defaulted on createFilter Description Indicates whether the division is your organization's global default division (<code>true</code>) or not (<code>false</code>). Label is Global Division .
<code>Name</code>	Type string Properties Create, Filter, Update Description A descriptive name for the division. Limit: 80 characters.
<code>SortOrder</code>	Type int Properties Create, Filter, Nillable, Update Description The order in which this division name appears in the Division picklist field when creating or editing users in the Salesforce user interface.

Usage

The values available for that field are the global division ID for the organization, created when divisions are first enabled, and any other division IDs that have been created. The division ID associated with a user is populated in the objects owned or created by the user.

You can use the division ID to make searches, reports, and list views run more quickly and return more relevant results if an organization has very large data sets. For more information, see the Salesforce online help, in the Fields description for the object.

You can use WITH in SOSL to pre-filter results based on division. This is faster than specifying the division in a WHERE clause.



Note: The User object has a `Division` field that is unrelated to this object. The `Division` field is a standard text field similar to Company or Department that has no special properties. Do not confuse it with the `DefaultDivision` field, which does relate to this object.

DivisionLocalization

When the Translation Workbench is enabled for your organization, the DivisionLocalization object provides the translation of the label for a division.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Your organization must be using Professional, Enterprise, Developer, Unlimited, or Performance Edition and be enabled for the Translation Workbench.
- To view this object, you must have the “View Setup and Configuration” permission.

Fields

Field	Details
Language	Type string Properties Create, Filter, Nillable, Restricted picklist Description The language for this translated label.
NamespacePrefix	Type string Properties Filter, Nillable Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field’s value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
ParentId	Type reference Properties Create, Filter, Nillable

Field	Details
	Description The ID of the Division associated with the label that is being translated.
Value	Type string Properties Create, Filter, Nillable, Update Description The actual translated label for the division. Label is Translation .

Usage

Use this object to translate the labels of your divisions into the different languages supported by Salesforce.

Document

Represents a file that a user has uploaded. Unlike Attachment records, documents are not attached to a parent object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

You must have the "Edit" permission on documents and the appropriate access to the Folder that contains a document in order to create or update a document in that Folder.

Fields

Field	Details
AuthorId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the User who is responsible for the Document.
Body	Type base64

Field	Details
	Properties Create, Nillable, Update Description Required. Encoded file data. If specified, then do not specify a URL.
BodyLength	Type int Properties Filter, Group, Sort Description Size of the file (in bytes).
ContentType	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Type of content. Label is Mime Type. Limit: 120 characters. If the Don't allow HTML uploads as attachments or document records security setting is enabled for your organization, you cannot upload files with the following file extensions: .htm, .html, .htt, .htx, .mhtm, .mhtml, .shtm, .shtml, .acgi, .svg.
Description	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Text description of the Document. Limit: 255 characters.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is Document Unique Name.

Field	Details
	 Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
<code>FolderId</code>	Type reference Properties Create, Filter, Group, Sort, Update Description Required. ID of the Folder that contains the document.
<code>IsBodySearchable</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the contents of the object can be searched using a SOSL <code>FIND</code> call. The <code>ALL FIELDS</code> search group includes the content as a searchable field.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
<code>IsInternalUseOnly</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the object is only available for internal use (<code>true</code>) or not (<code>false</code>). Label is Internal Use Only.
<code>IsPublic</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the object is available for external use (<code>true</code>) or not (<code>false</code>). Label is Externally Available.

Field	Details
Keywords	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Keywords. Limit: 255 characters.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of the document. Label is Document Name.
NamespacePrefix	Type string Properties Filter, Group, Sort, Nillable Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the

Field	Details
	installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
Type	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description File type of the Document. In general, the values match the file extension for the type of Document (such as pdf or jpg). Label is File Extension.
Url	Type string Properties Create, Filter, Nillable, Group, Sort, Update Description URL reference to the file (instead of storing it in the database). If specified, do not specify the <code>Body</code> or <code>BodyLength</code>.

Usage

When creating or updating a document, you can specify a value in either the `Body` or `Url` fields, but not both.

Encoded Data

The API sends and receives the binary file data encoded as a base64 data type. Prior to creating a record, clients must encode the binary file data as base64. Upon receiving an API response, clients must decode the base64 data to binary (this conversion is usually handled for you by the SOAP client).

Maximum Document Size

You can only create or update documents to a maximum size of 5 MB.

DocumentAttachmentMap

Maps the relationship between an `EmailTemplate` and its attachment, which is stored as a `Document`.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>DocumentId</code>	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the document that this object tracks.
<code>DocumentSequence</code>	Type int Properties Create, Filter, Group, Sort, Update Description Represents the order that the attachments will be included in the email defined by the <code>EmailTemplate</code> specified by the <code>DocumentId</code>. Label is Attachment Sequence. The first attachment is given a value of 0, and each subsequent attachment is given a value incremented by 1.
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the <code>EmailTemplate</code> parent. The attachment identified by <code>DocumentId</code> is attached to the <code>EmailTemplate</code> specified in this field.

Usage

Use this object to map the relationship of an `EmailTemplate` to its attachments, and to specify the order of the attachments.

DocumentTag

Associates a word or short phrase with a Document.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization.

Field Name	Details
	• <code>Personal</code>—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

DocumentTag stores the relationship between its parent TagDefinition and the Document being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

Domain

Read-only object that represents a custom Web address assigned to a site in your organization. This object is available in API version 26.0 and later.

To access this object, Force.com Sites or Site.com must be enabled for your organization.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

- Customer Portal users can't access this object.
- To view this object, you must have the "View Setup and Configuration" permission.
- Site.com Publisher users have read-only API access to the Domain and [DomainSite](#) objects.

Fields

Field	Description
<code>Domain</code>	Type string Properties Filter, Sort Description The branded custom Web address within the global namespace identified by this domain's type. In the Domain Name System (DNS) global namespace, this field is the custom Web address that you registered with a third-party domain name registrar. The custom Web address can be used to access the site of this domain.

Field	Description
DomainType	Type picklist Properties Filter, Group, Sort Description The global namespace that this custom Web address belongs to. This value is set to DNS for custom Web addresses in the global DNS. DomainType can have the following values: • Domain Name System (DNS) • Facebook Page
OptionsExternalHttps	Type boolean Properties Filter Description Indicates whether the domain supports secure connections (true) or not (false) via a non-Salesforce content delivery network (CDN) or endpoint. The value of this field is used only if the domain is not pointing to the <code>yourdomain.your18characterOrgId.live.siteforce.com</code> CNAME target.

Usage

Use this read-only object to query the domains that are associated with each website in your organization.

DomainSite

Read-only junction object that joins together the Site and Domain objects.

This object is available in API version 26.0 and later. To access this object, Force.com Sites or Site.com must be enabled for your organization.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

- Customer Portal users can't access this object.
- To view this object, you must have the "View Setup and Configuration" permission.
- Site.com Publisher users have read-only API access to the [Domain](#) and DomainSite objects.

Fields

Field	Description
DomainId	Type reference Properties Filter, Group, Sort Description The ID of the associated Domain.
PathPrefix	Type string Properties Filter, Group, Sort Description Shows where a site's root exists on a domain. Can only be set for custom Web addresses. Always begins with a /.
SiteId	Type reference Properties Filter, Group, Sort Description The ID of the associated Site.

Usage

Use this read-only object to query or retrieve information about your Force.com site.

DuplicateRecordItem

Represents an individual record that's part of a duplicate record set. Use this object to create custom report types.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

To access this object, your organization must have Data.com Duplicate Management enabled. Data.com Duplicate Management is currently available as a beta feature. Contact Salesforce for more information. For users to access this object, they must be given read and write access by their system administrator.

Fields

Field Name	Details
DuplicateRecordSetId	Type reference Properties Create, Filter, Group, Sort Description The duplicate record set that the duplicate record item is assigned to.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The autogenerated name that's given to the Duplicate Record Item. Label is Duplicate Record Item Name.
RecordId	Type reference Properties Create, Filter, Group, Sort, Update Description The name of the record as it appears on the record's detail page.

DuplicateRecordSet

Represents a group of records that have been identified as duplicates. Each duplicate record set contains one or more duplicate record items. Use this object to create custom report types.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

To access this object, your organization must have Data.com Duplicate Management enabled. Data.com Duplicate Management is currently available as a beta feature. Contact Salesforce for more information. For users to access this object, they must be given read and write access by their system administrator.

Fields

Field Name	Details
DuplicateRuleId	Type reference Properties Create, Filter, Group, Sort, Update Description The duplicate rule that's used to identify this list of duplicate records.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The autogenerated name that's given to the duplicate record set. Label is <code>Duplicate Record Set Name</code> .
RecordCount	Type int

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description The number of record items in the set.
SubjectType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The object that the duplicate rule and all the record items in the set apply to.

DuplicateRule

Represents a duplicate rule for detecting duplicate records.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `search()`

Fields

Field Name	Details
DeveloperName	Type string Properties Filter, Group, Sort Description The developer name for the duplicate rule.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language for the duplicate rule.
MasterLabel	Type string

Field Name	Details
	Properties Filter, Group, Sort Description The label for the duplicate rule.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the namespacePrefix__componentName notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, NamespacePrefix is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
ObjectType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of object the duplicate rule is defined for. For example, account, contact, or lead.

Usage

DuplicateRule is available to organizations that use duplicate rules.

You can only view details of a duplicate rule using the API. You must use the full Salesforce site to create, edit, and delete duplicate rules.

EmailDomainKey

Represents a domain key for an organization's domain, used to authenticate outbound email that Salesforce sends on the organization's behalf. This object is available in API version 28.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
Domain	Type string Properties Create, Filter, Group, Sort, Update Description The organization's domain name that the DKIM key is generated for.
DomainMatch	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The specificity of match required on the sending domain name before signing with this DKIM key. Valid values are: • <code>DomainOnly</code>—Sign if sending domain matches at the domain level only (example.com but not mail.example.com) • <code>SubdomainsOnly</code>—Sign if sending domain matches at the subdomain level only (mail.example.com but not example.com) • <code>DomainAndSubdomains</code>—Sign if sending domain matches at the domain and subdomain levels (example.com and mail.example.com)
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this DKIM key is active (<code>true</code>) or not (<code>false</code>). You can set <code>IsActive</code> to <code>true</code> on create if you specify an existing key pair.

Field Name	Details
PrivateKey	Type textarea Properties Create, Nillable, Update Description The private portion of the DKIM key pair used to encrypt mail headers from your domain. Salesforce generates an encrypted <code>PrivateKey</code> if you don't specify a value when creating the DKIM key. If you do specify a value, it must be an existing valid <code>PrivateKey</code> from another EmailDomainKey object. This field doesn't contain the actual private key, but a value that represents the key in our system. Therefore: • The actual private key can't be leaked. • You can't use the value to do your own email signing.
PublicKey	Type textarea Properties Create, Nillable, Update Description Part of the domain key pair that mail recipients retrieve to decrypt the DKIM header and verify your domain. Add the <code>PublicKey</code> value to your domain's DNS records before you start signing with this domain key. Otherwise, mail recipients may reject your email.
Selector	Type string Properties Create, Filter, Group, Sort, Update Description Text used to distinguish the DKIM key from any other DKIM keys your organization uses for the specified domain.

Usage

Use this object to define a DomainKeys Identified Mail (DKIM) key, which is used to authenticate outbound email that Salesforce sends on your organization's behalf. When you create a DKIM key, Salesforce generates a public and private key pair. You must publish the public key in the DNS, which tells recipients that you, as the owner of the domain, have authorized the use of this key to sign your mail. Salesforce uses the private key to create DKIM signature headers on your outgoing email. Then, recipients of the mail, can compare the signature header with the public key in the DNS to determine that the mail was signed with an authorized key. If your domain also publishes a Domain-based Message Authentication, Reporting and Conformance (DMARC) policy, recipients can use the DKIM signature to verify that the mail conforms to DMARC.

For each domain key you create, we recommend this sequence:

1. Insert the `Domain`, `DomainMatch`, and `Selector`.
2. Update your domain's DNS records.
 - a. Locate the DNS record at **`selector._domainkey.domain`**. For example, `mail._domainkey.mail.example.com`.
 - b. Add the `PublicKey` value, like this: `V=DKIM1; p=public_key`.

DKIM Signing Outbound Email

- a. In addition, you can optionally put the record in testing mode, which instructs recipients to not make decisions based on the email signature. Add parameter `t=y` to the DNS entry, like this: `V=DKIM1; t=y; p=public_key`.
3. Update the key via the API or UI to be active.

Consider the following when using domain keys.

- Make sure you add the public key to your DNS record before you make your key active in Salesforce and start DKIM signing. DKIM signing is active whenever your DKIM key is in the active state.
- You can't have more than one active DKIM key per domain name. You might have multiple active DKIM keys if your organization mails from more than a single domain or if you use subdomains under your organizational domain and have specified domain matching at the subdomain level.
- If you want to use the same DKIM key for multiple organizations, you can. Create the key and ensure it's working for one organization first. Then using the API or UI create the key in your other organizations by setting the corresponding fields in the new key to the same values as the original.
- When you insert or update a DKIM key, it's possible that the change affects existing domain keys. For example, if you've set `DomainMatch` to `DomainAndSubdomains` for the `example.com` domain, and you then set `DomainMatch` to `SubdomainsOnly` for the `mail.example.com` domain, either key could be used. Here's how we resolve conflicts in the case when DKIM keys overlap.
 - If two keys are equally specific about matching for the same domain, the new key replaces and deactivates the existing key.
 - If a new key is more specific about matching than an existing key, the new key is used and the existing key is modified to inactive.
 - If multiple keys have different domains that match the sending domain, the key with the longest domain name is used. In case of a tie, the most specific key is used. For example, because `DomainOnly` and `SubdomainsOnly` are more specific than `DomainAndSubdomains`, a new `DomainOnly` key would change the `DomainMatch` for an existing `DomainAndSubdomains` key to become `SubdomainsOnly`. In case of a tie, the most specific key is used.

EmailMessage

An email message.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`

Special Access Rules

Customer Portal users have read access to this object.

`update()` is supported only on records whose `Status` is `Draft`.

Fields

Field	Details
ActivityId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the activity that is associated with the email. Usually represents an open task that is created for the case owner when a new unread email message is received.
BccAddress	Type string Properties Create, Filter, Nillable, Sort, Update Description The addresses that were sent a blind carbon copy of the email.
CcAddress	Type string Properties Create, Filter, Nillable, Sort, Update Description The addresses that were sent a carbon copy of the email.
FromAddress	Type email Properties Create, Filter, Nillable, Update Description The address that originated the email.
FromName	Type string Properties Create, Filter, Nillable, Update Description The sender's name.
HasAttachment	Type boolean Properties Defaulted on create, Filter

Field	Details
	Description Indicates whether the email was sent with an attachment (<code>true</code>) or not (<code>false</code>).
Headers	Type textarea Properties Create, Nillable, Update Description The Internet message headers of the incoming email. Used for debugging and tracing purposes. Does not apply to outgoing emails.
HtmlBody	Type textarea Properties Create, Nillable, Update Description The body of the email in HTML format.
Incoming	Type boolean Properties Create, Defaulted on create, Filter Description Indicates whether the email was received (<code>true</code>) or sent (<code>false</code>).
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
IsExternallyVisible	Type boolean Properties Create, Defaulted on create, Filter, Group, Update Description Controls the external visibility of email messages in communities, and is accessible only if the community case feed is enabled. When this field is set to <code>true</code> —its default value—email messages are visible to external users in the case feed.

Field	Details
MessageDate	Type dateTime Properties Create, Filter, Nillable, Update Description The date the email was created.
ParentId	Type ID Properties Create, Filter Description ID of the Case to which the email is associated.
ReplyToEmailMessageId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the inbound or outbound EmailMessage the current EmailMessage is a reply to. It's not possible to reply to a message whose Status is Draft.
Status	Type picklist Properties Create, Filter, Restricted picklist Description Read only. The status of the email. For example, New, Draft, Unread, Replied, "Sent."
Subject	Type string Properties Create, Filter, Nillable, Update Description The subject line of the email.
TextBody	Type textarea Properties Create, Nillable, Update

Field	Details
	Description The body of the email, in plain text format.
ToAddress	Type string Properties Create, Filter, Nillable, Update Description The address of the email's recipient.

Usage

This object supports the Email-to-Case feature, which allows email sent to one of your company's email addresses to automatically create a new case.

EmailServicesAddress

An email service address.

Each email service has one or more email addresses to which users can send messages for processing. An email service only processes messages it receives at one of its addresses.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
AuthorizedSenders	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Configures the email service address to only accept messages from the email addresses or domains listed in this field. If the email service address receives a message from an unlisted email address or domain, the email service performs the action specified in the <code>AuthorizationFailureAction</code> field of its associated email service. Leave this field blank if you want the email service address to receive email from any email address.

Field	Details
EmailDomainName	Type string Properties Filter, Group, Nillable, Sort Description A read only field you can query that contains the system-generated domain part of this email service address. The system generates a unique domain-part for each email service address to ensure that no two email service addresses are identical.
FunctionId	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the email service for which the email service address receives messages.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this object is active (true) or not (false).
LocalPart	Type string Properties Create, Filter, Group, Sort, Update Description The local-part of the email service address. For the local-part of a Salesforce email address, all alphanumeric characters are valid, plus the following special characters: ! # \$ % & amp; ' * / = ? ^ _ + - ` { } ~ , The dot character (.) is also valid as long as it's not the first or last character. Email addresses aren't case sensitive.
RunAsUserId	Type reference Properties Create, Filter, Group, Sort, Update

Field	Details
	Description The user whose permissions the email service assumes when processing messages sent to this address.

Usage

This object supports the email services feature, which allows you to create automated processes that use Apex classes to process the contents, headers, and attachments of inbound email. For example, you can create an email service that automatically creates contact records based on contact information in messages.

EmailServicesFunction

An email service.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
AddressInactiveAction	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates what the email service does with messages received at an email address that is inactive. One of the following values: 0—The system default is used. 1—The email service returns the message to the sender with a notification that explains why the message was rejected. 2—The email service deletes the message without notifying the sender. 3—The email service queues the message for processing in the next 24 hours. If the message is not processed within 24 hours, the email service returns the message to the sender with a notification that explains why the message was rejected.
ApexClassId	Type reference

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description Required. The ID of the Apex class that the email service uses to process inbound messages. This field is required for API version 12.0 and later.
AttachmentOption	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Indicates the types of attachments the email service accepts. One of the following values: • 0—The email service accepts the message but discards any attachment. • 1—The email service only accepts the following types of attachments: – Attachments with a Multipurpose Internet Mail Extension (MIME) type of text. – Attachments with a MIME type of application/octet-stream and a file name that ends with either a .vcf or .vcs extension. These are saved as text/x-vcard and text/calendar MIME types, respectively. • 2—The email service only accepts binary attachments, such as image, audio, application, and video files. • 3—The email service accepts any type of attachment.
AuthenticationFailureAction	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates what the email service does with messages that fail or do not support any of the authentication protocols if the <code>IsAuthenticationRequired</code> field is true. One of the following values: • 0—The system default is used. • 1—The email service returns the message to the sender with a notification that explains why the message was rejected. • 2—The email service deletes the message without notifying the sender. • 3—The email service queues the message for processing in the next 24 hours. If the message is not processed within 24 hours, the email service returns the message to the sender with a notification that explains why the message was rejected.
AuthorizationFailureAction	Type picklist

Field	Details
	Properties Group, Sort, Create, Filter, Nillable, Restricted picklist, Update Description Indicates what the email service does with messages received from senders who are not listed in the <code>AuthorizedSenders</code> field on either the email service or email service address. One of the following values: 0—The system default is used. 1—The email service returns the message to the sender with a notification that explains why the message was rejected. 2—The email service deletes the message without notifying the sender. 3—The email service queues the message for processing in the next 24 hours. If the message is not processed within 24 hours, the email service returns the message to the sender with a notification that explains why the message was rejected.
AuthorizedSenders	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Configures the email service to only accept messages from the email addresses or domains listed in this field. If the email service receives a message from an unlisted email address or domain, the email service performs the action specified in the <code>AuthorizationFailureAction</code> field. Leave this field blank if you want the email service to receive email from any email address.
ErrorRoutingAddress	Type email Properties Create, Filter, Nillable, Sort, Update Description The destination email address for error notification email messages when <code>IsErrorRoutingEnabled</code> is <code>true</code>.
FunctionInactiveAction	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates what the email service does with messages it receives when the email service itself is inactive. One of the following values:

Field	Details
	• 0—The system default is used. • 1—The email service returns the message to the sender with a notification that explains why the message was rejected. • 2—The email service deletes the message without notifying the sender. • 3—The email service queues the message for processing in the next 24 hours. If the message is not processed within 24 hours, the email service returns the message to the sender with a notification that explains why the message was rejected.
FunctionName	Type string Properties Create, Filter, Group, Sort, Update Description The name of the email service.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this object is active (<code>true</code>) or not (<code>false</code>).
IsAuthenticationRequired	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Configures the email service to verify the legitimacy of the sending server before processing a message. The email service uses the SPF, SenderId, and DomainKeys protocols to verify the sender's legitimacy: If the sending server passes at least one of these protocols and does not fail any, the email service accepts the email. If the server fails a protocol or does not support any of the protocols, the email service performs the action specified in the <code>AuthenticationFailureAction</code> field.
IsErrorRoutingEnabled	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description When incoming email messages can't be processed, indicates whether error notification email messages are routed to a chosen address or to the senders.

Field	Details
IsTextAttachmentsAsBinary	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the email service converts text attachments to binary files.
IsTextTruncated	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description This field is deprecated. It is not available as of API version 23.0 and is deprecated and hidden in versions 17.0 through 22.0. In all API versions, the email service now accepts inbound email messages up to the 10 MB size limit, without truncating the text. Previously, it indicated whether the email service truncated and accepted email messages with HTML body text, plain body text, and text attachments over approximately 100,000 characters (<code>true</code>) or rejected these email messages and notified the sender (<code>false</code>).
IsTlsRequired	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Configures the email service to use Transport Layer Security (TLS), a protocol for secure email communication, to ensure the security and authenticity of inbound email.
OverLimitAction	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates what the email service does with messages if the total number of messages processed by all email services combined has reached the daily limit for your organization. One of the following values: 0—The system default is used. 1—The email service returns the message to the sender with a notification that explains why the message was rejected. 2—The email service deletes the message without notifying the sender. 3—The email service queues the message for processing in the next 24 hours. If the message is not processed within 24 hours, the email service returns the message to the sender with a notification that explains why the message was rejected.

Field	Details
	The system calculates the limit by multiplying the number of user licenses by 1,000.

Usage

This object supports the email services feature, which allows you to create automated processes that use Apex classes to process the contents, headers, and attachments of inbound email. For example, you can create an email service that automatically creates contact records based on contact information in messages.

EmailStatus

Represents the status of email sent.

Supported Calls

`describeSObjects()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
EmailTemplateName	Type string Properties Filter, Group, Nillable, Sort Description The name of the EmailTemplate.
FirstOpenDate	Type dateTime Properties Filter, Nillable, Sort Description Date when the email was first opened by recipient. Label is Date Opened .
LastOpenDate	Type dateTime

Field	Details
	Properties Filter, Nillable, Sort Description Date when the email was last opened by recipient.
TaskId	Type reference Properties Filter, Group, Sort Description The activity (task or event) associated with the email. Label is Activity ID .
TimesOpened	Type int Properties Filter, Group, Sort Description Number of times the recipient opened the email.
WhoId	Type reference Properties Filter, Group, Nillable, Sort Description The Whold represents a human such as a lead or a contact. Wholds are polymorphic. Polymorphic means a Whold is equivalent to a contact's ID or a lead's ID. The label is Name ID.

EmailTemplate

Represents a template for mass email, or email sent when the activity history related list of a record is modified.

 **Note:** You can't send a mass email using a Visualforce email template.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
ApiVersion	Type double Properties Create, Filter, Nillable, Sort, Update Description The API version for this class. Every class has an API version specified at creation.
Body	Type textarea Properties Create, Nillable, Update Description Content of the email. Limit: 384 KB.
BrandTemplateId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required. ID of the BrandTemplate associated with this email template. The brand template supplies letterhead information for the email template.
Description	Type string Properties Create, Filter, Nillable, Sort, Update Description Description of the template, for example, Promotion Mass Mailing.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a

Field	Details
	letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is Template Unique Name.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Encoding	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Character set encoding for the template.
FolderId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the folder that contains the template.
HtmlValue	Type textarea Properties Create, Nillable, Update Description This field contains the content of the email message, including HTML coding to render the email message. Limit: 384 KB.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates that this template is active if <code>true</code>, or inactive if <code>false</code>.
LastUsedDate	Type dateTime Properties Filter, Nillable, Sort

Field	Details
	Description Date and time when this EmailTemplate was last used.
Markup	Type textarea Properties Create, Nillable, Update Description The Visualforce markup, HTML, Javascript, or any other Web-enabled code that defines the content of the template.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Name of the template. Label is Email Template Name.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, NamespacePrefix is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field cannot be accessed unless the logged-in user has the "Customize Application" permission.
OwnerId	Type reference

Field	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the template.
Subject	Type string Properties Create, Group, Nillable, Sort, Update Description Content of the subject line.
TemplateStyle	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Style of the template, such as formalLetter or freeform.
TemplateType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Type of template, either HTML, text, or custom templates, or those generated by Visualforce.
TimesUsed	Type int Properties Filter, Group, Nillable, Sort Description Number of times this template has been used.

Usage

To retrieve this object, issue a describe call on an object, which will return a query result for each activity since the object was created. You can't query these records.

Entitlement

Represents the customer support an Account or Contact is eligible to receive. Entitlements may be based on an Asset, Product2, or ServiceContract.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AccountId	Type reference Properties Create, Filter, Group, Sort Description ID of the Account associated with the entitlement.
AssetId	Type reference Properties Filter, Group, Nillable, Sort Description Required. ID of the Asset associated with the entitlement. Must be a valid asset ID.
BusinessHoursId	Type reference Properties Filter, Group, Nillable, Sort Description Required. ID of the BusinessHours associated with the entitlement. Must be a valid business hours ID.
CasesPerEntitlement	Type int Properties Filter, Group, Nillable, Sort Description The total number of cases the entitlement supports. This field is only available if <code>IsPerIncident</code> is <code>true</code> .

Field	Details
ContractLineItemId	Type reference Properties Filter, Group, Nillable, Sort Description Required. ID of the ContractLineItem associated with the entitlement. Must be a valid ID.
EndDate	Type date Properties Create, Filter, Nillable, Update Description The last day the entitlement is in effect.
IsPerIncident	Type boolean Properties Defaulted on create, Filter, Update Description Indicates whether the entitlement is limited to supporting a specific number of cases (<code>true</code>) or not (<code>false</code>).
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string

Field	Details
	Properties Create, Filter, Update Description Required. Name of the entitlement.
RemainingCases	Type int Properties Create, Filter, Nillable, Update Description The number of cases the entitlement can support. This field decreases in value by one each time a case is created with the entitlement. This field is only available if <code>IsPerIncident</code> is selected.
ServiceContractId	Type reference Properties Create, Filter, Nillable, Update Description Required. ID of the ServiceContract associated with the entitlement. Must be a valid ID.
SlaProcessId	Type reference Properties Create, Filter, Nillable, Update Description ID of the SlaProcess associated with the entitlement. This field is available in version 19.0 and later.
StartDate	Type date Properties Create, Filter, Nillable, Update Description The first date the entitlement is in effect.
Status	Type picklist Properties Filter, Nillable

Field	Details
	Description Status of the entitlement, such as <code>Expired</code> .
Type	Type picklist Properties Create, Filter, Nillable, Update Description The type of entitlement, such as Web or phone support.

Usage

Use this object to query and manage entitlements.

EntitlementContact

Represents a Contact eligible to receive customer support via an Entitlement.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`

Fields

Field	Details
ContactId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Contact associated with the entitlement. Must be a valid ID.
EntitlementId	Type reference Properties Create, Filter Description Required. ID of the Entitlement associated with the entitlement contact. Must be a valid ID.

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Nillable Description Required. Name of the entitlement contact.

Usage

Use to query and manage entitlement contacts.

EntitlementFeed

Represents a single feed item in the feed displayed on the detail page for an entitlement.

An entitlement feed shows recent changes to an entitlement record for any fields that are tracked in feeds, as well as comments and posts about the record. It's a useful way to stay up-to-date with changes to entitlements. This object is available in API version 23.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Entitlement object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the EntitlementFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection changes a tracked record, the <code>CreatedBy</code> field contains the ID of the system administrator. The <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort

Field Name	Details
	Description The description of the file specified in <code>ContentData</code> .
<code>ContentFileName</code>	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code> .
<code>ContentSize</code>	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
<code>ContentType</code>	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
<code>InsertedById</code>	Type reference Properties Group, Nillable, Sort Description The ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, <code>InsertedById</code> is set to the ID of the logged-in user.
<code>LastModifiedDate</code>	Type dateTime Properties Defaulted on create, Filter, Sort

Field Name	Details
	Description This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on the feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for the <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nullable, Sort Description The URL of the <code>LinkPost</code>.
NetworkScope	Type picklist Properties Create, Filter, Group, Nullable, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.

Field Name	Details
ParentId	Type reference Properties Filter, Group, Sort Description ID of the entitlement record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing <code>ContentVersion</code> and post it to a feed as an <code>EntitlementFeed</code> object of <code>Type ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the <code>EntitlementFeed</code>. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of <code>EntitlementFeed</code> item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a <code>Task</code> associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a <code>Task</code> or <code>Event</code> associated with a case record (excluding email and call logging). For a recurring <code>Task</code> with <code>CaseFeed</code> disabled, one event is generated for the series only. For a recurring <code>Task</code> with <code>CaseFeed</code> enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement.

Field Name	Details
	• <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received.

Field Name	Details
	• <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>. • <code>Visibility</code> can be updated on record posts.

Usage

Use this object to track changes for an entitlement record.

EntitlementHistory

Represents the changes to field values on an Entitlement.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
EntitlementId	Type reference Properties Filter Description Required. ID of the Entitlement.
Field	Type picklist Properties Filter, Restricted picklist Description The name of the field that was changed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
NewValue	Type anyType Properties Nillable Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable Description The latest value of the field before it was changed.

Usage

This object respects field-level security on the parent object.

EntitlementTemplate

Represents predefined terms of customer support for a product (Product2).

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>BusinessHoursId</code>	Type reference Properties Create, Filter, Nillable, Update Description ID of the BusinessHours associated with the entitlement template. Must be a valid business hours ID.
<code>CasesPerEntitlement</code>	Type int Properties Create, Filter, Nillable, Update Description The total number of cases the entitlement template supports. This field is only available if <code>IsPerIncident</code> is <code>true</code>.
<code>IsPerIncident</code>	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates whether the entitlement template is limited to supporting a specific number of cases (<code>true</code>) or not (<code>false</code>).
<code>Name</code>	Type string Properties Create, Filter, idLookup, Update Description Required. Name of the entitlement template.

Field	Details
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. Available in version 34.0 and later.
SlaProcessId	Type reference Properties Create, Filter, Nillable, Update Description ID of the SlaProcess associated with the entitlement template. This field is available in API version 19.0 and later.
Term	Type int Properties Create, Filter, Nillable, Update Description Number of days that the entitlement template is valid.
Type	Type picklist Properties Create, Filter, Nillable, Update Description The type of entitlement template, such as Web or phone support.

Usage

Use this object to manage entitlement templates.

EntityHistory

Represents historical information about an object's changed field values. This object is only available to users with the "View All Data" permission.

This object is unavailable beginning with API version 8.0. Use the object-specific History objects instead: CaseHistory, ContractHistory, LeadHistory, OpportunityFieldHistory, OpportunityHistory ProcessInstanceHistory, QuantityForecastHistory, RevenueForecastHistory, or SolutionHistory.

Supported Calls

`describeSObjects()`, `getUpdated()`, `getDeleted()`, `query()`, `retrieve()`

Fields

Field	Details
FieldName	Type picklist Properties Filter, Restricted picklist Description ID of the standard or custom field.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
NewValue	Type anyType Properties Nillable Description New value of the modified field.
OldValue	Type anyType

Field	Details
	Properties Nillable Description Previous value of the modified field.
ParentId	Type reference Properties Filter Description ID of the object that contains the field.
ParentObjectType	Type picklist Properties Filter, Restricted picklist Description The kind of object that contains the field.

Usage

In API version 7.0 and later, this object works with Case, Contract, and Solution objects:

- This object is always read-only in the online application.
- When a field is modified, this object records both the old and new field values. There are exceptions to this behavior for certain fields such as long text areas and multi-select picklists. These fields appear in this object to indicate that the field was changed, but the old and new values are not recorded.
- Two rows are added to this object when foreign key fields change. One row contains the foreign key object names that display in the online application. For example, "Jane Doe" is recorded as the name of a contact. The other row contains the actual foreign key ID that is only returned to and visible from the API.
- Up to a total of twenty fields (standard or custom) can be tracked for a given object.
- In the online application, you can specify which fields are tracked or not tracked at any time.
- As soon as tracking is turned on for a field, all changes to its value are recorded in the database.
- Turning off tracking for a field stops further changes from being recorded, but the history data is not deleted.
- Be advised that deleting a custom field also permanently deletes the history data for that custom field.

EntitySubscription

Represents a subscription for a user following a record or another user. A user can subscribe to a record or to another user. Changes to the record and updates from the users are displayed in the Chatter feed on the user's home page, which is a useful way to stay up-to-date with other users and with changes made to records in Salesforce. Feeds are available in API version 18.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the community that this file originated from. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization.
ParentId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the record or user which the user is following.
SubscriberId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the User who is following the record or user.

Usage

Consider this when following records and users:

- Users can only follow records that they can see.
- Users can see which records other users are following, unless they don't have access to the records.
- Administrators and users with the "Modify All Users" permission can configure a user to follow records that the user has read access to.
- Administrators and users with the "Modify All Users" permission can configure users to stop following records.
- Following topics is available in API version 29.0 and later. For this reason, a topic ID is now a supported value for the `ParentId` field.
- If you deactivate a user, any EntitySubscription where the user is associated with the `ParentId` or `SubscriberId` field, meaning all subscriptions both to and from the user, are soft deleted. If the user is reactivated, the subscriptions are restored. However, if you

deactivate multiple users at once and these users follow each other, their subscriptions are hard deleted. In this case, the user-to-user EntitySubscription is deleted twice (double deleted). Such subscriptions can't be restored upon user reactivation.

When using `query()` with EntitySubscription,

- A query must include a `LIMIT` clause and the limit can't exceed 1000.
- A query using a `WHERE` clause can only filter by fields on the EntitySubscription object.
- If user sharing is enabled and the querying user is not an administrator, a SOQL query must be constrained either by the `ParentId` or `SubscriberId`. Otherwise, the query behavior at run time is undefined, meaning the result set can be incomplete or inconsistent from invocation to invocation. For an unconstrained query, the sharing check limits imposed on a non-administrative user are likely to be exceeded before the query completes, because access checks are run against both parent and subject, for each row of the result set. We recommend using the Chatter REST API to query EntitySubscription data instead of running a SOQL query.
- Users without the "View All Data" permission
 - Need read access on the object associated with the `ParentId` field to see which users are following records for the object.
 - Can use an `ORDER BY` clause in a query only to order by fields on the EntitySubscription object. For example, if the subscription relates to an Account record, the query can `ORDER BY ParentId`, but it can't `ORDER BY Account.Name`.
 - Don't always get all matching subscriptions when running a query. For these users, a query evaluates visibility criteria on a maximum of 500 records to reduce the prospect of long-running queries. If a user runs a query to see the CEO's subscriptions, it might scan a large number of records. The query only returns matches within the first 500 records scanned. It is possible that there are more subscriptions that are visible to the user, but they are not returned. To mitigate this, we recommend using a `WHERE` clause, if possible, to reduce the scope of the query.

Sample—SOQL

The following SOQL query returns subscriptions for all the accounts that a subscriber is following that have more than 10 employees:

```
SELECT Id
FROM EntitySubscription
WHERE SubscriberId = '005U00000000Rg2CIAS'
AND ParentId IN (
  SELECT Id FROM Account
  WHERE NumberOfEmployees > 10
)
LIMIT 200
```

EnvironmentHubMember

Represents a member organization in the Environment Hub. This object is available in API version 29.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`

Fields

Field Name	Details
CreatedById	Type reference Properties Defaulted on create, Filter Description System field that specifies the ID of the user who created this record.
CreatedDate	Type dateTime Properties Defaulted on create, Filter Description System field that specifies the date and time when this record was created.
Description	Type string Properties Filter, Group, Nillable, Sort Description A brief description of this organization.
DisplayName	Type string Properties Create, Filter, Group, Sort Description The name that the user has specified for this member organization.
EnvironmentHubId	Type reference Properties Filter, Group, Sort Description The Organization ID of this member's Environment Hub organization.
Id	Type ID Properties Defaulted on create

Field Name	Details
	Description System field that uniquely identifies this record.
IsFedIdSsoMatchAllowed	Type boolean Properties Defaulted on create Description Indicates if single sign-on has been enabled based on matching Federation ID. The default value is <code>false</code> .
LastModifiedById	Type reference Properties Defaulted on create, Filter Description System field that specifies the ID of the user who last updated this record.
LastModifiedDate	Type reference Properties Defaulted on create, Filter Description System field that specifies the date and time when this record was last modified.
MemberEntity	Type string Properties Create, Filter, Group, Sort Description The Organization ID of the member organization this record is representing.
OrgEdition	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The organization's edition, for example, Enterprise Edition or Unlimited Edition.
OrgStatus	Type picklist

Field Name	Details
	Properties Filter, Group, Sort, Update Description The licensing or creation status of this organization. Possible values include <code>Active</code>, <code>Demo</code>, <code>Deleted</code>, <code>Free</code>, <code>Inactive</code>, and <code>Trial</code>.
Origin	Type picklist Properties Filter, Group, Sort Description The method by which this organization was added to the Environment Hub. Possible values are <code>Auto Discovered</code> and <code>User Added</code>.
ShouldAddRelatedOrgs	Type boolean Properties Defaulted on create, Update Description If related organizations should be automatically connected to the hub, when this member organization is added. The default value is <code>true</code>.
SsoStatus	Type picklist Properties Filter, Group, Sort, Update Description If single sign-on has been enabled for this organization. Possible values are: • <code>Enabled</code>—Single sign-on is enabled. • <code>Disabled</code>—Single sign-on is disabled. • <code>Pending</code>—Single sign-on is in the process of being enabled. • <code>Failed</code>—Single sign-on enablement failed. Contact Salesforce support for assistance.
SsoUsernameFormula	Type string Properties Group, Nillable, Sort, Update Description The custom formula for matching users in the hub and member organizations.

Usage

Use this object to access and modify settings of member organizations in the Environment Hub.

Event

Represents an event in the calendar. In the user interface, event and task records are collectively referred to as activities.

 Note:

- An EventRelation object can't be related to a child event, and child events don't include the invitee related list.
- query(), delete(), and update() aren't allowed with events related to more than one contact in API versions 25.0 and earlier.

Supported Calls

create(), delete(), describeLayout(), describeSObjects(), getDeleted(), getUpdated(), query(), retrieve(), search(), undelete(), update(), upsert()

Fields

Field	Details
AcceptedEventInviteeIds	Type JunctionIdList Properties Create, Update Description A string array of contact or lead IDs who accepted this event. This JunctionIdList is linked to the AcceptedEventRelation child relationship.  Warning: Adding a JunctionIdList field name to the fieldsToNull property deletes all related junction records. This action can't be undone.
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description Represents the ID of the related Account. The AccountId is determined as follows. If the value of whatId is any of the following objects, then Salesforce uses that object's AccountId. • Account • Opportunity • Contract

Field	Details
	Custom object that is a child of Account If the value of the <code>whatId</code> field is any other object, and the value of the <code>whoId</code> field is a Contact object, then Salesforce uses that contact's <code>AccountId</code>. (If your organization uses Shared Activities, Salesforce uses the <code>AccountId</code> of the primary contact.) Otherwise, Salesforce sets the value of the <code>AccountId</code> field to <code>null</code>. For information on IDs, see ID Field Type.
ActivityDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Contains the event's due date if the <code>IsAllDayEvent</code> flag is set to <code>true</code>. This field is a date field with a timestamp that is always set to midnight in the Coordinated Universal Time (UTC) time zone. Don't attempt to alter the timestamp to account for time zone differences. Label is Due Date Only. This field is required in versions 12.0 and earlier if the <code>IsAllDayEvent</code> flag is set to <code>true</code>. The value for this field and <code>StartDateTime</code> must match, or one of them must be <code>null</code>.
ActivityDateTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Contains the event's due date if the <code>IsAllDayEvent</code> flag is set to <code>false</code>. This field is a regular Date/Time field with a relevant time portion. The time portion is always transferred in the Coordinated Universal Time (UTC) time zone. Translate the time portion to or from a local time zone for the user or the application, as appropriate. Label is Due Date Time. This field is required in versions 12.0 and earlier if the <code>IsAllDayEvent</code> flag is set to <code>false</code>. The value for this field and <code>StartDateTime</code> must match, or one of them must be <code>null</code>.
ClientGuid	Type string Properties Filter, Group, Nillable, Sort Description The client globally unique identifier identifies the external API client used to create the event. Label is Client GUID.

Field	Details
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
DeclinedEventInviteeIds	Type JunctionIdList Properties Create, Update Description A string array of contact, lead, or user IDs who declined this event. This <code>JunctionIdList</code> is linked to the <code>DeclinedEventRelation</code> child relationship.  Warning: Adding a <code>JunctionIdList</code> field name to the <code>fieldsToNull</code> property deletes all related junction records. This action can't be undone.
Description	Type textarea Properties Create, Nillable, Update Description Contains a text description of the event. Limit: 32,000 characters.
Division	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization's data. Available only if the organization has the Division permission enabled.
DurationInMinutes	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Contains the event length, in minutes. Note that even though this field represents a temporal value, it is an integer type—not a Date/Time type. This field is required in versions 12.0 and earlier if <code>IsAllDayEvent</code> is false.

Field	Details
	In versions 13.0 and later, this field is optional, depending on the following: • If <code>IsAllDayEvent</code> is true, you can supply a value for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time. If both fields are <code>null</code>, the duration defaults to one day. • If <code>IsAllDayEvent</code> is false, a value must be supplied for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time. If the multiday event feature is enabled, then API versions 13.0 and later support values greater than 1440 for the <code>DurationInMinutes</code> field. API versions 12.0 and earlier can't access event objects whose <code>DurationInMinutes</code> is greater than 1440. For more information, see Multiday Events.
EndTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Available in versions 13.0 and later. This field is optional, depending on the following: • If <code>IsAllDayEvent</code> is true, you can supply a value for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time. If both fields are <code>null</code>, the duration defaults to one day. • If <code>IsAllDayEvent</code> is false, a value must be supplied for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time.
EventWhoIds	Type JunctionIdList Properties Create, Update Description A string array of contact or lead IDs used to create many-to-many relationships with a shared event. <code>EventWhoIds</code> is available when the shared activities setting is enabled. The first contact or lead ID in the list becomes the primary <code>WhoId</code> if you don't specify a primary <code>WhoId</code>.  Warning: Adding a <code>JunctionIdList</code> field name to the <code>fieldsToNull</code> property deletes all related junction records. This action can't be undone.
GroupEventType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort

Field	Details
	Description Read-only. Available in API versions 19.0 and later. The possible values are: • 0 (Non-group event)—An event with no invitees. • 1 (Group event)—An event with invitees. • 2 (Proposed event)—An event created when a user requests a meeting with a contact, lead, or person account using the Salesforce user interface. When the user confirms the meeting, the proposed event becomes a group event. You can't create, edit, or delete proposed events in the API. For more information, see How Cloud Scheduler Works in the Salesforce help.
IsAllDayEvent	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the <code>ActivityDate</code> field (<code>true</code>) or the <code>ActivityDateTime</code> field (<code>false</code>) is used to define the date or time of the event. Label is All-Day Event. See also DurationInMinutes and EndDateTime.
IsArchived	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the event has been archived.
IsChild	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the event is a child of another event (<code>true</code>) or not (<code>false</code>). For a child event, you can update <code>IsReminderSet</code> and <code>ReminderDateTime</code> only. You can query and delete a child event. If the objects related to the child event are different from those related to the parent event (this difference is possible if you use API version 25.0 or earlier) and one of the objects related to the child event is deleted, the objects related to the parent event are updated to ensure data integrity.
IsClientManaged	Type boolean

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the event is managed by an external client. If the value of this field is false, the event isn't owned or managed by an external client, and Salesforce can be used to update it. If the value is true, Salesforce can be used to change only noncritical fields on the event. Label is Is Client Managed.
IsGroupEvent	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the event is a group event—that is, whether it has invitees (<code>true</code>) or not (<code>false</code>).
IsPrivate	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether users other than the creator of the event can (<code>false</code>) or can't (<code>true</code>) see the event details when viewing the event user's calendar. However, users with the View All Data or Modify All Data permission can see private events in reports and searches, or when viewing other users' calendars. Private events can't be associated with opportunities, accounts, cases, campaigns, contracts, leads, or contacts. Label is Private.
IsRecurrence	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Indicates whether the event is scheduled to repeat itself (<code>true</code>) or only occurs once (<code>false</code>). This is a read-only field when updating records, but not when creating them. If this field value is <code>true</code>, then <code>RecurrenceEndDateOnly</code>, <code>RecurrenceStartDateTime</code>, <code>RecurrenceType</code>, and any recurrence fields associated with the given recurrence type must be populated. Label is Create recurring series of events.
IsReminderSet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Details
	Description Indicates whether the activity is a reminder (<code>true</code>) or not (<code>false</code>).
IsVisibleInSelfService	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether an event associated with an object can be viewed in the Customer Portal (<code>true</code>) or not (<code>false</code>). If your organization has enabled Communities, events marked <code>IsVisibleInSelfService</code> are visible to any external user in the community, as long as the user has access to the record the event was created on. This field is available when Customer Portal or partner portal are enabled OR Communities is enabled and you have Customer Portal or partner portal licenses.
Location	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Contains the location of the event.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Contains the ID of the user who owns the event. Label is Assigned to ID .
RecurrenceActivityId	Type reference Properties Filter, Group, Nillable, Sort Description Read-only. Not required on create. Contains the ID of the main record of the recurring event. Subsequent occurrences have the same value in this field.
RecurrenceDayOfMonth	Type int Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description Indicates the day of the month on which the event repeats.
RecurrenceDayOfWeekMask	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Indicates the day or days of the week on which the event repeats. This field contains a bitmask. The values are as follows: • Sunday = 1 • Monday = 2 • Tuesday = 4 • Wednesday = 8 • Thursday = 16 • Friday = 32 • Saturday = 64 Multiple days are represented as the sum of their numerical values. For example, Tuesday and Thursday = 4 + 16 = 20.
RecurrenceEndDateOnly	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Indicates the last date on which the event repeats. For multiday recurring events, this is the day on which the last occurrence starts.
RecurrenceInstance	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates the frequency of the event's recurrence. For example, 2nd or 3rd.
RecurrenceInterval	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Indicates the interval between recurring events.

Field	Details
RecurrenceMonthOfYear	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates the month in which the event repeats.
RecurrenceStartDateTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Indicates the date and time when the recurring event begins. The value must precede the <code>RecurrenceEndDateOnly</code>.
RecurrenceTimeZoneSidKey	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates the time zone associated with a recurring event. For example, "UTC-8:00" for Pacific Standard Time.
RecurrenceType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates how often the event repeats. For example, daily, weekly, or every nth month (where "nth" is defined in <code>RecurrenceInstance</code>).
ReminderDateTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Represents the time when the reminder is scheduled to fire, if <code>IsReminderSet</code> is set to <code>true</code>. If <code>IsReminderSet</code> is set to <code>false</code>, then the user may have deselected the reminder checkbox in the Salesforce user interface, or the reminder has already fired at the time indicated by the value.

Field	Details
ShowAs	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates how this event appears when another user views the calendar: Busy, Out of Office, or Free Time. Label is Show Time As.
StartDateTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Indicates the start date and time of the event. Available in versions 13.0 and later. If the Event <code>IsAllDayEvent</code> flag is set to true (indicating that it is an all-day Event), then the event start date information is contained in the <code>StartDateTime</code> field. This field is a date field with a timestamp that is always set to midnight in the Coordinated Universal Time (UTC) time zone. The timestamp is not relevant, and you should not attempt to alter it to account for any time zone differences. If the Event <code>IsAllDayEvent</code> flag is set to false (indicating that it is not an all-day event), then the event start date information is contained in the <code>StartDateTime</code> field. The time portion is always transferred in the Coordinated Universal Time (UTC) time zone. You need to translate the time portion to or from a local time zone for the user or the application, as appropriate. If this field has a value, then <code>ActivityDate</code> and <code>ActivityDateTime</code> must either be <code>null</code> or match the value of this field.
Subject	Type combobox Properties Create, Filter, Nillable, Sort, Update Description The subject line of the event, such as Call, Email, or Meeting. Limit: 255 characters.
Type	Type picklist Properties Create, Filter, Nillable, Update Description Indicates the event type, such as Call, Email, or Meeting.

Field	Details
UndecidedEventInviteeIds	Type JunctionIdList Properties Create, Update Description A string array of contact, lead, or user IDs who are undecided about this event. This <code>JunctionIdList</code> is linked to the <code>UndecidedEventRelation</code> child relationship.  Warning: Adding a <code>JunctionIdList</code> field name to the <code>fieldsToNull</code> property deletes all related junction records. This action can't be undone.
WhatCount	Type int Properties Filter, Group, Nillable, Sort Description Available if your organization has enabled Shared Activities. Represents the count of related <code>EventRelations</code> pertaining to the <code>WhatId</code>. The count of the <code>WhatId</code> must be 1 or less.
WhatId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The <code>WhatId</code> represents nonhuman objects such as accounts, opportunities, campaigns, cases, or custom objects. <code>WhatIds</code> are polymorphic. Polymorphic means a <code>WhatId</code> is equivalent to the ID of a related object. The label is <code>Related To ID</code>.
WhoCount	Type int Properties Filter, Group, Nillable, Sort Description Available to organizations that have Shared Activities enabled. Represents the count of related <code>EventRelations</code> pertaining to the <code>WhoId</code>.
WhoId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description The <code>WhoId</code> represents a human such as a lead or a contact. WhoIds are polymorphic. Polymorphic means a <code>WhoId</code> is equivalent to a contact's ID or a lead's ID. The label is <code>Name ID</code>. If <code>Shared Activities</code> is enabled, the value of this field is the ID of the related lead or primary contact. If you add, update, or remove the <code>WhoId</code> field, you might encounter problems with triggers, workflows, and data validation rules that are associated with the record. The label is <code>Name ID</code>. If the <code>JunctionIdList</code> field is used, all <code>WhoIds</code> are included in the relationship list.

Usage

Use Event to manage calendar appointments.

Querying and Filtering Events

Queries on events will be denied before they time out if they involve amounts of data that are deemed too large. In such cases, the exception code `OPERATION_TOO_LARGE` is returned. If you receive `OPERATION_TOO_LARGE`, refactor your query to return or scan a smaller amount of data.

When querying for events with a specific due date, you must filter on both the `ActivityDateTime` and `ActivityDate` fields. For example to find all events with a due date of February 14, 2003, you need two filters:

- One filter with the `ActivityDate` field equal to the Coordinated Universal Time (UTC) time zone on February 14, 2003.
- One filter with the `ActivityDateTime` field greater than or equal to midnight on February 14, 2003 in the user's local time zone AND less than or equal to midnight on February 15, 2003 in the user's local time zone.

Alternatively, in version 13.0 and later, you can find events with a specific due date by filtering on `StartDateTime`. For example, to find all events with a due date of February 14, 2003, filter with the `StartDateTime` greater than or equal to midnight on February 14, 2003 in the user's local time zone AND less than or equal to midnight on February 15, 2003 in the user's local time zone.

The `EventId` field of an `EventRelation` object always points to the master record. An invitee on a group event can query the `EventRelation` object to view the master record.

Multiday Events

- Multiday events are available in version 13.0 and later. Also, in earlier versions SOQL queries do not return multiday events.
- Multiday events are enabled through the user interface from Setup by clicking **Customize > Activities > Activity Settings**.
- If the multiday event feature is enabled, then API versions 13.0 and later support values greater than 1440 for the `DurationInMinutes` field. API versions 12.0 and earlier can't access event objects whose `DurationInMinutes` is greater than 1440.
- Multiday events can't exceed 14 days.

Recurring Events

- Recurring events are available in version 7.0 and later.
- After an event is created, it can't be changed from recurring to nonrecurring or vice versa.
- When you delete a recurring event series through the API, all past and future events in the series are removed. However, when you delete a recurring event series through the user interface, only future occurrences are removed.

- When creating a recurring event series, the duration of the event must be 24 hours or less (either the `DurationInMinutes` or the difference between `RecurrenceStartDateTime` and `EndDateTime` must be greater than 24 hours). Once the recurring event series is created, you can extend the length of individual occurrences beyond 24 hours if Multiday events are enabled; see **Multiday Events**.
- If `IsRecurrence` is `true`, then `RecurrenceStartDateTime`, `RecurrenceEndDateOnly`, `RecurrenceType`, and any properties associated with the given recurrence type (see the following table) must be populated.
- When updating a recurring event series, it's not possible to update the `EventRelation` for the event series object and the `EventRelation` for the series object occurrences at the same time.

The following table describes the usage of recurrence fields. Each recurrence type must have all of its properties set. All unused properties must be set to null.

RecurrenceType Value	Properties	Example Pattern
RecursDaily	RecurrenceInterval	Every second day
RecursEveryWeekday	RecurrenceDayOfWeekMask	Every weekday - can't be Saturday or Sunday
RecursMonthly	RecurrenceDayOfMonth RecurrenceInterval	Every second month, on the third day of the month
RecursMonthlyNth	RecurrenceInterval RecurrenceInstance RecurrenceDayOfWeekMask	Every second month, on the last Friday of the month
RecursWeekly	RecurrenceInterval RecurrenceDayOfWeekMask	Every three weeks on Wednesday and Friday
RecursYearly	RecurrenceDayOfMonth RecurrenceMonthOfYear	Every March on the twenty-sixth day of the month
RecursYearlyNth	RecurrenceDayOfWeekMask RecurrenceInstance RecurrenceMonthOfYear	The first Saturday in every October

JunctionIdList

To create an event using `JunctionIdList`, IDs are pulled from the related contacts and both the event and the `EventRelation` records are created in one API call. If the `EventRelation` fails, the event is rolled back because it's all done in a single API call.

```
public void createEventNew(Contact[] contacts) {
    String[] contactIds = new String[contacts.size()];
    for (int i = 0; i < contacts.size(); i++) {
        contactIds[i] = contacts[i].getID();
    }
    Event event = new Event();
    event.setSubject("New Event");
    event.setEventWhoIds(contactIds);
    SaveResult[] results = null;
    try {
        results = connection.create(new Event[] {
            task
        });
    } catch (ConnectionException ce) {
        ce.printStackTrace();
    }
}
```

```
}
}
```

EventFeed

Represents a single feed item in the feed on an Event.

This object is available in API version 20.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"

 **Note:** Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of EventFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description When a <code>PartnerNetworkConnection</code> makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the <code>PartnerNetworkConnection</code> that made the change. Available if Salesforce to Salesforce is enabled for your organization.
<code>ContentData</code>	Type base64 Properties Nullable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
<code>ContentDescription</code>	Type textarea Properties Nullable, Sort Description The description of the file specified in <code>ContentData</code>.
<code>ContentFileName</code>	Type string Properties Group, Nullable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
<code>ContentSize</code>	Type int Properties Group, Nullable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
<code>ContentType</code>	Type string

Field	Details
	Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.

Field	Details
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, LastModifiedDate is the same as CreatedDate. If a FeedComment is inserted on that feed item, then LastModifiedDate becomes the CreatedDate for that FeedComment. Deleting the FeedComment does not change the LastModifiedDate. Ordering by LastModifiedDate DESC sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope:

Field	Details
	- Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the event record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging).

Field	Details
	For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Field	Details
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for an event record. You can only delete a feed if you created it, or if you have the “Modify All Data” permission.

EventLogFile

Represents event log files for event monitoring.

The event monitoring feature allows you to gather information about your Salesforce organization’s operational events, which you can use to analyze usage trends and user behavior. You can interact with event monitoring data using the EventLogFile object. This object is available in API versions 29.0 and later.



Note: Log data schema for each `EventType` can change. At the start of each release, use the `LogFileFieldNames` and `LogFileFieldTypes` fields to validate schema changes for each `EventType`. In the unlikely case where no log files are generated for 24 hours, contact Salesforce.

Refer to the [Force.com REST API Developer’s Guide](#) for details about event monitoring.

Special Access Rules

Accessing this object requires View Event Log Files and API Enabled user permissions. Users with View All Data permission can view event log files.

Supported Calls

query(), retrieve()

Fields

Field	Details
EventType	Type string Properties Filter, Group, Restricted picklist, Sort Description The event type—API, Login, Report, URI, and so forth. Use to determine which files were generated for your organization. See Supported Event Types.
LogDate	Type dateTime Properties Filter, Sort Description The log creation date.
LogFile	Type base64 Description Encoded file data.
LogFileContentType	Type string Properties Filter, Group, Sort Description The content type of the log file; always .csv.
LogFileFieldNames	Type string Properties Nillable Description The ordered list of fields in the log file data..  Note: LogFileFieldNames and LogFileFieldTypes are specific to each EventType. For example, LogFileFieldNames has a different value for an API EventType and a Login EventType.

Field	Details
LogFileFieldTypes	Type string Properties Nillable Description The ordered list of field types in the log file data (String, Id, and so forth).  Note: LogFileFieldNames and LogFileFieldTypes are specific to each EventType. For example, LogFileFieldTypes will have a different value for an API EventType and a Login EventType.
LogFileLength	Type double Properties Filter, Sort Description The log file length in bytes. You can use this field to plan storage needs for your log files.

Supported Event Types

The EventType field supports 29 events. The following tables serve as a reference for each event and its associated fields.

 **Note:** The LOGIN_EVENT and LOGOUT_EVENT events are available in supported Salesforce editions at no additional cost. Contact Salesforce to purchase the remaining event types.

APEX_CALLOUT_EVENT

APEX_CALLOUT_EVENT events contain details about callouts (external requests) during Apex code execution.

Field	Details
CLIENT_IP	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26
CPU_TIME	Type Number Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the

app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

METHOD

Type

String

Description

The HTTP method of the callout.

Example

GET, POST, PUT, and so on.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

REQUEST_SIZE

Type

Number

Description

The size of the callout request body, in bytes.

RESPONSE_SIZE

Type

Number

Description

The size of the callout response, in bytes.

RUN_TIME

Type

Number

	Description Not used for this event type. Use the <code>TIME</code> field instead.
SUCCESS	Type Boolean Description 1 if the request was successful, and 0 if not.
TIME	Type Number Description The amount of time that the request took in milliseconds (ms).
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
TYPE	Type String Description The type of Apex callout. Example REST or AJAX
URI	Type String Description The URI of the page that's receiving the request. Example /home/home.jsp
URL	Type String Description The callout endpoint URL. Example www.salesforce.com
USER_ID	Type Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

005300000009M9

APEX_EXECUTION_EVENT

APEX_EXECUTION_EVENT events contain details about Apex classes that are used.

Field	Details
CLIENT_IP	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26
CPU_TIME	Type Number Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
DB_TOTAL_TIME	Type Number Description The time in milliseconds for a database round trip. Compare this field to CPU_TIME to determine whether performance issues are occurring in the database layer or in your own code.
ENTRY_POINT	Type String Description The entry point for this Apex execution. Example - GeneralCloner.cloneAndInsertRecords - VF- /apex/CloneUser

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

NUMBER_SOQL_QUERIES

Type

Number

Description

The number of SOQL queries that were executed during the event.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDIk0FKfF5DV

RUN_TIME

Type

Number

Description

The amount of time that the request took in milliseconds.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

```
/home/home.jsp
```

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

APEX_SOAP_EVENT

APEX_SOAP_EVENT events contain details about Web Services API calls.

Field**Details**

CLASS_NAME

Type

String

Description

The Apex class name. If the class is part of a managed package, this string includes the package namespace.

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

DB_TOTAL_TIME

Type

Number

Description

The time in milliseconds for a database round trip. Compare this field to CPU_TIME to determine whether performance issues are occurring in the database layer or in your own code.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

LIMIT_USAGE_PERCENT

Type

Number

Description

The percentage of Apex SOAP calls that were made against the organization's limit.

METHOD_NAME

Type

String

Description

The name of the calling Apex method.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

QUERY

Type

String

Description

The SOQL query, if one was performed.

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

REQUEST_STATUS

Type

String

Description

The status of the request for a page view or user interface action.

Possible Values

- S: Success
- F: Failure
- U: Undefined
- A: Authorization Error
- R: Redirect
- N: Not Found

RUN_TIME

Type

Number

Description

The amount of time that the request took in milliseconds.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

APEX_TRIGGER_EVENT

APEX_TRIGGER_EVENT events contain details about triggers that fire in an organization.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

DB_TOTAL_TIME

Type

Number

Description

The time in milliseconds for a database round trip. Compare this field to `CPU_TIME` to determine whether performance issues are occurring in the database layer or in your own code.

ENTITY_NAME

Type

String

Description

The name of the object affected by the trigger.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

	Description The unique ID of a single transaction.
	Example 3nWgxWbDKWWDIk0FKfF5DV
REQUEST_STATUS	Type String Description The status of the request for a page view or user interface action. Possible Values • S: Success • F: Failure • U: Undefined • A: Authorization Error • R: Redirect • N: Not Found
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
TRIGGER_ID	Type String Description The 15-character ID of the trigger that was fired.
TRIGGER_NAME	Type String Description The name of the trigger that was fired.
TRIGGER_TYPE	Type String

	Description The type of this trigger.
	Possible Values • AfterInsert • AfterUpdate • BeforeInsert • BeforeUpdate
URI	Type String
	Description The URI of the page that's receiving the request.
	Example /home/home.jsp
USER_ID	Type Id
	Description The 15-character ID of the user who's using Salesforce services through the UI or the API.
	Example 005300000009M9

API_EVENT

API_EVENT events contain details about your organization's Force.com Web Services API activity.

Field	Details
API_TYPE	Type String
	Description The type of API request.
	Possible Values • D: Apex Class • E: SOAP Enterprise • I: SOAP Cross Instance • L: Live Agent • M: SOAP Metadata • O: Old SOAP • P: SOAP Partner

- R: REST API
- S: SOAP Apex
- T: SOAP Tooling
- X: XmlRPC

API_VERSION

Type

String

Description

The version of the API that's being used.

Example

32.0

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CLIENT_NAME

Type

String

Description

The name of the client that's using Salesforce services.

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

DB_BLOCKS

Type

Number

Description

Indicates how much activity is occurring in the database. A high value for this field suggests that you should add indexes or filters on your queries.

DB_CPU_TIME

Type

Number

Description

Allows you to monitor trends in database uptime.

DB_TOTAL_TIME

Type

Number

Description

The time in milliseconds for a database round trip. Compare this field to `CPU_TIME` to determine whether performance issues are occurring in the database layer or in your own code.

ENTITY_NAME

Type

Set

Description

API objects that are accessed.

Example

Account, Opportunity, Contact, and so on.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

METHOD_NAME

Type

String

Description

The name of the calling Apex method.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

REQUEST_SIZE

Type

Number

	Description The size of the callout request body, in bytes.
RESPONSE_SIZE	Type Number Description The size of the callout response, in bytes.
ROWS_PROCESSED	Type Number Description The number of rows that were processed in the request. Example 150
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
QUERY	Type String Description The SOQL query, if one was performed.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
USER_ID	Type Id Description The 15-character ID of the user who's using Salesforce services through the UI or the API. Example 00530000009M9

ASync_REPORT_EVENT

ASync_REPORT_EVENT events are created for reporting requests that are scheduled. This category includes dashboard refreshes, asynchronous reports, schedule reports, and analytics snapshots.

Field	Details
CLIENT_IP	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26
CPU_TIME	Type Number Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
DASHBOARD_ID	Type String Description The 15-character ID of the dashboard that was run.
DB_TOTAL_TIME	Type Number Description The time in milliseconds for a database round trip. Compare this field to CPU_TIME to determine whether performance issues are occurring in the database layer or in your own code.
DB_BLOCKS	Type Number Description Indicates how much activity is occurring in the database. A high value for this field suggests that you should add indexes or filters on your queries.
DB_CPU_TIME	Type Number Description Allows you to monitor trends in database uptime.

DISPLAY_TYPE

Type

String

Description

The report display type, indicating the run mode of the report.

Possible Values

- D: Dashboard
- S: Show Details
- H: Hide Details

ENTITY_NAME

Type

String

Description

The name of the object affected by the trigger.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

NUMBER_BUCKETS

Type

Number

Description

The number of buckets that were used in the report.

NUMBER_COLUMNS

Type

Number

Description

The number of columns in the report.

NUMBER_EXCEPTION_FILTERS

Type

Number

Description

The number of exception filters that are used in the report.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

RENDERING_TYPE

Type

String

Description

The report rendering type, describing the format of the report output.

Possible Values

- W: Web (HTML)
- E: Email
- P: Printable
- X: Excel
- C: Comma-separated values (CSV)
- J: JavaScript Object Notation (JSON)

REPORT_ID

Type

Id

Description

The 15-character ID of the report that was run.

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

REQUEST_STATUS

Type

String

Description

The status of the request for a page view or user interface action.

Possible Values

- S: Success
- F: Failure
- U: Undefined
- A: Authorization Error
- R: Redirect
- N: Not Found

RUN_TIME

Type

Number

	Description The amount of time that the request took in milliseconds.
SORT	Type String Description The sort column and order that was used in the report.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
URI	Type String Description The URI of the page that's receiving the request. Example /home/home.jsp
USER_ID	Type Id Description The 15-character ID of the user who's using Salesforce services through the UI or the API. Example 00530000009M9

BULK_API_EVENT

BULK_API_EVENT events contain details about Bulk API requests.

Field	Details
BATCH_ID	Type String Description The 15-character ID of the Bulk API batch.
CLIENT_IP	Type IP

	Description The IP address of the client that's using Salesforce services.
	Example 96.43.144.26
CPU_TIME	Type Number Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
ENTITY_TYPE	Type String Description The type of entity that the Bulk API used.
EVENT_TYPE	Type String Description The type of event. Example ReportExport, URI, UITracking, API, RestApi, and so on.
JOB_ID	Type String Description The 15-character ID of the Bulk API job.
MESSAGE	Type EscapedString Description Any success or error message that's associated with the request.
NUMBER_FAILURES	Type Number Description The number of failures that were returned with the request.
OPERATION_TYPE	Type String

	Description The type of Bulk API operation that was performed.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D0000000000123
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
ROWS_PROCESSED	Type Number Description The number of rows that were processed in the request. Example 150
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
SUCCESS	Type Boolean Description Whether the batch was successful.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
URI	Type String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

CHANGE_SET_OPERATION_EVENT

CHANGE_SET_OPERATION_EVENT events contain information from change set migrations.

Field**Details**

CHANGE_SET_NAME

Type

String

Description

The name of the change set.

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

EVENT_TYPE

Type

String

Description

The type of event.

	Example ReportExport, URI, UITracking, API, RestApi, and so on.
OPERATION	Type String Description The operation that's being performed. Possible Values • DEPLOY • RETRIEVE • LIST • DESCRIBE
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
TARGET_ORG_ID	Type Id Description The 15-character ID of the organization that's receiving the change set.
TIMESTAMP	Type String Description The access time of Salesforce services.

Example 20130715233322.670	
URI	Type String Description The URI of the page that's receiving the request. Example /home/home.jsp
USER_ID	Type Id Description The 15-character ID of the user who's using Salesforce services through the UI or the API. Example 00530000009M9

CONTENT_DISTRIBUTION_EVENT

CONTENT_DISTRIBUTION_EVENT events contain information about content distributions and deliveries to users.

Field	Details
ACTION	Type String Description The action that's used when a delivery is viewed. Possible Values - VIEW - INSERT - UPDATE
DELIVERY_ID	Type Id Description The 15-character ID of the content delivery.
DELIVERY_LOCATION	Type String Description The location of the delivery.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

RELATED_ENTITY_ID

Type

Id

Description

The 15-character ID of the record that's associated with the delivery distribution.

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDIk0FKf5DV

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

VERSION_ID

Type

Id

Description

The 15-character ID of the content version.

CONTENT_DOCUMENT_LINK_EVENT

CONTENT_DOCUMENT_LINK_EVENT events contain sharing information for content documents.

Field**Details**

DOCUMENT_ID

Type

Id

Description

The 15-character ID of the document that's being shared.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

SHARED_WITH_ENTITY_ID

Type

Id

Description

Who the document was shared with.

SHARING_OPERATION**Type**

String

Description

The type of sharing operation on the document.

Possible Values

- INSERT
- UPDATE
- DELETE

SHARING_PERMISSION**Type**

String

Description

What permissions the document was shared with.

Possible Values

- v: Viewer
- c: Collaborator
- i: Inferred—that is, the sharing permissions were inferred from a relationship between the viewer and document. For example, a document's owner has a sharing permission to the document itself. Or, a document can be a part of a content collection, and the viewer has sharing permissions to the collection rather than explicit permissions to the document directly.

TIMESTAMP**Type**

String

Description

The access time of Salesforce services.

Example

20130715233322.670

USER_ID**Type**

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

CONTENT_TRANSFER_EVENT

CONTENT_TRANSFER_EVENT events contain information about content transfer events, such as downloads, uploads, and previews.

Field	Details
DOCUMENT_ID	Type Id Description The 15-character ID of the document that's being shared.
EVENT_TYPE	Type String Description The type of event. Example ReportExport, URI, UITracking, API, RestApi, and so on.
FILE_PREVIEW_TYPE	Type String Description The content type of the file version.
FILE_TYPE	Type String Description The content type of the file preview.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDIk0FKfF5DV
SIZE_BYTES	Type Number Description The size of the file transfer, in bytes.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

TRANSACTION_TYPE

Type

String

Description

The operation that was performed.

Possible Values

- VersionDownloadAction and VersionDownloadApi represent downloads via the user interface and API respectively.
- VersionRenditionDownload represents a file preview action.
- saveVersion represents a file that's being uploaded.

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

005300000009M9

VERSION_ID

Type

Id

Description

The 15-character ID of the content version.

DASHBOARD_EVENT

DASHBOARD_EVENT events contain details about dashboards that users view.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

	Example 96.43.144.26
CPU_TIME	Type Number Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
DASHBOARD_COMPONENT_ID	Type Id Description The 15-character ID of the dashboard component.
DASHBOARD_ID	Type String Description The 15-character ID of the dashboard that was run.
DASHBOARD_TYPE	Type String Description The type of dashboard. Possible Values • R: Run as running user • C: Run as context user • S: Run as specific user
EVENT_TYPE	Type String Description The type of event. Example ReportExport, URI, UITracking, API, RestApi, and so on.
IS_SCHEDULED	Type Boolean Description The value is <code>true</code> if the dashboard is a scheduled dashboard.

IS_SUCCESS	Type Boolean Description 1 if the dashboard component ran successfully, 0 if it didn't.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
REPORT_ID	Type Id Description The 15-character ID of the report that was run.
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
URI	Type String Description The URI of the page that's receiving the request. Example /home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

DOCUMENT_ATTACHMENT_DOWNLOADS_EVENT

DOCUMENT_ATTACHMENT_DOWNLOADS_EVENT events contain details of document and attachment downloads.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

ENTITY_ID

Type

Id

Description

The 15-character ID of the entity that's associated with the document or attachment.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

FILE_NAME

Type

String

Description

The name of the file or attachment.

FILE_TYPE

Type

String

Description

The type of the file or attachment.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

LOGIN_AS_EVENT

LOGIN_AS_EVENT events contain details about what an administrator did while logged in as another user.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

DELEGATED_USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or API. In this case, the user who's doing the impersonation.

DELEGATED_USER_NAME

Type

String

Description

The username of the user who's using Salesforce services through the UI or API. In this case, the user who's doing the impersonation.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

005300000009M9

LOGIN_EVENT

LOGIN_EVENT events contain details about your organization's user login history.

Field**Details**

API_TYPE

Type

String

Description

The type of API request.

Possible Values

- D: Apex Class
- E: SOAP Enterprise
- I: SOAP Cross Instance
- L: Live Agent
- M: SOAP Metadata
- O: Old SOAP
- P: SOAP Partner
- R: REST API
- S: SOAP Apex
- T: SOAP Tooling
- X: XmlRPC

API_VERSION

Type

String

	Description The version of the API that's being used.
	Example 32.0
BROWSER_TYPE	Type String
	Description The browser used for login.
CPU_TIME	Type Number
	Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
CLIENT_IP	Type IP
	Description The IP address of the client that's using Salesforce services.
	Example 96.43.144.26
DB_TOTAL_TIME	Type Number
	Description The time in milliseconds for a database round trip. Compare this field to <code>CPU_TIME</code> to determine whether performance issues are occurring in the database layer or in your own code.
EVENT_TYPE	Type String
	Description The type of event.
	Example ReportExport, URI, UITracking, API, RestApi, and so on.
ORGANIZATION_ID	Type Id
	Description The 15-character ID of the organization.

	Example 00D000000000123
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
SOURCE_IP	Type IP Description The source IP of the login request.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
URI	Type String Description The URI of the page that's receiving the request. Example /home/home.jsp
USER_ID	Type Id Description The 15-character ID of the user who's using Salesforce services through the UI or the API. Example 00530000009M9

USER_NAME

Type

String

Description

The username that's used for login.

LOGOUT_EVENT

LOGOUT_EVENT events contain details of user log outs.

Field**Details**

API_TYPE

Type

String

Description

The type of API request.

Possible Values

- D: Apex Class
- E: SOAP Enterprise
- I: SOAP Cross Instance
- L: Live Agent
- M: SOAP Metadata
- O: Old SOAP
- P: SOAP Partner
- R: REST API
- S: SOAP Apex
- T: SOAP Tooling
- X: XmlRPC

API_VERSION

Type

String

Description

The version of the API that's being used.

Example

32.0

APP_TYPE

Type

Number

Description

The application type that was in use upon logging out.

BROWSER_TYPE

Type

String

Description

The browser used for login.

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CLIENT_VERSION

Type

Number

Description

The version of the client that was in use upon logging out.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

PLATFORM_TYPE

Type

Number

Description

The code for the client platform. If a timeout caused the logout, this field is null.

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDIk0FKfF5DV

RESOLUTION_TYPE

Type

Number

Description

The screen resolution of the client. If a timeout caused the logout, this field is null.

SESSION_LEVEL

Type

String

Description

The session level that was used when logging out.

SESSION_TYPE

Type

String

Description

The session type that was used when logging out.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

USER_INITIATED_LOGOUT

Type

Boolean

Description

The value is 1 if the user intentionally logged out of the organization by clicking the **Logout** button. If the user's session timed out due to inactivity or another implicit logout action, the value is 0.

USER_NAME

Type

String

Description

The username that's used for login.

USER_TYPE

Type

String

Description

The category of user license of the user that logged out.

Possible Values

- S: Standard
- P: Partner
- p: Customer Portal Manager
- C: Customer Portal User
- O: Power Custom
- o: Custom
- L: Package License Manager
- X: Black Tab User
- N: Salesforce to Salesforce
- G: Guest
- D: External Who
- A: Automated Process
- b: High Volume Portal
- n: CSN Only
- F: Self Service

MDAPI_OPERATION_EVENT

MDAPI_OPERATION_EVENT events contain details of Metadata API retrieval and deployment requests.

Field**Details**

API_VERSION

Type

String

Description

The version of the API that's being used.

Example

32.0

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

EVENT__TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

OPERATION

Type

String

Description

The operation that's being performed.

Possible Values

- DEPLOY
- RETRIEVE
- LIST
- DESCRIBE

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

RUN_TIME

Type

Number

Description

The amount of time that the request took in milliseconds.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

MULTI_BLOCK_REPORT_EVENT

MULTI_BLOCK_REPORT_EVENT events contain details about Joined Report reports.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

DB_TOTAL_TIME

Type

Number

Description

The time in milliseconds for a database round trip. Compare this field to `CPU_TIME` to determine whether performance issues are occurring in the database layer or in your own code.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

HAS_CHART

Type

Boolean

Description

True if the report has a chart.

MASTER_REPORT_ID

Type

String

Description

The 15-character ID of the master report.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDiK0FKfF5DV

REQUEST_STATUS

Type

String

Description

The status of the request for a page view or user interface action.

Possible Values

- S: Success
- F: Failure
- U: Undefined
- A: Authorization Error
- R: Redirect
- N: Not Found

RUN_TIME

Type

Number

Description

The amount of time that the request took in milliseconds.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

PACKAGE_INSTALL_EVENT

PACKAGE_INSTALL_EVENT events contain details about package installation in the organization.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

FAILURE_TYPE

Type

String

Description

A general categorization of any error that's encountered.

IS_MANAGED

Type

Boolean

Description

True if the operation is performed on a managed package.

IS_PUSH

Type

Boolean

Description

True if the package was installed as a result of a push upgrade.

IS_RELEASED

Type

Boolean

Description

True if the operation is performed on a released package.

IS_SUCCESSFUL

Type

Boolean

Description

True if the package was successfully installed.

OPERATION_TYPE

Type

String

Description

The type of package operation.

Possible Values

- INSTALL
- UPGRADE
- EXPORT
- UNINSTALL
- VALIDATE_PACKAGE
- INIT_EXPORT_PKG_CONTROLLER

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

Example

00D000000000123

PACKAGE_NAME

Type

String

Description

The name of the package that's being installed.

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDIk0FKfF5DV

RUN_TIME

Type

Number

Description

The amount of time that the request took in milliseconds.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

QUEUED_EXECUTION_EVENT

QUEUED_EXECUTION_EVENT events contain details about queued executions—for example, batch Apex.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds that it took to complete the batch apex request. This field indicates the amount of activity taking place in the app server layer, allowing you to identify pieces of Apex or Visualforce code that need refactoring.

Field	Details
DB_TOTAL_TIME	Type Number Description The time in milliseconds for a database round trip. Compare this field to <code>CPU_TIME</code> to determine whether performance issues are occurring in the database layer or in your own code.
ENTRY_POINT	Type String Description The name of the Apex class that serves as the execution point for the batch job. Example TaskPhoneExtensionBatchUpdate
EVENT_TYPE	Type String Description The type of event. Example ReportExport, URI, UITracking, API, RestApi, and so on.
JOB_ID	Type String Description The ID of the batch Apex job. Example 7073000000IDquo
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDIk0FKfF5DV

Field	Details
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
URI	Type String Description The URI of the page that's receiving the request. Example /home/home.jsp
USER_ID	Type Id Description The 15-character ID of the user who's using Salesforce services through the UI or the API. Example 00530000009M9

REPORT_EVENT

REPORT_EVENT events contain information about what happened when a user ran a report.

Field	Details
CLIENT_IP	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

DB_BLOCKS

Type

Number

Description

Indicates how much activity is occurring in the database. A high value for this field suggests that you should add indexes or filters on your queries.

DB_CPU_TIME

Type

Number

Description

Allows you to monitor trends in database uptime.

DB_TOTAL_TIME

Type

Number

Description

The time in milliseconds for a database round trip. Compare this field to `CPU_TIME` to determine whether performance issues are occurring in the database layer or in your own code.

DISPLAY_TYPE

Type

String

Description

The report display type, indicating the run mode of the report.

Possible Values

- D: Dashboard
- S: Show Details
- H: Hide Details

ENTITY_NAME

Type

String

Description

The name of the object affected by the trigger.

EVENT_TYPE

Type

String

	Description The type of event.
	Example ReportExport, URI, UITracking, API, RestApi, and so on.
NUMBER_BUCKETS	Type Number
	Description The number of buckets that were used in the report.
NUMBER_COLUMNS	Type Number
	Description The number of columns in the report.
NUMBER_EXCEPTION_FILTERS	Type Number
	Description The number of exception filters that are used in the report.
ORGANIZATION_ID	Type Id
	Description The 15-character ID of the organization.
	Example 00D000000000123
RENDERING_TYPE	Type String
	Description The report rendering type, describing the format of the report output.
	Possible Values • w: Web (HTML) • E: Email • P: Printable • X: Excel • C: Comma-separated values (CSV) • J: JavaScript Object Notation (JSON)
REPORT_ID	Type Id

	Description The 15-character ID of the report that was run.
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
REQUEST_STATUS	Type String Description The status of the request for a page view or user interface action. Possible Values • S: Success • F: Failure • U: Undefined • A: Authorization Error • R: Redirect • N: Not Found
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
SORT	Type String Description The sort column and order that was used in the report.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
URI	Type String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

REPORT_EXPORT_EVENT

REPORT_EXPORT_EVENT events contain details about reports that a user exported.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CLIENT_INFO

Type

String

Description

Information about the client that's using Salesforce services.

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

EVENT_TYPE

Type

String

Description

The type of event.

	Example ReportExport, URI, UITracking, API, RestApi, and so on.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
REPORT_DESCRIPTION	Type String Description Information about the report that was run.
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
URI	Type String Description The URI of the page that's receiving the request. Example /home/home.jsp
USER_ID	Type Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

REST_API_EVENT

REST_API_EVENT events contain details about REST-specific requests.

Field	Details
CLIENT_IP	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26
CPU_TIME	Type Number Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
DB_BLOCKS	Type Number Description Indicates how much activity is occurring in the database. A high value for this field suggests that you should add indexes or filters on your queries.
DB_CPU_TIME	Type Number Description Allows you to monitor trends in database uptime.
DB_TOTAL_TIME	Type Number

	Description The time in milliseconds for a database round trip. Compare this field to <code>CPU_TIME</code> to determine whether performance issues are occurring in the database layer or in your own code.
EVENT_TYPE	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26
MEDIA_TYPE	Type String Description The media type of the response.
METHOD	Type String Description The HTTP method of the request—GET, POST, PUT, and so on.
NUMBER_FIELDS	Type Number Description The number of fields or columns, where applicable.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D0000000000123
REQUEST_STATUS	Type String Description The status of the request for a page view or user interface action. Possible Values • S: Success • F: Failure • U: Undefined

- A: Authorization Error
- R: Redirect
- N: Not Found

REQUEST_ID

Type

String

Description

The unique ID of a single transaction.

Example

3nWgxWbDKWWDik0FKfF5DV

ROWS_PROCESSED

Type

Number

Description

The number of rows that were processed in the request.

Example

150

RUN_TIME

Type

Number

Description

The amount of time that the request took in milliseconds.

STATUS_CODE

Type

Number

Description

The HTTP status code for the response.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_AGENT

Type

EscapedString

Description

The browser that was used to make the request.

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

SANDBOX_EVENT

SANDBOX_EVENT events contain details about sandbox copies.

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CURRENT_SANDBOX_ORG_ID

Type

Id

Description

The 15-character ID of the current sandbox organization.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

ORGANIZATION_ID

Type

Id

Description

The 15-character ID of the organization.

	Example 00D000000000123
PENDING_SANDBOX_ORG_ID	Type Id Description The 15-character ID of the target sandbox org.
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
SANDBOX_ID	Type Id Description The 15-character ID of the sandbox organization.
STATUS	Type String Description The status of the sandbox copy.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670
USER_ID	Type Id Description The 15-character ID of the user who's using Salesforce services through the UI or the API. Example 00530000009M9

SITES_EVENT

SITES_EVENT events contain details of Site.com requests. Requests can originate from the browser (UI) or the API.

Field	Details
CLIENT_IP	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26
CPU_TIME	Type Number Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
DB_TOTAL_TIME	Type Number Description The time in milliseconds for a database round trip. Compare this field to <code>CPU_TIME</code> to determine whether performance issues are occurring in the database layer or in your own code.
EVENT_TYPE	Type String Description The type of event. Example ReportExport, URI, UITracking, API, RestApi, and so on.
HTTP_HEADERS	Type String Description The HTTP headers that were sent in the request.
METHOD	Type String Description The HTTP method of the request—GET, POST, PUT, and so on.
IS_API	Type Boolean

	Description True if this page was an API or Web Services request.
IS_ERROR	Type Boolean Description True if this page was an error page.
IS_FIRST_REQUEST	Type Boolean Description 1 if this page is the first Visualforce transaction in the request, or 0 if it isn't.
IS_GUEST	Type Boolean Description True if this page was a guest (unauthenticated) request.
IS_SECURE	Type Boolean Description True if this request is secure.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
PAGE_NAME	Type String Description The name of the Visualforce page that was requested.
QUERY	Type String Description The SOQL query, if one was performed.
REQUEST_ID	Type String

	Description The unique ID of a single transaction.
	Example 3nWgxWbDKWWDiK0FKfF5DV
REQUEST_STATUS	Type String Description The status of the request for a page view or user interface action. Possible Values • S: Success • F: Failure • U: Undefined • A: Authorization Error • R: Redirect • N: Not Found
REQUEST_TYPE	Type String Description The request type. Possible Values • page: a normal request for a page • content_UI: a content request for a page that originated in the user interface • content_apex: a content request that was initiated by an Apex call • PDF_UI: a request for a page in PDF format through the user interface • PDF_apex: a request for PDF format by an Apex call (usually a Web Service call)
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
SITE_ID	Type Id Description The 15-character ID of the Site.com site.

TIMESTAMP

Type

String

Description

The access time of Salesforce services.

Example

20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example

/home/home.jsp

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

TIME_BASED_WORKFLOW

TIME_BASED_WORKFLOW events contain details about queue activity monitoring.

Field**Details**

DATA

Type

String

Description

The record details of time queue activity.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

LOG_GROUP_ID

Type

String

	Description Marks log records that are committed or rolled back.
NUMBER_OF_RECORDS	Type Number
	Description The number of processed records.
ORGANIZATION_ID	Type Id
	Description The 15-character ID of the organization.
	Example 00D000000000123
REQUEST_ID	Type String
	Description The unique ID of a single transaction.
	Example 3nWgxWbDKWWDiK0FKfF5DV
TIMESTAMP	Type String
	Description The access time of Salesforce services.
	Example 20130715233322.670
TYPE	Type String
	Description The type of Apex callout.
	Example REST or AJAX

UI_TRACKING_EVENT

UI_TRACKING_EVENT events contain details about UI events.

Field	Details

ACTION	Type EscapedString Description The hierarchical user action.
APP_NAME	Type EscapedString Description The name of the application that the user accessed.
BROWSER_NAME	Type String Description The name of the browser that's accessed by the user.
BROWSER_VERSION	Type String Description The browser version that's accessed by the user.
CARRIER	Type String Description The name of the cellular service provider.
CLIENT	Type EscapedString Description The context of access. Example Phone, tablet, desktop, and so on.
CLIENT_ID	Type String Description The API client ID.
CLIENT_IP	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26

CONNECTION_TYPE

Type

String

Description

The type of the connection.

Possible Values

- WIFI
- CDMA1x
- CDMA
- EDGE
- EVDO0
- EVDOA
- EVDOB
- GPRS
- HSDPA
- HSUPA
- HRPD
- LTE

DEVICE_ID

Type

String

Description

The unique device identifier.

EVENT_TYPE

Type

String

Description

The type of event.

Example

ReportExport, URI, UITracking, API, RestApi, and so on.

LOCATION

Type

EscapedString

Description

The hierarchical location.

NETWORK_ID

Type

Id

	Description The network ID of the request.
NUMBER1	Type Number Description The record of a numeric value based on the operation. For example, the number of results returned by a search.
NUMBER2	Type Number Description The record of a numeric value based on operation, but for multiple values. Example NUMBER1 items selected in a list containing NUMBER2 items.
OBJECT_TYPE	Type String Description The API name of the record in the action.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
OS_NAME	Type String Description The operating system name.
OS_VERSION	Type String Description The operating system version.
RECORD_ID	Type Id Description The record ID of the operated request.

REFERRER

Type

EscapedString

Description

The HTTP referrer header.

REQUEST_METHOD

Type

String

Description

The HTTP request method.

SDK_APP_NAME

Type

String

Description

The name of the mobile SDK application that's installed on the device.

Example

Salesforce1

SDK_APP_TYPE

Type

String

Description

The mobile SDK application type.

Example

Native, hybrid, and so on.

SDK_APP_VERSION

Type

String

Description

The mobile SDK application version.

Example

5.0

SDK_MODEL

Type

String

Description

The model of the mobile SDK application that's installed on the device.

Example

Salesforce1

SDK_VERSION

Type

String

	Description The mobile SDK version.
	Example 2.1.0
SESSION_ID	Type String
	Description The user's unique session ID.
SIGNAL_STRENGTH	Type Number
	Description The cellular signal strength.
STATUS	Type Boolean
	Description Indicates whether an error was logged. Information is logged in data.
TARGET	Type EscapedString
	Description The request target.
TARGET2	Type EscapedString
	Description Additional information for the request target.
TIMESTAMP	Type String
	Description The access time of Salesforce services.
	Example 20130715233322.670
USAGE_TIMESTAMP	Type String
	Description The time when the usage occurred. Format: YYYYMMDDHHMMSS.sss.

USER_AGENT

Type

EscapedString

Description

The browser that was used to make the request.

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example

00530000009M9

URI_EVENT

URI_EVENT events contain details about your organization's Salesforce UI activity (user interface clicks).

Field**Details**

CLIENT_IP

Type

IP

Description

The IP address of the client that's using Salesforce services.

Example

96.43.144.26

CPU_TIME

Type

Number

Description

The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.

DB_BLOCKS

Type

Number

Description

Indicates how much activity is occurring in the database. A high value for this field suggests that you should add indexes or filters on your queries.

DB_CPU_TIME

Type

Number

	Description Allows you to monitor trends in database uptime.
DB_TOTAL_TIME	Type Number Description The time in milliseconds for a database round trip. Compare this field to CPU_TIME to determine whether performance issues are occurring in the database layer or in your own code.
EVENT_TYPE	Type IP Description The IP address of the client that's using Salesforce services. Example 96.43.144.26
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
REFERRER_URI	Type String Description The referring URI of the page that's receiving the request.
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
TIMESTAMP	Type String

	Description The access time of Salesforce services.
	Example 20130715233322.670
URI	Type String
	Description The URI of the page that's receiving the request.
	Example /home/home.jsp
USER_ID	Type Id
	Description The 15-character ID of the user who's using Salesforce services through the UI or the API.
	Example 00530000009M9

VISUALFORCE__REQUEST__EVENT

VISUALFORCE__REQUEST__EVENT events contain details of Visualforce requests. Requests can originate from the browser (UI) or the API.

Field	Details
CLIENT_IP	Type IP
	Description The IP address of the client that's using Salesforce services.
	Example 96.43.144.26
CONTROLLER_TYPE	Type Number
	Description The type of controller that's used by the requested Visualforce page.
CPU_TIME	Type Number

	Description The CPU time in milliseconds used to complete the request. This field indicates the amount of activity taking place in the app server layer, highlighting pieces of Apex or Visualforce code that need refactoring.
DB_BLOCKS	Type Number Description Indicates how much activity is occurring in the database. A high value for this field suggests that you should add indexes or filters on your queries.
DB_CPU_TIME	Type Number Description Allows you to monitor trends in database uptime.
DB_TOTAL_TIME	Type Number Description The time in milliseconds for a database round trip. Compare this field to <code>CPU_TIME</code> to determine whether performance issues are occurring in the database layer or in your own code.
EVENT_TYPE	Type String Description The type of event. Example ReportExport, URI, UITracking, API, RestApi, and so on.
HTTP_METHOD	Type String Description The HTTP method of the request—GET, POST, PUT, and so on.
IS AJAX_REQUEST	Type Boolean Description The value is <code>true</code> if the request is a partial page request.
IS_FIRST_REQUEST	Type Boolean

	Description 1 if this page is the first Visualforce transaction in the request, or 0 if it isn't.
MANAGED_PACKAGE_NAMESPACE	Type String Description If the page is part of a managed package, the namespace of that package.
ORGANIZATION_ID	Type Id Description The 15-character ID of the organization. Example 00D000000000123
PAGE_NAME	Type String Description The name of the Visualforce page that was requested.
QUERY	Type String Description The SOQL query, if one was performed.
REQUEST_ID	Type String Description The unique ID of a single transaction. Example 3nWgxWbDKWWDik0FKfF5DV
REQUEST_SIZE	Type Number Description The size of the request body, in bytes.
REQUEST_STATUS	Type String

	Description The status of the request for a page view or user interface action.
	Possible Values • S: Success • F: Failure • U: Undefined • A: Authorization Error • R: Redirect • N: Not Found
REQUEST_TYPE	Type String Description The request type. Possible Values • page: a normal request for a page • content_UI: a content request for a page that originated in the user interface • content_apex: a content request that was initiated by an Apex call • PDF_UI: a request for a page in PDF format through the user interface • PDF_apex: a request for PDF format by an Apex call (usually a Web Service call)
RESPONSE_SIZE	Type Number Description The size of the response, in bytes.
RUN_TIME	Type Number Description The amount of time that the request took in milliseconds.
TIMESTAMP	Type String Description The access time of Salesforce services. Example 20130715233322.670

URI

Type

String

Description

The URI of the page that's receiving the request.

Example`/home/home.jsp`

USER_AGENT

Type

EscapedString

Description

The browser that was used to make the request.

USER_ID

Type

Id

Description

The 15-character ID of the user who's using Salesforce services through the UI or the API.

Example`005300000009M9`

VIEW_STATE_SIZE

Type

Number

Description

The size of the Visualforce view state, in bytes.

EventRelation

Represents people (a user, a lead, or contacts) or a resource (such as a conference room) invited to an event. This object lets you add or remove invitees from an event and use the API to manage invitees' responses to invitations. If Shared Activities is enabled, this object doesn't support triggers, workflow, or data validation rules.

EventRelation allows a variable number of relationships and handles deleted events differently, depending on whether Shared Activities is enabled.

If Shared Activities Is Enabled

- An event can be related to up to 50 contacts or one lead.
- If you delete an event, then relations between the event and any specified contacts, leads, and records are also deleted. The `WhoId`, `WhatId`, and `AccountId` field values are cleared. If you restore a deleted event, relations between the event and any specified contacts, leads, and records are also restored. The `WhoId`, `WhatId`, and `AccountId` field values are recalculated using the field values on EventRelation.

If Shared Activities Isn't Enabled

- An event can be related to only one contact or lead.
- If you delete an event, the `WhoId`, `WhatId`, and `AccountId` field values aren't cleared.

Whether or not Shared Activities is enabled, an event can be related to one other kind of record, such as an account, an opportunity, or a custom object (in addition to one or more contacts).

 Note:

- With API versions 26.0 and later, the EventRelation object replaces the EventAttendee object, and the EventAttendee object is no longer visible. You can still query the EventAttendee object using packages that support API versions 25.0 and earlier, or by using Apex.
- An EventRelation object can't be created for a child event.
- EventRelation includes deactivated users.
- In API versions 25.0 and earlier, you can't use `query()`, `delete()`, or `update()` with events related to more than one contact.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `queryAll()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description Contains the Account ID of the relation. For information on IDs, see ID Field Type. <code>AccountId</code> is visible when Shared Activities is enabled.
EventId	Type reference Properties Create, Filter, Group, Sort Description Contains the ID of the event. This value can't be changed after it's been specified.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is <code>Deleted</code>.

Field	Details
IsInvitee	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the relation is an invitee. - IsInvitee is visible while Shared Activities is being enabled, after it has been enabled, and while it is being disabled. - IsInvitee defaults to <code>true</code> while Shared Activities is being enabled, after it has been enabled, and while it is being disabled if IsInvitee, IsParent, and IsWhat are not set. This configuration ensures compatibility when Shared Activities isn't enabled and EventRelation represents event invitees only. - IsInvitee defaults to <code>false</code> when Shared Activities is enabled if IsParent is set to <code>true</code>.
IsParent	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the relation is a contact or lead, or an account, opportunity, or other object. IsParent is visible when Shared Activities is enabled.
IsWhat	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Indicates whether the relation is an account, an opportunity, or another object. Value is <code>false</code> if RelationId is a contact or a lead, and <code>true</code> otherwise. IsWhat is visible when Shared Activities is enabled.
RelationId	Type reference Properties Create, Filter, Group, Sort Description Contains the ID of the person (User, Contact, or Lead) or the resource invited to an event. When Shared Activities is enabled, RelationId can also contain the ID of the contacts or lead related to an event. This value can't be changed after it's been specified.

Field	Details
RespondedDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Indicates the most recent date and time when the invitee responded to an invitation to an event.
Response	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Contains optional text that the invitee can enter when responding to an invitation to an event.
Status	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates the invitee status with one of the following values: • New: Invitee has received the invitation but hasn't yet responded. This value is the default. • Declined: Invitee has declined the invitation. • Accepted: Invitee has accepted the invitation.  Note: Uninvited and Maybe aren't currently supported.

Usage

Send email notifications

To send email notifications for a given event, query EventRelation for the event, iterate through the list, examine the status, and send email notifications to every person who accepted the invitation.

Determine what events a given invitee is attending

To determine all the events that a particular person is attending during a given time period (for example, next week), you can have a client application query the Event object for a given date range, iterate through the results, and, for each event, query the EventRelation object to determine whether the particular person (RelationId) has accepted an invitation to that event.

Create an invitee if Shared Activities is enabled (or during the process of enabling it or rolling back)

If the invitee is already a contact or lead, update IsInvitee to true.

If the invitee is not already a contact or lead, create an EventRelation object for the invitee with IsInvitee set to true.

Create an invitee if Shared Activities is not enabled

Create an EventRelation object for the invitee.

Query relations to a contact or a lead

```
List<EventRelation> whoRelations = [SELECT Id, Relation.Name FROM
    EventRelation WHERE EventId = '00UD0000005zijiD' AND isParent = true AND isWhat =
    false];
```

Query invitee relations

```
List<EventRelation> inviteeRelations = [SELECT Id, Relation.Name FROM
    EventRelation WHERE EventId = '00UD0000005zijiD' AND isInvitee = true];
```

Update an invitee relation to a contact or lead invitee relation

```
EventRelation er = [SELECT Id FROM EventRelation WHERE EventId =
    '00UD0000005zijiD' AND isInvitee = true and isParent = false LIMIT 1];
er.isParent = true;
update er;
```

Update a contact or lead relation to a contact or lead invitee relation

```
EventRelation er = [SELECT Id FROM EventRelation WHERE EventId =
    '00UD0000005zijiD' AND isParent = true and isInvitee = false LIMIT 1];
er.isInvitee = true;
update er;
```

Insert a contact or lead relation

```
EventRelation er = new EventRelation(EventId = '00UD0000005zijiH',
    RelationId = '003D000000Q8aeV', isParent = true, isInvitee = false);
insert er;
```

Insert an invitee relation

If isParent, isWhat and isInvitee are not set, and RelationId is a contact, lead, user, or calendar, isInvitee defaults to true. This means if an EventRelation isn't specifically inserted as a relation to a contact or lead, it's treated as an Invitee relation by default.

```
EventRelation er = new EventRelation(EventId = '00UD0000005zijiH',
    RelationId = '003D000000Q8adV');
insert er;
```

EventTag

Associates a word or short phrase with an Event.

Supported Calls

create(), delete(), describeSObjects(), query(), retrieve()

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • Public—The tag can be viewed and manipulated by all users in an organization. • Personal—The tag can be viewed or manipulated only by a user with a matching OwnerId.

Usage

EventTag stores the relationship between its parent TagDefinition and the Event being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

EventWhoRelation

Represents the relationship between an event and a lead or contacts. This derived object is a filtered version of the [EventRelation](#) on page 679 object; that is, `IsParent` is `true` and `IsWhat` is `false`. It doesn't represent relationships to invitees or to accounts, opportunities, or other objects.

EventWhoRelation allows a variable number of relationships: one lead or up to 50 contacts. Available only if you've enabled Shared Activities for your organization. This object is available in API versions 29.0 and later.



Note: EventWhoRelation objects aren't created for child events.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
EventId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the event.
RelationId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the contacts or lead related to the event.
Type	Type string Properties Filter, Group, Nillable, Sort Description Indicates whether the person related to the event is a contact or lead.

Usage

Apex example that queries relations to a contact or lead

```
List<EventWhoRelation> whoRelations = [SELECT Id, Relation.Name FROM
EventWhoRelation WHERE EventId = '00UD0000005z1jD'];
```

ExternalDataSource

Represents an external data source, such as SharePoint®.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ApiKey	Type string Properties Filter, Group, Nillable, Sort Description The organization-specific client key required by some external data systems.
DeveloperName	Type string Properties Filter, Group, Sort Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Endpoint	Type textarea

Field Name	Details
	Properties Nillable Description The root endpoint URL of the external data source.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language of the <code>MasterLabel</code>.
MasterLabel	Type string Properties Filter, Group, Sort Description Master label for the external data source. This display value is the internal label that does not get translated.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation.
PrincipalType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Used to track users accessing the external server. Anonymous implies a user identity is not specified for external server access. Named Principal uses one user identity for all users to access the external server.
Repository	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description An optional name of the repository in the data source. Not applicable to all data source types.
Type	Type picklist Properties Filter, Group, Restricted picklist, Sort Description File type of the source document.

Usage

External data sources connect with data sources outside Salesforce, such as SharePoint®. Selected tables in an external data source map to external objects, which function much like custom objects in Salesforce.

ExternalDataUserAuth

Stores authentication settings for a specific user to access an external system. The external system can be an external data source or a callout endpoint that's defined in a named credential. The external data source or named credential must be configured to use per-user authentication.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
ExternalDataSourceId	Type reference Properties Create, Filter, Group, Sort Description The name that's specified in the external data source or named credential definition.
UserId	Type reference

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Nillable, Sort, Update Description The user's first and last name in Salesforce.
Protocol	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The authentication protocol that's required by the external system. For SharePoint, specify Basic Authentication.
Username	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The username that's required by the external system.
Password	Type encrypted string Properties Create, Nillable, Update Description The password that's required by the external system.

Usage

These authentication settings enable the user to access an external system that restricts access on a per-user basis. The external system is defined in Salesforce as one of the following.

- External data source—Provides access to external objects, whose data is stored outside the Salesforce organization.
- Named credential—Enables the user's actions to trigger authenticated Apex callouts to the endpoint that's specified in the named credential.

If you grant users access to the external data source or named credential via permission sets or profiles, those users can manage their own authentication settings for external systems. See "Store Authentication Settings for External Systems" in the Salesforce Help.

FeedComment

Represents a comment added to a feed by a user. Represents a comment added to a feed by a user.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

Note the following when working with feed comments:

- You must have read access to the feed's parent type to see a FeedComment record.
- You can add a comment if you have access to the feed.
- If the comment is related to a user record, the user can delete the comment. For example, if John Smith makes a comment about Sasha Jones, Sasha can delete the comment.
- If the logged-in user has the "Insert System Field Values for Chatter Feeds" user permission, the `create` field property is available on `CreatedBy` and `CreatedDate` system fields for this object. This allows the logged-in user to set these fields to the original post author and creation date upon migration instead of accepting the system field value when migrated, which would be the logged-in user and the date the migration was performed, respectively. The fields can't be updated after migration.

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the object associated with the feed as well as delete permission on the parent feed
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

- "Manage Unlisted Groups"
Only users with this permission can delete items in unlisted groups.

Fields

Field	Details
CommentBody	Type textarea Properties Create, Filter, Sort, Update Description The text in the comment.
CommentType	Type reference Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description The type of comment: • ContentComment—an uploaded file on a comment

Field	Details
	• <code>TextComment</code>—a direct text entry on a comment Prior to API version 24.0, a text entry was required on a comment. As of version 24.0, a text entry is optional if the <code>CommentType</code> is <code>ContentComment</code>.
<code>FeedItemId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the feed containing the comment.
<code>InsertedById</code>	Type reference Properties Filter, Group, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
<code>LastEditById</code>	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the user who last edited the feed comment.
<code>LastEditDate</code>	Type datetime Properties Create, Filter, Nillable, Sort Description The date the feed comment was last edited.
<code>ParentId</code>	Type reference Properties Filter, Group, Nillable, Sort Description ID of a record associated with the feed comment. For example, if you are commenting on a change to a field on Account, <code>ParentId</code> is set to the account ID.

Field	Details
RelatedRecordId	Type reference Properties Create, Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentComment. This field is null for all comments except ContentComment. For example, set this field to an existing ContentVersion and post it to a comment as a FeedComment object of CommentTypeContentComment.
Revision	Type int Properties Create, Filter, Group, Nillable, Sort Description The number of times the comment was revised.

Usage

- As of API version 23.0 and beyond, if you have “View All Data” permission you can query [FeedComment](#) records directly, without an ID filter. However, if you don’t have “View All Data” permission, you can’t query [FeedComment](#) records directly, with or without an ID filter.

For example, the following query returns general information about a feed:

```
SELECT ID, CreatedDate, CreatedById, CreatedBy.FirstName,
       CreatedBy.LastName, ParentId, Parent.Name, Body
FROM FeedItem
WHERE CreatedDate > LAST_MONTH
ORDER BY CreatedDate DESC, Id DESC
```

- You can search for text in comments using SOSL. For example, the following Java class uses `search()` to find the string “foo” in any field of a record:

```
public void searchSample() {
    try {
        SearchResult sr = connection.search("find {foo} in all fields " +
            "returning feedcomment(Id, FeedItemId, CommentBody)");
        // Put the results into an array of SearchRecords
        SearchRecord[] records = sr.getSearchRecords();
        // Check the length of the returned array of records to see
        // if the search found anything
        if (records != null && records.length > 0) {
            System.out.println("Found " + records.length + " comments: ");
            // Display each comment
            for (SearchRecord record : records) {
                FeedComment comment = (FeedComment) record.getRecord();
            }
        }
    } catch (Exception e) {
        // Handle exception
    }
}
```

```

        System.out.println(comment.getId() + ": " +
            comment.getCommentBody());
    }
} else {
    System.out.println("No records were found for the search.");
}
} catch (ConnectionException ce) {
    ce.printStackTrace();
}
}
}

```

- If you use an Apex trigger to modify the `Body` of a `FeedComment` object, all mentions hyperlinks are converted to plain text and the mentioned users don't get email notifications.

 **Note:** This object is hard deleted. It isn't sent to the Recycle Bin.

FeedItem

`FeedItem` represents an entry in the feed, such as changes in a record feed, including text posts, link posts, and content posts.

This object is available in API version 21.0 and later. This object replaces `FeedPost`.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"

 **Note:** Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

- "Manage Unlisted Groups"

Only users with this permission can delete items in unlisted groups.

Only users with the "Modify All Data" permission can delete a `FeedItem` of `Type TrackedChange`.

If the logged-in user has the "Insert System Field Values for Chatter Feeds" user permission, the `create` field property is available on `CreatedBy` and `CreatedDate` system fields for this object. This allows the logged-in user to set these fields to the original post author and creation date upon migration instead of accepting the system field value when migrated, which would be the logged-in user and the date the migration was performed, respectively. The fields can't be updated after migration.

Fields

Field Name	Details
BestCommentId	Type reference Properties Filter, Group, Nillable, Sort Description The Id of the comment marked as best answer on a question post.
Body	Type textarea Properties Create, Nillable, Sort, Update on page 16 Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a <code>PartnerNetworkConnection</code> changes a tracked record, the <code>CreatedBy</code> field contains the ID of the system administrator. The <code>ConnectionId</code> contains the ID of the <code>PartnerNetworkConnection</code> that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Create, Nillable

Field Name	Details
	Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code> .
<code>ContentDescription</code>	Type <code>textarea</code> Properties <code>Create, Nillable, Sort</code> Description The description of the file specified in <code>ContentData</code> .
<code>ContentFileName</code>	Type <code>string</code> Properties <code>Create, Group, Nillable, Sort</code> Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code> .
<code>ContentSize</code>	Type <code>int</code> Properties <code>Group, Nillable, Sort</code> Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
<code>ContentType</code>	Type <code>string</code> Properties <code>Group, Nillable, Sort</code> Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
<code>FeedPostId</code>	Type <code>reference</code> Properties <code>Filter, Group, Nillable, Sort</code>

Field Name	Details
	Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
<code>HasContent</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the feed item has content.
<code>HasLink</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the feed item has a link attached.
<code>InsertedById</code>	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
<code>LastEditById</code>	Type reference Properties Create, Filter, Group, Nillable, Sort

Field Name	Details
	Description ID of the user who last edited the feed item.
LastEditDate	Type datetime Properties Create , Filter , Nillable , Sort Description The date the feed item was last edited.
LikeCount	Type int Properties Filter , Group , Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Create , Nillable , Sort Description The URL of a <code>LinkPost</code> .
NetworkScope	Type picklist Properties Create , Filter , Group , Nillable , Sort Description Specifies whether this feed item is available in the default community , a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: • <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. • <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code> : • Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. • For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>.

Field Name	Details
	You can't filter a FeedItem on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the object type to which the FeedItem object is related. For example, set this field to a <code>UserId</code> to post to someone's profile feed, or an <code>AccountId</code> to post to a specific account.
RelatedRecordId	Type reference Properties Create, Group, Nillable, Sort Description ID of the ContentVersion object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of Type <code>ContentPost</code>.
Revision	Type int Properties Create, Filter, Group, Nillable, Sort Description The revision number of the feed item.
Title	Type string Properties Create, Group, Nillable, Sort Description The title of the FeedItem. When the Type is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name. The <code>Title</code> field can be updated on posts of Type <code>QuestionPost</code>.
Type	Type picklist Properties Create, Filter, Group, Nillable, Sort

Field Name

Details

Description

The type of FeedItem. Except for `ContentPost`, `LinkPost`, and `TextPost`, don't create FeedItem types directly from the API.

- `ActivityEvent`—indirectly generated event when a user or the API adds a `Task` associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a `Task` or `Event` associated with a case record (excluding email and call logging).

For a recurring `Task` with `CaseFeed` disabled, one event is generated for the series only. For a recurring `Task` with `CaseFeed` enabled, events are generated for the series and each occurrence.

- `AdvancedTextPost`—created when a user posts a group announcement.
- `AnnouncementPost`—Not used.
- `ApprovalPost`—generated when a user submits an approval.
- `BasicTemplateFeedItem`—Not used.
- `CanvasPost`—a post made by a canvas app posts on a feed.
- `CollaborationGroupCreated`—generated when a user creates a public group.
- `CollaborationGroupUnarchived`—Not used.
- `ContentPost`—a post with an attached file.
- `CreatedRecordEvent`—generated when a user creates a record from the publisher.
- `DashboardComponentAlert`—generated when a dashboard metric or gauge exceeds a user-defined threshold.
- `DashboardComponentSnapshot`—created when a user posts a dashboard snapshot on a feed.
- `LinkPost`—a post with an attached URL.
- `PollPost`—a poll posted on a feed.
- `ProfileSkillPost`—generated when a skill is added to a user's Chatter profile.
- `QuestionPost`—generated when a user posts a question.
- `ReplyPost`—generated when Chatter Answers posts a reply.
- `RypplePost`—generated when a user creates a Thanks badge in Work.com.
- `TextPost`—a direct text entry on a feed.
- `TrackedChange`—a change or group of changes to a tracked field.
- `UserStatus`—automatically generated when a user adds a post. Deprecated.

The following values appear in the `Type` picklist for all feed objects but apply only to `CaseFeed`:

Field Name	Details
	<code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. <code>SocialPost</code>—generated when a social post is created from a case.  Note: If you set <code>Type</code> to <code>ContentPost</code>, also specify <code>ContentData</code> and <code>ContentFileName</code>.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: - For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. - External users can set <code>Visibility</code> only to <code>AllUsers</code>. - On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>. <code>Visibility</code> can be updated on record posts.

Usage

- If you are using API version 23.0 or later and have “View All Data” permission, you can directly query for a FeedItem. The following example returns the 20 most recent feed items.

```
SELECT ID, CreatedDate, CreatedById, CreatedBy.FirstName, CreatedBy.LastName, ParentId,
       Parent.Name, Body,
       (SELECT ID, FieldName, OldValue, NewValue, FROM FeedTrackedChanges ORDER BY ID DESC)
FROM FeedItem
WHERE CreatedDate > LAST_MONTH
ORDER BY CreatedDate DESC, Id DESC LIMIT 20;
```

- If you are using an earlier API version than version 23.0, query FeedItem objects through a feed (such as [AccountFeed](#) or [OpportunityFeed](#)). The following example returns all feed items for a given account, ordered by date descending:

```
SELECT Id, Type, FeedItem.Body
FROM AccountFeed
WHERE ParentId = AccountId ORDER BY CreatedDate DESC
```



Note: Prior to API version 23.0 provide the `ParentId`.

- A FeedItem of type `UserStatus` is automatically created when a user adds a post to update the current status. You can't explicitly create a FeedItem of type `UserStatus`.
- The FeedItem object doesn't support aggregate functions in queries.
- If the logged-in user has the “Insert System Field Values for Chatter Feeds” user permission, the `create` field property is available on `CreatedBy` and `CreatedDate` system fields for this object. This allows the logged-in user to set these fields to the original post author and creation date upon migration instead of accepting the system field value when migrated, which would be the logged-in user and the date the migration was performed, respectively. The fields can't be updated after migration.
- The size limit for an attachment on a profile or news feed is 25 MB.
- The size limit for an attachment on a record feed is 5 MB.
- You can't use the content fields to update or delete the content.
- You can't filter or update the content fields.
- Deleting a FeedItem via the API also deletes the associated content. Likewise, undeleting a FeedItem restores associated content.



Note: This object is hard deleted. It isn't sent to the Recycle Bin.

- After uploading to a feed, it is possible for an attachment or document to be deleted, marked private, or hidden by sharing rules. In this case, all content fields in a FeedItem object appear as `null` in a SOQL query.
- You can't explicitly create or delete a [FeedTrackedChange](#) record.
- If you insert a FeedItem or [FeedComment](#) of Type `ContentPost` on a [User](#) or [Group](#) to create a new file, the `NetworkScope` field value of the FeedItem is passed to the file.
- If you use an Apex trigger to modify the `Body` of a FeedItem object, all mentions hyperlinks are converted to plain text and the mentioned users don't get email notifications.

FeedLike

Indicates that a user has liked a feed item. FeedLike records represent likes on posts and not likes on comments. Likes on comments can't be queried via the API. A FeedLike is a child object of an associated FeedItem, FeedTrackedChange, or object feed, such as AccountFeed. This object is available in API version 21.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`

Special Access Rules

If the logged-in user has the "Insert System Field Values for Chatter Feeds" user permission, the `create` field property is available on `CreatedBy` and `CreatedDate` system fields for this object. This allows the logged-in user to set these fields to the original post author and creation date upon migration instead of accepting the system field value when migrated, which would be the logged-in user and the date the migration was performed, respectively. The fields can't be updated after migration.

Fields

Field Name	Details
FeedItemId	Type reference Properties Create, Filter, Group, Sort Description ID of the feed item that the user liked.
FeedEntityId	Type reference Properties Create, Filter, Group, Sort Description The Id of a feed item or feed comment the user liked. If the user liked a comment, FeedEntityId is set to the ID of the comment. If the user liked a feed item, FeedEntityId is set to the ID of the feed item. FeedEntityId is an optional field. The default value is the ID of the feed item.
InsertedById	Type reference Properties Filter, Group, Sort

Field Name	Details
	Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.

Usage

You can't query FeedLike records directly. They can only be queried via the entity feed, such as AccountFeed.

FeedLike records represent likes on posts and not likes on comments. Likes on comments can't be queried via the API.

FeedPollChoice

Shows the choices for a poll posted in the feed. This object is available in API version 29.0 and later.

Supported Calls

`query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

- "Manage Unlisted Groups"
Only users with this permission can delete items in unlisted groups.

Fields

Field Name	Details
ChoiceBody	Type string Properties Group Description A choice in the poll.

Field Name	Details
FeedItemId	Type reference Properties Create, Filter, Group, Sort Description ID of the feed item for the poll.
Position	Type int Properties Group, Sort Description Shows the position of the poll choice.

Usage

Use this object to query all of the choices associated with a particular poll. To view how people voted on the poll, see the FeedPollVote object.

FeedPollVote

Shows how users voted on a poll posted in the feed. This object is available in API version 29.0 and later.

Supported Calls

`query()`, `retrieve()`

Fields

Field Name	Details
ChoiceId	Type reference Properties Filter, Group Description Indicates which choice a user selected on a poll posted in a feed.
FeedItemId	Type reference

Field Name	Details
	Properties Filter, Group, Sort
	Description ID of the feed item for the poll.

Usage

Use this object to query how users voted on a particular poll.

FeedPost

FeedPost represents the following types of changes in a record feed, such as AccountFeed: text posts, link posts, and content posts. This object is available in API version 18.0 through 21.0. FeedPost is no longer available in later versions. Starting with API version 21.0, use FeedItem to represent text posts, link posts, and content posts in feeds.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `search()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Only users with the "Modify All Data" permission can delete a FeedItem of Type `TrackedChange`.

If the logged-in user has the "Insert System Field Values for Chatter Feeds" user permission, the `create` field property is available on `CreatedBy` and `CreatedDate` system fields for this object. This allows the logged-in user to set these fields to the original post author and creation date upon migration instead of accepting the system field value when migrated, which would be the logged-in user and the date the migration was performed, respectively. The fields can't be updated after migration.

Fields

Field	Details
Body	Type string
	Properties Create, Filter, Nillable, Sort

Field	Details
	Description The content of the FeedPost. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
<code>ContentData</code>	Type base64 Properties Create, Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
<code>ContentDescription</code>	Type string Properties Create, Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
<code>ContentFileName</code>	Type string Properties Create, Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
<code>ContentSize</code>	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
<code>ContentType</code>	Type string Properties Group, Nillable, Sort

Field	Details
	Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
FeedItemId	Type reference Properties Filter, Group, Sort Description ID of the feed containing the FeedPost.
InsertedById	Type reference Properties Filter, Group, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LinkUrl	Type url Properties Create, Filter, Nillable, Sort Description The URL of a <code>LinkPost</code> .
ParentId	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description ID of the object type to which the FeedPost is related. For example, set this field to a <code>UserId</code> to post to someone's profile feed, or an <code>AccountId</code> to post to a specific account.
Title	Type string Properties Create, Filter, Group, Nillable, Sort Description The title of the FeedPost. When the <code>Type</code> is <code>LinkPost</code>, the <code>Body</code> is the URL and the <code>Title</code> is the label for the link.
Type	Type picklist Properties Create, Defaulted on create, Filter, Group, Restricted picklist, Sort Description The type of FeedPost: • <code>UserStatus</code>—automatically generated when a user updates their status • <code>TrackedChange</code>—ignore • <code>TextPost</code>—a direct text entry on a feed • <code>LinkPost</code>—a URL posting on a feed • <code>ContentPost</code>—an uploaded file on a feed  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Usage

- You can't directly query for a FeedPost. FeedPosts are always associated with a feed item, so you can query for them through the feeds. The following example returns all feed items for a given account, ordered by date descending:

```
SELECT Id, Type, FeedPost.Body
FROM AccountFeed
WHERE ParentId = AccountId ORDER BY CreatedDate DESC
```

- A FeedPost of type `UserStatus` is automatically created when a user adds a post to update the current status. You can't explicitly create a FeedPost of type `UserStatus`.
- The size limit for an attachment on a profile, news, or record feed is 2 GB.
- You can't use the content fields to update or delete the content.
- You can't filter or update the content fields.

- Deleting a FeedPost via the API also deletes the associated content and FeedPost objects. Likewise, undeleting a FeedPost restores associated content and FeedPost objects.
-  **Note:** This object is hard deleted. It isn't sent to the Recycle Bin.
- After uploading to a feed, it is possible for an attachment or document to be deleted, marked private, or hidden by sharing rules. In this case, all content fields in FeedPost appear as `null` in a SOQL query.
- You can't explicitly create or delete a FeedTrackedChange record.

FeedRevision

Holds the revision history of a specific feed item or comment, including a list of attributes that changed for each revision.

This object is available in API version 34.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
Action	Type picklist Properties Filter, Group, Nillable, Sort Description Holds the type of modification to the underlying feed item or comment attribute. Action can have the value Changed.
EditedAttribute	Type picklist Properties Filter, Group, Nillable, Sort Description Identifies the part of the feed item or comment which was modified. A single revision can have many edited attributes.
FeedEntityId	Type reference Properties Filter, Group, Sort Description Identifies the modified feed item or comment.

Field Name	Details
<code>IsDeleted</code>	Type <code>boolean</code> Properties <code>Defaulted on create</code>, <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This field is a standard system field.
<code>OriginNetworkId</code>	Type <code>reference</code> Properties <code>Filter</code>, <code>Group</code>, <code>Nullable</code>, <code>Sort</code> Description The ID of the community in which a user modified the feed item or comment. This field is only available, if Salesforce Communities is enabled for your organization.
<code>Revision</code>	Type <code>int</code> Properties <code>Filter</code>, <code>Group</code>, <code>Nullable</code>, <code>Sort</code> Description The revision number of the feed item or comment.
<code>Value</code>	Type <code>textarea</code> Properties <code>Nullable</code> Description Identifies the value of the <code>EditedAttribute</code> field before the update.

Usage

This object tracks the changes made to a feed item or feed comment and stores a list of attributes that changed for each revision.

- To query the `FeedRevision` object, users either need the “View All Data” permission or supply a `WHERE` clause on the `FeedEntityId`.

FeedTrackedChange

Represents an individual field change or set of field changes. A `FeedTrackedChange` is a child object of a record feed, such as `AccountFeed`. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
CurrencyIsoCode	Type picklist Properties Group, Restricted picklist, Sort Description Available only for organizations with the multicurrency feature enabled. Contains the ISO currency code for the field, if <code>FieldName</code> is a currency field.
FeedItemId	Type reference Properties Group, Sort, Filter Description ID of the parent feed that tracks the field change.
FieldName	Type string Properties Group, Sort Description The name of the field that was changed.  Note: This field also tracks other events that are not related to an individual field for a parent feed. These events occur as the parent record advances through its pipeline. For example, a value of <code>LeadConverted</code> indicates that a lead has been converted to an opportunity. For a full list of values, see Tracking of Special Events.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldCurrencyIsoCode	Type string

Field	Details
	Properties Group, Nillable, Sort
	Description Available only for organizations with the multicurrency feature enabled. Contains the ISO currency code for the <code>OldValue</code> field, if <code>FieldName</code> is a currency field.
OldValue	Type anyType
	Properties Nillable, Sort
	Description The last value of the field before it was changed.

Usage

A user can subscribe to a record or to another user. Changes to the record and updates from the users are displayed in the Chatter feed on the user's home page, which is a useful way to stay up-to-date with other users and with changes made to records in Salesforce. Feeds are available in API version 18.0 and later.

If you move a custom field to the Recycle Bin, all `FeedTrackedChange` records that track historical changes to the custom field are automatically deleted and are not restored if the custom-field is undeleted.

The following sections outline the difference between standard feeds and custom feeds.

Standard Feeds

A standard feed is a record feed, such as `AccountFeed`. `FeedTrackedChange` records for standard feeds can only be queried via the parent feed object.

Note the following when working with standard feed items:

- Feed items for standard feeds are read only in the API.
- A `FeedTrackedChange` record is visible when you have read access on the record feed, and when the field in the `FeedTrackedChange` is visible in the field-level security settings.

Custom Feeds

If you want more control over the information provided in a record feed, such as `AccountFeed`, you can create a custom feed. A custom feed can replace or augment an existing record feed. For example, you might want to:

- Disable the standard account record feed and use an Apex trigger to generate `FeedTrackedChange` records for the events that you want to track in the feed instead.
- Augment the standard contact record feed by writing an API client that inserts feed items for events that are not tracked in the standard feed.

Tracking of Special Events

The `FieldName` field also tracks other events that are not related to an individual field for a parent feed. These events occur as the parent record advances through its pipeline. For example, a value of `leadConverted` indicates that a lead has been converted to an opportunity.

Valid values for the `FieldName` field for multiple objects:

- `created`
- `ownerAccepted`
- `ownerAssignment`

Additional valid values for the `FieldName` field for individual objects:

Account

- `accountCreatedFromLead`
- `accountMerged`
- `accountUpdatedByLead`
- `personAccountUpdatedByLead`

Case

- `closed`
- `ownerEscalated`

Contact

- `contactCreatedFromLead`
- `contactMerged`
- `contactUpdatedByLead`

Contract

- `contractActivation`
- `contractApproval`
- `contractConversion`
- `contractExpiration`
- `contractTermination`

Lead

- `leadConverted`
- `leadMerged`

Opportunity

- `opportunityCreatedFromLead`

FieldHistoryArchive

Represents field history values for all objects that retain field history. This object is available only to users with the “Retain Field History” permission. This object is available in API version 29.0 and later. Each instance of the `FieldHistoryArchive` object represents a single change in the value of a field. The `FieldHistoryArchive` can store history for both standard and custom fields. The `Field`

field returns the name of the field unless the parent field or object is deleted, in which case it returns the ID and you can retrieve the old field and object name from the `FieldNameAfterArchival` and `ParentNameAfterArchival` fields, respectively.

Supported Calls

`describeSObjects(), query()`

Fields

Field Name	Details
ArchiveFieldName	Type string Properties Nillable Description The name of the field at the time the data was archived. This may not be the same for all records related to a single field, if the field name changed.
ArchiveParentName	Type string Properties Nillable Description The name of the parent object at the time the data was archived. This may not be the same for all records related to a single field, if the object name changed.
ArchiveParentType	Type string Properties Nillable Description The type of the field at the time the data was archived. This may not be the same for all records related to a single field, if the field type changed.
ArchiveTimestamp	Type dateTime Properties Nillable Description The date and time at which the data was archived.
CreatedById	Type dateTime

Field Name	Details
	Properties Nillable Description The user ID of the user who created the archive.
CreatedDate	Type dateTime Properties Nillable Description The date and time at which the archive was created.
Field	Type picklist Properties Filter, Nillable, Restricted picklist Description The name of the field that was changed. If the field is deleted from the parent object, the <code>Field</code> field contains the ID instead.
FieldHistoryType	Type picklist Properties Nillable, Restricted picklist Description The name of the object that contains the field history (for example, Account).
Id	Type ID Properties Defaulted on create, Filter, idLookup Description The ID of the archived record. It's useful to have a field's ID for fields that you may have deleted. (Field names aren't retained in history when you delete fields from Salesforce.)
NewValue	Type anyType Properties Nillable Description The new value of the modified field.

Field Name	Details
OldValue	Type anyType Properties Nillable Description The previous value of the modified field.
ParentId	Type reference Properties Filter, Nillable Description The ID of the object that contains the field (the parent object).

FieldPermissions

Represents the enabled field permissions for the parent PermissionSet. To grant a user access to a field, associate a FieldPermissions record with a PermissionSet that's assigned to a user. FieldPermissions records are only supported in PermissionSet, not in Profile. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
Field	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The field's API name. This name must be prefixed with the <code>ObjectType</code> . For example, <code>Merchandise__c.Description__c</code>
ParentId	Type reference Properties Create, Filter, Group, Sort

Field Name	Details
	Description The <code>Id</code> of the field's parent PermissionSet .
PermissionsEdit	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code> , users assigned to the parent PermissionSet can edit this field. Requires <code>PermissionsRead</code> for the same field to be <code>true</code> .
PermissionsRead	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code> , users assigned to the parent PermissionSet can view this field. A FieldPermissions record must have at minimum <code>PermissionsRead</code> set to <code>true</code> , or it will be deleted.
ObjectType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The object's API name. For example, <code>Merchandise__c</code> .

Usage

[FieldPermissions](#) work similarly to [ObjectPermissions](#). However, [FieldPermissions](#) includes a `Field` attribute to return the name of the field.

For example, the following query returns all [FieldPermissions](#) records that have at least the "Read" permission. The results includes the field, object, and permission set names.

```
SELECT ObjectType, Field, PermissionsRead, Parent.Name
FROM FieldPermissions
WHERE PermissionsRead = True
```

Include the field's parent object when querying [FieldPermissions](#). For example, to find all rows that match the `Account` object's `Type` field, create the following query:

```
SELECT Id, ObjectType, Field
FROM FieldPermissions
WHERE Field = 'Account.Type' AND ObjectType = 'Account'
```

Both `SubjectType` and `Field` must be included in the `SELECT` line of the query. You must also provide the full API name of the field in the form of `SubjectType.Field` when querying for a field.

Special Properties for Field Permissions

The auto-number and formula fields have special rules for how field permissions work. Both have `FieldPermissions` records, but inserting and updating is limited to `PermissionsRead`. `PermissionsEdit` isn't allowed for either field type, since these fields must be read-only for users.

The following field types don't return a `FieldPermissions` record because they are assumed to always be readable.

- `Id`
- `CreatedById`
- `CreatedDate`
- `IsDeleted`
- `LastModifiedById`
- `LastModifiedDate`
- `SystemModStamp`

The following field types don't return a `FieldPermissions` record because they are assumed to always be readable and writable.

- `OwnerId`
- Master-detail custom (relationship) fields
- Universally required custom fields

As a result, the following query returns no records, even though users do have some access to some of the fields.

```
SELECT Field, SubjectType, PermissionsRead
FROM FieldPermissions
WHERE Field='Id'
```

To determine if a field can return a `FieldPermissions` record, you can call a `describeSObject()` on the field. For example, `describeSObject('Merchandise__c')`, returns all the properties of the `Merchandise` custom object, including field properties. If you're using a field whose `permissionable` property is `false` (such as any of the field types listed in this section), you can't query, insert, update, or delete any field permissions records, because none exist.

Working with Custom Activity Fields

While tasks and events are considered separate objects, they share a common set of activity custom fields. As a result, when a custom task field is created, a custom event field is also created, and vice versa. You can display the custom field on the event layout, task layout, or both event and task layouts.

Although custom activity fields are shared between tasks and events, you'll see separate `FieldPermissions` records for the task and event. However, changes made to one field permission record are automatically made to the other. For example, if you create a custom activity field, assign field permissions to it in a permission set, and run the following query, the query will return two records with the same permission value.

```
SELECT Field, Id, ParentId, PermissionsEdit, PermissionsRead, SubjectType
FROM FieldPermissions
WHERE SubjectType = 'event' OR SubjectType = 'task'
```

If you then update one of the records with a different set of field permission values and run the query again, the same permission values for both records are returned.

Nesting Field Permissions

You can nest FieldPermissions in a PermissionSet query. For example, the following returns any permission sets where “Edit Read Only Fields” is `true`. Additionally, the result set will include both the “Read” and “Edit” field permission on the Merchandise object. This is done by nesting the SOQL with a field permission query using the relationship name for field permissions: `FieldPerms`.

```
SELECT PermissionsEditReadonlyFields,
  (SELECT SubjectType, Field, PermissionsRead, PermissionsEdit
   FROM FieldPerms
  WHERE SubjectType = 'Merchandise__c')
 FROM PermissionSet
 WHERE PermissionsEditReadonlyFields = true
```

As a result, it's possible to traverse the relationship between the PermissionSet and any child related objects (in this case, FieldPermissions). You can do this from the PermissionSet object by using the child relationship (`ObjectPerms`, `FieldPerms`, and so on) or from the child object by referencing the PermissionSet with `Parent.permission_set_attribute`.

It's important to consider when to use a conditional `WHERE` statement to restrict the result set. To query based on an attribute on the permission set object, nest the SOQL with the child relationship. However, to query based on an attribute on the child object, you must reference the permission set parent attribute in your query.

The following two queries return the same columns with different results, based on whether you use the child relationship or parent notation.

```
SELECT PermissionsEditReadonlyFields,
  (SELECT SubjectType, Field, PermissionsRead, PermissionsEdit
   FROM FieldPerms
  WHERE SubjectType = 'Merchandise__c')
 FROM PermissionSet
 WHERE PermissionsEditReadonlyFields = true
```

versus:

```
SELECT SubjectType, Field, PermissionsRead, PermissionsEdit, Parent.Name,
  Parent.PermissionsEditReadonlyFields
 FROM FieldPermissions
 WHERE SObjectType='Merchandise__c'
```

FiscalYearSettings

Settings to define a custom or standard fiscal year for your organization. This object has a parent-child relationship with the Period object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
Description	Type string Properties Filter, Group, Nillable, Sort Description Description of the setting.
EndDate	Type date Properties Filter, Group, Nillable, Sort Description End date of the fiscal year.
IsStandardYear	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the fiscal year is a standard calendar year (<code>true</code>) or a custom fiscal year (<code>false</code>).
Name	Type string Properties Filter, Group, Sort Description A name for the fiscal year. Limit: 80 characters.
PeriodId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the associated fiscal period.
PeriodLabelScheme	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort

Field	Details
	Description The numbering scheme used for fiscal periods.
PeriodPrefix	Type picklist Properties Filter, Group, Nillable, Sort Description The prefix of fiscal periods. For example, if <i>p</i> is the prefix, then the first period is "P1."
QuarterLabelScheme	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The numbering scheme used for fiscal quarters.
QuarterPrefix	Type picklist Properties Filter, Group, Nillable, Sort Description The prefix of fiscal quarters. For example, if "Q" is the prefix, then the fourth quarter would be "Q4."
StartDate	Type date Properties Filter, Group, Nillable, Sort Description Start date of the fiscal year.
WeekLabelScheme	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The numbering scheme used for weeks.
WeekStartDay	Type int

Field	Details
	Properties Filter, Group, Nillable, Sort Description The name of the day that starts the week, for example <code>Monday</code> or <code>Sunday</code>
<code>YearType</code>	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Indicates one of two types of fiscal years, Standard or Custom. Standard denotes the standard Gregorian calendar, while Custom means a fiscal year with a custom structure.

FlowInterview

Represents a flow interview. A *flow interview* is a running instance of a flow.

Supported Calls

`delete()`, `describeLayout()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `describeSObject()`

Special Access Rules

To delete a flow interview, you must have the “Manage Force.com Flow” user permission. All other calls require the “Run Flows” user permission or the `Force.com Flow User` field enabled on the user detail page.

Fields

Field Name	Details
<code>CurrentElement</code>	Type string Properties Filter, Group, Nillable, Sort Description The flow element at which the interview is currently paused or waiting.
<code>InterviewLabel</code>	Type string Properties Filter, Nillable, Sort

Field Name	Details
	Description Label for the interview. This label helps users and administrators differentiate interviews from the same flow. In the user interface, this label appears in the Paused Flow Interviews component on the user's Home tab and in the Paused and Waiting Interviews list on the flow management page.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The name for the interview.
PauseLabel	Type string Properties Filter, Nillable, Sort Description Information about why the interview was paused. This string is entered by the user who paused the flow interview. Label is Why Paused

Folder

Represents a repository for a Document, EmailTemplate, Report, or Dashboard. Only one type of item can be contained in a folder.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- You must have the “Modify All Data” permission to create, update, or delete document folders, email template folders, or report folders.
- To query this object, no special permissions are needed.
- Customer Portal users can't access this object.

Fields

Field	Details
AccessType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. Indicates who can access the Folder. Available values include: • Hidden—Folder is hidden from everyone. • Public—Folder is accessible by all users. • Shared—Folder is accessible only by a User in a particular Group or UserRole. The API doesn't allow you to view, insert, or update which group or Role the Folder is shared with.
DeveloperName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is Folder Unique Name.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
IsReadOnly	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this Folder is read-only (<code>true</code>) or editable (<code>false</code>). Label is <i>Read Only</i>.
Name	Type string Properties Create, Filter, Group, Sort, Update

Field	Details
	Description Label of the folder as it appears in the user interface. Label is Document Folder Label.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, NamespacePrefix is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Required. Type of objects contained in the Folder. This field can't be updated. Available values include: • Dashboard • Document • Email template • Report

Usage

Only one type of item can be contained in a folder, either Document, EmailTemplate, Report, or Dashboard.

ForecastingAdjustment

This object represents an individual sales manager's adjustment for a subordinate's forecast via a ForecastingItem. Available in API versions 26 and greater. This object is separate from the ForecastingOwnerAdjustment object, which represents forecast users' adjustments of their *own* forecasts.

 **Note:** This information only applies to Collaborative Forecasts.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`,
`retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AdjustedAmount	Type double Properties Create, Filter, Sort, Update Description The revenue amount of an individual forecast item, after an adjustment.
AdjustedQuantity	Type double Properties Create, Filter, Sort, Update Description The quantity amount of an individual forecast item, after an adjustment. This field is available in API version 28 and later.
AdjustmentNote	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description A text note providing information about the adjustment. The maximum length is 140 characters. This field does not appear in reports.
CurrencyIsoCode	Type picklist

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Restricted picklist, Sort, Update Description The currency code of the adjustment. If omitted, the default is the importing user's personal currency.
ForecastCategoryName	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description The category within the sales cycle that an opportunity is assigned to based on its opportunity stage. The standard forecast categories are Pipeline, Best Case, Commit, Omitted, and Closed. You can customize forecast category names. The forecast categories display information for that specific category; for example, Best Case only reflects amounts in the Best Case category.
ForecastingItemCategory	Type picklist Properties Create, Filter, Group, Sort Description This field indicates which type of forecast rollup the manager adjustment belongs to. Depending on whether your organization uses individual forecast category rollups or cumulative forecast rollups, you have these possible values for the <code>ForecastingItemCategory</code> field. Individual forecast category rollups: • PipelineOnly - Rollup from Pipeline opportunities only. • BestCaseOnly - Rollup from Best Case opportunities only. Adjustable. • CommitOnly - Rollup from Commit opportunities only. Adjustable. Cumulative forecast rollups: • OpenPipeline - Rollup from Pipeline + Best Case + Commit opportunities. • BestCaseForecast - Rollup from Best Case + Commit + Closed opportunities. Adjustable. • CommitForecast - Rollup from Commit + Closed opportunities. Adjustable. Either cumulative or individual forecast category rollups: • ClosedOnly - Rollup from Closed opportunities only. The <code>ForecastingItemCategory</code> field differs from the <code>ForecastCategoryName</code> field.

Field Name	Details
	- The <code>ForecastCategoryName</code> field represents the forecast category of the <i>underlying opportunities</i> rolling up to forecast amounts. In organizations using cumulative forecast rollups, the <code>ForecastCategoryName</code> field can be null because the cumulative forecast amounts include opportunities from multiple forecast categories. - The new <code>ForecastingItemCategory</code> field represents the <i>type of rollup</i> a forecast amount or adjustment is from. In organizations using individual forecast category columns, it contains the individual forecast rollup categories. In organizations using cumulative forecast rollups, it contains the cumulative rollup categories. When inserting manager adjustments, the values you insert for <code>ForecastCategoryName</code> and <code>ForecastingItemCategory</code> must be compatible with each other. In organizations using cumulative forecast rollups, the <code>ForecastCategoryName</code> is nillable. These are the valid pairs. Individual forecast category rollups: <code>ForecastCategoryName: BestCase,</code> <code>ForecastingItemCategory: BestCaseOnly</code> <code>ForecastCategoryName: Commit,</code> <code>ForecastingItemCategory: CommitOnly</code> Cumulative forecast category rollups: <code>ForecastCategoryName: null, ForecastingItemCategory: BestCaseForecast</code> <code>ForecastCategoryName: null, ForecastingItemCategory: CommitForecast</code>
<code>ForecastingTypeId</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of the related <code>ForecastingType</code>.
<code>ForecastingItemId</code>	Type reference Properties Filter, Group, Sort Description The ID of the related <code>ForecastingItem</code>.
<code>IsAmount</code>	Type boolean

Field Name	Details
	Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a revenue amount. If false, then <code>IsQuantity</code> must be true. This field is available in API version 28 and later.
IsQuantity	Type boolean Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a quantity amount. If false, then <code>IsAmount</code> must be true. This field is available in API version 28 and later.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort Description The ID of the forecast owner.
PeriodId	Type reference Properties Filter, Group, Nillable, Sort Description Period ID for the adjustment. Read only.
ProductFamily	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The Product Family for the adjustment. Read only. This field is available in API version 29 and later.
StartDate	Type date Properties Create, Filter, Group, Sort

Field Name	Details
	Description The start of the adjustment, expressed as month and year. The date can include any day in a given month. Stored using the first date of the month.

Usage

Use this object to obtain a manager's adjustment detail for a specified `ForecastingItem`. The `ForecastingAdjustment` object itself is visible to all users, but only forecast managers and users above them in the forecast hierarchy can read or write `ForecastingAdjustment` records.

 **Note:** Beginning with API version 30.0, organizations can have more than one forecasting type enabled. The `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingOwnerAdjustment`, `ForecastingItem`, and `ForecastingFact` objects can all have records with different `ForecastingTypeId` values. Use the `ForecastingType` object to determine the ID for each forecast type and then filter `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingItem`, or `ForecastingFact` records as necessary.

ForecastingFact

This is a read-only object linking a `ForecastingItem` with its opportunities, such as opportunities that share the same owner or forecast category and have a closing date within the period of the forecasting item. Available in API versions 26 and greater.

 **Note:** This information only applies to Collaborative Forecasts.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>ForecastCategoryName</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A forecast category is the category within the sales cycle that an opportunity is assigned to based on its opportunity stage. The standard forecast categories are Pipeline, Best Case, Commit, Omitted, and Closed. You can customize forecast category names for your organization.
<code>ForecastedObjectId</code>	Type reference

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description Contains the Split ID of the forecasted OpportunitySplit object if the forecast data source is opportunity splits or the OpportunityLineItem ID of the forecasted opportunity if the data source is product families. If the data source is product families and the opportunity has no line item, this field is Null. If the forecast data source is opportunities, this field is Null. This field is available in API version 29 and later. Read only.
ForecastingItemId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the ForecastingItem.
ForecastingTypeId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the related ForecastingType.
OpportunityId	Type reference Properties Filter, Group, Sort Description The opportunity ID.
OwnerId	Type reference Properties Filter, Group, Sort Description The ID of the opportunity owner.
PeriodId	Type reference

Field Name	Details
	Properties Filter, Group, Nillable, Sort
	Description Period ID for the forecast.

Usage

Use this object to get information about opportunities linked to forecasting items.



Note: Beginning with API version 30.0, organizations can have more than one forecasting type enabled. The `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingOwnerAdjustment`, `ForecastingItem`, and `ForecastingFact` objects can all have records with different `ForecastingTypeId` values. Use the `ForecastingType` object to determine the ID for each forecast type and then filter `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingItem`, or `ForecastingFact` records as necessary.

s

ForecastingItem

This is a read-only object used for individual forecast amounts. Users see amounts based on their perspectives and forecast roles. The amounts users see include one of the following when forecasting in revenue: `AmountWithoutAdjustments`, `AmountWithoutManagerAdjustment`, `ForecastAmount`, `OwnerOnlyAmount`. The amounts users see include one of the following when forecasting in quantity: `QuantityWithoutAdjustments`, `QuantityWithoutManagerAdjustments`, `ForecastQuantity`, `OwnerOnlyQuantity`. Additionally, note that users:

- with the “View All Forecasts” permission have access to all `ForecastingItem` fields.
- without the “View All Forecasts” permission have access to all fields for their own subordinates.

Other users can see the `ForecastingItem` object, but not its records. Available in API versions 26 and greater.



Note: This information only applies to Collaborative Forecasts.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>AmountWithoutAdjustments</code>	Type double
	Properties Filter, Sort, Nillable

Field Name	Details
	Description The sum of all of a person's owned revenue opportunities and also his or her subordinates' opportunities, without adjustments. Subordinates include everyone reporting up to a person in the forecast hierarchy.
AmountWithoutManagerAdjustment	Type double Properties Filter, Sort, Nillable Description The forecast number as seen by the forecast owner. This is the sum of the owner's revenue opportunities and his or her subordinates' opportunities, including adjustments made by the forecast owner on her or her own or subordinates' forecasts. <i>It doesn't include adjustments made by forecast managers above the owner in the forecast hierarchy.</i>
ForecastAmount	Type double Properties Filter, Sort, Nillable Description The revenue forecast from the forecast manager's perspective and the sum of the owner's and subordinates' opportunities, including all forecast adjustments.
ForecastCategoryName	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description A forecast category is the category within the sales cycle that an opportunity is assigned to based on its opportunity stage. The standard forecast categories are Pipeline, Best Case, Commit, Omitted, and Closed. You can customize forecast category names for your organization.
ForecastQuantity	Type double Properties Filter, Sort, Nillable

Field Name	Details
	Description The quantity forecast from the forecast manager's perspective and the sum of the owner's and subordinates' opportunities, including all forecast adjustments. This field is available in API version 28 and later.
ForecastingItemCategory	Type picklist Properties Filter, Group, Sort Description This field indicates which type of forecast rollup the forecasting item belongs to. Depending on whether your organization uses individual forecast category rollups or cumulative forecast rollups, you have these possible values for the <code>ForecastingItemCategory</code> field. Individual forecast category rollups: • PipelineOnly - Rollup from Pipeline opportunities only. • BestCaseOnly - Rollup from Best Case opportunities only. Adjustable. • CommitOnly - Rollup from Commit opportunities only. Adjustable. Cumulative forecast rollups: • OpenPipeline - Rollup from Pipeline + Best Case + Commit opportunities. • BestCaseForecast - Rollup from Best Case + Commit + Closed opportunities. Adjustable. • CommitForecast - Rollup from Commit + Closed opportunities. Adjustable. Either cumulative or individual forecast category rollups: • ClosedOnly - Rollup from Closed opportunities only. The <code>ForecastingItemCategory</code> field differs from the <code>ForecastCategoryName</code> field. • The <code>ForecastCategoryName</code> field represents the forecast category of the <i>underlying opportunities</i> rolling up to forecast amounts. In organizations using cumulative forecast rollups, the <code>ForecastCategoryName</code> field can be null because the cumulative forecast amounts include opportunities from multiple forecast categories. • The new <code>ForecastingItemCategory</code> field represents the <i>type of rollup</i> a forecast amount or adjustment is from. In organizations using individual forecast category columns, it contains the individual forecast rollup categories. In organizations using cumulative forecast rollups, it contains the cumulative rollup categories.
ForecastingTypeId	Type reference

Field Name	Details
	Properties Filter, Group, Sort Description The ID of the related ForecastingType.
HasAdjustment	Type boolean Properties Defaulted on create, Filter, Group, Sort Description A flag that indicates if the forecasting item includes a <i>manager</i> adjustment. This flag is true only when the item includes an adjustment and the user performing the query has read access to the adjustment.
HasOwnerAdjustment	Type boolean Properties Defaulted on create, Filter, Group, Sort Description A flag that indicates if the forecasting item includes an <i>owner</i> adjustment. This flag is true only when the item includes an adjustment and the user performing the query has read access to the adjustment. Available in API versions 33 and greater.
IsAmount	Type boolean Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a revenue amount. If false, then <code>IsQuantity</code> must be true. This field is available in API version 28 and later.
IsQuantity	Type boolean Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a quantity amount. If false, then <code>IsAmount</code> must be true. This field is available in API version 28 and later.

Field Name	Details
IsUpToDate	Type boolean Properties Defaulted on create, Filter, Group, Sort Description A flag indicating whether or not a specific forecasting item reflects current information. For example, if users are making adjustments which are in process, the item won't be up-to-date.
OwnerId	Type reference Properties Filter, Group, Sort Description The ID of the forecast owner.
OwnerOnlyAmount	Type double Properties Filter, Sort, Nillable Description The sum of all of a person's revenue opportunities, without adjustments.
OwnerOnlyQuantity	Type double Properties Filter, Sort, Nillable Description The sum of all of a person's quantity opportunities, without adjustments. This field is available in API version 28 and later.
ParentForecastingItemId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the ForecastingItem that the current item rolls up to.
PeriodId	Type reference

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description Period ID for the forecast.
ProductFamily	Type picklist Properties Filter, Group, Nillable, Sort Description The product family of the forecast item. This field is available in API version 29 and later. Read only.
QuantityWithoutAdjustments	Type double Properties Filter, Sort, Nillable Description The sum of a person's owned quantity opportunities and also his or her subordinates' opportunities, without adjustments. Subordinates include everyone reporting up to a person in the forecast hierarchy. This field is available in API version 28 and later.
QuantityWithoutManagerAdjustments	Type double Properties Filter, Sort, Nillable Description The forecast number as seen by the forecast owner. This is the sum of the owner's quantity opportunities and his or her subordinates' opportunities, including adjustments made on the subordinates' forecasts. <i>It doesn't include adjustments made by forecast managers above the owner in the forecast hierarchy.</i> This field is available in API version 28 and later.

Usage

Use this object to obtain individual forecast amounts, either with or without adjustments, based on a user's perspective and forecast role. The ForecastingItem object is visible to all users, but only forecast managers and users above them in the forecast hierarchy can read or write ForecastingAdjustment records.



Note: Beginning with API version 30.0, organizations can have more than one forecasting type enabled. The ForecastingQuota, ForecastingAdjustment, ForecastingOwnerAdjustment, ForecastingItem,

and `ForecastingFact` objects can all have records with different `ForecastingTypeId` values. Use the `ForecastingType` object to determine the ID for each forecast type and then filter `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingItem`, or `ForecastingFact` records as necessary.

ForecastingOwnerAdjustment

This object represents an individual forecast user's adjustment of their *own* forecast via a `ForecastingItem`. Available in API versions 33 and greater. This object is separate from the `ForecastingAdjustment` object, which represents managers' adjustments of *subordinates'* forecasts.

 **Note:** This information only applies to Collaborative Forecasts.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The currency code of the adjustment. If omitted, the default is the importing user's personal currency.
ForecastCategoryName	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description The category within the sales cycle that an opportunity is assigned to based on its opportunity stage. The standard forecast categories are Pipeline, Best Case, Commit, Omitted, and Closed. You can customize forecast category names. The forecast categories display information for that specific category; for example, Best Case only reflects amounts in the Best Case category.
ForecastingItemCategory	Type picklist Properties Create, Filter, Group, Sort

Field Name

Details

Description

This field indicates which type of forecast rollup the owner adjustment belongs to. Depending on whether your organization uses individual forecast category rollups or cumulative forecast rollups, you have these possible values for the `ForecastingItemCategory` field.

Individual forecast category rollups:

- `PipelineOnly` - Rollup from Pipeline opportunities only.
- `BestCaseOnly` - Rollup from Best Case opportunities only. Adjustable.
- `CommitOnly` - Rollup from Commit opportunities only. Adjustable.

Cumulative forecast rollups:

- `OpenPipeline` - Rollup from Pipeline + Best Case + Commit opportunities.
- `BestCaseForecast` - Rollup from Best Case + Commit + Closed opportunities. Adjustable.
- `CommitForecast` - Rollup from Commit + Closed opportunities. Adjustable.

Either cumulative or individual forecast category rollups:

- `ClosedOnly` - Rollup from Closed opportunities only.

The `ForecastingItemCategory` field differs from the `ForecastCategoryName` field.

- The `ForecastCategoryName` field represents the forecast category of the *underlying opportunities* rolling up to forecast amounts. In organizations using cumulative forecast rollups, the `ForecastCategoryName` field can be null because the cumulative forecast amounts include opportunities from multiple forecast categories.
- The new `ForecastingItemCategory` field represents the *type of rollup* a forecast amount or adjustment is from. In organizations using individual forecast category columns, it contains the individual forecast rollup categories. In organizations using cumulative forecast rollups, it contains the cumulative rollup categories.

When inserting owner adjustments, the values you insert for `ForecastCategoryName` and `ForecastingItemCategory` must be compatible with each other. In organizations using cumulative forecast rollups, the `ForecastCategoryName` is nillable. These are the valid pairs.

Individual forecast category rollups:

- `ForecastCategoryName: BestCase`,
`ForecastingItemCategory: BestCaseOnly`
- `ForecastCategoryName: Commit`,
`ForecastingItemCategory: CommitOnly`

Cumulative forecast category rollups:

- `ForecastCategoryName: null`, `ForecastingItemCategory: BestCaseForecast`

Field Name	Details
	ForecastCategoryName:null,ForecastingItemCategory:CommitForecast
ForecastingItemId	Type reference Properties Filter, Group, Sort Description The ID of the related ForecastingItem.
ForecastingTypeId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the related ForecastingType.
ForecastOwnerId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the forecast owner.
IsAmount	Type boolean Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a revenue amount. If false, then IsQuantity must be true.
IsQuantity	Type boolean Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a quantity amount. If false, then IsAmount must be true.

Field Name	Details
OwnerAdjustedAmount	Type currency Properties Create, Filter, Nillable, Sort, Update Description The revenue amount of an individual forecast item, after an adjustment.
OwnerAdjustedQuantity	Type double Properties Create, Filter, Nillable, Sort, Update Description The quantity amount of an individual forecast item, after an adjustment.
OwnerAdjustmentNote	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description A text note providing information about the adjustment. The maximum length is 140 characters. This field does not appear in reports.
PeriodId	Type reference Properties Filter, Group, Nillable, Sort Description Period ID for the adjustment. Read only.
ProductFamily	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The Product Family for the adjustment. Read only.
StartDate	Type date Properties Create, Filter, Group, Nillable, Sort

Field Name	Details
	Description The start of the adjustment, expressed as month and year. The date can include any day in a given month. Stored using the first date of the month.

Usage

Use this object to obtain a user's adjustment detail for a specified `ForecastingItem` in their own forecast.



Note: Beginning with API version 30.0, organizations can have more than one forecasting type enabled. The `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingOwnerAdjustment`, `ForecastingItem`, and `ForecastingFact` objects can all have records with different `ForecastingTypeId` values. Use the `ForecastingType` object to determine the ID for each forecast type and then filter `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingItem`, or `ForecastingFact` records as necessary.

ForecastingQuota

This object represents an individual user's quota for a specified time period. The "Manage Quotas" user permission is required for creating, updating, or deleting quotas. (Users can only edit their subordinates' quotas, not their own.) The "View All Forecasts" permission is required to View any user's forecast, regardless of the forecast role hierarchy. Available in API versions 25 and greater. Forecast managers can view the forecasts of subordinates who report to them in the forecast hierarchy.



Note: This information only applies to Collaborative Forecasts.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>CurrencyIsoCode</code>	Type picklist Properties Create, Defaulted on create, Filter, Group, Restricted picklist, Sort, Update Description The currency code of the quota. If omitted, the default is the importing user's personal currency.
<code>ForecastingTypeId</code>	Type reference

Field Name	Details
	Properties Create, Filter, Group, Sort Description The ID of the related ForecastingType.
IsAmount	Type boolean Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a revenue amount. If false, then <code>IsQuantity</code> must be true. This field is available in API version 28 and later.
IsQuantity	Type boolean Properties Defaulted on create, Filter, Group, Sort Description True indicates that the adjustment is made in a quantity amount. If false, then <code>IsAmount</code> must be true. This field is available in API version 28 and later.
PeriodId	Type reference Properties Filter, Group, Nillable, Sort Description Period ID for the quota. Read only.
ProductFamily	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The product family for the quota. This field is available in API version 29 and later.
QuotaAmount	Type currency Properties Create, Filter, Sort, Update

Field Name	Details
	Description The revenue quota amount for an individual user and for a specific period.
QuotaOwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID that identifies the quota owner.
QuotaQuantity	Type double Properties Create, Filter, Sort, Update Description The quantity quota amount for an individual user and for a specific period. This field is available in API version 28 and later.
StartDate	Type date Properties Create, Filter, Group, Sort, Update Description The start of the quota, expressed as month and year. The date can include any day in a given month. Stored using the first date of the month.

Usage

Use this object to get an individual user’s quota for a specified time period.

 **Note:** Beginning with API version 30.0, organizations can have more than one forecasting type enabled. The `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingOwnerAdjustment`, `ForecastingItem`, and `ForecastingFact` objects can all have records with different `ForecastingTypeId` values. Use the `ForecastingType` object to determine the ID for each forecast type and then filter `ForecastingQuota`, `ForecastingAdjustment`, `ForecastingItem`, or `ForecastingFact` records as necessary.

ForecastingType

This object is used to identify the forecast type associated with `ForecastingAdjustment`, `ForecastingOwnerAdjustment`, `ForecastingQuota`, `ForecastingFact`, and `ForecastingItem` objects.

Available in API versions 30.0 and greater.

 **Note:** This information only applies to Collaborative Forecasts.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
DeveloperName	Type string Properties Filter, Group, Sort Description The name of the forecasting type. Allowed values include: • <code>OpportunityRevenue</code> : Opportunities - Revenue • <code>OpportunityQuantity</code> : Opportunities - Quantity • <code>OpportunitySplitRevenue</code> : Opportunity Revenue Splits - Revenue • <code>OpportunityOverlayRevenue</code> : Opportunity Overlay Splits - Revenue • <code>OpportunityLineItemRevenue</code> : Product Families - Revenue • <code>OpportunityLineItemQuantity</code> : Product Families - Quantity • The name of a custom opportunity split type that has been enabled as a forecast type. Custom split types are based on currency fields, which can only contain revenue amounts. The <code>DeveloperName</code> is called <code>name</code> in the Metadata API and Forecasting Type in custom reports.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the forecasting type is currently enabled in the organization.
IsAmount	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the forecasting type is based on the revenue measurement.

Field Name	Details
IsQuantity	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the forecasting type is based on the quantity measurement.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language of the forecasting type.
MasterLabel	Type string Properties Filter, Group, Sort Description Master label for this Forecasting Type value. This display value is the internal label that does not get translated.

Usage

Use this object to identify the forecast type of `ForecastingAdjustment`, `ForecastingQuota`, `ForecastingFact`, and `ForecastingItem` objects.

ForecastShare

Represents the sharing of a customizable forecast at a given role and territory.



Note: This information applies to Customizable Forecasting and not Collaborative Forecasts.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
AccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A value (Read, Edit, or All) that represents the type of sharing being allowed.
CanSubmit	Type boolean Properties Filter, Group, Sort Description Indicates whether the user or group can submit forecasts (True) or not (False).
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. There are many possible values, including: • Manual—The User or Group has access because a User has manually shared the forecast with them. • Owner—The User is the owner of the forecast.
UserOrGroupId	Type reference Properties Filter, Group, Sort Description The ID representing the User or Group being granted access.
UserRoleId	Type reference Properties Filter, Group, Sort Description ID of the UserRole associated with this object.

Usage

This object allows you to determine which users and groups can view or submit forecasts owned by other users.

Goal

The Goal object represents the components of a goal such as its name, description, and status.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
CompletionDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The completion date of the goal.
Description	Type textarea Properties Create, Nillable, Update Description The description of the goal. The maximum length is 65,535 characters.
DueDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The date the goal is due.
ImageUrl	Type url Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The URL for the goal image. The image must be stored in Documents and set as externally available. Applicable only to Goal objects of Type: Goal.
IsKeyCompanyGoal	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the goal is a key company goal.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp that indicates when a user last viewed a record that is related to this goal.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp that indicates when a user last viewed this goal. If this value is null, this record might have been only referenced (LastReferencedDate) and not viewed.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the goal. The maximum length is 255 characters.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the user who owns the goal.

Field Name	Details
Progress	Type percent Properties Filter, Nillable, Sort Description The progress of the goal measured as a percentage.
StartDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The start date of the goal.
Status	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The status of the goal. Possible values: • Draft • Published • Completed • Canceled

GoalFeed

Represents a single feed item in the feed displayed for a Goal record. The goal feed shows changes to a goal for fields that are tracked in feeds, posts, and comments about the goal.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The numbers of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.

Field Name	Details
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then <code>InsertedById</code> is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
ParentId	Type reference

Field Name	Details
	Properties Filter, Group, Sort Description ID of the goal record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of TypeContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the FeedItem. When the <code>Type</code> is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of <code>ContentPost</code>, <code>LinkPost</code>, and <code>TextPost</code>, feed item types should not be created directly from the API. • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval.

Field Name

Details

- `BasicTemplateFeedItem`—Not used.
- `CanvasPost`—a post made by a canvas app posts on a feed.
- `CollaborationGroupCreated`—generated when a user creates a public group.
- `CollaborationGroupUnarchived`—Not used.
- `ContentPost`—a post with an attached file.
- `CreatedRecordEvent`—generated when a user creates a record from the publisher.
- `DashboardComponentAlert`—generated when a dashboard metric or gauge exceeds a user-defined threshold.
- `DashboardComponentSnapshot`—created when a user posts a dashboard snapshot on a feed.
- `LinkPost`—a post with an attached URL.
- `PollPost`—a poll posted on a feed.
- `ProfileSkillPost`—generated when a skill is added to a user's Chatter profile.
- `QuestionPost`—generated when a user posts a question.
- `ReplyPost`—generated when Chatter Answers posts a reply.
- `RypplePost`—generated when a user creates a Thanks badge in Work.com.
- `TextPost`—a direct text entry on a feed.
- `TrackedChange`—a change or group of changes to a tracked field.
- `UserStatus`—automatically generated when a user adds a post. Deprecated.

The following values appear in the `Type` picklist for all feed objects but apply only to [CaseFeed](#):

- `AttachArticleEvent`—generated event when a user attaches an article to a case.
- `CallLogPost`—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event.
- `CaseCommentPost`—generated event when a user adds a case comment for a case object.
- `ChangeStatusPost`—generated event when a user changes the status of a case.
- `ChatTranscriptPost`—generated event when Live Agent transcript is saved to a case.
- `EmailMessageEvent`—generated event when an email related to a case object is sent or received.
- `FacebookPost`—generated when a Facebook post is created from a case. Deprecated.

Field Name	Details
	• MilestoneEvent—generated when a case milestone is completed or reaches violation status. • SocialPost—generated when a social post is created from a case.

GoalHistory

This read-only object contains historical information about changes that have been made to the Goal object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
GoalId	Type reference Properties Filter, Group, Sort Description ID of the goal.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType

Field Name	Details
	Properties Nillable, Sort
	Description The latest value of the field before it was changed.

GoalLink

Represents the relationship between two goals. This is a many-to-many relationship, meaning that each goal can link to many other goals.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
Name	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description The auto-generated name of the goal link.
ParentGoalId	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the parent goal.
SubgoalId	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the subgoal.

GoalShare

Represents a sharing entry on a Goal object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccessLevel</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the goal. The possible values are: • Read Only • Read/Write • Owner This field must be set to an access level that is higher than the organization's default access level for goals.
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the goal that is associated with this sharing entry.
<code>RowCause</code>	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: • Owner: User is the owner of the Goal or is in a user role above the Goal owner in the role hierarchy. • Manual: User or group has access because a user with "All" access manually shared the Goal with the user or group. • Rule: User or group has access via a Goal sharing rule.

Field Name	Details
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the Goal. This field can't be updated.

GoogleDoc

Represents a link to a Google Document. This object is available in API version 14.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

This object is available in **All** Editions except **Database.com** for Google Apps Premier Edition accounts. See the Salesforce online help for more information.

Fields

Field	Details
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the Google document.
Owner	Type reference Properties Create, Defaulted on create, Filter, Nillable, Update Description The ID of the user who currently owns this Google Document. Default value is the user logged in to the API to perform the create.

Field	Details
ParentId	Type reference Properties Create, Filter Description Required. ID of the attachment's parent object. The following objects are supported as parents of Google documents: Account, Asset, Campaign, Case, Contact, Contract, Custom Objects, Lead, Opportunity, Product2, and Solution.
Url	Type string Properties Create, Filter, Nillable, Update Description The URL of the Google document.

Group

Groups are sets of users. They can contain individual users, other groups, the users in a particular role or territory, or the users in a particular role or territory plus all of the users below that role or territory in the hierarchy.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `search()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
DefaultDivision	Type picklist Properties Filter, Group, Restricted picklist, Sort Description This record's default division. Only applicable if divisions are enabled for your organization.

Field	Details
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Group Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
DoesIncludeBosses	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the managers have access (<code>true</code>) or do not have access (<code>false</code>) to records shared with members of the group. This field is only available for public groups. This field is available in API version 18.0 and later.
DoesSendEmailToMembers	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the email is sent (<code>true</code>) or not sent (<code>false</code>) to the group members. The email is sent to queue members as well.
Email	Type email Properties Create, Filter, Group, Nillable, Sort, Update Description Email address for a group of type Case. Applies only for a case queue.

Field	Details
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of the group. Corresponds to Label on the user interface.
OwnerId	Type reference Properties Filter, Group, Sort Description ID of the user who owns the group.
RelatedId	Type reference Properties Filter, Group, Nillable, Sort Description Represents the ID of the associated groups. For Groups of type “Role,” the ID of the associated UserRole. The <code>RelatedId</code> field is polymorphic.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Required. Type of the Group. One of the following values: • Regular—Standard Public Group. When you <code>create()</code> a Group, its type must be <code>Regular</code>, unless a partner portal is enabled for the organization, in which case the type can be <code>Regular</code> or <code>PRMOrganization</code>. • Role—Public Group that includes all of the User records in a particular UserRole. • RoleAndSubordinates—Public Group that includes all of the User records in a particular UserRole and all of the User records in any subordinateUserRole. • Organization—Public Group that includes all of the User records in the organization. This Group is read-only. • Case—Public group of users, members of a queue that can own a Case. • Lead—Public group of users, members of a queue that can own a Lead. • Manager—Public group that includes a user’s direct and indirect managers. This Group is read-only.

Field	Details
	• <code>ManagerAndSubordinatesInternal</code>—Public Group that includes a user and the user's direct and indirect reports. This Group is read-only. • <code>PRMOrganization</code>—Public Group that includes all of the partners in an organization that has the partner portal feature enabled. • <code>Queue</code>—Public Group that includes all of the User records that are members of a queue. • <code>Territory</code>—Public Group that includes all of the User records in an organization that has the territory feature enabled. • <code>TerritoryAndSubordinates</code>—Public Group that includes all of the User records in a particular UserRole and all of the User records in any subordinateUserRole. • <code>Collaboration</code>—Chatter group. Only <code>Regular</code>, <code>Case</code>, and <code>Lead</code> can be used when creating a group. The other values are reserved.

Usage

Unlike users, this object can be deleted. Any User can access this object—no special permissions are needed.

Only public groups are accessible via the API. Personal groups are not available.

In API version 34.0 and later, you can query a Group using `Related.Name` to retrieve the Group's name. `Related.Name` is supported for public groups, user roles, territories, manager groups, and user names.

In API version 13.0 and later, if you delete a public group, it will be deleted even if it has been used in sharing, consistent with the behavior for UserRole. In versions before 13.0, such sharing prevents the record from being deleted.

GroupMember

Represents a User or Group that is a member of a public group.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users cannot access this object.

Fields

Field	Details
<code>GroupId</code>	Type reference

Field	Details
	Properties Create, Filter, Group, Sort Description Required. ID of the Group.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the User or Group that is a direct member of the group.

Usage

A record exists for every User or Group who is a direct member of a public group whose `Type` field is set to Regular. User records that are indirect members of Regular public groups are not listed as group members. A User can be an indirect member of a group if he or she is in a `UserRole` above the direct group member in the hierarchy, or if he or she is a member of a group that is included as a subgroup in that group.

If you attempt to create a record that matches an existing record, system simply returns the existing record.

HashtagDefinition

HashtagDefinition represents hashtag (#) topics in public Chatter posts and comments. Public posts and comments include those on profiles and in public groups, but not those on records or in private groups. This object is available in API version 26.0 and later.

Supported Calls

`describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
HashtagCount	Type int Properties Filter, Group, Nillable, Sort Description The number of times a hashtag topic is used.

Field Name	Details
Name	Type string Properties Filter, Nillable, Sort Description The string of characters following the hashtag (#) in a hashtag topic.
NameNorm	Type string Properties Filter, Nillable, Sort Description The string of characters following the hashtag (#) in a hashtag topic, normalized to remove capitalization and punctuation.
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description Identifier of the community to which the HashtagDefinition belongs. This field is available only if Salesforce Communities is enabled in your organization.

Usage

Use this object to identify public hashtag topics and see how often they're used.

Holiday

Represents a period of time during which your customer support team is unavailable. Business hours and escalation rules associated with business hours are suspended during any holidays with which they are affiliated.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
ActivityDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description If the Holiday <code>IsAllDay</code> flag is set to <code>true</code> (indicating that it is an all-day holiday), then the holiday due date information is contained in the <code>ActivityDate</code> field. This field is a date field with a timestamp that is always set to midnight in the Coordinated Universal Time (UTC) time zone. The timestamp is not relevant, and you should not attempt to alter it to account for any time zone differences.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Text description of the holiday.
EndTimeInMinutes	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The end time of the holiday in minutes.
IsAllDay	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the duration of the holiday is all day (<code>true</code>) or not (<code>false</code>).
IsRecurrence	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the holiday is scheduled to repeat itself (<code>true</code>) or only occurs once (<code>false</code>). This is a read only field on update, but not on create. If this field value is <code>true</code>, then any recurrence fields associated with the given recurrence type must be populated.

Field	Details
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the holiday.
RecurrenceDayOfMonth	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The day of the month on which the holiday repeats.
RecurrenceDayOfWeekMask	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The day or days of the week on which the holiday repeats. This field contains a bitmask. For each day of the week, the values are as follows: • Sunday = 1 • Monday = 2 • Tuesday = 4 • Wednesday = 8 • Thursday = 16 • Friday = 32 • Saturday = 64 Multiple days are represented as the sum of their numerical values. For example, Tuesday and Thursday = 4 + 16 = 20.
RecurrenceEndDateOnly	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The last date on which the holiday repeats. For multiday recurring events, this is the day on which the last occurrence starts.
RecurrenceInstance	Type picklist

Field	Details
	Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The frequency of the recurring holiday. For example, 2nd or 3rd.
RecurrenceInterval	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The interval between recurring holidays.
RecurrenceMonthOfYear	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The month of the year on which the event repeats.
RecurrenceStartDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The date when the recurring holiday begins. Must be a date and time before RecurrenceEndDateOnly.
RecurrenceType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates how often the holiday repeats. For example, daily, weekly, or every Nth month (where "Nth" is defined in RecurrenceInstance).
StartTimeInMinutes	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The start time of the holiday in minutes.

Usage

Use this object to view and update holidays, which specify dates and times at which associated business hours and escalation rules are suspended.

Idea

Represents an idea on which users are allowed to comment and vote, for example, a suggestion for an enhancement to an existing product or process. This object is available in API version 12 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

 **Note:** For other standard objects, the `describeLayout()` call returns the `recordTypeMappings` section that contains the layout ID and picklist values for each record type. However, the `recordTypeMappings` section and the fields it includes are not available for the Idea object.

When performing a SOSL search on Idea objects, IdeaComment objects are also searched.

Fields

Field	Details
AttachmentBody	Type base64 Properties Create, Nillable, Update Description File data for the attachment. This field is available in API version 28.0 and later.
AttachmentContentType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Type of the attachment. This field is available in API version 28.0 and later.
AttachmentLength	Type int Properties Filter, Group, Nillable, Sort

Field	Details
	Description Size of the attachment in bytes. This field is available in API version 28.0 and later.
AttachmentName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Name of the attachment. This field is available in API version 28.0 and later.
Body	Type textarea Properties Create, Nillable, Update Description Description of the Idea.
Categories	Type multipicklist Properties Create, Filter, Nillable, Update Description Customizable multi-select picklist used to organize Ideas into logical groupings.  Note: This field is only available if your organization has the <code>Categories</code> field enabled. This field is enabled by default in organizations created after API version 14 was released. If the <code>Categories</code> field is enabled, API versions 13 and earlier do not have access to either the <code>Categories</code> or <code>Category</code> fields.
Category	Type picklist Properties Create, Filter, Nillable, Update Description Customizable picklist of values used to organize Ideas into logical groupings.  Note: This field is not available if your organization has the multi-select <code>Categories</code> field enabled.
CommunityId	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description The zone ID associated with the idea. Once you create an idea, you can't change the zone ID associated with that idea.  Note: API version 12 does not support zone ID. If you create an idea in version 12, your idea is automatically posted to the oldest zone that you have permission to access.
CreatorFullPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's profile photo. This field is available in API version 28.0 and later.
CreatorName	Type string Properties Filter, Group, Nillable, Sort Description Name of the user who posted the idea or commented on the idea. This field is available in API version 28.0 and later.
CreatorSmallPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's thumbnail photo. This field is available in API version 28.0 and later.
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
IdeaThemeID	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description Identifies the idea theme associated with the idea.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
IsHtml	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read-only. If this value is <code>true</code> , your organization has the Ideas HTML editor enabled, and the Idea <code>Body</code> may contain HTML. If this value is <code>false</code> , the HTML editor is disabled and the Idea <code>Body</code> only contains regular text.
IsMerged	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read only. Indicates whether the idea has been merged with a parent idea (<code>true</code>) or not (<code>false</code>). You can't vote for or add comments to a merged idea.  Note: In API version 27, <code>IsMerged</code> replaces <code>IsLocked</code> . Existing formula fields that use <code>IsLocked</code> must be edited to use <code>IsMerged</code> .
LastCommentDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time the last comment (child <code>IdeaComment</code> object) was added.
LastCommentId	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description Read only. The ID of the last comment (child IdeaComment object).
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (LastReferencedDate) and not viewed.
NumComments	Type int Properties Defaulted on create, Filter, Group, Nillable, Sort Description The number of comments (child IdeaComment objects) that users have submitted for the given idea.
ParentIdeaId	Type reference Properties Filter, Group, Nillable, Sort Description The ID associated with this idea's parent idea. When multiple ideas are merged together, one idea becomes the parent (master) of the other ideas. The ParentIdeaId is automatically set when you merge ideas.
RecordTypeId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the record type assigned to this object.

Field	Details
Status	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Customizable picklist of values used to specify the status of an idea.
Title	Type string Properties Create, Filter, Group, Sort, Update Description The descriptive title of the idea.
VoteScore	Type double Properties Filter, Nillable, Sort Description The internal score of the Idea, used to sort Ideas on the Popular tab in the application user interface. The internal algorithm that determines the score gives older votes less weight than newer votes, simulating exponential decay. The score itself does not display in the application user interface.  Note: Unlike other fields of type double, you can't use a SOQL aggregate function with this field.
VoteTotal	Type double Properties Filter, Nillable, Sort Description An Idea's total number of points. Each vote a user makes is worth ten points, therefore the value of this field is ten times the number of votes an idea has received.  Note: Unlike other fields of type double, you can't use a SOQL aggregate function with this field.

 **Note:** If you are importing Idea data and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself..

Usage

Use this object to track ideas, which are written suggestions on which users can vote and comment.

IdeaComment

Represents a comment that a user has submitted in response to an idea.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

 **Note:** When performing a SOSL search on IdeaComment objects, Idea objects are also searched.

Fields

Field	Field Type
CommentBody	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Body of the submitted comment.
CommunityId	Type reference Properties Create, Filter, Group, Sort Description The zone ID associated with the idea. Once you create an idea, you can't change the zone ID associated with that idea.  Note: API version 12 does not support zone ID. If you create an idea in version 12, your idea is automatically posted to the oldest zone that you have permission to access.
CreatorFullPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's profile photo. This field is available in API version 28.0 and later.

Field	Field Type
CreatorName	Type string Properties Filter, Group, Nillable, Sort Description Name of the user who posted the idea or commented on the idea. This field is available in API version 28.0 and later.
CreatorSmallPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's thumbnail photo. This field is available in API version 28.0 and later.
IdeaId	Type reference Properties Create, Filter, Group, Sort Description ID of the idea on which this comment was made.
IsHtml	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read-only. If this value is <code>true</code> , your organization has the Ideas HTML editor enabled, and the <code>CommentBody</code> field may contain HTML. If this value is <code>false</code> , the HTML editor is disabled and the <code>CommentBody</code> field only contains regular text.
UpVotes	Type int Properties Filter, Group, Nillable, Sort Description Total number of up votes for the question.



Note: If you import these records, and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself.

Usage

Use this object to track comments on ideas, which are users' text responses to ideas.

IdeaReputation

Represents a collection of statistics and scores derived from a user's activity within an Ideas zone or internal organization. This object is available in API version 28.0 and later.

Supported Calls

`query()`, `retrieve()`,

Fields

Field	Details
CommentCount	Type int Properties Filter, Group, Nillable, Sort Description The number of comments a user has created in a zone or the internal organization. This number excludes comments the user creates on his or her own idea.
CommentsReceivedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of comments a user has received in a zone or the internal organization.
ContextId	Type reference Properties Filter, Group, Namepointing, Nillable, Sort Description The ID of the zone or internal organization.
DownVotesGivenCount	Type int Properties Filter, Group, Nillable, Sort

Field	Details
	Description The number of down votes a user has given in a zone or the internal organization.
DownVotesReceivedCount	Type int Properties Filter, Group, Nillable, Sort Description The number of down votes a user has received in a zone or the internal organization.
IdeaCount	Type int Properties Filter, Group, Nillable, Sort Description The number of ideas a user has created in a zone or the internal organization.
ReputationLevel	Type string Properties Nillable Description The reputation level that a user has achieved based on their score in a zone or within an organization.
Score	Type double Properties Filter, Nillable, Sort Description The total score of a user's activity within a zone or within an organization.
UpVotesGivenCount	Type int Properties Filter, Group, Nillable, Sort Description The number of up votes a user has given in a zone or the internal organization. This number doesn't include the default vote the system applies when the user creates the idea.
UpVotesReceivedCount	Type int

Field	Details
	Properties Filter, Group, Nillable, Sort
	Description The number of up votes a user has received in a zone or the internal organization.
UserId	Type reference
	Properties Filter, Group, Sort
	Description The user ID associated with the reputation.

Usage

Use to query a user's reputation within a zone.

IdeaReputationLevel

Represents a reputation level within an Ideas zone or internal organization and is used by the system to calculate reputation. You can create up to 25 levels per zone or internal organization. This object is available in API version 28.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
ContextId	Type reference
	Properties Create, Filter, Group, Namepointing, Sort, Update
	Description The ID of the zone or internal organization.
Name	Type string
	Properties Create, Filter, Group, Sort, Update

Field Name	Details
	Description Name of the reputation level. The name must be unique within the zone or internal organization. Maximum size is 50 characters.
Threshold	Type int Properties Create, Filter, Group, Sort, Update Description Minimum number of points for this level. The threshold must be unique within the zone or internal organization and must be greater than or equal to zero.

Usage

Use to create or edit reputation levels for an Ideas zone or internal organization.

IdeaTheme

Represents an invitation to community members to submit ideas that are focused on a specific topic. This object is available in API version 26 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`,

Fields

Field Name	Details
Categories	Type multipicklist Properties Create, Filter, Nillable, Update Description Customizable multi-select picklist used to organize ideas and idea themes into logical groupings.
CommunityId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Description The zone ID associated with the idea theme.
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
Description	Type textarea Properties Create, Nillable, Update Description Description of the idea theme.
EndDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Date marking the end of the idea theme.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
StartDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Date that the idea theme begins.

Field Name	Details
Status	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Customizable picklist of values used to specify the status of the idea theme.
Title	Type string Properties Create, Filter, Group, idLookup, Namefield, Sort, Update Description Title of the idea theme.

Usage

Use the object to track ideas that are submitted to an idea theme.

KnowledgeableUser

Represents a user identified as knowledgeable about a specific topic, and ranks them relative to other knowledgeable users. This object is available in API version 31.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the community the topic exists in. This field is available only if Salesforce Communities is enabled for your organization.

Field Name	Details
RawRank	Type int Properties Filter, Group, Nillable, Sort Description Rank of this user's knowledge on the topic relative to other users.
TopicId	Type reference Properties Filter, Group, Sort Description Unique ID for the topic in Salesforce.
UserId	Type reference Properties Filter, Group, Sort Description Unique ID for the user in Salesforce.

KnowledgeArticle

Provides read-only access to an article and the ability to delete the master article. Unlike KnowledgeArticleVersion, the ID of a KnowledgeArticle record is identical irrespective of the article's version (status). For more information on articles and article types, see “Managing Articles and Translations” and “Managing Article Types” in the Salesforce online help.

Supported Calls

`delete()`, `describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

A user must have the “View Articles” permission enabled. Salesforce Knowledge users, unlike Customer Portal and partner portal users, must also be granted the `Knowledge User` feature license.

Fields

Field Name	Details
ArchivedById	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the user who archived the article.
ArchivedDate	Type dateTime Properties Filter, Nillable, Sort Description The date when the article was archived.
ArticleNumber	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description The unique number automatically assigned to the article when it's created. You can't change the format or value for this field.
CaseAssociationCount	Type int Properties Filter, Group, Sort Description The number of cases attached to the article.
FirstPublishedDate	Type dateTime Properties Filter, Nillable, Sort Description The date when the article was first published.
LastPublishedDate	Type dateTime Properties Filter, Nillable, Sort

Field Name	Details
	Description The date when the article was last published.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (LastReferencedDate) and not viewed.
MasterLanguage	Type picklist Properties Filter, Restricted picklist Description The article's original language. Only accessible if your knowledge base supports multiple languages.

Usage

Use this object to query or retrieve articles. KnowledgeArticle can be used in a SOQL clause, but doesn't provide access to the fields from the article. Provides read-only access to an article and the ability to delete the master article.

KnowledgeArticleVersion

Provides a global view of standard article fields across all article types depending on their version. Use this object to:

- Query or search generically across multiple article types.
- Filter on a specific version.
- Update standard fields, those that are updateable, in draft versions.

When you query on the archived article, the results include both the article and the article's archived versions.



Note: You can't update draft translations with the API.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `search()`, and `update()`.

Note:

- You can only update draft versions.
- To create, update, or delete a Knowledge article version, use the call on *ArticleType_kav*, where *ArticleType* is the name of the article's type. For example, to delete use *ArticleType_kav.delete()*.

Special Access Rules

A user must have the “View Articles” permission enabled. Salesforce Knowledge users, unlike Customer Portal and partner portal users, must also be granted the `Knowledge User` feature license in order to view and edit article versions.

Fields

Field Name	Details
ArchivedById	Type reference Properties Filter, Nillable Description The ID of the user who archived the article.
ArchivedDate	Type dateTime Properties Filter, Nillable Description The date when the article was archived.
ArticleNumber	Type string Properties Autonumber, Defaulted on create, Filter Description The unique number automatically assigned to the article when it's created. You can't change the format or value for this field.
ArticleType	Type string

Field Name	Details
	Properties Defaulted on create, Filter Description Indicates the API Name of the article type. The <code>ArticleType</code> is assigned to the article when it's created. You can't change the value of this field. This field is available in API version 26.0 and later.
FirstPublishedDate	Type dateTime Properties Filter, Nillable Description The date when the article was first published.
IsLatestVersion	Type boolean Properties Defaulted on create, Group, Filter, Sort Description Indicates whether the article is the most current version. (<code>true</code>) or not (<code>false</code>). This field is available in API version 24.0 and later.
IsMasterLanguage	Type boolean Properties Defaulted on create, Filter Description Indicates whether the article has one or more translations associated with it (<code>true</code>) or not (<code>false</code>). Only accessible if your knowledge base supports multiple languages.
IsOutOfDate	Type boolean Properties Defaulted on create, Filter Description Indicates whether the source article has been updated since this translated version was created (<code>true</code>) or not (<code>false</code>). Only accessible if your knowledge base supports multiple languages.
IsVisibleInApp	Type boolean

Field Name	Details
	Properties Defaulted on create, Filter Description Required. Indicates whether the article is visible in the Articles tab (<code>true</code>) or not (<code>false</code>).
IsVisibleInCsp	Type boolean Properties Defaulted on create, Filter Description Required. Indicates whether the article is visible in the Customer Portal (<code>true</code>) or not (<code>false</code>).
IsVisibleInPkb	Type boolean Properties Defaulted on create, Filter Description Required. Indicates whether the article is visible in the public knowledge base (<code>true</code>) or not (<code>false</code>).
IsVisibleInPrm	Type boolean Properties Defaulted on create, Filter Description Required. Indicates whether the article is visible in the partner portal (<code>true</code>) or not (<code>false</code>).
KnowledgeArticleId	Type reference Properties Filter Description The ID of the article independent from its version. The value for this field is retrieved from the <code>Id</code> field of the KnowledgeArticle object.
Language	Type picklist Properties Filter, Restricted picklist

Field Name	Details
	Description The language that the article is written in, such as <code>French</code> or <code>Chinese (Traditional)</code>. Querying or searching articles in SOQL or SOSL requires that you specify the <code>Language</code> field in the WHERE clause. The language must be the same for all article types.
<code>LastPublishedDate</code>	Type <code>dateTime</code> Properties Filter, Nillable Description The date when the article was last published.
<code>MasterVersionId</code>	Type <code>reference</code> Properties Filter, Nillable Description ID of the source article, if this is the translation of a source article. Only accessible if your knowledge base supports multiple languages.
<code>OwnerId</code>	Type <code>reference</code> Properties Filter Description The ID of the article's owner.
<code>PublishStatus</code>	Type <code>picklist</code> Properties Filter, Restricted picklist Description The publication status for the article: • <code>Draft</code>: any draft articles. • <code>Online</code>: articles published in Salesforce Knowledge. • <code>Archived</code>: archived articles. A user must have the “Manage Articles” permission enabled to use <code>Online</code>. Querying or searching articles in SOQL or SOSL requires that you specify either the <code>PublishStatus</code> or the <code>Id</code> field in the WHERE clause. You can search for only

Field Name	Details
	one publication status per article type in a single SOSL query. When searching for articles with a <code>PublishStatus</code> of <code>Archived</code> , also check that <code>IsLatestVersion</code> equals <code>false</code> in your WHERE clause.
SourceId	Type reference Properties Filter, Nillable Description ID of the source from which the article was created (Case or Reply).
Summary	Type textarea Properties Filter, Nillable Description Summary of the article. Maximum size is 1000 characters.
Title	Type string Properties Defaulted on create, Filter, idLookup Description Required. Article's title. Maximum size is 255 characters.
TranslationCompletedDate	Type dateTime Properties Filter, Nillable Description Date and time when the article was last translated. Only accessible if your knowledge base supports multiple languages.
TranslationExportedDate	Type dateTime Properties Filter, Nillable Description Date and time when the article was last exported for translation. Only accessible if your knowledge base supports multiple languages.

Field Name	Details
TranslationImportedDate	Type dateTime Properties Filter, Nillable Description Date and time when the article was last imported for translation. Only accessible if your knowledge base supports multiple languages.
UrlName	Type string Properties Filter Description Required. Represents the article's URL. Can contain alphanumeric characters and hyphens but can't begin or end with a hyphen. <code>UrlName</code> is case-sensitive and its maximum size is 255 characters.
ValidationStatus	Type picklist Properties Filter, Group Description Shows whether the content of the article has been validated. Default values are <code>Validated</code> and <code>Not Validated</code>. This field is available in API version 24.0 or later.
VersionNumber	Type int Properties None Description The number assigned to a version of an article. This field is available in API version 24.0 and later.

Usage

Use this object to query, retrieve, or search for articles across all article types depending on their version. You can update draft master articles. Additionally, you can delete articles that are not drafts. Client applications can use `KnowledgeArticleVersion` with `describeDataCategoryGroups()` and `describeDataCategoryGroupStructures()` to return the category groups and the category structure associated with Salesforce Knowledge.

Alternatively, client applications can use the article type `API Name` followed by `__kav` to query, retrieve, or search for articles for a specific article type.

To access an article independent of its version, use the KnowledgeArticle object.

SOQL Samples

The following SOQL clause uses KnowledgeArticleVersion to query all published articles from **all article types** complying with the classification specified in the WITH DATA CATEGORY clause:

```
SELECT Title, Summary
FROM KnowledgeArticleVersion
WHERE PublishStatus='Online'
AND Language = 'en_US'
WITH DATA CATEGORY Geography__c ABOVE_OR_BELOW europe__c AND Product__c BELOW All__c
```

The following SOQL clause uses the article type API Name to limit the query to all draft articles from the Offer__kav article type:

```
SELECT Id, Title
FROM Offer__kav
WHERE PublishStatus='Draft'
AND Language = 'en_US'
WITH DATA CATEGORY Geography__c AT (france__c,usa__c) AND Product__c ABOVE dsl__c
```

The following SOQL clause uses KnowledgeArticleVersion to query the Ids of all archived versions of a particular article:

```
SELECT Id
FROM KnowledgeArticleVersion
WHERE PublishStatus='Archived'
AND IsLatestVersion=false
AND KnowledgeArticleId='kA1D000000001PQ6KAM'
```

SOQL and SOSL with KnowledgeArticleVersion

- Always filter on a single value of PublishStatus unless the query filters on one or more primary key IDs. To support security, only users with the “Manage Articles” permission see articles whose PublishStatus value is Draft.
- Archived article versions are stored in the articletype__kav object. To query archived article versions, specify the article Id and set sLatestVersion='0'.
- Always filter on a single value of Language. However, in SOQL, you can filter on more than one Language if there is a filter on Id or KnowledgeArticleId.

KnowledgeArticleVersionHistory

Enables read-only access to the full history of an article. This object is available in API version 25.0 and later.

Supported Calls

describeSObjects(), getDeleted(), getUpdated(), query(), retrieve()

Special Access Rules

This object respects field, entity, and record-level security. You must have at least “Read” permission on the article type or the field to access its history. For data category security, Salesforce determines access based on the categorization of the online version of an article. If there is no online version, then security is applied based on the archived version, followed by the security of the draft version.

Fields

Field Name	Details
EventType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of event that is tracked in the history table.
FieldName	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Name of the tracked field.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language that the article is written in, such as <code>French</code> or <code>Chinese (Traditional)</code>. Querying or searching articles in SOQL or SOSL requires that you specify the <code>Language</code> field in the WHERE clause. The language must be the same for all article types.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType

Field Name	Details
	Properties Nillable, Sort Description The most recent value of the field before it was changed.
ParentId	Type reference Properties Filter, Group, Sort Description The ID of the article.
ParentObjectType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of object that contains the field.
VersionId	Type reference Properties Filter, Group, Nillable, Sort Description The ID assigned to a version of the article.
VersionNumber	Type int Properties Filter, Group, Sort Description The number assigned to a version of an article. This field is available in API version 24.0 and later.

Usage

Use this object to query events in the history of an article. For example, you can retrieve the number of edits a particular user has made to an article, how many times the article has been published, and so on.

KnowledgeArticleViewStat

Provides statistics on the number of views for the specified article across all article types. This object is read-only and available in API version 20 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Users must have access to the published version of an article to retrieve its views. For more information on published article version, see the `PublishStatus` field in `KnowledgeArticleVersion`.

Fields

Field Name	Details
Channel	Type picklist Properties Filter, Restricted picklist Description The channel where the article is viewed: • <code>AllChannels</code> for article views across all channels. • <code>App</code> for the internal Salesforce Knowledge application. • <code>Pkb</code> for article views in public knowledge base. • <code>Csp</code> for Customer Portal. • <code>Prm</code> for article view in partner portal.
NormalizedScore	Type double Properties Filter, Nillable Description Article's weighted views in the selected channel. The article with most views has a score of 100. Other article views are then calculated relative to this highest view score. For example, if the best read article has 2000 views and another has 1000. The first one gets a score of 100 while the second gets 50.
ParentId	Type reference

Field Name	Details
	Properties Filter
	Description ID of the viewed article. This corresponds to a KnowledgeArticle record.
ViewCount	Type int
	Properties Filter, Group, Sort
	Description The number of unique views an article has received in the selected channel. An article with a high number of views may not always have a high normalized score. The normalized score for an article is calculated based on views over time, with more recent views earning a higher score. This field is available in API version 27.0 and later.

Usage

Use this object to query or retrieve statistics for article views.

Alternatively, client applications can use the article type `API__Name` followed by `__ViewStat` to query or retrieve most viewed articles from a specific article type.

SOQL Samples

The following SOQL clause uses KnowledgeArticleViewStat to query all the article views in Salesforce Knowledge and return the related articles:

```
SELECT Id, NormalizedScore, Parent.Id
FROM KnowledgeArticleViewStat where Channel = 'App'
ORDER BY NormalizedScore
```

Use the following clause to restrict your query to Offer articles for the Offer article type:

```
SELECT Id, NormalizedScore, Parent.Id
FROM Offer__ViewStat where Channel = 'App'
ORDER BY NormalizedScore
```

KnowledgeArticleVoteStat

Provides the weighted rating for the specified article on a scale of 1 to 5 across all article types. This object is read-only and available in API version 20 and later.

Supported Calls

`describeObjects()`, `query()`, `retrieve()`

Special Access Rules

Users must have access to the published version of an article to retrieve its votes. For more information on published article version, see the `PublishStatus` field in `KnowledgeArticleVersion`

Fields

Field Name	Details
<code>Channel</code>	Type picklist Properties Filter, Restricted picklist Description The channel where the article is rated: • <code>AllChannels</code> for article views across all channels. • <code>App</code> for the internal Salesforce Knowledge application. • <code>Pkb</code> for article views in public knowledge base. • <code>Csp</code> for Customer Portal. • <code>Prm</code> for article view in partner portal.
<code>NormalizedScore</code>	Type double Properties Filter, Nillable Description Article's weighted score on a scale of 1 to 5. A higher score means more votes. Articles without recent votes trend towards an average rating of three stars.
<code>ParentId</code>	Type reference Properties Filter Description The rated article. This corresponds to a <code>KnowledgeArticle</code> record.

Usage

Use this object to query or retrieve the rating for an article.

Alternatively, client applications can use the article type `API__Name` followed by `__VoteStat` to query or retrieve the rating for an article for a specific article type.

SOQL Samples

See KnowledgeArticleViewStat.

Lead

Represents a prospect or potential Opportunity.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `merge()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Address	Type address Properties Filter, Nillable Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.
AnnualRevenue	Type currency Properties Create, Filter, Nillable, Sort, Update Description Annual revenue for the company of the lead.
City	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description City for the address of the lead.
CleanStatus	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field	Details
	Description Indicates the record's clean status as compared with Data.com. Values are: <code>Matched</code>, <code>Different</code>, <code>Acknowledged</code>, <code>NotFound</code>, <code>Inactive</code>, <code>Pending</code>, <code>SelectMatch</code>, or <code>Skipped</code>. Several values for <code>CleanStatus</code> display with different labels on the lead record detail page. • <code>Matched</code> displays as <code>In Sync</code> • <code>Acknowledged</code> displays as <code>Reviewed</code> • <code>Pending</code> displays as <code>Not Compared</code>
<code>Company</code>	Type string Properties Create, Filter, Group, Sort, Update Description Required. Company of the lead.  Note: If person account record types have been enabled, and if the value of <code>Company</code> is null, the lead converts to a person account.
<code>CompanyDunsNumber</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The Data Universal Numbering System (D-U-N-S) number is a unique, nine-digit number assigned to every business location in the Dun&Bradstreet database that has a unique, separate, and distinct operation. D-U-N-S numbers are used by industries and organizations around the world as a global standard for business identification and tracking. Maximum size is 9 characters.  Note: This field is only available to organizations that use Data.com Prospector or Data.com Clean.
<code>ConnectionReceivedId</code>	Type reference Properties Filter, Group, Nillable, Sort Description ID of the <code>PartnerNetworkConnection</code> that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.

Field	Details
ConnectionSentId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the ConnectionSentId field is no longer supported. The ConnectionSentId field is still visible, but the value is null. You can use the new PartnerNetworkRecordConnection object to forward records to connections.
ConvertedAccountId	Type reference Properties Filter, Group, Nillable, Sort Description Object reference ID that points to the Account into which the Lead has been converted.
ConvertedContactId	Type reference Properties Filter, Group, Nillable, Sort Description Object reference ID that points to the Contact into which the Lead has been converted.
ConvertedDate	Type date Properties Filter, Group, Nillable, Sort Description Date on which this Lead was converted.
ConvertedOpportunityId	Type reference Properties Filter, Group, Nillable, Sort Description Object reference ID that points to the Opportunity into which the Lead has been converted.
Country	Type string

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description Country for the address of the lead.
CountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the lead's address.
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
Description	Type textarea Properties Create, Nillable, Update Description Description of the lead.
Division	Type picklist Properties Filter, Group, Restricted picklist, Sort Description A logical segment of your organization's data. Available only if the organization has the Division permission enabled.
Email	Type email Properties Create, Filter, Group, Nillable, Sort, Update Description Email address for the lead.

Field	Details
EmailBouncedDate	Type dateTime Properties Filter, Nillable, Sort, Update Description If bounce management is activated and an email sent to the lead bounced, the date and time the bounce occurred.
EmailBouncedReason	Type string Properties Filter, Group, Nillable, Sort, Update Description If bounce management is activated and an email sent to the lead bounced, the reason the bounce occurred.
Fax	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Fax number for the lead.
FirstName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description First name of the lead. Limited to 40 characters.
HasOptedOutOfEmail	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates whether the lead has opted out of email (<code>true</code>) or not (<code>false</code>). Label is Email Opt Out.
Industry	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description Industry the lead works in.
IsConverted	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Indicates whether the Lead has been converted (<code>true</code>) or not (<code>false</code>). Label is Converted .
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
IsUnreadByOwner	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If true, lead has been assigned, but not yet viewed. See Unread Leads for more information. Label is Unread By Owner .
Jigsaw	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description References the ID of a contact in Data.com. If a lead has a value in this field, it means that a contact was imported as a lead from Data.com. If the contact (converted to a lead) was not imported from Data.com, the field value is null. Maximum size is 20 characters. Available in API version 22.0 and later. Label is Data.com Key .  Important: The <code>Jigsaw</code> field is exposed in the API to support troubleshooting for import errors and reimporting of corrected data. Do not modify the value in the <code>Jigsaw</code> field.
LastActivityDate	Type date

Field	Details
	Properties Filter, Group, Nillable, Sort Description Value is one of the following, whichever is the most recent: • Due date of the most recent event logged against the record. • Due date of the most recently closed task associated with the record.
LastName	Type string Properties Create, Filter, Group, Sort, Update Description Required. Last name of the lead. Limited to 80 characters.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Latitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>Longitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
Longitude	Type double Properties Create, Filter, Nillable, Sort, Update

Field	Details
	Description Used with <code>Latitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
LeadSource	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Source from which the lead was obtained.
MasterRecordId	Type reference Properties Filter, Group, Nillable, Sort Description If this object was deleted as the result of a merge, this field contains the ID of the record that was kept. If this object was deleted for any other reason, or has not been deleted, the value is <code>null</code>.  Note: When using Apex triggers to determine which record was deleted in a merge event, this field's value is the ID of the record that was kept only in <code>Trigger.old</code>. In <code>Trigger.new</code>, the value is <code>null</code>.
MiddleName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Middle name of the lead. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.
MobilePhone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Mobile phone number for the lead.
Name	Type string Properties Filter, Group, Sort

Field	Details
	Description Concatenation of <code>FirstName</code> , <code>MiddleName</code> , <code>LastName</code> , and <code>Suffix</code> . Maximum size is 121 characters.
<code>NumberOfEmployees</code>	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Number of employees at the lead's company. Label is Employees .
<code>OwnerId</code>	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the lead.
<code>PartnerAccountId</code>	Type reference Properties Filter, Nillable Description ID of the partner account for the partner user that owns this lead. Available only if Partner Relationship Management is enabled OR Communities is enabled and you have partner portal licenses.  Note: If you are uploading leads using API version 15.0 or earlier, and one of the leads in the batch has a partner user as the owner, the <code>Partner Account</code> field on all leads in the batch is set to that partner user's account regardless of whether the partner user is the owner. In version 16.0, the <code>Partner Account</code> field is set to the appropriate account for the partner user that owns the lead. If the owner of the lead is not a partner user, this field remains blank.
<code>Phone</code>	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description Phone number for the lead.
<code>PhotoUrl</code>	Type url

Field	Details
	Properties Filter, Group, Sort Description Path to be combined with the URL of a Salesforce instance (for example, https://na1.salesforce.com/) to generate a URL to request the social network profile image associated with the lead. Generated URL returns an HTTP redirect (code 302) to the social network profile image for the lead. Blank if Social Accounts and Contacts isn't enabled for the organization or if Social Accounts and Contacts has been disabled for the requesting user.
PostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Postal code for the address of the lead. Label is Zip/Postal Code.
Rating	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Rating of the lead.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object.
Salutation	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Salutation for the lead.
State	Type string

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description State for the address of the lead.
StateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the lead's address.
Status	Type picklist Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Status code for this converted lead. Status codes are defined in <code>Status</code> and represented in the API by the <code>LeadStatus</code> object.
Street	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Street number and name for the address of the lead.
Suffix	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Name suffix of the lead. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.
Title	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Title for the lead, for example CFO or CEO.

Field	Details
Website	Type url Properties Create, Filter, Group, Nillable, Sort, Update Description Website for the lead.

 **Note:** If you import Lead data and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself..

Converted Leads

Leads have a special state to indicate that they have been converted into an Account, Contact, and optionally, an Opportunity. Your client application can convert leads via the `convertLead()` call. Users can also convert leads through the user interface. Once a lead has been converted, it is read-only. You can't update or delete a converted lead. However, you can query converted lead records.

Leads have several fields that indicate their converted status. These special fields are set when converting the lead in the user interface.

- `ConvertedAccountId`
- `ConvertedContactId`
- `ConvertedDate`
- `ConvertedOpportunityId`
- `IsConverted`
- `Status`

 **Note:** If person account record types have been enabled, and if the value of `Company` is null, the lead converts to a person account.

Unread Leads

Leads have a special state to indicate that they have not been viewed or edited by the lead owner. In the user interface, this is helpful for users to know which leads have been assigned to them but which they have not touched yet. `IsUnreadByOwner` is `true` if the lead owner has not yet viewed or edited the lead, and `false` if the lead owner has viewed or edited the lead at least once.

Lead Status Picklist

Each `Status` value corresponds to either a converted or unconverted status in the lead status picklist, as defined in the user interface. To obtain the lead status values in the picklist, a client application can query `LeadStatus`.

You can't convert a lead via the API by changing `Status` to one of the converted lead status values. When you convert qualified leads into an account, contact, and opportunity, you can select one of the converted status types for the lead. Leads with a converted status type are no longer available in the Leads tab, although you can include them in reports.

Usage

To update a Lead or to convert one with `convertLead()`, your client application must log in with the “Edit” permission on leads.

When you create, update, or upsert a lead, your client application can have the lead automatically assigned to one or more User records based on assignment rules that have been configured in the user interface.

To use this feature, your client application needs to set either of the following options (but not both) in the `AssignmentRuleHeader` used in create or update:

Field	Field Type	Details
<code>assignmentRuleId</code>	reference	ID of the assignment rule to use. Can be an inactive assignment rule. If unspecified and <code>useDefaultRule</code> is <code>true</code>, then the default assignment rule is used. To find the ID for a given assignment rule, query the <code>AssignmentRule</code> object (specifying <code>RuleType="leadAssignment"</code>), iterate through the returned <code>AssignmentRule</code> records, find the one you want to use, retrieve its ID, and then specify its ID in this field in the <code>AssignmentRuleHeader</code>.
<code>useDefaultRule</code>	boolean	Specifies whether to use the default rule for rule-based assignment (<code>true</code>) or not (<code>false</code>). Default rules are assigned in the user interface.

Java Sample

The following Java sample shows how to automatically assign a newly created lead.

```
package com.doc.samples;
import java.net.MalformedURLException;
import java.net.URL;
import java.rmi.RemoteException;
import javax.xml.rpc.ServiceException;

import com.sforce.soap.enterprise.LoginResult;
import com.sforce.soap.enterprise.QueryResult;
import com.sforce.soap.enterprise.SaveResult;
import com.sforce.soap.enterprise.SforceServiceLocator;
import com.sforce.soap.enterprise.SoapBindingStub;
import com.sforce.soap.enterprise._AssignmentRuleHeader;
import com.sforce.soap.enterprise._SessionHeader;
import com.sforce.soap.enterprise.fault.LoginFault;
import com.sforce.soap.enterprise.fault.UnexpectedErrorFault;
import com.sforce.soap.enterprise.sobject.Lead;
import com.sforce.soap.enterprise.sobject.SObject;

public class LeadAssignment
{
    static LeadAssignment _leadAssignment;

    public static void main(String[] args)
    {
        _leadAssignment = new LeadAssignment();
        try {
```

```

        _leadAssignment.CreateLead();
    } catch (Exception e) {
        e.printStackTrace();
    }
}

public void CreateLead() throws UnexpectedErrorFault, LoginFault,
    RemoteException, ServiceException
{
    //Create the proxy binding and login
    SoapBindingStub binding = (SoapBindingStub) new SforceServiceLocator().getSoap();
    LoginResult lr = binding.login("user@domain.net", "secret");

    //Reset the binding to use the endpoint returned from login
    binding._setProperty(SoapBindingStub.ENDPOINT_ADDRESS_PROPERTY,
        lr.getServerUrl());

    //Create the session id header, and add it to the proxy binding
    _SessionHeader sh = new _SessionHeader();
    sh.setSessionId(lr.getSessionId());
    binding.setHeader(
        new SforceServiceLocator().getServiceName().getNamespaceURI(),
        "SessionHeader", sh );

    //Create a new case and assign various properties
    Lead lead = new Lead();

    lead.setFirstName("Joe");
    lead.setLastName("Smith");
    lead.setCompany("ABC Corporation");
    lead.setLeadSource("API");
    //The lead assignment rule will assign any new leads that
    //have "API" as the LeadSource to a particular user

    //Create the assignment rule header and add it to the proxy binding
    _AssignmentRuleHeader arh = new _AssignmentRuleHeader();

    //In this sample we will look for a particular rule and if found
    //use the id for the lead assignment. If it is not found we will
    //instruct the call to use the current default rule. You can't use
    //both of these values together.
    QueryResult qr = binding.query("Select Id From AssignmentRule where Name = " +
        "'Mass Mail Campaign' and RuleType = 'leadAssignment'");
    if (qr.getSize() == 0) {
        arh.setUseDefaultRule(new Boolean(true));
    } else {
        arh.setAssignmentRuleId(qr.getRecords(0).getId());
    }

    binding.setHeader(
        new SforceServiceLocator().getServiceName().getNamespaceURI(),
        "AssignmentRuleHeader", arh);

    // Every operation that results in a new or updated case, will

```

```

// use the specified rule until the header is removed from the
// proxy binding.
SaveResult[] sr = binding.create(new SObject[] {lead});
for (int i=0;i<sr.length;i++) {
    if (sr[i].isSuccess()) {
        System.out.println("Successfully created lead with id of: " +
            sr[i].getId().getValue() + ".");
    }
    else {
        System.out.println("Error creating lead: " +
            sr[i].getErrors(0).getMessage());
    }
}

// This call effectively removes the header, the next lead will
// be assigned to the default lead owner. Remember to add the
// session header back in.
binding.clearHeaders();
binding.setHeader(
    new SforceServiceLocator().getServiceName().getNamespaceURI(),
    "SessionHeader", sh);
}
}

```

C# Sample

The following C# sample shows how to automatically assign a newly created lead.

```

using System;
using System.Collections.Generic;
using System.Text;
using LeadAssignment.sforce;

namespace LeadAssignment
{
    class LeadAssignment
    {
        private SforceService binding;

        private static readonly string Username = "ENTERUSERNAME";
        private static readonly string Password = "ENTERPASSWORD";

        /// <summary>
        /// Create the proxy binding and login
        /// </summary>
        private LeadAssignment()
        {
            this.binding = new SforceService();
            LoginResult lr = binding.login(LeadAssignment.Username, LeadAssignment.Password);

            // Reset the binding to use the endpoint returned from login
            this.binding.Url = lr.serverUrl;
        }
    }
}

```

```

        // Create the session ID header and add it to the proxy binding
        this.binding.SessionHeaderValue = new SessionHeader();
        this.binding.SessionHeaderValue.sessionId = lr.sessionId;
    }

    [STAThread]
    static void Main(string[] args)
    {
        LeadAssignment leadAssignment = new LeadAssignment();
        try
        {
            leadAssignment.CreateLead();
        }
        catch (Exception e)
        {
            Console.WriteLine(e.Message);
            Console.WriteLine(e.StackTrace);
            Console.WriteLine(e.InnerException);
        }
    }

    public void CreateLead()
    {
        // Create a new Lead and assign various properties
        Lead lead = new Lead();

        lead.FirstName = "John";
        lead.LastName = "Brown";
        lead.Company = "ABC Corporation";
        lead.LeadSource = "Advertisement";
        // Setting the lead source for a pre-existing lead assignment rule. This
        // rule was created outside of this sample and will assign any new leads
        // that have "Advertisement" as the LeadSource to a particular user

        // Create the assignment rule header and add it to the proxy binding
        AssignmentRuleHeader arh = new AssignmentRuleHeader();

        // In this sample we will look for a particular rule and if found
        // use the id for the lead assignment. If it is not found we will
        // instruct the call to use the current default rule. Both these
        // values can't be used together.
        QueryResult qr = binding.query("Select Id from AssignmentRule where Name = "
+
            "'Mass Mail Campaign' and SobjectType = 'lead'");
        if (qr.size == 0)
        {
            arh.useDefaultRule = true;
        }
        else
        {
            arh.assignmentRuleId = qr.records[0].Id;
        }
        binding.AssignmentRuleHeaderValue = arh;
    }

```

```

// Every operation that results in a new or updated lead will use the
// specified rule until the header is removed from the proxy binding
SaveResult[] sr = binding.create(new sObject[] { lead });
foreach (SaveResult s in sr)
{
    if (s.success)
    {
        Console.WriteLine("Successfully created Lead with ID: {0}", s.id);
    }
    else
    {
        Console.WriteLine("Error creating Lead: {0}", s.errors[0].message);
    }
}

// This call effectively removes the header. The next lead will be assigned
// to the default lead owner.
binding.AssignmentRuleHeaderValue = null;
}
}
}

```

LeadCleanInfo

Stores the metadata Data.com Clean uses to determine a lead record's clean status. Helps you automate the cleaning or related processing of lead records. LeadCleanInfo includes a number of bit vector fields.

- **CleanedBy** indicates who (a user) or what (a Clean job) cleaned the lead record.
- **IsDifferent** indicates whether or not a field on the lead record has a value that differs from the corresponding field on the matched Data.com record.
- **IsFlaggedWrong** indicates whether or not a field on the lead record has a value that is flagged as wrong to Data.com.
- **IsReviewed** indicates whether or not a field on the lead record is in a Reviewed state, which means that the value was reviewed by a user but not accepted.

Their individual bits are defined here

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
Address	Type address
	Properties Filter, Nillable

Field Name	Details
	Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.
AnnualRevenue	Type currency Properties Filter, Nillable, Sort Description Estimated annual revenue of the lead.
City	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the lead.
CleanedByJob	Type boolean Properties Filter Description Indicates whether the lead record was cleaned by a Data.com Clean job (<code>true</code>) or not (<code>false</code>).
CleanedByUser	Type boolean Properties Filter Description Indicates whether the lead record was cleaned by a Salesforce user (<code>true</code>) or not (<code>false</code>).
CompanyDunsNumber	Type string Properties Filter, Group, Nillable, Sort Description The Data Universal Numbering System (D-U-N-S) number is a unique, nine-digit number assigned to every business location in the Dun & Bradstreet database that has a unique, separate, and distinct operation. D-U-N-S numbers are used

Field Name	Details
	by industries and organizations around the world as a global standard for business identification and tracking.
CompanyName	Type string Properties Filter, Group, Nillable, Sort Description The name of the company.
ContactStatusDataDotCom	Type picklist Properties Filter, Group, Nillable, Sort Description The status of the contact associated with the lead per Data.com. Values are: Contact is Active per Data.com, Phone is Wrong per Data.com , Email is Wrong per Data.com, Phone and Email are Wrong per Data.com, Contact Not at Company per Data.com, Contact is Inactive per Data.com, Company this contact belongs to is out of business per Data.com, Company this contact belongs to never existed per Data.com OR Email address is invalid per Data.com.
Country	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the lead.
DandBCompanyDunsNumber	Type string Properties Filter, Group, Nillable, Sort Description The D-U-N-S Number on the D&B Company record (if any) that is linked to the lead.
DataDotComCompanyId	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description The ID Data.com maintains for the company associated with the lead.
DataDotComId	Type string Properties Filter, Group, Nillable, Sort Description The ID Data.com maintains for the contact associated with the lead.
Email	Type email Properties Filter, Group, Nillable, Sort Description The lead's email address.
FirstName	Type string Properties Filter, Group, Nillable, Sort Description The lead's first name.
Industry	Type picklist Properties Filter, Group, Nillable, Sort Description The industry the lead belongs to.
IsDifferentAnnualRevenue	Type boolean Properties Filter Description Indicates whether the lead's <code>AnnualRevenue</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).

Field Name	Details
IsDifferentCity	Type boolean Properties Filter Description Indicates whether the lead's <code>City</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentCompanyDunsNumber	Type boolean Properties Filter Description Indicates whether the lead's <code>Company D-U-N-S Number</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentCompanyName	Type boolean Properties Filter Description Indicates whether the lead's <code>Company Name</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentCountry	Type boolean Properties Filter Description Indicates whether the lead's <code>Country</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentCountryCode	Type boolean Properties Filter Description Indicates whether the account's <code>Country Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).

Field Name	Details
IsDifferentDandBCompanyDunsNumber	Type boolean Properties Filter Description Indicates whether the lead's <code>D&B Company D-U-N-S Number</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentEmail	Type boolean Properties Filter Description Indicates whether the lead's <code>Email</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentFirstName	Type boolean Properties Filter Description Indicates whether the lead's <code>First Name</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentIndustry	Type boolean Properties Filter Description Indicates whether the lead's <code>Industry</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentLastName	Type boolean Properties Filter Description Indicates whether the lead's <code>Last Name</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).

Field Name	Details
IsDifferentNumberOfEmployees	Type boolean Properties Filter Description Indicates whether the lead's <code>No. of Employees</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentPhone	Type boolean Properties Filter Description Indicates whether the lead's <code>Phone</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentPostalCode	Type boolean Properties Filter Description Indicates whether the lead's <code>Postal Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentState	Type boolean Properties Filter Description Indicates whether the lead's <code>State</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentStateCode	Type boolean Properties Filter Description Indicates whether the account's <code>State Code</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).

Field Name	Details
IsDifferentStreet	Type boolean Properties Filter Description Indicates whether the lead's <code>Street</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsDifferentTitle	Type boolean Properties Filter Description Indicates whether the lead's <code>Title</code> field value is different from the corresponding value on its matched Data.com record (<code>true</code>) or not (<code>false</code>).
IsFlaggedWrongAddress	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Address</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
IsFlaggedWrongAnnualRevenue	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Annual Revenue</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
IsFlaggedWrongCompanyDunsNumber	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Company D-U-N-S Number</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
IsFlaggedWrongCompanyName	Type boolean

Field Name	Details
	Properties Filter, Update Description Indicates whether the lead's <code>Company Name</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongEmail</code>	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Email</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongIndustry</code>	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Industry</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongName</code>	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Name</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongNumberOfEmployees</code>	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>No. of Employees</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongPhone</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the lead's <code>Phone</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsFlaggedWrongTitle</code>	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Title</code> field value is flagged as wrong to Data.com (<code>true</code>) or not (<code>false</code>).
<code>IsInactive</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the lead has been reported to Data.com as <i>Inactive</i> (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedAddress</code>	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Address</code> field value is in a <i>Reviewed</i> state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedAnnualRevenue</code>	Type boolean Properties Filter, Update Description Indicates whether the lead's <code>Annual Revenue</code> field value is in a <i>Reviewed</i> state (<code>true</code>) or not (<code>false</code>).
<code>IsReviewedCompanyDunsNumber</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the lead's Company D-U-N-S Number field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
IsReviewedCompanyName	Type boolean Properties Filter, Update Description Indicates whether the lead's Company Name field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
IsReviewedDandBCompanyDunsNumber	Type boolean Properties Filter, Update Description Indicates whether the lead's D&B Company D-U-N-S Number field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
IsReviewedEmail	Type boolean Properties Filter, Update Description Indicates whether the lead's Email field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
IsReviewedIndustry	Type boolean Properties Filter, Update Description Indicates whether the lead's Industry field value is in a Reviewed state (<code>true</code>) or not (<code>false</code>).
IsReviewedName	Type boolean Properties Filter, Update

Field Name	Details
	Description Indicates whether the lead's Name field value is in a Reviewed state (true) or not (false).
IsReviewedNumberOfEmployees	Type boolean Properties Filter, Update Description Indicates whether the lead's No. of Employees field value is in a Reviewed state (true) or not (false).
IsReviewedPhone	Type boolean Properties Filter, Update Description Indicates whether the lead's Phone field value is in a Reviewed state (true) or not (false).
IsReviewedTitle	Type boolean Properties Filter, Update Description Indicates whether the lead's Title field value is in a Reviewed state (true) or not (false).
LastMatchedDate	Type dateTime Properties Filter, Sort Description The date the lead record was last matched and linked to a Data.com record.
LastName	Type string Properties Filter, Group, Nillable, Sort Description The lead's last name.

Field Name	Details
LastStatusChangedById	Type reference Properties Filter, Group, Nillable, Sort Description The ID of who or what last changed the record's <code>Clean Status</code> field value: a Salesforce user or a Clean job.
LastStatusChangedDate	Type dateTime Properties Filter, Nillable, Sort Description The date on which the record's <code>Clean Status</code> field value was last changed.
Latitude	Type double Properties Filter, Nillable, Sort Description Used with <code>Longitude</code> to specify the precise geolocation of a billing address. Data not currently provided.
LeadId	Type reference Properties Filter, Group, Sort Description The unique, system-generated ID assigned when the lead record was created.
Longitude	Type double Properties Filter, Nillable, Sort Description Used with <code>Latitude</code> to specify the precise geolocation of a billing address. Data not currently provided.
Name	Type string Properties Filter, Group, Sort, Update

Field Name	Details
	Description Field label is Lead Clean Info Name . The name of the lead. Maximum size is 255 characters.
NumberOfEmployees	Type int Properties Filter, Group, Nillable, Sort Description The number of employees working at the lead.
Phone	Type phone Properties Filter, Group, Nillable, Sort Description The phone number for the lead.
PostalCode	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the lead.
State	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address of the lead.
Street	Type textarea Properties Filter, Group, Nillable, Sort Description Details for the billing address of the lead.
Title	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort
	Description The lead's title.

Usage

Use triggers to map values from fields on imported or cleaned records onto a standard set of values.

LeadFeed

Represents a single feed item in the feed displayed on the detail page for a lead record.

A lead feed shows recent changes to a lead record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to leads in Salesforce. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Lead object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea
	Properties Nillable, Sort
	Description The content of LeadFeed. Required when <code>Type</code> is <code>TextPost</code> . Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code> . This is the message that appears in the feed.

Field	Details
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.

Field	Details
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort

Field	Details
	Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the lead record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist

Field

Details

Properties

Filter, Group, Nillable, Restricted picklist, Sort

Description

The type of feed item:

- **ActivityEvent**—indirectly generated event when a user or the API adds a [Task](#) associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a [Task](#) or [Event](#) associated with a case record (excluding email and call logging).

For a recurring [Task](#) with [CaseFeed](#) disabled, one event is generated for the series only. For a recurring [Task](#) with [CaseFeed](#) enabled, events are generated for the series and each occurrence.

- **AdvancedTextPost**—created when a user posts a group announcement.
- **AnnouncementPost**—Not used.
- **ApprovalPost**—generated when a user submits an approval.
- **BasicTemplateFeedItem**—Not used.
- **CanvasPost**—a post made by a canvas app posts on a feed.
- **CollaborationGroupCreated**—generated when a user creates a public group.
- **CollaborationGroupUnarchived**—Not used.
- **ContentPost**—a post with an attached file.
- **CreatedRecordEvent**—generated when a user creates a record from the publisher.
- **DashboardComponentAlert**—generated when a dashboard metric or gauge exceeds a user-defined threshold.
- **DashboardComponentSnapshot**—created when a user posts a dashboard snapshot on a feed.
- **LinkPost**—a post with an attached URL.
- **PollPost**—a poll posted on a feed.
- **ProfileSkillPost**—generated when a skill is added to a user's Chatter profile.
- **QuestionPost**—generated when a user posts a question.
- **ReplyPost**—generated when Chatter Answers posts a reply.
- **RypplePost**—generated when a user creates a Thanks badge in Work.com.
- **TextPost**—a direct text entry on a feed.
- **TrackedChange**—a change or group of changes to a tracked field.
- **UserStatus**—automatically generated when a user adds a post. Deprecated.

The following values appear in the **Type** picklist for all feed objects but apply only to CaseFeed:

- **CaseCommentPost**—generated event when a user adds a case comment for a case object
- **EmailMessageEvent**—generated event when an email related to a case object is sent or received

Field	Details
	• <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>.

Usage

Use this object to track changes for a lead record. If a lead record is converted, use this object to query and retrieve the associated lead feed items.

LeadHistory

Represents the history of changes to the values in the fields of a lead.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort, Description The name of the field that was changed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
LeadId	Type reference Properties Filter, Group, Sort Description ID of the Lead. Label is Lead ID.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this object to identify changes to a lead.

This object respects field level security on the parent object.

LeadOwnerSharingRule

Represents the rules for sharing a lead with users other than the owner.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference

Field	Details
	Properties Create, Filter, Group, Sort Description The ID representing the source group. Leads owned by users in the source group trigger the rule to give access.
LeadAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing being allowed. The possible values are: • Read • Edit
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the target user or group. The target user or group is being given access.

Usage

Use these objects to manage the sharing rules for leads. General sharing and Territory-related sharing use this object.

LeadShare

Represents a sharing entry on a Lead.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
LeadAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the User or Group has to the Lead. The possible values are: • Read • Edit • All This value is not valid when creating or updating these records. This field must be set to an access level that is higher than the organization's default access level for leads.
LeadId	Type reference Properties Filter, Group, Sort Description ID of the Lead associated with this sharing entry. This field can't be updated.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to <code>Manual</code> (default). Values may include:

Field	Details
	• Manual—The User or Group has access because a user with “All” access manually shared the Lead with them. • Owner—The User is the owner of the Lead. • Rule—The User or Group has access via a Lead sharing rule.
UserOrGroupId	Type reference Properties Filter, Group, Sort Description ID of the User or Group that has been given access to the Lead. This field can't be updated.

Usage

This object allows you to determine which users and groups can view or edit leads owned by other users.

If you attempt to create a record that matches an existing record, the existing record is returned.

LeadStatus

Represents the status of a Lead, such as Open, Qualified, or Converted.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
IsConverted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this lead status value represents a converted lead (<code>true</code>) or not (<code>false</code>). Multiple lead status values can represent a converted lead.
IsDefault	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description Indicates whether this is the default lead status value (<code>true</code>) or not (<code>false</code>) in the picklist.
MasterLabel	Type string Properties Filter, Group, Nillable, Sort Description Master label for this lead status value. This display value is the internal label that does not get translated.
SortOrder	Type int Properties Filter, Group, Nillable, Sort Description Number used to sort this value in the lead status picklist. These numbers are not guaranteed to be sequential, as some previous lead status values might have been deleted.

Usage

This object represents a value in the lead status picklist (see Lead Status Picklist). The lead status picklist provides additional information about the status of a Lead, such as whether a given status value represents a converted Lead. Query this object to retrieve the set of values in the lead status picklist, and then use that information while processing Lead objects to determine more information about a given lead. For example, the application could test whether a given lead is converted based on its `Status` value and the value of the `IsConverted` property in the associated LeadStatus record.

LeadTag

Associates a word or short phrase with a Lead.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference

Field Name	Details
	Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • Public—The tag can be viewed and manipulated by all users in an organization. • Personal—The tag can be viewed or manipulated only by a user with a matching OwnerId.

Usage

LeadTag stores the relationship between its parent TagDefinition and the Lead being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

LimitAllocationPerApp

Represents a connected app quota for an API limit. This object is available in API version 30.0 and later.



Note: LimitAllocationPerApp is currently available through a pilot program. For information on enabling LimitAllocationPerApp for your organization, contact Salesforce.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
ConnectedAppName	Type string Properties Create, Filter, Group, Sort, Update Description The name of the connected app.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the record in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. This field is automatically generated but you can supply your own value if you create the record using the API. Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the MasterLabel.

Field Name	Details
LimitType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of API limit for which you're setting a quota. The available values are: • TotalRequests—Total API requests per 24-hour period • ApiBatchItems—Number of Bulk API batches per 24-hour period • StreamEventsPerDay—Number of Streaming API events per 24-hour period • GenStreamingEventsPerDay—Number of generic streaming events per 24-hour period  Note: Generic streaming is currently available through a pilot program. For information on enabling generic streaming for your organization, contact Salesforce.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description Master label for the API limit quota. This is the internal label that does not get translated.
Percentage	Type int Properties Create, Filter, Group, Sort, Update Description The percentage of the API limit reserved for the connected app. The app can't consume more than this percentage of the API limit. You can find the available percentage for each limit type through the user interface or by using the <code>query()</code> call.

Usage

App quotas for API limits enable you to reserve API capacity for mission-critical connected apps or set a ceiling for API usage of non-critical connected apps.

LineitemOverride

A forecast override of a line item on an Opportunity. This read-only object for customizable forecasting has a child-parent relationship with OpportunityOverride.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

This object is only accessible if your organization has enabled the customizable forecasting feature, which can be done in the user interface. Requires the “View All Data” permission.

Fields

Field	Details
AmountInherited	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the overridden amount rolls up through the forecast hierarchy (<code>true</code>), or was overridden by the owner of this record (<code>false</code>).
ForecastCategoryInherited	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the overridden forecast category rolls up through the forecast hierarchy (<code>true</code>), or was overridden by the owner of this record (<code>false</code>).
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.

Field	Details
OpportunityId	Type reference Properties Create, Filter, Group, Sort Description ID of the associated Opportunity.
OpportunityLineItemId	Type reference Properties Create, Filter, Group, Sort Description ID of the associated OpportunityLineItem.
OverrideAmount	Type currency Properties Create, Filter, Sort, Update Description The total monetary amount of the line item, which may be overridden.
OverrideForecastCategory	Type picklist Properties Create, Filter, Group, Sort, Update Description The forecast category of the line item. Can be overridden.
OverrideQuantity	Type double Properties Create, Filter, Sort, Update Description The quantity of the line item, which may be overridden.
OverrideUnitPrice	Type currency Properties Create, Filter, Sort, Update Description The monetary amount of the unit price. Can be overridden.

Field	Details
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort Description ID of the owner of this record.
QuantityInherited	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the overridden quantity rolls up through the forecast hierarchy (<code>true</code>), or is overridden by the owner of this record (<code>false</code>).
UnitPriceInherited	Type boolean Properties Defaulted on create, Filter Description Indicates whether the overridden unit price rolls up through the forecast hierarchy (<code>true</code>), or was overridden by the owner of this record (<code>false</code>).

ListView

Represents a list view. A list view specifies a set of records for an object, based on specific criteria.

This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Name	Details
CreatedBy	Type User Properties Filter, Query, Retrieve, Sort

Name	Details
	Description The name of the user who created the list view.
	Type string Properties Filter, Query, Retrieve, Sort
	Description The fully qualified developer name of the list view.
IsSoqlCompatible	Type boolean
	Properties Filter, Query, Retrieve, Sort
	Description Whether the list view can be used with SOQL..
LastModifiedBy	Type User
	Properties Filter, Query, Retrieve, Sort
	Description The name of the user who last modified the list view.
LastModifiedById	Type ID
	Properties Filter, Query, Retrieve, Sort
	Description The ID of the user who last modified the list view.
LastModifiedDate	Type dateTime
	Properties Filter, Query, Retrieve, Sort
	Description The date and time of the last modification of the list view, with a precision of one second.
LastReferencedDate	Type dateTime
	Properties Filter, Query, Retrieve, Sort

Name	Details
	Description The date and time when the list view was last referenced, with a precision of one second.
LastViewedDate	Type dateTime Properties Filter, Query, Retrieve, Sort Description The date and time when the list view was last viewed, with a precision of one second.
Name	Type string Properties Filter, Query, Retrieve, Sort Description The name of the list view.
NamespacePrefix	Type string Properties Filter, Query, Retrieve, Sort Description The namespace of the list view.
SubjectType	Type string Properties Filter, Query, Retrieve, Sort Description The API name of the sObject for the list view.

ListViewChart

Represents a graphical chart that's displayed on Salesforce1 list views. The chart aggregates data that is filtered based on the list view that's currently displayed.

This object is available in API version 33.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Name	Description
AggregateField	Type string Properties Create, Filter, Query, Restricted picklist, Retrieve, Sort, Update Description The field that's used for calculating data on each group. AggregateField can't be the same as GroupingField.
AggregateType	Type picklist Properties Create, Filter, Query, Retrieve, Sort, Update Description The type of calculations to run on each group. The supported AggregateType values are Count, Sum, and Avg.
ChartType	Type picklist Properties Create, Filter, Query, Retrieve, Sort, Update Description The type of chart to create. The supported chart types are horizontal bar chart, vertical bar chart, and donut chart.
DeveloperName	Type string Properties Create, Filter, Query, Retrieve, Sort, Update Description The fully qualified developer name of the chart.
GroupingField	Type string Properties Create, Filter, Query, Retrieve, Sort, Update Description The field that's used to divide the data into collections. The field has to be supported by SQL GROUP BY functionality. GroupingField can't be the same as AggregateField.

Name	Description
MasterLabel	Type string Properties Create, Filter, Query, Retrieve, Sort, Update Description The label for the chart.
OwnerId	Type ID Properties Defaulted on create, Filter, Query, Retrieve, Sort Description The ID of the user who owns the chart.
SubjectType	Type string Properties Create, Filter, Query, Retrieve, Sort Description The API name of the sObject for the chart.

ListViewChartInstance

Retrieves metadata for all standard and custom charts for a given entity in context of a given list view.

This object is available in API versions 34.0 and later.

Supported Calls

`describeSObjects()`, `query()`

Fields

Field Name	Details
AggregateField	Type string Properties Filter, Group, Sort

Field Name	Details
	Description The field that's used for calculating data on each group. <code>AggregateField</code> can't be the same as <code>GroupingField</code>.
AggregateType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of calculations to run on each group. The supported <code>AggregateType</code> values are <code>Count</code>, <code>Sum</code>, and <code>Avg</code>.
ChartType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of chart to create. The supported chart types are horizontal bar chart, vertical bar chart, and donut chart.
DataQuery	Type textarea Properties Filter, Nillable, Sort Description The SOQL query that can be executed to fetch the data for drawing a chart.
DeveloperName	Type string Properties Filter, Group, Sort Description API name of the chart. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.

Field Name	Details
ExternalId	Type string Properties Filter, Group, Nillable, Sort Description Reserved for future use.
GroupingField	Type string Properties Filter, Group, Sort Description The field that's used to divide the data into collections. The field has to be supported by SOQL GROUP BY functionality. GroupingField can't be the same as AggregateField.
IsDeletable	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates if the chart can be deleted.
IsEditable	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates if the chart can be edited. Standard charts are not editable.
IsLastViewed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates if a chart is the last viewed by a user.
Label	Type string Properties Filter, Group, Sort

Field Name	Details
	Description The display name of the chart.
ListViewChartId	Type reference Properties Filter, Group, Sort Description ID of the chart created by a user. For standard charts, this is null.
ListViewContextId	Type reference Properties Filter, Group, Sort Description ID of the list view in context of which the chart is generated. Required to query ListViewChartInstance.
SourceEntity	Type string Properties Filter, Group, Sort Description API name of the entity to which the chart is related. Required to query ListViewChartInstance.

Usage

Example 1. Retrieve all custom and standard charts for Account entity for All Accounts list view

```
SELECT AggregateField, AggregateType, ChartType, DataQuery, DeveloperName, ExternalId,
GroupingField, Id, IsDeletable, IsEditable, IsLastViewed, Label, ListViewChartId,
ListViewContextId, SourceEntity FROM ListViewChartInstance WHERE SourceEntity='Account'
and ListViewContextId='00BR0000000U8Hr'
```

Example 2. Retrieve metadata for a specific custom chart by ID for Account entity and All Accounts list view

```
SELECT AggregateField, AggregateType, ChartType, DataQuery, DeveloperName, ExternalId,
GroupingField, Id, IsDeletable, IsEditable, IsLastViewed, Label, ListViewChartId,
ListViewContextId, SourceEntity FROM ListViewChartInstance WHERE SourceEntity='Account'
and ListViewContextId='00BR0000000U8Hr' and ListViewChartId='0DdR00000004CBxKAM'
```

Example 3. Retrieve metadata for a specific standard chart by its developer name for Account entity and All Accounts list view

```
SELECT AggregateField, AggregateType, ChartType, DataQuery, DeveloperName, ExternalId,
    GroupingField, Id, IsDeletable, IsEditable, IsLastViewed, Label, ListViewChartId,
    ListViewContextId, SourceEntity FROM ListViewChartInstance WHERE SourceEntity='Account'
    and ListViewContextID='00BR0000000U8Hr' and DeveloperName='AccountsByIndustry'
```

LiveAgentSession

This object is automatically created for each Live Agent session and stores information about the session. This object is available in API versions 28.0 and later.



Note: Standard fields for the LiveAgentSession object can only be modified if your administrator has given you editing permissions for these records.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`

Fields

Field Name	Details
AgentId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the agent associated with the session.
ChatReqAssigned	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of chat requests that were assigned to an agent during a session.
ChatReqDeclined	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of chat requests that were declined by an agent during a session.

Field Name	Details
ChatReqEngaged	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of chats in which an agent was engaged during a session.
ChatReqTimedOut	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of chat requests that timed out in an agent's queue during a session.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time that the session record was last referenced.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time that the session record was last viewed.
LoginTime	Type dateTime Properties Create, Filter, Sort, Update Description The date and time an agent logged in during the session.
LogoutTime	Type dateTime Properties Create, Filter, Sort, Update Description The date and time an agent logged out during a session.

Field Name	Details
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookupSort Description The name of the session.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the session record.
TimeAtCapacity	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The amount of time an agent spent with the maximum number of chats in his or her queue.
TimeIdle	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The amount of time an agent spent idle during the session.
TimeInAwayStatus	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The amount of time an agent spent with a status of "Away" during a session.
TimeInChats	Type int Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The amount of time an agent spent engaged in chats during a session.
TimeInOnlineStatus	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The amount of time an agent spent with a status of "Online" during a session.

Usage

Use this object to query and manage live chat session records.

LiveAgentSessionHistory

This object is automatically created for each Live Agent session and stores information about changes made to the session. This object is available in API versions 28.0 and later.



Note: Standard fields for the LiveAgentSession object can only be modified if your administrator has given you editing permissions for these records.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed in a session record.
LiveAgentSessionId	Type reference Properties Filter, Group, Sort

Field Name	Details
	Description ID of the session record that was changed.
newValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
oldValue	Type anyType Properties Nillable, Sort Description The original value of the field that was changed.

Usage

Use this object to identify changes to live chat session records.

LiveAgentSessionOwnerSharingRule

Represents the rules for sharing a Live Agent session record with users other than the record owner.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
AccessLevel	Type picklist Properties Create, Filter, Group, restrictedPicklist, Sort, Update Description Determines the level of access users have to session records. Specifies whether or not users can read, edit, or transfer session records. Corresponds to the Default Access column in the UI.

Field	Details
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the UI.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. Session records owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label in the UI.
UserOrGroupId	Type reference

Field	Details
	Properties Create, Filter, Group, Sort
	Description The ID representing the target user or group. The target user or group is being given access.

Usage

Use this object to manage the sharing rules for Live Agent session records.

LiveAgentSessionShare

This object is automatically created for each Live Agent session and stores information about the session. This object is available in API versions 28.0 and later.



Note: Standard fields for the LiveAgentSession object can only be modified if your administrator has given you editing permissions for these records.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccessLevel</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Level of access that the User or Group has to the LiveAgentSession. The possible values are: • Read • Edit • All (This value is not valid for <code>create()</code> or <code>update()</code> calls.) This value must be set to an access level that is higher than the organization's default access level for live chat transcripts.
<code>ParentId</code>	Type reference

Field Name	Details
	Properties Create, Filter, Group, Sort Description ID of the parent object, if any.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Values can include: • Manual—The user or group has access because a user with “All” access manually shared the LiveAgentSession with them. • Owner—The user is the owner of the LiveAgentSession or is in a role above the QuickText owner in the role hierarchy.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that has been given access to the LiveAgentSession.

Usage

This object lets you determine which users and groups can view and edit LiveAgentSession records owned by other users.

If you attempt to create a new record that matches an existing record, the `create()` call updates any modified fields and returns the existing record.

LiveChatBlockingRule

Represents a rule for blocking chat visitors' IP addresses from starting new chats with agents. This object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
Description	Type string Properties Create, Nillable, Update Description The description of the blocking rule—for example, the reason why the given IP address or range of addresses is being banned from starting new chats.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
FromIpAddress	Type string Properties Create, Filter, Group, Sort, Update Description The IP address of the user that you want to block, or the beginning of the range of IP addresses you want to block. If you want to block a range of IP addresses, indicate the end of the range in the <code>ToIpAddress</code> field. If you don't indicate an IP address in the <code>ToIpAddress</code> field, the only IP address that will be blocked is the IP address in the <code>FromIpAddress</code> field.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field Name	Details
	Description The language of the blocking rule.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description Label for the blocking rule.
ToIpAddress	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description (Optional) The end of the range of IP addresses that you want to block. The range begins with and includes the IP address in the <code>FromIpAddress</code> field, and it ends with and includes the IP address in the <code>ToIpAddress</code> field.

Usage

Use this object to query and manage rules for blocking customers from starting new chats with agents.

LiveChatButton

Represents a button that allows visitors to request chats with Live Agent users. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
Animation	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field Name	Details
	Description The type of animation used when an automated chat invitation appears on-screen. For automated chat invitations only. Available in API version 29.0 and later.
AutoGreeting	Type textarea Properties Create, Filter, Nillable, Sort, Update Description The text that is automatically sent from an agent to a visitor when a chat session starts.  Note: A greeting message in the <code>AutoGreeting</code> field of the <code>LiveChatButton</code> object overrides individual users' greeting messages in the <code>AutoGreeting</code> field in the <code>LiveChatUserConfig</code> object.
ChatPageId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the custom Visualforce page that contains the custom chat window code.
CustomAgentName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The custom name of the agent associated with the button. Available in API version 29.0 and later.  Note: A custom agent name in the <code>CustomAgentName</code> field of the <code>LiveChatButton</code> object overrides individual users' custom agent name in the <code>CustomAgentName</code> field in the <code>LiveChatUserConfig</code> object.
CustomRoutingClassId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the Apex class you customize to create your custom routing rules if <code>RoutingType</code> equals <code>Custom</code>. Available in API version 29.0 and later.

Field Name	Details
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
HasQueue	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether to allow incoming chat requests to queue until an agent is available.
InviteEndPosition	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The position on-screen where an automated chat invitation's animation ends.  Note: You don't need to select an end position for your automated chat invitation if you use a custom animation. For automated chat invitations only. Available in API version 29.0 and later.
InviteImageId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the static image resource displayed on your automated chat invitation. For automated chat invitations only. Available in API version 29.0 and later.

Field Name	Details
InviteStartPosition	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The position on-screen where an automated chat invitation's animation begins.  Note: You don't need to select a start position for your automated chat invitation if you use a custom animation. For automated chat invitations only. Available in API version 29.0 and later.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description For automated chat invitations, specifies whether an automated chat invitation is active and able to be sent to customers (<code>true</code>) or not (<code>false</code>). For chat buttons, this is set to <code>true</code> by default.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The language of the chat.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description Label for the live chat button.
NumberOfReroutingAttempts	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Specifies the number of times a chat request can be rerouted to available agents if all agents reject the chat request.

Field Name	Details
OfflineImageId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the static image resource that is displayed when the button is offline (inactive).
OnlineImageId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the static image resource that is displayed when the button is online (active).
OptionsHasInviteAfterAccept	Type boolean Properties Create, Filter, Update Description Specifies whether an automated chat invitation can be sent to a customer after that customer has accepted a prior automated chat invitation (<code>true</code>) or not (<code>false</code>). For automated chat invitations only. Available in API version 29.0 and later.
OptionsHasInviteAfterReject	Type boolean Properties Create, Filter, Update Description Specifies whether an automated chat invitation can be sent to a customer after that customer has rejected a prior automated chat invitation (<code>true</code>) or not (<code>false</code>). For automated chat invitations only. Available in API version 29.0 and later.
OptionsHasRerouteDeclinedRequest	Type boolean Properties Create, Filter, Update

Field Name	Details
	Description Specifies whether a chat request that has been rejected by all available agents should be rerouted to available agents again (<code>true</code>) or not <code>false</code>).
<code>OptionsIsAutoAccept</code>	Type boolean Properties Create, Filter, Update Description Specifies whether a chat request should be automatically accepted by the agent it's assigned to (<code>true</code>) or not <code>false</code>). For chat buttons and automated chat invitations with <code>RoutingType</code> set to <code>Most Available</code> or <code>Least Active</code> . Available in API version 30.0 and later.
<code>OptionsIsInviteAutoRemove</code>	Type boolean Properties Create, Filter, Update Description Specifies whether an automated chat invitation should be automatically removed from the screen after a certain amount of time (<code>true</code>) or not (<code>false</code>). For automated chat invitations only. Available in API version 29.0 and later.
<code>OverallQueueLength</code>	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The maximum number of chat requests allowed to queue.
<code>PerAgentQueueLength</code>	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The maximum number of chat requests allowed to queue for each agent with the required skill.
<code>PostchatPageId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The record ID of the custom Visualforce page displayed when the chat ends.
PostchatUrl	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The URL the user is directed to after the chat ends.
PrechatFormPageId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the custom Visualforce page displayed before the chat begins.
PrechatFormUrl	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The URL the user is directed to before the chat begins.
PushTimeout	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of seconds an agent has to answer a chat request before it's routed to the next available agent.
RoutingType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description How chat requests are routed to agents. The values are: • Choice—Incoming chat requests are added to the queue in Live Agent in the Salesforce console and are available to any agent with the required skill. • Least Active—Incoming chats are routed to the agent with the required skill who has the fewest active chats.

Field Name	Details
	Most Available—Incoming chats are routed to the agent with the required skill and the greatest difference between chat capacity and active chat sessions. For example, if Agent A and Agent B each have a chat capacity of five, and Agent A has three active chat sessions while Agent B has one, incoming chats will be routed to Agent B. Custom—Incoming chats are routed to agents based on the custom routing rules specified in the Apex class you use to create them.
SiteId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the site used for loading static resources and custom Visualforce pages.
SkillId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the skill used to route incoming chat requests. To associate multiple skills with a live chat button, reference one skill in the <code>SkillId</code> field and use <code>LiveChatButtonSkill</code> junction objects for the remaining skills.
TimeToRemoveInvite	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of seconds an automated invitation stays on-screen before it is automatically removed. For automated chat invitations only. Available in API version 29.0 and later.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of element to display to customers (either a chat button or an automated invitation).

Field Name	Details
WindowLanguage	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The language used for standard chat windows. Custom chat windows use the language of the user's browser.

Usage

Use this object to query and manage live chat buttons and automated chat invitations.

LiveChatButtonDeployment

Associates a Live Agent automated chat invitation with a specific deployment. This object is available in API versions 28.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
ButtonId	Type reference Properties Create, Filter, Group, Sort Description The ID of the automated invitation associated with the deployment.
DeploymentId	Type reference Properties Create, Filter, Group, NillableSort Description The ID of the deployment that will feature the automated invitation.

Usage

Use this object to associate automated chat invitations with specific deployments.

LiveChatButtonSkill

Represents all the skills available to a LiveChatButton except the one currently assigned. To retrieve the skill currently assigned, query LiveChatButton.

Supported Calls

`create()`, `delete()`, `query()`, `update()`

Fields

Field Name	Details
ButtonID	Type reference Properties Create, Filter, Group, Sort Description The record ID of the button.
SkillID	Type reference Properties Create, Filter, Group, Nillable, Sort Description The record ID of the skill.

Usage

Use this object to assign a specific skill to a specific button for multi-skill routing. For example:

```
String myButtonId = button_Id;  
String myButtonDevName = button_DeveloperName;  
List<String> skillIds = new List<String>();  
  
//Get one skill ID from button  
for(LiveChatButton lcb : [Select SkillId FROM LiveChatButton WHERE DeveloperName =:  
myButtonDevName]) {  
    skillIds.add(lcb.SkillId);  
}  
//Get remaining skills from LiveChatButtonSkill join object
```

```
for(LiveChatButtonSkill lcbs : [Select SkillID FROM LiveChatButtonSkill WHERE ButtonId =:
myButtonId]) {
skillIds.add(lcbs.SkillId);
}
//Retrieve all skills into a single list
List<Skill> skills = [Select Id, DeveloperName from Skill WHERE Id IN :SkillIds];
```

LiveChatDeployment

Represents the general settings for deploying Live Agent on a website. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
BrandingId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the static image resource that's displayed in the chat window
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Domains	Type textarea

Field Name	Details
	Properties Create, Filter (unavailable in API version 25.0 and later), Nillable, Sort (unavailable in API version 25.0 and later), Update Description A comma-separated list of domains the deployment is whitelisted for. Leave this blank to allow the deployment to be used on any domain.
HasTranscriptSave	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether visitors can download and save transcripts from the chat window
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the deployment
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The name of the deployment
MobileBrandingId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the static image resource displayed in the mobile version of the chat window
OptionsHasPrechatApi	Type boolean Properties Create, Filter, Update

Field Name	Details
	Description Determines whether developers can access the Pre-Chat API
SiteId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the site used for loading static resources
WindowTitle	Type string Properties Create, Filter, Group, Sort, Update Description The text displayed in the title bar of the browser window used to launch the chat window

Usage

Use this object to query and manage live chat deployments.

LiveChatTranscript

This object is automatically created for each Live Agent chat session and stores information about the session. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
Abandoned	Type int Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description The amount of time in seconds an incoming chat request remained unanswered by an agent before the chat was disconnected by the customer.
AccountId	Type ID Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the account associated with the chat transcript.
AverageResponseTimeOperator	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The agent's average response time (in seconds) to chat messages from the visitor.
AverageResponseTimeVisitor	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The visitor's average response time (in seconds) to chat messages from the agent.
Body	Type textarea Properties Create, Nillable, Update Description The contents of the chat.
Browser	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The browser the visitor used for the chat.
BrowserLanguage	Type string

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The language of the visitor's browser.
CaseID	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the case associated with the chat transcript.
ChatDuration	Type int Properties Filter, Group, Nillable, Sort Description The total duration of the chat in seconds.
ChatKey	Type string Properties Create, Filter, Group, idLookup, Nillable, Sort Description The session ID of the chat before it is persisted. ChatKey can be used with advanced integrations in the Salesforce console. This field is available in API version 25.0 and later.
ContactID	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the contact associated with the chat transcript.
EndedBy	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The way the chat was ended: by the operator, the visitor, or the system.

Field Name	Details
EndTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The time the chat ended.
IpAddress	Type string Properties Create, Filter, Nillable, Sort, Update Description The visitor's IP address.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
LeadID	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the lead associated with the chat transcript.
LiveChatButtonID	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The ID of the LiveChatButton the chat session originated from.
LiveChatDeploymentID	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Type The ID of the LiveChatDeployment the chat session originated from.
LiveChatVisitorID	Type reference Properties Create, Filter, Group, Sort Description The ID of the visitor associated with the chat transcript.
Location	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The best-guess approximation of the visitor's location.
MaxResponseTimeOperator	Type int Properties Filter, Group, Nillable, Sort Description The maximum time in seconds it took an agent to respond to a chat visitor's message.
MaxResponseTimeVisitor	Type int Properties Filter, Group, Nillable, Sort Description The maximum time in seconds it took a customer to respond to an agent's message.
Name	Type string

Field Name	Details
	Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The name of the transcript.
OperatorMessageCount	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of messages sent by agent(s) during the chat.
OwnerID	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The ID of the operator who participated in the chat last; for missed chats, this is a system user.
Platform	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The visitor's operating system platform.
ReferrerUri	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Where the chat request originated.
RequestTime	Type dateTime Properties Create, Filter, Nillable. Sort, Update Description The time the visitor requested the chat.

Field Name	Details
ScreenResolution	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The visitor's screen resolution.
SkillId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The record ID of the primary Skill associated with the LiveChatButton the chat session originated from. To associate multiple skills with a LiveChatTranscript, use LiveChatTranscriptSkill junction objects.
StartTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The time the chat started.
Status	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The final status of the chat: completed, missed, dropped or blocked.
SupervisorTranscriptBody	Type textarea Properties Create, Nillable, Update Description The text body of the supervisor's chat transcript.
UserAgent	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The visitor's user agent string.
VisitorMessageCount	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The number of messages sent by the visitor during the chat.
WaitTime	Type int Properties Filter, Group, Nillable, Sort Description The total amount of time in seconds a chat request was waiting to be accepted by an agent.

Usage

Use this object to query and manage live chat transcripts.

LiveChatTranscriptEvent

Captures specific events that occur over the lifetime of a chat. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelele()`, `update()`, `upsert()`

Fields

Field Name	Details
AgentId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the agent associated with the event.

Field Name	Details
Detail	Type string Properties Create, Filter, Group, Nillable, Sort Description Details associated with the event.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
LiveChatTranscriptId	Type reference Properties Create, Filter, Group, Sort Description The ID of the live chat transcript associated with the event.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The name of the event.
Time	Type dateTime Properties Create, Filter, Sort

Field Name	Details
	Description The time at which the event happened.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The kind of event that occurred.

Usage

Use this object to query and manage live chat transcript events.

LiveChatTranscriptHistory

Represents changes to field values on a LiveChatTranscript object. This object is available in API version 24.0 and later.

Supported Calls

`getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed
LiveChatTranscriptID	Type reference Properties Filter, Group, Sort Description The ID of the transcript that was changed

Field Name	Details
newValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed
oldValue	Type anyType Properties Nillable, Sort Description The old value of the field that was changed

Usage

Use this object to identify changes to a live chat transcript.

LiveChatTranscriptOwnerSharingRule

Represents the rules for sharing a Live Agent chat transcript record with users other than the record owner.

Supported Calls

`create()`, `delete()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
AccessLevel	Type picklist Properties Create, Filter, Group, restrictedPicklist, Sort, Update Description Determines the level of access users have to chat transcript records. Specifies whether or not users can read, edit, or transfer chat transcript records. Corresponds to the Default Access column in the UI.
Description	Type textarea

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the UI.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. Chat transcript records owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label in the UI.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description The ID representing the target user or group. The target user or group is being given access.

Usage

Use this object to manage the sharing rules for Live Agent chat transcript records.

LiveChatTranscriptShare

Represents a sharing entry on a LiveChatTranscript object. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Level of access that the User or Group has to the LiveChatTranscript. The possible values are: • Read • Edit • All (This value is not valid for <code>create()</code> or <code>update()</code> calls.) This value must be set to an access level that is higher than the organization's default access level for live chat transcripts.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the parent object, if any

Field Name	Details
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Values may include: Manual—The User or Group has access because a user with “All” access manually shared the LiveChatTranscript with them. Owner—The User is the owner of the LiveChatTranscript or is in a role above the QuickText owner in the role hierarchy.
UserOrGroupID	Type reference Properties Create, Filter, Group, Sort Description ID of the User or Group that has been given access to the LiveChatTranscript.

Usage

This object lets you determine which users and groups can view and edit LiveChatTranscript records owned by other users.

If you attempt to create a new record that matches an existing record, the `create()` call updates any modified fields and returns the existing record.

LiveChatTranscriptSkill

Represents a join between LiveChatTranscript and Skill.

Supported Calls

`create()`, `delete()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`

Fields

Field Name	Details
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort

Field Name	Details
	Description The name of the transcript.
SkillID	Type reference Properties Create, Filter, Group, Nillable, Sort Description The record ID of the skill.
TranscriptID	Type reference Properties Create, Filter, Group, Sort Description The record ID of the transcript.

Usage

Use this object to assign a specific skill to a specific transcript for multi-skill routing.

LiveChatUserConfig

Represents a setting that controls the console settings for Live Agent users. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AutoGreeting	Type textarea Properties Create, Nillable, Update Description The text that is automatically sent from an agent to a visitor when a chat session starts.

Field Name	Details
Capacity	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Limits the number of active chat session an agent can engage in.
CriticalWaitTime	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The amount of time before a chat flashes to alert an agent to answer it.
CustomAgentName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The custom name of the agent associated with the Live Agent configuration.
DeveloperName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
HasCrmChatlet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field Name	Details
	Description Determines whether the CRM chatlet appears in the agent console.
HasDetailsChatlet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether the Details chatlet appears in the agent console.
HasHistoryChatlet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether the History chatlet appears in the agent console.
HasKnowledgeChatlet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether the Knowledge chatlet appears in the agent console.
HasLivetrackChatlet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether the Livetrack chatlet appears in the agent console.
HasLogoutSound	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether a sound plays when an agent logs out of the console.
HasMapChatlet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field Name	Details
	Description Determines whether the Map chatlet appears in the agent console.
HasNotifications	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether desktop notifications are enabled for the configuration. Available in API version 25.0 and later.
HasQueueChatlet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether the Queue chatlet appears in the agent console.
HasRequestSound	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether a sound plays when a chat request comes in.
HasSneakPeek	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether an agent sees a real-time preview of the messages a visitor types.
IsAutoAwayOnDecline	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Determines whether agents' status is automatically changed to Away when they decline a chat request. Available in API version 26.0 and later.

Field Name	Details
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the configuration.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The name of the configuration.
OptionsHasAgentFileTransfer	Type boolean Properties Create, Filter, Update Description Determines whether agents can initiate a file transfer from a chat customer. Available in API version 31.0 and later.
OptionsHasAgentSneakPeek	Type boolean Properties Create, Filter, Update Description Determines whether Sneak Peek is enabled for agents. Available in API version 29.0 and later.
OptionsHasChatConferencing	Type boolean Properties Create, Filter, Update Description Determines whether agents can invite other agents into a customer chat. Available in API version 34.0 and later.
OptionsHasChatMonitoring	Type boolean Properties Create, Filter, Update

Field Name	Details
	Description Determines whether supervisors can view agents' ongoing chats. Available in API version 29.0 and later.
OptionsHasChatTransfer	Type boolean Properties Create, Filter, Update Description Determines whether an agent can transfer a chat to other agents. Available in API version 31.0 and later.
OptionsHasVisitorBlocking	Type boolean Properties Create, Filter, Update Description Determines whether an agent has the ability to block troublesome visitors by IP address. Available in API version 34.0 and later.
OptionsHasWhisperMessage	Type boolean Properties Create, Filter, Update Description Determines whether supervisors can send private messages to agents within an agent's chat with a customer. Available in API version 29.0 and later.
OptionsIsAutoAwayOnPushTimeout	Type boolean Properties Create, Filter, Update Description Determines whether an agent's status automatically changes to Away if the agent doesn't respond to a chat request within the specified push time-out limit. Available in API version 34.0 and later.
SupervisorDefaultAgentStatus	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field Name	Details
	Description The default agent status by which to filter agents in the Agent Status list in the supervisor panel.
SupervisorDefaultButtonId	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The default button ID by which to filter agents in the Agent Status list in the supervisor panel.
SupervisorDefaultSkillId	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The default skill ID by which to filter agents in the Agent Status list in the supervisor panel.

Usage

Use this object to query and manage agent configurations in Live Agent.

LiveChatUserConfigProfile

Represents a join between LiveChatUserConfig and Profile. This object is available in API version 24.0 and later.

Supported Calls

`create()` `delete()` `query()` `retrieve()` `update()` `upsert()`

Fields

Field Name	Details
LiveChatUserConfigId	Type reference Properties Create, Filter, Group, Sort

Field Name	Details
	Description The record ID of the agent configuration
ProfileId	Type reference Properties Create, Filter, Group, Sort Description The record ID of the profile

Usage

Use this object to assign specific agent configurations to specific user profiles.

LiveChatUserConfigUser

Represents a join between LiveChatUserConfig and User. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
LiveChatUserConfigId	Type reference Properties Create, Filter, Group, Sort Description The record ID of the agent configuration
UserId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The record ID of the user

Usage

Use this object to assign specific agent configurations to specific users.

LiveChatVisitor

Represents a website visitor who has started or tried to start a chat session. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>LastReferencedDate</code>	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
<code>LastViewedDate</code>	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
<code>Name</code>	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description The name of the visitor
<code>SessionKey</code>	Type string Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description The session key used to uniquely identify the visitor

Usage

Use this object to query and manage live chat visitors.

LoginGeo

Represents the geographic location of the user's IP address for a login event. Due to the nature of geolocation technology, the accuracy of geolocation fields (for example, country, city, postal code) may vary. This object is available in API version 34.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Only users with Manage Users permissions can access this object.

Fields

Field	Details
City	Type string Properties Filter, Group, Nillable, Sort Description The city where the user's IP address is physically located. This value is not localized.
Country	Type string Properties Filter, Group, Nillable, Sort Description The country where the user's IP address is physically located. This value is not localized.
CountryIso	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description The ISO 3166 code for the country where the user's IP address is physically located. For more information, see Country Codes - ISO 3166
Latitude	Type double Properties Filter, Nillable, Sort Description The latitude where the user's IP address is physically located.
LoginTime	Type dateTime Properties Filter, Sort Description Time of the login attempt, in GMT time zone.
Longitude	Type double Properties Filter, Nillable, Sort Description The longitude where the user's IP address is physically located.
PostalCode	Type string Properties Filter, Group, Nillable, Sort Description The postal code where the user's IP address is physically located. This value is not localized.
Subdivision	Type string Properties Filter, Group, Nillable, Sort Description The name of the subdivision where the user's IP address is physically located. In the U.S., this value is usually the state name (for example, Pennsylvania). This value is not localized.

Usage

The API allows you to do many powerful queries. A few examples are:

Sample Query	Query String
Query showing the country for a login event, where Id=LoginGeoId from AuthSession	<code>SELECT Country FROM LoginGeo WHERE Id = 'OLE#####'</code>
Query showing the city and postal code for a login event, where Id=LoginGeoId from LoginHistory	<code>SELECT City, PostalCode FROM LoginGeo WHERE Id = 'OSO#####'</code>

LoginHistory

Represents the login history for all successful and failed login attempts for organizations and enabled portals.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Only users with Manage Users permissions can access this object.

Fields

Field	Details
ApiType	Type string Properties Group, Nillable, Sort Description Indicates the API type, for example Soap Enterprise. Label is API Type .
APIVersion	Type string Properties Group, Nillable, Sort Description Displays the API version used by the client. Label is API Version .
Application	Type string

Field	Details
	Properties Group, Nillable, Sort Description The application used to access the organization. Label is Application.
AuthenticationServiceId	Type reference Properties Filter, Group, Nillable, Sort Description The 18-character ID for an authentication service for a login event. For example, you can use this field to identify the SAML or authentication provider configuration with which the user logged in. This field is available in API version 34.0 and later. Label is Authentication Service Id.
Browser	Type string Properties Group, Nillable, Sort Description The current browser version. Label is Browser.
ClientVersion	Type string Properties Group, Nillable, Sort Description Version of the API client. Label is Client Version.
LoginGeoId	Type reference Properties Filter, Group, Nillable, Sort Description The 18-character ID for the record of the geographic location of the user for a successful or unsuccessful login event. Due to the nature of geolocation technology, the accuracy of geolocation fields (for example, country, city, postal code) may vary. This field is available in API version 34.0 and later.
LoginTime	Type dateTime

Field	Details
	Properties Filter, Nillable, Sort Description Time zone is based on GMT. Label is Login Time.
LoginType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of login, for example, Application. Label is Login Type.
LoginUrl	Type string Properties Filter, Group, Nillable, Sort Description URL from which the login request is coming. Label is Login URL.
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the community that the user is logging in to. This field is available in API version 31.0 and later, if Salesforce Communities is enabled for your organization.
Platform	Type string Properties Group, Nillable, Sort Description Operating system on the login machine. Label is Platform.
SourceIp	Type string Properties Group, Nillable, Sort Description IP address of the machine from which the login request is coming. This can be an IPv4 or IPv6 address in API version 23.0 or later. In API version 22.0 or earlier, this is an IPv4 address, and IPv6 addresses are null. Label is Source IP.

Field	Details
Status	Type string Properties Group, Nillable, Sort Description Displays the status of the attempted login. Status is either success or a reason for failure. Label is Status.
UserId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user logging in. Label is User ID.

Usage

Not all fields are filterable. You can only filter on the following fields:

- AuthenticationServiceId
- Id
- LoginTime
- LoginType
- LoginUrl
- NetworkId
- UserId

The API allows you to do many powerful queries. A few examples are:

Sample Query	Query String
Simple query showing UserId & LoginTime for each user	<code>SELECT UserId, LoginTime from LoginHistory;</code>
Query showing logins only after a specified date and time	<code>SELECT UserId, LoginTime from LoginHistory WHERE LoginTime > 2010-09-20T22:16:30.000Z;</code>
Query showing logins for a specific time interval	<code>SELECT UserId, LoginTime from LoginHistory WHERE LoginTime > 2010-09-20T22:16:30.000Z AND LoginTime < 2010-09-21T22:16:30.000Z;</code>
Query showing the authentication service for a SAML login event, where Id=AuthenticationServiceId from LoginHistory	<code>SELECT name, issuer, samlVersion FROM SamlSsoConfig WHERE Id = '0LE#####'</code>

Sample Query

Query showing the authentication service for an authentication provider login event, where
 Id=AuthenticationServiceId from LoginHistory

Query String

```
SELECT Type, DeveloperName FROM
AuthProvider WHERE Id =
'OSO#####'
```

LoginIp

Represents a validated IP address. This object is available in version 28.0 and later.

Supported Calls

`describeSObjects()`, `delete()`, `query()`, `retrieve()`

Fields

Field	Details
ChallengeMethod	Type picklist Properties Filter, Nillable, Sort Description The challenge method used to confirm the user's identity. Possible values include the following. - Email - SMS - TOTP_CHOICE: The user chooses two-factor authentication. - TOTP_ONLY: The user is required to use two-factor authentication.
ChallengeSentDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time that the user was authenticated.
IsAuthenticated	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If <code>true</code>, the user has already been authenticated.

Field	Details
SourceIp	Type string Properties Filter, Group, Nillable, Sort Description The IP address the user logged in from.
UsersId	Type reference Properties Filter, Group, Sort Description The ID of the user associated with this item.

Usage

At every login, the IP address of the login request is checked against the validated IP addresses using LoginIp. A match means the login IP address is a known IP address. If there's no match, the address is unknown, and the user is asked to confirm their identity.

LookedUpFromActivity

This read-only object is displayed as a related list on an activity record (an event or a task); the list contains records that have custom lookup relationships from the activity to another object. This object is not queryable.

Supported Calls

`describeSObjects()`

Fields

Field Name	Details
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the related account, which is determined as follows: • The account associated with the <code>whatId</code>, if it exists; or • The account associated with the <code>whoId</code>, if it exists; otherwise

Field Name	Details
	• null For information on IDs, see Field Types
ActivityDate	Type date Properties Filter, Group, Nillable, Sort Description Indicates one of the following: • The due date of a task • The date of an event if <code>IsAllDayEvent</code> is set to <code>true</code> This field has a time stamp that is always set to midnight in the Universal Time Coordinated (UTC) time zone. The time stamp doesn't represent the time of the activity; don't attempt to alter it to accommodate time zone differences. Label is <code>Date</code>.
ActivityType	Type picklist Properties Filter, Group, Nillable, Sort Description Represents one of the following values: <code>Call</code>, <code>Meeting</code>, or <code>Other</code>. Label is <code>Type</code>.
CallDisposition	Type string Properties Filter, Group, Nillable, Sort Description Represents the result of a given call; for example, "we'll call back," or "call unsuccessful." Limit is 255 characters.
CallDurationInSeconds	Type int Properties Filter, Group, Nillable, Sort Description Duration of the call in seconds.
CallObject	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description Name of a call center. Limit is 255 characters.
CallType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of call being answered: Inbound, Internal, or Outbound.
Description	Type textarea Properties Nillable Description Contains a description of the event or task. Limit is 32 KB.
DurationInMinutes	Type int Properties Filter, Group, Nillable, Sort Description Indicates the duration of the event or task.
EndTime	Type dateTime Properties Filter, Nillable, Sort Description Indicates the end date and time of the event or task. Available in versions 27.0 and later. This field is optional, depending on the following: • If <code>IsAllDayEvent</code> is true, you can supply a value for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time. If both fields are <code>null</code>, the duration defaults to one day. • If <code>IsAllDayEvent</code> is false, a value must be supplied for either <code>DurationInMinutes</code> or <code>EndTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time.

Field Name	Details
IsAllDayEvent	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If the value of this field is set to <code>true</code>, then the activity is an event spanning a full day, and the <code>ActivityDate</code> defines the date of the event. If the value of this field is set to <code>false</code>, then the activity may be an event spanning less than a full day, or it may be a task. Label is <code>All-Day Event</code>.
IsClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a task is closed; value is always <code>false</code>. This field is set indirectly by setting <code>Status</code> on the task—each picklist value has a corresponding <code>IsClosed</code> value. Label is <code>Closed</code>.
IsHighPriority	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates a high-priority task. This field is derived from the <code>Priority</code> field.
IsReminderSet	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a reminder is set for an activity (<code>true</code>) or not (<code>false</code>).
IsTask	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If the value of this field is set to <code>true</code>, then the activity is a task; if the value is set to <code>false</code>, then the activity is an event. Label is <code>Task</code>.

Field Name	Details
IsVisibleInSelfService	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If the value of this field is set to <code>true</code>, then the activity can be viewed in the self-service portal. Label is <code>Visible in Self-Service</code>.
Location	Type string Properties Filter, Group, Nillable, Sort Description If the activity is an event, then this field represents the location of the event. If the activity is a task, then the value is <code>null</code>.
OwnerId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the user who owns the activity.
Priority	Type picklist Properties Filter, Group, Nillable, Sort Description Indicates the priority of a task, such as high, normal, or low.
ReminderDateTime	Type dateTime Properties Filter, Nillable, Sort Description Represents the time at which a reminder is scheduled to fire if <code>IsReminderSet</code> is set to <code>true</code>. If <code>IsReminderSet</code> is set to <code>false</code>, then either the user has deselected the reminder checkbox in the user interface or the reminder has already fired at the time indicated by the value.
StartDateTime	Type dateTime

Field Name	Details
	Properties Filter, Nillable, Sort Description Indicates the start date and time of the event. Available in versions 13.0 and later. The <code>StartDateTime</code> field contains the event start date. However, if the event's <code>IsAllDayEvent</code> flag is set to <code>true</code> (indicating an all-day event), then the time stamp in the <code>StartDateTime</code> field is always set to midnight in the Coordinated Universal Time (UTC) time zone. Don't attempt to alter the time stamp to account for any time zone differences. If the event's <code>IsAllDayEvent</code> flag is set to <code>false</code>, then you must translate the time portion of the time stamp in the <code>StartDateTime</code> field to or from a local time zone for the user or the application, as appropriate, and the translation must be in the Coordinated Universal Time (UTC) time zone. If this field has a value, then <code>ActivityDate</code> and <code>ActivityDateTime</code> either must be <code>null</code> or must match the value of this field.
Status	Type picklist Properties Filter, Group, Nillable, Sort Description Indicates the current status of a task, such as in progress or complete. Each predefined status field sets a value for <code>IsClosed</code>.
Subject	Type combobox Properties Filter, Nillable, Sort Description Contains the subject of the task or event.
WhatId	Type reference Properties Filter, Group, Nillable, Sort Description The <code>WhatId</code> represents nonhuman objects such as accounts, opportunities, campaigns, cases, or custom objects. <code>WhatIds</code> are polymorphic. Polymorphic means a <code>WhatId</code> is equivalent to the ID of a related object. The label is <code>Related To ID</code>.

Field Name	Details
WhoId	Type reference Properties Filter, Group, Nillable, Sort Description The Whold represents a human such as a lead or a contact. Wholds are polymorphic. Polymorphic means a Whold is equivalent to a contact's ID or a lead's ID. The label is Name ID.

Usage

Query activities related to an object

1. Optionally, issue a describe call against the object whose activities you wish to query, to get a suggestion of the correct SOQL to use.
2. Issue a SOQL relationship query with a main clause that references the object, and an inner clause that references the activity custom lookup relationship; for example:

```
SELECT id, name,
(SELECT id, subject from sponsoredact__r)
FROM Contact
```

In this example `sponsoredact__r` is a user defined relationship list.

The user interface enforces sharing rules, filtering out related-list items that a user doesn't have permission to see.

The following restrictions on users who don't have "View All Data" permission help prevent performance issues:

- In the main clause of the relationship query, you can reference only one record. For example, you can't filter on all records where the account name starts with 'A'; instead, you must reference a single account record.
- In the inner clause of the query, you can't use `WHERE`.
- In the inner clause of the query, you must specify a limit of 500 or fewer on the number of rows that are returned in the list.
- You must sort on `ActivityDate` in descending order and `LastModifiedDate` in descending order; you can display nulls last. For example: `ORDER BY ActivityDate DESC NULLS LAST, LastModifiedDate DESC`.

MailmergeTemplate

Represents a mail merge template (a Microsoft Word document) used for performing mail merges for your organization.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

- All users can view this object, but you need the “Customize Application” permission to modify it.
- Customer Portal users can’t access this object.

Fields

Field	Details
Body	Type base64 Properties Create Description Required. Microsoft Word document to use as a mail merge template. Due to limitations with Microsoft Word mail merge templates, your client application can specify the Body field when creating these records, but not when updating them. Limit: 5 MB.
BodyLength	Type int Properties Filter, Group, Nillable, Sort Description Length of the Microsoft Word document.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Required. Text description of this mail merge template. Limit: 255 characters.
Filename	Type string Properties Create, Filter, Group, Sort Description Required. File name of the Microsoft Word document that was uploaded as a mail merge template. Limit: 255 characters in length.
IsDeleted	Type boolean Properties Defaulted on create, Filter

Field	Details
	Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
<code>LastUsedDate</code>	Type dateTime Properties Filter, Nillable, Sort Description Date and time when this MailmergeTemplate was last used.
<code>Name</code>	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of this mail merge template.

Usage

Use this object to manage mail merge templates for your organization.

Metric

The Metric object represents the components of a goal metric such as its name, metric type, and current value.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>CompletionDate</code>	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The completion date of the metric.

Field Name	Details
CurrentValue	Type double Properties Create, Defaulted on create, Filter, Nillable, Sort, Update Description The current value of the metric.
Description	Type textarea Properties Create, Nillable, Update Description The description of the metric. The maximum length is 65,535 characters.
DueDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The due date of the metric.
GoalId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the goal the metric is related to.
InitialValue	Type double Properties Create, Defaulted on create, Filter, Nillable, Sort, Update Description The initial value of the metric.
IsCompletionMetric	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field Name	Details
	Description Read only. If <code>true</code>, the metric measures whether or not the metric is finished. If <code>false</code>, the metric measures how much is finished compared to a targeted value.
LastComment	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description A comment that provides more context about the metric, such as its status or progress. The maximum length is 255 characters.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp that indicates when a user last viewed a record that is related to this metric.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp that indicates when a user last viewed this metric. If this value is null, this record might have been only referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the metric.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field Name	Details
	Description ID of the user who owns the metric.
Progress	Type percent Properties Filter, Nillable, Sort Description Read only. The overall progress of the metric.
RecordTypeId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the related record type.
Status	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The status of the metric. Possible values include: • Not Started • On Track • Behind • Critical • Completed • Postponed • Canceled
TargetValue	Type double Properties Create, Defaulted on create, Filter, Nillable, Sort, Update Description The target value of the metric.
Weight	Type double

Field Name	Details
	Properties Create, Filter, Nillable, Sort, Update
	Description The weight of the metric. The sum of the weights should equal 100%.

MetricDataLink

The link between the metric and the data source, such as a report.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>DatasourceFieldName</code>	Type string Properties Create, Filter, Group, Sort, Update Description The field name of the data source, such as a report summary field.
<code>DataSourceId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the data source.
<code>LastSynchronizationTime</code>	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The last time the data was synchronized.

Field Name	Details
Name	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description The name given to the data link record.
TargetId	Type reference Properties Create, Filter, Group, Sort Description The ID of the metric that the data is linked to.

MetricDataLinkHistory

This read-only object contains historical information about changes that have been made to the MetricDataLink object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
MetricDataLinkId	Type reference Properties Filter, Group, Sort Description ID of the MetricDataLink.

Field Name	Details
newValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

MetricFeed

Represents a single feed item in the feed displayed on a Metric record.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code> . Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code> . This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The numbers of FeedComments associated with this feed item.

Field Name	Details
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is ContentPost. The name of the file uploaded to the feed. Setting ContentFileName automatically sets <code>Type</code> to ContentPost.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.

Field Name	Details
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then <code>InsertedById</code> is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the metric record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing <code>ContentVersion</code> and post it to a feed as a <code>FeedItem</code> object of type <code>ContentPost</code>.

Field Name	Details
Title	Type string Properties Group, Nillable, Sort Description The title of the FeedItem. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of <code>ContentPost</code>, <code>LinkPost</code>, and <code>TextPost</code>, feed item types should not be created directly from the API. • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a <code>Task</code> associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a <code>Task</code> or <code>Event</code> associated with a case record (excluding email and call logging). For a recurring <code>Task</code> with <code>CaseFeed</code> disabled, one event is generated for the series only. For a recurring <code>Task</code> with <code>CaseFeed</code> enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed.

Field Name	Details
	• <code>ProfileSkillPost</code>—generated when a skill is added to a user’s Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated.

MetricHistory

This read-only object contains historical information about changes that have been made to the Metric object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>Field</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
<code>MetricId</code>	Type reference Properties Filter, Group, Sort Description ID of the Metric.
<code>NewValue</code>	Type anyType

Field Name	Details
	Properties Nillable, Sort
	Description The new value of the field that was changed.
OldValue	Type anyType
	Properties Nillable, Sort
	Description The latest value of the field before it was changed.

MetricsDataFile

Represents a data file containing usage metrics on all installations of a managed package in a Salesforce instance. This object is available in API version 30.0 and later.

Supported Calls

`query()`, `delete()`

Fields

Field Name	Details
MetricsDataFile	Type base64
	Properties Filter, Query, Sort
	Description A text file containing the usage data encoded in Base 64.
MetricsDataFileContentType	Type string
	Properties Filter, Query, Sort
	Description The format of the data file. Currently, the only allowed value is <code>text/csv</code> .

Field Name	Details
MetricsDataFileLength	Type int Properties Filter, Query, Sort Description The size of the data file in bytes.
MetricsRunDate	Type dateTime Properties Filter, Query, Sort Description The date when the usage metrics collection job was run.
MetricsEndDate	Type dateTime Properties Filter, Query, Sort Description The end time and date for the data collection.
MetricsStartDate	Type dateTime Properties Filter, Query, Sort Description The start time and date for the data collection.
MetricsType	Type picklist Properties Filter, Query, Sort Description The type of data being collected. The possible values are CustomObject and Visualforce.
NamespacePrefix	Type string Properties Filter, Query, Sort

Field Name	Details
	Description The namespace prefix of the package for which data is being collected.
SendingInstance	Type string Properties Filter, Query, Sort Description The server instance from which this data was collected, for example, "na8."

Usage

Use this object to access customer usage metrics for a managed package. Each record contains one day's data, on either custom objects or Visualforce pages, for all organizations in a Salesforce instance that have the package installed. The following data is collected each day.

- **Custom objects** — the number of records stored in each custom object.
- **Visualforce pages** — the number of times each Visualforce page was accessed, the number of unique users who accessed it, and the average loading time (in milliseconds).

The custom objects data is a snapshot that reflects the state of the organization at the time the database was sampled, while the Visualforce data covers usage over a 24-hour period.

This feature is intended for API access only. The owner of the package must write a secondary process to retrieve the metrics data from the reporting organization, and export it to another system for analysis.

The usage metrics data for all production organizations in a given instance is merged and written into a text file, in a specified format, once a day. If an instance doesn't have any organizations with the package installed or any organizations that accessed Visualforce pages in the package, a blank record is created for that day, with `MetricsDataFileLength` set to zero.

In a record for custom objects, each row of the text file contains usage data in the following order.

- Organization ID
- Organization name
- Organization edition
- Organization status
- Name of the custom object
- Number of records of the custom object on the specified day

The custom object count is a snapshot captured once each day. Here's a section of a sample data file for custom objects. It shows there were 3500 and 1500 records in the `Alpha` and `Beta` custom objects, respectively, in the specified customer organization on the specified day.

```
"00Dxx0000001gbk","org1","Enterprise Edition","TRIAL","Alpha", "3500"
"00Dxx0000001gbk","org1","Enterprise Edition","TRIAL","Beta", "1500"
```

In a record for Visualforce pages, each row of the text file contains usage data in the following order.

- Organization ID

- Organization name
- Organization edition
- Organization status
- Package version number
- Name of the Visualforce page
- Number of times the page was accessed
- Number of unique users who accessed the page
- Average loading time of the page, in milliseconds

The Visualforce counts for each organization measure the number of times the page was viewed in the duration between the start and end times. Here's a section of a sample data file for Visualforce pages.

```
"00Dxx0000001gbk","org1","Enterprise Edition","TRIAL","1.0","/apex/gml2__f1","1","1","66.0"
"00Dxx0000001gbk","org1","Enterprise Edition","TRIAL","1.0","/apex/gml2__f2","1","1","128.0"
"00Dxx0000001gbk","org1","Enterprise Edition","TRIAL","1.0","/apex/gml2__f3","1","1","107.0"
"00Dxx0000001gbf","org1","Enterprise Edition","TRIAL","1.0","/apex/gml2__f1","5","1","73.6"
"00Dxx0000001gbf","org1","Enterprise Edition","TRIAL","1.0","/apex/gml2__f2","1","1","72.0"
"00Dxx0000001gbf","org1","Enterprise Edition","TRIAL","1.0","/apex/gml2__f3","7","1","50.8"
```

MetricShare

Represents a sharing entry on a Metric object.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the metric. The possible values are: • Read Only • Read/Write • Owner This field must be set to an access level that is higher than the organization's default access level for metrics.
ParentId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Sort Description ID of the Metric object that is associated with this sharing entry.
RowCause	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: - Owner: User is the owner of the Metric or is in a user role above the Metric owner in the role hierarchy. - Manual: User or group has access because a user with “All” access manually shared the Metric with the user or group. - Rule: User or group has access via a Metric sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the Metric. This field can't be updated.

MilestoneType

Represents a milestone (required step in a customer support process).

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
Description	Type textarea

Field	Details
	Properties Create, Filter, Nillable, Update Description A description of the milestone.
Name	Type string Properties Create, Filter, idLookup, Update Description The name of the milestone.
Name	Type string Properties Create, Filter, idLookup, Update Description The name of the milestone.
RecurrenceType	Type picklist Properties Create, Update Description The type of recurrence for the milestone.

Usage

Use this object to query and manage the milestone type for CaseMilestone records.

Name

This object is used to retrieve information from related records where the related record may be from more than one object type (a polymorphic foreign key). For example, the owner of a case can be either a user or a group (queue). This object allows retrieval of the owner name, whether the owner is a user or a group (queue). You can use a describe call to access the information about parents for an object, or you can use the `who`, `what`, or `owner` fields (depending on the object) in SOQL queries. This object cannot be directly accessed.

Supported Calls

`describeSObjects()`

Fields

Field	Details
Alias	Type string Properties Filter, Group, Nillable, Sort Description The user alias. This field contains a value only if the related record is a user.
Email	Type email Properties Filter, Group, Nillable, Sort Description The email address of the user. This field contains a value only if the related record is a user.
FirstName	Type string Properties Filter, Group, Nillable, Sort Description The first name of the user, contact, or lead.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the related record is an active user (<code>true</code>) or not (<code>false</code>). This field contains a value only if the related record is a user.
LastName	Type string Properties Filter, Group, Nillable, Sort Description The last name of the user, contact, or lead.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update

Field	Details
	Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
MiddleName	Type string Properties Filter, Group, Nillable, Sort Description The middle name of the user, contact, or lead.
Name	Type string Properties Filter, Group, Nillable, Sort Description Name of the parent of the object queried. If the parent is a user, contact, or lead, the value is a concatenation of the <code>FirstName</code> , <code>MiddleName</code> , <code>LastName</code> , and <code>Suffix</code> fields of the related record.
Phone	Type phone Properties Filter, Group, Nillable, Sort Description The phone number of the user. This field contains a value only if the related record is a user.
Profile	Type reference Properties Filter, Nillable Description The Profile of the user. Only populated if the related record is a user.

Field	Details
ProfileId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the user's Profile. Only populated if the related record is a user.
Suffix	Type string Properties Filter, Group, Nillable, Sort Description The name suffix of the user, contact, or lead.
Title	Type string Properties Filter, Group, Nillable, Sort Description The title of the user, for example CFO or CEO.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description A list of the types of sObjects that can be an owner of this object. You can use this field to filter on a type of owner, for example, return only the leads owned by a user.
Username	Type string Properties Filter, Group, Nillable, Sort Description Contains the name that a user enters to log into the API or the user interface. The value for this field is in the form of an email address, and is only populated if the related record is a user.
UserRole	Type picklist Properties Filter, Nillable

Field	Details
	Description Name of the <code>Role</code> played by the user. Only populated for user rows.
<code>UserRoleId</code>	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the user role associated with this object.

Usage

To query on relationships where the parent may be more than one type of object, use `who`, `what`, or `owner` relationship fields.

NamedCredential

Represents a named credential, which specifies the URL of a callout endpoint and its required authentication parameters in one definition. A named credential can be specified as an endpoint to simplify the setup of authenticated callouts. This object is available in API version 33.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>DeveloperName</code>	Type string Properties Filter, Group, Sort Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.

Field Name	Details
Endpoint	Type textarea Properties Nillable Description The root URL of the endpoint.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language of the <code>MasterLabel</code>.
MasterLabel	Type string Properties Filter, Group, Sort Description The master label for the named credential. This display value is the internal label that doesn't get translated.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation.
PrincipalType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Tracks users who are accessing the external system. <code>Anonymous</code> implies that a user identity isn't specified for external system access. <code>Named Principal</code> uses one user identity for all users to access the external system.

Usage

Use the NamedCredential object to query named credentials in your organization.

Network

Represents a community, which is a customizable public or private space where employees, end-customers, and partners can collaborate on best practices and business processes. Communities give you the opportunity to share information, records, and files with coworkers and related external stakeholders all in one place. This object is available in API version 26.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `update()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization.

Fields

Field Name	Details
CaseCommentEmailTemplateId	Type reference Properties Filter, Group, Nillable, Sort, Update Description ID of the email template used when submitting a comment on a case. This field is available in API version 28.0 and later.
ChangePasswordEmailTemplateId	Type reference Properties Filter, Group, Sort, Update Description ID of the email template used when notifying a user that their password has been reset.
Description	Type string Properties Filter, Group, Nillable, Sort, Update Description Description of the community.

Field Name	Details
EmailFooterLogoId	Type reference Properties Filter, Group, Nillable, Sort, Update Description ID of the Document object that displays as an image in the footer of community Chatter emails.
EmailFooterText	Type string Properties Filter, Nillable, Sort, Update Description Text that displays in the footer of community Chatter emails.
EmailSenderAddress	Type email Properties Filter, Group, Sort Description Read only. Email address from which community emails are sent.  Note: To change the EmailSenderAddress value, you must first specify NewSenderAddress, which triggers the sending of an address change verification email. After you complete the address verification process, EmailSenderAddress changes to the specified NewSenderAddress.
EmailSenderName	Type string Properties Filter, Group, Sort, Update Description Name from which community emails are sent.
FirstActivationDate	Type date Properties Filter, Group, Nillable, Sort Description The date the community was first activated. This field is available in API version 34.0 and later. If the community was activated or inactive prior to the release of API version 34.0, this field returns the date the community was first created.

Field Name	Details
ForgotPasswordEmailTemplateId	Type reference Properties Filter, Group, Sort, Update Description ID of the email template used when a user forgets their password.
Name	Type string Properties Filter, Group, Sort, Update Description The name of the community.
NewSenderAddress	Type email Properties Filter, Group, Nillable, Sort, Update Description Email address that has been entered as the new value for <code>EmailSenderAddress</code> but has not been verified yet. After a user has requested to change the sender email address and has successfully responded to the verification email, the <code>NewSenderAddress</code> value overwrites the value in <code>EmailSenderAddress</code>. This becomes the email address from which community emails are sent.  Note: • If verification is pending for a new email address and you set <code>NewSenderAddress</code> to null, this cancels the verification request. • <code>NewSenderAddress</code> is automatically set to null after <code>EmailSenderAddress</code> has been set to the new verified address. • If verification is pending for a new email address and you specify a different new address for this field, only the latest value is retained and used for verification.
OptionsAllowMembersToFlag	Type boolean Properties Filter, Update Description Determines whether users can flag posts, comments, or files as inappropriate in the community.

Field Name	Details
	This field is available in API version 29.0 and later. The ability to flag files is available in version 30.0 and later.
OptionsGuestChatterEnabled	Type boolean Properties Filter, Update Description Specifies whether guest users can access public Chatter groups in the community without logging in.
OptionsInvitationsEnabled	Type boolean Properties Filter, Update Description Determines whether users can invite others to the community.
OptionsKnowledgeableEnabled	Type boolean Properties Filter Description Determines whether users can see knowledgeable people for topics and endorse people for topics.
OptionsNicknameDisplayEnabled	Type boolean Properties Filter, Update Description Determines whether user nicknames display instead of their first and last names in most places in the community. A few restrictions to keep in mind about nickname display: • Private messages display full names. You can choose to turn off private messages to avoid this. • Records and user lookups on records show full names. Keep in mind, though, that you can control record and user visibility with sharing rules. • Mobile notifications in Salesforce1 show full names. You can turn off mobile notifications in Salesforce1 to avoid this. • Searches by first, last, and full names aren't restricted and return matches, but the search results display only nicknames. The auto-complete

Field Name	Details
	recommendations in global search and the recent items list show any first, last, and full names that the user has already searched by or has accessed via a record or another location.
OptionsPrivateMessagesEnabled	Type boolean Properties Filter Description Determines whether users can send and receive Chatter messages in the community.
OptionsReputationEnabled	Type boolean Properties Filter, Update Description Determines if reputation is calculated and displayed for community members. This field is available in API version 31.0 and later.
OptionsSelfRegistrationEnabled	Type boolean Properties Filter, Update Description Determines whether external users can self-register to join the community. External users are users with Community, Customer Portal, or partner portal licenses. If <code>true</code>, displays a Not a member? link on the login page that points to the default self-registration page. This field is available in API version 28.0 and later.
OptionsSendWelcomeEmail	Type boolean Properties Filter, Update Description Determines whether a welcome email is sent when a new user is added to the community.
OptionsShowAllNetworkSettings	Type boolean Properties Filter, Update

Field Name	Details
	Description Determines whether settings in Community Management that were hidden based on how you set up your community are visible or remain hidden. This field is available in API version 33.0 and later.
OptionsSiteAsContainerEnabled	Type boolean Properties Filter, Update Description Determines whether the community uses Site.com pages instead of tabs. This field is available in API version 29.0 and later.
SelfRegProfileId	Type reference Properties Filter, Group, Nillable, Sort, Update Description ID of the profile assigned to users who self register. Only applies if self registration is enabled for the community. This field is available in API version 29.0 and later.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description Status of the community. Available values are: • Live—The community is online and members can access it. Label is Published. • DownForMaintenance—The community was previously published, but was taken offline. Members with “Create and Set Up Communities” can still access the setup for offline communities regardless of profile or membership. Members are not able to access offline communities, but they still appear in the user interface drop-down as CommunityName (Offline). Label is Offline. • UnderConstruction—The community has not yet been published. Users with “Create and Set Up Communities” can access communities in this status if their profile is associated with the community. Once a community is published, it can never be in this status again. Label is Preview.

Field Name	Details
<code>UrlPathPrefix</code>	Type string Properties Filter, Group, Sort, Update Description The <code>UrlPathPrefix</code> is a unique string at the end of the URL for this community. For example, in the community URL <code>UniversalTelco.force.com/customers</code>, <code>customers</code> is the <code>UrlPathPrefix</code>.
<code>WelcomeEmailTemplateId</code>	Type reference Properties Filter, Group, Sort, Update Description ID of the email template used when sending welcome emails to new community members.

Usage

Use this object to find, view, and update communities in your organization. If you have “Modify All Data,” “View All Data,” or “Create and Set Up Communities,” you can view all communities in the organization. Users without these permissions only see the `Preview` or `Published` communities that they’re members of. If you have “Create and Set Up Communities,” you can customize community settings.

NetworkActivityAudit

Represents an audit trail of moderation actions in Communities. This object is available in API version 30.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization.

Fields

Field Name	Details
Action	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The moderation action a user performed on a post, comment, or file in a community. Values are: - Flagged—A community member flagged a post, comment or file. - Unflagged—A community member removed the flag from a post, comment or file. - RemovedFlags—A moderator removed all flags from a post, comment, or file. - DeletedFlaggedItem—A moderator deleted a flagged post, comment, or file.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Notes entered by the user. If the entity being moderated is a file, records the version number of the file when it was flagged.
EntityCreatedById	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the user that created the entity being moderated.
EntityId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the entity that is being moderated.

Field Name	Details
EntityType	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The key prefix of entity being moderated.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The ID of the item being moderated.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the network (community) where the moderation action was performed.
ParentEntityId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the parent of the entity on which an action was performed.
ParentEntityType	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The key prefix of the parent of the entity being audited.

Usage

Use this object to view an audit trail of moderation activity for your communities. You must have the “Modify All Data” permission to access this object.

Users with “Moderate Communities Feeds”, “Moderate Communities Files” or “View All Data” can view the audit trail using reports in the Salesforce user interface.

NetworkMember

Represents a member of a community. Members can be either users in your company or external users with portal profiles. This object is available in API version 26.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `update()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization.

Fields

Field Name	Details
DefaultGroupNotificationFrequency	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description Required. The default frequency for sending the member's group email notifications when the member joins groups in the community. The valid values are: • P—Email on each post • D—Daily digests • W—Weekly digests • N—Never The default value is W. However, this field is not currently enabled. These values are reserved for future use.
DigestFrequency	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description Required. The frequency for sending the member's personal email digest for the community. The valid values are: • D—Daily • W—Weekly • N—Never

Field Name	Details
	The default value is <code>D</code>. However, daily and weekly personal digests aren't currently available in communities. These values are reserved for future use.
<code>LastChatterActivityDate</code>	Type date Properties Filter, Group, Nillable, Sort Description The last time the member posted or commented in the community.
<code>MemberId</code>	Type reference Properties Filter, Group, Sort Description The ID of a person who is a member of a community.
<code>NetworkId</code>	Type reference Properties Filter, Group, Sort Description The ID of the community that the member is part of.
<code>PreferencesDisableAllFeedsEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code>, the member can automatically receive email for updates in the community, based on the types of feed emails and digests the member has enabled.
<code>PreferencesDisableBookmarkEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code>, the member automatically receives email every time someone comments on a feed item after the member has bookmarked it.

Field Name	Details
PreferencesDisableChangeCommentEmail	Type boolean Properties Filter, Update Description When <code>false</code>, the member automatically receives email every time someone comments on a change the member has made, such as an update to their profile.
PreferencesDisableEndorsementEmail	Type boolean Properties Filter, Update Description When <code>false</code>, the member automatically receives email every time someone endorses them for a topic.
PreferencesDisableFollowersEmail	Type boolean Properties Filter, Update Description When <code>false</code>, the member automatically receives email every time someone in the community starts following the member.
DisableItemFlaggedEmail	Type boolean Properties Filter, Update Description When <code>false</code>, the user automatically receives email every time a community member flags a post or comment. This setting only applies for community moderators (with the “Moderate Communities Feeds” permission) and group owners or managers. This field is available in API version 29.0 and later.
PreferencesDisableLaterCommentEmail	Type boolean Properties Filter, Update

Field Name	Details
	Description When <code>false</code> , the member automatically receives email every time someone comments on a feed item after the member has commented on the feed item.
<code>PreferencesDisableLikeEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code> , the member automatically receives email every time someone comments on a feed item after the member has liked the feed item.
<code>PreferencesDisableMentionsPostEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code> , the member automatically receives email every time the member is mentioned in posts.
<code>PreferencesDisableMessageEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code> , the member automatically receives email every time the member is sent a Chatter message.
<code>PreferencesDisableProfilePostEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code> , the member automatically receives email every time someone posts to the member's profile.
<code>PreferencesDisableSharePostEmail</code>	Type boolean Properties Filter, Update

Field Name	Details
	Description When <code>false</code> , the member automatically receives email every time the member's post is shared.
<code>PreferencesDisCommentAfterLikeEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code> , the member automatically receives email every time someone comments on a post the member has liked.
<code>PreferencesDisMentionsCommentEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code> , the member automatically receives email every time the member is mentioned in comments.
<code>PreferencesDisProfPostCommentEmail</code>	Type boolean Properties Filter, Update Description When <code>false</code> , the member automatically receives email every time someone comments on posts on the member's profile.
<code>ReputationPoints</code>	Type double Properties Filter, Sort, Update Description The number of reputation points the user has accumulated by performing actions in the community.

Usage

Use this object to query members of a certain community and to update their email notification settings. If you have "Modify All Data," "View All Data," or "Create and Set Up Communities," you can view all members of any community, regardless of your own membership. If you have "Modify All Data" or "Create and Set Up Communities," you can also update any member's email settings. Users without these permissions can update their own email settings and can see members of the communities that they're also members of.

 **Tip:** You can directly update reputation points for a community member via the Salesforce API. You can also use Apex triggers to send custom notifications based on changes to reputation points.

NetworkMemberGroup

Represents a group of members in a community. Members can be either users in your internal organization or external users assigned portal profiles. An administrator adds members to a community by adding a profile or a permission set, and any user with the profile or permission set becomes a member of the community.

 **Note:** If a Chatter customer (from a customer group) is assigned a permission set that is also associated with a community, the Chatter customer won't be added to the community.

This object is available in API version 26.0 and later.

 **Note:** Prior to API version 27.0, this object was called NetworkProfile.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`

 **Note:** The `upsert()` call is not supported for this object.

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization.

Fields

Field Name	Details
AssignmentStatus	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description The status of a profile or permission set within a community. Values are: • Added—Users with this profile or permission set are members of the community. • Waiting for Add—The profile or permission set was added to the community, but the async process hasn't completed yet. After the process is complete, the status is updated to Added. • Waiting for Remove—Use this status to remove all the community members belonging to a profile or permission set and remove a profile or permission set from a community.

Field Name	Details
NetworkId	Type reference Properties Create, Filter, Group, Sort Description The ID of the community that this group of members is associated with.
ParentId	Type reference Properties Create, Filter, Group, Sort Description The ID of the profile or permission set associated with the community.

Usage

Use this object to view the profiles or permission sets associated with a particular community. Profiles and permission sets are added and removed asynchronously, so you can also check the status of a profile or permission set that was updated in a community.

If you have “Modify All Data,” “View All Data,” or “Create and Set Up Communities,” you can view all profiles or permission sets for any community in the organization, regardless of your membership. If you have “Modify All Data” or “Create and Set Up Communities,” you can also add profiles or permission sets. Users without these permissions can only find profiles and permission sets for communities that they’re members of.

Sample Code

```
// Create a new NetworkMemberGroup with a profile as the ParentId
NetworkMemberGroup nmgInsert = new NetworkMemberGroup();
nmg.setNetworkId("0DBD0000000029o");
nmg.setParentId("00eD0000000z1Ww");
SaveResult[] results = connection.create(new SObject[] { nmgInsert });

// Update an existing NetworkMemberGroup to be removed from the Network
NetworkMemberGroup nmgUpdate = new NetworkMemberGroup();
nmg.setId("0DL000000003enOAA");
nmg.setAssignmentStatus("WaitingForRemove");
SaveResult[] results = connection.update(new SObject[] { nmgUpdate });
```

NetworkModeration

Represents a flag on an item in a community. This object is available in API version 30.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization.

Fields

Field Name	Details
EntityId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the post, comment, or file that was flagged.
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the community in which the item was flagged.
Visibility	Type picklist Properties Create, Filter, Group, Restricted picklist, Nillable, Sort Description Determines visibility of a flagged item. Values are: - SelfAndModerators—The user who flagged the item and any moderators can see the flagged item. This is the default value. - ModeratorsOnly—Only moderators can see the flagged item. If ModeratorsOnly is selected, only moderators can set flags using the API.

Usage

Use this object to view the items flagged for moderation within a community. Additionally, users with “Moderate Feeds” and “Modify All Data” can remove flags.

Flags on items are created either when a member manually flags an item in a community (if flagging is enabled for that community), or when a trigger automatically flags an item because the item met the trigger criteria.

NetworkPageOverride

Represents information about custom pages used to override the default pages in communities. You can create Community Builder (Site.com Studio) or Visualforce pages and override the default pages in a community. Using custom pages allows you to create a more personalized experience for your users. This object is available in API version 34.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Only users with the “Create and Setup Networks” permission can update this object.
- You can’t override the Change Password Page with a page created using Community Builder (Site.com Studio). You can only override it with a Visualforce page.

Fields

Field Name	Details
NetworkId	Type reference Properties Create, Filter, Group, Sort Description The ID of the community where a custom page is used to override a default page.
OverrideSetting	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of the page used to override a default page in the community. <code>OverrideSetting</code> can take the following values: • <code>Standard</code>—The standard page that comes by default with the community. • <code>Designer</code>—A custom page created using Community Builder (Site.com Studio). • <code>Visualforce</code>—A custom page created using Visualforce.
OverrideType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update

Field Name	Details
	Description The name of the default page in the community that you want to override with a custom page. <code>OverrideType</code> can take the following values: • <code>LoginRequired</code> • <code>ChangePassword</code> • <code>ForgotPassword</code> • <code>SelfReg</code> • <code>Home</code>

NetworkSelfRegistration

Represents the account that self-registering community members are associated with by default. Self-registering users in a community are required to be associated with an account, which the administrator must specify while setting up self-registration for the community. If an account isn't specified, Salesforce creates person accounts (when enabled) for self-registering users. This object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccountId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the account that self-registering users in the community are associated with.
<code>NetworkId</code>	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the community.

Field Name

Details



Note: You can use only one account per community to assign self-registering users.

NewsFeed

Represents a single feed item on a user's home tab. A Chatter feed shows recent changes to records that the user is following.

NewsFeed is available in API version 18.0 through API version 26.0. In API version 27.0 and later, NewsFeed is no longer available in the SOAP API. Use the Chatter REST API to access NewsFeed.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field

Details

Body

Type

textarea

Properties

Nillable, Sort

Description

The content of NewsFeed. Required when `Type` is `TextPost`. Optional when `Type` is `ContentPost` or `LinkPost`. This is the message that appears in the feed.

CommentCount

Type

int

Properties

Filter, Group, Sort

Description

The number of FeedComments associated with this feed item.

ConnectionId

Type

reference

Properties

Filter, Group, Nillable, Sort

Description

When a `PartnerNetworkConnection` makes a change to a record that is tracked, the `CreatedBy` field contains the ID of the system administrator while the `ConnectionId` contains the ID of the `PartnerNetworkConnection` that made the change. Available if Salesforce to Salesforce is enabled for your organization.

Field	Details
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.

Field	Details
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field.

Field	Details
	When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference

Field	Details
	Properties Filter, Group, Sort Description ID of the newsfeed record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with <code>CaseFeed</code> disabled, one event is generated for the series only. For a recurring Task with <code>CaseFeed</code> enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group.

Field	Details
	• <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to <code>CaseFeed</code>: • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item.

Field	Details
	• InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to query and retrieve record changes tracked in a news feed. Note the following when working with news feeds:

- This object is read only in the API.
- Users can only query their own news feed.
- Queries retrieve feed items that include mentions from other users.
- Use this object to query and retrieve lead feed items that were associated with a converted lead record.

Users that do not have the “View All Data” permission have the following limitations when querying records:

- Must specify a **LIMIT** clause and the limit must be less than or equal to 1000.
- May include a **WHERE** clause that references **NewsFeed** fields, but may not include references to fields in related objects. For example, you can filter by **CreatedDate** or **ParentId**, but not by **Parent.Name**.
- May include an **ORDER BY** clause that references **NewsFeed** fields, but may not include references to fields in related objects. For example, you can **ORDER BY CreatedDate** or **ParentId**, but not by **Parent.Name**.



Tip: To query for the most recent feed items, you should **ORDER BY CreatedDate DESC, Id DESC**.

Note the following SOQL restrictions.

- No SOQL limit if logged-in user has “View All Data” permission. If not, specify a **LIMIT** clause of 1,000 records or fewer.
- SOQL **ORDER BY** on fields using relationships is not available. Use **ORDER BY** on fields on the root object in the SOQL query.

Note

Represents a note, which is text associated with a custom object or a standard object, such as a **Contact**, **Contract**, or **Opportunity**.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Body	Type textarea Properties Create, Nillable, Update Description Body of the note. Limited to 32 KB.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsPrivate	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, only the note owner or a user with the “Modify All Data” permission can view the note or query it via the API. Note that if a user who does not have the “Modify All Data” permission sets this field to <code>true</code> on a note that they do not own, then they can no longer query, delete, or update the note. Label is Private.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the user who owns the note.
ParentId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the object associated with the note.

Field	Details
Title	Type string Properties Create, Filter, Group, Sort, Update Description Title of the note.

Usage

Use this object to manage notes for an object.

OAuthToken

Represents an OAuth access token for connected app authentication and can be used to create a user interface for token management.

A connected app integrates an application with Salesforce using APIs. Connected apps use standard SAML and OAuth protocols to authenticate, provide Single Sign-On, and provide tokens for use with Salesforce APIs. In addition to standard OAuth capabilities, connected apps allow administrators to set various security policies and have explicit control over who may use the corresponding applications. Each time that a user grants access to an application, the application obtains a new access token. This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`

Special Access Rules

If you are a user with the “Manage Users” permission, you see all tokens for all users in the organization. Otherwise, you see only your own tokens.

Fields

Field Name	Details
AccessToken	Type string Properties Filter, Group, Nillable, Sort Description The refresh token for authorization.

Field Name	Details
AppMenuItemId	Type reference Properties Filter, Group, Nillable, Sort Description The unique ID for the App Picker menu item that's associated with this OAuth token.
AppName	Type string Properties Filter, Group, Nillable, Sort Description The label for the connected app that's associated with this OAuth token.
DeleteToken	Type string Properties Filter, Group, Nillable, Sort Description A token that can be used at the revoke OAuth token endpoint to remove this token.
Id	Type ID Properties Defaulted on create, Filter, Group, idLookup, Sort Description Reserved for future use. Currently, the value is always <code>null</code>.
LastUsedDate	Type dateTime Properties Filter, Nillable, Sort Description The most recent date when the OAuth token was used.
RequestToken	Type string

Field Name	Details
	Properties Filter, Group, Nillable, Sort Description The authorization code that was used to request the corresponding AccessToken. With this authorization code, you can revoke the corresponding AccesToken by passing the DeleteToken.
UseCount	Type int Properties Filter, Group, Nillable, Sort Description How often the token has been used.
UserId	Type reference Properties Filter, Group, Nillable, Sort Description The owner of the token.

Usage

To delete an AccessToken, send a request to the revoke OAuth token endpoint with the DeleteToken as the parameter. For example, this URL `https://login.salesforce.com/services/oauth2/revoke?token=(the Delete Token)` causes the deletion of the token.

In API version 34.0 and later, this object was enhanced to help manage high instance counts. A `query()` call returns up to 500 rows. A `queryMore()` call returns 500 more, up to 2500 total. No more records are returned after 2500. To make sure you don't miss any records, issue a `COUNT()` query in a `SELECT` clause for OAuthToken. This gives you the total number of records. If there are more than 2500 records, divide your query by filtering on fields, like `UserId`, to return subsets of less than 2500 records.

NoteAndAttachment

This read-only object contains all notes and attachments associated with an object.

Supported Calls

`describeSObjects()`

Fields

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsNote	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the object contains a note (<code>true</code>) or an attachment (<code>false</code>).
IsPrivate	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If <code>true</code>, only the note owner or a user with the “Modify All Data” permission can view the note or query it via the API. Note that if a regular user who does not have “Modify All Data” permission sets this field to <code>true</code> on a note that they do not own, then they can no longer query, delete, or update that note. Label is Private.
OwnerId	Type reference Properties Filter, Group, Sort Description ID of the user who owns the note and attachment.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the parent object.

Field	Details
Title	Type string Properties Filter, Nillable, Group, Sort Description Title of the note.

Usage

Use this object to list all notes and attachments for an object.

To retrieve notes and attachments, issue a describe call on an object, which returns a query result for each activity since the record was created. You can't directly query this object.

NoteTag

Associates a word or short phrase with a Note.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.

Field Name	Details
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization. • <code>Personal</code>—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

NoteTag stores the relationship between its parent TagDefinition and the Note being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

ObjectPermissions

Represents the enabled object permissions for the parent PermissionSet. To grant a user access to an object, associate an ObjectPermissions record with a PermissionSet that's assigned to a user. ObjectPermissions records are only supported in PermissionSet, not in Profile. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
ParentId	Type reference Properties Create, Filter, Group, Sort Description The Id of this object's parent PermissionSet.
PermissionsCreate	Type boolean Properties Create, Filter, Update Description If <code>true</code>, users assigned to the parent <code>PermissionSet</code> can create records for this object. Requires <code>PermissionsRead</code> for the same object to be <code>true</code>.
PermissionsDelete	Type boolean Properties Create, Filter, Update Description If <code>true</code>, users assigned to the parent <code>PermissionSet</code> can delete records for this object. Requires <code>PermissionsRead</code> and <code>PermissionsEdit</code> for the same object to be <code>true</code>.
PermissionsEdit	Type boolean Properties Create, Filter, Update Description If <code>true</code>, users assigned to the parent <code>PermissionSet</code> can edit records for this object. Requires <code>PermissionsRead</code> for the same object to be <code>true</code>.
PermissionsModifyAllRecords	Type boolean Properties Create, Filter, Update Description If <code>true</code>, users assigned to the parent <code>PermissionSet</code> can edit all records for this object, regardless of sharing settings. Requires <code>PermissionsRead</code>,

Field Name	Details
	PermissionsDelete, PermissionsEdit, and PermissionsViewAllRecords for the same object to be <code>true</code> .
PermissionsRead	Type boolean Properties Create, Filter, Update Description If <code>true</code>, users assigned to the parent PermissionSet can view records for this object.
PermissionsViewAllRecords	Type boolean Properties Create, Filter, Update Description If <code>true</code>, users assigned to the parent PermissionSet can view all records for this object, regardless of sharing settings. Requires <code>PermissionsRead</code> for the same object to be <code>true</code>.
ObjectType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The object's API name. For example, <code>Merchandise__c</code>.

Permission Dependencies

Some user permissions have dependencies on object permissions. For example, if a permission set has the “Transfer Leads” permission, it also has “Read” and “Create” on the leads object.

You can query from `ObjectPermissions` up to the parent `PermissionSet` object. For example:

```
SELECT Parent.Name, Parent.PermissionsTransferAnyLead, PermissionsRead, PermissionsCreate
FROM ObjectPermissions
WHERE ObjectType = 'Lead'
```

Determining Object Access with “Modify All Data”

When using SOQL to query object permissions, be aware that some object permissions are enabled because a user permission requires them.

The exception to this rule is when “Modify All Data” is enabled. While it enables all object permissions, it doesn't physically store any object permission records in the database. As a result, unlike object permissions that are required by a user permission—such as “View

All Data” or “Import Leads”—the query still returns permission sets with “Modify All Data,” but the object permission record will contain an invalid ID that begins with “000”. This ID indicates that the object has full access due to “Modify All Data” and the object permission record can’t be updated or deleted. To remove full access from these objects, disable “Modify All Data” and then delete the resulting object permission record. This ensures that when using SOQL to find all the objects that have full access, it returns all objects that have this access regardless of whether it’s due to “Modify All Data” or because an administrator set full access.

For example, the following will return all permission sets that have “Read” on the Merchandise__c object, regardless of whether it’s explicitly defined on the object or implicitly defined through “Modify All Data.”

```
SELECT Id, Parent.label, SubjectType, PermissionsRead,
       Parent.PermissionsModifyAllData, ParentId
FROM ObjectPermissions
WHERE PermissionsRead = true and SubjectType = 'Merchandise__c'
```

Nesting Object Permissions

You can nest ObjectPermissions in a PermissionSet query. For example, the following returns any permission sets where “Transfer Leads” is true. Additionally, the result set will include the “Read” object permission on leads. This is done by nesting the SOQL with an object permission query using the relationship name for object permissions: `ObjectPerms`.

```
SELECT Id, Name, PermissionsTransferAnyLead,
       (SELECT Id, PermissionsRead from ObjectPerms where SubjectType='Lead')
FROM PermissionSet
WHERE PermissionsTransferAnyLead = true
```

As a result, it’s possible to traverse the relationship between the PermissionSet and any child related objects (in this case, ObjectPermissions). You can do this from the PermissionSet object by using the child relationship (`ObjectPerms`, `FieldPerms`, and so on) or from the child object by referencing the PermissionSet with `Parent.permission_set_attribute`.

It’s important to consider when to use a conditional `WHERE` statement to restrict the result set. To query based on an attribute on the permission set object, nest the SOQL with the child relationship. However, to query based on an attribute on the child object, you must reference the permission set parent attribute in your query.

The following two queries return the same columns with different results, based on whether you use the child relationship or parent notation.

```
SELECT Id, Name, PermissionsModifyAllData,
       (SELECT Id, SubjectType, PermissionsRead from Objectperms)
FROM PermissionSet
WHERE PermissionsModifyAllData=true
```

versus:

```
SELECT Id, SObjectType, PermissionsRead, Parent.Id, Parent.Name,
       Parent.PermissionsModifyAllData
FROM ObjectPermissions
WHERE SObjectType='Merchandise__c'
```

ObjectTerritory2AssignmentRule

Represents a territory assignment rule that’s associated with an object, such as Account. `ObjectTerritory2AssignmentRuleItem` can only be created or deleted if the `BooleanFilter` field on its corresponding `ObjectTerritory2AssignmentRule` is `null`. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

If a territory model is in `Active` state, any user can view that model, including its territories, assignment rules, assigned records, and assigned users. Users cannot view territory models in other states (such as `Planning` or `Archived`).

Fields

Field Name	Details
<code>BooleanFilter</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Represents advanced filter conditions that were specified for the rule in the online application. For example, "(1 AND 2) OR 3."
<code>DeveloperName</code>	Type string Properties Create, Filter, Group, Sort, Update Description Required. The unique name of the object in the API. This name can contain only underscores and alphanumeric characters and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. The field label in the user interface is <code>Unique Name</code>.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
<code>IsActive</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the rule is active (true) or inactive (false). Via the API, active rules run automatically when object records are created and edited. The exception is when the value of the <code>IsExcludedFromRealign</code> field on an object record is <code>true</code>, which prevents record assignment rules from evaluating that record.

Field Name	Details
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the master label in the user interface.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description Required. The user interface label for the territory type.
ObjectType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The object that the rule is defined for. For API version 31, Account only.
Territory2ModelId	Type reference Properties Create, Filter, Group, Sort Description The ID of the territory model.

ObjectTerritory2AssignmentRuleItem

A single row of selection criteria for an ObjectTerritory2AssignmentRule object. ObjectTerritory2AssignmentRuleItem can only be created or deleted if the `BooleanFilter` field on its corresponding ObjectTerritory2AssignmentRule object is a `null` value. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

If a territory model is in `Active` state, any user can view that model, including its territories and assignment rules. For territories in an active model, any user can view assigned records and assigned users subject to your organization's sharing settings. Users cannot view territory models in other states (such as `Planning` or `Archived`).

Fields

Field Name	Details
Field	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The standard or custom object field that the rule item will operate on.
Operation	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The criterion to apply for the rule item. For example: <i>equals</i> or <i>starts with</i>.
RuleId	Type reference Properties Create, Filter, Group, Sort Description The ID of the associated ObjectTerritory2AssignmentRule.
SortOrder	Type int Properties Create, Filter, Group, Sort, Update Description The order in which this row is evaluated in relation to other ObjectTerritoryAssignmentRuleItem objects for the given ObjectTerritoryAssignmentRule.
Value	Type string

Field Name	Details
	Properties Create, Filter, Nillable, Sort, Update
	Description The field value or values to evaluate. For example: if the field is <code>Billing ZIP/Postal Code</code> , a value might be <code>94105</code> .

ObjectTerritory2Association

Represents an association (by assignment) between a territory and an object record, such as an account. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

If a territory model is in `Active` state, any user can view that model, including its territories and assignment rules. For territories in an active model, any user can view assigned records and assigned users subject to your organization's sharing settings. Users cannot view territory models in other states (such as `Planning` or `Archived`).

Fields

Field Name	Details
<code>AssociationCause</code>	Type picklist
	Properties Create, Filter, Group, Restricted picklist, Sort
	Description The means by which the record was associated with the territory: by rules or manually. User interface field label is <code>Method</code> . Manual cause can only be set by a user or via the API. Rules cause is used by the rules engine when the object is assigned.
<code>ObjectId</code>	Type reference
	Properties Create, Filter, Group, Sort
	Description The ID of the object. For API version 31, Account only.

Field Name	Details
SubjectType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of the record. For API version 31, Account only.
Territory2Id	Type reference Properties Create, Filter, Group, Sort Description The ID of the territory that the record is assigned to.

OpenActivity

This read-only object is displayed in a related list of open activities—future events and open tasks—related to an object. It includes activities for all contacts related to the object. OpenActivity fields for phone calls are only available if your organization uses Salesforce CRM Call Center.

Supported Calls

`describeSObjects()`

Fields

Field	Details
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the related account, which is determined as follows: • The account associated with the <code>whatId</code>, if it exists; or • The account associated with the <code>whoId</code>, if it exists; otherwise • <code>null</code> For information on IDs, see ID Field Type .

Field	Details
ActivityDate	Type date Properties Filter, Group, Nillable, Sort Description Indicates one of the following: • The due date of a task • The date of an event if <code>IsAllDayEvent</code> is set to <code>true</code> This field has a time stamp that is always set to midnight in the Universal Time Coordinated (UTC) time zone. The time stamp doesn't represent the time of the activity; don't attempt to alter it to accommodate time zone differences. Label is <code>Date</code>.
ActivityType	Type picklist Properties Filter, Group, Nillable, Sort Description Represents one of the following values: <code>Call</code>, <code>Meeting</code>, or <code>Other</code>. Label is <code>Type</code>.
CallDisposition	Type string Properties Filter, Group, Nillable, Sort Description Represents the result of a given call, for example, "we'll call back," or "call unsuccessful." Limit is 255 characters.
CallDurationInSeconds	Type int Properties Filter, Group, Nillable, Sort Description Duration of the call in seconds.
CallObject	Type string Properties Filter, Group, Nillable, Sort Description Name of a call center. Limit is 255 characters.

Field	Details
CallType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of call being answered: Inbound, Internal, or Outbound.
ConnectionReceivedId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the PartnerNetworkConnection that shared this record with your organization. This field is available only if your organization has enabled Salesforce to Salesforce and only in API versions 28.0 and later.
ConnectionSentId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the PartnerNetworkConnection that your organization shared this record with. This field is available only if your organization has enabled Salesforce to Salesforce, and only in API versions 28.0 and later. The value is always null. You can use the PartnerNetworkRecordConnection object to forward records to connections.
Description	Type textarea Properties Nillable Description Contains a description of the event or task. Limit is 32 KB.
DurationInMinutes	Type int Properties Filter, Group, Nillable, Sort Description Indicates the duration of the event or task.
EndTime	Type dateTime

Field	Details
	Properties Filter, Nillable, Sort Description Indicates the end date and time of the event or task. Available in versions 27.0 and later. This field is optional, depending on the following: • If <code>IsAllDayEvent</code> is true, you can supply a value for either <code>DurationInMinutes</code> or <code>EndDateTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time. If both fields are <code>null</code>, the duration defaults to one day. • If <code>IsAllDayEvent</code> is false, a value must be supplied for either <code>DurationInMinutes</code> or <code>EndDateTime</code>. Supplying values in both fields is allowed if the values add up to the same amount of time.
<code>IsAllDayEvent</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If the value of this field is set to <code>true</code>, then the activity is an event spanning a full day, and the <code>ActivityDate</code> defines the date of the event. If the value of this field is set to <code>false</code>, then the activity may be an event spanning less than a full day, or it may be a task. Label is <code>All-Day Event</code>.
<code>IsClosed</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a task is closed; value is always <code>false</code>). This field is set indirectly by setting <code>Status</code> on the task—each picklist value has a corresponding <code>IsClosed</code> value. Label is <code>Closed</code>.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the activity has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is <code>Deleted</code>.
<code>IsHighPriority</code>	Type boolean

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description Indicates a high-priority task. This field is derived from the <code>Priority</code> field.
<code>IsReminderSet</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a reminder is set for an activity (<code>true</code>) or not (<code>false</code>).
<code>IsTask</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If the value of this field is set to <code>true</code>, then the activity is a task; if the value is set to <code>false</code>, then the activity is an event. Label is <code>Task</code>.
<code>IsVisibleInSelfService</code>	Type boolean Properties Defaulted on create, Filter Description If the value of this field is set to <code>true</code>, then the activity can be viewed in the self-service portal. Label is <code>Visible in Self-Service</code>.
<code>Location</code>	Type string Properties Filter, Group, Nillable, Sort Description If the activity is an event, then this field represents the location of the event. If the activity is a task, then the value is <code>null</code>.
<code>OwnerId</code>	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the user who owns the activity.

Field	Details
PrimaryAccountId	Type reference Properties Filter, Group, Nillable, Sort Description Contains the <code>AccountId</code> value from the activity record. Available in API versions 30.0 and later to organizations that use Shared Activities.
PrimaryWhoId	Type reference Properties Filter, Group, Nillable, Sort Description Contains the <code>whoId</code> value from the activity record. Available in API versions 30.0 and later to organizations that have enabled Shared Activities.
Priority	Type picklist Properties Filter, Group, Nillable, Sort Description Indicates the priority of a task, such as high, normal, or low.
ReminderDateTime	Type dateTime Properties Filter, Nillable, Sort Description Represents the time at which a reminder is scheduled to fire if <code>IsReminderSet</code> is set to <code>true</code>. If <code>IsReminderSet</code> is set to <code>false</code>, then either the user has deselected the reminder checkbox in the user interface or the reminder has already fired at the time indicated by the value.
Status	Type picklist Properties Filter, Group, Nillable, Sort Description Indicates the current status of a task, such as in progress or complete. Each predefined status field sets a value for <code>IsClosed</code>. To obtain picklist values, query <code>TaskStatus</code>.

Field	Details
Subject	Type combobox Properties Filter, Nillable, Sort Description Contains the subject of the task or event.
WhatId	Type reference Properties Filter, Group, Nillable, Sort Description The <code>WhatId</code> represents nonhuman objects such as accounts, opportunities, campaigns, cases, or custom objects. <code>WhatIds</code> are polymorphic. Polymorphic means a <code>WhatId</code> is equivalent to the ID of a related object. The label is <code>Related To ID</code>.
WhoId	Type reference Properties Filter, Group, Nillable, Sort Description The <code>WhoId</code> represents a human such as a lead or a contact. <code>WhoIds</code> are polymorphic. Polymorphic means a <code>WhoId</code> is equivalent to a contact's ID or a lead's ID. The label is <code>Name ID</code>. If Shared Activities is enabled, the value of this field is the ID of the related lead or primary contact. If you add, update, or remove the <code>WhoId</code> field, you might encounter problems with triggers, workflows, and data validation rules that are associated with the record. The label is <code>Name ID</code>.

Usage

Query activities that are related to an object

1. Optionally, issue a describe call against the object whose activities you want to query, to get a suggestion of the correct SOQL query to use.
2. Issue a SOQL relationship query with a main clause that references the object and an inner clause that references the activity history. For example:

```
SELECT
  (SELECT ActivityDate, Description
   FROM OpenActivities)
FROM Account
WHERE Name Like 'XYZ%'
```

The user interface enforces sharing rules, filtering out related-list items that a user doesn't have permission to see.

The following constraints on users who don't have the "View All Data" permission help prevent performance issues.

- In the main clause of the relationship query, you can reference only one record. For example, you can't filter on all records where the account name starts with "A." Instead, you must reference a single account record.

```
SELECT
  (SELECT ActivityDate, Description
   FROM OpenActivities
   ORDER BY ActivityDate ASC NULLS LAST, LastModifiedDate DESC
   LIMIT 500)
FROM Account
WHERE Name = 'Acme '
LIMIT 1
```

- In the inner clause of the query, you can't use `WHERE`.
- In the inner clause of the query, you must specify a limit of 500 or fewer on the number of rows that are returned in the list.
- In the inner clause of the query, you must sort on `ActivityDate` in ascending order and `LastModifiedDate` in descending order. You can optionally display nulls last. For example: `ORDER BY ActivityDate ASC NULLS LAST, LastModifiedDate DESC`.

Opportunity

Represents an opportunity, which is a sale or pending deal.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Field Type
AccountId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the account associated with this opportunity.
Amount	Type currency Properties Create, Filter, Nillable, Sort, Update

Field	Field Type
	Description Estimated total sale amount. For opportunities with products, the amount is the sum of the related products. Any attempt to update this field, if the record has products, will be ignored. The update call will not be rejected, and other fields will be updated as specified, but the Amount will be unchanged.
CampaignId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of a related Campaign. This field is defined only for those organizations that have the campaign feature Campaigns enabled. The User must have read access rights to the cross-referenced Campaign object in order to create or update that campaign into this field on the opportunity.
CloseDate	Type date Properties Create, Filter, Group, Sort, Update Description Required. Date when the opportunity is expected to close.
ConnectionReceivedId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
ConnectionSentId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the ConnectionSentId field is no longer supported. The ConnectionSentId field is still visible, but the value is null. You can use the new PartnerNetworkRecordConnection object to forward records to connections.

Field	Field Type
ContractId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the contract that's associated with this opportunity.
CurrencyIsoCode	Type picklist Properties Create, Defaulted on create, Filter, Nillable, Restricted picklist, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization. If the organization has multicurrency and a Pricebook2 is specified on the opportunity (i.e., the <code>Pricebook2Id</code> field is not blank), then the currency value of this field must match the currency of the PricebookEntry records that are associated with any opportunity line items it has.
Description	Type textarea Properties Create, Nillable, Update Description Text description of the opportunity. Limit: 32,000 characters.
ExpectedRevenue	Type currency Properties Filter, Nillable, Sort Description Read-only field that is equal to the product of the opportunity <code>Amount</code> field and the <code>Probability</code>. You can't directly set this field, but you can indirectly set it by setting the <code>Amount</code> or <code>Probability</code> fields.
Fiscal	Type string Properties Filter, Group, Nillable, Sort

Field	Field Type
	Description If fiscal years are not enabled, the name of the fiscal quarter or period in which the opportunity <code>CloseDate</code> falls. Value should be in YYYY Q format, for example, '2006 1' for first quarter of 2006.
<code>FiscalQuarter</code>	Type int Properties Filter, Group, Nillable, Sort Description Represents the fiscal quarter. Valid values are 1, 2, 3, or 4.
<code>FiscalYear</code>	Type int Properties Filter, Group, Nillable, Sort Description Represents the fiscal year, for example, 2006.
<code>ForecastCategory</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Restricted picklist field. It is implied, but not directly controlled, by the <code>StageName</code> field. You can override this field to a different value than is implied by the <code>StageName</code> value. The values of this field are fixed enumerated values. The field labels are localized to the language of the user performing the operation, if localized versions of those labels are available for that language in the user interface. In API version 12.0 and later, the value of this field is automatically set based on the value of the <code>ForecastCategoryName</code> and can't be updated any other way. The field properties Create, Defaulted on create, Nillable, and Update are not available in version 12.0.
<code>ForecastCategoryName</code>	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Available in API version 12.0 and later. The name of the forecast category. It is implied, but not directly controlled, by the <code>StageName</code> field. You can override this field to a different value than is implied by the <code>StageName</code> value.

Field	Field Type
HasOpportunityLineItem	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read-only field that indicates whether the opportunity has associated line items. A value of <code>true</code> means that Opportunity line items have been created for the opportunity. An opportunity can have opportunity line items only if the opportunity has a price book. The opportunity line items must correspond to PricebookEntry objects that are listed in the opportunity Pricebook2. However, you can insert opportunity line items on an opportunity that does not have an associated Pricebook2. For the first opportunity line item that you insert on an opportunity without a Pricebook2, the API automatically sets the <code>Pricebook2Id</code> field, if the opportunity line item corresponds to a PricebookEntry in an active Pricebook2 that has a <code>CurrencyIsoCode</code> field that matches the <code>CurrencyIsoCode</code> field of the opportunity. If the Pricebook2 is not active or the <code>CurrencyIsoCode</code> fields do not match, then the API returns an error. You can't update the <code>Pricebook2Id</code> or <code>PricebookId</code> fields if opportunity line items exist on the Opportunity. You must delete the line items before attempting to update the <code>PricebookId</code> field.
IsClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Directly controlled by <code>StageName</code>. You can query and filter on this field, but you can't directly set it in a create, upsert, or update request. It can only be set via <code>StageName</code>. Label is Closed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsExcludedFromTerritory2Filter	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Field Type
	Description Used for Filter-Based Opportunity Territory Assignment (Pilot in Spring '15 / API version 33). Indicates whether the opportunity is excluded (<i>True</i>) or included (<i>False</i>) each time the APEX filter is executed.
IsSplit	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read-only field that indicates whether credit for the opportunity is split between opportunity team members. Label is <code>IsSplit</code>. This field is available in versions 14.0 and later for organizations that enabled Opportunity Splits during the pilot period.  Warning: This field should not be used. However, it's documented for the benefit of pilot customers who find references to <code>IsSplit</code> in code.
IsWon	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Directly controlled by <code>StageName</code>. You can query and filter on this field, but you can't directly set the value. It can only be set via <code>StageName</code>. Label is Won.
LastActivityDate	Type date Properties Filter, Group, Nillable, Sort Description Value is one of the following, whichever is the most recent: • Due date of the most recent event logged against the record. • Due date of the most recently closed task associated with the record.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date

Field	Field Type
	Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
LeadSource	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Source of this opportunity, such as Advertisement or Trade Show.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. A name for this opportunity. Limit: 120 characters.
NextStep	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Description of next task in closing opportunity. Limit: 255 characters.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the User who has been assigned to work this opportunity. If you update this field, the previous owner's access becomes Read Only or the access specified in your organization-wide default for opportunities, whichever is greater. If you have set up opportunity teams in your organization, updating this field has different consequences depending on your version of the API: • For API version 12.0 and later, sharing records are kept, as they are for all objects. • For API version before 12.0, sharing records are deleted. • For API version 16.0 and later, users must have the “Transfer Record” permission in order to update (transfer) account ownership using this field.

Field	Field Type
Pricebook2Id	Type reference Properties Create, Defaulted on create, Filter, Group, Nillable, Sort, Update Description ID of a related Pricebook2 object. The <code>Pricebook2Id</code> field indicates which Pricebook2 applies to this opportunity. The <code>Pricebook2Id</code> field is defined only for those organizations that have products enabled as a feature. You can specify values for only one field (<code>Pricebook2Id</code> or <code>PricebookId</code>)—not both fields. For this reason, both fields are declared nillable.
PricebookId	Type reference Properties Create, Defaulted on create, Filter, Nillable, Update Description Unavailable as of version 3.0. As of version 8.0, the Pricebook object is no longer available. Use the <code>Pricebook2Id</code> field instead, specifying the ID of the Pricebook2 record.
Probability	Type percent Properties Create, Defaulted on create, Filter, Nillable, Sort, Update Description Percentage of estimated confidence in closing the opportunity. It is implied, but not directly controlled, by the <code>StageName</code> field. You can override this field to a different value than what is implied by the <code>StageName</code>.  Note: If you're changing the <code>Probability</code> field through the API using a partner WSDL call, or an Apex <code>before</code> trigger, and the value may have several decimal places, we recommend rounding the value to a whole number. For example, the following Apex in a <code>before</code> trigger uses the <code>round</code> method to change the field value: <code>o.probability = o.probability.round();</code>
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to this object.
StageName	Type picklist

Field	Field Type
	Properties Create, Filter, Group, Sort, Update Description Required. Current stage of this record. The <code>StageName</code> field controls several other fields on an opportunity. Each of the fields can be directly set or implied by changing the <code>StageName</code> field. In addition, the <code>StageName</code> field is a picklist, so it has additional members in the returned <code>describeObjectResult</code> to indicate how it affects the other fields. To obtain the stage name values in the picklist, query the <code>OpportunityStage</code> object. If the <code>StageName</code> is updated, then the <code>ForecastCategoryName</code>, <code>IsClosed</code>, <code>IsWon</code>, and <code>Probability</code> are automatically updated based on the stage-category mapping.
SyncedQuoteID	Type reference Properties Create, Filter, Nillable, Update Description Read only in an Apex trigger. The ID of the Quote that syncs with the opportunity. Setting this field lets you start and stop syncing between the opportunity and a quote. The ID has to be for a quote that is a child of the opportunity.
Territory2Id	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the territory that is assigned to the opportunity. Available only if Enterprise Territory Management has been enabled for your organization.
TotalOpportunityQuantity	Type double Properties Create, Filter, Nillable, Sort, Update Description Number of items included in this opportunity. Used in quantity-based forecasting.
Type	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Type of opportunity. For example, Existing Business or New Business. Label is Opportunity Type.

 **Note:** If you are importing Opportunity data and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself.

Usage

Use the Opportunity object to manage information about a sale or pending deal. You can also sync this object with a child Quote. To update an Opportunity, your client application needs "Edit" permission on opportunities. You can create, update, delete, and query Attachment records associated with an opportunity via the API. To split credit for an opportunity among multiple opportunity team members, use the OpportunitySplit object.

Client applications can also create or update opportunity objects by converting a Lead with `convertLead()`.

 **Note:** On opportunities and opportunity products, the workflow rules, validation rules, and Apex triggers fire when an update to a child opportunity product or schedule causes an update to the parent record. This means your custom application logic is enforced when there are updates to the parent record, ensuring higher data quality and compliance with your organization's business policies.

Sample Code—Java

This code starts the sync between an object and a child quote.

```
public void startQuoteSync() {
    Opportunity opp = new Opportunity();
    opp.setId(new ID("006D000000CpOSy"));
    opp.setSyncedQuoteId(new ID("0Q0D000000002OZ"));
    // Invoke the update call and save the results
    try {
        SaveResult[] saveResults = binding.update(new SObject[] {opp});
        // check results and do more processing after the update call ...
    }
    catch (Exception ex) {
        System.out.println("An unexpected error has occurred." + ex.getMessage());
        return;
    }
}
```

This code stops the sync between an object and a child quote.

```
public void stopQuoteSync() {
    Opportunity opp = new Opportunity();
    opp.setId(new ID("006D000000CpOSy"));
    opp.setFieldsToNull(new String[] {"SyncedQuoteId"} );
    // Invoke the update call and save the results
    try {
        SaveResult[] saveResults = binding.update(new SObject[] {opp});
        // check results and do more processing after the update call ...
    }
    catch (Exception ex) {
        System.out.println("An unexpected error has occurred." + ex.getMessage());
        return;
    }
}
```

OpportunityCompetitor

Represents a competitor on an Opportunity.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
CompetitorName	Type combobox Properties Create, Filter, Nillable, Sort, Update Description Name of the competitor.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
OpportunityId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the associated Opportunity.
Strengths	Type string Properties Create, Filter, Nillable, Sort, Update Description Description of the competitor's strengths. Limit: 1,000 characters.

Field	Details
Weaknesses	Type string Properties Create, Filter, Nillable, Sort, Update Description Description of the competitor's weaknesses. Limit: 1,000 characters.

Usage

Use this object to manage competitors on an Opportunity, associating multiple competitors on a opportunity and specifying the strengths and weaknesses of each competitor.

OpportunityContactRole

Represents the role that a Contact plays on an Opportunity.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
ContactId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of an associated Contact. The API applies user access rights to the associated Opportunity for this object, but not to the associated Contact. The API may return rows from a query on this object that include this field's values for contacts to which the user does not have sufficient access rights. It may also return values for this field for contacts that have been deleted. In either case, the client must perform a query on the contact table for this field's value to determine whether the Contact is accessible to the user and has not been deleted.
IsDeleted	Type boolean Properties Defaulted on create, Filter

Field	Details
	Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
<code>IsPrimary</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the associated Contact plays the primary role on the Opportunity (<code>true</code>) or not (<code>false</code>). Each Opportunity has only one primary contact. Label is Primary .
<code>OpportunityId</code>	Type reference Properties Create, Filter, Group, Sort, Description Required. ID of an associated Opportunity. This field is non-nullable, and it cannot be updated. You must provide a value for this field when creating new records. You can't change it after it has been created.
<code>Role</code>	Type picklist Properties Create, Filter, Group, Sort, Nillable, Update Description Name of the role played by the associated Contact on the Opportunity, such as Business User or Decision Maker.

Usage

Records of this object type appear in the user interface on the Opportunity detail page. Like most other objects, records of this object type have their own unique ID that you use when updating or deleting records.

Although allowed, we do not recommend that you create multiple relationships between the same Opportunity and a Contact.

OpportunityFeed

Represents a single feed item in the feed displayed on the detail page for an opportunity record. An opportunity feed shows recent changes to an opportunity record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to opportunities. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Opportunity object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of OpportunityFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a <code>PartnerNetworkConnection</code> makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the <code>PartnerNetworkConnection</code> that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64

Field	Details
	Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code> .
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code> .
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code> .
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime

Field	Details
	Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the

Field	Details
	CreatedDate for that FeedComment. Deleting the FeedComment does not change the LastModifiedDate. Ordering by LastModifiedDate DESC sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope: • Only feed items with a Group or User parent can set a NetworkId or a null value for NetworkScope. • For feed items with a record parent, users can set NetworkScope only to AllNetworks. • You can't filter a FeedItem on the NetworkScope field.
ParentId	Type reference

Field	Details
	Properties Filter, Group, Sort Description ID of the opportunity record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group.

Field	Details
	• <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to <code>CaseFeed</code>: • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item.

Field	Details
	<code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: - For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. - External users can set <code>Visibility</code> only to <code>AllUsers</code>. - On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>.

Usage

Use this object to track changes for an opportunity record.

OpportunityFieldHistory

Represents the history of changes to the values in the fields of an opportunity. This object is available in versions 13.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
<code>Field</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
<code>OpportunityId</code>	Type reference

Field	Details
	Properties Filter, Group, Sort Description ID of the Opportunity. Label is Opportunity ID .
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Usage

Use this object to identify changes to any fields on an Opportunity. The OpportunityHistory object represents the history of a change to the `Amount`, `Probability`, `Stage`, or `Close Date` fields of an Opportunity.

This object respects field level security on the parent object.

OpportunityHistory

Represents the stage history of an Opportunity.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Amount	Type currency

Field	Details
	Properties Filter, Nillable, Sort Description Estimated total sale amount.
CloseDate	Type date Properties Filter, Group, Nillable, Sort Description Date when the opportunity is expected to close.
ExpectedRevenue	Type currency Properties Filter, Nillable, Sort Description Calculated revenue based on the <code>Amount</code> and <code>Probability</code> fields.
ForecastCategory	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Category that determines the column in which an opportunity is totaled in a forecast. Label is To ForecastCategory .
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
OpportunityId	Type reference Properties Filter, Group, Sort Description ID of the associated Opportunity.

Field	Details
Probability	Type percent Properties Filter, Nillable, Sort Description Percentage of estimated confidence in closing the opportunity.
StageName	Type picklist Properties Filter, Group, Sort Description Name of the current stage of the opportunity (for example, Prospect or Proposal).

Usage

This object represents the history of a change to the `Amount`, `Probability`, `Stage`, or `Close Date` fields of an Opportunity. The `OpportunityFieldHistory` object represents the history of a change to any of the fields of an Opportunity. To obtain information about how a particular opportunity is progressing, query the `OpportunityHistory` records associated with a given Opportunity. Please note that if an opportunity's `Amount`, `Probability`, `Stage`, or `Close Date` fields have not changed, nothing will be returned in the `OpportunityHistory` objects. In this case, query the `OpportunityFieldHistory` records associated with a given Opportunity to get more information about changes to the opportunity.

This object is read-only. The system generates a new record whenever a user or client application changes the value of any of the above fields; the then-current values of all of these major fields are saved in the newly-generated object.

This object respects field-level security on the parent object.



Note: The record is automatically deleted if its parent Opportunity is deleted.

OpportunityLineItem

Represents an opportunity line item, which is a member of the list of `Product2` products associated with an Opportunity.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

The user must have the “Edit” permissions on Opportunity records in order to create or update opportunity line items on an opportunity.

Fields

Field	Details
ConnectionReceivedId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
ConnectionSentId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the ConnectionSentId field is no longer supported. The ConnectionSentId field is still visible, but the value is null. You can use the new PartnerNetworkRecordConnection object to forward records to connections.
CurrencyIsoCode	Type picklist Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization. If the organization has multicurrency enabled, and a Pricebook2 is specified on the parent opportunity (that is, the Pricebook2Id field is not blank on the opportunity referenced by this object's OpportunityId), then the value of this field must match the currency of the CurrencyIsoCode field on the PricebookEntry records that are associated with this object.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Text description of the opportunity line item. Limit: 255 characters.

Field	Details
Discount	Type percent Properties Filter, Nillable, Sort Description Discount for the product as a percentage. When updating these records: • If you specify <code>Discount</code> without specifying <code>TotalPrice</code>, the <code>TotalPrice</code> is adjusted to accommodate the new <code>Discount</code> value, and the <code>UnitPrice</code> is held constant. • If you specify both <code>Discount</code> and <code>Quantity</code>, you must also specify either <code>TotalPrice</code> or <code>UnitPrice</code> so the system knows which one to automatically adjust.
HasQuantitySchedule	Type boolean Properties Defaulted on create, Filter, Group Description Read-only. Indicates whether a quantity schedule has been created for this object (<code>true</code>) or not (<code>false</code>).
HasRevenueSchedule	Type boolean Properties Defaulted on create, Filter, Sort Description Indicates whether a revenue schedule has been created for this object (<code>true</code>) or not (<code>false</code>). If this object has a revenue schedule, the <code>Quantity</code> and <code>TotalPrice</code> fields can't be updated. In addition, the <code>Quantity</code> field can't be updated if this object has a quantity schedule. Update requests aren't rejected but the updated values are ignored.
HasSchedule	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If either <code>HasQuantitySchedule</code> or <code>HasRevenueSchedule</code> is <code>true</code>, this field is also <code>true</code>.

Field	Details
ListPrice	Type currency Properties Filter, Nillable, Sort Description Corresponds to the <code>UnitPrice</code> on the PricebookEntry that is associated with this line item, which can be in the standard pricebook or a custom pricebook. A client application can use this information to show whether the unit price (or sales price) of the line item differs from the pricebook entry list price.
Name	Type string Properties Filter, Nillable, Sort Description The opportunity line item name (known as “Opportunity Product” in the user interface). This read-only field is available in API version 30.0 and later.
OpportunityId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the associated Opportunity.
PricebookEntryId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required. ID of the associated PricebookEntry. Exists only for those organizations that have Products enabled as a feature. You can specify values for either this field or <code>ProductId</code>, but not both. For this reason, both fields are declared nillable.
ProductId	Type reference Properties Create, Filter, Nillable Description ID of the related Product record. This field is unavailable as of version 3.0 and is only provided for backward compatibility. The Product object is unavailable beginning with version 8.0.

Field	Details
	Use the <code>PricebookEntryId</code> field instead, specifying the ID of the <code>PricebookEntry</code> record.
<code>Product2Id</code>	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the related <code>Product2</code> record. This is a read-only field available in API version 30.0 and later. Use the <code>PricebookEntryId</code> field instead, specifying the ID of the <code>PricebookEntry</code> record.
<code>ProductCode</code>	Type string Properties Filter, Group, Nillable, Sort Description This read-only field is available in API version 30.0 and later. It references the value in the <code>ProductCode</code> field of the related <code>Product2</code> record.
<code>Quantity</code>	Type double Properties Create, Filter, Sort, Update Description Read-only if this record has a quantity schedule, a revenue schedule, or both a quantity and a revenue schedule. When updating these records: • If you specify <code>Quantity</code> without specifying the <code>UnitPrice</code>, the <code>UnitPrice</code> value will be adjusted to accommodate the new <code>Quantity</code> value, and the <code>TotalPrice</code> will be held constant. • If you specify both <code>Discount</code> and <code>Quantity</code>, you must also specify either <code>TotalPrice</code> or <code>UnitPrice</code> so the system can determine which one to automatically adjust.
<code>RecalculateTotalPrice</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description Changes behavior of OpportunityLineItem calculations when a line item has child schedule rows for the <code>Quantity</code> value. When enabled, if the rollup quantity changes, then the quantity rollup value is multiplied against the sales price to change the total price. <code>Product2</code> flag must be set to true.
<code>ServiceDate</code>	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date when the product revenue will be recognized and the product quantity will be shipped. Whether this value is used by customizable forecasting depends upon the Forecast Date setting for the organization: • Opportunity Close Date—<code>ServiceDate</code> is ignored. • Product Date—<code>ServiceDate</code> is used if not null. • Schedule Date—<code>ServiceDate</code> is used if not null and there are no revenue schedules present for this line item, that is, there are no OpportunityLineItemSchedule records with a field <code>Type</code> value of Revenue that are children of this record.
<code>SortOrder</code>	Type int Properties Filter, Group, Nillable, Sort Description Number indicating the sort order selected by the user. Client applications can use this to match the sort order in Salesforce.
<code>Subtotal</code>	Type currency Properties Filter, Nillable Description Difference between standard and discounted pricing. Converted currency amounts when the opportunity's currency is different from the user's currency.
<code>TotalPrice</code>	Type currency Properties Create, Defaulted on create, Filter, Nillable, Sort, Update

Field	Details
	Description This field is available only for backward compatibility. It represents the total price of the OpportunityLineItem. If you do not specify <code>UnitPrice</code>, this field is required. If you specify <code>Discount</code> and <code>Quantity</code>, this field or <code>UnitPrice</code> is required. When updating these records, you can change either this value or the <code>UnitPrice</code>, but not both at the same time. This field is nillable, but you can't set both <code>TotalPrice</code> and <code>UnitPrice</code> to null in the same update request. To insert the <code>TotalPrice</code> via the API (given only a unit price and the quantity), calculate this field as the unit price multiplied by the quantity. This field is read-only if the opportunity line item has a revenue schedule. If the opportunity line item does not have a schedule or only has quantity schedule, this field can be updated.
UnitPrice	Type currency Properties Create, Defaulted on create, Filter, Nillable, Sort, Update Description The unit price for the opportunity line item. In the Salesforce user interface, this field's value is calculated by dividing the total price of the opportunity line item by the quantity listed for that line item. Label is Sales Price. This field or <code>TotalPrice</code> is required. You can't specify both. If you specify <code>Discount</code> and <code>Quantity</code>, this field or <code>TotalPrice</code> is required.

Usage

An Opportunity can have associated OpportunityLineItem records only if the Opportunity has a Pricebook2. An OpportunityLineItem must correspond to a Product2 that is listed in the opportunity's Pricebook2. For information about inserting OpportunityLineItem for an opportunity that does not have an associated Pricebook2 or any existing line items, see [Effects on Opportunities](#).

This object is defined only for those organizations that have products enabled as a feature. If the organization does not have the products feature, this object does not appear in the `describeGlobal()` call, and you can't use `describeObjects()` or query the OpportunityLineItem object.

For a visual diagram of the relationships between OpportunityLineItem and other objects, see [Product and Schedule Objects](#).



Note: If multicurrency option has been enabled, the `CurrencyIsoCode` field is present. It can't be modified, and is always set to the value of the `CurrencyIsoCode` of the parent Opportunity.

Effects on Opportunities

Opportunities that have associated OpportunityLineItem records are affected in the following ways:

- Creating an OpportunityLineItem increments the Opportunity `Amount` value by the `TotalPrice` of the OpportunityLineItem. Additionally, inserting an OpportunityLineItem increments the `ExpectedRevenue` on the opportunity by the `TotalPrice` times the opportunity `Probability`.

- The Opportunity `Amount` becomes a read-only field when the opportunity has line items. The API ignores any attempt to update this field on an opportunity with line items. Update requests are not rejected, but the updated value is ignored.
- You can't update the `PricebookId` field or the `CurrencyIsoCode` field on the opportunity if line items exist. The API rejects any attempt to update these fields on an opportunity with line items.
- When you create or update an `OpportunityLineItem`, the API verifies that the line item corresponds to a `PricebookEntry` in the `Pricebook2` that is associated with the opportunity. If the opportunity does not have an associated `Pricebook2`, the API automatically sets the pricebook on the opportunity if the line item corresponds to a `PricebookEntry` in an active `Pricebook2`, and if the `PricebookEntry` has a `CurrencyIsoCode` field that matches the `CurrencyIsoCode` field of the opportunity. If the `Pricebook2` is not active or the `CurrencyIsoCode` fields do not match, an error is returned.
- The Opportunity `HasOpportunityLineItem` field is set to `true` when an `OpportunityLineItem` is inserted for that Opportunity.

OpportunityLineItemSchedule

Represents information about the quantity, revenue distribution, and delivery dates for a particular `OpportunityLineItem`.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>CurrencyIsoCode</code>	Type picklist Properties Create, Defaulted on create, Filter, Nillable, Restricted picklist, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization. This field is available in version 10.0 and later.
<code>Description</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Text description of the opportunity line item schedule. Limit: 255 characters. Label is Comments.
<code>IsDeleted</code>	Type boolean

Field	Details
	Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
OpportunityLineItemId	Type reference Properties Create, Filter Description Required. ID of the associated OpportunityLineItem.
Quantity	Type double Properties Create, Filter, Nillable, Update Description Required. The total number of units to be scheduled in a quantity schedule.
Revenue	Type currency Properties Create, Filter, Nillable, Update Description The revenue that should be recognized, or the quantity that should be shipped, or both - depending upon the value of <code>Type</code>.
ScheduleDate	Type date Properties Create, Filter, Update Description Required. The date the associated OpportunityLineItem is to be scheduled for an event: delivery, shipping, or any other date you wish to track.
Type	Type picklist Properties Create, Filter, Restricted picklist

Field	Details
	Description The type of the schedule. Required when inserting an OpportunityLineItemSchedule. Valid values include <code>Quantity</code> , <code>Revenue</code> , or <code>Both</code> .

Allowed Type Field Values

The allowed `Type` values for an OpportunityLineItemSchedule depend on the product-level schedule preferences and whether the line item has any existing schedules. The following criteria must be met:

- The Product2 on which the OpportunityLineItem is based must have the appropriate `CanUseRevenueSchedule` or `CanUseQuantitySchedule` fields (or both) set to `true`.
- When you create a schedule for a line item that does not have any existing schedules, you can specify any valid value.
- If you create a schedule for a line item that already has existing schedules, the new schedule must be consistent with the existing schedules. The following matrix outlines the allowable values:

Value of HasRevenueSchedule on line item	Value of HasQuantitySchedule on line item	Allowable Type Values
false	false	Revenue, Quantity, both
false	true	Quantity
true	false	Revenue
true	true	both

Allowed Quantity and Revenue Field Values

The allowable `Quantity` and `Revenue` field values depend on the value of the `Type` field:

Type Value	Allowable Quantity Value	Allowable Revenue Value
Revenue	Null	Non-null
Quantity	Non-null	Null
both	Non-null	Non-null

The `Quantity` and `Revenue` fields have the following restrictions when this object is updated:

- For a schedule of `Type Quantity`, you can't update a null `Revenue` value to non-null. Likewise for a schedule of `Type Revenue`, you can't update a null `Quantity` value to non-null.
- You can't null out the `Quantity` field for a schedule of `Type Quantity`. Likewise you can't null out the `Revenue` field for a schedule of `Type Revenue`.
- You can't null out either the `Revenue` or `Quantity` fields for a schedule of type `Both`.

Usage

OpportunityLineItemSchedule supports two types of schedules:

- Quantity schedules
- Revenue schedules

The user must have edit access rights on the Opportunity in order to create or update line item schedules on that opportunity.

Products and Schedules Must Be Enabled

The OpportunityLineItemSchedule object is defined only for those organizations that have the products and schedules features enabled. If the organization does not have the products and schedules features, the OpportunityLineItemSchedule object is not returned in a describe, and you can't describe or query OpportunityLineItemSchedule records.

Effects on Opportunities and Opportunity Line Items

OpportunityLineItemSchedule records affect opportunities and opportunity line items in the following ways:

- Inserting an OpportunityLineItemSchedule of Type "Revenue" or "Quantity" increments the TotalPrice field on the OpportunityLineItem by the OpportunityLineItemSchedule Revenue amount. Inserting an OpportunityLineItemSchedule of Type Quantity or Both increments the Quantity field on the OpportunityLineItem by the OpportunityLineItemSchedule Quantity amount.
- Creating an OpportunityLineItemSchedule record affects the original opportunity:
 1. The Opportunity Amount is incremented by the OpportunityLineItemSchedule revenue amount
 2. The Opportunity ExpectedRevenue is incremented by the line item schedule amount multiplied by the Opportunity Probability
- Deleting an OpportunityLineItemSchedule has a similar effect on the related OpportunityLineItem and Opportunity. Deleting an OpportunityLineItemSchedule decrements the OpportunityLineItem TotalPrice by the deleted OpportunityLineItemSchedule Quantity or Revenue amount. The Opportunity Amount is also decremented by the OpportunityLineItemSchedule Quantity or Revenue amount, and the Opportunity ExpectedRevenue is reduced by OpportunityLineItemSchedule Quantity or Revenue amount multiplied by the Opportunity Probability.

Deleting an Opportunity Line Item Schedule

Deleting the last remaining schedule will set the corresponding HasQuantitySchedule or HasRevenueSchedule flags (or both) to false on the parent line item.

OpportunityOverride

A forecast override of an Opportunity. This read-only object is specific to customizable forecasting. It has a parent-child relationship with LineItemOverride

Supported Calls

`create()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Requires the “View All Data” permission.

Fields

Field	Details
AmountInherited	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the overridden amount rolls up through the forecast hierarchy (<code>true</code>), or was overridden by the owner of the OpportunityOverride (<code>false</code>).
ForecastCategoryInherited	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the overridden forecast category rolls up through the forecast hierarchy (<code>true</code>) or was overridden by the owner of the OpportunityOverride (<code>false</code>).
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
OpportunityId	Type reference Properties Create, Filter, Group, Sort Description ID of the associated Opportunity.
OutOfDate	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description true if a subordinate user's OpportunityOverride, or the opportunity itself, has been updated since this override was last updated, such that an overridden value on this override may be obsolete. For example, a subordinate user has more recently overridden the same period, category, or amount field.
OverrideAmount	Type currency Properties Create, Filter, Sort, Update Description The total monetary amount of the opportunity, possibly overridden.
OverrideComment	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The comment entered on the opportunity forecast edit page. Limit: 255 characters.
OverrideForecastCategory	Type picklist Properties Create, Filter, Group, Sort, Update Description The forecast category of the opportunity, possibly overridden.
OverridePeriodId	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the associated fiscal Period, possibly overridden. If you are using custom fiscal years and the period falls after your custom fiscal year has ended, then the override is not returned.
OverrideQuantity	Type double Properties Create, Filter, Sort, Update

Field	Details
	Description The quantity of the opportunity, possibly overridden.
OwnerId	Type reference Properties Create, Filter, Group, Sort Description ID of the OpportunityOverride owner.
PeriodInherited	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the overridden period rolls up through the forecast hierarchy (<code>true</code>) or was overridden by the OpportunityOverride owner (<code>false</code>).
QuantityInherited	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the overridden quantity rolls up through the forecast hierarchy (<code>true</code>) or was overridden by the OpportunityOverride owner (<code>false</code>).

OpportunityOwnerSharingRule

Represents the rules for sharing an opportunity with users other than the owner.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. Opportunities owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.

Field	Details
OpportunityAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing being allowed. The possible values are: • Read • Edit
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the target user or group. The target user or group is being given access.

Usage

Use this object to manage the sharing rules for opportunities. General sharing and Territory-related sharing use this object.

OpportunityPartner

This read-only object represents a partner relationship between an Account and an Opportunity. This object is automatically created when a Partner object is created for a partner relationship between an account and an opportunity.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
AccountToId	Type reference Properties Filter, Group, Sort Description ID of the partner Account in the partner relationship.

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsPrimary	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the account is the opportunity's primary partner (<code>true</code>) or not (<code>false</code>). Label is Primary.
OpportunityId	Type reference Properties Filter, Group, Sort Description ID of the Opportunity that is in the partner relationship.
Role	Type picklist Properties Filter, Group, Nillable, Sort Description The UserRole that the Account has on the Opportunity. For example, Reseller or Manufacturer.

Creating an Account-Opportunity Partner Relationship

When you create a partner relationship between an account and an opportunity (when you create a Partner object and specify the `OpportunityId` field), the API automatically creates an OpportunityPartner with the corresponding values:

- The value of the Partner field `AccountToId` maps to the value of the OpportunityPartner field `AccountToId`.
- The values of the `OpportunityId`, `Role`, and `IsPrimary` fields in both objects are the same.
- If you set the `IsPrimary` value to 1 (`true`) upon insert of a new OpportunityPartner, any other existing primary partners for that opportunity will automatically have the `IsPrimary` value set to 0 (`false`).

This mapping allows the API to manage the objects and their relationship efficiently.

OpportunityShare

Represents a sharing entry on an Opportunity.

Supported Calls

`describeSObjects()`, `create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
<code>OpportunityAccessLevel</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Level of access that the user or group has to the opportunity. The possible values are: • <code>Read</code> • <code>Edit</code> • <code>All</code> This value is not valid when creating, updating, or deleting records. This field must be set to an access level that is higher than the organization's default access level for opportunities.
<code>OpportunityId</code>	Type reference Properties Filter, Group, Sort Description ID of the Opportunity associated with this sharing entry. This field can't be updated.
<code>RowCause</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field	Details
	Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to <code>Manual</code> (default). Valid values include: <code>Owner</code>—The User is the owner of the Opportunity. <code>Manual</code>—User or group has access because a user with “All” access manually shared the opportunity with them. <code>Rule</code>—User or group has access via an opportunity sharing rule. <code>ImplicitChild</code>—User or group has access to the opportunity on the Account associated with this Opportunity. <code>Sales Team</code>—User has access to the opportunity because she or he is on the opportunity sales team for the opportunity. The <code>OpportunityTeamMember</code> object for this opportunity sets the access level. See <code>OpportunityTeamMember</code> for more information.
<code>UserOrGroupId</code>	Type reference Properties Filter, Group, Sort Description ID of the User or Group that has been given access to the opportunity. This field can't be updated.

Usage

This object allows you to determine which users and groups can view or edit opportunities owned by other users.

If you attempt to create a record that matches an existing record, any modified fields are updated, the system returns the existing record.

OpportunitySplit

`OpportunitySplit` credits one or more opportunity team members with a portion of the opportunity amount. This object is available in API version 16.0 and later for pilot customers, and version 28.0 and later for others.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>OpportunityId</code>	Type reference

Field	Details
	Properties Create, FilterGroup, Sort Description ID of the opportunity for which the split is being created. Label is <code>Opportunity ID</code>.
Split	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description Read-only. Automatically-generated number identifying the split within the opportunity.
SplitAmount	Type currency Properties Filter, Nillable, Sort Description Monetary amount of the split. Label is <code>Split Amount</code>.
SplitNote	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Enter any notes or comments about the split. Character limit is 255. Label is <code>Split Note</code>.
SplitOwnerId	Type reference Properties Create, Filter, Group, Sort Description The opportunity owner. Label is <code>User ID</code>.
SplitPercentage	Type percent

Field	Details
	Properties Create, Filter, Sort, Update Description Split percentage that this team member will receive. If the split type is validated to a 100% total, this number can range from 0 to 100. If the total isn't validated, this number can range from 0 to 1,000. Label is <code>Split (%)</code> .
<code>SplitTypeId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Auto-generated, numeric ID for the split type defined by the OpportunitySplitType object. This field is available in API version 28 and later. If this field is blank, the system automatically specifies the default split type for the opportunity amount, which is validated to 100%.

Usage

Use the OpportunitySplit object to manage splits for an opportunity.

If you change the opportunity owner using the API, the old owner remains on the opportunity team with either Read-only access, or the level of access specified in your organization-wide defaults.

OpportunitySplitType

OpportunitySplitType provides unique labels and behavior for each split type. This object is available in API version 28.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
Description	Type textarea Properties Create, Filter, Group, Sort, Update

Field Name	Details
	Description Describes the purpose of the split type, providing context to future developers.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description Required. The unique name of the object in the API. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Enables or disables the split type.
IsTotalValidated	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description If <code>true</code> , the split must total 100%. If <code>false</code> , the split can total any percentage.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Indicates language of split labels in the user interface.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update

Field Name	Details
	Description The user-interface label for the split type.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <i>NamespacePrefix</i> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.

Usage

Use OpportunitySplitType if your organization uses different naming conventions for the default Revenue and Overlay splits.

OpportunityStage

Represents the stage of an Opportunity in the sales pipeline, such as New Lead, Negotiating, Pending, Closed, and so on.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
DefaultProbability	Type percent Properties Filter, Nillable, Sort, Description The default percentage estimate of the confidence in closing a specific opportunity for this opportunity stage value. Label is Probability (%).
Description	Type string Properties Filter, Group, Nillable, Sort Description Description of this opportunity stage value. Limit: 255 characters.
ForecastCategory	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The default forecast category for this opportunity stage value. The forecast category automatically determines how opportunities are tracked and totaled in a forecast.
ForecastCategoryName	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Available in API version 12.0 and later. The default forecast category value for this opportunity stage value.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this opportunity stage value is active (<code>true</code>) or not (<code>false</code>). Inactive opportunity stage values are not available in the picklist and are retained for historical purposes only.

Field	Details
IsClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this opportunity stage value represents a closed opportunity (<code>true</code>) or not (<code>false</code>). Multiple opportunity stage values can represent a closed opportunity. Label is Closed.
IsWon	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this opportunity stage value represents a won opportunity (<code>true</code>) or not (<code>false</code>). Multiple opportunity stage values can represent a won opportunity. Label is Won.
MasterLabel	Type string Properties Filter, Group, Nillable, Sort Description Master label for this opportunity stage value. This display value is the internal label that does not get translated. Limit: 255 characters.
SortOrder	Type int Properties Filter, Group, Nillable, Sort Description Number used to sort this value in the opportunity stage picklist. These numbers are not guaranteed to be sequential, as some previous opportunity stage values might have been deleted.

Usage

This object represents a value in the opportunity stage picklist, which provides additional information about the stage of a Opportunity, such as its probability or forecast category. Query this object to retrieve the set of values in the opportunity stage picklist, and then use that information while processing Opportunity records to determine more information about a given opportunity. For example, the application could test whether a given opportunity is won or not based on its `StageName` value and the value of the `IsWon` property in the associated OpportunityStage object.

This object is read-only via the API.

OpportunityTag

Associates a word or short phrase with an Opportunity.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization.

Field Name	Details
	Personal—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

OpportunityTag stores the relationship between its parent TagDefinition and the Opportunity being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

OpportunityTeamMember

Represents a User on the opportunity team of an Opportunity.

See also `UserTeamMember`, which represents a User who is on the default opportunity team of another user.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>CurrencyIsoCode</code>	Type picklist Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.  Note: Any OpportunityTeamMember record that is deleted is not moved to the Recycle Bin, and cannot be undeleted, unless the record was cascade-deleted

Field	Details
	when deleting a related Opportunity. For directly deleted OpportunityTeamMember records, don't use the isDeleted field to detect deleted records in SOQL queries or <code>queryAll()</code> calls. Instead, use <code>getDeleted()</code>.
Name	Type string Properties Filter, Nillable, Sort Description The team member name. This read-only field is available in API version 30.0 and later.
OpportunityAccessLevel	Type picklist Properties Filter, Nillable, Restricted picklist Description Opportunity access level for this team member. Valid values: • None • Read • Edit • All
OpportunityId	Type reference Properties Create, Filter Description Required. ID of the Opportunity associated with this opportunity team. This field can't be updated.
PhotoURL	Type URL Properties Filter, Nillable, Sort, Group Description Retrieves the users Chatter photo URL. The field is read only. This field is available in API version 32.0 and later.
TeamMemberRole	Type picklist Properties Create, Filter, Nillable, Update

Field	Details
	Description Role that the team member has on the opportunity. The valid values are set by the organization's administrator in the Opportunity Team Roles picklist. Label is Team Role .
UserId	Type reference Properties Create, Filter Description Required. ID of the User who is a member of the opportunity team. This field can't be updated.

Usage

If you attempt to create a record for this object and it matches an existing record, the system updates any modified fields and returns the existing record.

In the user interface, users can set up an opportunity team for the opportunities they own. The opportunity team includes other users that are working on the opportunity with them. This object is available only in organizations that have enabled team selling.



Note: The behavior for changing ownership of opportunities is different using the user interface when the previous owner is on an opportunity team. For example, when you change the owner of an opportunity using the API, the previous owner's access becomes Read Only or the access specified in your organization-wide default for opportunities, whichever is greater. However, performing this same action in the user interface allows you to select the access level for the previous owner when he or she is on an opportunity team.

Order

Represents an order associated with a contract or an account.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
AccountId	Type reference

Field Name	Details
	Properties Create, Filter, Nillable, Group, Sort, Update Description Required. ID of the Account associated with this order. Can only be updated when the order's <code>StatusCode</code> value is <i>Draft</i> .
ActivatedById	Type reference Properties Filter, Group, Nillable, Sort, Update Description ID of the User who activated this order.
ActivatedDate	Type dateTime Properties Filter, Nillable, Sort, Update Description Date and time when the order was activated.
BillingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description City for the billing address for this order. Maximum size is 40 characters.
BillingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Country for the billing address for this order. Maximum size is 80 characters.
BillingCountryCode (beta)	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO country code for the billing address for this order.

Field Name	Details
BillingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLongitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
BillingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLatitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
BillingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Postal code for the billing address for this order. Maximum size is 20 characters.
BillingState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description State for the billing address for this order. Maximum size is 80 characters.
BillingStateCode (beta)	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO state code for the order's billing address.
BillingStreet	Type textarea

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description Street address for the billing address.
BillToContactId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the contact that the order will be billed to.
CompanyAuthorizedById	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the user who authorized the account associated with the order.
CompanyAuthorizedDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date on which the order was authorized by your organization.
ContractId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the contract associated with this order. Can only be updated when the order's <i>StatusCode</i> value is <i>Draft</i> .
CustomerAuthorizedById	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the contact who authorized the order.

Field Name	Details
CustomerAuthorizedDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date on which the contact authorized the order.
Description	Type textarea Properties Create, Nillable, Update Description Description of the order.
EffectiveDate	Type date Properties Create, Filter, Group, Sort, Update Description Date at which the order becomes effective. Label is Order Start Date.
End Date	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date at which the order ends. Label is Order End Date.
IsReductionOrder	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Read-only. Determines whether an order is a reduction order. Label is Reduction Order.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort

Field Name	Details
	Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (LastReferencedDate) and not viewed.
Name	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Name for this order.
OpportunityId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID for the opportunity that's associated with this order.
OrderNumber	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description Order number assigned to this order (not the unique, system-generated ID assigned during creation). Maximum size is 30 characters.
OrderReferenceNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Order reference number assigned to this order. Maximum size is 80 characters.

Field Name	Details
OriginalOrderId	Type reference Properties Create, Defaulted on create, Filter, Group, Nillable, Sort Description Optional. ID of the original order that a reduction order is reducing, if the reduction order is reducing a single order. Label is Original Order. Editable only if <code>isReductionOrder</code> is <code>true</code>. If the reduction order is reducing more than one order, leave blank.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Required. ID of the User or queue that owns this order.
PoDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Date of the purchase order.
PoNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Number identifying the purchase order. Maximum is 80.
Pricebook2Id	Type reference Properties Create, Defaulted on create, Filter, Group, Nillable, Sort, Update Description Required. ID of the price book associated with this order.
QuoteId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the quote that's associated with this order. If you set <code>QuoteId</code> to null, <code>QuoteLineItemId</code> on all of the order's child order products is set to null.
RecordTypeId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the record type assigned to this order.
ShippingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description City of the shipping address. Maximum size is 40 characters.
ShippingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Country of the shipping address. Maximum size is 80 characters.
ShippingCountryCode (beta)	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO country code for the order's shipping address.
ShippingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update

Field Name	Details
	Description Used with <code>ShippingLongitude</code> to specify the precise geolocation of a shipping address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
<code>ShippingLongitude</code>	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLatitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
<code>ShippingPostalCode</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Postal code of the shipping address. Maximum size is 20 characters.
<code>ShippingState</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description State of the shipping address. Maximum size is 80 characters.
<code>ShippingStateCode</code> (beta)	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO state code for the order's shipping address.
<code>ShippingStreet</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Street address of the shipping address. Maximum of 255 characters.

Field Name	Details
ShipToContactId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the contact the order will be shipped to.
Status	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Picklist of values that indicate order status. Each value is within one of two status categories defined in <code>StatusCode</code>. For example, the status picklist might contain <i>Draft</i>, <i>Ready for Review</i>, and <i>Ready for Activation</i> values with a <code>StatusCode</code> of <i>Draft</i>.
StatusCode	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description The status category for the order. An order can be either <i>Draft</i> or <i>Activated</i>. Label is Status Category.
TotalAmount	Type currency Properties Filter, Sort Description The total amount for the order products associated with this order.
Type	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The type of order.

Usage

The `Status` field specifies the current state of an order. Status strings represent its current state (*Draft* or *Activated*).

When a client application creates an order, the `Status Code` must be *Draft* and the `Status` must be any value that corresponds to a `Status Code` of *Draft*. The application can subsequently activate an order by updating it and setting the value in its `Status` field to an *Activated* state; however, the `Status` field is the only field you can update when activating the order.

After an order is activated, your client application can change the `Status` back to the *Draft* state—but only if the order doesn't have any child reduction order products. Your client application can delete orders when the `Status` is *Draft* but not when its `Status` is *Activated*.

Client applications can use the API to create, update, delete, and query any Attachment associated with an order.

OrderFeed

Represents a single feed item in the feed displayed on an order.

Supported Calls

`delete()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the OrderFeed. Required when <code>Type</code> is <code>TextPost</code> . Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code> . This is the message that appears in the feed.
CommentCount	Type int

Field Name	Details
	Properties Filter , Group , Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code> .
ContentDescription	Type textarea Properties Create, Nillable, Sort Description The description of the file specified in <code>ContentData</code> .
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code> .
ContentSize	Type int Properties Group , Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group , Nillable, Sort

Field Name	Details
	Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>:

Field Name	Details
	- Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the order record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing <code>ContentVersion</code> and post it to a feed as a <code>FeedItem</code> object of <code>Type ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of <code>FeedItem</code>: <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging).

Field Name	Details
	For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case. • CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • CaseCommentPost—generated event when a user adds a case comment for a case object. • ChangeStatusPost—generated event when a user changes the status of a case.

Field Name	Details
	• <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>. • <code>Visibility</code> can be updated on record posts.

Usage

Use this object to track changes for an order record.

OrderHistory

Represents historical information about changes that have been made to the standard fields of the associated order, or to any custom fields with history tracking enabled.

Supported Calls

`getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Name of the order field that was modified, or a special value to indicate some other modification to the order.
NewValue	Type anyType Properties Nillable, Sort Description New value of the modified order field. Maximum of 255 characters.
OldValue	Type anyType Properties Nillable, Sort Description Previous value of the modified order field. Maximum of 255 characters.
OrderId	Type reference Properties Filter, Group, Sort Description ID of the order associated with this record.

Usage

Order history entries are automatically created each time an order is modified.

Two rows are added to this record when foreign key fields change. One row contains the foreign key object names that display in the online application. For example, `Jane Doe` is recorded as the name of a Contact. The other row contains the actual foreign key ID that is only returned to and visible from the API.

This object respects field-level security on the parent object.

OrderItem

Represents an order product that your organization sells.

Supported Calls

`create()`, `delete()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
AvailableQuantity	Type double Properties Filter, Nillable, Sort Description Amount of an order product that is available to be reduced. Value must be greater than or equal to 0. An order product is reducible only if AvailableQuantity is greater than 0. Value is always 0 if the order product's parent order is a reduction order.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Text description of this object.
EndDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Optional. Last day the order product is available.
ListPrice	Type currency Properties Filter, Nillable, Sort

Field Name	Details
	Description List price for the order product. Value is inherited from the associated <code>PriceBookEntry</code> upon order product creation.
<code>OrderId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the order that this order product is a child of.
<code>OrderItemNumber</code>	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description Automatically-generated number that identifies the order product.
<code>OriginalOrderItemId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required if <code>isReductionOrder</code> on the parent order is <code>true</code> . ID of the original order product being reduced.
<code>PricebookEntryId</code>	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the associated <code>PricebookEntry</code> . This field must be specified when creating <code>OrderItem</code> records. It can't be changed in an update.
<code>Quantity</code>	Type double Properties Create, Filter, Sort, Update Description Number of units of this order product.

Field Name	Details
	If you specify <code>Quantity</code> without specifying <code>UnitPrice</code>, <code>UnitPrice</code> is adjusted to accommodate the new <code>Quantity</code> value while keeping <code>TotalPrice</code> constant.
<code>QuoteLineItemId</code>	Type reference Properties Create, Filter, Group, Sort, Update Description ID of the associated quote line item. If this field is specified, the quote line item's <code>Quoteld</code> must match the <code>Quoteld</code> for the order product's parent order.
<code>ServiceDate</code>	Type date Properties Create, Filter, Nillable, Sort, Update Description Start date for the order product. Label is Start Date.
<code>UnitPrice</code>	Type currency Properties Create, Filter, Nillable, Sort, Update Description Unit price for the order product. In the Salesforce user interface, this field's value is calculated by dividing the total price of the order product by the quantity listed for that order product.

Usage

An order can have associated order product records only if the order has a price book associated with it. An order product must correspond to a product that is listed in the order's price book.

OrderItemFeed

Represents a single feed item in the feed displayed on the detail page for an order product record. An order product feed shows changes to an order product for fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to order products in Salesforce.

Supported Calls

`delete()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group, Nillable, Sort

Field Name	Details
	Description The file uploaded to the feed. Required if Type is ContentPost. The name of the file uploaded to the feed. Setting ContentFileName automatically sets Type to ContentPost.
ContentSize	Type string Properties Group, Nillable, Sort Description Read-only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type int Properties Group, Nillable, Sort Description Read-only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then InsertedById is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort

Field Name	Details
	Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Create , Filter , Group , Nillable , Sort Description Specifies whether this feed item is available in the default community , a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope: • Only feed items with a Group or User parent can set a NetworkId or a null value for NetworkScope. • For feed items with a record parent, users can set NetworkScope only to AllNetworks. • You can't filter a FeedItem on the NetworkScope field.
ParentId	Type string Properties Filter , Group , Sort Description ID of the account record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group , Nillable , Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of TypeContentPost.

Field Name	Details
Title	Type string Properties Group, Nillable, Sort Description The title of the FeedItem. When the Type is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of FeedItem: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with <code>CaseFeed</code> disabled, one event is generated for the series only. For a recurring Task with <code>CaseFeed</code> enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed.

Field Name	Details
	• <code>ProfileSkillPost</code>—generated when a skill is added to a user’s Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Visibility

Type

[picklist](#)

Properties

[Create](#), [Filter](#), [Group](#), [Nillable](#), [Sort](#)

Description

Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization.

`Visibility` can have the following values:

Field Name	Details
	<code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: - For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. - External users can set <code>Visibility</code> only to <code>AllUsers</code>. - On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>. <code>Visibility</code> can be updated on record posts.

Usage

Use this object to track changes for an order product record.

OrderItemHistory

Represents the history of changes to the values in the fields of an order product.

Supported Calls

`getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>Field</code>	Type picklist Properties Group, Restricted picklist, Sort Description The name of the field that was changed.
<code>NewValue</code>	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.

Field Name	Details
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.
OrderItemId	Type reference Properties Group, Sort Description ID of the order product. Label is Order Product ID .

Usage

Use this object to identify changes to an order product.

This object respects field-level security on the parent object.

OrderOwnerSharingRule

Represents a rule which determines order sharing access for the order's owners.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
CreatedById	Type reference

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description ID of the creator of the order owner sharing rule.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date when the order owner sharing rule was created.
Description	Type string Properties Create, Filter, Nillable, Sort, Update Description Description of the order owner sharing rule. Maximum length is 1,000 characters.
DeveloperName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Name of the developer of the order owner sharing rule.
GroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the group whose orders are shared.
Id	Type ID Properties Defaulted on create, Filter, Group, idLookup, Sort Description ID of the order owner sharing rule.
LastModifiedById	Type reference

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description ID of the user who last modified the order owner sharing rule.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date when the order owner sharing rule was last modified.
Name	Type string Properties Create, Filter, Group, idLookup, Namefield, Sort, Update Description Name of the order owner sharing rule. Maximum length is 80 characters.
OrderAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Access level for the order owner sharing rule.
SystemModstamp	Type dateTime Properties Defaulted on create, Filter, Sort Description System modification time for the order owner sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group with whom order access is shared.

Usage

Use this object to manage the sharing rules for orders. For example, the following code creates an order owner sharing rule between two public groups, which can also contain portal users.

```
OrderOwnerSharingRule rule = new OrderOwnerSharingRule();
rule.setName("RuleName"); // Set the sharing rule name
rule.setDeveloperName("RuleDeveloperName"); // Set the sharing rule developer name
rule.setGroupId("00Gx000000000000"); // Set the group of users to share records from
rule.setUserOrGroupId("00Gx000000000001"); // Set the group of users to share records to
rule.setOrderAccessLevel("Edit");
connection.create(rule);
```

Organization

This object represents key configuration information for an organization.

Supported Calls

describeSObjects(), getDeleted(), getUpdated(), query(), retrieve(), update()

Executing a SOQL SELECT query returns the value of fields in this object, but no value is visible for some of the fields.

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
Address (beta)	Type address Properties Filter, Nillable Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.
AllowsSelfServiceLogin	Type boolean Properties Defaulted on create, Filter, Update Description Indicates whether the organization allows Self-Service login (<code>true</code>) or not (<code>false</code>).

Field	Details
City	Type string Properties Filter, Group, Nillable, Sort, Update Description Name of the city for the organization's address.
ComplianceBccEmail	Type email Properties Filter, Group, Nillable, Sort Description Email address for compliance blind carbon copies. Limit: 80 characters.
Country	Type string Properties Filter, Group, Nillable, Sort Description Name of the country for the organization's address. Limit: 80 characters.
CountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the organization's address.
DailyWebToCaseCount	Type int Properties Filter, Nillable Description The number of web form submissions that have been converted to cases for the day.
DailyWebToCaseLimit	Type int Properties Filter, Nillable

Field	Details
	Description The maximum number of web form submissions that can be converted to cases per day.
DailyWebToLeadCount	Type int Properties Filter, Nillable Description The number of web form submission that have been converted to leads for the day
DailyWebToLeadLimit	Type int Properties Filter, Nillable Description The maximum number of web form submissions that can be converted to leads per day.
DefaultAccountAccess	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description In API version 10.0 and later, represents the default access level for accounts, contracts, and assets. The possible values are: • None • Read • Edit In versions before 10.0, <code>DefaultAccountAndContactAccess</code> represented this value.
DefaultAccountAndContactAccess	Type picklist Properties Filter, Nillable, Restricted picklist Description Default access level for accounts, contacts, contracts, and assets. This field is supported for backward compatibility only and is not available in API version 10.0 or later. In version 10.0 and later, use

Field	Details
	either DefaultAccountAccess or DefaultContactAccess.
DefaultCalendarAccess	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Default access level for calendars. The possible values are listed, followed by the user interface labels in parentheses: • HideDetails (Hide Details) • HideDetailsInsert (Hide Details and Add Events) • ShowDetails (Show Details) • ShowDetailsInsert (Show Details and Add Events) • AllowEdits (Full Access)
DefaultCampaignAccess	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Default access level for campaigns. The possible values are: • None • Read • Edit • All
DefaultCaseAccess	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Default access level for cases. The possible values are: • None • Read • Edit • ReadEditTransfer
DefaultContactAccess	Type picklist

Field	Details
	Properties Filter, Group, Nillable, Restricted picklist, Sort Description Default access level for contacts. The possible values are: • None • Read • Edit • ControlledByParent In versions before 10.0, <code>DefaultAccountAndContactAccess</code> represented this value.  Note: When <code>DefaultContactAccess</code> is set to “Controlled by Parent,” you can’t update the <code>ContactAccessLevel</code> field.
<code>DefaultLeadAccess</code>	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Default access level for leads. The possible values are: • NoneRead • Edit • ReadEditTransfer
<code>DefaultLocaleSidKey</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description Default locale SID key.
<code>DefaultOpportunityAccess</code>	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Default access level for opportunities. The possible values are: • None • Read

Field	Details
	Edit
DefaultPricebookAccess	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Default access level for price books. The possible values are listed, followed by the user interface labels in parentheses: - None (No access) - Read (Read only) - ReadSelect (Use)
DefaultTerritoryAccountAccess	Type picklist Properties Filter, Group, Nillable, Sort Description Default access level for accounts in territories. The possible values are: - Read - Edit - All
DefaultTerritoryCaseAccess	Type picklist Properties Filter, Group, Nillable, Sort Description Default access level for cases associated with accounts in territories. The possible values are: - None - Read - Edit
DefaultTerritoryContactAccess	Type picklist Properties Filter, Group, Nillable, Sort

Field	Details
	Description Default access level for contacts associated with accounts in territories. The possible values are: • NoneRead • Edit  Note: When <code>DefaultContactAccess</code> is set to "Controlled by Parent" you can't update this field.
<code>DefaultTerritoryOppAccess</code>	Type picklist Properties Filter, Group, Nillable, Sort Description Default access level for opportunities in territories. Valid values: • NoneRead • Edit
<code>Division</code>	Type string Properties Filter, Nillable, Update Description The name of the division for this organization. This field is not related to the Division object.
<code>Fax</code>	Type phone Properties Filter, Group, Nillable, Sort, Update Description Fax number. Limit: 40 characters.
<code>FiscalYearStartMonth</code>	Type int Properties Filter, Group, Nillable, Sort Description Number that corresponds to the month that this organization's fiscal year starts.

Field	Details
HomepageHtml	Type textarea Properties Nillable, Update Description The Home tab custom links and company message for this organization.
InstanceName	Type string Properties Filter, Group, Nillable, Sort Description Read-only. The name of the instance. Available in API version 31.0 or later.
IsSandbox	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read-only. Indicates whether the current organization is a sandbox (<code>true</code>) or production (<code>false</code>) instance. Available in API version 31.0 or later.
LanguageLocaleKey	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description The same as <code>Language</code>, the two-to-five character code which represents the language and locale ISO code. This controls the language for labels displayed in an application.
LastWebToCaseDate	Type dateTime Properties Filter, Nillable Description The last date that a web form submission was converted to a case.

Field	Details
LastWebToLeadDate	Type dateTime Properties Filter, Nillable Description The last date that a web form submission was converted to a lead.
Latitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>Longitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
Longitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>Latitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
MaxActionsPerRule	Type int Properties Filter, Nillable Description Maximum number of actions per workflow, assignment, escalation, and auto-response rules. This field is unavailable in version 15.0 and later.
MaxRulesPerEntity	Type int Properties Filter, Nillable Description Maximum number of rules per object, inclusive of workflow, assignment, escalation, and auto-response rules. This field is unavailable in version 15.0 and later.

Field	Details
MonthlyPageViewsEntitlement	Type int Properties Filter, Group, Nillable, Sort Description The number of page views allowed for the current calendar month for the sites in your organization. To access this field, Force.com Sites must be enabled for your organization. This field is generally available in API versions 18.0 and later.
MonthlyPageViewsUsed	Type int Properties Filter, Group, Nillable, Sort Description The number of page views used in the current calendar month for the sites in your organization. To access this field, Force.com Sites must be enabled for your organization. This field is generally available in API versions 18.0 and later.
Name	Type string Properties Filter, Group, Sort, Update Description The name of the organization.
OrganizationType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Edition of the organization, for example Enterprise Edition or Unlimited Edition.
Phone	Type phone Properties Filter, Group, Nillable, Sort, Update Description Phone number for the organization.

Field	Details
PostalCode	Type string Properties Filter, Group, Nillable, Sort, Update Description Postal code for the address of the organization. Limit: 20 characters.
PreferencesEventScheduler	Type boolean Properties Update Description Indicates whether opportunities require products (<code>true</code>) or not (<code>false</code>).
PreferencesRequireOpportunityProducts	Type boolean Properties Filter, Update Description Indicates whether opportunities require products (<code>true</code>) or not (<code>false</code>).
PreferencesSlBrowserEnabled	Type boolean Properties Filter, Update Description Indicates whether the Salesforce1 mobile browser app is enabled for all users in your organization (<code>true</code>) or is disabled for all users (<code>false</code>). This field is available in API version 29.0 or later.
PrimaryContact	Type string Properties Filter, Group, Nillable, Sort, Update Description Name of the primary contact for the organization. Limit: 80 characters.

Field	Details
ReceivesAdminInfoEmails	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the organization receives administrator emails (<code>true</code>) or not (<code>false</code>).
ReceivesInfoEmails	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the organization receives informational email from Salesforce (<code>true</code>) or not (<code>false</code>).
SelfServiceCasePlural	Type string Properties Filter, Nillable, Update Description The plural version of the term used to represent the Case object in the Self-Service portal.
SelfServiceCaseSingle	Type string Properties Filter, Nillable, Update Description The singular version of the term used to represent the Case object in the Self-Service portal.
SelfServiceCaseSubmitRecordTypeId	Type reference Properties Filter, Nillable, Update Description The ID of the record type associated with a case submitted via the Self-Service portal.
SelfServiceDefaultCaseOrigin	Type string

Field	Details
	Properties Filter, Nillable, Update Description The default origin of a case submitted via the Self-Service portal.
SelfServiceEmailSenderAddress	Type email Properties Filter, Nillable, Update Description The Self-Service email address from which new Self-Service user and password email messages are sent, such as support@acme.com.
SelfServiceEmailSenderName	Type string Properties Filter, Nillable, Update Description The name associated with the email address in the SelfServiceEmailSenderAddress field, such as Acme Customer Support.
SelfServiceEmailUserOnCaseCreationTemplateId	Type reference Properties Filter, Nillable, Update Description The ID of the email template used when email is sent to a Self-Service user when he or she creates a case.
SelfServiceEnabledForResponseRules	Type boolean Properties Filter, Nillable, Update Description Indicates whether the Self-Service portal is enabled for auto-response rules (true) or not (false).
SelfServiceFeatureConfig	Type int Properties Filter, Nillable, Update

Field	Details
	Description An integer representing the active Self-Service feature configuration for this organization.
SelfServiceLogoutUrl	Type url Properties Filter, Nillable, Update Description The Web page that displays when a Self-Service user logs out of the Self-Service portal.
SelfServiceMaxNumSuggestions	Type int Properties Filter, Nillable, Update Description The maximum number of suggested solutions allowed for a Self-Service case.
SelfServiceNewCommentCheckedByDefault	Type boolean Properties Defaulted on create, Filter, Update Description If <code>true</code> , When a customer notification is automatically sent when a new comment is added to a case.
SelfServiceNewCommentTemplateId	Type reference Properties Filter, Nillable, Update Description The ID of the email template used to send a notification to Self-Service users when a public comment is added to one of their cases.
SelfServiceNewPassTemplateId	Type reference Properties Filter, Nillable, Update

Field	Details
	Description The ID of the email template used when new passwords are generated for Self-Service users.
SelfServiceNewUserTemplateId	Type reference Properties Filter, Nillable, Update Description The ID of the email template used when new Self-Service users are enabled.
SelfServicePageHeight	Type int Properties Filter, Nillable, Update Description The maximum height in pixels of Self-Service pages.
SelfServicePageWidth	Type int Properties Filter, Nillable, Update Description The maximum width in pixels of Self-Service pages.
SelfServiceSelfClosedCaseStatus	Type picklist Properties Filter, Nillable, Update Description The default status for cases closed by Self-Service users.
SelfServiceSolutionCategoryAvailable	Type boolean Properties Defaulted on create, Filter, Update Description Indicates whether solution categories are available in the Self-Service portal (<code>true</code>) or not (<code>false</code>).

Field	Details
SelfServiceSolutionCategoryStartNodeId	Type reference Properties Filter, Nillable, Update Description The ID of the top-level category in the Self-Service portal.
SelfServiceSolutionPlural	Type string Properties Filter, Nillable, Update Description The plural version of the term used to represent the Solution object in the Self-Service portal.
SelfServiceSolutionSingle	Type string Properties Filter, Nillable, Update Description The singular version of the term used to represent the Solution object in the Self-Service portal.
SelfServiceStyleSheetUrl	Type url Properties Filter, Nillable, Update Description The public URL of your organization's Self-Service portal stylesheet.
SelfServiceWelcomePageConfig	Type int Properties Filter, Nillable, Update Description Integer that represents the welcome page configuration for the Self-Service portal.
SelfServiceWelcomeText	Type string Properties Filter, Nillable, Update

Field	Details
	Description The custom welcome message displayed at the top of the Self-Service home page when Self-Service users log in. Limit: 32,000 characters.
State	Type string Properties Filter, Group, Nillable, Sort, Update Description State of the address of the organization. Limit: 80 characters.
StateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the organization's address.
Street	Type textarea Properties Filter, Group, Nillable, Sort, Update Description Street address for the organization. Limit: 255 characters.
TrialExpirationDate	Type dateTime Properties Filter, Nillable, Sort Description The date that this organization's trial license expires.
UiSkin	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort, Update Description The user interface theme selected for the organization.
UsesStartDateAsFiscalYearName	Type boolean

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the calendar year when the fiscal year begins is referred to as the year of the company's fiscal year (<code>true</code>) or not (<code>false</code>). For example, if the fiscal year begins in February 2006, a <code>true</code> value means the fiscal year is FY2006, and a <code>false</code> value means the fiscal year is FY2007.
UsesWebToCase	Type boolean Properties Filter, Nillable, Update Description Indicates whether this organization can use Web-to-Case (<code>true</code>) or not (<code>false</code>).
UsesWebToLead	Type boolean Properties Filter, Nillable, Update Description Indicates whether this organization can use Web-to-Lead (<code>true</code>) or not (<code>false</code>).
WebToCaseAssignedEmailTemplateId	Type reference Properties Filter, Nillable, Update Description The ID of the email template used when a new case is assigned to a user via Web-to-Case.
WebToCaseCreatedEmailTemplateId	Type reference Properties Filter, Nillable, Update Description The ID of the email template used when a new case is created via Web-to-Case.

Field	Details
WebToCaseDefaultCreatorId	Type reference Properties Filter, Nillable, Update Description The ID of the user specified as the default creator of cases created via Web-to-Case.
WebToCaseDefaultOrigin	Type string Properties Filter, Group, Nillable, Sort, Update Description The default value for the Case Origin field on cases submitted via Web-to-Case. Limit: 40 characters.

Usage

Query this object to obtain information about an organization's settings. Only one organization object exists per organization.

OrgWideEmailAddress

Represents an organization-wide email address for user profiles.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
Address	Type email Properties Create, Filter, Sort, Update Description The organization-wide email address.

Field	Details
IsAllowAllProfiles	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, any user profile in your organization can use this object. If <code>false</code>, only specified user profiles can use this object when sending email. If you do not have the appropriate user profile, you can't use this object.
DisplayName	Type string Properties Create, Filter, Sort, Update Description The name that is used to identify the sender of the email.

Usage

This object represents an email alias for user profiles. You can pass in the ID to an `OrgWideEmailAddress` record when calling `sendEmail()` for a `SingleEmailMessage`.

OwnedContentDocument

Represents a file owned by a user. This object is available in versions 30.0 and later.

Supported Calls

`describeSObjects()`

Fields

Field Name	Details
ContentDocumentId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the document.

Field Name	Details
ContentSize	Type int Properties Filter, Group, Nillable, Sort Description Size of the document in bytes.
ContentUrl	Type url Properties Filter, Group, Nillable, Sort Description URL for links and Google Docs. This field is set only for links and Google Docs, and is one of the fields that determine the <code>FileType</code>. This field is available in API version 31.0 and later.
ExternalDataSourceName	Type string Properties Filter, Group, Nillable, Sort Description Name of the external data source in which the document is stored. This field is set only for external documents that are connected to Salesforce. This field is available in API version 32.0 and later.
FileExtension	Type string Properties Filter, Group, Nillable, Sort Description File extension of the document. This field is available in API version 31.0 and later.
FileType	Type string Properties Filter, Group, Nillable, Sort Description Type of document, determined by the file extension.

Field Name	Details
OwnerId	Type reference Properties Filter, Group, Sort Description ID of the owner of the document.
Title	Type string Properties Filter, Group, idLookup, Sort Description Title of the document.

PackageLicense

Represents a license for an installed managed package. This object is available in API version 31.0 and later.

Supported Calls

`query()`, `retrieve()`

Fields

Field Name	Details
AllowedLicenses	Type int Properties Filter, Group, Nillable, Sort Description The number of users allowed to use the package.
ExpirationDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time when the package license expires.

Field Name	Details
NamespacePrefix	Type string Properties Filter, Group, Sort Description The namespace prefix associated with the package.
Status	Type picklist Properties Filter, Group, Sort Description The status of the license. Possible values are: Active, Expired, Free, and Trial.
UsedLicenses	Type int Properties Create, Filter, Nillable, Sort Description The number of users who have a license to the package.

Usage

Use this object to determine the number of licenses allowed and in use for a managed package installed in your organization.

The following example demonstrates the use of the API to manage licenses for a package. The example defines an Apex class that does the following.

- Retrieves the PackageLicense record for the specified package (identified by its namespace prefix).
- Defines a function that returns a list of all users with the specified profile.
- Creates a UserPackageLicense record for each user with that profile, which has the effect of assigning a license for the package to all users with that profile.
- Returns an error message if the number of users exceeds the number of available licenses.

```
public class AssignPackageLicense {

    static String PACKAGE_NAMESPACE_PREFIX = 'acme_101';
    static String PROFILE_ID = '00exx000000jz1SAAQ';
    public static String exceptionText {get; set;}

    public AssignPackageLicense() {
        exceptionText = 'Initialized';
    }

    static List<User> getUsersWithProfile(){
```

```

String userQuery = 'SELECT Id FROM User WHERE ProfileId = :PROFILE_ID';
List<User> matchingUsers = new List<User>();
matchingUsers = [SELECT Id FROM User WHERE ProfileId = :PROFILE_ID];
return matchingUsers;
}

public static void assignLicenseByProfile() {
    //find the PackageLicense Id
    PackageLicense pl = [SELECT Id, NamespacePrefix, AllowedLicenses, UsedLicenses,
        ExpirationDate, Status FROM PackageLicense WHERE
        NamespacePrefix = :PACKAGE_NAMESPACE_PREFIX];
    System.assert(pl != null, 'PackageLicense cannot be null.');
```

List<User> usersToAssignLicenses = getUsersWithProfile();

List<UserPackageLicense> firstUPLs = new List<UserPackageLicense>();

//create a new UserPackageLicense record for each user with the specified profile

```

for (Integer i = 0; i < usersToAssignLicenses.size(); i++){
    UserPackageLicense upl = new UserPackageLicense();
    upl.PackageLicenseId = pl.Id;
    upl.UserId = usersToAssignLicenses[i].Id;
    firstUPLs.add(upl);
}

try {
    //bulk insert
    insert(firstUPLs);
} catch (DmlException e) {
    for (Integer i = 0; i < e.getNumDml(); i++) {
        // process exception here
        System.debug(e.getDmlMessage(i));
        String status = e.getDmlStatusCode(i);
        System.debug(status + ' ' + e.getDmlMessage(i));
        if(status.equals('LICENSE_LIMIT_EXCEEDED')){
            exceptionText = 'You tried to assign more licenses than available. '
                + ' You tried to create ' + firstUPLs.size() + ' licenses but only have '
                + (pl.AllowedLicenses - pl.UsedLicenses) + ' licenses free.';
            System.debug(exceptionText);
        }
    }
}
}
}
}

```

Partner

Represents a partner relationship between two Account records or between an Opportunity and an Account.

Supported Calls

create(), delete(), describeObjects(), getDeleted(), getUpdated(), query(), retrieve()

Special Access Rules

- You must have the “View All Data” permission to access this object via the API. All of the Partner fields are accessible in the `describeObjects()` and `query()` calls. You cannot `update()` or `upsert()` partners via the API.
- Customer Portal users can't access this object.

Fields

Field	Details
<code>AccountFromId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required if <code>OpportunityId</code> is null. ID of the main Account in a partner relationship between two accounts. Specifying this field when creating a Partner record creates two AccountPartner objects, one for each direction of the relationship. If you specify the <code>OpportunityId</code> field, you can't specify this field as well.
<code>AccountToId</code>	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Partner Account related to either an opportunity or an account. You must specify this field when creating an opportunity Partner or an Account Partner.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
<code>IsPrimary</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Valid for Opportunity Partners only. Indicates that the account is the primary partner for the opportunity. Only one account can be marked as primary for an opportunity. If you set this field to 1 (<code>true</code>) upon insert of a

Field	Details
	new opportunity partner, any other primary partners for that opportunity will automatically have this field set to 0 (<code>false</code>). Label is Primary.
OpportunityId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required if <code>AccountFromId</code> is null. ID of the Opportunity in a partner relationship between an Account and an Opportunity. Specifying this field when creating a record creates an OpportunityPartner. If you specify the <code>AccountFromId</code> field, you can't specify this field as well.
Role	Type picklist Properties Create, Filter, Group, Nillable, Sort, Description UserRole that the account has towards the related opportunity or account, such as consultant or distributor.

Roles

In the Salesforce user interface, system administrators can set up the valid role values and their corresponding reverse role values in the PartnerRole object. Each account in the relationship is assigned a `Role` (such as `Consultant` or `Distributor`) designating that account's role towards the related account or opportunity.

Creating an Account-Opportunity Partner Relationship

When you create a partner relationship between an account and an opportunity (when you create a Partner object and specify the `OpportunityId` field), the API automatically creates an OpportunityPartner with the corresponding values:

- The value of the Partner field `AccountToId` maps to the value of the OpportunityPartner field `AccountToId`.
- The values of the `OpportunityId`, `Role`, and `IsPrimary` fields in both objects are the same.
- If you set the `IsPrimary` value to 1 (`true`) upon insert of a new OpportunityPartner, any other existing primary partners for that opportunity will automatically have the `IsPrimary` value set to 0 (`false`).

This mapping allows the API to manage the objects and their relationship efficiently.

Creating an Account-Account Partner Relationship

When you create a partner relationship between two accounts (when you create a Partner object and specify the `AccountFromId`), the API automatically creates two AccountPartner objects, one for the forward relationship and one for the reverse. For example, if you

create a Partner object with "Acme, Inc." as the `AccountFromId` and "Acme Consulting" as the `AccountToId`, the API automatically creates two AccountPartner objects:

- The forward relationship AccountPartner with "Acme, Inc." as the `AccountFromId` and "Acme Consulting" as the `AccountToId`.
- The reverse relationship AccountPartner with "Acme Consulting" as the `AccountFromId` and "Acme, Inc." as the `AccountToId`.
- The value of the `Role` field in the reverse relationship AccountPartner is set to the PartnerRole object `ReverseRole` value associated with the value of the `Role` field in the forward relationship AccountPartner.

This mapping allows the API to manage the objects and their relationship efficiently.

PartnerNetworkConnection

Represents a Salesforce to Salesforce connection between Salesforce organizations.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the Account associated with this connection.
ConnectionName	Type string Properties Filter, idLookup, Sort Description A descriptive name for the connection. Limit: 295 characters.
ConnectionStatus	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The status of the Salesforce to Salesforce connection. The picklist includes the following values: • Sent • Received

Field	Details
	• Pending • Accepted • Rejected • Inactive • Disconnecting • UsersInitialSync • BulkSyncMetadata
ConnectionType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The type of Salesforce to Salesforce connection. The picklist includes the following values: • Standard • Replication This field is available in API version 30.0 and later.
ContactId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the Contact associated with this connection.
IsSyncAuditFields	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Specifies whether audit fields are synced between the primary and secondary organization in a replication connection. This field is available in API version 32.0 and later, and is only accessible in Salesforce organizations where Organization Sync is enabled.
IsSyncMetadata	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description Specifies whether user metadata is synced between the primary and secondary organization in a replication connection. This field is available in API version 33.0 and later, and is only accessible in Salesforce organizations where Organization Sync is enabled.
PrimaryContactId	Type reference Properties Filter, Group, Sort Description ID of the User associated with this connection.
ReplicationRole	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The role of this Salesforce organization in the replication connection. The picklist includes the following values: • Primary • Secondary This field is available in API version 30.0 and later, and is only accessible in Salesforce organizations where Organization Sync is enabled.
ResponseDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time that the connection was accepted or rejected.

Usage

Represents Salesforce to Salesforce standard and replication connections. This object is referenced by all objects that have been shared with other organizations, enabling you to determine which connections shared a record with you. If the organization does not have Salesforce to Salesforce enabled, the PartnerNetworkConnection object is not available, and you can't access it via the API.

PartnerNetworkRecordConnection

Represents a record shared between Salesforce organizations using Salesforce to Salesforce.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`

Fields

Field	Details
ConnectionId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Required. ID of the connection a record is shared with.
EndDate	Type dateTime Properties Filter, Nillable, Sort Description Date that sharing of the record was stopped.
LocalRecordId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the shared record.
ParentRecordId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the parent record of the shared record.
PartnerRecordId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the shared record in the connection's organization.

Field	Details
RelatedRecords	Type string Properties Create, Filter, Nillable, Sort Description A comma-separated list of API names for child records to be shared with a parent record.
SendClosedTasks	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Forwards closed tasks related to the shared record.
SendEmails	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Sends an email notifying the connection's representative that you have forwarded the record to them. Only new recipients of a record will receive a notification email.
SendOpenTasks	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Forwards open tasks related to the shared record.
StartDate	Type dateTime Properties Filter, Nillable, Sort Description Date that the shared record was accepted.
Status	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort

Field	Details
	Description The status of the shared record. One of the following values: • Active (received) • Active (sent) • Connected • Inactive • Inactive (converted) • Inactive (deleted) • Pending (sent)

Usage

When you create a `PartnerNetworkRecordConnection`, you forward a record to a connection.

 **Note:** Attempting to forward a record from an object to which the connection is not subscribed results in an `Invalid Partner Network Status` error.

Don't forward a record to the connection that originally shared it. Doing so causes errors when Apex triggers run.

When you delete a `PartnerNetworkRecordConnection`, you stop sharing a record with a connection.

- To share a record, use the following fields: `LocalRecordID` and `ConnectionId`
- To share a child of a parent record, use the following fields: `LocalRecordID`, `ConnectionId`, and `ParentRecordID`
- To share a child of a parent record and its child records, use the following fields: `LocalRecordID`, `ConnectionId`, `ParentRecordID`, and `RelatedRecords`

If the organization does not have Salesforce to Salesforce enabled, the `PartnerNetworkRecordConnection` object is not available, and you can't access it using the API.

Sample Code—Apex

The following example shows how to forward a record.

```
List<PartnerNetworkConnection> connMap = new List<PartnerNetworkConnection>(
    [select Id, ConnectionStatus, ConnectionName from PartnerNetworkConnection
     where ConnectionStatus = 'Accepted']
);
for(PartnerNetworkConnection network : connMap) {
    PartnerNetworkRecordConnection newrecord = new PartnerNetworkRecordConnection();

    newrecord.ConnectionId = network.Id;
    newrecord.LocalRecordId = accountId;
    newrecord.RelatedRecords = 'Contact,Opportunity,Orders__c';
    newrecord.SendClosedTasks = true;
    newrecord.SendOpenTasks = true;
    newrecord.SendEmails = true;
```

```
        insert newrecord;
    }
```

The following example shows how to stop sharing a record.

```
List<PartnerNetworkRecordConnection> recordConns = new List<PartnerNetworkRecordConnection>(
    [select Id, Status, ConnectionId, LocalRecordId from PartnerNetworkRecordConnection
     where LocalRecordId in :accounts]
);

for(PartnerNetworkRecordConnection recordConn : recordConns) {
    if(recordConn.Status.equalsignorecase('Sent')){ //account is connected - outbound

        delete nets;
    }
}
```

PartnerNetworkSyncLog

PartnerNetworkSyncLog corresponds to the Org Sync Log tab in Salesforce, where Salesforce administrators can track the replication of record inserts and updates being performed in Organization Sync. The Connection Detail page for the replication connection also displays the Org Sync Log’s twenty most recent entries, and provides a link to the log.

Supported Calls

describeSObjects(),getDeleted(),getUpdated(),query(),retrieve(),search()

Special Access Rules

The Org Sync Log tab can only be added in organizations where Organization Sync has been enabled. To add the tab in Salesforce, users must also have the “Manage Connections” user permission.

Fields

Field Name	Details
ConnectionEvent	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The action being replicated to the partner organization, such as a record insertion.
ConnectionId	Type reference

Field Name	Details
	Properties Filter, Group, Sort Description The ID of the Salesforce-to-Salesforce replication connection in which the replication event succeeded or failed.
Description	Type textarea Properties Nillable Description A description of the replication event.
EntityType	Type string Properties Filter, Group, Nillable, Sort Description The type of record being inserted or updated.
Error	Type string Properties Filter, Group, Nillable, Sort Description The code used to describe the replication failure or success.
LocalRecord	Type string Properties Filter, Group, Sort Description The record being inserted or updated.

PartnerRole

Represents a role for an account Partner, such as consultant, supplier, and so on.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
MasterLabel	Type string Properties Filter, Group, Nillable, Sort Description Master label for this partner role value. This display value is the internal label that does not get translated. Limit: 255 characters.
ReverseRole	Type picklist Properties Filter, Group, Nillable, Sort Description Name of the reverse role that corresponds to this partner role. For example, if the role is "subcontractor," then the reverse role might be "general contractor." In the user interface, assigning a partner role to an account creates a reverse partner relationship so that both accounts list the other as a partner.
SortOrder	Type int Properties Filter, Group, Nillable, Sort Description Number used to sort this value in the partner role picklist. These numbers are not guaranteed to be sequential, as some previous partner role values might have been deleted.

Usage

This object represents a value in the partner role picklist. In the user interface, the partner role picklist provides additional information about the role of a Partner, such as their corresponding reverse role. Query this object to retrieve the set of values in the partner role picklist, and then use that information while processing PartnerRole records to determine more information about a given partner role. For example, the application could determine the reverse role of a given Partner Role value and the value of the ReverseRole property in the associated PartnerRole object.

Period

Represents a fiscal period defined in FiscalYearSettings.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
EndDate	Type date Properties Filter, Group, Sort Description The last date of the fiscal period.
FiscalYearSettingsId	Type reference Properties Filter, Nillable, Group, Sort Description The parent record for this period.
IsForecastPeriod	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the period is associated with customizable forecasts (<code>true</code>) or not (<code>false</code>).
Number	Type int Properties Filter, Nillable, Group, Sort

Field	Details
	Description If the labeling scheme of your fiscal year's quarters or months is numbered, this field indicates the relative number of the row.
PeriodLabel	Type picklist Properties Filter, Group, Nillable, Sort Description If the months in your fiscal year use custom names, then this field contains the appropriate name for rows of type Month.
QuarterLabel	Type picklist Properties Filter, Group, Nillable, Sort Description If the quarters in your fiscal year use custom names, then this field contains the appropriate name for rows of type Quarter.
StartDate	Type date Properties Filter, Group, Sort Description The first date of the fiscal period.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Indicates whether the period is of type Month, Quarter, Week, or Year. Label is the field value.

PermissionSet

Represents a set of permissions that's used to grant additional access to one or more users without changing their profile or reassigning profiles. You can use permission sets to grant access, but not to deny access. This object is available in API version 22.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Fields

Field Name	Details
Description	Type string Properties Create, Filter, Nillable, Group, Sort, Update Description A description of the permission set. Limit: 255 characters.
IsOwnedByProfile	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If <code>true</code>, the permission set is owned by a profile. Available in API version 25.0 and later.
Label	Type string Properties Create, Filter, Group, Sort, Update Description The permission set label, which corresponds to Label in the user interface. Limit: 80 characters.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. Corresponds to API Name in the user interface. Limit: 80 characters.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description The namespace prefix for a permission set that's been installed as part of a managed package. If the permission set isn't packaged or is part of an unmanaged package, this value is empty. Available in API version 23.0 and later.
PermissionsPermissionName	Type boolean Properties Create, Filter, Update Description One field for each permission. If <code>true</code>, users assigned to this permission set have the named permission. The number of fields varies depending on the permissions for the organization and license type.  Tip: To get a list of available permissions in the SOAP API, use <code>describeSObjects()</code>.
ProfileId	Type reference Properties Filter, Group, Nillable, Sort Description If the permission set is owned by a profile, this field returns the ID of the Profile. If the permission set isn't owned by a profile, this field returns a null value. Available in API version 25.0 and later.
UserLicenseId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the UserLicense associated with this permission set. This field is nillable in API version 26.0 and later.

Usage

Use the PermissionSet object to query existing permission sets.

For example, to search for all permission sets that contain the “Modify All Data” permission:

```
SELECT Name, PermissionsModifyAllData
FROM PermissionSet
WHERE PermissionsModifyAllData=true
```

When combined with the PermissionSetAssignment object, you can create a nested query that returns all users assigned to a particular permission like “Modify All Data”:

```
SELECT Name, (SELECT AssigneeId FROM Assignments)
FROM PermissionSet
WHERE PermissionsModifyAllData=true
```

You can also create a permission set, or delete a permission set if it isn't assigned to a user.

User Licenses

The user license controls the permissions that are available in a permission set.

Every permission set may be associated with a user license. If you plan to assign a permission set to multiple users with different licenses, leave `UserLicenseId` empty. If only users with one type of license will use this permission set, set the `UserLicenseId` to that single user license. To get the `UserLicenseId`, run this query:

```
SELECT Id, Name
FROM UserLicense
```

Alternatively, to query a user or profile for the `UserLicenseId`.

```
SELECT Id, Profile.UserLicenseId
FROM User
```


Child Objects

When using the API, think of each permission set or related set of access controls as starting as an empty container that you fill with permission records.

In the API, a permission set can contain user, object, and field permissions, as well as setup entity access settings for other settings, such as Apex classes.

- ObjectPermissions and FieldPermissions objects are available in API version 24.0 and later.
- The SetupEntityAccess object is available in API version 25.0 and later.

Only user permissions are managed in the PermissionSet API object; all other permission types are managed in child API objects.



In these child objects, access is stored in a record, while the absence of a record indicates no access. In order to return a record in a SOQL query, a minimum permission or setting is required for each child object.

Because permissions are stored in related objects, it's important to understand what questions to ask when using SOQL. For example, you may want to know which permission sets have "Delete" on an object or have the right to approve a return merchandise authorization (where the approval checkbox is controlled with field permissions). Asking the right questions when using SOQL with permission sets will ensure that you get the information you need to make an informed decision, such as whether to migrate permissions or assign a permission set to a user.

For example, the following returns all permission sets where the "Read" permission is enabled for the Merchandise__c object.

```
SELECT SubjectType, ParentId, PermissionsRead
FROM ObjectPermissions
WHERE PermissionsRead = True AND SubjectType = 'Merchandise__c'
```

You can query for all permission sets that have "Read" on an object. However, you can't query for permission sets that have no access on an object, because no records exist for that object. For example, the following returns no records because the object must have at least "Read" to return any records.

```
SELECT SubjectType, ParentId, PermissionsRead
FROM ObjectPermissions
WHERE PermissionsRead = False AND SubjectType = 'Merchandise__c'
```

If you have at least the “Read” permission on an object, you can create a conditional query on other permissions in the same object. For example, the following returns any records where the object has at least the “Read” permission but not the “Edit” permission.

```
SELECT ParentId, PermissionsRead, PermissionsEdit
FROM ObjectPermissions
WHERE PermissionsEdit = False AND SubjectType = 'Merchandise__c'
```

To set an object or field permission to no access, just delete the record that contains the permission. For example, to disable all object permissions in the Merchandise__c object for a particular permission set, first query to retrieve the ID of the object permission record.

```
SELECT Id
FROM ObjectPermissions
WHERE SubjectType = 'Merchandise__c'
```

Then delete the IDs returned from the query.



Note: If you try to update the object or field permissions by setting all permissions to false, the permission record is automatically deleted. As a result, any subsequent queries for the record ID won’t return any results and you must add a new permission record to grant access.

Viewing a Permission Set with Nested Queries

You can build on the PermissionSet object using child relationships that show all of the permissions in a single permission set. For example, the following returns all permission sets and displays the “Transfer Leads” permission as well as any “Read” permissions on any objects and fields.

```
SELECT Label, PermissionsTransferAnyLead,
(SELECT SubjectType, PermissionsRead FROM ObjectPerms),
(SELECT SubjectType, Field, PermissionsRead FROM FieldPerms)
FROM PermissionSet
```

Associated Profiles

In API version 25.0 and later, every profile is associated with a permission set that stores the profile’s user, object, and field permissions, as well as setup entity access settings. Permission sets that are owned by profiles can be queried but not modified.

The following example returns all permission sets, including those owned by a profile.

```
SELECT Id, Label, ProfileId, Profile.Name
FROM PermissionSet
```

The following returns all permission sets except those owned by profiles.

```
SELECT Id, Label, ProfileId, Profile.Name, IsOwnedByProfile
FROM PermissionSet
WHERE IsOwnedByProfile = FALSE
```

Because permission sets have child objects in the API, you can query their values on permission sets owned by a profile. For example, the following returns all enabled object permission records for profiles only.

```
SELECT Id, ParentId, PermissionsRead, SubjectType, Parent.ProfileId
FROM ObjectPermissions
WHERE Parent.IsOwnedByProfile = TRUE
```

Once you have the IDs for permission sets that are owned by profiles as well as those not owned by profiles, you can use the [PermissionSetAssignment](#) object to determine whether users can access an object or field via a permission in their profile or any of their

permission sets. For example, the following SOQL query returns all users who have the “Read” permission on the Merchandise__c object and specifies whether the permission is granted through a profile or permission set.

```
SELECT Assignee.Name, PermissionSet.Id, PermissionSet.isOwnedByProfile
FROM PermissionSetAssignment
WHERE PermissionSetId
IN (SELECT ParentId
FROM ObjectPermissions
WHERE SObjectType = 'Merchandise__c' AND PermissionsRead = true)
```

 **Note:** For permission sets that are owned by profiles, don’t use any Name and Label values that are returned in a query, as they can change at any time.

PermissionSetAssignment

Represents the association between a User and a PermissionSet. This object is available in API version 22.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
AssigneeId	Type reference Properties Create, Filter, Group, Sort Description ID of the User to assign the permission set specified in <code>PermissionSetId</code>.
PermissionSetId	Type reference Properties Create, Filter, Group, Sort Description ID of the PermissionSet to assign to the user specified in <code>AssigneeId</code>.

Usage

Finding Permission Set Assignments

Use the PermissionSetAssignment object to query permission set assignments to find out which permission sets are assigned to which users. Because each user may be assigned to many permission sets and each permission set may be assigned to many users, each PermissionSetAssignment ID represents the association of a single user and single permission set.

For example, to search for all of the permission sets assigned to a particular user:

```
SELECT Id, PermissionSetId
FROM PermissionSetAssignment
WHERE AssigneeId = '005600000017cKt'
```

To search for all users assigned to a particular permission set:

```
SELECT Id, AssigneeId
FROM PermissionSetAssignment
WHERE PermissionSetId = '0PS30000000000e'
```

You can also create a new permission set assignment, or use delete to remove a permission set that's assigned to a user. To update an assignment, delete an existing assignment and insert a new one.

User Licenses

When assigning a permission set, if the `PermissionSet` has a `UserLicenseId`, its `UserLicenseId` and the `Profile UserLicenseId` must match. To determine a user's license assignment, query the user's profile and then query the profile's license.

For example, to find a user's profile ID:

```
SELECT Id, ProfileId
FROM User
WHERE Id = '005D00000001GMAT'
```

To find a permission set's `UserLicenseId`:

```
SELECT Id, UserLicenseId
FROM PermissionSet
WHERE Id = '0PS30000000000e'
```

If the IDs match, the assignment succeeds.

To find all the permission sets with no license that are assigned to any user:

```
SELECT Id, Assignee.Name, PermissionSet.Name
FROM PermissionSetAssignment
WHERE PermissionSet.UserLicenseId = null
```

PermissionSetLicense

Represents a license that's used to enable one or more users to receive a specified permission without changing their profile or reassigning profiles. You can use permission set licenses to grant access, but not to deny access. This object is available in API version 29.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
DeveloperName	Type string Properties Filter, Group, Sort Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
ExpirationDate	Type date Properties Filter, Group, Nillable, Sort Description The date at which the permission set license expires.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language of the permission set license.
MasterLabel	Type string Properties Filter, Group, Sort Description The label of the permission set license. Label is Permission Set License Label.
MaximumPermissionsPermissionName	Type boolean Properties Filter,

Field Name	Details
	Description One field for each permission. For example, <code>MaximumPermissionsIdentityConnect</code> corresponds to the “Use Identity Connect” permission. If <code>true</code>, this <code>PermissionSetLicense</code> grants the specified permission. The number of fields varies depending on the permissions available for the organization.
<code>PermissionSetLicenseKey</code>	Type string Properties Filter, Group, idLookup, Sort Description A string that uniquely identifies a particular permission set license.
<code>Status</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The status of a permission set license. If <code>Active</code>, the permission set license is available. If <code>Disabled</code>, the permission set license has expired.
<code>TotalLicenses</code>	Type int Properties Filter, Group, Sort Description The total number of this permission set license that are available to your organization.
<code>UsedLicenses</code>	Type int Properties Filter, Group, Sort Description The number of this permission set license that are currently assigned to users.

Usage

Users with the “View Setup and Configuration” permission can use the `PermissionSetLicense` object to view the set of currently defined permission set licenses in your organization.

Use the PermissionSetLicense object to query existing permission licenses.
For example, to return a list of all active permission set licenses:

```
SELECT MasterLabel
FROM PermissionSetLicense
WHERE Status = 'Active'
```

When combined with the PermissionSetLicenseAssign object, you can create a nested query that returns all users assigned to a particular permission set license like “Identity Connect”:

```
SELECT MasterLabel, (SELECT AssigneeId FROM PermissionSetLicenseAssignments)
FROM PermissionSetLicense
WHERE MaximumPermissionsIdentityConnect=true
```

PermissionSetLicenseAssign

Represents the association between a User and a PermissionSetLicense. This object is available in API version 29.0 and later.

 **Note:** The relationship name for PermissionSetLicenseAssign is *PermissionSetLicenseAssignments*.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
AssigneeId	Type reference Properties Create, Filter, Group, Sort Description ID of the User to assign the permission set license specified in <code>PermissionSetLicenseId</code>.
PermissionSetLicenseId	Type reference Properties Create, Filter, Group, Sort Description The ID of the permission set license the user is assigned to.

Usage

Use the PermissionSetLicenseAssign object for querying permission set license assignments to find out which permission set licenses are assigned to which users. Because each user can be assigned to many permission set licenses, each PermissionSetLicenseAssign ID represents the association of a single user and single permission set license.

For example, to search for all of the permission sets assigned to a particular user:

```
SELECT Id, PermissionSetLicenseId
FROM PermissionSetLicenseAssign
WHERE AssigneeId = '005D0000001RFek'
```

To search for all users assigned to a particular permission set license:

```
SELECT AssigneeId
FROM PermissionSetLicenseAssign
WHERE PermissionSetLicenseId = '0PLD000000003mwOAA'
```

You can also create a new permission set license assignment, or use delete to remove a permission set license that’s been assigned to a user. To update an assignment, delete an existing assignment and insert a new one.

PlatformAction

PlatformAction is a virtual read-only object that enables you to query for actions—such as standard and custom buttons, quick actions, and productivity actions—that should be displayed in a UI, given a user, a context, device format, and a record ID.

Supported Calls

query()

Fields

Field	Details
ActionListContext	Type string Properties Filter, Group, Nillable, Restricted picklist, Sort Description Required. The list context this action applies to. Valid values are: - Chatter - FeedElement - FlexiPage - Global - ListView - ListViewRecord - MruList

Field	Details
	• MruRow • Record • RelatedList • RelatedListRecord
ActionTargetType	Type string Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of the target when this action is triggered. Valid values are: • Describe—applies to actions with a user interface, such as quick actions • Invoke—applies to actions with no user interface, such as action links or dynamic actions
ActionTargetUrl	Type string Properties Filter, Group, Nillable, Sort Description URL to invoke or describe the action when the user invokes the action.
Category	Type string Properties Filter, Group, Nillable, Restricted picklist, Sort Description Applies only to action links. Denotes whether the action link shows up in the feed item list of actions or the overflow list of actions. Valid values are: • Primary • Overflow
ConfirmationMessage	Type string Properties Filter, Group, Nillable, Sort Description Applies only to action links. The message to display before the action is invoked. Field is null if no confirmation is required prior to invoking the action.

Field	Details
DeviceFormat	Type string Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specify what action icon is returned by the PlatformAction query. If this field isn't specified, it defaults to Phone. Valid values are: • Aloha • Desktop • Phone • Tablet
ExternalId	Type string Properties Filter, Group, Nillable, Sort Description The unique ID for the PlatformAction. If the action doesn't have an ID, its API name is used.
GroupId	Type ID Properties Filter, Group, Nillable, Sort Description The unique ID of a group of action links.
IconContentType	Type string Properties Filter, Group, Nillable, Sort Description The content type—such as .jpg, .gif, or .png—of the icon for this action. Applies to both custom and standard icons assigned to actions.
IconHeight	Type int Properties Filter, Group, Nillable, Sort Description The height of the icon for this action. Applies only to standard icons.

Field	Details
IconUrl	Type string Properties Filter, Group, Nillable, Sort Description The URL of the icon for this action.
IconWidth	Type int Properties Filter, Group, Nillable, Sort Description The width of the icon for this action. Applies only to standard icons.
InvocationStatus	Type string Properties Filter, Group, Nillable, Restricted picklist, Sort Description The status of the action within the feed item. Applies to action links only. Valid values are: - Failed - New - Pending - Successful
InvokedByUserId	Type ID Properties Filter, Group, Nillable, Sort Description The ID of the user who most recently invoked this action within the current feed item. Applies to action links only.
IsGroupDefault	Type boolean Properties Filter, Group, Sort Description Denotes whether this is the default action in an action link group. False for other action types. Applies to action links only.

Field	Details
Label	Type string Properties Filter, Group, Sort Description The label to display for this action.
PrimaryColor	Type string Properties Filter, Group, Nillable, Sort Description The primary color of the icon for this action.
RelatedSourceEntity	Type string Properties Filter, Group, Nillable, Sort Description When the <code>ActionListContext</code> is <code>RelatedList</code> or <code>RelatedListRecord</code>, this field represents the API name of the related list to which the action belongs.
SourceEntity	Type string Properties Filter, Group, Sort Description Required. The object or record with which this action is associated.
Subtype	Type string Properties Filter, Group, Nillable, Sort Description The subtype of the action. For quick actions, the subtype is <code>QuickActionType</code>. For custom buttons, the subtype is <code>WebLinkTypeEnum</code>. For action links, subtypes are <code>Api</code>, <code>ApiAsync</code>, <code>Download</code>, and <code>Ui</code>. Standard buttons and productivity actions have no subtype.
Type	Type string

Field	Details
	Properties Filter, Group, Restricted picklist, Sort
	Description The type of the action. Valid values are: • ActionLink • CustomButton • ProductivityAction • QuickAction • StandardButton

Usage

PlatformAction can be described using describeSObject().

You can directly query for PlatformAction. For example, this query returns all fields for actions associated with each of the records of the listed objects:

```
SELECT ExternalId, ActionTargetType, ActionTargetUrl, ApiName,Category, ConfirmationMessage,
       ExternalId, GroupId, UiTheme, IconUrl, IconContentType, IconHeight, IconWidth,
       PrimaryColor,
       InvocationStatus, InvokedByUserId, IsGroupDefault, Label, LastModifiedDate, Subtype,
       SourceEntity, Type FROM PlatformAction WHERE SourceEntity IN ('001xx000003DGsH',
       '001xx000003DHBq', 'Task', 'Global') and ActionListContext = 'Record';
```

 **Note:** To query PlatformAction, you must provide the ActionListContext and SourceEntity.

PresenceUserConfig

Represents a configuration that determines a presence user's settings. This object is available in API version 32.0 and later.

Supported Calls

create(), delete(), query(), retrieve(), update()

Fields

Field	Details
Capacity	Type int

Field	Details
	Properties Create, Filter, Group, Sort, Update Description The maximum number of work assignments that can be pushed to an agent at a time.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the presence configuration.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The label of the presence configuration.
OptionsIsAutoAcceptEnabled	Type boolean Properties Create, Filter, Update Description Indicates whether work items that are routed to agents are automatically accepted (<code>true</code>) or not (<code>false</code>). Available only if <code>OptionsIsDeclineEnabled</code> is set to <code>false</code>.

Field	Details
OptionsIsDeclineEnabled	Type boolean Properties Create, Filter, Update Description Indicates whether agents can decline work items that are routed to them (<code>true</code>) or not (<code>false</code>). Available only if <code>OptionsIsAutoAcceptEnabled</code> is set to <code>false</code> .
PresenceStatusOnDeclineId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the presence status that's automatically assigned to the agent when the agent declines a work item. Available only if <code>OptionsIsDeclineEnabled</code> is set to <code>true</code> .

PresenceUserConfigProfile

Represents a configuration that determines the settings that are assigned to presence users who are assigned to a specific profile. User-level configurations override profile-level configurations. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
PresenceUserConfigId	Type reference Properties Create, Filter, Group, Sort Description If an individual user is also assigned a presence configuration through the <code>PresenceUserConfigProfile</code> , this configuration will override that.
ProfileId	Type reference Properties Create, Filter, Group, Sort

Field	Details
	Description The ID of the profile that's associated with this presence configuration. A profile can be associated with only one presence configuration.

PresenceUserConfigUser

Represents a configuration that determines the settings that are assigned to a presence user. These user-level configurations override profile-level configurations. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
PresenceUserConfigId	Type reference Properties Create, Filter, Group, Sort Description The ID of the presence configuration.
UserId	Type reference Properties Create, Filter, Group, Sort Description The ID of the user who's associated with this presence configuration. A user can be associated with only one presence configuration.

Pricebook2

Represents a price book that contains the list of products that your organization sells.



Note: In this release, price books are represented by Pricebook2 objects. The Pricebook object is no longer available for use.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Text description of this object.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this object is active (<code>true</code>) or not (<code>false</code>). Inactive objects are hidden in many areas in the user interface. You can change this field's value as often as necessary. Label is Active.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
IsStandard	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this object is the standard price book for the organization (<code>true</code>) or not (<code>false</code>). Every organization has one standard price book—all other price books are custom price books.
Name	Type string

Field	Details
	Properties Create, Filter, Group, Sort, Update
	Description Required. Name of this object. This field is read-only for the standard price book. Label is Price Book Name .

Usage

A price book is a list of products that your organization sells:

- Each organization has one standard price book that defines the standard or generic list price for each product or service that it sells.
- An organization can have multiple custom price books that can be used for specialized purposes, such as a discount price book, price books for different channels or markets, price books for select accounts or opportunities, and so on. While your client application can create, delete, and update custom price books, your client application can only update the standard price book.
- For some organizations, the standard price book might be the only price needed, but if you need to set up further price books, you can reference the standard price book when setting up list prices in custom price books.

Use this object to query standard and custom price books that have been configured for your organization. A common use of this object is to allow your client application to obtain valid Pricebook2 object IDs for use when configuring PricebookEntry records via the API.

Your client application can perform the following tasks on PricebookEntry objects:

- Query
- Create for the standard pricebook or custom pricebooks.
- Update
- Delete
- Change the `IsActive` field when creating or updating records

PriceBook2, Product2, and PricebookEntry Relationships

In the API:

- Price books are represented by Pricebook2 objects (the Pricebook object is no longer available).
- Products are represented by Product2 objects (the Product object is not available as of version 8.0.).
- Each price book contains zero or more entries (represented by PricebookEntry records) that specify the products that are associated with the price book. A price book entry defines the price for which you sell a product at a particular currency.

These objects are defined only for those organizations that have products enabled as a feature. If the organization does not have the products feature enabled, the Pricebook2 object does not appear in the `describeGlobal()` call, and you can't access it via the API.

If you delete a Pricebook2, while a line item references PricebookEntry in the price book, the line item is unaffected, but the Pricebook2 will be archived and unavailable from the API.

For a visual diagram of the relationships between Pricebook2 and other objects, see Product and Schedule Objects.

Price Book Setup

The process of setting up a price book via the API usually means:

1. Initially loading product data from your organization into Product2 objects (creating a Product2 record for each product that you want to add).
2. For each Product2 object, creating a PricebookEntry that links the Product2 object to the standard Pricebook2. You need to define a standard price for a product at a given currency (if you have multicurrency enabled), before defining a price for that product in the same currency in a custom price book.
3. Creating a custom Pricebook2.
4. Querying the Pricebook2 object to obtain their IDs.
5. For each Pricebook2 object, creating a PricebookEntry for every Product2 that you want to add, specifying unique properties for each PricebookEntry (such as the UnitPrice and CurrencyIsoCode) as needed.

Code Sample—Java

```
public void pricebookSample() {
    try {
        //Create a custom pricebook
        Pricebook2 pb = new Pricebook2();
        pb.setName("Custom Pricebok");
        pb.setIsActive(true);
        SaveResult[] saveResults = connection.create(new SObject[]{pb});
        pb.setId(saveResults[0].getId());

        // Create a new product
        Product2 product = new Product2();
        product.setIsActive(true);
        product.setName("Product");
        saveResults = connection.create(new SObject[]{product});
        product.setId(saveResults[0].getId());

        // Add product to standard pricebook
        QueryResult result = connection.query(
            "select Id from Pricebook2 where isStandard=true"
        );
        SObject[] records = result.getRecords();
        String stdPbId = records[0].getId();

        // Create a pricebook entry for standard pricebook
        PricebookEntry pbe = new PricebookEntry();
        pbe.setPricebook2Id(stdPbId);
        pbe.setProduct2Id(product.getId());
        pbe.setIsActive(true);
        pbe.setUnitPrice(100.0);
        saveResults = connection.create(new SObject[]{pbe});

        // Create a pricebook entry for custom pricebook
        pbe = new PricebookEntry();
        pbe.setPricebook2Id(pb.getId());
        pbe.setProduct2Id(product.getId());
```

```
pbe.setIsActive(true);
pbe.setUnitPrice(100.0);
saveResults = connection.create(new SObject[]{pbe});
} catch (ConnectionException ce) {
    ce.printStackTrace();
}
}
```

Pricebook2History

Represents historical information about changes that have been made to the standard fields of the associated Pricebook2, or to any custom fields with history tracking enabled. This object is available in API version 34.0 and later.

Supported Calls

describeSObjects(), getDeleted(), getUpdated(), query(), retrieve()

Special Access Rules

This object is always read-only.

Fields

Field	Details
Pricebook2Id	Type reference Properties Filter, Group, Sort Description ID of the Pricebook2 associated with this record.
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Name of the price book field that was modified, or a special value to indicate some other modification to the price book.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field. Label is Deleted .
NewValue	Type anyType Properties Nillable, Sort Description New value of the modified price book field. Maximum of 255 characters.
OldValue	Type anyType Properties Nillable, Sort Description Previous value of the modified price book field. Maximum of 255 characters.

Usage

Price book history entries are indirectly created each time a price book is modified.

Two rows are added to this record when foreign key fields change. One row contains the foreign key object names that display in the online application. For example, `Jane Doe` is recorded as the name of a Contact. The other row contains the actual foreign key ID that is only returned to and visible from the API.

This object respects field level security on the parent object.

PricebookEntry

Represents a product entry (an association between a Pricebook2 and Product2) in a price book.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
CurrencyIsoCode	Type picklist

Field	Details
	Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this price book entry is active (<code>true</code>) or not (<code>false</code>). Although you can never delete PricebookEntry records, your client application can set this flag to <code>false</code>. Inactive PricebookEntry records are hidden in many areas in the user interface. You can change this flag on a PricebookEntry record as often as necessary.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether this PricebookEntry record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
Name	Type string Properties Filter, Group, Nillable, Sort Description Name of this PricebookEntry record. This read-only field references the value in the Name field of the Product2 record. Label is Product Name.
Pricebook2Id	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Pricebook2 record with which this record is associated. This field must be specified when creating Pricebook2 records. It can't be changed in an update.
Product2Id	Type reference

Field	Details
	Properties Create, Filter, Group, Sort Description Required. ID of the Product2 record with which this record is associated. This field must be specified when creating Product2 records. It can't be changed in an update.
ProductCode	Type string Properties Filter, Group, Nillable, Sort Description Product code for this record. This read-only field references the value in the ProductCode field of the associated Product2 record.
UnitPrice	Type currency Properties Create, Filter, Sort, Update Description Required. Unit price for this price book entry. You can specify a value only if <code>UseStandardPrice</code> is set to <code>false</code>. Label is List Price.
UseStandardPrice	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this price book entry uses the standard price defined in the standard Pricebook2 record (<code>true</code>) or not (<code>false</code>). If set to <code>true</code>, then the <code>UnitPrice</code> field is read-only, and the value will be the same as the <code>UnitPrice</code> value in the corresponding PricebookEntry in the standard price book (that is, the PricebookEntry record whose <code>Pricebook2Id</code> refers to the standard price book and whose <code>Product2Id</code> and <code>CurrencyIsoCode</code> are the same as this record). For PricebookEntry records associated with the standard Pricebook2 record, this field must be set to <code>true</code>.

Usage

Use this object to define the association between your organization's products (Product2) and your organization's standard price book or to other, custom-defined price books (Pricebook2). Create one PricebookEntry record for each standard or custom price and currency combination for a product in a Pricebook2.

When creating these records, you must specify the IDs of the associated Pricebook2 record and Product2 record. Once created, your client application can't update these IDs.

This object is defined only for those organizations that have products enabled as a feature. If the organization does not have the products feature enabled, then the PricebookEntry object does not appear in the `describeGlobal()` call, and you can't access it.

If you delete a PricebookEntry while a line item references it, the line item is unaffected, but the PricebookEntry will be archived and unavailable from the API.

You must load the standard price for a product before you are permitted to load its custom price(s).

ProcessDefinition

Represents the definition of a single approval process.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `search()`

Special Access Rules

Portal and Communities users can't access this object.

Fields

Field	Details
Description	Type string Properties Filter, Nillable, Sort Description A description of this process, with a maximum of 3,000 characters.
DeveloperName	Type string Properties Filter, Group, Sort Description The external name of the process; the name seen by users.
LockType	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field	Details
	Description The type of lock applied to the record being approved. When a record is in the approval process, it's always locked, and only an administrator can edit it. However, the currently assigned approver can also be allowed to edit the record. • Total • Admin • Owner • Workitem • Node • none
Name	Type string Properties Filter, Group, Sort Description The unique process name, used internally.
State	Type picklist Properties Filter, Group, Sort Description The current state of this process. • Active • Inactive • Obsolete
TableEnumOrId	Type picklist Properties Filter, Group, Sort Description Specifies the object associated with the approval process, such as Account or Contact.
Type	Type picklist Properties Filter, Group, Sort Description The type of this process.

Field	Details
	- Approval Process—Used to control the action taken for a record. - State-based Process—Used internally to track various control processes, such as for developing Salesforce Knowledge articles.

Usage

Use this object to read the description of an approval process. The definition is read-only.

ProcessInstance

Represents an instance of a single, end-to-end approval process. Use this and the node, step, and workitem process instance objects to create approval history reports.



Note: Exceptions apply to approval history data retrieved with this object and available only via the SOAP API. For each approval process instance that was pending when Summer '14 became available for your organization, some field values are never populated or are populated only after the approval process instance is next acted upon—such as when a user approves, rejects, or reassigns an approval request—after the Summer '14 rollout.

For approval process instances that were completed before the Summer '14 rollout, all Process Instance fields are automatically populated, with one exception: `CompletedDate` is never populated for approval process instances that were completed before January 1, 2013. For approval process instances that were pending during the Summer '14 rollout, all ProcessInstance fields are automatically populated, with two exceptions: `CompletedDate` and `LastActorId` are populated only after the approval process instance is complete.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Portal and Communities users can't access this object.

Fields

Field	Details
CompletedDate	Type dateTime Properties Filter, Sort Description The completion date and time of the approval process. The <code>ElapsedTimeDay</code>, <code>ElapsedTimeHours</code>, and <code>ElapsedTimeMinutes</code> field values are calculated using <code>CompletedDate</code>.

Field	Details
ElapsedTimeInDays	Type double Properties Filter, Sort Description The total elapsed time in days between when the approval process instance was started and now.
ElapsedTimeInHours	Type double Properties Filter, Sort Description The total elapsed time in hours between when the approval process instance was started and now.
ElapsedTimeInMinutes	Type double Properties Filter, Sort Description The total elapsed time in minutes between when the approval process instance was started and now.
LastActorId	Type reference Properties Group, Filter, Sort Description The last actor that approved, rejected, or recalled the process.
ProcessDefinitionId	Type reference Properties Defaulted on create, Group, Filter, Sort Description The ID of this approval process instance.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field	Details
	Description The status of this approval process instance, for example Started, Pending, or Approved.
TargetObjectId	Type reference Properties Filter, Group, Sort Description ID of the object affected by this approval process instance.

Usage

Use this object to query or retrieve an approval process.

The following SOQL query returns details for all the ProcessInstanceStep records related to individual ProcessInstance records. The nested query references `Steps`, which is the child `relationshipName` for ProcessInstanceStep in the ProcessInstance object.

```
SELECT Id, (SELECT Id, StepStatus, Comments FROM Steps)
FROM ProcessInstance
```

The following SOQL query returns details for all the ProcessInstanceWorkitem records related to individual ProcessInstance records. The nested query references `Workitems`, which is the child `relationshipName` for ProcessInstanceWorkitem in the ProcessInstance object.

```
SELECT Id, (SELECT Id, ActorId, ProcessInstanceId FROM Workitems)
FROM ProcessInstance
```

ProcessInstanceHistory can help provide a unified read-only view of the ProcessInstanceStep and ProcessInstanceWorkitem objects.

ProcessInstanceHistory

This read-only object shows all steps and pending approval requests associated with an approval process (ProcessInstance).

Supported Calls

`describeSObjects()`

Special Access Rules

Portal and Communities users can't access this object.

Fields

Field	Details
ActorId	Type reference Properties Filter, Group, Sort Description ID of the user who is currently assigned to this ProcessInstance.
Comments	Type string Properties Filter, Nillable, Sort Description Comments for a ProcessInstanceStep. This field doesn't apply to ProcessInstanceWorkitem records.
ElapsedTimeInDays	Type double Properties Filter, Nillable, Sort Description The total time in days between when the approval process instance was started and when it was completed.
ElapsedTimeInHours	Type double Properties Filter, Nillable, Sort Description The total time in hours between when the approval process instance was started and when it was completed.
ElapsedTimeInMinutes	Type double Properties Filter, Nillable, Sort Description The total time in minutes between when the approval process instance was started and when it was completed.

Field	Details
IsPending	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the ProcessInstance is pending (<code>true</code>) or not (<code>false</code>).
OriginalActorId	Type reference Properties Filter, Group, Sort Description ID of the user who was originally assigned this ProcessInstance.
ProcessInstanceId	Type reference Properties Filter, Group, Sort Description ID of the ProcessInstance.
RemindersSent	Type int Properties Filter, Group, Nillable, Sort Description Number of reminders that have been sent. Default is 0 (zero).
StepStatus	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Indicates the current status of the ProcessInstanceStep.
TargetObjectId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the object being approved.

Usage

This object helps you replicate the related list functionality of the Salesforce user interface for approval processes. Use `ProcessInstanceHistory` for a unified read-only view of the `ProcessInstanceStep` and `ProcessInstanceWorkitem` objects. You can't query `ProcessInstanceHistory`. Instead, you can query `ProcessInstanceHistory` by including it in a nested query on the parent `ProcessInstance` object. For example, the following SOQL query returns all the `ProcessInstanceHistory` records related to individual `ProcessInstance` records. The nested query references `StepsAndWorkitems`, which is the child `relationshipName` for `ProcessInstanceHistory` in the `ProcessInstance` object.

```
SELECT Id, (SELECT Id, StepStatus, Comments FROM StepsAndWorkitems)
FROM ProcessInstance
```

This object respects field-level security on the parent object.

ProcessInstanceStep

Represents one work item in an approval process (`ProcessInstance`).

 **Note:** Exceptions apply to approval history data retrieved with this object and available only via the SOAP API. For each approval process instance that was pending when Summer '14 became available for your organization, some field values are never populated or are populated only after the approval process instance is next acted upon—such as when a user approves, rejects, or reassigns an approval request—after the Summer '14 rollout.

`ProcessInstanceStep` fields are never populated for approval process instances that were completed before the Summer '14 rollout. For approval process instances that were pending during the Summer '14 rollout, all `ProcessInstanceStep` fields are populated only after the approval process instance is next acted upon after the Summer '14 rollout.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Portal and Communities users can't access this object.

Fields

Field	Details
ActorId	Type reference
	Properties Filter, Group, Sort
	Description ID of the user who is currently assigned to this approval step.
Comments	Type string

Field	Details
	Properties Filter, Nillable, Sort Description Limit: 4,000 bytes.
ElapsedTimeInDays	Type double Properties Filter, Nillable, Sort Description The total time in days since this step was started.
ElapsedTimeInHours	Type double Properties Filter, Nillable, Sort Description The total time in hours since this step was started.
ElapsedTimeInMinutes	Type double Properties Filter, Nillable, Sort Description The total time in minutes since this step was started.
OriginalActorId	Type reference Properties Filter, Group, Sort Description ID of the user who was originally assigned to this approval step.
ProcessInstanceId	Type reference Properties Filter, Group, Sort Description ID of the ProcessInstance that this approval step belongs to.
StepNodeId	Type reference

Field	Details
	Properties Filter, Group, Nillable, Sort Description ID of the node currently assigned to this approval step.
StepStatus	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The current status of this approval step. • Approved • Fault • Held • NoResponse • Pending • Reassigned • Rejected • Removed • Started If the approval step requires unanimous approval and one approver rejects the request, the value of this field for the other approvers changes to NoResponse. Likewise, if approval is based on the first response and an approver responds, the value of this field for the other approvers changes to NoResponse.

Usage

Query or retrieve a new step in an approval process (ProcessInstance).

ProcessInstanceNode

Represents a step in an instance of an approval process. Compare to ProcessNode, which describes the step in a process definition. Use this object to retrieve approval history.

 **Note:** Exceptions apply to approval history data retrieved with this object and available only via the SOAP API. For each approval process instance that was pending when Summer '14 became available for your organization, some field values are never populated or are populated only after the approval process instance is next acted upon—such as when a user approves, rejects, or reassigns an approval request—after the Summer '14 rollout.

ProcessInstanceNode fields are never populated for approval process instances that were completed before the Summer '14 rollout. For approval process instances that were pending during the Summer '14 rollout, all ProcessInstanceNode fields are populated only after the approval process instance is next acted upon after the Summer '14 rollout.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Portal and Communities users can't access this object.

Fields

Field	Details
CompletedDate	Type dateTime Properties Filter, Sort Description The completion date and time of this step in the approval process. The <code>ElapsedTimeDay</code>, <code>ElapsedTimeHours</code>, and <code>ElapsedTimeMinutes</code> field values are calculated using <code>CompletedDate</code>.
ElapsedTimeInDays	Type double Properties Filter, Sort Description The total time in days since this step was started.
ElapsedTimeInHours	Type double Properties Filter, Sort Description The total time in hours since this step was started.
ElapsedTimeInMinutes	Type double Properties Filter, Sort Description The total time in minutes since this step was started.
LastActorId	Type reference

Field	Details
	Properties Defaulted on create, Group, Filter, Sort Description The last actor that approved or rejected this step.
NodeStatus	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The status of this approval instance, for example Started, Pending, or Approved.
ProcessInstanceId	Type reference Properties Filter, Group, Sort Description The approval process this step is part of.
ProcessNodeId	Type reference Properties Filter, Group, Sort Description The identifier for this step.
ProcessNodeName	Type string Properties Filter, Group, Sort Description The name of this step.

ProcessInstanceWorkitem

Represents a user's pending approval request.



Note: Exceptions apply to approval history data retrieved with this object and available only via the SOAP API. For each approval process instance that was pending when Summer '14 became available for your organization, some field values are never populated or are populated only after the approval process instance is next acted upon—such as when a user approves, rejects, or reassigns an approval request—after the Summer '14 rollout.

ProcessInstanceWorkitem fields are never populated for approval process instances that were completed before the Summer '14 rollout. For approval process instances that were pending during the Summer '14 rollout, all ProcessInstanceWorkitem fields are populated after the approval process instance is next acted upon after the Summer '14 rollout, with three exceptions: `ElapsedTimeInDays`, `ElapsedTimeInDays`, and `ElapsedTimeInMinutes` fields are never populated in ProcessInstanceWorkitem records for which equivalent ProcessInstanceStep records were created before the Summer '14 rollout.

For all other ProcessInstanceWorkitem records, these three fields are populated after the approval process instance is next acted upon after the Summer '14 rollout.



Note: Because ProcessInstanceHistory combines fields from ProcessInstanceStep and ProcessInstanceWorkitem, you may notice incorrect elapsed times of 0 in ProcessInstanceHistory records because the elapsed time fields were never populated in the related ProcessInstanceWorkitem record.

Supported Calls

`delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`

Special Access Rules

Portal and Communities users can't access this object.

Fields

Field	Details
ActorId	Type reference Properties Filter, Group, Sort, Update Description ID of the user who is currently responsible for approving an approval request.
ElapsedTimeInDays	Type double Properties Filter, Nillable Description The total time in days since this approval request was started.
ElapsedTimeInHours	Type double Properties Filter, Nillable Description The total time in hours since this approval request was started.

Field	Details
ElapsedTimeInMinutes	Type double Properties Filter, Nillable Description The total time in minutes since this approval request was started.
OriginalActorId	Type reference Properties Filter, Group, Sort, Update Description ID of the user who was originally assigned this approval request.
ProcessInstanceId	Type reference Properties Filter, Group, Sort, Update Description ID of the ProcessInstance associated with this approval request.

Usage

Use this object to manage a pending approval request for a user.

ProcessNode

Describes a step in a process definition. Compare to ProcessInstanceNode, which describes the step in a running process.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Portal and Communities users can't access this object.

Fields

Field	Details
Description	Type string Properties Filter, Nillable, Sort Description A description of this node, no longer than 3,000 bytes.
DeveloperName	Type string Properties Filter, Group, Sort Description The external name of the node; the name seen by users.
Name	Type string Properties Filter, Group, Sort Description The unique node name.
ProcessDefinition	Type reference Properties Filter, Group, Sort Description ID of the object affected by this approval instance.

Usage

Use this object to get the description of a process definition.

The following SOQL query returns details for all the ProcessInstanceStep records related to individual ProcessInstance records. The nested query references `Steps`, which is the child `relationshipName` for ProcessInstanceStep in the ProcessInstance object.

```
SELECT Id, (SELECT Id, StepStatus, Comments FROM Steps)
FROM ProcessInstance
```

The following SOQL query returns details for all the ProcessInstanceWorkitem records related to individual ProcessInstance records. The nested query references `Workitems`, which is the child `relationshipName` for `ProcessInstanceWorkitem` in the `ProcessInstance` object.

```
SELECT Id, (SELECT Id, ActorId, ProcessInstanceId FROM Workitems)
FROM ProcessInstance
```

`ProcessInstanceHistory` can help provide a unified read-only view of the `ProcessInstanceStep` and `ProcessInstanceWorkitem` objects.

Product2

Represents a product that your organization sells.

This object has several fields that are used only for quantity and revenue schedules (for example, annuities). Schedules are available only for organizations that have enabled the products and schedules features. If these features aren't enabled, the schedule fields don't appear in the `DescribeSObjectResult`, and you can't query, create, or update the fields.

 **Note:** Products are represented by `Product2` objects. The `Product` object is no longer available.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
CanUseQuantitySchedule	Type boolean
	Properties Defaulted on create, Filter, Group, Sort
	Description Indicates whether the product can have a quantity schedule (<code>true</code>) or not (<code>false</code>). Label is Quantity Scheduling Enabled .
CanUseRevenueSchedule	Type boolean
	Properties Defaulted on create, Filter, Group, Sort
	Description Indicates whether the product can have a revenue schedule (<code>true</code>) or not (<code>false</code>). Label is Revenue Scheduling Enabled .
ConnectionReceivedId	Type reference

Field	Details
	Properties Filter, Nillable Description ID of the PartnerNetworkConnection that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
ConnectionSentId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the ConnectionSentId field is no longer supported. The ConnectionSentId field is still visible, but the value is null. You can use the new PartnerNetworkRecordConnection object to forward records to connections.
CurrencyIsoCode	Type picklist Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
DefaultPrice	Type currency Properties Create, Filter, Update Description The default price for this record.
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A text description of this record. Label is Product Description.
Family	Type picklist

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description Name of the product family associated with this record. Product families are configured as picklists in the user interface. To obtain a list of valid values, call <code>describeObjects()</code> and process the <code>DescribeObjectResult</code> for the values associated with the <code>Family</code> field. Label is Product Family.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this record is active (<code>true</code>) or not (<code>false</code>). Inactive Product2 records are hidden in many areas in the user interface. You can change the <code>IsActive</code> flag on a Product2 object as often as necessary. Label is Active.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Default name of this record. Label is Product Name.
NumberOfQuantityInstallments	Type int Properties Filter, Group, Sort Description If the product has a quantity schedule, the number of installments.
NumberOfRevenueInstallments	Type int

Field	Details
	Properties Filter, Group, Nillable, Sort Description If the product has a revenue schedule, the number of installments.
ProductCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Default product code for this record. The product code naming pattern is defined by your organization.
QuantityInstallmentPeriod	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description If the product has a quantity schedule, the amount of time covered by the schedule.
QuantityScheduleType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of the quantity schedule, if the product has one.
RecalculateTotalPrice	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Changes behavior of OpportunityLineItem calculations when a line item has child schedule rows for the <code>Quantity</code> value. When enabled, if the rollup quantity changes, then the quantity rollup value is multiplied against the sales price to change the total price.
RevenueInstallmentPeriod	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description If the product has a revenue schedule, the period of time covered by the schedule.

Field	Details
RevenueScheduleType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of the revenue schedule, if the product has one.

Schedule Enabled Flags

When enabling the schedules feature, organizations can decide whether to enable quantity schedules, revenue schedules, or both. In addition, you can use the API to control quantity and revenue scheduling at the product level via the `CanUseQuantitySchedule` and `CanUseRevenueSchedule` flags. A value of `true` for either flag indicates that the product and any `OpportunityLineItem`s can have a schedule of that type. These flags can be set when creating or updating Product2 records.

Default Schedule Fields

The remaining schedule fields for this object define default schedules. Default schedule values are used to create an `OpportunityLineItemSchedule` when an `OpportunityLineItem` is created for the Product.

The default schedule fields support the following valid values (all fields are also nillable).

Field	Valid Values
RevenueScheduleType	Divide, Repeat
RevenueInstallmentPeriod	Daily, Weekly, Monthly, Quarterly, Yearly
NumberOfRevenueInstallments	Integer between 1 to 150, inclusive.
QuantityScheduleType	Divide, Repeat
QuantityInstallmentPeriod	Daily, Weekly, Monthly, Quarterly, Yearly
NumberOfQuantityInstallments	Integer between 1 to 150, inclusive

When you attempt to set the schedule fields when creating or updating, the API applies cross-field integrity checks. The integrity requirements are:

- If the schedule type is nil, the installment period and number of installments must be nil.
- If the schedule type is set to any value, then the installment period and number of installments must be non-nil.

Any create or update that fails these integrity checks is rejected with an error.

These default schedule fields, as well as `CanUseQuantitySchedule` and `CanUseRevenueSchedule`, are restricted picklist fields and are available only if the organization has the schedules feature enabled.

Usage

Use this object to define the default product information for your organization. This object is associated by reference with Pricebook2 objects via PricebookEntry objects. The same product can be represented in different price books as price book entries. In fact, the same product can be represented multiple times (as separate PricebookEntry records) in the same price book with different prices or currencies. A product can only have one price for a given currency within the same price book. To be used in custom price books, all standard prices must be added as price book entries to the standard price book.

You can query the products that have been configured for your organization. For example, you can allow your client application to obtain valid product IDs for use when configuring PricebookEntry records via the API. Your client application can perform the following tasks on PricebookEntry objects:

- Query
- Create for the standard pricebook or custom pricebooks.
- Update
- Delete
- Change the `IsActive` field when creating or updating records

This object is defined only for those organizations that have products enabled as a feature. If the organization does not have the products feature, this object does not appear in the `describeGlobal()` call, and you can't describe or query this object.

If you try to delete a product via the API but there is an opportunity that uses that product, the delete fails. The workaround is to delete the product in the user interface, which gives you an option to archive the product.

 **Note:** On opportunities and opportunity products, the workflow rules, validation rules, and Apex triggers fire when an update to a child opportunity product or schedule causes an update to the parent record. This means your custom application logic is enforced when there are updates to the parent record, ensuring higher data quality and compliance with your organization's business policies.

Product2Feed

Represents a single feed item in the feed displayed on the detail page for a product record.

A product feed shows recent changes to a product record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to products in Salesforce. This object is available in API version 18.0 and later.

 **Note:** Products are represented by Product2 objects. The Product object is no longer available.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Product2 object
- "Moderate Chatter"



Note: Users with the “Moderate Chatter” permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of Product2Feed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type <code>int</code> Properties <code>Filter</code>, <code>Group</code>, <code>Sort</code> Description The number of <code>FeedComments</code> associated with this feed item.
ConnectionId	Type reference Properties <code>Filter</code>, <code>Group</code>, <code>Nillable</code>, <code>Sort</code> Description When a <code>PartnerNetworkConnection</code> makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the <code>PartnerNetworkConnection</code> that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties <code>Nillable</code> Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea

Field	Details
	Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
<code>ContentFileName</code>	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
<code>ContentSize</code>	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
<code>ContentType</code>	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
<code>CreatedDate</code>	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
<code>FeedPostId</code>	Type reference Properties Filter, Group, Nillable, Sort

Field	Details
	Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
<code>InsertedById</code>	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
<code>LastModifiedDate</code>	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
<code>LikeCount</code>	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.

Field	Details
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the product record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.

Field	Details
Title	Type string Properties Group, Nillable, Sort Description The title of the feed item. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com.

Field	Details
	• TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for a product record.

ProductEntitlementTemplate

Represents predefined terms of customer support (Entitlement) that users can add to products (Product2).

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
EntitlementTemplateId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the entitlement template. Must be a valid ID.
Product2Id	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the Product2 associated with the entitlement template. Must be a valid ID.

Usage

Use to query and manage entitlement templates.

Profile

Represents a profile, which defines a set of permissions to perform different operations, such as querying, adding, updating, or deleting information.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`

Special Access Rules

- Customer Portal users can't access this object.

- Partner portal users can't access this object.

Fields

Field	Details
Description	Type string Properties Filter, Group, Nillable, Sort, Update Description Description of the profile.
IsSsoEnabled	Type boolean Properties Defaulted on create, Filter, Group, Sort Description If <code>true</code>, users assigned to this profile can delegate username and password authentication to a corporate database instead of the user database.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp for when the current user last viewed a record related to this profile. Available in API version 29.0 and later.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp for when the current user last viewed this profile. Available in API version 29.0 and later.
Name	Type string Properties Filter, Group, Sort, Update Description The name of the profile.

Field	Details
Permissions <i>PermissionName</i>	Type boolean Properties Filter, Update Description One field for each permission. If <code>true</code>, users assigned to this profile have the named permission. The number of fields varies depending on the permissions for the organization and license type.  Tip: To get a list of available permissions in the SOAP API, use <code>describeObjects()</code>.
UserLicenseId	Type reference Properties Filter, Group, Sort Description ID of the UserLicense associated with this profile.
UserType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The category of user license. Each <code>USERType</code> is associated with one or more UserLicense records. Each UserLicense is associated with one or more profiles. In API version 10.0 and later, valid values include: • Standard: user license. This user type also includes Salesforce Platform and Salesforce Platform One user licenses. Label is Standard. • PowerPartner: User whose access is limited because he or she is a partner and typically accesses the application through a partner portal or community. Label is Partner. • CSPLitePortal: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal or community. Label is High Volume Portal. • CustomerSuccess: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal. Label is Customer Portal User. • PowerCustomerSuccess: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal. Label is Customer Portal Manager. Users with this license type can view and edit data they directly own or data owned by or shared with users below them in the Customer Portal role hierarchy.

Field	Details
	• CsnOnly: user whose access to the application is limited to Chatter. This user type includes Chatter Free and Chatter moderator users. Label is Chatter Free. UserType replaces LicenseType, which is unavailable as of API version 10.0. In API versions 8.0 and 9.0 LicenseType is still available with the following valid values: • AUL: Force.com user license. Label is Apex Platform. • AUL1: Force.com user license with only one user. Label is Apex Platform One. • Salesforce: Salesforce user license. Label is Salesforce. • PackageManager: user who can create and work with managed packages for Force.com AppExchange. Label is Package Manager. • PRM: user whose access is limited because he or she is a partner and typically accesses the application through a partner portal. Label is Partner. • CustomerUser: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal. Label is Customer Portal User. • CustomerManager: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal. Label is Customer Portal Manager. Users with this license type can view and edit data they directly own or data owned by or shared with users below them in the Customer Portal role hierarchy.

Usage

Use the Profile object to query the set of currently configured user profiles in your organization. Your client application can use Profile objects to obtain valid profile IDs for use when querying or modifying users through the API.

In the user interface, profiles can be used to assign user licenses from specific pools (Force.com Platform user license or Salesforce user license, for example). If a user is assigned to a profile with a different license type, the number of available licenses in the old license type pool increases, one per user changed, and decreases by the same amount in the new license type pool.

ProfileSkill

Represents a profile skill, which describes a user's professional knowledge. This is a global record for the organization, and users are associated through the ProfileSkillUser object.

 **Note:** For information about Live Agent skills, see the [Skill](#) topic.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
Description	Type textarea Properties Create, Nillable, Update Description Description of the profile skill.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp indicating when the current user last viewed a record related to this profile skill. Available in API version 29.0 and later.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The timestamp indicating when the current user last viewed this profile skill. Available in API version 29.0 and later.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The name of the profile skill.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The owner of the profile skill.
UserCount	Type int

Field Name	Details
	Properties Filter, Group, Nillable, Sort
	Description The number of users with the profile skill.

Usage

Use the ProfileSkill object to look up the attributes of a skill that can be assigned to a user. This is a global object and is not owned by any specific user.

ProfileSkillEndorsement

Represents a detail relationship of ProfileSkillUser. An endorsement of a profile skill shows approval and support of another user's publicly declared skill.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The name of the profile skill being endorsed.
ProfileSkillUserId	Type reference Properties Create, Filter, Group, Sort Description The ID of the ProfileSkillUser record that is being endorsed.
UserId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update
	Description The user ID of the person giving the endorsement.

Usage

Use the ProfileSkillEndorsement object to query about a single endorsement given to a user about a specific skill. Users can't endorse themselves, they can only be endorsed by others unless they are administrators with the "Modify All Data" permission.

ProfileSkillEndorsementFeed

Represents a single feed item in the feed displayed on the detail page for a ProfileSkillEndorsement record. This object is available in API version 34.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code> . Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code> . This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The numbers of FeedComments associated with this feed item.
ContentData	Type base64

Field Name	Details
	Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code> .
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code> .
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code> . The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code> .
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference

Field Name	Details
	Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then <code>InsertedById</code> is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the ProfileSkillEndorsement record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of TypeContentPost.
Title	Type string

Field Name	Details
	Properties Group, Nillable, Sort Description The title of the FeedItem. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of ContentPost, LinkPost, and TextPost, feed item types should not be created directly from the API. • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question.

Field Name	Details
	• <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated.

ProfileSkillEndorsementHistory

Represents the history of changes to the fields of a ProfileSkillEndorsement.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>Field</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The profile skill endorsement changed field.
<code>NewValue</code>	Type anyType Properties Nillable, Sort Description The new value of the profile skill endorsement field.
<code>OldValue</code>	Type anyType Properties Nillable, Sort Description The old value of the profile skill endorsement field.

Field Name	Details
ProfileSkillEndorsementId	Type reference Properties Filter, Group, Sort Description The ID of the profile skill endorsement.

Usage

Use this read-only object to identify changes to a ProfileSkillEndorsement.

ProfileSkillFeed

Represents a single feed item in the feed displayed on the detail page for a profile skill.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the ProfileSkillFeed. Required when <code>Type</code> is <code>TextPost</code> . Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code> . This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64

Field Name	Details
	Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nillable, Sort

Field Name	Details
	Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nilable, Sort Description The URL of a <code>LinkPost</code>.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the object type to which the <code>FeedItem</code> object is related. For example, set this field to a <code>UserId</code> to post to someone's profile feed, or an <code>AccountId</code> to post to a specific account.
RelatedRecordId	Type reference Properties Group, Nilable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing ContentVersion and post it to a feed as a <code>FeedItem</code> object of <code>Type ContentPost</code>.
Title	Type string Properties Group, Nilable, Sort

Field Name	Details
	Description The title of the FeedItem. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of ProfileSkillFeed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a <code>Task</code> associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a <code>Task</code> or <code>Event</code> associated with a case record (excluding email and call logging). For a recurring <code>Task</code> with <code>CaseFeed</code> disabled, one event is generated for the series only. For a recurring <code>Task</code> with <code>CaseFeed</code> enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com.

Field Name	Details
	• <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Usage

A ProfileSkill feed shows recent changes to a ProfileSkill record for any fields that are tracked in feeds, as well as comments and posts about the record. It is a useful way to stay up-to-date with changes to solutions. Use this object to track changes for a ProfileSkill record.

ProfileSkillHistory

Represents the history of changes to the fields of a ProfileSkill.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The value of the field before it was changed.
ProfileSkillId	Type reference Properties Filter, Group, Sort Description Required. ID of the ProfileSkill.

Usage

Use this read-only object to identify changes to a ProfileSkill.

ProfileSkillShare

Represents a sharing entry on a ProfileSkill.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Level of access that the User or Group has to the ProfileSkill. The possible values are: • Read • Edit • All (This value is not valid for <code>create()</code> or <code>update()</code> calls.) This value must be set to an access level that is higher than the organization's default access level for ProfileSkill objects.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the parent object, if any.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Values may include: • Manual—The User or Group has access because a user with "All" access manually shared the ProfileSkill with them. • Owner—The User is the owner of the ProfileSkill or is in a role above the ProfileSkill owner in the role hierarchy.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the User or Group that has been given access to the ProfileSkill.

Usage

This object is read only. It is visible because of constraints to the ProfileSkill object, but it is ignored and does not control which users and groups can view and edit ProfileSkill records owned by other users.

ProfileSkillUser

Represents a detail relationship of User. The object connects profile skills with users.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
EndorsementCount	Type int Properties Filter, Group, Nillable, Sort Description The number of endorsements.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The name of the skill user.
ProfileSkillId	Type reference Properties Create, Filter, Group, Sort Description The ID of the ProfileSkill.
UserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The ID of the user. This field can't be changed once it is created.

Usage

Use this object to assign specific skills to specific users. ProfileSkillUser appears on the Overview tab on the Chatter profile page. Users can only create a skill mapping for themselves, they can't create skill mappings for others unless they are administrators with the "Modify All Data" permission. Additionally, users can only edit this object if they are the context user and are not editing the `userId` field.

ProfileSkillUserFeed

Represents a single feed item in the feed displayed on the detail page for a ProfileSkillUser record. This object is available in API version 34.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when <code>Type</code> is TextPost. Optional when <code>Type</code> is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The numbers of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable

Field Name	Details
	Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nilable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nilable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nilable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nilable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nilable, Sort

Field Name	Details
	Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then <code>InsertedById</code> is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the ProfileSkillUser record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of TypeContentPost.
Title	Type string Properties Group, Nillable, Sort

Field Name	Details
	Description The title of the FeedItem. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of ContentPost, LinkPost, and TextPost, feed item types should not be created directly from the API. - ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. - AdvancedTextPost—created when a user posts a group announcement. - AnnouncementPost—Not used. - ApprovalPost—generated when a user submits an approval. - BasicTemplateFeedItem—Not used. - CanvasPost—a post made by a canvas app posts on a feed. - CollaborationGroupCreated—generated when a user creates a public group. - CollaborationGroupUnarchived—Not used. - ContentPost—a post with an attached file. - CreatedRecordEvent—generated when a user creates a record from the publisher. - DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. - DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. - LinkPost—a post with an attached URL. - PollPost—a poll posted on a feed. - ProfileSkillPost—generated when a skill is added to a user's Chatter profile. - QuestionPost—generated when a user posts a question. - ReplyPost—generated when Chatter Answers posts a reply.

Field Name	Details
	• <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated.

ProfileSkillUserHistory

Represents the history of changes to the fields of a ProfileSkillUser.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>Field</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
<code>NewValue</code>	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
<code>OldValue</code>	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Field Name	Details
ProfileSkillUserId	Type reference Properties Filter, Group, Sort Description Required. ID of the ProfileSkillUser.

Usage

Use this read-only object to identify changes to a ProfileSkillUser.

PushTopic

Represents a query that is the basis for notifying listeners of changes to records in an organization. This is available from API version 21.0 or later.

Supported Calls

REST: DELETE, GET, PATCH, POST (query requests are specified in the URI)

SOAP: `create()`, `delete()`, `describe()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`

Special Access Rules

- This object is only available if Streaming API is enabled for your organization.
- Only users with “Create” permission can create this record. Users with “View All Data” can view PushTopic records and see streaming messages.

Fields

Field	Field Type	Description
ApiVersion	double	Required. API version to use for executing the query specified in <code>Query</code> . It must be an API version greater than 20.0. If your query applies to a custom object from a package, this value must match the package's <code>ApiVersion</code> . Example value: 34.0 Field Properties: Create, Filter, Sort, Update
Description	string	Description of the PushTopic. Limit: 400 characters Field Properties: Create, Filter, Sort, Update

Field	Field Type	Description
ID	ID	System field: Globally unique string that identifies a record. Field Properties: Default on create, Filter, Group, idLookup, Sort
isActive	boolean	Indicates whether the record currently counts towards the organization's limit. Field Properties: Create, Default on create, Filter, Group, Sort, Update
IsDeleted	boolean	System field: Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Field Properties: Default on create, Filter, Group, Sort
Name	string	Required. Descriptive name of the PushTopic, such as <code>MyNewCases</code> or <code>TeamUpdatedContacts</code> . Limit: 25 characters. This value identifies the channel. Field Properties: Create, Filter, Group, Sort, Update
NotifyForFields	picklist	Specifies which fields are evaluated to generate a notification. Valid values: - All - Referenced (default) - Select - Where Field Properties: Create, Filter, Sort, Update
NotifyForOperations	picklist	Specifies which record events may generate a notification. Valid values: - All (default) - Create - Extended - Update Field Properties for API version 28.0 and earlier: Create, Filter, Sort, Update Field Properties for API version 29.0 and later: Filter, Sort In API version 29.0 and later, this field is read-only, and will not contain information about delete and undelete events. Use <code>NotifyForOperationCreate</code> , <code>NotifyForOperationDelete</code> , <code>NotifyForOperationUndelete</code> and <code>NotifyForOperationUpdate</code> to specify which record events should generate a notification. A value of <code>Extended</code> means that neither create or update operations are set to generate events.
NotifyForOperationCreate	boolean	<code>true</code> if a create operation should generate a notification, otherwise, <code>false</code> . Defaults to <code>true</code> . This field is available in API version 29.0 and later.

Field	Field Type	Description
NotifyForOperationDelete	boolean	<code>true</code> if a delete operation should generate a notification, otherwise, <code>false</code> . Defaults to <code>true</code> . Clients must connect using the <code>cometd/29.0</code> (or later) Streaming API endpoint to receive delete and undelete event notifications. This field is available in API version 29.0 and later.
NotifyForOperationUndelete	boolean	<code>true</code> if an undelete operation should generate a notification, otherwise, <code>false</code> . Defaults to <code>true</code> . Clients must connect using the <code>cometd/29.0</code> (or later) Streaming API endpoint to receive delete and undelete event notifications. This field is available in API version 29.0 and later.
NotifyForOperationUpdate	boolean	<code>true</code> if an update operation should generate a notification, otherwise, <code>false</code> . Defaults to <code>true</code> . This field is available in API version 29.0 and later.
Query	string	Required. The SOQL query statement that determines which record changes trigger events to be sent to the channel. Limit: 1300 characters Field Properties: Create, Filter, Sort, Update

PushTopic and Notifications

The PushTopic defines when notifications are generated in the channel. This is specified by configuring the following PushTopic fields:

- PushTopic Queries
- Events
- Notifications

QuantityForecast

Represents a quantity-based forecast.

The API also provides revenue-based forecasts using RevenueForecast.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Requires the “View All Data” permission.
- Customer Portal users can’t access this object.

Fields

Field	Details
Closed	Type double Properties Filter, Nillable, Sort Description Read-only. A rollup of opportunities or opportunity line items that have closed in this period.
Commit	Type double Properties Filter, Nillable, Sort Description The owner's Commit total.
CommitComment	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Read-only. The comment entered when the owner edited his or her Commit total from the Adjusted Total link on the forecast edit page.
CommitOverride	Type double Properties Create, Filter, Nillable, Sort, Update Description Read-only. The owner's override of their own My Commit total.
DefaultRollupCommit	Type double Properties Filter, Nillable, Sort Description Read-only. The owner's standard Commit rollup, including their own opportunities and forecast-level overrides from subordinate users in the role hierarchy.
DefaultRollupUpside	Type double

Field	Details
	Properties Filter, Nillable, Sort Description Read-only. The owner's standard Best Case rollup, including their own opportunities and forecast-level overrides from subordinate users in the role hierarchy.
InvalidationDate	Type dateTime Properties Filter, Nillable, Sort Description Read-only. If not blank, indicates that the rollup numbers for Forecast Override fields that represent calculated (summarized) amounts may not be up to date.
ManagerChoiceCommit	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Read-only. The manager's choice regarding the commit amount: • DefaultRollup: Use the manager's default commit rollup for owner's forecast, which reflects the manager's opportunity forecast overrides. • AcceptForecast (default selection): Accept the forecast owner's Adjusted Total commit amount, which may or may not be an override. • ManagerManualOverride: Use the manager's manual override. • OpportunityOnlyRollup: Use the opportunity rollup, including opportunity forecast overrides, but excluding any forecast-level (Adjusted Total) overrides.
ManagerChoiceUpside	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description Read-only. The manager's choice regarding the best case amount: • DefaultRollup: Use the manager's default best case rollup for owner's forecast, which reflects the manager's opportunity forecast overrides. • AcceptForecast (default selection): Accept the forecast owner's Adjusted Total best case amount, which may or may not be an override. • ManagerManualOverride: Use the manager's manual override. • OpportunityOnlyRollup: Use the opportunity rollup, including opportunity forecast overrides, but excluding any forecast-level (Adjusted Total) overrides.

Field	Details
ManagerClosed	Type double Properties Filter, Nillable, Sort Description Read-only. The manager's closed total for the owner's forecast, including any opportunity or opportunity product overrides made by the manager.
ManagerCommit	Type double Properties Filter, Nillable, Sort Description The manager's Commit total.
ManagerCommitOverride	Type double Properties Create, Filter, Nillable, Sort, Update Description Read-only. The manager's manual override of the forecast owner's Commit total. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerDefaultRollupCommit	Type double Properties Filter, Nillable, Sort Description Read-only. The manager's standard Commit rollup for the forecast owner. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerDefaultRollupUpside	Type double Properties Filter, Nillable, Sort Description Read-only. The manager's standard Best Case rollup for the forecast owner. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.

Field	Details
ManagerId	Type reference Properties Filter, Group, Nillable, Sort Description Read-only. ID of the direct manager of the user who owns this forecast.
ManagerOpportunityRollupCommit	Type double Properties Filter, Nillable, Sort Description Read-only. The manager's view of the forecast owner's opportunity-level Commit rollup, ignoring all forecast overrides. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerOpportunityRollupUpside	Type double Properties Filter, Nillable, Sort Description Read-only. The manager's view of the forecast owner's opportunity-level Best Case rollup, ignoring all forecast overrides. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerPipeline	Type double Properties Filter, Nillable, Sort Description The manager's pipeline total for the owner's forecast, including any opportunity or opportunity product overrides made by the manager.
ManagerUpside	Type double Properties Filter, Nillable, Sort Description The manager's Best Case total.

Field	Details
ManagerUpsideOverride	Type double Properties Create, Filter, Nillable, Sort, Update Description The manager's manual override of the forecast owner's Best Case total. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
OpportunityRollupClosed	Type double Properties Filter, Nillable, Sort Description The owner's Closed total for his or her opportunities only.
OpportunityRollupCommit	Type double Properties Filter, Nillable, Sort Description The owner's Commit total for his or her opportunities only.
OpportunityRollupPipeline	Type double Properties Filter, Nillable, Sort Description The owner's Pipeline total for his or her opportunities only.
OpportunityRollupUpside	Type double Properties Filter, Nillable, Sort Description The owner's Best Case total for his or her opportunities only.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort

Field	Details
	Description ID of the User who owns this forecast. Required on create.
PeriodId	Type reference Properties Filter, Nillable, Group, Sort Description The ID of the Period that contains the <code>StartDate</code> .
Pipeline	Type double Properties Filter, Nillable, Sort Description The total pipeline rollup from subordinates in the role hierarchy, including the owner's opportunities.
ProductFamily	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The value chosen in the Product Family picklist, which can be configured from Setup at Customize > Products > Fields . This field is relevant if you have chosen "Use Product Families" as the Forecast Type from Setup at Customize > Forecast > Settings . If you are not forecasting by product family or if the forecast represents opportunities that are not associated with a product family, then this field is blank. Required on create.
Quota	Type double Properties Create, Filter, Nillable, Sort, Update Description The quota amount for the period. You can create, update, upsert, and delete. Requires the "Modify All Data" and "Manage Users" permission. Required on create.
StartDate	Type date Properties Create, Filter, Group, Nillable, Sort

Field	Details
	Description The start date of this forecast. The ID of the Period that contains this date is written to the <code>PeriodId</code> field if it changes. A new Period is created if none exists. Required on create.
Upside	Type currency Properties Filter, Nillable Description The owner's Best Case total.
UpsideComment	Type string Properties Filter, Nillable, Update Description The comment entered when the owner edited his or her Best Case total.
UpsideOverride	Type double Properties Filter, Nillable, Update Description Read only. The owner's override of their own My Best Case total.

Usage

Query this object to support customizable forecasts based on quantities.

You can update one field, `Quota`, which means that you can mass update sales users' quotas instead of updating them one by one in the user interface. Editing `Quota`, which means that you can mass update sales users' quotas instead of updating them one by one in the user interface. Editing `Quota` requires the “Modify All Data” and “Manage Users” permissions.

The rollup fields always reflect opportunity and opportunity product overrides by the forecast owner or one of the forecast owner's subordinates in the role hierarchy. In addition, the manager rollup fields include overrides by the forecast owner's direct manager in the role hierarchy.

Some of the rollup fields ignore forecast-level (**Adjusted Total**) overrides, but they never ignore opportunity forecast overrides that are visible to the owner or manager.

QuantityForecastHistory

Represents historical information about quantity-based forecasts that have been submitted (saved) in the user interface.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

- Requires the “View All Data” permission.
- Customer Portal users can’t access this object.

Fields

Field	Details
Closed	Type double Properties Filter, Nillable, Sort Description The closed amount of the forecast.
Commit	Type double Properties Filter, Nillable, Sort Description The commit amount of the forecast.
CommitComments	Type string Properties Filter, Group, Nillable, Sort Description Comments about the commit value.
CommitOverridden	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the commit value was overridden (<code>true</code>) or not (<code>false</code>).
CurrencyIsoCode	Type picklist

Field	Details
	Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
ForecastOverrideId	Type reference Properties Filter, Group, Sort Description ID of the related forecast override.
Pipeline	Type double Properties Filter, Nillable, Sort Description The pipeline amount of the forecast.
Quota	Type currency Properties Filter, Nillable Description The quota amount of the forecast.
Upside	Type currency Properties Filter, Nillable Description The best case amount of the forecast.
UpsideComments	Type string Properties Filter, Nillable Description Comments about the upside value.

Field	Details
UpsideOverridden	Type boolean Properties Defaulted on create, Filter Description Indicates whether the upside value was overridden (<code>true</code>) or not (<code>false</code>).

Usage

This is a read-only object specific to customizable forecasting.

When a user submits a revenue-based forecast in the user interface, a new record is created. If the same forecast is ever resubmitted, additional records are added. The `CreatedDate` of a record reflects the day on which the forecast was submitted. This object respects field level security on the parent object.

QueueRoutingConfig

Represents the settings that determine how work items are routed to agents. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
CapacityPercentage	Type percent Properties Create, Filter, Nillable, Sort, Update Description The percentage of an agent's capacity for work items that's consumed by a specific type of work item from this service channel. For example, you might give phone calls a capacity percentage of <code>100</code> . If an agent receives a phone call, the agent won't receive new work items until the call ends, because at that point the agent's capacity will have reached 100%. This field is available in API version 33.0 and later.
CapacityWeight	Type double

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description The amount of an agent's capacity for work items that's consumed by a work item from this service channel. For example, if an agent has a capacity of 6, and cases are assigned a capacity weight of 2, an agent can be assigned up to 3 cases before the agent is at capacity and can't receive new work items. This field is available in API version 33.0 and later.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the presence status.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The label of the presence status.
RoutingModel	Type picklist

Field	Details
	Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The routing type that determines how work items are routed (pushed) to agents. Possible values are <code>Least Active</code> and <code>Most Available</code> .
RoutingPriority	Type int Properties Create, Filter, Group, Sort, Update Description The priority in which work items from the service channels that are related to this routing configuration are routed to agents. Work items from routing configurations that have lower priority values (for example, <code>0</code>) are routed to agents first.
ServiceChannelId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the service channel that's associated with this configuration.

Question

Represents a question in a community that users can view and reply to.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
BestReplyId	Type reference Properties Filter, Group, Nillable, Sort, Update

Field	Details
	Description The ID of the Reply that has been identified as the best answer to the question. You must use the user interface to identify the best answer for a question.
BestReplySelectedById	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the User who selected the best answer to the question. This field is available in API version 24.0 and later. In API version 24.0 through version 29.0, you must update this field using the UI. In API version 34.0 and later, you can update this field using the API.
Body	Type textarea Properties Create, Nillable, Update Description Description of the question.
CommunityId	Type reference Properties Create, Filter, Group, Sort Description The zone ID associated with the question. Once you create a question, you can't change the zone ID associated with that question.
CreatorFullPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's profile photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
CreatorName	Type string Properties Filter, Group, Nillable, Sort

Field	Details
	Description Name of the user who posted the question or reply. Only the first name of internal users (agents) appears to portal users in the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
CreatorSmallPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's thumbnail photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
HasSingleFieldForContent	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the content of a Chatter Answers question is: • Included in only one field: <code>Title</code> if the content is unformatted and less than 255 characters; or <code>Body</code> if the content is formatted or more than 255 characters (<code>true</code>) • Included in two fields: <code>Title</code> and <code>Body</code> (<code>false</code>) This field also determines if content displays in one or two fields in Chatter Answers question feeds. This field is available in API version 25.0 and later.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastReplyDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time the last reply (child Reply object) was posted.

Field	Details
LastReplyId	Type reference Properties Filter, Group, Nillable, Sort Description Read only. The ID of the last reply (child Reply object) posted to the question.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (LastReferencedDate) and not viewed.
MostReportAbusesOnReply	Type int Properties Filter, Group, Nillable, Sort Description The most number of user-reported abuses on a Reply associated with the question. This field is available in API version 24.0 and later.
NumReplies	Type int Properties Filter, Group, Nillable, Sort Description The number of replies (child Reply object) that users have submitted for the question.
NumReportAbuses	Type int Properties Filter, Group, Nillable, Sort Description Represents the number of user-reported abuses on the question. This field is available in API version 24.0 and later.
NumSubscriptions	Type int

Field	Details
	Properties Filter, Group, Nillable, Sort Description Represents the number of users following the question. This field is available in API version 24.0 and later.
Origin	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The source of the question, such as <code>Chatter Answers</code>. This field is available in API version 24.0 and later.
Title	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The descriptive title of the question.
UpVotes	Type int Properties Filter, Group, Nillable, Sort Description The total number of up votes for the question.
VoteScore	Type double Properties Filter, Nillable, Sort Description The internal score of the question, used to sort questions and articles on the Popular tab in the application user interface. The internal algorithm that determines the score gives older votes less weight than newer votes, simulating exponential decay. The score itself does not display in the application user interface.  Note: Unlike other fields of type double, you can't use a SOQL aggregate function with this field.

Usage

Use this object to track questions in azone.

QuestionDataCategorySelection

A data category selection represents a data category that classifies a question. This object can be used to associate a question with a data category from a data category group or to query the categorization for a question.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

To create, read or update data category selection, you must have create, read or update permission on the categorized question. Users who can update question can also delete its category selection. Users who can create questions can only select categories visible to their role.

Fields

Field Name	Details
DataCategoryGroupName	Type DataCategoryGroupReference Properties Create Description Unique name of the data category group which has a category associated with the question.
DataCategoryName	Type DataCategoryGroupReference Properties Create Description Unique name of the data category associated with the question.
ParentId	Type reference Properties Create, Filter Description ID of the question associated with the data category selection.

Usage

Every question can be categorized in a data category. You can use the `QuestionDataCategorySelection` object to query and manage question categorization. Client applications can create categorization for a question. They can also delete, query, and retrieve question categorization.



Warning: Even though the API lets you select more than one category for `QuestionDataCategorySelection`, the Answers tab only supports one data category selection for questions. Selecting multiple categories through `QuestionDataCategorySelection` may result in unexpected behavior in the Answers tab, such as losing your multiple selections. You should only select one data category when using `QuestionDataCategorySelection`.

Sample Code—Java

In the following example, the `selectCategory` method adds a category to a question data category selection. The `retrieveCategorySelections` method returns all the categories from a question data category selection.

```
public void selectCategory(ID parentId, String categoryGroupName, String categoryName) {
    try {
        QuestionDataCategorySelection categorySelection = new
        QuestionDataCategorySelection();

        categorySelection.setParentId(parentId);
        categorySelection.setDataCategoryGroupName(categoryGroupName);
        categorySelection.setDataCategoryName(categoryName);
        binding.create(new SObject[]{categorySelection});
    } catch (RemoteException e) {
        System.out.println("An unexpected error has occurred." + e.getMessage());
    }
}

public String[] retrieveCategorySelections(String parentId) {
    QueryResult qr = null;

    try {
        qr = binding.query("SELECT DataCategoryName FROM QuestionDataCategorySelection
        WHERE Id = '" + parentId + "'");
    } catch (RemoteException e) {
        System.out.println("An unexpected error has occurred." + e.getMessage());
    }

    String[] categoryNames = new String[qr.getRecords().length];
    for (int index = 0; index < qr.getRecords().length; index++) {
        categoryNames[index] =
        ((QuestionDataCategorySelection)qr.getRecords()[index]).getDataCategoryName();
    }

    return categoryNames;
}
```

Salesforce Knowledge uses a similar object for article data category selection. See [Article Type__DataCategorySelection](#) for SOQL examples using this object.

QuestionReportAbuse

Represents a user-reported abuse on a Question in a Chatter Answers community. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The name of the Question from which the user reported abuse.
QuestionId	Type reference Properties Create, Filter, Group, Sort Description The ID of the Question from which the user reported abuse.
Reason	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The reason the user reported abuse on the Question, such as <code>Spam</code> , <code>Hateful</code> , or <code>Inappropriate</code> .

Usage

Use this object to track user-reported abuse on questions created in a Chatter Answers community.

QuestionSubscription

Represents a subscription for a user following a Question. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
CommunityId	Type reference Properties Filter, Group, Nillable, Sort Description Required. ID of the zone associated with the Question the user is following. This field can't be updated.
Name	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description The name of the question subscription.
QuestionCreatedDate	Type dateTime Properties Filter, Nillable, Sort Description Required. Creation date of the Question which the user is following. This field can't be updated.
QuestionId	Type reference Properties Create, Filter, Group, Sort, Update Description Required. ID of the Question which the user is following. This field can't be updated.
SubscriberId	Type reference Properties Create, Filter, Group, Sort, Update

Field	Details
	Description Required. ID of the User who is following the Question. This field can't be updated.

Usage

Things to consider when following a Question:

- A user can only follow questions that they have permission to view.
- Administrators and users with the “Modify All Data” permission can configure other users to follow questions that the other user has read access to.
- Administrators and users with the “Modify All Data” permission can configure users to stop following questions.

Queries on QuestionSubscription:

- Users with the “Read” permission on Question can see which questions other users are following.
- A query must include a LIMIT clause and the limit can't exceed 1,000.
- A query using a WHERE clause can only filter by fields on Question.

QueueSubject

Represents the mapping between a queue Group and the sObject types associated with the queue, including custom objects.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object. A queue is a Group whose `Type` is `Queue`. To create a Group, you must have the “Manage Users” permission.

Fields

Field	Details
<code>QueueId</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of a queue.

Field	Details
SubjectType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description A list of object types that can be associated with the queue specified by the <code>QueueId</code> .

Usage

Use this object to associate a queue with the `sObject` that can be associated with the queue, including custom objects.

QuickText

This object stores a snippet of text that allows an agent to send a quick response to a customer in the Live Agent console. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
Category	Type picklist Properties Create, Filter, Group, Sort, Update Description A customizable picklist that can be used to group multiple related Quick Text records together
Channel	Type picklist Properties Create, Filter, Nillable, Update Description A multi-select picklist that can be used to specify where specific Quick Text messages should be available, such as in Live Agent or in the Email publisher in Case Feed.

Field Name	Details
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Message	Type textarea Properties Create, Filter (unavailable in API version 25.0 and later), Sort (unavailable in API version 25.0 and later), Update Description The content of the Quick Text record
Name	Type string Properties Create, Filter (unavailable in API version 25.0 and later), Group, Sort (unavailable in API version 25.0 and later), Update Description A descriptive label for the Quick Text record
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the User who owns the Quick Text record

Usage

Use this object to create and manage the QuickText messages available to agents in the Live Agent console. You can categorize multiple QuickText records into groups using the Category field. The Category field can also be a parent to multiple custom dependent Picklist fields to create a hierarchical structure of categories.

QuickTextHistory

Represents changes to field values on a QuickText object. This object is available in API version 24.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed
OldValue	Type anyType Properties Nillable, Sort Description The old value of the field that was changed
QuickTextId	Type reference Properties Filter, Group, Sort

Field Name	Details
	Description The ID of the QuickText that was changed

Usage

Use this object to identify changes to a QuickText.

QuickTextOwnerSharingRule

Represents a rule for sharing a QuickText object with users other than the owner.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccessLevel</code>	Type picklist Properties Create, Group, Sort, Update Description A value that represents the type of sharing allowed. The possible values are: • Read • Edit
<code>Description</code>	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
<code>DeveloperName</code>	Type string

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupID	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. QuickText objects owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label in the user interface.
UserorGroupID	Type reference Properties Create, Filter Description The ID representing the target user or group. Target users or groups have access to the QuickText.

Usage

Use this object to manage the sharing rules for a QuickText object.

QuickTextShare

Represents a sharing entry on a QuickText object. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Level of access that the User or Group has to the QuickText. The possible values are: - Read - Edit - All (This value is not valid for <code>create()</code> or <code>update()</code> calls.) This value must be set to an access level that is higher than the organization's default access level for QuickText objects.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the parent object, if any
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Values may include: - Manual—The User or Group has access because a user with "All" access manually shared the QuickText with them. - Owner—The User is the owner of the QuickText or is in a role above the QuickText owner in the role hierarchy.

Field Name	Details
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the User or Group that has been given access to the QuickText

Usage

This object lets you determine which users and groups can view and edit QuickText records owned by other users.

If you attempt to create a new record that matches an existing record, the `create()` call updates any modified fields and returns the existing record.

Quote

The Quote object represents a quote, which is a record showing proposed prices for products and services. Quotes can be created from and synced with opportunities, and emailed as PDFs to customers

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the account that's associated with the quote.
AdditionalAddress	Type address Properties Filter, Nillable Description Compound form of the additional address. Read-only. See Address Compound Fields for details on compound address fields.

Field	Details
AdditionalCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description City for the quote's additional address. Up to 40 characters allowed.
AdditionalCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Country for the quote's additional address. Up to 80 characters allowed.
AdditionalCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO country code for the quote's additional address.
AdditionalLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>AdditionalLongitude</code> to specify the precise geolocation of an additional address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
AdditionalLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>AdditionalLatitude</code> to specify the precise geolocation of an additional address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
AdditionalName	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description Name associated with the quote's additional address. Limited: 255 characters.
AdditionalPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Postal Code for the quote's additional address.
AdditionalState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description State for the quote's additional address. Up to 80 characters allowed.
AdditionalStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO state code for the quote's additional address.
AdditionalStreet	Type textarea Properties Create, Filter, Nillable, Group, Sort, Update Description Street name for the quote's additional address.
BillingAddress	Type address Properties Filter, Nillable Description Compound form of the billing address. Read-only. See Address Compound Fields for details on compound address fields.

Field	Details
BillingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description City for the quote's billing address. Up to 40 characters allowed.
BillingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Country for the quote's billing address. Up to 80 characters allowed.
BillingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO country code for the quote's billing address.
BillingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLongitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
BillingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLatitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
BillingName	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description Entity that the quote is billed to.
BillingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Postal Code for the quote's billing address.
BillingState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description State for the quote's billing address. Up to 80 characters allowed.
BillingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO state code for the quote's billing address.
BillingStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Street name for the quote's billing address.
ContactId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the contact that's associated with the quote.
ContractId	Type reference

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the contract that's associated with the quote.
CurrencyIsoCode	Type picklist Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization. If the organization has multicurrency and a <code>Pricebook2Id</code> specified on the quote, then the currency value of this field must match the currency of the <code>PricebookEntry</code> objects that are associated with any quote line items it has. This value is copied from the related Opportunity and can't be changed.
Description	Type textarea Properties Nillable Description Text description of the quote. Limit: 32,000 characters.
Discount	Type percent Properties Filter, Nillable, Sort Description Difference between the sum of the <code>QuoteLineItem</code> record's <code>Subtotal</code> and the sum of the <code>QuoteLineItem</code> record's <code>Discount</code> totals. Expressed as a percentage.
Email	Type email Properties Filter, Group, Nillable, Sort Description Email address of the contact associated with the quote.
ExpirationDate	Type date

Field	Details
	Properties Create, Filter, Nillable, Update Description Date this quote is no longer valid.
Fax	Type phone Properties Create, Filter, Nillable, Update Description Fax number for the contact associated with the quote.
GrandTotal	Type currency Properties Filter, Nillable Description Total price of the quote plus shipping and taxes.
IsSyncing	Type boolean Properties Defaulted on create, Filter Description Indicates whether the quote is syncing with an opportunity.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.

Field	Details
LineItemCount	Type int Properties Filter, Nillable Description Number of line items on the quote.
Name	Type string Properties Create, Filter, idLookup, Update Description Required. Name for the quote. Limit: 225 characters.
OpportunityId	Type reference Properties Create, Filter Description ID for the opportunity associated with the quote.
Phone	Type phone Properties Create, Filter, Nillable, Update Description Phone number of the contact associated with the quote.
Pricebook2Id	Type reference Properties Create, Filter, Nillable, Update Description ID of the price book associated with the quote.
QuoteNumber	Type string Properties Defaulted on create, Filter Description Automatically-generated number identifying the quote.

Field	Details
QuoteToAddress	Type address Properties Filter, Nillable Description Compound form of the quote to address. Read-only. See Address Compound Fields for details on compound address fields.
QuoteToCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description City for the address to send the quote to for approval, such as a third party-agency representing a buyer. Up to 40 characters allowed.
QuoteToCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Country for the address to send the quote to for approval. Up to 80 characters allowed.
QuoteToLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>QuoteToLongitude</code> to specify the precise geolocation of a quote to address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
QuoteToLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>QuoteToLatitude</code> to specify the precise geolocation of a quote to address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.

Field	Details
QuoteToName	Type string Properties Create, Filter, Nillable, Update Description Name of the entity (such as a person or business) the quote is sent to for approval. Limit: 255 characters.
QuoteToPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Postal code for the address to send the quote to for approval.
QuoteToState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description State for the address to send the quote to for approval. Up to 80 characters allowed.
QuoteToStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Street name for the address to send the quote to for approval.
RecordTypeID	Type reference Properties Create, Filter, Nillable, Update Description ID of the record type assigned to the object.
ShippingAddress	Type address Properties Filter, Nillable

Field	Details
	Description Compound form of the shipping address. Read-only. See Address Compound Fields for details on compound address fields.
ShippingCity	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description City for the quote's shipping address. Up to 40 characters allowed.
ShippingCountry	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Country for the quote's shipping address. Up to 80 characters allowed.
ShippingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO country code for the quote's shipping address.
ShippingHandling	Type currency Properties Create, Filter, Nillable, Update Description Total shipping and handling costs for the quote.
ShippingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLongitude</code> to specify the precise geolocation of a shipping address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.

Field	Details
ShippingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLatitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
ShippingName	Type string Properties Create, Filter, Nillable, Update Description Name of the entity (such as a person or business) the quote is sent to for approval.
ShippingPostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Postal code for the quote's shipping address.
ShippingState	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description State for the quote's shipping address. Up to 80 characters allowed.
ShippingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description ISO state code for the quote's shipping address.
ShippingStreet	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description Street name for the quote's shipping address.
Status	Type picklist Properties Create, Filter, Nillable, Update Description Current status of the quote. The standard options are: • —None— • Draft • Needs Review • In Review • Approved • Rejected • Presented • Accepted • Denied
Subtotal	Type currency Properties Filter, Nillable Description Line item's sales price multiplied by the quantity minus the discount.
Tax	Type currency Properties Create, Filter, Nillable, Update Description Total taxes for the quote.
TotalPrice	Type currency Properties Filter, Nillable Description Total of the quote line items after discounts and before taxes and shipping.

Usage

Use Quote to manage proposed product prices for customers. To update a Quote, your client application needs "Edit" permission.

- Client applications can create, update, delete, and query Attachment records associated with a quote via the API.
- You can sync a quote and its parent Opportunity.

QuoteDocument

The QuoteDocument object represents a quote in document format.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
CurrencyIsoCode	Type picklist Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization. If the organization has multicurrency and a <code>Pricebook2Id</code> specified on the quote, then the currency value of this field must match the currency of the PricebookEntry objects that are associated with any quote line items it has.
Discount	Type percent Properties Create, Filter, Nillable Description The discount for the quote used in the document.
Document	Type base64 Properties Create, Nillable Description The binary data of the document stored in the QuoteDocument object.

Field	Details
GrandTotal	Type currency Properties Create, Filter, Nillable Description Grand total for the quote used in the document.
Name	Type string Properties Filter, idLookup Description Name of the quote document.
QuoteId	Type reference Properties Create, Filter Description ID for the quote used for the document.

Usage

Use the QuoteDocument object to store a document that can be used to present the quote information to the customer.

QuoteLineItem

The QuoteLineItem object represents a quote line item, which is a member of the list of Product2 products associated with a Quote, along with other information about those line items on that quote.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

The user must have “Edit” permissions on Quote records in order to create or update quote line items on a quote. The user must have “Edit” permissions on Quote records to delete a quote line item.

Fields

Field	Details
CurrencyIsoCode	Type picklist Properties Filter, Restricted picklist Description Available only for organizations enabled for multiples currencies. Contains the ISO code for any currency allowed by the organization. If the organization has multicurrency and a Pricebook2 is specified on the quote (the <code>Pricebook2Id</code> field is not blank), then the currency value of this field must match the currency of the PricebookEntry objects for any associated quote line items. This value is copied from the related Quote and can't be changed.
Description	Type string Properties Filter, Group, Nillable, Sort Description Text description of the line item. Limit: 225 characters.
Discount	Type percent Properties Filter, Nillable, Sort Description Editable number from 0 to 100.
HasQuantitySchedule	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read-only. Indicates whether the opportunity line item that the quote line item is synced with has a quantity schedule.
HasRevenueSchedule	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description Read-only. Indicates whether the opportunity line item that the quote line item is synced with has a revenue schedule. If this object has a revenue schedule, the <code>GrandTotal</code> and <code>TotalPrice</code> fields can't be updated. In addition, the <code>Quantity</code> field can't be updated if this object has a quantity schedule. The system ignores any attempt to update this field. The update isn't rejected but the updated value is ignored.
HasSchedule	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Read-only. Indicates whether the line item uses schedules.
LineNumber	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description Read-only. Automatically-generated number identifying the quote line item. In the form of <code>QL-XXXXX</code>.
ListPrice	Type currency Properties Filter, Nillable, Sort Description Read-only. Corresponds to the <code>UnitPrice</code> on the <code>PricebookEntry</code> that is associated with this line item, which can be in the standard price book or a custom price book. A client application can use this information to show whether the unit price (or sales price) of the line item differs from the price book entry list price.
PricebookEntryId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the associated <code>PricebookEntry</code>. Exists only for those organizations that have Products enabled as a feature.
Product2Id	Type reference

Field	Details
	Properties Create, Filter, Group, Sort, Update Description ID of the Product2 associated with this QuoteLineItem.
Quantity	Type double Properties Create, Filter, Sort, Update Description The number of units for the line item.
QuoteId	Type reference Properties Create, Filter, Group, Sort Description Required. ID of the associated Quote.
ServiceDate	Type date Properties Filter, Group, Nillable, Sort Description Date when the product revenue will be recognized and the product quantity will be shipped.
SortOrder	Type int Properties Filter, Group, Nillable, Sort Description The value of where the line item is in the sorted order, such as 1, 2, and so on. The SortOrder value determines the order in which a quote line item displays in the Quote Detail page. Client applications can use this to match the sort order in Salesforce. This field is only available in API versions 21.0 and greater.
Subtotal	Type currency Properties Filter, Nillable Description The line item's <code>Quantity</code> multiplied by the <code>UnitPrice</code> .

Field	Details
TotalPrice	Type currency Properties Filter, Nillable Description Read-only. Calculated by applying the <code>Discount</code> to the <code>Subtotal</code>. This field is nillable, but you can't set both <code>TotalPrice</code> and <code>UnitPrice</code> to null in the same update. To insert the <code>TotalPrice</code> for a quote line item via the API (given only a unit price and the quantity), calculate this field as the unit price multiplied by the quantity. This field is read-only if the quote line item has a revenue schedule.
UnitPrice	Type currency Properties Create, Filter, Update Description The price per unit for the quote line item.

Usage

A Quote record can have QuoteLineItem records only if the Quote has a Pricebook2. A QuoteLineItem must correspond to a Product2 that is listed in the quote's Pricebook2.



Note: If the multicurrency option has been enabled, the `CurrencyIsoCode` field is present. It can't be modified, it is always set to the value of the `CurrencyIsoCode` of the parent Quote.

Effects on Quotes

Quotes that have associated QuoteLineItem objects are affected in the following ways:

- Creating a QuoteLineItem increments the Quote value by the `TotalPrice` of the QuoteLineItem.
- When you create or update a QuoteLineItem, the API verifies that the line item corresponds to a PricebookEntry in the Pricebook2 that is associated with the quote.

RecentlyViewed

Represents records that the current user has recently viewed or referenced (by viewing a related record).

Supported Calls

`query()`, `update()`

Special Usage Rules

The RecentlyViewed object does not support the Report, KnowledgeArticle, and Article objects.

Fields

Field	Details
Alias	Type string Properties Filter, Group, Nillable, Sort Description The alias on the record.
Email	Type email Properties Filter, Group, Nillable, Sort Description The email address on the record.
FirstName	Type string Properties Filter, Group, Nillable, Sort Description The first name on the record. If the recently viewed record is a user, this is the user's first name.
Id	Type ID Properties Defaulted on create, Filter, Group, Sort Description The ID of the recently viewed record.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the recently viewed record is an active user (<code>true</code>) or not (<code>false</code>). This field contains a value only if the recently viewed record is a user.

Field	Details
LastName	Type string Properties Filter, Group, Nillable, Sort Description The last name on the record.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Filter, Group, Nillable, Sort Description The name on the recently viewed record. If the recently viewed record is a user, contact, or lead, the value is a concatenation of the <code>firstname</code> and <code>lastname</code> field values.
NetworkId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the community that this group is part of. This field is available only if Salesforce Communities is enabled in your organization. You can add a <code>NetworkId</code> only when creating a group. You can't change or add a <code>NetworkId</code> for an existing group. This field is available in API version 27.0 and later.
Phone	Type phone

Field	Details
	Properties Filter, Group, Nillable, Sort Description The phone number on the record.
ProfileId	Type reference Properties Filter, Group, Nillable, Sort Description If the recently viewed record is a user, this is the user's profile ID.
Title	Type string Properties Filter, Group, Nillable, Sort Description If the recently viewed record is a user, this is the title of the user; for example CFO or CEO.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The sObject type for this recently viewed record. Valid values include any standard or custom objects that RecentlyViewed supports.
UserRoleId	Type reference Properties Filter, Group, Nillable, Sort Description The ID of the user role associated with this object.

Usage

This object provides a heterogeneous list of different object types and consists of recently viewed records or records that were recently referenced (a related record was viewed). A record is considered viewed when the user sees the details associated with it, but not when the user sees it in a list with other records. Use this object to programmatically construct a list of recently viewed items specific to the current user, for example, on a custom user interface or for search auto-complete options. You can also retrieve a filtered list of records by object type (`Type`). The RecentlyViewed data is periodically truncated down to 200 records per object.

Use this query in your code to retrieve a list of all the records that were recently viewed. The results are ordered from most to least recent.

```
SELECT Id, Name
FROM RecentlyViewed
WHERE LastViewedDate !=null
ORDER BY LastViewedDate DESC
```

Use this query to retrieve data that was either viewed or referenced, but only for a limited set of objects.

```
SELECT Id, Name
FROM RecentlyViewed
WHERE Type IN ('Account', 'Contact', 'Plan__c')
ORDER BY LastViewedDate DESC
```

This query retrieves a list of all recently viewed contacts with contact-specific fields, such as the contact's account name, and the custom website field. Records are ordered from most to least recent.

```
SELECT Account.Name, Title, Email, Phone, Website__c
FROM Contact
WHERE LastViewedDate != NULL
ORDER BY LastViewedDate DESC
```

RecordType

Represents a record type.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
BusinessProcessId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Required for Opportunity and Lead record types in API version 17.0 and later. ID of an associated BusinessProcess.
Description	Type string

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description A description of this record. Limit: 255 characters.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description Required. The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is Record Type Name.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description Indicates whether this record is active (<code>true</code>) or not (<code>false</code>). Only active record types can be applied to records. Label is Active.
IsPersonType	Type boolean Properties Defaulted on create, Filter Description Indicates whether this record has been designated as a person account (<code>true</code>) or not (<code>false</code>). Visible only if the organization has the person account feature enabled.
Name	Type string Properties Create, Filter, Group, Sort, Update

Field	Details
	Description Required. Label of the record type in the user interface. Limit: 80 characters. Label is Record Type Label.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.
ObjectType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Object to which this record type applies, including custom objects.

Usage

Use this object to offer different BusinessProcess records and subsets of picklist values to different users based on their Profile. Your client application can describe or query RecordType records.

The following objects have a `RecordTypeId` field:

- Account
- Campaign
- CampaignMember
- Case

- Contact
- Contract
- Lead
- Opportunity
- QuickText
- Solution
- Custom objects

Client applications can create or update values in `RecordTypeId` on these objects, specifying a valid record type ID associated with these objects.

 **Note:** You can't create or update the `RecordTypeId` field on the CampaignMember records. Set the CampaignMember record type using the `CampaignMemberRecordTypeId` field on Campaign.

A client application can retrieve the list of valid record type IDs for a given object by querying the `RecordType`.

RecordTypeLocalization

When the Translation Workbench is enabled for your organization, the `RecordTypeLocalization` object provides the translation of the label for a record type.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Your organization must be using Professional, Enterprise, Developer, Unlimited, or Performance Edition and be enabled for the Translation Workbench.
- To view this object, you must have the "View Setup and Configuration" permission.

Fields

Field	Details
Language	Typestring PropertiesCreate, Filter, Nillable, Restricted picklist DescriptionThe language for this translated label.
NamespacePrefix	Typestring

Field	Details
	Properties Filter, Nillable Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
ParentId	Type reference Properties Create, Filter, Nillable Description The ID of the RecordType associated with the label that is being translated.
Value	Type string Properties Create, Filter, Nillable, Update Description The actual translated label for the record type. Label is Translation.

Usage

Use this object to translate the labels of your record types into other supported languages.

Reply

Represents a reply that a user has submitted to a question in an answers community.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Body	Type textarea Properties Create, Update Description Body of this reply.
CommunityId	Type reference Properties Filter, Group, Nillable, Sort Description The zone ID associated with the question and its reply. This field is available in API version 27.0 and later.
CreatorFullPhotoUrl	Type string Properties Filter, Group, Nillable, Sort Description URL of the user's profile photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
CreatorName	Type string Properties Filter, Group, Nillable, Sort Description Name of the user who posted the question or reply. Only the first name of internal users (agents) appears to portal users in the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later
CreatorSmallPhotoUrl	Type string

Field	Details
	Properties Filter, Group, Nillable, Sort Description URL of the user's thumbnail photo from the feed. Chatter Answers must be enabled to view this field. This field is available in API version 26.0 and later.
DownVotes	Type int Properties Filter, Group, Nillable, Sort Description The total number of down votes for a reply.
Name	Type string Properties Filter, Group, idLookup, Sort Description When creating a Reply, the <code>Name</code> field is automatically populated with a truncated, plain text version of the Reply <code>Body</code> field.
NumReportAbuses	Type int Properties Filter, Group, Nillable, Sort Description Represents the number of reported abuses on the reply by users. This field is available in API version 24.0 and later.
QuestionId	Type reference Properties Create, Filter, Group, Sort Description ID of the Question to which this reply was made.
UpVotes	Type int Properties Filter, Group, Nillable, Sort

Field	Details
VoteTotal	Description The total number of up votes for a reply.
	Type double
	Properties Filter, Nillable, Sort
	Description The total number of all votes for a reply, including up and down votes.

Usage

Use this object to track replies to a Question.

ReplyReportAbuse

Represents a user-reported abuse on a Reply in a Chatter Answers community. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Name	Type string
	Properties Autonumber, Defaulted on create, Filter, idLookup, Sort
	Description The name of the Reply from which the user reported abuse.
Reason	Type picklist
	Properties Create, Filter, Group, Restricted picklist, Sort
	Description The reason the user reported abuse on the Reply, such as <code>Spam</code> , <code>Hateful</code> , or <code>Inappropriate</code> .

Field	Details
ReplyId	Type reference Properties Create, Filter, Group, Sort Description The ID of the Reply from which the user reported abuse.

Usage

Use this object to track user-reported abuse on replies created in a Chatter Answers community.

Report

Represents a report, a set of data that meets certain criteria, displayed in an organized way. Access is read-only. This object is available in API version 20.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `search()`

Fields

Field	Details
Description	Type string Properties Filter, Group, Nillable, Sort Description The description of the report. Limit: 255 characters.
DeveloperName	Type string Properties Filter, Group, Sort Description Required. The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package

Field	Details
	installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is Report Unique Name.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Format	Type picklist Properties Filter, Group, Sort Description Required. Indicates the format of the report. This field is available in API version 34.0 and later. Can have one of these values: • Tabular for reports in that format. The label is <code>Tabular</code>. • Summary for reports in that format. The label is <code>Summary</code>. • Matrix for reports in that format. The label is <code>Matrix</code>. • Multiblock for reports in joined format. The label is <code>Joined</code>.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastRunDate	Type dateTime Properties Filter, Nillable, Sort Description Returns the date the report was last run. Label is Last Run.

Field	Details
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Filter, Group, Sort Description Required. The report label used in the user interface.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.
OwnerId	Type reference Properties Filter Description The ID of the user who currently owns this report.

Usage

Use the report object to get report metadata. Query, search, or retrieve specific metadata on reports. Report object fields are read-only.

Sample

In this example, a SOQL query returns reports that contain the name “sales” and are listed by their developer names, format, ID, and report name.

```
SELECT DeveloperName,Format,Id,Name FROM Report WHERE Name LIKE '%sales%'
```

ReportFeed

Represents a single feed item in the feed displayed on a report. This object is available in API version 20.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn’t create, you must have one of these permissions:

- “Modify All Data”
- “Moderate Chatter”

 **Note:** Users with the “Moderate Chatter” permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of ReportFeed. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort

Field	Details
	Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the CreatedBy field contains the ID of the system administrator while the ConnectionId contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if Type is ContentPost. The name of the file uploaded to the feed. Setting ContentFileName automatically sets Type to ContentPost.
ContentSize	Type int Properties Group, Nillable, Sort

Field	Details
	Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group , Nillable , Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter , Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter , Group , Nillable , Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost . A FeedPost represents the following types of changes in an FeedItem : changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group , Nillable , Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values:

Field	Details
	NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope: - Only feed items with a Group or User parent can set a NetworkId or a null value for NetworkScope. - For feed items with a record parent, users can set NetworkScope only to AllNetworks. - You can't filter a FeedItem on the NetworkScope field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the account record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the report record. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also

Field	Details
	occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Field	Details
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this to retrieve the current contents of the feed fields, such as type of feed or feed ID.

ReportTag

Associates a word or short phrase with a Report. This object is available in API version 20.0 and later.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter

Field Name	Details
	Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: - Public—The tag can be viewed and manipulated by all users in an organization. - Personal—The tag can be viewed or manipulated only by a user with a matching OwnerId.

Usage

ReportTag stores the relationship between its parent TagDefinition and the Report being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

ReputationLevel

Represents a reputation level defined for a community. This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization. Only users with permissions to create or manage a community can view the ReputationPointsRule records.

Fields

Field Name	Details
Label	Type string Properties Filter, Group, Nillable, Sort Description The label for the reputation level.
LevelNumber	Type int Properties Filter, Group, Sort Description The rank of the reputation level.
ParentId	Type reference Properties Filter, Group, Sort Description The ID of the parent community (network) the reputation level applies to.
Threshold	Type double Properties Filter, Sort Description The lower limit of reputation points associated with this reputation level. The maximum number of reputation points a user can accrue is 999,999,999,999,999.

ReputationPointsRule

Represents the reputation point rules for a community. Each rule specifies an action that community members can earn points from and the points associated with those actions in a particular community. This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

This object is available only if Salesforce Communities is enabled in your organization. Only users with permissions to create or manage a community can view the ReputationPointsRule records.

Fields

Field Name	Details
ParentId	Type reference Properties Filter, Group, Sort Description The ID of the parent community (network) that the point rule applies to.
Points	Type int Properties Filter, Group, Sort Description The reputation points associated with the member action this rule is for. The maximum value this field can contain is 999,999.
Type	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The member action associated with this rule, limited to one of these values: • Write a post • Write a comment • Receive a comment • Like something

Field Name	Details
	- Receive a like - Share a post - Someone shares your post - Mention someone - Receive a mention - Ask a question - Respond to a question - Receive an answer - Mark an answer as best - Your answer is marked as best

RevenueForecast

Represents a revenue-based forecast.

The API also provides quantity-based forecasts with QuantityForecast.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
Closed	Type currency Properties Create, Filter Description Read only. A rollup of opportunities or opportunity line items that have closed in this period.
Commit	Type currency Properties Filter, Nillable

Field	Details
	Description The owner's Commit total.
CommitComment	Type string Properties Filter, Nillable, Update Description Read only. The comment entered when the owner edited his or her Commit total from the Adjusted Total link on the forecast edit page.
CommitOverride	Type currency Properties Filter, Nillable, Update Description Read only. The owner's override of their own My Commit total.
CurrencyIsoCode	Type picklist Properties Filter, Restricted picklist, Update Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization. You can update or upsert this field and <code>Quota</code> only.
DefaultRollupCommit	Type currency Properties Filter, Nillable Description Read only. The owner's standard Commit rollup, including their own opportunities and forecast-level overrides from subordinate users in the role hierarchy.
DefaultRollupUpside	Type currency Properties Filter, Nillable

Field	Details
	Description Read only. The owner's standard Best Case rollup, including their own opportunities and forecast-level overrides from subordinate users in the role hierarchy.
InvalidationDate	Type dateTime Properties Filter, Nillable Description Read only. If not blank, indicates that the rollup numbers for Forecast Override fields that represent calculated (summarized) amounts may not be up to date.
ManagerChoiceCommit	Type picklist Properties Filter, Nillable, Restricted picklist, Update Description Read only. The manager's choice regarding the commit amount: • DefaultRollup: Use the manager's default commit rollup for owner's forecast, which reflects the manager's opportunity forecast overrides. • AcceptForecast (default selection): Accept the forecast owner's Adjusted Total commit amount, which may or may not be an override. • ManagerManualOverride: Use the manager's manual override. • OpportunityOnlyRollup: Use the opportunity rollup, including opportunity forecast overrides, but excluding any forecast-level (Adjusted Total) overrides.
ManagerChoiceUpside	Type picklist Properties Filter, Nillable, Restricted picklist, Update Description Read only. The manager's choice regarding the best case amount: • DefaultRollup: Use the manager's default best case rollup for owner's forecast, which reflects the manager's opportunity forecast overrides. • AcceptForecast (default selection): Accept the forecast owner's Adjusted Total best case amount, which may or may not be an override. • ManagerManualOverride: Use the manager's manual override.

Field	Details
	OpportunityOnlyRollup: Use the opportunity rollup, including opportunity forecast overrides, but excluding any forecast-level (Adjusted Total) overrides.
ManagerClosed	Type currency Properties Filter, Nillable Description Read only. The manager's closed total for the owner's forecast, including any opportunity or opportunity product overrides made by the manager.
ManagerCommit	Type currency Properties Filter, Nillable Description The manager's Commit total.
ManagerCommitOverride	Type currency Properties Filter, Nillable, Update Description Read only. The manager's manual override of the forecast owner's Commit total. Represents an option in the override popup window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerDefaultRollupCommit	Type currency Properties Filter, Nillable Description Read only. The manager's standard Commit rollup for the forecast owner. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerDefaultRollupUpside	Type currency Properties Filter, Nillable

Field	Details
	Description Read only. The manager's standard Best Case rollup for the forecast owner. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerId	Type reference Properties Filter, Nillable Description Read only. ID of the direct manager of the user who owns this forecast.
ManagerOpportunityRollupCommit	Type currency Properties Filter, Nillable Description The manager's view of the forecast owner's opportunity-level Commit rollup, ignoring all forecast overrides. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerOpportunityRollupUpside	Type currency Properties Filter, Nillable Description The manager's view of the forecast owner's opportunity-level Best Case rollup, ignoring all forecast overrides. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
ManagerPipeline	Type currency Properties Filter, Nillable Description The manager's pipeline total for the owner's forecast, including any opportunity or opportunity product overrides made by the manager.
ManagerTerritoryId	Type reference

Field	Details
	Properties Filter, Nillable Description ID of the manager's UserRole or Territory.
ManagerUpside	Type currency Properties Filter, Nillable Description The manager's Best Case total.
ManagerUpsideOverride	Type currency Properties Filter, Nillable, Update Description The manager's manual override of the forecast owner's Best Case total. Represents an option in the override pop-up window, which allows managers to choose how to roll up the forecast numbers of a direct report.
OpportunityRollupClosed	Type currency Properties Filter, Nillable Description The owner's Closed total for his or her opportunities only.
OpportunityRollupCommit	Type currency Properties Filter, Nillable Description The owner's Commit total for his or her opportunities only.
OpportunityRollupPipeline	Type currency Properties Filter, Nillable Description The owner's Pipeline total for his or her opportunities only.

Field	Details
OpportunityRollupUpside	Type currency Properties Filter, Nillable Description Read only. The owner's Best Case total for his or her opportunities only.
OwnerId	Type reference Properties Create, Defaulted on create, Filter Description ID of the User who owns this forecast. Required on create.
PeriodId	Type reference Properties Filter, Nillable Description The ID of the Period that contains the <code>StartDate</code>.
Pipeline	Type currency Properties Filter, Nillable Description The total pipeline rollup from subordinates in the role hierarchy, including the owner's opportunities.
ProductFamily	Type picklist Properties Create, Filter, Nillable Description The value chosen in the Product Family picklist, which can be configured from Setup at Customize > Products > Fields. This field is relevant if you have chosen "Use Product Families" as the Forecast Type from Setup at Customize > Forecast > Settings. If you are not forecasting by product family or if the forecast represents opportunities that are not associated with a product family, then this field is blank. Otherwise, this field is required on create.

Field	Details
Quota	Type currency Properties Create, Filter, Nillable, Update Description The quota amount for the period. You can update or upsert this field and <code>CurrencyIsoCode</code>, and for Quota only, create. Requires the "Modify All Data" and "Manage Users" permission. Required on create.
StartDate	Type date Properties Create, Filter, Nillable Description The start date of this forecast. The period ID of the period that contains this date is written to the <code>PeriodId</code> field if it changes. A new Period is created if none exists. Required on create.
TerritoryId	Type reference Properties Create, Filter, Nillable Description ID of the forecast owner's UserRole or Territory. Required on create if Territory Management is enabled (if this field is available).
Upside	Type currency Properties Filter, Nillable Description The owner's Best Case total.
UpsideComment	Type string Properties Filter, Nillable, Update Description Read only. The comment entered when the owner edited his or her Best Case total. Label is Best Case Comment.

Field	Details
UpsideOverride	Type currency Properties Filter, Nillable, Update Description Read only. The owner's override of their My Best Case total. Label is Best Case Override.

Usage

Query this object to support customizable forecasts based on revenue. Requires the “View All Data” permission.

You can also update `CurrencyIsoCode` and `Quota`, which means that you can mass update sales users' quotas instead of updating them one by one in the user interface. Editing `Quota` requires “Modify All Data” and “Manage Users” permissions.

The rollup fields always reflect opportunity and opportunity product overrides by the forecast owner or one of the forecast owner's subordinates in the role hierarchy. In addition, the manager rollup fields include overrides by the forecast owner's direct manager in the role hierarchy.

Some of the rollup fields ignore forecast-level (**Adjusted Total**) overrides, but they never ignore opportunity forecast overrides that are visible to the owner or manager.

RevenueForecastHistory

Represents historical information about revenue-based forecasts that have been submitted (saved) in the user interface.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

- Requires the “View All Data” permission.
- Customer Portal users can't access this object.

Fields

Field	Details
Closed	Type currency Properties Filter Nillable

Field	Details
	Description The closed amount of the forecast.
Commit	Type currency Properties Filter, Nillable Description The commit amount of the forecast.
CommitComments	Type string Properties Filter, Nillable Description Comments about the commit value.
CommitOverridden	Type boolean Properties Defaulted on create, Filter Description Indicates whether the commit value was overridden (<code>true</code>) or not (<code>false</code>).
CurrencyIsoCode	Type picklist Properties Filter, Restricted picklist Description Available only for organizations with the multicurrency feature enabled. Contains the ISO code for any currency allowed by the organization.
ForecastOverrideId	Type reference Properties Filter Description ID of the related forecast override.
Pipeline	Type currency

Field	Details
	Properties Filter, Nillable Description The pipeline amount of the forecast.
Quota	Type currency Properties Filter, Nillable Description The quota amount of the forecast.
Upside	Type currency Properties Filter, Nillable Description The best case amount of the forecast.
UpsideComments	Type string Properties Filter, Nillable Description Comments about the upside value.
UpsideOverridden	Type boolean Properties Defaulted on create Filter Description Indicates whether the upside value was overridden (<code>true</code>) or not (<code>false</code>).

Usage

This is a read-only object specific to customizable forecasting.

When a user submits a revenue-based forecast in the user interface, a new record is created. If the same forecast is ever resubmitted, additional records are added. The `CreatedDate` of a record reflects the day on which the forecast was submitted. This object respects field-level security on the parent object.

RuleTerritory2Association

Represents a record-assignment rule and its association to an object, such as Account. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

If a territory model is in `Active` state, any user can view that model, including its territories and assignment rules. For territories in an active model, any user can view assigned records and assigned users subject to your organization's sharing settings. Users cannot view territory models in other states (such as `Planning` or `Archived`).

Fields

Field Name	Details
<code>IsInherited</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Indicates whether the rule is an <i>inherited</i> rule (<code>true</code>) or a <i>local</i> rule (<code>false</code>). Rule inheritance flows from the parent territory where the rule is created to the rule's descendent territories (if any) in the territory model hierarchy. A local rule is created within a single territory and affects that territory only.
<code>RuleId</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of the rule.
<code>Territory2Id</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of the territory where the rule was created.

SamlSsoConfig

Represents a SAML Single Sign-On configuration.

Single sign-on is a process that allows network users to access all authorized network resources without having to log in separately to each resource. Single sign-on allows you to validate usernames and passwords against your corporate user database or other client application rather than having separate user passwords managed by Salesforce. This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
AttributeFormat	Type string Properties Filter, Group, Nillable, Sort Description For SAML 2.0 only and when <code>identityLocation</code> is set to <code>Attribute</code>. Possible values include <code>unspecified</code>, <code>emailAddress</code> or <code>persistent</code>. All legal values can be found in the “Name Identifier Format Identifiers” section of the Assertions and Protocols SAML 2.0 specification.
AttributeName	Type string Properties Filter, Group, Nillable, Sort Description The name of the identity provider’s application. Get this name value from your identity provider.
Audience	Type string Properties Filter, Group, Sort Description The Issuer, also called the “Entity ID.” The value is a URL that uniquely identifies the SAML identity provider.
DeveloperName	Type string

Field Name	Details
	Properties Filter, Group, Sort Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package, and the changes are reflected in a subscriber's organization.
ErrorUrl	Type string Properties Filter, Nillable, Sort Description The URL of the page users should be directed to if there's an error during SAML login. It must be a publicly accessible page, such as a public site Visualforce page. The URL can be absolute or relative.
ExecutionUserID	Type reference Properties Filter, Group, Nillable, Sort Description The user that runs the Apex handler class. The user must have the "Manage Users" permission. A user is required if you specify a SAML JIT handler class.
IdentityLocation	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The location in the assertion where a user is identified. Valid values are: • <code>SubjectNameId</code>—The identity is in the <code><Subject></code> statement of the assertion. • <code>Attribute</code>—The identity is specified in an <code><AttributeValue></code>, located in the <code><Attribute></code> of the assertion.
IdentityMapping	Type picklist

Field Name	Details
	Properties Filter, Group, Restricted picklist, Sort Description The identifier that the service provider uses for the user during Just-in-Time user provisioning. Valid values are: • <code>Username</code>—The user's Salesforce username. • <code>FederationId</code>—The federation ID from the user object; the identifier that's used by the service provider for the user. • <code>UserId</code>—The user ID from the user's Salesforce organization.
Issuer	Type string Properties Filter, idLookup, Group, Sort Description Also called the "Entity ID." The value is a URL that uniquely identifies the SAML identity provider.
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The language for the organization.
LoginUrl	Type string Properties Filter, Nillable, Sort Description For SAML 2.0 only: The URL where Salesforce sends a SAML request to start the login sequence.
LogoutUrl	Type string Properties Filter, Nillable, Sort Description For SAML 2.0 only: The URL to direct users to where they click the Logout link. The default is <code>http://www.salesforce.com</code>.

Field Name	Details
MasterLabel	Type string Properties Filter, Group, Sort Description The text that's used to identify the Visualforce page in the Setup area of Salesforce.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
OptionsSpInitBinding	Type boolean Properties Filter Description The service provider initiated request binding, either HTTP Redirect (<code>true</code>) or HTTP POST (<code>false</code>).
OptionsUserProvisioning	Type boolean Properties Filter

Field Name	Details
	Description If <code>true</code>, Just-in-Time user provisioning is enabled, which creates users on the fly the first time that they try to log in. Specify <code>Federation ID</code> for the <code>identityMapping</code> value to use this feature.
<code>RequestSignatureMethod</code>	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The method that's used to sign the SAML request. Valid values are: • <code>RSA-SHA1</code> • <code>RSA-SHA256</code>
<code>SamlJitHandlerId</code>	Type reference Properties Filter, Group, Nillable, Sort Description The name of an existing Apex class that implements the <code>Auth.SamlJitHandler</code> interface.
<code>ValidationCert</code>	Type string Properties Filter, Sort Description The certificate that's used to validate the request. Get this certificate value from your identity provider.
<code>Version</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The SAML version. Valid values are: • <code>SAML1_1</code> • <code>SAML2_2</code>

Scontrol

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited. We recommend that you move your s-controls to Visualforce. We continue to support the Scontrol object.

Represents a custom s-control, which is custom content that the system hosts, but client applications execute. An s-control can contain any type of content that you can display or run in a Web browser.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`

Special Access Rules

- Your organization must be using Enterprise, Developer, or Unlimited Edition and be enabled for custom s-controls.
- Customer Portal users can't access this object.

Fields

Field	Details
Binary	Type base64 Properties Nillable, Update Description Binary content of this custom s-control, such as an ActiveX control or a Java archive. Can be specified when created, but not when updated. Limit: 5 MB.
BodyLength	Type int Properties Filter, Group, Sort Description The length of the custom s-control. Label is Binary Length.
ContentSource	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort, Update Description Specifies the source of the s-control content, either custom HTML, a snippet (s-controls that are included in other s-controls), or a URL.

Field	Details
Description	Type string Properties Filter, Group, Nillable, Sort, Update Description Description of the custom s-control.
DeveloperName	Type string Properties Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Label is S-Control Name.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
EncodingKey	Type picklist Properties Filter, Group, Restricted picklist, Sort, Update Description Picklist of character set encodings, including ISO-08859-1, UTF-8, EUC, JIS, Shift-JIS, Korean (ks_c_5601-1987), Simplified Chinese (GB2312), and Traditional Chinese (Big5).
Filename	Type string Properties Filter, Group, Nillable, Sort, Update Description An uploaded object to display when the custom s-control is added to a custom link. Can be a Java applet, an ActiveX control, or any other type of desired content.
HtmlWrapper	Type textarea Properties Update

Field	Details
	Description Required. HTML page that will be delivered when the user views this custom s-control. This HTML page can be the entire content of the custom s-control, or it can reference the binary. Limit: 1,048,576 characters. Label is HTML Body.
Name	Type string Properties Filter, Group, Sort, Update Description Required. Name of this custom s-control. Label is Label.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, NamespacePrefix is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
SupportsCaching	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the s-control supports caching (true) or not (false).

Usage

Use custom s-controls to manage custom content that extends application functionality. All users can view custom s-controls, but the "Customize Application" permission is required to create or update custom s-controls.

ScontrolLocalization

 **Important:** Visualforce pages supersede s-controls. Organizations that haven't previously used s-controls can't create them. Existing s-controls are unaffected, and can still be edited.

When the Translation Workbench is enabled for your organization, provides the translation of the field label of an s-control.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Your organization must be using Professional, Enterprise, Developer, or Unlimited Edition and be enabled for the Translation Workbench.
- To view this object, you must have the "View Setup and Configuration" permission.

Fields

Field	Details
LanguageLocaleKey	Type picklist Properties Create, Filter, Nillable, Restricted picklist Description This field is available in API version 16.0 and earlier. It is the same as the <code>Language</code> field.
Language	Type picklist Properties Create, Filter, Nillable, Restricted picklist Description This field is available in API version 17.0 and later. The combined language and locale ISO code, which controls the language for labels displayed in an application. This picklist contains the following fully-supported languages: • Chinese (Simplified): <code>zh_CN</code> • Chinese (Traditional): <code>zh_TW</code> • Danish: <code>da</code>

Field	Details
	- Dutch: <code>n1_NL</code> - English: <code>en_US</code> - Finnish: <code>fi</code> - French: <code>fr</code> - German: <code>de</code> - Italian: <code>it</code> - Japanese: <code>ja</code> - Korean: <code>ko</code> - Norwegian: <code>no</code> - Portuguese (Brazil): <code>pt_BR</code> - Russian: <code>ru</code> - Spanish: <code>es</code> - Spanish (Mexico): <code>es_MX</code> - Swedish: <code>sv</code> - Thai: <code>th</code> The following end-user only languages are available. - Arabic: <code>ar</code> - Bulgarian: <code>bg</code> - Croatian: <code>hr</code> - Czech: <code>cs</code> - English (UK): <code>en_GB</code> - Greek: <code>el</code> - Hebrew: <code>iw</code> - Hungarian: <code>hu</code> - Indonesian: <code>in</code> - Polish: <code>pl</code> - Portuguese (Portugal): <code>pt_PT</code> - Romanian: <code>ro</code> - Slovak: <code>sk</code> - Slovenian: <code>sl</code> - Turkish: <code>tr</code> - Ukrainian: <code>uk</code> - Vietnamese: <code>vi</code> The following platform languages are available for organizations that use Salesforce exclusively as a platform. - Albanian: <code>sq</code> - Arabic (Algeria): <code>ar_DZ</code> - Arabic (Bahrain): <code>ar_BH</code>

Field

Details

- Arabic (Egypt): ar_EG
- Arabic (Iraq): ar_IQ
- Arabic (Jordan): ar_JO
- Arabic (Kuwait): ar_KW
- Arabic (Lebanon): ar_LB
- Arabic (Libya): ar_LY
- Arabic (Morocco): ar_MA
- Arabic (Oman): ar_OM
- Arabic (Qatar): ar_QA
- Arabic (Saudi Arabia): ar_SA
- Arabic (Sudan): ar_SD
- Arabic (Syria): ar_SY
- Arabic (Tunisia): ar_TN
- Arabic (United Arab Emirates): ar_AE
- Arabic (Yemen): ar_YE
- Armenian: hy
- Basque: eu
- Bosnian: bs
- Bengali: bn
- Chinese (Simplified—Singapore): zh_SG
- Chinese (Traditional—Hong Kong): zh_HK
- English (Australia): en_AU
- English (Canada): en_CA
- English (Hong Kong): en_HK
- English (India): en_IN
- English (Ireland): en_IE
- English (Malaysia): en_MY
- English (Philippines): en_PH
- English (Singapore): en_SG
- English (South Africa): en_ZA
- Estonian: et
- French (Belgium): fr_BE
- French (Canada): fr_CA
- French (Luxembourg): fr_LU
- French (Switzerland): fr_CH
- Georgian: ka
- German (Austria): de_AT
- German (Luxembourg): de_LU

Field**Details**

- German (Switzerland): `de_CH`
- Hindi: `hi`
- Icelandic: `is`
- Irish: `ga`
- Italian (Switzerland): `it_CH`
- Latvian: `lv`
- Lithuanian: `lt`
- Luxembourgish: `lb`
- Macedonian: `mk`
- Malay: `ms`
- Maltese: `mt`
- Romanian (Moldova): `ro_MD`
- Montenegrin: `sh_ME`
- Romansh: `rm`
- Serbian (Cyrillic): `sr`
- Serbian (Latin): `sh`
- Spanish (Argentina): `es_AR`
- Spanish (Bolivia): `es_BO`
- Spanish (Chile): `es_CL`
- Spanish (Colombia): `es_CO`
- Spanish (Costa Rica): `es_CR`
- Spanish (Dominican Republic): `es_DO`
- Spanish (Ecuador): `es_EC`
- Spanish (El Salvador): `es_SV`
- Spanish (Guatemala): `es_GT`
- Spanish (Honduras): `es_HN`
- Spanish (Nicaragua): `es_NI`
- Spanish (Panama): `es_PA`
- Spanish (Paraguay): `es_PY`
- Spanish (Peru): `es_PE`
- Spanish (Puerto Rico): `es_PR`
- Spanish (United States): `es_US`
- Spanish (Uruguay): `es_UY`
- Spanish (Venezuela): `es_VE`
- Tagalog: `tl`
- Tamil: `ta`
- Urdu: `ur`
- Welsh: `cy`

Field	Details
	The values in this field are not related to the default locale selection.
NamespacePrefix	Type string Properties Filter, Nillable Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
ScontrolId	Type reference Properties Create, Filter, Nillable Description The ID of the Scontrol that is being translated.
Value	Type string Properties Create, Filter, Nillable, Update Description The actual translated field label of the s-control. Label is Translation.

Usage

Use this object to translate your s-controls into a supported language. Users with the Translation Workbench enabled can view s-control translations, but either the "Customize Application" or "Manage Translation" permission is required to create or update s-control translations.

SearchPromotionRule

Represents a promoted search term, which is one or more keywords that you associate with a Salesforce Knowledge article. When a user's search query includes these keywords, the associated article is returned first in search results. This object is available in API version 31.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

A user must have the "Manage Promoted Search Terms" permission.

Fields

Field Name	Details
PromotedEntityId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the KnowledgeArticleVersion that the promoted search term is associated with. The article must be in published status.
Query	Type string Properties Create, Filter, Group, Sort, Update Description The text of the promoted search term. Maximum length: 100 characters. You can associate the same promoted search term with multiple articles. If the user's search matches the promoted term, all associated articles are promoted in search results, ordered by relevancy. For best results, create promoted search terms selectively and limit the number of articles that are promoted per term.

Usage

Use this object to optimize article search results in Salesforce Knowledge.

For example, if an article addresses a common support issue such as login problems, you can associate the terms *password* and *password change*. Article search matches a promoted term whenever all keywords within the term occur within the user's search terms, in any sequence. Each keyword must match exactly. For example:

- The promoted term *password* matches a search for *change password*.
- The promoted term *password change* matches a search for *how do I change my password* but doesn't match *forgot password*.
- The promoted term *password* doesn't match a search for *change passwords*.

Consider these limitations and general limits when you use promoted search terms.

- Your organization can create a maximum of 2,000 promoted terms. For best results, use them selectively, which means create a limited number of promoted terms and a limited number of promoted articles per term.
- If your organization translates articles into multiple languages, each promoted term is associated with one article version and the article version's language. If you need equivalent promoted terms to be associated with each translation, you must specify promoted terms for each translation. For example, associate change password with an English language article version and changer mot de passe with a French language article version.
- The end user's language setting determines the scope of the article search. Search results exclude article versions and any associated promoted terms that are not in the user's language.

SelfServiceUser

Represents a Self-Service user.

 **Note:** Starting with Spring '12, the Self-Service portal isn't available for new organizations. Existing organizations continue to have access to the Self-Service portal.

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>ContactId</code>	Type reference Properties Create, Filter, Group, Sort Description Required. All Self-Service users must be associated with a Contact. The contact's email should match the Self-Service user email. The contact must have a value in the <code>AccountId</code> field or an error occurs.
<code>Email</code>	Type email

Field	Details
	Properties Create, Filter, Group, Sort, Update Description Required. Make this the same as the email address for the Contact associated with this SelfServiceUser. Password resets and other system communication will be sent to this email address.
FirstName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description First name of the Self-Service user.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the Self-Service user is allowed to log in to the Self-Service portal (<code>true</code>) or not (<code>false</code>). Note that there is no way to delete a Self-Service user. They can only be marked as inactive.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
LanguageLocaleKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. This is a restricted picklist field. It is the primary language for the user. All on-screen text in the Self-Service portal is displayed in this language.
LastLoginDate	Type dateTime

Field	Details
	Properties Filter, Nillable, Sort Description The date and time when the Self-Service user last logged in.
LastName	Type string Properties Create, Filter, Group, Sort, Update Description Required. Last name of the Self-Service user.
LocaleSidKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. This is a restricted picklist field. The value of this field affects the formatting and parsing of values, especially numeric values, in the Self-Service portal. Values are two-letter codes that indicate language and sometimes language and country. The codes are based on ISO standards.
Name	Type string Properties Filter, Group, Sort Description Concatenation of <code>FirstName</code> and <code>LastName</code>. Limited to 121 characters.
SuperUser	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this Self-Service user is a super user with additional access on his or her company's Self-Service portal (<code>true</code>) or not (<code>false</code>).
TimeZoneSidKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update

Field	Details
	Description Required. This is a restricted picklist field. The time zone of a affects the offset used when displaying or entering times in the Self-Service portal.
Username	Type string Properties Create, Filter, Group, Sort, Update Description Required. This contains the name that a Self-Service user enters to log into the Self-Service portal. Value must be unique in your organization. If you try to create or update a user with a duplicate value, the operation is rejected and an error is returned.

Usage

For security reasons, you can't query Self-Service user passwords via the API or the user interface. However, the API allows you to set and reset Self-Service user passwords using the `setPassword()` and `resetPassword()` calls.

SelfServiceUser records created from the API don't cause a notification email to be sent. If you want to notify the user, you must send them an email after creating the user.

ServiceChannel

Represents a channel of work items that are received from your organization—for example, cases, chats, or leads. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
CapacityPercentage	Type percent Properties Create, Filter, Nillable, Sort, Update Description The percentage of an agent's capacity for work items that's consumed by a specific type of work item from this service channel.

Field	Details
	For example, you might give phone calls a capacity percentage of <code>100</code>. If an agent receives a phone call, the agent won't receive new work items until the call ends, because at that point the agent's capacity will have reached 100%. This field is available in API version 32.0 and earlier. For later API versions, you can set the capacity percentage of work items on the QueueRoutingConfig object.
CapacityWeight	Type double Properties Create, Filter, Nillable, Sort, Update Description The amount of an agent's capacity for work items that's consumed by a work item from this service channel. For example, if an agent has a capacity of <code>6</code>, and cases are assigned a capacity weight of <code>2</code>, an agent can be assigned up to 3 cases before the agent is at capacity and can't receive new work items. This field is available in API version 32.0 and earlier. For later API versions, you can set the capacity weight of work items on the QueueRoutingConfig object.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the service channel.

Field	Details
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The label of the service channel.
RelatedEntity	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Unique, Update Description The type of object that's associated with this service channel.

ServiceChannelStatus

Represents the status that's associated with a specific service channel. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
ServiceChannelId	Type reference Properties Create, Filter, Group, Sort Description The ID of the service channel.
ServicePresenceStatusId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the presence status that's associated with the service channel that's specified by the <code>ServicePresenceChannelId</code> .

ServiceContract

Represents a customer support contract (business agreement).

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the account associated with the service contract.
ActivationDate	Type dateTime Properties Filter, Nillable, Sort Description The initial day the service contract went into effect (whereas <code>StartDate</code> may include a renewal date).
ApprovalStatus	Type picklist Properties Filter, Group, Nillable, Sort Description Approval status of the service contract.
BillingAddress (beta)	Type address Properties Filter, Nillable Description The compound form of the billing address. Read-only. See Address Compound Fields for details on compound address fields.

Field	Details
BillingCity	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address. Maximum size is 40 characters.
BillingCountry	Type string Properties Filter, Group, Nillable, Sort Description Details for the billing address. Maximum size is 40 characters.
BillingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the service contract's billing address.
BillingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLongitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
BillingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>BillingLatitude</code> to specify the precise geolocation of a billing address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
BillingPostalCode	Type string Properties Filter, Group, Nillable, Sort

Field	Details
	Description Details for the billing address. Maximum size is 20 characters.
BillingState	Type string Properties Group, Sort, Filter, Nillable Description Details for the billing address. Maximum size is 20 characters.
BillingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the service contract's billing address.
BillingStreet	Type textarea Properties Filter, Group, Nillable, Sort Description Street address for the billing address.
ContactId	Type reference Properties Filter, Group, Nillable, Sort Description Required. ID of the Contact associated with the service contract. Must be a valid ID.
ContractNumber	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description Unique number automatically assigned to the service contract.
Description	Type textarea Properties Nillable

Field	Details
	Description Description of the service contract.
Discount	Type percent Properties Filter, Nillable, Sort Description The last day the service contract is in effect. Weighted average of all contract line item discounts on the service contract.
EndDate	Type date Properties Filter, Group, Nillable, Sort Description The last day the service contract is in effect.
GrandTotal	Type currency Properties Filter, Nillable, Sort Description Total price of the service contract plus shipping and taxes.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date

Field	Details
	Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
LineItemCount	Type int Properties Filter, Nillable, Group, Sort Description Number of ContractLineItem records associated with the service contract.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Name of the service contract.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The ID of the user who currently owns the service contract.
Pricebook2Id	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the Pricebook2 associated with the service contract. Must be a valid ID.
ShippingAddress (beta)	Type address Properties Filter, Nillable Description The compound form of the shipping address. Read-only. See Address Compound Fields for details on compound address fields.

Field	Details
ShippingCity	Type string Properties Filter, Group, Nillable, Sort Description Details of the shipping address. Maximum size is 40 characters.
ShippingCountry	Type string Properties Filter, Group, Nillable, Sort Description Details of the shipping address. Country maximum size is 40 characters.
ShippingCountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code for the service contract's shipping address.
ShippingLatitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLongitude</code> to specify the precise geolocation of a shipping address. Acceptable values are numbers between –90 and 90 with up to 15 decimal places.
ShippingLongitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>ShippingLatitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between –180 and 180 with up to 15 decimal places.
ShippingPostalCode	Type string Properties Create, Filter, Nillable, Update

Field	Details
	Description Details of the shipping address. Postal code maximum size is 20 characters.
ShippingState	Type string Properties Create, Filter, Nillable, Update Description Details of the shipping address. State maximum size is 20 characters.
ShippingStateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code for the service contract's shipping address.
ShippingStreet	Type textarea Properties Create, Filter, Nillable, Update Description The street address of the shipping address. Maximum of 255 characters.
SpecialTerms	Type textarea Properties Create, Nillable, Update Description Any terms specifically agreed to and tracked in the service contract.
StartDate	Type date Properties Create, Filter, Nillable, Update Description The first day the service contract is in effect.
Status	Type picklist Properties Filter, Nillable

Field	Details
	Description The status of the service contract, such as Inactive.
Subtotal	Type currency Properties calculated, Filter, Nillable Description Total of the service contract line items (products) before discounts, taxes, and shipping are applied.
Tax	Type currency Properties Create, Filter, Nillable, Update Description Total taxes for the service contract.
Term	Type int Properties Create, Filter, Nillable, Update Description Number of months that the service contract is valid.
TotalPrice	Type currency Properties calculated, Filter, Nillable Description Total of the contract line items (products) after discounts and before taxes and shipping.

Usage

Use this object to query and manage service contracts.

ServiceContractFeed

Represents a single feed item in the feed displayed on the detail page for a service contract record. A service contract feed shows recent changes to a service contract for any fields that are tracked in feeds, as well as comments and posts about the record. It's a useful way to stay up-to-date with changes to service contracts. This object is available in API version 23.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the ServiceContract object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content for the ServiceContractFeed. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection changes a tracked record, the CreatedBy field contains the ID of the system administrator. The ConnectionId contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.

Field Name	Details
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if Type is <code>ContentPost</code>. Setting <code>ContentFileName</code> automatically sets Type to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.

Field Name	Details
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, <code>InsertedById</code> is set to the ID of the logged-in user.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on the feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for the <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Create, Filter, Group, Nillable, Sort

Field Name	Details
	Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the service contract record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing <code>ContentVersion</code> and post it to a feed as a <code>ServiceContractFeed</code> object of <code>Type ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description Title of the <code>ServiceContractFeed</code>. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.

Field Name	Details
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of ServiceContractFeed: • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field.

Field Name	Details
	• <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>. • <code>Visibility</code> can be updated on record posts.

Usage

Use this object to track changes for a service contract record.

ServiceContractHistory

Represents the history of changes to the values in the fields on a ServiceContract (customer support agreement).

Supported Calls

`create()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
Field	Type picklist Properties Filter, Restricted picklist Description The name of the field that was changed.
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
NewValue	Type anyType Properties Nillable Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable

Field	Details
	Description The latest value of the field before it was changed.
ServiceContractId	Type reference Properties Filter Description Required. ID of the ServiceContract.

Usage

Use this object to identify changes to a service contract.

This object respects field level security on the parent object.

ServiceContractOwnerSharingRule

Represents the rules for sharing a ServiceContract (customer service agreement) with users other than the owner.



Note: Contact Salesforce customer support to enable access to this object for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Sort, Update Description A value that represents the type of sharing allowed. The possible values are: • Read • Edit
Description	Type textarea

Field Name	Details
	Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort, Description The ID representing the source group. Service contracts owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label in the user interface.
UserorGroupId	Type reference

Field Name	Details
	Properties Create, Filter
	Description The ID representing the target user or group. Target users or groups are given access.

Usage

Use this object to manage the sharing rules for a service contract. General sharing and territory management-related sharing use this object.

ServiceContractShare

Represents a sharing entry on a ServiceContract (customer support agreement).

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>AccessLevel</code>	Type picklist Properties Create, Filter, Group, Sort, Update Description Level of access that the User or Group has to the ServiceContract. The possible values are: • <code>Read</code> • <code>Edit</code> • <code>All</code> (This value is not valid for create or update calls.) This field must be set to an access level that is higher than the organization's default access level for service contracts.
<code>ParentId</code>	Type reference Properties Create, Filter

Field	Details
	Description ID of the parent object, if any.
RowCause	Type picklist Properties Create, Filter, Defaulted on create, Restricted picklist Description Reason that this sharing entry exists. Values may include: • Manual—The User or Group has access because a user with “All” access manually shared the ServiceContract with them. • Owner—The User is the owner of the ServiceContract or is in a role above the service contract owner in the role hierarchy.
UserOrGroupId	Type reference Properties Create, Filter Description ID of the User or Group that has been given access to the ServiceContract.

Usage

This object allows you to determine which users and groups can view and edit ServiceContract records owned by other users.

If you attempt to create a new record that matches an existing record, the create call updates any modified fields and returns the existing record.

ServicePresenceStatus

Represents a presence status that can be assigned to a service channel. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
DeveloperName	Type string

Field	Details
	Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the presence status.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The label of the presence status.

SetupEntityAccess

Represents the enabled setup entity access settings (such as for Apex classes) for the parent `PermissionSet`. To grant users access to an entity, associate the appropriate `SetupEntityAccess` record with a `PermissionSet` that's assigned to a user. This object is available in API version 25.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ParentId	Type reference Properties Create, Filter, Group, Sort Description The ID of the entity's parent PermissionSet.
SetupEntityId	Type reference Properties Create, Filter, Group, Sort Description The ID of the entity for which access is enabled, such as an Apex class or Visualforce page.
SetupEntityType	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of setup entity for which access is enabled. Valid values are: • <code>ApexClass</code> for Apex classes • <code>ApexPage</code> for Visualforce pages • In API version 28.0 and later, <code>ConnectedApplication</code> for OAuth connected apps • In API version 31.0 and later, <code>CustomPermission</code> for custom permissions • In API version 28.0 and later, <code>ServiceProvider</code> for service providers • In API version 28.0 and later, <code>TabSet</code> for apps

Usage

Because SetupEntityAccess is a child of the PermissionSet object, the usage is similar to other PermissionSet child objects like FieldPermissions and ObjectPermissions.

For example, the following code returns all permission sets that grant access to any setup entities for which access is enabled:

```
SELECT Id, ParentId, Parent.Name, SetupEntityId
FROM SetupEntityAccess
```

The following code returns permission sets that grant access only to Apex classes:

```
SELECT Id, ParentId, Parent.Name, SetupEntityId
FROM SetupEntityAccess
WHERE SetupEntityType='ApexClass'
```

The following code returns permission sets that grant access to any setup entities, and are not owned by a profile:

```
SELECT Id, ParentId, Parent.Name, SetupEntityId
FROM SetupEntityAccess
WHERE ParentId
IN (SELECT Id
    FROM PermissionSet
    WHERE isOwnedByProfile = false)
```

You may want to return only those permission sets that have access to a specific setup entity. To do this, query the parent object. For example, this code returns all permission sets that grant access to the `helloWorld` Apex class:

```
SELECT Id, Name,
    (SELECT Id, Parent.Name, Parent.Profile.Name
     FROM SetupEntityAccessItems)
FROM ApexClass
WHERE Name = 'helloWorld'
```

While it's possible to return permission sets that have access to a `ConnectedApplication`, `ServiceProvider`, or `TabSet` by `SetupEntityId`, it's not possible to return permission sets that have access to these `SetupEntityType` fields by any other `AppMenuItem` attribute, such as `Name` or `Description`. For example, to find out if a user has access to the Recruiting app, you'd run two queries. First, query to get the `AppMenuItem` ID:

```
SELECT Id, Name, Label
FROM AppMenuItem
WHERE Name = 'Recruiting'
```

Let's say the previous query returned the `AppMenuItem` ID `02uD0000000GliMIAW`. Using this ID, you can now run a query to find out if a user has access to the Recruiting app:

```
SELECT Id, SetupEntityId, SetupEntityType
FROM SetupEntityAccess
WHERE ParentId
IN
    (SELECT PermissionSetId
     FROM PermissionSetAssignment
     WHERE AssigneeId = '005D00000001QOzF')
AND (SetupEntityId = '02uD0000000GliMIAW')
```

SignupRequest

Represents a request for a new Trialforce signup. This object is available in API version 27.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`

Fields

Field Name	Details
AuthCode	Type string Properties Create, Filter, Group, Sort Description A one-time authorization code that can be exchanged for an OAuth access token and refresh token using standard Salesforce APIs. It's used in conjunction with <code>ConnectedAppCallbackUrl</code> and <code>ConnectedAppConsumerKey</code>, when the specified connected app hasn't been configured with an X.509 certificate. This is a read-only field provided by the system once the signup request has been processed. This field is available in API version 29.0 and later.
Company	Type string Properties Create, Filter, Group, Sort Description The name of the company requesting the trial signup.
ConnectedAppCallbackUrl	Type string Properties Create, Filter, Group, Sort Description When used in conjunction with <code>ConnectedAppConsumerKey</code>, specifies a connected app that should be approved automatically during the signup creation. This field is available in API version 28.0 and later.
ConnectedAppConsumerKey	Type string Properties Create, Filter, Group, Sort Description When used in conjunction with <code>ConnectedAppCallbackUrl</code>, specifies a connected app that should be approved automatically during the signup creation. This field is available in API version 28.0 and later.
Country	Type string

Field Name	Details
	Properties Create, Filter, Group, Sort Description The two-character, upper-case ISO-3166 country code. You can find a full list of these codes at a number of sites, such as: www.iso.ch/iso/en/prods-services/iso3166ma/02iso-3166-code-lists/list-en1.html. The language of the trial organization is auto-determined based on the value of this field.
CreatedOrgId	Type string Properties Filter, Group, Nillable, Sort Description The 15-character organization ID of the trial organization created. This is a read-only field provided by the system once the signup request has been processed.
CreatedOrgInstance	Type string Properties Filter, Group, Nillable, Sort Description The server instance of the new trial organization, for example, "na8." This field is available in API version 29.0 and later.
ErrorCode	Type string Properties Filter, Group, Nillable, Sort Description The error code if the signup request isn't successful. This is a read-only field provided by the system to be used for support purposes.
FirstName	Type string Properties Create, Filter, Nillable, Sort Description The first name of the admin user for the trial signup.
LastName	Type string

Field Name	Details
	Properties Create, Filter, Group, Sort Description The last name of the admin user for the trial signup.
SignupEmail	Type email Properties Create, Filter, Group, Sort Description The email address of the admin user for the trial signup.
Status	Type picklist Properties Filter, Group, Sort, Update Description The status of the request. Possible values are New, In Progress, Error, or Success. The default value is New.
Subdomain	Type string Properties Create, Filter, Group, Sort Description The subdomain for the new trial organization when it uses a custom My Domain. The maximum length is 33 characters for Developer Edition (DE) and 40 characters for all other editions (because a suffix is appended to all DE organizations).
SuppressSignupEmails	Type boolean Properties Filter, Group, Nillable, Sort Description When set to <code>true</code>, no signup emails are sent when the trial organization is created. This field is used for the Proxy Signup feature, and is available in API version 29.0 and later.
TemplateId	Type string Properties Create, Filter, Group, Sort

Field Name	Details
	Description The 15-character ID of the approved Trialforce template that is the basis for the trial signup. The template is required and must be approved by Salesforce.
TrialDays	Type anyType Properties Create, Defaulted on create, Filter, Group, Sort Description The duration of the trial signup in days. Must be equal to or less than the trial days for the approved Trialforce template. If not provided, it defaults to the trial duration specified for the Trialforce template.
TrialSourceOrgId	Type string Properties Filter, Group, Nillable, Sort Description The 15-character organization ID of the Trialforce Source Organization from which the Trialforce template was created.
Username	Type string Properties Create, Filter, Group, Sort Description The username of the admin user for the trial signup. It must follow the address convention specified in RFC822: www.w3.org/Protocols/rfc822/#z10

Usage

The Java class below uses the REST API to create a SignupRequest object. It authenticates to the Trialforce Management Organization and then posts a request to the SignupRequest object.

Here are the variables you need to specify in this example.

- **SERVER** — The name of the host server for the Trialforce Management Organization (TMO), for example, "na1.salesforce.com."
- **USERNAME** — The admin username for the TMO.
- **PASSWORD** — The concatenation of the admin password and the security token for the TMO. To get an email with the security token, from your personal settings in Salesforce select **Reset My Security Token** and click **Reset Security Token**.
- **CLIENT_ID** — From Setup in Salesforce, click **Create > Apps** and click **New** under Connected Apps. Enter values for the required fields (the Callback URL is required but can initially be set to any valid URL as it's not used), grant full access for the OAuth scopes in the "Selected OAuth Scopes" selector, and click **Save**. Then copy the value of "Consumer Key" and use it for this variable.

- CLIENT_SECRET — On the same page, click **Click to reveal**. Then copy the value of "Consumer Secret" and use it for this variable.

```
public class IsvSignupDriver {
    private static final String SERVER = server_name:port;
    private static final String USERNAME = tmo_username;
    private static final String PASSWORD = tmo_passwordsecurity_token;
    private static final String CLIENT_ID = consumer_key;
    private static final String CLIENT_SECRET = consumer_secret;

    private static SignupRequestInfo signupRequest = null;

    public static String createSignupRequest (SignupRequestInfo sr)
        throws JSONException, IOException {
        JSONObject createResponse = null;
        signupRequest = sr;
        JSONObject loginResponse = login(SERVER, USERNAME, PASSWORD);
        String instanceUrl = loginResponse.getString("instance_url");
        String accessToken = loginResponse.getString("access_token");
        createResponse = create(instanceUrl, accessToken);
        System.out.println("Created SignupRequest object: " + createResponse + "\n");
        return createResponse.toString();
    }

    /* Authenticates to the TMO using the required credentials */

    private static JSONObject login(String server, String username, String password)
        throws ClientProtocolException, IOException, JSONException {
        String authEndPoint = server + "/services/oauth2/token";
        HttpClient httpClient = new DefaultHttpClient();
        try {
            HttpPost post = new HttpPost(authEndPoint);

            List<NameValuePair> params = new ArrayList<NameValuePair>();
            params.add(new BasicNameValuePair("grant_type", "password"));
            params.add(new BasicNameValuePair("client_id", CLIENT_ID));
            params.add(new BasicNameValuePair("client_secret", CLIENT_SECRET));
            params.add(new BasicNameValuePair("username", username));
            params.add(new BasicNameValuePair("password", password));
            post.setEntity(new UrlEncodedFormEntity(params, Consts.UTF_8));

            BasicResponseHandler handler = new BasicResponseHandler();
            String response = httpClient.execute(post, handler);
            return new JSONObject(response);
        } finally {
            httpClient.getConnectionManager().shutdown();
        }
    }

    /* Posts a request to the SignupRequest object */

    private static JSONObject create(String instanceUrl, String accessToken)
        throws ClientProtocolException, IOException, JSONException {
        HttpClient httpClient = new DefaultHttpClient();
        try {
            HttpPost post = new HttpPost(instanceUrl +
```

```

"/services/data/v27.0/objects/SignupRequest/");
post.setHeader("Authorization", "Bearer " + accessToken);
post.setHeader("Content-Type", "application/json");

JSONObject requestBody = new JSONObject();
requestBody.put("TemplateId", signupRequest.getTemplateID());
requestBody.put("SignupEmail", signupRequest.getEmail());
requestBody.put("username", signupRequest.getUsername());
requestBody.put("Country", "US");
requestBody.put("Company", signupRequest.getCompanyName());
requestBody.put("lastName", signupRequest.getLastName());

StringEntity entity = new StringEntity(requestBody.toString());
post.setEntity(entity);
BasicResponseHandler handler = new BasicResponseHandler();
String response = httpClient.execute(post, handler);
return new JSONObject(response);
} finally {
    httpClient.getConnectionManager().shutdown();
}
}
}

```

Error Codes

If the signup fails, the system generates an error code that can help you identify the cause. This table shows the most important error codes.

Error Code	Description
C-1007	Duplicate username.
C-1015	Error while establishing the new organization's My Domain settings. Contact Salesforce support for assistance.
C-1016	Error while configuring the OAuth connected app for Proxy Signup. Verify that your connected app has a valid consumer key, callback URL, and unexpired certificate (if applicable).
C-1018	Invalid subdomain value provided during signup.
C-1019	Subdomain in use. Please choose a new subdomain value.
C-9999	Generic "fatal error." Contact Salesforce support for assistance.
S-1006	Invalid email address (not in a proper email address format).
S-2006	Invalid country code.
T-0001	Template ID not valid (not in the format OTTxxxxxxxxxx).
T-0002	Template not found. Either the template doesn't exist (it may have been deleted), or it doesn't exist at the appropriate version.
T-0003	Template not approved for use by Salesforce.

Site

Represents a public website that is integrated with an Organization. This object is generally available in API version 16.0 and later. To access this object, Force.com Sites or Site.com must be enabled for your organization.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

- Customer Portal users can't access this object.
- To view this object, you must have the "View Setup and Configuration" permission.

Fields

Field	Description
<code>AdminId</code>	Type reference Properties Filter, Group, Sort Description The site administrator designated as the contact for the site. This user receives site-related communications from site visitors and from Salesforce.
<code>AnalyticsTrackingCode</code>	Type string Properties Filter, Group, Nillable, Sort Description The tracking code associated with your site. This code can be used by services like Google Analytics to track page request data for your site.
<code>ClickjackProtectionLevel</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Sets the clickjack protection level. The options are: • <code>AllowAllFraming</code>—Allow framing by any page (no protection) • <code>SameOriginOnly</code>—Allow framing by the same origin only (recommended)

Field	Description
	• NoFraming—Don't allow framing by any page (most protection) This field is available in API version 30.0 and later.
DailyBandwidthLimit	Type int Properties Filter, Group, Nillable, Sort Description The rolling 24-hour daily bandwidth limit for the sites in your organization.
DailyBandwidthUsed	Type double Properties Filter, Group, Nillable, Sort Description The current rolling 24-hour daily bandwidth usage for the sites in your organization.
DailyRequestTimeLimit	Type int Properties Filter, Group, Nillable, Sort Description The rolling 24-hour daily service request time limit for the sites in your organization. Service request time is calculated as the total server time in minutes required to generate pages for the site.
DailyRequestTimeUsed	Type int Properties Filter, Group, Nillable, Sort Description The current rolling 24-hour daily service request time for the sites in your organization.
Description	Type textarea Properties Filter, Nillable, Sort Description An optional description of the site.

Field	Description
GuestUserId	Type reference Properties Filter, Group, Nillable, Sort Description The site or Salesforce Communities specific user that anonymous, unauthenticated users run as when interacting with the site.
MasterLabel	Type string Properties Filter, Group, Sort Description The name of the site as it appears in the user interface.
MonthlyPageViewsEntitlement	Type int Properties Filter, Group, Nillable, Sort Description The number of page views allowed for the current calendar month for the sites in your organization.
Name	Type string Properties Filter, Group, Sort Description The name used when referencing the site in the API.
OptionsAllowHomePage	Type boolean Properties Filter Description The option to enable the standard page associated with the Home tab (/home/home.jsp).
OptionsAllowStandardAnswersPages	Type boolean Properties Filter

Field	Description
	Description The option to enable standard pages associated with an answers community. If you want to use default Answers pages (such as AnswersHome), enable these pages.
OptionsAllowStandardIdeasPages	Type boolean Properties Filter Description The option to enable standard pages associated with an Ideas community. If you want to use default Ideas pages (such as IdeasHome), enable these pages.
OptionsAllowStandardLookups	Type boolean Properties Filter Description The option to enable the standard lookup pages. These are the popup windows associated with lookup fields on Visualforce pages.
OptionsAllowStandardSearch	Type boolean Properties Filter Description The option to enable the standard search pages. To allow public users to perform standard searches, enable these pages.
OptionsEnableFeeds	Type boolean Properties Filter Description The option that displays the Syndication Feeds related list, where you can create and manage syndication feeds for users on your public sites. This field is visible only if you have the feature enabled for your organization.
OptionsRequireHttps	Type boolean Properties Filter

Field	Description
	Description When true, the site requires secure connections. When false, the site operates normally via insecure connections instead of redirecting to a secure connection.
SiteType	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Identifies whether the site is a Visualforce (Force.com Sites) or a Site.com site. <code>SiteType</code> is available in API version 21.0 and later. In API version 26.0 and later, if Salesforce Communities is enabled for your organization, the site could also be a Network Visualforce or Network Site.com site.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The status for the site. For example, <code>Active</code> or <code>In Maintenance</code> .
Subdomain	Type string Properties Filter, Group, Nillable, Sort Description The Force.com domain that you registered for your site. For example, if your Force.com domain is <code>mycompany.force.com</code> , then <code>mycompany</code> is the subdomain.
TopLevelDomain	Type url Properties Filter, Nillable Description The optional branded custom Web address that you registered with a third-party domain name registrar. The custom Web address acts as an alias to your Force.com address. Beginning with API version 21.0, <code>TopLevelDomain</code> is no longer available. Instead, use the Domain and DomainSite objects.

Field	Description
UrlPathPrefix	Type string Properties Filter, Group, Nillable, Sort Description The unique Force.com URL that the public uses to access this site.

Usage

Use this read-only object to query or retrieve information on your Force.com site.

SiteDomain

SiteDomain is a read-only object, and a one-to-many replacement for the Site.TopLevelDomain field. This object is available in API version 21.0, and has been deprecated as of API version 26.0. In API version 26.0 and later, use the [Domain](#) and [DomainSite](#) objects instead.

To access this object, Force.com Sites or Site.com must be enabled for your organization.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

- Customer Portal users can't access this object.
- To view this object, you must have the "View Setup and Configuration" permission.

Fields

Field	Description
Domain	Type url Properties Filter, Sort Description The branded custom Web address within the global namespace identified by this domain's type. In the Domain Name System (DNS) global namespace, this field is the custom Web address that you registered with a third-party domain name registrar. The custom Web address can be used to access the site of this domain.

Field	Description
SiteId	Type reference Properties Filter, Group, Sort Description The ID of the associated Site.
DomainType	Type picklist Properties Filter, Group, Sort, Nillable Description The global namespace that this custom Web address belongs to. This value is set to DNS for custom Web addresses in the global DNS. This field is available in version 24.0 of the API.

Usage

Use this read-only object to query the custom Web addresses that are associated with each website in your organization.

SiteHistory

Represents the history of changes to the values in the fields of a site. This object is generally available in API version 18.0 and later. To access this object, Force.com Sites must be enabled for your organization.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

- Customer Portal users can't access this object.
- To view this object, you must have the "View Setup and Configuration" permission.

Fields

Field	Details
Field	Type picklist

Field	Details
	Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The last value of the field before it was changed.
SiteId	Type reference Properties Filter, Group, Sort Description The ID of the associated Site.

Skill

Represents a category or group that Live Agent users can be assigned to. This object is available in API version 24.0 and later.



Note: For information about Work.com skills on a user's profile, see the [ProfileSkill](#) topic.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the skill.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The name of the skill.

Usage

Use this object to assign Live Agent users to groups based on their abilities. The skills associated with a LiveChatButton determine which agents receive chat requests that come in through that button.

SkillProfile

Represents a join between Skill and Profile. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
ProfileId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the profile.
SkillId	Type reference Properties Create, Filter, Group, Sort Description The ID of the skill.

Usage

Use this object to assign specific skills to specific profiles.

SkillUser

Represents a join between Skill and User. This object is available in API version 24.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
SkillId	Type reference Properties Create, Filter, Group, Sort

Field Name	Details
	Description The ID of the skill.
UserId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the user.

Usage

Use this object to assign specific skills to specific users.

SlaProcess

Represents an entitlement process associated with an Entitlement. An entitlement process is a timeline that includes all the steps (MilestoneType records) that your support team must complete to resolve cases. Each process includes the logic necessary to determine how to enforce the correct service level for your customers.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
BusinessHoursId	Type reference Properties Filter, Group, Nillable, Sort Description Required. ID of the BusinessHours associated with the entitlement. Must be a valid business hours ID.

Field	Details
Description	Type textarea Properties Filter, Nillable Description A description of the entitlement process.
IsActive	Type boolean Properties Defaulted on create, Filter Description Indicates whether the entitlement process is active (<code>true</code>) or not (<code>false</code>).
IsVersionDefault	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the entitlement process is the default version (<code>true</code>) or not (<code>false</code>). This field is available in API version 28.0 and later in organizations that have entitlement versioning enabled.
Name	Type string Properties Filter, idLookup Description The name of the entitlement process.
NameNorm	Type string Properties Filter, Group, Sort Description The read-only value for the unique name of the entitlement process or the entitlement process version. If entitlement versioning is enabled, this value is automatically generated for each version of an entitlement process in this form: <i>process name+_v + x</i>, where <i>x</i> is the version number (for example, "gold_support_v2"). If entitlement versioning isn't enabled, this value is the same as <code>Name</code>.

Field	Details
	This field is available in API version 28.0 and later.
StartDateField	Type picklist Properties Filter, Restricted picklist Description The criteria for cases to enter the entitlement process. Cases can enter the process based on: • The creation date on a case • A custom date/time field on a case
VersionMaster	Type string Properties Filter, Group, Nillable, Sort Description Identifies the sequence of versions to which this entitlement process belongs. This field's contents can be any value as long as it is identical among all versions of the entitlement process. This field is available in API version 28.0 and later in organizations that have entitlement versioning enabled.
VersionNotes	Type textarea Properties Filter, Group, Nillable, Sort Description The description of the entitlement process version. This field is available in API version 28.0 and later in organizations that have entitlement versioning enabled.
VersionNumber	Type int Properties Filter, Group, Nillable, Sort Description The version number of the entitlement process. Must be 1 or greater. This field is available in API version 28.0 and later in organizations that have entitlement versioning enabled.

Usage

Use this object to query entitlement processes on entitlements.

Solution

Represents a detailed description of a customer issue and the resolution of that issue.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
<code>IsDeleted</code>	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
<code>IsHtml</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the Solution is an HTML solution (<code>true</code>) or not (<code>false</code>).
<code>IsOutOfDate</code>	Type boolean Properties Defaulted on create, Filter Description Read-only field that indicates whether a solution master has been updated since the translated version was created (<code>true</code>) or not (<code>false</code>). Note that this field does not appear in the page layout of master solutions.
<code>IsPublished</code>	Type boolean

Field	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the Solution has been published (<code>true</code>) or not (<code>false</code>). A solution's published state does not affect how it can be used, or whether you can query, update, or delete it. Label is Public.  Note: Prior to Spring '14, the label was Visible in Self-Service Portal.
<code>IsPublishedInPublicKb</code>	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the Solution has been published as a Public Solution (<code>true</code>) or not (<code>false</code>). Label is Visible in Public Knowledge Base. This field only applies to solutions, not articles in the public knowledge base.
<code>IsReviewed</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the Solution has been reviewed (<code>true</code>) or not (<code>false</code>). This flag can only be set indirectly via the <code>Status</code> picklist. Each predefined <code>Status</code> value implies an <code>IsReviewed</code> value. Label is Reviewed.
<code>LastReferencedDate</code>	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
<code>LastViewedDate</code>	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.

Field	Details
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the User who owns the Solution.
ParentId	Type reference Properties Create, Defaulted on create, Filter, Update Description ID of the master solution, if this is the translation of a master solution.
RecordTypeId	Type reference Properties Create, Filter, Nillable, Update Description ID of the RecordType to which the Solution is associated.
SolutionLanguage	Type picklist Properties Create, Filter, Restricted picklist, Update Description The language that the solution is written in, such as <code>French</code> or <code>Chinese (Traditional)</code>.
SolutionName	Type string Properties Create, Filter, Group, Sort, Update Description Required. If a client application creates a new Solution and a value for this field is unspecified, a hyphen (-), the default value for this field, is used. Limit: 255 characters. Label is Title.
SolutionNote	Type textarea Properties Create, Nillable, Update

Field	Details
	Description The details of the Solution record. Limit: 32,000 characters. Label is Solution Details.  Note: If you have HTML Solutions enabled, any HTML tags used in this field are verified before the object is created or updated. If invalid HTML is entered, an error is thrown. Any JavaScript used in this field is removed before the object is created or updated.
SolutionNumber	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description An identifying number that is assigned automatically when a solution is created. It can't be set directly, and it can't be modified.
Status	Type picklist Properties Create, Filter, Group, Sort, Update Description Required. The status of the solution. Directly controls the <code>IsReviewed</code> value. To obtain the status values in the picklist, a client application can query the <code>SolutionStatus</code>.
TimesUsed	Type int Properties Filter, Group, Sort Description Number of times this solution has been used. Label is Num Related Case.

Usage

Use this object to manage your organization's solutions. Client applications can create, update, delete, and query Attachment records associated with a solution.

SolutionFeed

Represents a single feed item in the feed displayed on the detail page for a solution record. A solution feed shows recent changes to a solution record for any fields that are tracked in feeds, as well as comments and posts about the record. It is a useful way to stay up-to-date with changes to solutions. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the Solution object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the SolutionFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedComments</code> associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a <code>PartnerNetworkConnection</code> changes a tracked record, the <code>CreatedBy</code> field contains the ID of the system administrator. The <code>ConnectionId</code> contains the ID of the <code>PartnerNetworkConnection</code> that made the change. Available if Salesforce to Salesforce is enabled for your organization.

Field Name	Details
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.

Field Name	Details
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. Use FeedItem instead. The ID of the associated FeedPost. A FeedPost represents the following types of changes in a SolutionFeed: status updates, changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description The ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into the feed, <code>InsertedById</code> is set to the ID of the logged-in user.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on the feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for the <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.

Field Name	Details
LinkUrl	Type url Properties Nillable, Sort Description The URL of the <code>LinkPost</code>.
NetworkScope	Type picklist Properties Create, Filter, Group, Nillable, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the solution record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort

Field Name	Details
	Description ID of the <code>ContentVersion</code> article associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing <code>ContentVersion</code> and post it to a feed as a <code>SolutionFeed</code> object of <code>Type</code> <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the <code>SolutionFeed</code>. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL, and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of <code>SolutionFeed</code> item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a <code>Task</code> associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a <code>Task</code> or <code>Event</code> associated with a case record (excluding email and call logging). For a recurring <code>Task</code> with <code>CaseFeed</code> disabled, one event is generated for the series only. For a recurring <code>Task</code> with <code>CaseFeed</code> enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher.

Field Name	Details
	• <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.
Visibility	Type picklist Properties Create, Filter, Group, Nillable, Sort

Field Name	Details
	Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>. • <code>Visibility</code> can be updated on record posts.

Usage

Use this object to track changes for a solution record.

SolutionHistory

Represents the history of changes to the values in the fields of a solution.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
<code>Field</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed. Label is Custom Field Definition ID.

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed. Limited to 255 characters.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed. Limited to 255 characters.
SolutionId	Type reference Properties Filter, Group, Sort Description ID of the Solution. Label is Solution ID.

Usage

Use this read-only object to identify changes to a solution.

This object respects field-level security on the parent object.

SolutionStatus

Represents the status of a Solution, such as Draft, Reviewed, and so on.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
IsDefault	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this is the default solution status value (<code>true</code>) or not (<code>false</code>) in the picklist. Only one value can be the default value.
IsReviewed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this solution status value represents a reviewed Solution (<code>true</code>) or not (<code>false</code>). Multiple solution status values can represent a reviewed Solution.
MasterLabel	Type string Properties Filter, Group, Nillable, Sort Description Master label for this solution status value. This display value is the internal label that does not get translated.
SortOrder	Type int Properties Filter, Group, Nillable, Sort Description Number used to sort this value in the solution status picklist. These numbers are not guaranteed to be sequential, as some previous solution status values might have been deleted.

Usage

This object represents a value in the solution status picklist. The solution status picklist provides additional information about the status of a Solution, such as whether a given status value represents a reviewed or unreviewed solution. Your client application can query this object to retrieve the set of values in the solution status picklist, and then use that information while processing Solution objects to determine more information about a given solution. For example, the application could test whether a given case has been reviewed or not based on its `Status` value and the value of the `IsReviewed` property in the associated SolutionStatus record.

SolutionTag

Associates a word or short phrase with a Solution.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ItemId	Type reference Properties Create, Filter Description ID of the tagged item.
Name	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • <code>Public</code>—The tag can be viewed and manipulated by all users in an organization.

Field Name	Details
	Personal—The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

`SolutionTag` stores the relationship between its parent `TagDefinition` and the `Solution` being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent `TagDefinition` will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a `TagDefinition` sends it to the Recycle Bin, along with any associated tag entries.

SOSDeployment

Represents the general settings for deploying SOS video call capability in a native mobile application. This object is available in API version 34.0 and later.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>DeveloperName</code>	Type string Properties Create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
<code>Language</code>	Type picklist

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the deployment.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description The name of the deployment.
OptionsIsBackwardFacingCameraEnabled	Type boolean Properties Create, Filter, Update Description Determines whether customers can use the backwards-facing camera on their mobile devices to talk to SOS agents.
OptionsIsEnabled	Type boolean Properties Create, Filter, Update Description Determines whether the deployment is enabled for customers to request new SOS video calls.
OptionsIsVoiceOnlyMode	Type boolean Properties Create, Filter, Update Description Determines whether video functionality is disabled for customers, making it so customers can only talk to SOS agents using only audio.
QueueId	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the queue that's associated with the SOS deployment.

Usage

Use this object to query and manage SOS deployments.

SOSSession

This object is automatically created for each SOS session and stores information about the session. This object is available in API versions 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
AppVersion	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The version of the customer's mobile application in which SOS is implemented.
CaseId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the case that's associated with the SOS session.
ContactId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the contact that's associated with the SOS session.
DeploymentId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The ID of the SOS deployment that the SOS session originated from.
EndTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The time that the SOS session ended.
IpAddress	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The IP address from which the customer's SOS call originated.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time that the session record was last referenced by a user.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time that the session record was last viewed.
Name	Type string Properties Autonumber, Defaulted on create, Filter, Sort Description The name of the session.
OpentokSession	Type encryptedstring Properties Create, Nillable, Update

Field Name	Details
	Description The ID of the OpenTok session that's associated with the SOS video call.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The ID of the session record's owner.
SessionDuration	Type int Properties Filter, Group, Nillable, Sort Description The amount of time that the SOS session lasted.
SessionRecordingUrl	Type url Properties Create, Filter, Group, Nillable, Sort, Update Description The URL where the SOS session recording is stored.
SosVersion	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The version of SOS that was used in your organization's mobile application when this session occurred.
StartTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The time that the SOS session began.
SystemInfo	Type string

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description Information about the customer's mobile device from which the SOS call originated, such as the device's operating system.
WaitDuration	Type int Properties Filter, Group, Nillable, Sort Description The amount of time the customer waited before an agent accepted the SOS session and the call began.

Usage

Use this object to query and manage SOS session records.

SOSSessionActivity

Captures information about specific events that occur during an SOS video call, such as when an SOS call begins or ends. This object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
ActivityTime	Type dateTime Properties Create, Filter, Sort Description The time at which the activity occurred.
Name	Type string

Field Name	Details
	Properties Autonumber, Defaulted on create, idLookup, Filter, Sort Description The name of the activity.
SessionId	Type reference Properties Create, Filter, Group, Sort Description The ID of the SOS session that's associated with the event.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description The kind of activity that occurred.

Usage

Use this object to query and manage SOS session activities.

SOSSessionHistory

This object is automatically created for each SOS session and stores information about changes made to the session. This object is available in API versions 34.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field Name	Details
	Description The name of the field that was changed in a session record.
newValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
oldValue	Type anyType Properties Nillable, Sort Description The original value of the field that was changed.
SOSSessionId	Type reference Properties Filter, Group, Sort Description ID of the session record that was changed.

Usage

Use this object to identify changes to SOS session records.

SOSSessionOwnerSharingRule

Represents the rules for sharing an SOS session record with users other than the record owner. This object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Determines the level of access users have to session records. Specifies whether or not users can read, edit, or transfer session records. Corresponds to the <code>Default Access</code> column in the UI.
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum length is 1000 characters.
DeveloperName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to <code>Rule Name</code> in the UI.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID that represents the source group. Session records that are owned by users in the source group trigger the rule to give access.

Field Name	Details
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label in the UI.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID that represents the User or Group that you are granting access to.

Usage

Use this object to manage the sharing rules for SOS session records.

SOSSessionShare

Represents a sharing entry on an SOS session. This object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Level of access that the User or Group has to the SOSSession. The possible values are: • Read • Edit

Field Name	Details
	• <code>All</code> (This value is not valid for <code>create()</code> or <code>update()</code> calls.) This field must be set to an access level that is higher than the organization's default access level for live chat transcripts.
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the parent object, if any.
<code>RowCause</code>	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description Reason that this sharing entry exists. Values can include: • <code>Manual</code>—The user or group has access because a user with “All” access manually shared the <code>SOSSession</code> with them. • <code>Owner</code>—The user is the owner of the <code>SOSSession</code> or is in a role above the <code>SOSSession</code> owner in the role hierarchy.
<code>UserOrGroupId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that has been given access to the <code>SOSSession</code>.

Usage

This object lets you determine which users and groups can view and edit `SOSSession` records that are owned by other users.

If you attempt to create a new record that matches an existing record, the `create()` call updates any modified fields and returns the existing record.

StaticResource

Represents a static resource that can be used in Visualforce markup.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Fields

Field	Details
Body	Type base64 Properties Create, Nillable, Update Description Required. Encoded file data.
BodyLength	Type int Properties Filter, Group, Sort Description Size of the file (in bytes).
CacheControl	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The sharing policy for the static resource when cached. The cache control can have one of the following values: • <i>Private</i> specifies that the static resource data cached on the Salesforce server shouldn't be shared with other users. The static resource is only stored in cache for the current user's session. • <i>Public</i> specifies that the static resource data cached on the Salesforce server be shared with other users in your organization for faster load times.
ContentType	Type string Properties Create, Filter, Group, Sort, Update Description Type of content. Label is Mime Type. Limit: 120 characters.

Field	Details
Description	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description Text description of the static resource. Limit: 255 characters.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of the static resource.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, NamespacePrefix is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.

Usage

Use static resources to upload content that you can reference in Visualforce markup, including archives (such as .zip and .jar files), images, stylesheets, JavaScript, and other files. Using a static resource is preferable to uploading a file to the Documents tab because:

- You can package a collection of related files into a directory hierarchy and upload that hierarchy as a .zip or .jar archive.

- You can reference a static resource in page markup by name using the `$Resource` global variable instead of hard-coding document IDs.

Encoded Data

The API sends and receives the binary file data encoded as a base64 data type. Prior to creating a record, clients must encode the binary file data as base64. Upon receiving an API response, clients must decode the base64 data to binary (this conversion is usually handled for you by the SOAP client).

Maximum Static Resource Size

You can create or update static resources to a maximum size of 5 MB. An organization can have up to 250 MB of static resources, total.

StreamingChannel

Represents a channel that is the basis for notifying listeners of generic Streaming API events. This is available from API version 29.0 or later.

Supported Calls

REST: DELETE, GET, PATCH, POST (query requests are specified in the URI)

SOAP: `create()`, `delete()`, `describe()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`

Special Access Rules

- This object is only available if Streaming API is enabled for your organization.
- Only users with “Create” permission can create this record. Users with “View All Data” can view StreamingChannel records and see streaming messages.
- You can apply user sharing to StreamingChannel. You can restrict access to receiving or sending events on a channel by sharing channels with specific users or groups. Channels shared with public read only or read-write access will only send events to clients subscribed to the channel that also are using a user session associated with the set of shared users or groups. Only users with read-write access to a shared channel can generate events on the channel, or modify the actual StreamingChannel record.

Fields

Field	Field Type	Description
Description	string	Description of the StreamingChannel. Limit: 255 characters. Field Properties: Create, Filter, Group, Nillable, Sort, Update Label: Description
ID	ID	System field: Globally unique string that identifies a StreamingChannel record. Field Properties: Default on create, Filter, Group, idLookup, Sort

Field	Field Type	Description
IsDeleted	boolean	System field: Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Field Properties: Default on create, Filter, Group, Sort
IsDynamic	boolean	<code>true</code> if the channel gets dynamically created on subscribe if necessary, <code>false</code> otherwise. To enable dynamic streaming channels in your organization, from Setup, go to Customize > User Interface and enable Enable Dynamic Streaming Channel Creation . Field Properties: Default on create, Filter, Group, Sort
LastReferencedDate	date	The timestamp for when the current user last viewed a record related to this record. Field Properties: Filter, Sort
LastViewedDate	date	The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed. Field Properties: Filter, Sort
Name	string	Required. Descriptive name of the StreamingChannel. Limit: 80 characters, alphanumeric and “_”, “/” characters only. Must start with “/u/”. This value identifies the channel. Field Properties: Create, Filter, Group, idLookup, Sort, Update Label: Streaming Channel Name
OwnerId	reference	The ID of the owner of the StreamingChannel. Field Properties: Create, Default on create, Filter, Group, Sort, Update Label: Owner Name

TagDefinition

Defines the attributes of child Tag objects.

Supported Calls

`delete()`, `describeSObjects()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`

Fields

Field	Detail
Name	Type string

Field	Detail
	Properties Filter, Nillable, Update Description Identifies the tag word or phrase.
Type	Type picklist Properties Filter, Nillable, Restricted picklist Description Defines the visibility of a tag. Possible value are: • Public: The tag can be viewed and manipulated between all users in an organization. • Personal: The tag can be viewed or manipulated only by a user with a matching <code>OwnerId</code>.

Usage

When you create a tag for a record, an association is created with to a corresponding TagDefinition:

- If the value in the tag's `Name` field is new, a new TagDefinition record is automatically created and becomes the parent of the tag.
- If the value in the tag's `Name` field already exists in a TagDefinition, that TagDefinition automatically becomes the parent of the tag.

Each TagDefinition record has a one-to-many relationship with its child tag records.

The following standard objects represent tags for records:

- AccountTag
- AssetTag
- CampaignTag
- CaseTag
- ContactTag
- ContractTag
- DocumentTag
- EventTag
- LeadTag
- NoteTag
- OpportunityTag
- SolutionTag
- TaskTag

Custom objects may also be tagged. Tags for custom objects are identified by a suffix of two underscores immediately followed by the word `tag`. For example, a custom object named `Meeting` has a corresponding tag named `Meeting__tag` in that organization's WSDL. `Meeting__tag` is only valid for `Meeting` objects.

TagDefinition is useful for mass operations on any tag record. For instance, if you want to rename existing tags, you can search for the appropriate TagDefinition object, update it, and the child tag's Name values are also changed. The following Java example replaces all WC tags with the phrase West Coast:

```
public void tagDefinitionSample() {
    String soqlQuery = "SELECT Id, Name FROM TagDefinition " +
        "WHERE Name = 'WC'";
    QueryResult qResult = null;
    try {
        qResult = connection.query(soqlQuery);
        TagDefinition tagDef = (TagDefinition) qResult.getRecords()[0];
        tagDef.setName("West Coast");
        connection.update(new SObject[]{tagDef});
    } catch (ConnectionException ce) {
        ce.printStackTrace();
    }
}
```

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

Task

Represents a business activity such as making a phone call or other to-do items. In the user interface, Task and Event records are collectively referred to as activities.

 **Note:** Task fields related to calls are exclusive to Salesforce CRM Call Center. Additionally, query(), delete(), and update() aren't allowed with tasks related to more than one contact in API versions 23.0 and earlier.

Supported Calls

create(), delete(), describeLayout(), describeSObjects(), getDeleted(), getUpdated(), query(), retrieve(), search(), undelete(), update(), upsert()

Fields

Field	Field Type
AccountId	Type reference Properties Group, Sort, Filter, Nillable Description Represents the ID of the related Account. The AccountId is determined as follows. If the value of whatId is any of the following objects, then Salesforce uses that object's AccountId. - Account - Opportunity

Field	Field Type
	- Contract - Custom object that is a child of Account If the value of the <code>whatId</code> field is any other object, and the value of the <code>whoId</code> field is a Contact object, then Salesforce uses that contact's <code>AccountId</code>. (If your organization uses Shared Activities, then Salesforce uses the <code>AccountId</code> of the primary contact.) Otherwise, Salesforce sets the value of the <code>AccountId</code> field to <code>null</code>. For information on IDs, see ID Field Type.
ActivityDate	Type date Properties Group, Sort, Create, Filter, Nillable, Update Description Represents the due date of the task. This field has a timestamp that is always set to midnight in the Coordinated Universal Time (UTC) time zone. The timestamp is not relevant; do not attempt to alter it in order to accommodate time zone differences. Label is Due Date.  Note: This field can't be set or updated for a recurring task (<code>IsRecurrence</code> is <code>true</code>).
CallDisposition	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Represents the result of a given call, for example, "we'll call back," or "call unsuccessful." Limit is 255 characters. Not subject to field-level security, available for any user in an organization with Salesforce CRM Call Center.
CallDurationInSeconds	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Duration of the call in seconds. Not subject to field-level security, available for any user in an organization with Salesforce CRM Call Center.
CallObject	Type string

Field	Field Type
	Properties Create, Filter, Group, Nillable, Sort, Update Description Name of a call center. Limit is 255 characters. Not subject to field-level security, available for any user in an organization with Salesforce CRM Call Center.
CallType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The type of call being answered: Inbound, Internal, or Outbound.
ConnectionReceivedId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that shared this record with your organization. This field is only available if you have enabled Salesforce to Salesforce.
ConnectionSentId	Type reference Properties Filter, Nillable Description ID of the PartnerNetworkConnection that you shared this record with. This field is only available if you have enabled Salesforce to Salesforce. Beginning with API version 15.0, the <code>ConnectionSentId</code> field is no longer supported. The <code>ConnectionSentId</code> field is still visible, but the value is null. You can use the new <code>PartnerNetworkRecordConnection</code> object to forward records to connections.
Description	Type textarea Properties Create, Nillable, Update Description Contains a text description of the task.

Field	Field Type
IsArchived	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the event has been archived.
IsClosed	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the task has been completed (<code>true</code>) or not (<code>false</code>). Is only set indirectly via the <code>Status</code> picklist. Label is Closed.
IsHighPriority	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates a high-priority task. This field is derived from the <code>Priority</code> field.
IsRecurrence	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort Description Indicates whether the task is scheduled to repeat itself (<code>true</code>) or only occurs once (<code>false</code>). This is a read-only field on update, but not on create. If this field value is <code>true</code>, then <code>RecurrenceStartDateOnly</code>, <code>RecurrenceEndDateOnly</code>, <code>RecurrenceType</code>, and any recurrence fields associated with the given recurrence type must be populated. See Recurring Tasks.
IsReminderSet	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether a popup reminder has been set for the task (<code>true</code>) or not (<code>false</code>).
IsVisibleInSelfService	Type boolean

Field	Field Type
	Properties Defaulted on create, Filter, Update Description Indicates whether a task associated with an object can be viewed in the Customer Portal (<code>true</code>) or not (<code>false</code>). If your organization has enabled Communities, tasks marked <code>IsVisibleInSelfService</code> are visible to any external user in the community, as long as the user has access to the record the task was created on. This field is available when Customer Portal or partner portal are enabled OR Communities is enabled and you have Customer Portal or partner portal licenses.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the User who owns the record. Label is Assigned To ID.
Priority	Type picklist Properties Group, Sort, Create, Filter, Update Description Required. Indicates the importance or urgency of a task, such as high or low.
RecurrenceActivityId	Type reference Properties Filter, Group, Nillable, Sort Description Read-only. Not required on create. ID of the main record of the recurring task. Subsequent occurrences have the same value in this field.
RecurrenceDayOfMonth	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The day of the month in which the task repeats.
RecurrenceDayOfWeekMask	Type int

Field	Field Type
	Properties Create, Filter, Group, Nillable, Sort, Update Description The day or days of the week on which the task repeats. This field contains a bitmask. The values are as follows: • Sunday = 1 • Monday = 2 • Tuesday = 4 • Wednesday = 8 • Thursday = 16 • Friday = 32 • Saturday = 64 Multiple days are represented as the sum of their numerical values. For example, Tuesday and Thursday = 4 + 16 = 20.
RecurrenceEndDateOnly	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The last date on which the task repeats.
RecurrenceInstance	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The frequency of the recurring task. For example, "2nd" or "3rd."
RecurrenceInterval	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The interval between recurring tasks.
RecurrenceMonthOfYear	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field	Field Type
	Description The month of the year in which the task repeats.
RecurrenceRegeneratedType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Represents what triggers a repeating task to repeat. Add this field to a page layout together with the <code>RecurrenceInterval</code> field, which determines the number of days between the triggering date (due date or close date) and the due date of the next repeating task in the series. Label is Repeat This Task . This field has the following picklist values: • None: The task doesn't repeat. • After due date: The next repeating task will be due the specified number of days after the current task's due date. • After the task is closed: The next repeating task will be due the specified number of days after the current task is closed. • (Task closed): This task, now closed, was opened as part of a repeating series.
RecurrenceStartDateOnly	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The date when the recurring task begins. Must be a date and time before <code>RecurrenceEndDateOnly</code> .
RecurrenceTimeZoneSidKey	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The time zone associated with the recurring task. For example, "UTC-8:00" for Pacific Standard Time.
RecurrenceType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field	Field Type
	Description Indicates how often the task repeats. For example, daily, weekly, or every nth month (where “nth” is defined in <code>RecurrenceInstance</code>).
ReminderDateTime	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description Represents the time when the reminder is scheduled to fire, if <code>IsReminderSet</code> is set to <code>true</code> . If <code>IsReminderSet</code> is set to <code>false</code> , then the user may have deselected the reminder checkbox in the Salesforce user interface, or the reminder has already fired at the time indicated by the value.
Status	Type picklist Properties Create, Filter, Group, Sort, Update Description Required. The current status of the task, such as In Progress or Completed. Each predefined <code>Status</code> field implies a value for the <code>IsClosed</code> flag. To obtain picklist values, query the <code>TaskStatus</code> object.  Note: This field can't be updated for recurring tasks (<code>IsRecurrence</code> is <code>true</code>).
Subject	Type combobox Properties Create, Filter, Nillable, Sort, Update Description The subject line of the task, such as “Call” or “Send Quote.” Limit: 255 characters.
TaskWhoIds	Type JunctionIdList Properties Create, Update Description A string array of contact or lead IDs related to this task. This <code>JunctionIdList</code> field is linked to the <code>TaskWhoRelations</code> child relationship. <code>TaskWhoIds</code> is only available when the shared activities setting is enabled. The first contact or lead ID in the list becomes the primary <code>whoId</code> if you don't specify a primary <code>whoId</code> .

Field	Field Type
	 Warning: Adding a <code>JunctionIdList</code> field name to the <code>fieldsToNull</code> property deletes all related junction records. This action can't be undone.
Type	Type picklist Properties Create, Filter, Nillable, Update Description The type of task, such as Call or Meeting.
WhatCount	Type int Properties Filter, Group, Nillable, Sort Description Available to organizations that have Shared Activities enabled. Count of related TaskRelations pertaining to <code>WhatId</code> . Count of the <code>WhatId</code> must be 1 or less.
WhatId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The <code>WhatId</code> represents nonhuman objects such as accounts, opportunities, campaigns, cases, or custom objects. <code>WhatIds</code> are polymorphic. Polymorphic means a <code>WhatId</code> is equivalent to the ID of a related object. The label is <code>Related To ID</code> .
WhoCount	Type int Properties Filter, Group, Nillable, Sort Description Available to organizations that have Shared Activities enabled. Count of related TaskRelations pertaining to <code>WhoId</code> .
WhoId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field	Field Type
	Description The Whold represents a human such as a lead or a contact. Wholds are polymorphic. Polymorphic means a Whold is equivalent to a contact's ID or a lead's ID. The label is Name ID. If Shared Activities is enabled, the value of this field is the ID of the related lead or primary contact. If you add, update, or remove the Whold field, you might encounter problems with triggers, workflows, and data validation rules that are associated with the record. The label is Name ID.

Usage

Recurring Tasks

- Recurring tasks are available in API version 16.0 and later.
- After a task is created, it can't be changed from recurring to nonrecurring or vice versa.
- When you delete a recurring task series through the API, all open and closed task occurrences in the series are removed. However, when you delete a recurring task series through the user interface, only open tasks occurrences (`IsClosed` is `false`) in the series are removed.
- If `IsRecurrence` is `true`, then `RecurrenceStartDateOnly`, `RecurrenceEndDateOnly`, `RecurrenceType`, and any properties associated with the given recurrence type (see the following table) must be populated.
- When you change the `RecurrenceStartDateOnly` field or the recurrence pattern, all open tasks occurrences in the series are deleted and new open task occurrences are created based on the new recurrence pattern. The recurrence pattern is determined by the following fields: `RecurrenceType`, `RecurrenceTimeZoneSidKey`, `RecurrenceInterval`, `RecurrenceDayOfWeekMask`, `RecurrenceDayOfMonth`, `RecurrenceInstance`, and `RecurrenceMonthOfYear`.
- When you change the value of `RecurrenceEndDateOnly` to an earlier date (for example, from January 20th to January 10th), all open task occurrences in the series with the `ActivityDate` value greater than the new end date value are deleted. Other open and closed task occurrences in the series are not affected.
- When you change the value of `RecurrenceEndDateOnly` to a later date (for example, from January 10th to January 20th), new task occurrences are created up to the new end date. Existing open and closed tasks in the series are not affected.

The following table describes the usage of recurrence fields. Each recurrence type must have all of its properties set. All unused properties must be set to null.

RecurrenceType Value	Properties	Example Pattern
RecursDaily	RecurrenceInterval	Every second day
RecursEveryWeekday	RecurrenceDayOfWeekMask	Every weekday - can't be Saturday or Sunday
RecursMonthly	RecurrenceDayOfMonth RecurrenceInterval	Every second month, on the third day of the month
RecursMonthlyNth	RecurrenceInterval RecurrenceInstance RecurrenceDayOfWeekMask	Every second month, on the last Friday of the month

RecurrenceType Value	Properties	Example Pattern
RecursWeekly	RecurrenceInterval RecurrenceDayOfWeekMask	Every three weeks on Wednesday and Friday
RecursYearly	RecurrenceDayOfMonth RecurrenceMonthOfYear	Every March on the twenty-sixth day of the month
RecursYearlyNth	RecurrenceDayOfWeekMask RecurrenceInstanceRecurrenceMonthOfYear	The first Saturday in every October

JunctionIdList

The `JunctionIdList` field is now implemented in the Event and Task objects. With a single API call, it's easy to create many-to-many relationships between the Event or Task object with contacts, leads, or users.

To create a Task with related Contacts without `JunctionIdList`, you first have to create the task, then use the returned task ID to create the `TaskRelation` records. If the `TaskRelation` save call fails, error handling is your responsibility because the task has already been committed to the database.

```
public void createTasksOld(Contact[] contacts) {
    Task task = new Task();
    task.setSubject("New Task");
    SaveResult[] results = null;
    try {
        results = connection.create(new Task[] {
            task
        });
        if (results[0].isSuccess()) {
            TaskRelation[] relations = new TaskRelation[contacts.size()];
            for (int i = 0; i < contacts.length; i++) {
                relations[i] = new TaskRelation();
                relations[i].setTaskId(results[0].getID());
                relations[i].setRelationId(contacts[i].getID());
            }
            results = connection.create(relations);
        }
    } catch (ConnectionException ce) {
        ce.printStackTrace();
    }
}
```

To create a task using `JunctionIdList`, IDs are pulled from the related contacts and both the task and the `TaskRelation` records are created in one API call. If the `TaskRelation` fails, the task is rolled back because it's all done in a single API call.

```
public void createTaskNew(Contact[] contacts) {
    String[] contactIds = new String[contacts.size()];
    for (int i = 0; i < contacts.size(); i++) {
        contactIds[i] = contacts[i].getID();
    }
    Task task = new Task();
    task.setSubject("New Task");
    task.setTaskWhoIds(contactIds);
    SaveResult[] results = null;
    try {
```



```
results = connection.create(new Task[] {
    task
});
} catch (ConnectionException ce) {
    ce.printStackTrace();
}
}
```

TaskFeed

Represents a single feed item in the feed on an Task.
Represents a

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Moderate Chatter"

 **Note:** Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of TaskFeed. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.

Field	Details
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.

Field	Details
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an FeedItem: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.

Field	Details
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, LastModifiedDate is the same as CreatedDate. If a FeedComment is inserted on that feed item, then LastModifiedDate becomes the CreatedDate for that FeedComment. Deleting the FeedComment does not change the LastModifiedDate. Ordering by LastModifiedDate DESC sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope:

Field	Details
	- Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the account record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the task record. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging).

Field	Details
	For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.

Field	Details
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for a task record.

TaskPriority

Represents the importance or urgency of a Task, such as High, Normal, or Low.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>IsDefault</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this is the default task priority value (<code>true</code>) or not (<code>false</code>) in the picklist. Only one value in the picklist can be the default value.
<code>IsHighPriority</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this task priority value represents a high priority Task (<code>true</code>) or not (<code>false</code>). Multiple task priority values can represent a high-priority Task.
<code>MasterLabel</code>	Type string Properties Filter, Group, Nillable, Sort Description Master label for this task priority value. This display value is the internal label that does not get translated. Limit: 255 characters.
<code>SortOrder</code>	Type int Properties Filter, Nillable, Group, Sort Description Number used to sort this value in the task priority picklist. These numbers are not guaranteed to be sequential, as some previous task priority values might have been deleted.

Usage

This object represents a value in the task priority picklist. The task priority picklist provides additional information about the importance of a Task, such as whether a given priority value represents a high priority. Your client application can query on this object to retrieve the set of values in the task priority picklist, and then use that information while processing Task objects to determine more information about a given task. For example, the application could test whether a given Task is high priority based on its `Priority` value and the value of the `IsHighPriority` in the associated TaskPriority object.

TaskRelation

Represents the relationship between a task and a lead, contacts, and other objects related to the task. If Shared Activities is enabled, this object doesn't support triggers, workflow, or data validation rules.

TaskRelation is available:

- In API versions 24.0 and later
- Only if you've enabled Shared Activities in your organization

TaskRelation allows the following relationships:

- A task can be related to one lead or up to 50 contacts.
- A task can also be related to one account, asset, campaign, case, contract, opportunity, product, solution, or custom object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `queryAll()`, `retrieve()`

Fields

Field Name	Details
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the Account ID of the relation. For information on IDs, see ID Field Type.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a task has been deleted; label is Deleted. When a TaskRelation record is deleted, it isn't moved to the Recycle Bin and can't be undeleted, unless the record was cascade-deleted when the parent object was deleted. Don't use the <code>IsDeleted</code> field to detect deleted records in SOQL queries or <code>queryAll()</code> calls on directly deleted relation records. Instead, use the call <code>getDeleted()</code>.
IsWhat	Type boolean

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Sort Description Indicates whether the relation is an Account, Opportunity, Campaign, Case, other standard object, or a custom object. Value is <code>false</code> if <code>RelationId</code> is a contact or lead and <code>true</code> otherwise.
RelationId	Type reference Properties Create, Filter, Group, Sort Description Indicates the <code>whatId</code> or <code>whoId</code> in the relationship. For more information, see Task. For information on IDs, see ID Field Type.
TaskId	Type reference Properties Create, Filter, Group, Sort Description Represents the ID of the associated Task. For information on IDs, see ID Field Type.

Usage

See contacts associated with a task

```
public void queryWhosOfTaskSample() {
    String soqlQuery = "SELECT Id, Subject, (SELECT RelationId, Relation.Name, IsWhat
from TaskRelations WHERE isWhat = false) FROM Task WHERE Id = '00T x0000005OKEN'";
    QueryResult qResult = null;
    try {
        qResult = connection.query(soqlQuery);
        TaskRelation relation1 =
(TaskRelation)qResult.getRecords()[0].getTaskRelations().getRecords()[0];
    } catch (ConnectionException ce) {
        ce.printStackTrace();
    }
}
```

TaskStatus

Represents the status of a Task, such as Not started, Completed, or Closed.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>IsClosed</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this task status value represents a closed Task (<code>true</code>) or not (<code>false</code>). Multiple task status values can represent a closed Task.
<code>IsDefault</code>	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether this is the default task status value (<code>true</code>) or not (<code>false</code>) in the picklist.
<code>MasterLabel</code>	Type string Properties Filter, Group, Nillable, Sort Description Master label for this task status value. This display value is the internal label that does not get translated. Limit: 255 characters.
<code>SortOrder</code>	Type int Properties Filter, Group, Nillable, Sort

Field	Details
	Description Number used to sort this value in the task status picklist. These numbers are not guaranteed to be sequential, as some previous task status values might have been deleted.

Usage

This object represents a value in the task status picklist. The task status picklist provides additional information about the status of a Task, such as whether a given status value represents an open or closed task. Your client application can query this object to retrieve the set of values in the task status picklist, and then use that information while processing Task records to determine more information about a given task. For example, the application could test whether a given task is open or closed based on the Task `Status` value and the value of the `IsClosed` property in the associated TaskStatus record.

TaskTag

Associates a word or short phrase with a Task.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
<code>ItemId</code>	Type reference Properties Create, Filter Description ID of the tagged item.
<code>Name</code>	Type string Properties Create, Filter Description Name of the tag. If this value does not already exist, a new TagDefinition is created and becomes the parent of this Tag object. Otherwise, a TagDefinition with the same name becomes the parent of this Tag object. Parent relationships are created automatically.

Field Name	Details
TagDefinitionId	Type reference Properties Filter Description ID of the parent TagDefinition object that owns the tag.
Type	Type picklist Properties Create, Filter, Restricted picklist Description Defines the visibility of a tag. Valid values: • Public—The tag can be viewed and manipulated by all users in an organization. • Personal—The tag can be viewed or manipulated only by a user with a matching OwnerId.

Usage

TaskTag stores the relationship between its parent TagDefinition and the Task being tagged. Tag objects act as metadata, allowing users to describe and organize their data.

When a tag is deleted, its parent TagDefinition will also be deleted if the name is not being used; otherwise, the parent remains. Deleting a TagDefinition sends it to the Recycle Bin, along with any associated tag entries.

TaskWhoRelation

TaskWhoRelation represents the relationship between a task and a lead or contacts. This derived object is a filtered version of the [TaskRelation](#) on page 1369 object; that is, IsParent is `true` and IsWhat is `false`. It doesn't represent relationships to accounts, opportunities, or other objects.

TaskWhoRelation allows a variable number of relationships: one lead or up to 50 contacts. Available only if you've enabled Shared Activities for your organization. This object is available in API versions 29.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
RelationId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the contacts or lead related to the task.
TaskId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the task.
Type	Type string Properties Filter, Group, Nillable, Sort Description Indicates whether the person related to the task is a lead or contact.

Usage

Apex example that queries contacts associated with a task

```
public void queryWhosOfTaskSample() {  
    String soqlQuery = "SELECT Id, Subject, (SELECT RelationId, Relation.Name, IsWhat  
from TaskWhoRelations) FROM Task WHERE Id = '00Tx0000005OKEN'";  
    QueryResult qResult = null;  
    try {  
        qResult = connection.query(soqlQuery);  
        TaskWhoRelation relation1 =  
(TaskWhoRelation)qResult.getRecords()[0].getTaskWhoRelations().getRecords()[0];  
    } catch (ConnectionException ce) {  
        ce.printStackTrace();  
    }  
}
```

TenantSecret

This object stores an encrypted organization-specific key fragment that is used with the master secret to produce organization-specific data encryption keys.

You can rotate the tenant secret once every four hours in a sandbox organization or every 24 hours in production organizations. This object is available in API version 34 and later.

 **Note:** This information applies to Platform Encryption and not to Classic Encryption. See the Salesforce Online Help for more information.

Supported Calls

`create()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
Description	Type string Properties Create, Nillable, Update Description The description of the tenant secret.
SecretValue	Type base64 Properties Nillable, Update Description The encrypted 256-bit secret value encoded in base64.
Status	Type Restricted picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The current status of the tenant secret. Values are: ACTIVE Used to encrypt and decrypt new or existing data. ARCHIVED Used to decrypt data previously encrypted with this key when it was active. Archived keys cannot encrypt new data.

Field Name	Details
	DESTROYED Cannot encrypt or decrypt data. Data encrypted with this key when it was active can no longer be decrypted.
Version	Type int Properties Filter, Group, idLookup, Sort Description The version number of this secret. The version number is unique within your organization.

Usage

Use this object to create or update your organization-specific tenant secret. For example, you can build an automated tenant secret creation and activation solution similar to the following.

1. Start by creating an Apex class to create the new tenant secret.

```
global class CreateNewSecret implements Schedulable {
    global void execute(SchedulableContext SC) {
        TenantSecret k = new TenantSecret ();
        k.description = 'Created new secret from scheduled job';
        insert k;
    }
}
```

2. Schedule the Apex class to run at the specified interval.

This Apex code only needs to be run a single time to schedule the job. This code runs the job every 90 days.

```
CreateNewSecret secret = new CreateNewSecret();
String schedule = '0 0 0 1 JAN,APR,JUL,OCT ?';
String jobID = system.schedule('Automated secret creation and activation', schedule,
secret);
```

3. Validate that the job is scheduled.
4. Validate that tenant secrets are created after the job is run.

Here is an example of destroying a tenant secret.



Warning: Your tenant secret is unique to your organization and to the specific data to which it applies. Once you destroy a tenant secret, related data is not accessible unless you previously exported the key and then import the key back into Salesforce.

```
TenantSecret secret = [SELECT Id FROM TenantSecret WHERE Version = 2];
secret.SecretValue = NULL;
update secret;
```


Territory

Represents a flexible collection of accounts and users where the users have at least read access to the accounts, regardless of who owns the accounts. Only available if territory management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
<code>AccountAccessLevel</code>	Type picklist Properties Create, Filter, Group, Sort, Update Description Account access level granted to users assigned to this territory.
<code>CaseAccessLevel</code>	Type picklist Properties Create, Filter, Nillable, Group, Sort, Update Description Case access level granted to users assigned to this territory.
<code>ContactAccessLevel</code>	Type picklist Properties Filter, Group, Nillable, Sort Description A value that represents the type of access granted to the target Group, UserRole, or User for any associated contacts. The possible values are: • None • Read • Edit  Note: When <code>DefaultContactAccess</code> is set to "Controlled by Parent," you can't create or update this field.
<code>Description</code>	Type string

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description A description of the territory that is 1,000 characters or less.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Territory Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.
ForecastUserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the Forecast Manager, who is the user to whom forecasts from this territory's child territories roll up.
MayForecastManagerShare	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the forecast manager can manually share their own forecast.
Name	Type string Properties Create, Filter, Group, Sort, Update

Field	Details
	Description A name for the territory. Limit is 80 characters. Corresponds to Label on the user interface.
OpportunityAccessLevel	Type picklist Properties Create, Filter, Group, Sort, Update Description Opportunity access level granted to users assigned to this territory.
ParentTerritoryID	Type reference Properties Create, Filter, Nillable, Update Description Territory immediately above this territory in the territory hierarchy. Label is Parent Territory ID .
RestrictOppTransfer	Type boolean Properties Create, Defaulted on create, Filter, Update Description Indicates whether the opportunities associated with this territory are kept within the bounds of this territory and this territory's children when account assignment rules are run (<code>true</code>), or if opportunities associated with this territory can be assigned to other nodes of the territory hierarchy when account assignment rules are run (<code>false</code>). Label is Confine Opportunity Assignment .

Usage

Use the Territory object to query your organization's territory hierarchy. Use it to obtain valid territory IDs when querying or modifying records associated with territories.

Territory2

Represents a sales territory. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

If a territory model is in **Active** state, any user can view that model, including its territories and assignment rules. For territories in an active model, any user can view assigned records and assigned users subject to your organization's sharing settings. Users cannot view territory models in other states (such as **Planning** or **Archived**).

Fields

Field Name	Details
AccountAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Represents the default account record access levels for users that are assigned to the territory. Values are: • Read Only • Read/Write • Owner
CaseAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Represents the default case record access levels for users that are assigned to the territory. Values are: • Private • Read Only • Read/Write
ContactAccessLevel	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Represents the default contact record access levels for users that are assigned to the territory. Values are: • Private • Read Only • Read/Write

Field Name	Details
Description	Type string Properties Create, Filter, Nillable, Sort, Update Description The description of the territory.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description Required. The unique name of the object in the API. This name can contain only underscores and alphanumeric characters and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. The field label in the user interface is <code>Territory Name</code>.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The name of the territory. The field label in the user interface is <code>Label</code>.
OpportunityAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Represents the default opportunity record access levels for users that are assigned to the territory. Values are: • Private • Read Only • Read/Write
ParentTerritory2Id	Type reference

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the territory's parent territory (if any). If the territory has no parent territory, this value is <code>null</code> .
Territory2ModelId	Type reference Properties Create, Filter, Group, Sort Description The ID of the territory model that the territory belongs to.
Territory2TypeId	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the territory type that the territory belongs to.

Territory2Model

Represents a territory model. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

If a territory model is in `Active` state, any user can view that model, including its territories and assignment rules. For territories in an active model, any user can view assigned records and assigned users subject to your organization's sharing settings. Users cannot view territory models in other states (such as `Planning` or `Archived`).

Fields

Field Name	Details
ActivatedDate	Type dateTime

Field Name	Details
	Properties Filter, Nillable, Sort Description The date when the territory model was activated.
DeactivatedDate	Type dateTime Properties Filter, Nillable, Sort Description The date when the territory model was archived.
Description	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description The description of the territory model.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description Required. The unique name of the object in the API. This name can contain only underscores and alphanumeric characters and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. The field label in the user interface is <code>Territory Model Name</code> .  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
LastOppTerrAssignEndDate	Type dateTime Properties Filter, Nillable, Sort Description Read-only. The date when the opportunity territory assignment filter was last run. Used for Filter-Based Opportunity Territory Assignment (Pilot in Spring '15 / API version 33).

Field Name	Details
LastRunRulesEndDate	Type dateTime Properties Filter, Nillable, Sort Description The date when the last rules run was completed.
Name	Type string Properties Create, Filter, Group, Sort, Update Description The territory model name. The field label in the user interface is <code>Label</code> .
State	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort, Update Description The state of the territory model. Values are: <code>Planning</code> , <code>Activating</code> , <code>Activation Failed</code> , <code>Active</code> , <code>Archiving</code> , <code>Archiving Failed</code> , <code>Archived</code> , <code>Deleting</code> , and <code>Deletion Failed</code> .

Territory2ModelHistory

Represents the history of changes to the values in the fields on a territory model. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field Name	Details
	Description The name of the field whose value was changed.
newValue	Type anyType Properties Nillable, Sort Description The new value of the changed field.
oldValue	Type anyType Properties Nillable, Sort Description The previous value of the changed field.
Territory2ModelId	Type reference Properties Filter, Group, Sort Description The ID of the territory model whose history is tracked.

Usage

This object is automatically generated whenever any field value changes on a territory model record. Use this object it to identify those changes.

Territory2Type

Represents a category for territories (Territory2). Every Territory2 must have a Territory2Type. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

All users (including standard users) have access to this object in the user interface

Fields

Field Name	Details
Description	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description The description of the territory type.
DeveloperName	Type string Properties Create, Filter, Group, Sort, Update Description Required. The unique name of the object in the API. This name can contain only underscores and alphanumeric characters and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. The field label in the user interface is <code>Territory Type Name</code>.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
Language	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The language of the master label in the user interface.
MasterLabel	Type string Properties Create, Filter, Group, Sort, Update Description Required The user interface label for the territory type.
Priority	Type int Properties Create, Filter, Group, SortUpdate

Field Name	Details
	Description Required. Used for Filter-Based Opportunity Territory Assignment (Pilot in Spring '15 / API version 33). Lets you specify a priority for a territory type. For opportunity assignments, the filter examines all territories assigned to the account that the opportunity is assigned to. The account-assigned territory whose territory type priority is highest is then assigned to the opportunity. The <code>priority</code> field value on each territory type must be unique. Further, if there are multiple territories with the same territory type (and therefore the same priority) assigned to the account, no territory is not assigned to the opportunity.

ThirdPartyAccountLink

Represents the list of external users who authenticated using an Auth. Provider.

A list of third-party account links is generated when users of an organization authenticate using an external Auth. Provider. Use this object to list and revoke a given user's social sign-on connections (such as Facebook®). This object is available in API version 32.0 and later.

Supported Calls

`describeSObjects()`, `query()`

Fields

Field Name	Details
Handle	Type string Properties Filter, Nillable, Sort Description The username in the third-party system.
IsNotSsoUsable	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Support for single sign-on. If <code>true</code>, the link cannot be used for a single sign-on flow. It is only available OAuth access and refresh tokens.

Field Name	Details
Provider	Type string Properties Filter, Group, Nillable, Sort Description The third-party account provider name.
RemoteIdentifier	Type string Properties Filter, Group, Nillable, Sort Description The unique ID for the user in the third-party system.
SsoProvider	Type AuthProvider on page 200 Properties Filter, Group, Nillable, Sort Description The foreign key to the AuthProvider of the third-party system.
SsoProviderId	Type reference Properties Filter, Group, Nillable, Sort Description The ID associated with the SsoProvider value.
SsoProviderName	Type string Properties Filter, Group, Nillable, Sort Description The name associated with the AuthProvider of the third-party system, in case the user has no access to the provider foreign key (the SsoProvider value).
ThirdPartyAccountLinkKey	Type string Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description A concatenated string including the organization ID, the <code>SsoProviderId</code> value, the <code>SsoProvider</code> value, and the <code>RemoteIdentifier</code> value.
<code>UserId</code>	Type reference Properties Filter, Group, Nillable, Sort Description The Salesforceuser associated with this third-party account link.

Usage

Use this object makes to build custom screens to manage a user's third-party account links.

Administrators (with the "Manage Users" permission) querying this object can see all the links for all users in the organization. Without the "Manage Users" permission, users can only retrieve thier own links. A user may not have access to the `SsoProvider` value (the foreign key). In this case, use the `SsoProviderName` to render the name of the provider for the associated link.

Use the Apex method `Auth.AuthToken.revokeAccess()` to revoke a link.

In API version 34.0 and later, this object was enhanced to help manage high instance counts. A `query()` call returns up to 500 rows. A `queryMore()` call returns 500 more, up to 2500 total. No more records are returned after 2500. To make sure you don't miss any records, issue a `COUNT()` query in a `SELECT` clause for `ThirdPartyAccountLink`. This gives you the total number of records. If there are more than 2500 records, divide your query by filtering on fields, like `UserId`, to return subsets of less than 2500 records.

Topic

Represents a topic on a Chatter post or record. This object is available in API version 28.0 and later.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>Description</code>	Type string Properties Create, Filter, Nillable, Sort, Update Description Description of the topic.

Field Name	Details
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update  Note: You can change only the spacing and capitalization of a topic name with the update property. Description Name of the topic.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Identifier of the community to which the Topic belongs. This field is available only if Salesforce Communities is enabled in your organization.
TalkingAbout	Type int Properties Filter, Group, Sort Description Number of people talking about the topic over the last two months, based on factors such as topic additions and comments on posts with the topic.

Usage

Use this object to query a specific topic or to get a list of all topics, even those used solely in private groups and on records, and the number of people talking about them.

Use this object to create, edit, or delete topics. To create a topic, you must have the “Create Topics” permission. To edit a topic, you must have the “Edit Topics” permission. To delete a topic, you must have the “Delete Topics” or “Modify All Data” permission.

TopicAssignment

Represents the assignment of a topic to a specific feed item or record. This object is available in API version 28.0 and later. Topics for objects is available in API version 30.0 and later. Administrators must enable topics for objects before users can add topics to records of that object type.

Supported Calls

`create()`, `describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
EntityId	Type reference Properties Create, Filter, Group, Sort Description Identifier of the feed item or record.
EntityKeyPrefix	Type string Properties Filter, Group, idLookup, Sort Description The first three digits of the <code>EntityID</code> field, which identify the object type (account, opportunity, etc). This read-only field is available in API version 32.0 and later. Interface label is "Record Key Prefix," which appears only in reports.
EntityType	Type string Properties Filter, Group, Nillable, Sort Description The standard name for the object type (account, opportunity, etc). This read-only field is available in API version 33.0 and later. Interface label is "Object Type," which appears only in reports.  Tip: In most cases, you should use this field rather than <code>EntityKeyPrefix</code>, which exists primarily to support older reports.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Identifier of the community to which the TopicAssignment belongs. This field is available only if Salesforce Communities is enabled in your organization.
TopicId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Sort
	Description Identifier of the topic.

Usage

Use this object to query the assignments of topics to feed items or records. To assign or remove topics, you must have the “Assign Topics” permission.

In SOQL `SELECT` syntax, this object supports nested semi-joins, allowing queries on Knowledge articles assigned to specific topics. For example:

```
SELECT parentId FROM KnowledgeArticleViewStat
WHERE parentId in (SELECT KnowledgeArticleId FROM KnowledgeArticleVersion
WHERE publishStatus = 'Online' AND language = 'en_US'
AND Id in (select EntityId from TopicAssignment where TopicId ='0T0xx0000000xxx'))
```

No SOQL limit if logged-in user has “View All Data” permission. If not, do one of the following:

- Specify a `LIMIT` clause of 1,100 records or fewer.
- Filter on `Id` or `Entity` when using a `WHERE` clause with “=”.

TopicFeed

Represents a single feed tracked change for a topic. This object is available in API version 29.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn’t create, you must have one of these permissions:

- “Modify All Data”
- “Moderate Chatter”



Note: Users with the “Moderate Chatter” permission can delete only the feed items and comments they see.

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a PartnerNetworkConnection changes a tracked record, the <code>CreatedBy</code> field contains the ID of the system administrator. The <code>ConnectionId</code> contains the ID of the PartnerNetworkConnection that made the change. Available if Salesforce to Salesforce is enabled for your organization.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort

Field Name	Details
	Description The description of the file specified in <code>ContentData</code> .
<code>ContentFileName</code>	Type string Properties Group, Nillable, Sort Description The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code> .
<code>ContentSize</code>	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
<code>ContentType</code>	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
<code>InsertedById</code>	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
<code>LikeCount</code>	Type int Properties Filter, Group, Sort

Field Name	Details
	Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code> .
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community , a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code> : - Only feed items with a <code>CollaborationGroup</code> or <code>User</code> parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the topic that is tracked in the feed.
RelatedRecordId	Type reference Properties Group, Nillable, Sort

Field Name	Details
	Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the FeedItem. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of FeedItem: • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold.

Field Name	Details
	• DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user’s Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case. • CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • CaseCommentPost—generated event when a user adds a case comment for a case object. • ChangeStatusPost—generated event when a user changes the status of a case. • ChatTranscriptPost—generated event when Live Agent transcript is saved to a case. • EmailMessageEvent—generated event when an email related to a case object is sent or received. • FacebookPost—generated when a Facebook post is created from a case. Deprecated. • MilestoneEvent—generated when a case milestone is completed or reaches violation status. • SocialPost—generated when a social post is created from a case.  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort

Field Name	Details
	Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item. • <code>InternalUsers</code>—The feed item is available to internal users only. Note the following exceptions for <code>Visibility</code>: • For record posts, <code>Visibility</code> is set to <code>InternalUsers</code> for all internal users by default. • External users can set <code>Visibility</code> only to <code>AllUsers</code>. • On user and group posts, only internal users can set <code>Visibility</code> to <code>InternalUsers</code>.

Usage

Use this object to track changes for a topic.

TopicLocalization—Beta

Represents the translated version of a topic name. Topic localization applies only to navigational and featured topics in communities. This object is available in API version 33.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Users with the Translation Workbench enabled can view topic translations, but the “Customize Application,” “Manage Translation,” or “Manage Categories” permission is required to create or update them.

Fields

Field Name	Details
Language	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort

Field Name**Details****Description**

The combined language and locale ISO code, which controls the language for labels displayed in an application. (The values in this field are not related to the default locale selection.)

This picklist contains the following fully-supported languages:

- Chinese (Simplified): zh_CN
- Chinese (Traditional): zh_TW
- Danish: da
- Dutch: nl_NL
- English: en_US
- Finnish: fi
- French: fr
- German: de
- Italian: it
- Japanese: ja
- Korean: ko
- Norwegian: no
- Portuguese (Brazil): pt_BR
- Russian: ru
- Spanish: es
- Spanish (Mexico): es_MX
- Swedish: sv
- Thai: th

The following end-user only languages are available.

- Arabic: ar
- Bulgarian: bg
- Croatian: hr
- Czech: cs
- English (UK): en_GB
- Greek: el
- Hebrew: iw
- Hungarian: hu
- Indonesian: in
- Polish: pl
- Portuguese (Portugal): pt_PT
- Romanian: ro
- Slovak: sk
- Slovenian: sl

Field Name

Details

- Turkish: `tr`
- Ukrainian: `uk`
- Vietnamese: `vi`

The following platform languages are available for organizations that use Salesforce exclusively as a platform.

- Albanian: `sq`
- Arabic (Algeria): `ar_DZ`
- Arabic (Bahrain): `ar_BH`
- Arabic (Egypt): `ar_EG`
- Arabic (Iraq): `ar_IQ`
- Arabic (Jordan): `ar_JO`
- Arabic (Kuwait): `ar_KW`
- Arabic (Lebanon): `ar_LB`
- Arabic (Libya): `ar_LY`
- Arabic (Morocco): `ar_MA`
- Arabic (Oman): `ar_OM`
- Arabic (Qatar): `ar_QA`
- Arabic (Saudi Arabia): `ar_SA`
- Arabic (Sudan): `ar_SD`
- Arabic (Syria): `ar_SY`
- Arabic (Tunisia): `ar_TN`
- Arabic (United Arab Emirates): `ar_AE`
- Arabic (Yemen): `ar_YE`
- Armenian: `hy`
- Basque: `eu`
- Bosnian: `bs`
- Bengali: `bn`
- Chinese (Simplified—Singapore): `zh_SG`
- Chinese (Traditional—Hong Kong): `zh_HK`
- English (Australia): `en_AU`
- English (Canada): `en_CA`
- English (Hong Kong): `en_HK`
- English (India): `en_IN`
- English (Ireland): `en_IE`
- English (Malaysia): `en_MY`
- English (Philippines): `en_PH`
- English (Singapore): `en_SG`
- English (South Africa): `en_ZA`

Field Name	Details
	- Estonian: <code>et</code> - French (Belgium): <code>fr_BE</code> - French (Canada): <code>fr_CA</code> - French (Luxembourg): <code>fr_LU</code> - French (Switzerland): <code>fr_CH</code> - Georgian: <code>ka</code> - German (Austria): <code>de_AT</code> - German (Luxembourg): <code>de_LU</code> - German (Switzerland): <code>de_CH</code> - Hindi: <code>hi</code> - Icelandic: <code>is</code> - Irish: <code>ga</code> - Italian (Switzerland): <code>it_CH</code> - Latvian: <code>lv</code> - Lithuanian: <code>lt</code> - Luxembourgish: <code>lb</code> - Macedonian: <code>mk</code> - Malay: <code>ms</code> - Maltese: <code>mt</code> - Romanian (Moldova): <code>ro_MD</code> - Montenegrin: <code>sh_ME</code> - Romansh: <code>rm</code> - Serbian (Cyrillic): <code>sr</code> - Serbian (Latin): <code>sh</code> - Spanish (Argentina): <code>es_AR</code> - Spanish (Bolivia): <code>es_BO</code> - Spanish (Chile): <code>es_CL</code> - Spanish (Colombia): <code>es_CO</code> - Spanish (Costa Rica): <code>es_CR</code> - Spanish (Dominican Republic): <code>es_DO</code> - Spanish (Ecuador): <code>es_EC</code> - Spanish (El Salvador): <code>es_SV</code> - Spanish (Guatemala): <code>es_GT</code> - Spanish (Honduras): <code>es_HN</code> - Spanish (Nicaragua): <code>es_NI</code> - Spanish (Panama): <code>es_PA</code> - Spanish (Paraguay): <code>es_PY</code> - Spanish (Peru): <code>es_PE</code>

Field Name	Details
	- Spanish (Puerto Rico): <code>es_PR</code> - Spanish (United States): <code>es_US</code> - Spanish (Uruguay): <code>es_UY</code> - Spanish (Venezuela): <code>es_VE</code> - Tagalog: <code>t1</code> - Tamil: <code>ta</code> - Urdu: <code>ur</code> - Welsh: <code>cy</code>
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: - In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. - In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID that identifies the topic. After a TopicLocalization record is created, this ID can't be modified.
Value	Type string Properties Create, Filter, Sort, Update

Field Name	Details
	Description The translated text for the topic name. Label is Topic Name Translation .

TwoFactorInfo

Stores a user's secret for all two-factor operations.

Use this object when customizing two-factor authentication in your organization. This object is available in API version 32.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

You need the "Manage Two-Factor Authentication" permission to create or update this object.

Fields

Field Name	Details
SharedKey	Type string Properties Create, Group, Sort, Update Description This field is never read-enabled, though it is write-enabled. A request for this value always returns <code>null</code> . The value must be a base32-encoded string of a 20-byte secret. You can use the Apex method <code>Auth.SessionManagement.getQrCode()</code> to get a value to write to this field.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The two-factor method. TOTP: The time-based one-time password.

Field Name	Details
UserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID for the user who's associated with the authentication secret.

UndecidedEventRelation

Represents invitees with the status `Not_Responded` for a given event.

This object is available in API versions 29.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
EventId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the event.
RelationId	Type reference Properties Filter, Group, Nillable, Sort Description Indicates the ID of the invitee.
RespondedDate	Type dateTime Properties Filter, Nillable, Sort Description This field is always <code>null</code> .

Field Name	Details
Response	Type string Properties Filter, Group, Nillable, Sort Description Indicates the content of the response field. Label is <code>Comment</code>.
Type	Type string Properties Filter, Group, Nillable, Sort Description Indicates whether the invitee is a user, lead or contact, or resource.

Usage

Query invitees who have not responded to an invitation to an event

```
SELECT eventId, type, response FROM UndecidedEventRelation WHERE
eventId='00UTD000000ZH5LA'
```

User

Represents a user in your organization.

Supported Calls

`create()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

- To create or update a User record, you must have the “Manage Internal Users” permission. Additionally, if the user is a Customer Portal user, you must have the “Edit Self-Service Users” permission, and if the user is a partner portal user, you must have the “Manage External Users” permission.
- If [Communities](#) is enabled in your organization, to create or update external users for Customer Portal, partner portal, or Communities, you must also have the “Manage External Users” permission.
- Information in hidden fields in a user’s profile is not searchable by external users (with a portal profile) in a community. For example, if a user in a community has a hidden email address and an external user searches for it, the user record is not returned in the search results. Hidden field values are also not returned when external users perform searches on non-hidden fields. So if an external user searches for a user’s name (cannot be hidden), any hidden field values associated with the user record (for example, a hidden email address) are not returned in the search results.

Internal users from your organization who belong to the same community, however, can both search for and view hidden field values in search results.

- When requested by portal users, queries that look up to the User object, such as `owner.name` or `owner.email` might not return values when the portal user making the request doesn't have Read access to the User record being queried.

The behavior depends on the number of domains associated with the lookup field. If the object can look up to more than one domain, `owner.name` returns a value, but other detail fields don't. For example, Case owner can look up to the User or Queue objects. In this case, portal users can see only the value of `owner.name`. Other User detail fields, such as `owner.email` or `owner.phone` don't return a value.

If the object can look up to only a single domain, such as Account owner, then no detail fields return values, including `owner.name`.

- Changing ownership of a record by updating its `OwnerId` field requires the user making the change to have both the "Transfer Record" permission and Read access to the User record of the new record owner.

Fields

Field	Details
AboutMe	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Information about the user, such as areas of interest or skills.
AccountId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the Account associated with a Customer Portal user. This field is null for Salesforce users.
Address (beta)	Type address Properties Filter, Nillable Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.
Alias	Type string Properties Create, Filter, Group, Sort, Update

Field	Details
	Description Required. The user's alias. For example, jsmith.
BadgeText	Type string Properties Filter, Group, Nillable, Sort Description The text description of a user badge that appears over a user's photo. Users of the same Chatter user type (internal, external) are badged. Different user types are not badged.
CallCenterId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description If Salesforce CRM Call Center is enabled, represents the call center to which this user is assigned.
City	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The city associated with the user. Up to 40 characters allowed.
CommunityNickname	Type string Properties Create, Filter, Group, Sort, Update Description Name used to identify this user in the Community application, which includes the ideas and answers features.
CompanyName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The name of the user's company.

Field	Details
ContactId	Type reference Properties Create, Filter, Group, Nillable, Sort Description ID of the Contact associated with this account. The contact must have a value in the <code>AccountId</code> field or an error occurs.
Country	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The country associated with the user. Up to 80 characters allowed.
CountryCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO country code associated with the user.
CurrentStatus	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Text that describes what the user is working on.  Note: If you update this field, the API automatically adds a post of type <code>UserStatus</code> on the user's profile in Chatter. This field is deprecated in API version 25.0. To achieve similar behavior, post to the user directly by creating a <code>FeedItem</code> with the user's <code>ParentId</code>.
DefaultCurrencyIsoCode	Type picklist Properties Create, Filter, Nillable, Restricted picklist, Update

Field	Details
	Description The user's default currency setting for new records. For example, a user in France could have a <code>DefaultCurrencyIsoCode</code> set to Euros, and that would be their default currency in the application. Only applicable for organizations that use multiple currencies.
<code>DefaultDivision</code>	Type picklist Properties Create, Defaulted on create, Filter, Group, Sort, Update Description This record's default division. Only applicable if divisions are enabled for your organization.
<code>DefaultGroupNotificationFrequency</code>	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Required. The default frequency for sending the user's Chatter group email notifications when the user joins groups. The valid values are: • <code>P</code>—Email on each post • <code>D</code>—Daily digests • <code>W</code>—Weekly digests • <code>N</code>—Never The default value is <code>N</code>. For Professional, Enterprise, Unlimited, and Developer Edition organizations that existed prior to API version 22.0, the default value remains <code>D</code>. This field is available in API version 21.0 and later.
<code>DelegatedApproverId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Id of the user who is a delegated approver for this user.
<code>Department</code>	Type string

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The company department associated with the user.
DigestFrequency	Type picklist Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Required. The frequency at which the system sends the user's Chatter personal email digest. The valid values are: • D = Daily • W = Weekly • N = Never The default value is D.
Division	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The division associated with this user, similar to Department and unrelated to <code>DefaultDivision</code> .
Email	Type email Properties Create, Filter, Group, idLookup, Sort, Update Description Required. The user's email address.
EmailEncodingKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. The email encoding for the user, such as ISO-8859-1 or UTF-8.

Field	Details
EmailPreferencesAutoBcc	Type boolean Properties Create, Filter, Update Description Determines whether the user will receive copies of sent emails. This option applies only if compliance BCC emails are not enabled.
EmailPreferencesAutoBccStayInTouch	Type boolean Properties Create, Filter, Update Description Determines whether the user will receive copies of sent Stay-in-Touch emails. This option applies only if compliance BCC emails are not enabled.
EmailPreferencesStayInTouchReminder	Type boolean Properties Create, Filter, Update Description Determines whether the user is reminded to use the Stay-in-Touch feature when creating a new contact.
EmployeeNumber	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The user's employee number.
Extension	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description The user's phone extension number.
Fax	Type phone

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The user's fax number.
FederationIdentifier	Type string Properties Create, Filter, idLookup, Nillable, Sort, Update Description Indicates the value that must be listed in the <code>subject</code> element of a Security Assertion Markup Language (SAML) <i>IDP certificate</i> to authenticate the user for a client application using single sign-on. This value must be specified if the <code>SAML User ID Type</code> is Assertion contains Federation ID from the User record. Otherwise, this field can't be edited.
FirstName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The user's first name.
ForecastEnabled	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the user is enabled as a Forecast Manager (<code>true</code>) or not (<code>false</code>) in customizable forecasting. Forecast managers see forecast rollups from users below them in the forecast hierarchy.
FullPhotoUrl	Type string Properties Filter, Nillable, Sort Description The URL for the user's profile photo if Chatter is enabled. The URL is updated every time a photo is uploaded and reflects the most recent photo. The URL returned for an older photo is not

Field	Details
	guaranteed to return a photo if a newer photo has been uploaded. You should always query this field for the URL of the most recent photo. This field is available in API version 20.0 and later.
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the user has access to log in (<code>true</code>) or not (<code>false</code>). You can modify a User's active status from the user interface or via the API.
IsPartner	Type boolean Properties Defaulted on create, Filter Description Indicates whether the user is a partner who has access to the partner portal (<code>true</code>) or not (<code>false</code>). This field is not available for release 9.0 and later. Instead, use <code>UserType</code> with the value <code>Partner</code> or <code>Power Partner</code>.
IsPortalEnabled	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the user has access to Communities or portals (<code>true</code>) or not (<code>false</code>). This field is only available if one of the following conditions is true: • Communities are enabled in your organization and you have community or portal user licenses • Portals are enabled in your organization
IsPortalSelfRegistered	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort

Field	Details
	Description Indicates whether the user is a Customer Portal user who self-registered for your organization's Customer Portal (<code>true</code>) or not (<code>false</code>). This field is not available for release 9.0 and earlier.
IsPrmSuperUser	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the user has super user access in the partner portal (<code>true</code>) or not (<code>false</code>). This field is available in API version 24.0 and later.  Note: This field is not automatically enabled. Contact Salesforce to enable this field.
JigsawImportLimitOverride	Type int Properties Create, Filter, Group Nillable, Sort, Update Description The Data.com user's monthly addition limit. The value must be between zero and the organization's monthly addition limit. Label is Data.com Monthly Addition Limit. This field is available in API version 27.0 and later.
LanguageLocaleKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. The user's language, such as "French" or "Chinese (Traditional)." Label is Language.
LastLoginDate	Type dateTime Properties Filter, Sort, Nillable Description The date and time when the user last successfully logged in. This value is updated if 60 seconds have elapsed since the user's last login.

Field	Details
LastName	Type string Properties Create, Filter, Group, Sort, Update Description Required. The user's last name.
LastReferencedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed a record related to this record.
LastViewedDate	Type date Properties Filter, Nillable, Sort, Update Description The timestamp for when the current user last viewed this record. If this value is null, this record might only have been referenced (<code>LastReferencedDate</code>) and not viewed.
Latitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>Longitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
LocaleSidKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. This field is a restricted picklist field. The value of the field affects formatting and parsing of values, especially numeric values, in the user interface. It does not affect the API.

Field	Details
	The field values are named according to the language, and country if necessary, using two-letter ISO codes. The set of names is based on the ISO standard. It can often be more convenient to manually set a user's locale in the user interface, and then use that value for inserting or updating other users via the API.
Longitude	Type double Properties Create, Filter, Nillable, Sort, Update Description Used with <code>Latitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
Manager	Type picklist Properties Create, Filter, Restricted picklist, Update Description User lookup field used to select the user's manager. This establishes a hierarchical relationship, preventing you from selecting a user that directly or indirectly reports to itself.
ManagerId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The Id of the user who manages this user.
MiddleName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The user's middle name. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.
MobilePhone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update

Field	Details
	Description The user's mobile or cellular phone number.
Name	Type string Properties Filter, Group, Sort Description Concatenation of <code>FirstName</code> and <code>LastName</code> . Limited to 121 characters.
OfflineTrialExpirationDate	Type dateTime Properties Filter, Nillable, Sort Description The date and time when the user's Connect Offline trial expires.
Phone	Type phone Properties Create, Filter, Group, Nillable, Sort, Update Description The user's phone number.
PortalRole	Type picklist Properties Create, Filter, Group, Nillable, Sort Description The role of the user in the Customer Portal (either Executive, Manager, User, or PersonAccount). Prior to API version 16.0, you could set this field to null and the system automatically included a portal role. In API version 16.0 and above, when you set this field to null, a portal role is not automatically created. When this field is null and a <code>ContactId</code> is provided, the user is assigned to the User role. The field is available if Customer Portal is enabled OR Communities is enabled and have available partner portal, Customer Portal, or High-Volume Portal User licenses.

Field	Details
PostalCode	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The user's postal or ZIP code. Label is Zip/Postal Code.
ProfileId	Type reference Properties Create, Filter, Group, Sort, Update Description Required. ID of the user's Profile. Use this value to cache metadata based on profile. In earlier releases, this was <code>RoleId</code>.
ReceivesAdminInfoEmails	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the user receives email for administrators from Salesforce (<code>true</code>) or not (<code>false</code>).
ReceivesInfoEmails	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the user receives informational email from Salesforce (<code>true</code>) or not (<code>false</code>).
SenderEmail	Type email Properties Create, Filter, Group, Nillable, Sort, Update Description The email address used as the From address when the user sends emails. This is the same value shown in Setup on the My Email Settings page.
SenderName	Type string

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The name used as the email sender when the user sends emails. This is the same value shown in Setup on the My Email Settings page.
Signature	Type string Properties Create, Filter, Nillable, Sort, Update Description The signature text added to emails. This is the same value shown in Setup on the My Email Settings page.
SmallPhotoUrl	Type string Properties Filter, Nillable, Sort Description The URL for a thumbnail of the user's profile photo if Chatter is enabled. The URL is updated every time a photo is uploaded and reflects the most recent photo. The URL returned for an older photo is not guaranteed to return a photo if a newer photo has been uploaded. You should always query this field for the URL of the most recent photo. This field is available in API version 20.0 and later.
State	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The state associated with the User. Up to 80 characters allowed.
StateCode	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The ISO state code associated with the user.
StayInTouchNote	Type string

Field	Details
	Properties Create, Filter, Nillable, Sort, Update Description The body specified for the Stay-in-Touch email.
StayInTouchSignature	Type string Properties Create, Filter, Nillable, Sort, Update Description The signature specified for the Stay-in-Touch email.
StayInTouchSubject	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The subject specified for the Stay-in-Touch email.
Street	Type textarea Properties Create, Filter, Group, Nillable, Sort, Update Description The street address associated with the User.
Suffix	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The user's name suffix. Maximum size is 40 characters. Contact Salesforce Customer Support to enable this field.
TimeZoneSidKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. This field is a restricted picklist field. A User time zone affects the offset used when displaying or entering times in the user interface.

Field	Details
	However, the API does not use a User time zone when querying or setting values. Values for this field are named using region and key city, according to ISO standards. It can often be more convenient to manually set one User time zone in the user interface, and then use that value for creating or updating other User records via the API.
Title	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The user's business title, such as "Vice President."
Username	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Required. Contains the name that a user enters to log into the API or the user interface. The value for this field must be in the form of an email address. It must also be unique across all organizations. If you try to create or update a User with a duplicate value for this field, the operation is rejected. Each inserted User also counts as a license. Every organization has a maximum number of licenses. If you attempt to exceed the maximum number of licenses by inserting User records, the create is rejected.
UserPermissionsCallCenterAutoLogin	Type boolean Properties Create, Filter, Update Description Required if Salesforce CRM Call Center is enabled. Indicates whether the user is enabled to use the auto login feature of the call center (<code>true</code>) or not (<code>false</code>).
UserPermissionsChatterAnswersUser	Type boolean Properties Create, Filter, Update

Field	Details
	Description Indicates whether the portal user is enabled to use the Chatter Answers feature (<code>true</code>) or not (<code>false</code>). This field defaults to <code>false</code> when a Customer Portal user is created from the API.
UserPermissionsInteractionUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user can run flows or not. Label is Force.com Flow User.
UserPermissionsJigsawProspectingUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user is allocated one Data.com user license (<code>true</code>) or not (<code>false</code>). The Data.com user license lets the user add Data.com contact and lead records to Salesforce in supported editions. Label is Data.com User.
UserPermissionsKnowledgeUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user is enabled to use Salesforce Knowledge (<code>true</code>) or not (<code>false</code>). Label is Knowledge User.
UserPermissionsLiveAgentUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user is enabled to use Live Agent (<code>true</code>) or not (<code>false</code>). Label is Live Agent User.
UserPermissionsMarketingUser	Type boolean

Field	Details
	Properties Create, Filter, Update Description Required. Indicates whether the user is enabled to manage campaigns in the user interface (<code>true</code>) or not (<code>false</code>). Label is Marketing User.
UserPermissionsMobileUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user is allocated one Salesforce Classic license (<code>true</code>) or not (<code>false</code>). Label is Apex Mobile User. The Salesforce Classic license grants the user access to the Salesforce Classic application on supported mobile devices.
UserPermissionsOfflineUser	Type boolean Properties Create, Filter, Update Description Required. Indicates whether the user is enabled to use Offline Edition (<code>true</code>) or not (<code>false</code>). Label is Offline User.
UserPermissionsSFContentUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user is allocated one Salesforce CRM Content User License (<code>true</code>) or not (<code>false</code>). Label is Salesforce CRM Content User. The Salesforce CRM Content User license grants the user access to the Salesforce CRM Content application.
UserPermissionsSiteforceContributorUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user is allocated one Site.com Contributor feature license (<code>true</code>) or not (<code>false</code>). Label is Site.com Contributor User. The Site.com Contributor feature license grants the user access to the

Field	Details
	Site.com application. Users with a Contributor license can use Site.com Studio to edit site content only.
UserPermissionsSiteforcePublisherUser	Type boolean Properties Create, Filter, Update Description Indicates whether the user is allocated one Site.com Publisher feature license (<code>true</code>) or not (<code>false</code>). Label is Site.com Publisher User. The Site.com Publisher feature license grants the user access to the Site.com application. Users with a Publisher license can build and style websites, control the layout and functionality of pages and page elements, and add and edit content.
UserPermissionsSupportUser	Type boolean Properties Create, Filter, Update Description When <code>true</code>, the user can use the Salesforce console.
UserPermissionsWirelessUser	Type boolean Properties Create, Update Description Required if the Wireless permission is enabled for your organization. Indicates whether the user is enabled to use Wireless Edition (<code>true</code>) or not (<code>false</code>). Label is Wireless User.  Note: As of November 2005, Salesforce Wireless Edition is no longer available for purchase. If you are a Professional Edition customer and purchased Wireless Edition prior to November 7, 2005 or are an Enterprise Edition customer who has signed or renewed your Salesforce contract prior to November 7, 2005, you may continue using Wireless Edition through the end of your existing contract term.
UserPermissionsWorkDotComUserFeature	Type boolean Properties Create, Filter, Update

Field	Details
	Description Indicates whether the Work.com feature is enabled for the user (<code>true</code>) or not (<code>false</code>).
UserPreferencesActivityRemindersPopup	Type boolean Properties Create, Filter, Update Description When <code>true</code> , a reminder popup window automatically opens when an activity reminder is due. Corresponds to the <code>Trigger alert when reminder comes due</code> checkbox at the Reminders page in the personal settings in the user interface.
UserPreferencesApexPagesDeveloperMode	Type boolean Properties Create, Filter, Update Description When <code>true</code> , indicates the user has enabled developer mode for editing Visualforce pages and controllers.
UserPreferencesContentEmailAsAndWhen	Type boolean Properties Create, Filter, Update Description When <code>false</code> , a user with Salesforce CRM Content subscriptions will receive a once daily email summary if activity occurs on his or her subscribed content, libraries, tags, or authors. To receive email, the <code>UserPreferencesContentNoEmail</code> field must also be <code>false</code> . The default value is <code>false</code> .  Note: This field is only visible when Salesforce CRM Content is enabled for your organization.
UserPreferencesContentNoEmail	Type boolean Properties Create, Filter, Update

Field	Details
	Description When <code>false</code>, a user with Salesforce CRM Content subscriptions will receive email notifications if activity occurs on his or her subscribed content, libraries, tags, or authors. To receive real-time email alerts, set this field to <code>false</code> and set the <code>UserPreferencesContentEmailAsAndWhen</code> field to <code>true</code>. The default value is <code>false</code>.  Note: This field is only visible when Salesforce CRM Content is enabled for your organization.
<code>UserPreferencesEnableAutoSubForFeeds</code>	Type boolean Properties Create, Filter, Update Description When <code>true</code>, the user automatically subscribes to feeds for any objects that the user creates. This field is available in API version 25.0 and later.
<code>UserPreferencesDisableAllFeedsEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email for all updates to Chatter feeds, based on the types of feed emails and digests the user has enabled. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableAutoSubForFeeds</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically subscribes to feeds for any objects that the user creates. This field is deprecated in API version 25.0 and later. Starting with API version 25.0, use <code>UserPreferencesEnableAutoSubForFeeds</code> to enable or disable auto-follow for objects a user creates.
<code>UserPreferencesDisableBookmarkEmail</code>	Type boolean Properties Create, Filter, Update

Field	Details
	Description When <code>false</code>, the user automatically receives email every time someone comments on a Chatter feed item after the user has bookmarked it. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableChangeCommentEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time someone comments on a change the user has made, such as an update to their profile. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableEndorsementEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the member automatically receives email every time someone endorses them for a topic.
<code>UserPreferencesDisableFileShareNotificationsForApi</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, email notifications are sent from the person who has shared a file to the users with whom the file has been shared. This field is available in API version 25.0 and later.
<code>UserPreferencesDisableFollowersEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time someone starts following the user in Chatter. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableLaterCommentEmail</code>	Type boolean

Field	Details
	Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time someone comments on a feed item after the user has commented on the feed item. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableLikeEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time someone likes a post or comment the user has made. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableMentionsPostEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time the user is mentioned in posts. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableProfilePostEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time someone posts to the user's profile. This field is available in API version 24.0 and later.
<code>UserPreferencesDisableSharePostEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time the user's post is shared. This field is available in API version 24.0 and later.

Field	Details
UserPreferencesDisableFeedbackEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives emails related to Work.com feedback. This includes when someone requests or offers feedback, shares feedback with the user, or reminds the user to answer a feedback request.
UserPreferencesDisCommentAfterLikeEmail	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time someone comments on a post the user has liked. This field is available in API version 24.0 and later.
UserPreferencesDisMentionsCommentEmail	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time the user is mentioned in comments. This field is available in API version 24.0 and later.
UserPreferencesDisableMessageEmail	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email for Chatter messages sent to the user. This field is available in API version 24.0 and later.
UserPreferencesDisableRewardEmail	Type boolean Properties Filter

Field	Details
	Description When <code>false</code>, the user automatically receives emails related to Work.com rewards. This includes when someone gives a reward to the user.
<code>UserPreferencesDisableWorkEmail</code>	Type boolean Properties Filter Description When <code>false</code>, the user receives emails related to Work.com feedback, goals, and coaching. The user must also sign up for individual emails listed on the Work.com email settings page. When <code>true</code>, the user will not receive any emails related to Work.com feedback, goals, or coaching even if they are signed up for individual emails.
<code>UserPreferencesDisProfPostCommentEmail</code>	Type boolean Properties Create, Filter, Update Description When <code>false</code>, the user automatically receives email every time someone comments on posts on the user's profile. This field is available in API version 24.0 and later.
<code>UserPreferencesEventRemindersCheckboxDefault</code>	Type boolean Properties Create, Filter, Update Description When <code>true</code>, a reminder popup is automatically set on the user's events. Corresponds to the <code>By default, set reminder on Events to...</code> checkbox on the Reminders page in the user interface. This field is related to UserPreference and customizing activity reminders.
<code>UserPreferencesHideChatterOnboardingSplash</code>	Type boolean Properties Filter Description When <code>true</code>, the initial Chatter onboarding prompts do not appear.

Field	Details
UserPreferencesHideCSNDesktopTask	Type boolean Properties Create, Filter, Update Description When <code>true</code>, the Chatter recommendations panel never displays the recommendation to install Chatter Desktop. This field is available in API version 26.0 and later.
UserPreferencesHideCSNGetChatterMobileTask	Type boolean Properties Create, Filter, Update Description When <code>true</code>, the Chatter recommendations panel never displays the recommendation to install Chatter Mobile. This field is available in API version 26.0 and later.
UserPreferencesHideSecondChatterOnboardingSplash	Type boolean Properties Filter Description When <code>true</code>, the secondary Chatter onboarding prompts do not appear.
UserPreferencesHideS1BrowserUI	Type boolean Properties Create, Filter, Update Description Controls the interface that the user sees when logging in to Salesforce from a supported mobile browser. If <code>false</code>, the user is automatically redirected to the Salesforce1 mobile browser app. If <code>true</code>, the user sees the full Salesforce site. The default value is <code>false</code>. Label is Salesforce1 User. This field is available in API version 29.0 or later.
UserPreferencesJigsawListUser	Type boolean Properties Create, Filter, Update

Field	Details
	Description When <code>true</code>, the user is a Data.com List user and, therefore, shares record additions from a pool. <code>UserPermissionsJigsawProspectingUser</code> must also be set to <code>true</code>. Label is Data.com List User. This field is available in API version 27.0 and later.
<code>UserPreferencesOptOutOfTouch</code>	Type boolean Properties Create, Filter, Update Description This field is deprecated in API version 29.0. When <code>false</code>, the user automatically accesses the Salesforce Touch app when logging in to Salesforce from an iPad. If <code>true</code>, automatic access to the Salesforce Touch app is turned off and the user's iPad is directed to the full Salesforce site instead. The default value is <code>false</code>.  Note: Salesforce Touch must be enabled before this field is visible.
<code>UserPreferencesProcessAssistantCollapsed</code>	Type boolean Properties Create, Filter, Update Description When <code>true</code>, Sales Path appears collapsed or hidden to the user. This field is available in API version 33.0 and later.
<code>UserPreferencesReminderSoundOff</code>	Type boolean Properties Create, Filter, Update Description When <code>true</code>, a sound automatically plays when an activity reminder is due. Corresponds to the <code>Play a reminder sound</code> checkbox on the Reminders page in the user interface.
<code>UserPreferencesShowCityToExternalUsers</code>	Type boolean Properties Create, Filter, Update

Field	Details
	Description Indicates the visibility of the city field in the user's contact information. City is visible only to internal members of the user's organization when: - This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. City is visible to external members in a community when: - This field is <code>true</code>, or - This field is <code>false</code> but <code>UserPreferencesShowCityToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowCityToGuestUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the city field in the user's contact information. When <code>true</code>, city is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowCityToExternalUsers</code>, making the user's city visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowCountryToExternalUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the country field in the user's contact information. Country is visible only to internal members of the user's organization when: This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. Country is visible to external members in a community when:

Field	Details
	- This field is <code>true</code>, or - This field is <code>false</code> but <code>UserPreferencesShowCountryToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowCountryToGuestUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the country field in the user's contact information. When <code>true</code>, country is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowCountryToExternalUsers</code>, making the user's country visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowEmailToExternalUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the email address field in the user's contact information. Email address is visible only to internal members of the user's organization when this field is <code>false</code>. Email address is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowEmailToGuestUsers</code>	Type boolean Properties Create, Filter, Update

Field	Details
	Description Indicates the visibility of the email address field in the user's contact information. When <code>true</code>, the email address is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowEmailToExternalUsers</code>, making the user's email address visible to guests. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 34.0 and later.
<code>UserPreferencesShowFaxToExternalUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the fax number field in the user's contact information. Fax number is visible only to internal members of the user's organization when this field is <code>false</code>. Fax number is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowFaxToGuestUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the fax number field in the user's contact information. When <code>true</code>, the fax number field is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowFaxToExternalUsers</code>, making the user's fax number visible to guests. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 34.0 and later.
<code>UserPreferencesShowManagerToExternalUsers</code>	Type boolean

Field	Details
	Properties Create, Filter, Update Description Indicates the visibility of the manager field in the user's contact information. Manager is visible only to internal members of the user's organization when this field is <code>false</code>. Manager is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
UserPreferencesShowManagerToGuestUsers	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the manager field in the user's contact information. When <code>true</code>, the manager field is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowManagerToExternalUsers</code>, making the user's manager visible to guests. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 34.0 and later.
UserPreferencesShowMobilePhoneToExternalUsers	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the mobile or cellular phone number field in the user's contact information. The number is visible only to internal members of the user's organization when this field is <code>false</code>. The number is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
UserPreferencesShowMobilePhoneToGuestUsers	Type boolean

Field	Details
	Properties Create, Filter, Update Description Indicates the visibility of the mobile phone field in the user's contact information. When <code>true</code>, the mobile phone field is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowMobilePhoneToExternalUsers</code>, making the user's mobile phone visible to guests. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 34.0 and later.
<code>UserPreferencesShowPostalCodeToExternalUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the postal or ZIP code field in the user's contact information. Postal code is visible only to internal members of the user's organization when: • This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. Postal code is visible to external members in a community when: • This field is <code>true</code>, or • This field is <code>false</code> but <code>UserPreferencesShowPostalCodeToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowPostalCodeToGuestUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the postal or ZIP code field in the user's contact information. When <code>true</code>, postal code is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages

Field	Details
	in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowPostalCodeToExternalUsers</code>, making the user's postal code visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowProfilePicToGuestUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the user's profile photo. When <code>true</code>, the photo is visible to guest users in a community. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the stock photo. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowStateToExternalUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the state field in the user's contact information. State is visible only to internal members of the user's organization when: - This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. State is visible to external members in a community when: - This field is <code>true</code>, or - This field is <code>false</code> but <code>UserPreferencesShowStateToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowStateToGuestUsers</code>	Type boolean

Field	Details
	Properties Create, Filter, Update Description Indicates the visibility of the state field in the user's contact information. When <code>true</code>, state is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowStateToExternalUsers</code>, making the user's state visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowStreetAddressToExternalUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the street address field in the user's contact information. The address is visible only to internal members of the user's organization when this field is <code>false</code>. The address is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowStreetAddressToGuestUsers</code>	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the street address field in the user's contact information. When <code>true</code>, the street address field is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowStreetAddressToExternalUsers</code>, making the user's street address visible to guests. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 34.0 and later.

Field	Details
UserPreferencesShowTitleToExternalUsers	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the business title field in the user's contact information. Title is visible only to internal members of the user's organization when: - This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. Title is visible to external members in a community when: - This field is <code>true</code>, or - This field is <code>false</code> but <code>UserPreferencesShowTitleToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. The default value is <code>true</code>. This field is available in API version 26.0 and later.
UserPreferencesShowTitleToGuestUsers	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the business title field in the user's contact information. When <code>true</code>, title is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowTitleToExternalUsers</code>, making the user's title visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
UserPreferencesShowWorkPhoneToExternalUsers	Type boolean Properties Create, Filter, Update

Field	Details
	Description Indicates the visibility of the work phone number field in the user's contact information. The number is visible only to internal members of the user's organization when this field is <code>false</code>. The number is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
UserPreferencesShowWorkPhoneToGuestUsers	Type boolean Properties Create, Filter, Update Description Indicates the visibility of the work phone field in the user's contact information. When <code>true</code>, the work phone field is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowWorkPhoneToExternalUsers</code>, making the user's work phone visible to guests. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 34.0 and later.
UserPreferencesTaskRemindersCheckboxDefault	Type boolean Properties Create, Filter, Update Description When <code>true</code>, a reminder popup is automatically set on the user's tasks. Corresponds to the <code>By default, set reminder on Tasks to...</code> checkbox on the Reminders page in the user interface. This field is related to UserPreference and customizing activity reminders.
UserRoleId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the user's UserRole. Label is Role ID.

Field

Details

UserType

Type

picklist

Properties

Filter, Group, Nillable, Sort, Restricted picklist

Description

The category of user license. Each `UserType` is associated with one or more `UserLicense` records. Each `UserLicense` is associated with one or more profiles. In API version 10.0 and later, valid values include:

- Standard: user license. This user type also includes Salesforce Platform and Salesforce Platform One user licenses. Label is **Standard**.
 - PowerPartner: User whose access is limited because he or she is a partner and typically accesses the application through a partner portal or community. Label is **Partner**.
 - CSPLitePortal: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal or community. Label is **High Volume Portal**.
 - CustomerSuccess: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal. Label is **Customer Portal User**.
 - PowerCustomerSuccess: user whose access is limited because he or she is an organization's customer and accesses the application through a Customer Portal. Label is **Customer Portal Manager**.
- Users with this license type can view and edit data they directly own or data owned by or shared with users below them in the Customer Portal role hierarchy.
- CsnOnly: user whose access to the application is limited to Chatter. This user type includes Chatter Free and Chatter moderator users. Label is **Chatter Free**.

WirelessEmail

Type

email

Properties

Create, Filter, Group, Nillable, Sort, Update

Description

Wireless email address associated with this user. For use with Salesforce Wireless Edition. This field is available only if the Wireless and Email permissions are enabled for your organization.



Note: As of November 2005, Salesforce Wireless Edition is no longer available for purchase. If you are a Professional Edition customer and purchased Wireless Edition prior to November 7, 2005 or are an Enterprise Edition customer who has signed or

Field	Details
	renewed your Salesforce contract prior to November 7, 2005, you may continue using Wireless Edition through the end of your existing contract term.

Usage

Use this object to query information about users and to provision and modify users in your organization. Unlike other objects, the records in the User table represent actual users—not data owned by users. Any user can query or describe User records.

For example, the following SOQL code finds users with a particular user role.

```
SELECT Id, Username
FROM User
WHERE UserRoleId='00ED0000000xict'
```

Each portal user is associated with a portal account. A portal account can have a maximum of three portal roles (Executive, Manager, and User). You can select the default number of roles to be created from the user interface. The role hierarchy is maintained when you insert and delete portal roles, and roles are created bottom-up. Deleting the User role causes the Manager role to be renamed to User role. Deleting both the Executive and User roles causes the Manager role to be renamed to User role. Before deleting a role, you must assign users under that role to another role.

Deactivate Users

You can't delete a user in the user interface or the API. You can deactivate a user in the user interface; and you can deactivate or disable a Customer Portal or partner portal user in the user interface or the API. Because users can never be deleted, we recommend that you exercise caution when creating them.

If you deactivate a user, any EntitySubscription where the user is associated with the ParentId or SubscriberId field, meaning all subscriptions both to and from the user, are soft deleted. If the user is reactivated, the subscriptions are restored. However, if you deactivate multiple users at once and these users follow each other, their subscriptions are hard deleted. In this case, the user-to-user EntitySubscription is deleted twice (double deleted). Such subscriptions can't be restored upon user reactivation.

Passwords

For security reasons, you can't query User passwords via the API or the user interface. However, the API allows you to set and "reset" User passwords using the `setPassword()` and `resetPassword()` calls. The password lockout status and the ability to reset the User locked-out status is not available via the API. You must check and reset the User password lockout status using the user interface.

UserAccountTeamMember

Represents a User on the default account team of another User.

See also `OpportunityTeamMember`, which represents a User on the opportunity team of an Opportunity

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
<code>AccountAccessLevel</code>	Type picklist Properties Create, Filter, Restricted picklist, Update Description Required. For Account records that the user has added to his or her default account team, the level of access the account team member has. . The possible values are: • Read • Edit This field must be set to an access level that is higher than the organization's default access level for accounts.
<code>CaseAccessLevel</code>	Type picklist Properties Create, Filter, Restricted picklist, Update Description Required. Level of access that the account team member has to Case records related to the account. The possible values are: • None • Read • Edit This field must be set to an access level that is higher than the organization's default access level for cases.
<code>ContactAccessLevel</code>	Type picklist Properties Create, Filter, Restricted picklist, Update

Field	Details
	Description Required. For Contact records related to the account, the level of access that the account team member has. The possible values are: • None • Read • Edit This field must be set to an access level that is higher than the organization's default access level for contacts.  Note: When <code>DefaultContactAccess</code> is set to <code>Controlled by Parent</code>, you can't create or update this field.
OpportunityAccessLevel	Type picklist Properties Create, Filter, Restricted picklist, Update Description Required. Level of access that the team member has to Opportunity records related to the account. The possible values are: • None • Read • Edit This field must be set to an access level that is higher than the organization's default access level for opportunities.
OwnerId	Type reference Properties Create, Filter Description Required. ID of the User who owns the default account team.
TeamMemberRole	Type picklist Properties Create, Filter, Nillable, Update Description Role that the team member has on opportunities for which the user has added his or her default account team. The valid values are set by the organization's administrator in the Account Team Roles picklist. Label is Team Role.

Field	Details
UserId	Type reference
	Properties Create, Filter
	Description Required. ID of the User who is a member of the default account team. This field cannot be updated.

Usage

This object is available only in organizations that have enabled the account teams functionality, which can be done using the user interface.

If you attempt to create a record that matches an existing record, the create call updates any modified fields and returns the existing record.

You can set up a User record so the default account team includes the others who typically work with them on accounts.

UserConfigTransferButton

Represents the association between a Live Agent configuration and a live chat button. This association allows users associated with a specific configuration to transfer chats to a button queue.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
LiveChatButtonId	Type reference
	Properties Create, Filter, Group, Nillable, Sort
	Description The ID of the live chat button that agents can transfer chats to.
LiveChatUserConfigId	Type reference
	Properties Create, Filter, Group, Sort

Field Name	Details
	Description The ID of the Live Agent configuration; agents associated with this configuration can transfer chats to the chat button indicated by the <code>LiveChatButtonId</code> .

UserConfigTransferSkill

Represents the association between a Live Agent configuration and a skill. This association allows users associated with a specific configuration to transfer chats to agents who have that skill.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>LiveChatUserConfigId</code>	Type reference Properties Create, Filter, Group, Sort Description The ID of the Live Agent configuration; agents associated with this configuration can transfer chats to the chat button indicated by the <code>LiveChatButtonId</code> .
<code>SkillId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the skill group that agents can transfer chats to.

UserFeed

Represents a single feed item in the feed displayed on a Chatter user profile feed. A user profile feed shows changes to a user record for fields that are tracked in feeds, as well as posts and comments about the record.

A user feed shows recent changes to a user record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to users in the organization. This object is available in API version 18.0 and later.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

If you use the `FeedComment` object to comment on a user record, the user can delete the comment. For example, if John Smith makes a comment about Sasha Jones, Sasha can delete the comment.

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the User object
- "Moderate Chatter"



Note: Users with the "Moderate Chatter" permission can delete only the feed items and comments they see.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of UserFeed. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ConnectionId	Type reference Properties Filter, Group, Nillable, Sort Description When a <code>PartnerNetworkConnection</code> makes a change to a record that is tracked, the <code>CreatedBy</code> field contains the ID of the system administrator while the <code>ConnectionId</code> contains the ID of the <code>PartnerNetworkConnection</code> that made the change. Available if Salesforce to Salesforce is enabled for your organization.

Field	Details
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.

Field	Details
CreatedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type reference Properties Filter, Group, Nillable, Sort Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field.

Field	Details
	When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a <code>LinkPost</code>.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>: - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
ParentId	Type reference

Field	Details
	Properties Filter, Group, Sort Description ID of the account record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>.
Title	Type string Properties Group, Nillable, Sort Description The title of the user record. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group.

Field	Details
	• <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to <code>CaseFeed</code>: • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case  Note: If you set <code>Type</code> to <code>ContentPost</code>, you must specify <code>ContentData</code> and <code>ContentFileName</code>.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>Visibility</code> can have the following values: • <code>AllUsers</code>—The feed item is available to all users who have permission to see the feed item.

Field	Details
	InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: - For record posts, Visibility is set to InternalUsers for all internal users by default. - External users can set Visibility only to AllUsers. - On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to track changes for a user record.

UserLicense

Represents a user license in your organization. A user license entitles a user to specific functionality and determines the profiles and permission sets available to the user.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field	Details
<code>LicenseDefinitionKey</code>	Type string Properties Filter, Nillable Description A string that uniquely identifies a particular user license. Label is <code>License Def. ID</code>. Values are: AUL: corresponds to the Salesforce Platform user license AUL1: corresponds to the Salesforce Platform One user license AUL_LIGHT corresponds to the Salesforce Platform Light user license FDC_ONE corresponds to the Force.com - One App user license FDC_SUB corresponds to the Force.com App Subscription user license High Volume Customer Portal_User: corresponds to the High Volume Customer Portal user license

Field	Details
	Overage_Platform_Portal_User corresponds to the Overage Authenticated Website user license PID_STRATEGIC_PRM: corresponds to the Gold Partner user license PID_CHATTER corresponds to the Chatter Only user license PID_CONTENT corresponds to the Content Only user license PID_Customer_Portal_Basic: corresponds to the Customer Portal Manager Standard user license and the Customer Portal User license PID_Customer_Portal_Standard: corresponds to the Customer Portal Manager Custom user license PID_FDC_FREE corresponds to the Force.com Free user license PID_IDEAS corresponds to the Ideas Only user license PID_Ideas_Only_Portal corresponds to the Ideas Only Portal user license PID_Ideas_Only_Site corresponds to the Ideas Only Site user license PID_KNOWLEDGE corresponds to the Knowledge Only user license PID_Customer_Community corresponds to the Customer Community license. PID_Customer_Community_Login corresponds to the Customer Community Login license. PID_Partner_Community corresponds to the Partner Community license. PID_Partner_Community_Login corresponds to the Partner Community Login license. PID_Limited_Customer_Portal_Basic: corresponds to the Limited Customer Portal Manager Standard user license PID_Limited_Customer_Portal_Standard: corresponds to the Limited Customer Portal Manager Custom user license PID_Overage_Customer_Portal_Basic: corresponds to the Overage Customer Portal Manager Standard user license PID_Overage_High Volume Customer Portal corresponds to the Overage High Volume Customer Portal user license Platform_Portal_User: corresponds to the Authenticated Website user license POWER_PRM: corresponds to the Partner user license POWER_SSP: corresponds to the Customer Portal Manager user license SFDC: corresponds to the Full CRM user license
MasterLabel	Type string Properties Filter, Group, Sort Description The user license label.

Field	Details
	This field is available in API version 32.0 and later. This field is available through the API Access to User Licenses pilot program. For information on enabling this pilot program for your organization, contact Salesforce.
MonthlyLoginsEntitlement	Type int Properties Filter, Nillable Description The maximum number of customer or partner portal logins allowed per month. A <code>null</code> value in this field means the user license is charged according to the number of users rather than the number of logins. This field is available in API version 20.0 and later.
MonthlyLoginsUsed	Type int Properties Nillable Description The number of successful logins for all users associated with a customer or partner portal user license. This field has a non-<code>null</code> value if <code>MonthlyLoginsEntitlement</code> has a non-<code>null</code> value. This field is available in API version 20.0 and later.
Name	Type string Properties Filter, Group, Sort Description The internal name of the user license.  Note: Your organization may also include custom user licenses.
Status	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The current status of the user license. Valid values for this field are <code>Active</code> and <code>Disabled</code>. This field is available in API version 32.0 and later. This field is available through the API Access to User Licenses pilot program. For information on enabling this pilot program for your organization, contact Salesforce.

Field	Details
TotalLicenses	Type int Properties Filter, Group, Sort Description The number of user licenses in the organization. This field is available in API version 32.0 and later. This field is available through the API Access to User Licenses pilot program. For information on enabling this pilot program for your organization, contact Salesforce.
UsedLicenses	Type int Properties Filter, Group, Sort Description The number of user licenses that are assigned to active users in the organization. This field is available in API version 32.0 and later. This field is available through the API Access to User Licenses pilot program. For information on enabling this pilot program for your organization, contact Salesforce.

Usage

Users with the “View Setup and Configuration” permission can use the UserLicense object to view the set of currently defined user licenses in your organization.

The UserLicense object is currently used by bulk user creation to determine the user license to which each profile and permission set belongs. For example, if you use the API to create portal users and you want to know which profile belongs to each portal user license, you can query this object for each profile and check the `LicenseDefinitionKey` to identify the associated user license.

UserLogin

Represents the settings that affect a user’s ability to log into an organization. To access this object, you need the `UserPermissions.ManageUsers` permission. This object is available in API version 29.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
IsFrozen	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code> , the user account associated with this object is frozen.
IsPasswordLocked	Type boolean Properties Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code> , the user account associated with this object is locked because of too many login failures. From the API, you can set this field to <code>false</code> , but not <code>true</code> .
UserId	Type reference Properties Filter, Group, Nillable, Sort Description ID of the associated user account. This field can't be updated.

Usage

To query for all frozen users in your organization:

```
SELECT Id, UserId
FROM UserLogin
WHERE IsFrozen = true
```

UserMembershipSharingRule

Represents the rules for sharing user records from a source group to a target group. A user record contains details about a user. Users who are members of the source group can be shared with members of the target group. The source and target groups can be based on roles, portal roles, public groups, or territories. This object is available in API version 26.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`

Fields

Field	Details
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters. This field is available in API version 29.0 and later.
DeveloperName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Rule Name in the user interface.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label on the user interface.

Field	Details
UserAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing being allowed. The possible values are: • Read • Edit
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the target group being given access.

Usage

Use this object to manage sharing rules for user records. Source and target groups can include internal users, portal users, Chatter or Chatter External users.

UserPackageLicense

Represents a license for an installed managed package, assigned to a specific user. This object is available in API version 31.0 and later.

Supported Calls

`create()`, `delete()`, `query()`, `retrieve()`, `update()`

Fields

Field Name	Details
PackageLicenseId	Type reference Properties Filter, Group, Sort Description The 18-character Globally Unique ID (GUID) that identifies the package license

Field Name	Details
UserId	Type reference Properties Filter, Group, Sort Description The User ID of the user licensed to use this package

Usage

Use this object, in conjunction with PackageLicense, to provide users access to a managed package installed in your organization.

UserPreference

Represents a functional preference for a specific user in your organization.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
Preference	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the user preference. Supported values are Event Reminder Default Lead Time, Task Reminder Default Time, Prevent Logs on Load, Autocomplete Apex After Key Press, Visualforce Viewstate Inspector, Forecasting Displayed Type, Editor Theme, Editor Font Size, Pinned Folders, and Enable Query Plan. These values are related to UserPreferencesEventRemindersCheckboxDefault and UserPreferencesTaskRemindersCheckboxDefault on the User object. Enable New Open Dialog is reserved for future use.

Field	Details
UserId	Type reference Properties Filter, Group, Sort Description The ID of the user associated with this role. Label is User ID.
Value	Type string Properties Filter, Nillable, Sort Description The value of the user preference. For Event Reminder Default Lead Time, the values are increasing intervals of time from 0 minutes to 2 days. For Task Reminder Default Time, the values are half-hours from 12:00 AM to 11:30 PM. To view the respective sets of values, access the Reminders in your personal settings in the online application.

Usage

Use this object to query the set of currently configured user preferences in your organization. In your client application, you can query the User object to obtain valid User IDs in order to access the UserPreference object.

All users can invoke `query()` or `describeObjects()` with this object.

UserProfile

Represents a Chatter user profile.



Note: This object has been deprecated as of API version 34.0. Use the [User](#) object to query information about a user in API version 34.0 and later.

Supported Calls

`describeLayout()`, `query()`, `retrieve()`

Special Access Rules

- Information in hidden fields in a user's profile is not searchable by external users (with a portal profile) in a community. For example, if a user in a community has a hidden email address and an external user searches for it, the user record is not returned in the search results. Hidden field values are also not returned when external users perform searches on non-hidden fields. So if an external user searches for a user's name (cannot be hidden), any hidden field values associated with the user record (for example, a hidden email address) are not returned in the search results.

Internal users from your organization who belong to the same community, however, can both search for and view hidden field values in search results.

- Any fields that have been restricted in visibility will be returned empty, whether or not they are, and will not be removed from the field listing.

Fields

Field	Details
AboutMe	Type textarea Properties Filter, Nillable, Sort Description Information about the user, such as areas of interest or skills.
Address (beta)	Type address Properties Filter, Nillable Description The compound form of the address. Read-only. See Address Compound Fields for details on compound address fields.
City	Type string Properties Filter, Group, Nillable, Sort Description The city associated with the user profile.
CompanyName	Type string Properties Filter, Group, Nillable, Sort Description The company associated with the user profile.
Country	Type string Properties Filter, Group, Nillable, Sort

Field	Details
	Description The country associated with the user profile.
Email	Type email Properties Filter, Group, idLookup, Sort Description The email address associated with the user profile.
Fax	Type phone Properties Filter, Group, Nillable, Sort Description The fax number associated with the user profile.
FirstName	Type string Properties Filter, Group, Nillable, Sort Description The user's first name.
FullPhotoUrl	Type url Properties Filter, Nillable, Sort Description The URL for the user's profile photo if Chatter is enabled. The URL is updated every time a photo is uploaded and reflects the most recent photo. The URL returned for an older photo is not guaranteed to return a photo if a newer photo has been uploaded. You should always query this field for the URL of the most recent photo.
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort

Field	Details
	Description Indicates whether the user has access to log in (<code>true</code>) or not (<code>false</code>). You can modify a User's active status from the user interface or via the API.
IsBadged	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the user is visually badged (<code>true</code>) or not (<code>false</code>). Users of the same Chatter user type (internal, external) are badged. Different user types are not badged.
LastName	Type string Properties Filter, Group, Sort Description The user's last name.
Latitude (beta)	Type double Properties Filter, Nillable, Sort Description Used with <code>Longitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.
Longitude (beta)	Type double Properties Filter, Nillable, Sort Description Used with <code>Latitude</code> to specify the precise geolocation of an address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.
ManagerId	Type reference

Field	Details
	Properties Filter, Group, Nillable, Sort Description The ID of the user who manages this user.
MobilePhone	Type phone Properties Filter, Group, Nillable, Sort Description The user's mobile or cellular phone number.
Name	Type string Properties Filter, Group, Sort Description Concatenation of <code>FirstName</code> and <code>LastName</code>.
Phone	Type phone Properties Filter, Group, Nillable, Sort Description The user's phone number.
PostalCode	Type string Properties Filter, Group, Nillable, Sort Description The user's postal or ZIP code. Label is Zip/Postal Code.
SmallPhotoUrl	Type url Properties Filter, Nillable, Sort Description The URL for a thumbnail of the user's profile photo if Chatter is enabled.

Field	Details
	The URL is updated every time a photo is uploaded and reflects the most recent photo. The URL returned for an older photo is not guaranteed to return a photo if a newer photo has been uploaded. You should always query this field for the URL of the most recent photo.
State	Type string Properties Filter, Group, Nillable, Sort Description The state associated with the user profile.
Street	Type textarea Properties Filter, Group, Nillable, Sort Description The street address associated with the user profile.
Title	Type string Properties Filter, Group, Nillable, Sort Description The user's business title, such as "Vice President."
UserPreferencesActivityRemindersPopup	Type boolean Properties Filter Description When <code>true</code>, a reminder popup window automatically opens when an activity reminder is due. Corresponds to the <code>Trigger alert when reminder comes due</code> checkbox at the Reminders page in the personal settings in the user interface.
UserPreferencesApexPagesDeveloperMode	Type boolean Properties Filter

Field	Details
	Description When <code>true</code> , indicates the user has enabled developer mode for editing Visualforce pages and controllers.
<code>UserPreferencesDisableAllFeedsEmail</code>	Type boolean Properties Filter Description When <code>false</code> , the user automatically receives email for all updates to Chatter feeds, based on the types of feed emails and digests the user has enabled.
<code>UserPreferencesDisableBookmarkEmail</code>	Type boolean Properties Filter Description When <code>false</code> , the user automatically receives email every time someone comments on a Chatter feed item after the user has bookmarked it.
<code>UserPreferencesDisableChangeCommentEmail</code>	Type boolean Properties Filter Description When <code>false</code> , the user automatically receives email every time someone comments on a change the user has made, such as an update to their profile.
<code>UserPreferencesDisableEndorsementEmail</code>	Type boolean Properties Filter Description When <code>false</code> , the member automatically receives email every time someone endorses them for a topic.
<code>UserPreferencesDisableFeedbackEmail</code>	Type boolean

Field	Details
	Properties Filter Description When <code>false</code>, the user automatically receives emails related to Work.com feedback. This includes when someone requests or offers feedback, shares feedback with the user, or reminds the user to answer a feedback request.
UserPreferencesDisableFileShareNotificationsForApi	Type boolean Properties Filter Description When <code>false</code>, email notifications are sent from the person who has shared a file to the users with whom the file has been shared.
UserPreferencesDisableFollowersEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time someone starts following the user in Chatter.
UserPreferencesDisableLaterCommentEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time someone comments on a feed item after the user has commented on the feed item.
UserPreferencesDisableLikeEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time someone likes a post or comment the user has made.

Field	Details
UserPreferencesDisableMentionsPostEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time the user is mentioned in posts.
UserPreferencesDisableMessageEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email for Chatter messages sent to the user.
UserPreferencesDisableProfilePostEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time someone posts to the user's profile.
UserPreferencesDisableRewardEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives emails related to Work.com rewards. This includes when someone gives a reward to the user.
UserPreferencesDisableSharePostEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time the user's post is shared.

Field	Details
UserPreferencesDisableWorkEmail	Type boolean Properties Filter Description When <code>false</code>, the user receives emails related to Work.com feedback, goals, and coaching. The user must also sign up for individual emails listed on the Work.com email settings page. When <code>true</code>, the user will not receive any emails related to Work.com feedback, goals, or coaching even if they are signed up for individual emails.
UserPreferencesDisCommentAfterLikeEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time someone comments on a post the user has liked.
UserPreferencesDisMentionsCommentEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time the user is mentioned in comments.
UserPreferencesDisProfPostCommentEmail	Type boolean Properties Filter Description When <code>false</code>, the user automatically receives email every time someone comments on posts on the user's profile.
UserPreferencesEnableAutoSubForFeeds	Type boolean Properties Filter

Field	Details
	Description When <code>true</code> , the user automatically subscribes to feeds for any objects that the user creates.
<code>UserPreferencesEventRemindersCheckboxDefault</code>	Type boolean Properties Filter Description When <code>true</code> , a reminder popup is automatically set on the user's events. Corresponds to the <code>By default, set reminder on Events to...</code> checkbox on the Reminders page in the user interface. This field is related to UserPreference and customizing activity reminders.
<code>UserPreferencesHideChatterOnboardingSplash</code>	Type boolean Properties Filter Description When <code>true</code> , the initial Chatter onboarding prompts do not appear.
<code>UserPreferencesHideCSNDesktopTask</code>	Type boolean Properties Filter Description When <code>true</code> , the Chatter recommendations panel never displays the recommendation to install Chatter Desktop.
<code>UserPreferencesHideCSNGetChatterMobileTask</code>	Type boolean Properties Filter Description When <code>true</code> , the Chatter recommendations panel never displays the recommendation to install Chatter Mobile.
<code>UserPreferencesHideS1BrowserUI</code>	Type boolean Properties Filter

Field	Details
	Description Controls the interface that the user sees when logging in to Salesforce from a supported mobile browser. If <code>false</code>, the user is automatically redirected to the Salesforce1 mobile browser app. If <code>true</code>, the user sees the full Salesforce site. The default value is <code>false</code>. Label is Salesforce1 User. This field is available in API version 29.0 or later.
UserPreferencesHideSecondChatterOnboardingSplash	Type boolean Properties Filter Description When <code>true</code>, the secondary Chatter onboarding prompts do not appear.
UserPreferencesReminderSoundOff	Type boolean Properties Filter Description When <code>true</code>, a sound automatically plays when an activity reminder is due. Corresponds to the <code>Play a reminder sound</code> checkbox on the Reminders page in the user interface.
UserPreferencesShowCityToExternalUsers	Type boolean Properties Filter Description Indicates the visibility of the city field in the user's contact information. City is visible only to internal members of the user's organization when: - This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. City is visible to external members in a community when: - This field is <code>true</code>, or - This field is <code>false</code> but <code>UserPreferencesShowCityToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses.

Field	Details
	The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowCityToGuestUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the city field in the user's contact information. When <code>true</code>, city is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowCityToExternalUsers</code>, making the user's city visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowCountryToExternalUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the country field in the user's contact information. Country is visible only to internal members of the user's organization when: - This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. Country is visible to external members in a community when: - This field is <code>true</code>, or - This field is <code>false</code> but <code>UserPreferencesShowCountryToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowCountryToGuestUsers</code>	Type boolean

Field	Details
	Properties Filter Description Indicates the visibility of the country field in the user's contact information. When <code>true</code>, country is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowCountryToExternalUsers</code>, making the user's country visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowEmailToExternalUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the email address field in the user's contact information. Email address is visible only to internal members of the user's organization when this field is <code>false</code>. Email address is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowFaxToExternalUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the fax number field in the user's contact information. Fax number is visible only to internal members of the user's organization when this field is <code>false</code>. Fax number is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.

Field	Details
UserPreferencesShowManagerToExternalUsers	Type boolean Properties Filter Description Indicates the visibility of the manager field in the user's contact information. Manager is visible only to internal members of the user's organization when this field is <code>false</code>. Manager is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
UserPreferencesShowMobilePhoneToExternalUsers	Type boolean Properties Filter Description Indicates the visibility of the mobile or cellular phone number field in the user's contact information. The number is visible only to internal members of the user's organization when this field is <code>false</code>. The number is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
UserPreferencesShowPostalCodeToExternalUsers	Type boolean Properties Filter Description Indicates the visibility of the postal or ZIP code field in the user's contact information. Postal code is visible only to internal members of the user's organization when: • This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. Postal code is visible to external members in a community when: • This field is <code>true</code>, or • This field is <code>false</code> but <code>UserPreferencesShowPostalCodeToGuestUsers</code> is <code>true</code>, which overrides this field's value.

Field	Details
	External users are users with Community, Customer Portal, or partner portal licenses. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowPostalCodeToGuestUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the postal or ZIP code field in the user's contact information. When <code>true</code>, postal code is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowPostalCodeToExternalUsers</code>, making the user's postal code visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowProfilePicToGuestUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the user's profile photo. When <code>true</code>, the photo is visible to guest users in a community. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the stock photo. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowStateToExternalUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the state field in the user's contact information. State is visible only to internal members of the user's organization when:

Field	Details
	- This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. State is visible to external members in a community when: - This field is <code>true</code>, or - This field is <code>false</code> but <code>UserPreferencesShowStateToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
<code>UserPreferencesShowStateToGuestUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the state field in the user's contact information. When <code>true</code>, state is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowStateToExternalUsers</code>, making the user's state visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
<code>UserPreferencesShowStreetAddressToExternalUsers</code>	Type boolean Properties Filter Description Indicates the visibility of the street address field in the user's contact information. The address is visible only to internal members of the user's organization when this field is <code>false</code>. The address is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.

Field	Details
UserPreferencesShowTitleToExternalUsers	Type boolean Properties Filter Description Indicates the visibility of the business title field in the user's contact information. Title is visible only to internal members of the user's organization when: • This field is <code>false</code>. When <code>false</code>, this field returns the value <code>#N/A</code>. Title is visible to external members in a community when: • This field is <code>true</code>, or • This field is <code>false</code> but <code>UserPreferencesShowTitleToGuestUsers</code> is <code>true</code>, which overrides this field's value. External users are users with Community, Customer Portal, or partner portal licenses. The default value is <code>true</code>. This field is available in API version 26.0 and later.
UserPreferencesShowTitleToGuestUsers	Type boolean Properties Filter Description Indicates the visibility of the business title field in the user's contact information. When <code>true</code>, title is visible to guest users. Guest users can access public Site.com and Force.com sites, and public pages in Communities, via the Guest User license associated with each site or community. When <code>false</code>, this field returns the value <code>#N/A</code>. When <code>true</code>, this field overrides the value <code>false</code> in <code>UserPreferencesShowTitleToExternalUsers</code>, making the user's title visible to external members. The default value is <code>false</code>. This field is available in API version 28.0 and later.
UserPreferencesShowWorkPhoneToExternalUsers	Type boolean Properties Filter

Field	Details
	Description Indicates the visibility of the work phone number field in the user's contact information. The number is visible only to internal members of the user's organization when this field is <code>false</code>. The number is visible to external members in a community when this field is <code>true</code>. External users are users with Community, Customer Portal, or partner portal licenses. When <code>false</code>, this field returns the value <code>#N/A</code>. The default value is <code>false</code>. This field is available in API version 26.0 and later.
UserPreferencesTaskRemindersCheckboxDefault	Type boolean Properties Filter Description When <code>true</code>, a reminder popup is automatically set on the user's tasks. Corresponds to the <code>By default, set reminder on Tasks to...</code> checkbox on the Reminders page in the user interface. This field is related to UserPreference and customizing activity reminders.

Usage

Use this object to query Chatter—related information about the user. While the User object contains all the information about a user and is historically tied to user management, UserProfile is a read-only entity that contains the information that is relevant in a Chatter context.

UserProfileFeed

Represents a user profile feed, which tracks all actions by a user on records that can be tracked in a feed. This feed is displayed on the user profile page.

UserProfileFeed is available in API version 18.0 through API 26.0. In API version 27.0 and later, UserProfileFeed is no longer available in the SOAP API. Use the Chatter REST API to access UserProfileFeed.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items you created. To delete feed items you didn't create, you must have one of these permissions:

- "Modify All Data"

- “Moderate Chatter”



Note: Users with the “Moderate Chatter” permission can delete only the feed items and comments they see.

- “Manage Unlisted Groups”

Only users with this permission can delete items in unlisted groups.

Fields

Field	Details
Body	Type textarea Properties Nillable, Sort Description The content of UserProfileFeed. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string

Field	Details
	Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type <code>int</code> Properties <code>Group, Nillable, Sort</code> Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type <code>string</code> Properties <code>Group, Nillable, Sort</code> Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
CreatedDate	Type <code>dateTime</code> Properties Defaulted on create, Filter, Sort Description Date and time when this record was created. This is a standard system field. Ordering by <code>CreatedDateDESC</code> sorts the feed by the most recent feed item.
FeedPostId	Type <code>reference</code> Properties <code>Filter, Group, Nillable, Sort</code> Description This field was removed in API version 22.0, and is available in earlier versions for backward compatibility only. ID of the associated FeedPost. A FeedPost represents the following types of changes in an <code>FeedItem</code>: changes to tracked fields, text posts, link posts, and content posts.

Field	Details
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then the <code>InsertedBy</code> value is set to the ID of the logged-in user.
IsDeleted	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the record has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). This is a standard system field.
LastModifiedDate	Type dateTime Properties Defaulted on create, Filter, Sort Description Date and time when this record was last modified by a user. This is a standard system field. When a feed item is created, <code>LastModifiedDate</code> is the same as <code>CreatedDate</code>. If a <code>FeedComment</code> is inserted on that feed item, then <code>LastModifiedDate</code> becomes the <code>CreatedDate</code> for that <code>FeedComment</code>. Deleting the <code>FeedComment</code> does not change the <code>LastModifiedDate</code>. Ordering by <code>LastModifiedDate DESC</code> sorts the feed by both the most recent feed item or comment.
LikeCount	Type int Properties Filter, Group, Sort Description The number of <code>FeedLikes</code> associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort

Field	Details
	Description The URL of a <code>LinkPost</code> .
<code>NetworkScope</code>	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community , a specific community, or all communities. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. <code>NetworkScope</code> can have the following values: <code>NetworkId</code>—The ID of the community in which the <code>FeedItem</code> is available. If left empty, the feed item is only available in the default community. <code>AllNetworks</code>—The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code> : - Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
<code>ParentId</code>	Type reference Properties Filter, Group, Sort Description ID of the account record that is tracked in the feed. The feed is displayed on the detail page for this record.
<code>RelatedRecordId</code>	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code> . This field is null for all posts except <code>ContentPost</code> .
<code>Title</code>	Type string

Field	Details
	Properties Group, Nillable, Sort Description The title of the user profile record. When the <code>Type</code> is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item: • <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • <code>AdvancedTextPost</code>—created when a user posts a group announcement. • <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field.

Field	Details
	• UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • CaseCommentPost—generated event when a user adds a case comment for a case object • EmailMessageEvent—generated event when an email related to a case object is sent or received • CallLogPost—generated event when a user logs a call for a case through the user interface. This event is also generated by CTI calls. • ChangeStatusPost—generated event when a user changes the status of a case • AttachArticleEvent—generated event when a user attaches an article to a case  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available to all users or internal users only. This field is available in API version 26.0 and later, if Salesforce Communities is enabled for your organization. Visibility can have the following values: • AllUsers—The feed item is available to all users who have permission to see the feed item. • InternalUsers—The feed item is available to internal users only. Note the following exceptions for Visibility: • For record posts, Visibility is set to InternalUsers for all internal users by default. • External users can set Visibility only to AllUsers. • On user and group posts, only internal users can set Visibility to InternalUsers.

Usage

Use this object to query and retrieve record changes tracked in a user profile feed. Note the following when working with user profile feeds:

- This object is read only in the API.
- Queries retrieve feed items that include mentions from other users.
- Use this object to query and retrieve lead feed items that were associated with a converted lead record.

- You must include a `WITH` clause and specify the `UserId` of the user whose profile you want to query. The `WITH` clause must come after a `WHERE` clause.

Users that do not have the “View All Data” permission have the following limitations when querying records:

- Must specify a `LIMIT` clause and the limit must be less than or equal to 1000.
- May include a `WHERE` clause that references `UserProfileFeed` fields, but may not include references to fields in related objects. For example, you can filter by `CreatedDate` or `ParentId`, but not by `Parent.Name`.
- May include an `ORDER BY` clause that references `UserProfileFeed` fields, but may not include references to fields in related objects. For example, you can `ORDER BY CreatedDate` or `ParentId`, but not by `Parent.Name`.

 **Tip:** To query for the most recent feed items, you should `ORDER BY CreatedDate DESC, Id DESC`.

Note the following SOQL restrictions.

- No SOQL limit if logged-in user has “View All Data” permission. If not, specify a `LIMIT` clause of 1,000 records or fewer.
- SOQL `ORDER BY` on fields using relationships is not available. Use `ORDER BY` on fields on the root object in the SOQL query.

UserProvAccount

Represents information that links a Salesforce user account with an account in a third-party (target) system, such as Google, for users of connected apps with Salesforce user provisioning enabled.

The `UserProvAccount` object is available in API version 33.0 and later.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
<code>ConnectedAppId</code>	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The 15 character application ID.
<code>DeletedDate</code>	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The date and time when the associated user account in the target system was deleted. This value is automatically updated during the provisioning and reconciling processes.

Field	Details
ExternalEmail	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The email address as stored in the target system for the associated user account.
ExternalFirstName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The first name as stored in the target system for the associated user account.
ExternalLastName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The last name as stored in the target system for the associated user account.
ExternalUserId	Type string Properties Create, Filter, Group, idLookup, Nillable, Sort, Update Description The unique identifier for the user as stored in the target system.
ExternalUsername	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The username as stored in the target system for the associated user account.
IsKnownLink	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Details
	Description Setting the <code>IsKnownLink</code> value to <code>true</code> implies the administrator or another user is managing the relationship between the Salesforce user account and the third-party user account, manually. This field helps Salesforce coordinate updates between the <code>UserProvAccountStaging</code> object and the <code>UserProvAccount</code> object while committing staged accounts. Typically, for a matching user account (the same <code>ExternalUserId</code> for both objects), Salesforce copies the values from the <code>UserProvAccountStaging</code> object to the <code>UserProvAccount</code> object. However, if Salesforce encounters a <code>UserProvAccountStaging</code> object with a matching <code>ExternalUserId</code> but different <code>LinkState</code> and <code>SalesforceUserId</code> values during this process, Salesforce checks the <code>UserProvAccount</code> <code>IsKnownLink</code> value. If the <code>IsKnownLink</code> value is <code>true</code>, Salesforce doesn't copy the <code>LinkState</code> and <code>SalesforceUserId</code> values from the <code>UserProvAccountStaging</code> object to the <code>UserProvAccount</code> object (all other values are copied). The default is <code>false</code>, meaning Salesforce manages the account relationship.
LinkState	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The state of the current connection between the user account in the Salesforce organization and the associated user account in the target system. The valid values are: • <code>linked</code>— changes to the account in the Salesforce organization are queued to be updated for the associated user account in the target system. • <code>duplicate</code>— an associated account in the target system exists. • <code>orphaned</code>—no associated account exists in the target system. • <code>ignored</code>— changes to the account in the Salesforce organization have no effect on the associated user account in the target system.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The unique name for this object.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Namepointing, Sort, Update

Field	Details
	Description The user ID of the owner of this object—typically a Salesforce administrator.
SalesforceUserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The user ID for the user account in the Salesforce organization that is associated with the user account in the target system.
Status	Type picklist Properties Create, Filter, Group, Sort, Update Description The status of the account in the target system. The valid values are: • Active • Deactivated • Deleted

UserProvAccountStaging

Temporarily stores user account information while a user completes the User Provisioning Wizard. This information that is stored in the UserProvAccount object when you click the button to collect and analyze accounts on the target system.

User provisioning links a Salesforce user account with an account in a third-party (target) system. To configure user provisioning, you use a User Provisioning Wizard that guides you through the setup process. As you enter values about account details in the wizard, these values are stored in this object until you click the button to collect and analyze accounts on the target system. The general user provisioning configuration details are stored in the UserProvisioningConfig object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
ConnectedAppId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The 15 character connected app ID.
ExternalEmail	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The email address as stored in the target system for the associated user account.
ExternalFirstName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The first name as stored in the target system for the associated user account.
ExternalLastName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The last name as stored in the target system for the associated user account.
ExternalUserId	Type string Properties Create, Filter, Group, idLookup, Nillable, Sort, Update Description The unique identifier for the user as stored in the target system.
ExternalUsername	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The username as stored in the target system for the associated user account.

Field Name	Details
LinkState	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The state of the current connection between the user account in the Salesforce organization and the associated user account in the target system. The valid values are: • <code>linked</code>— a user account matches one in the target system. • <code>duplicate</code>— an associated account in the target system exists. • <code>orphaned</code>—no associated account exists in the target system. • <code>ignored</code>— changes to the account in the Salesforce organization have no effect on the associated user account in the target system.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The unique name for this object.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The user ID of the owner of this object—typically a Salesforce administrator.
SalesforceUserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The user ID for the user account in the Salesforce organization that is associated with the user account in the target system.
Status	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update

Field Name	Details
	Description The status of the account in the target system. The valid values are: • Active • Deactivated • Deleted

Usage

When committing fields from a `UserProvAccountStaging` to a `UserProvAccount` object, Salesforce looks up the `UserProvAccount` record where `UserProvAccountStaging.ExternalUserId = UserProvAccount.ExternalUserId`.

- If an `ExternalUserId` doesn't match an existing account, Salesforce creates a `UserProvAccount` record based on the `UserProvAccountStaging` record.
- If an `ExternalUserId` matches, then Salesforce checks the `UserProvAccount.isKnownLink` value, and does the following.
 - If `UserProvAccount.isKnownLink = true`, Salesforce copies the `UserProvAccountStaging` values to the `UserProvAccount` object, except for the `ExternalUserId` and `LinkState` values.
 - If `UserProvAccount.isKnownLink = false`, Salesforce copies all of the `UserProvAccountStaging` values to the `UserProvAccount` object.

UserProvMockTarget

Represents an entity for testing user data before committing the data to a third-party system for user provisioning.

During the user provisioning process, user account information is sent to a third-party system to create, update or delete a user account on that system. While configuring user provisioning for your organization using a flow or Apex plugin, you can use this object to confirm the associated flow or plugin is sending the desired data. After confirming the correct fields and values, you can update the flow or Apex plugin to send the data to the target system.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>ExternalEmail</code>	Type string Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The email address as stored in the target system for the associated user account.
ExternalFirstName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The first name as stored in the target system for the associated user account.
ExternalLastName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The last name as stored in the target system for the associated user account.
ExternalUserId	Type string Properties Create, Filter, Group, idLookup, Nillable, Sort, Update Description The unique identifier for the user as stored in the target system.
ExternalUsername	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The username as stored in the target system for the associated user account.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The unique name for this object.
OwnerId	Type reference

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update
	Description The user ID of the owner of this object—typically a Salesforce administrator.

UserProvisioningConfig

Represents information for a flow to use during a user provisioning request process, such as the attributes for an update. The values of this object are read-only.

The UserProvisioningConfig object is available in API version 34.0 and later.

Supported Calls

`describeSObjects()`, `query()`, `retrieve()`

Fields

Field Name	Details
ApprovalRequired	Type textarea Properties Nillable Description Denotes whether approvals are required for provisioning users for the associated connected app. If the value is null, no approval is required.
ConnectedAppId	Type reference Properties Filter, Group, Nillable, Sort Description The 18-digit application ID for the connected app.
DeveloperName	Type string Properties Filter, Group, Sort

Field Name	Details
	Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package, and the changes are reflected in a subscriber's organization.
Enabled	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether user provisioning is enabled for the associated connected app (<code>true</code>) or not (<code>false</code>).
EnabledOperations	Type textarea Properties Nullable Description Lists the operations, as comma-separated values, that create a <code>UserProvisioningRequest</code> object for the associated connected app. Allowed values are: • <code>Create</code> • <code>Update</code> • <code>EnableAndDisable</code> (activation and deactivation) • <code>SuspendAndRestore</code> (freeze and unfreeze)
Language	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The two- to five-character code that represents the language and locale ISO. This controls the language for labels displayed in an application.
LastReconDateTime	Type dateTime

Field Name	Details
	Properties Filter, Nillable, Sort Description The date and time when user accounts were last reconciled between Salesforce and the target system.
MasterLabel	Type string Properties Filter, Group, Sort Description The master label for this object. This value is the internal label that doesn't get translated.
NamedCredentialId	Type reference Properties Filter, Group, Nillable, Sort Description The unique API name for the named credential uses for a request. The named credential identifies the third-party system and the third-party authentication settings.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.

Field Name	Details
Notes	Type textarea Properties Nillable Description A utility field for administrators to add any additional information about the configuration. This field is for internal reference only, and is not used by any process.
OnUpdateAttributes	Type textarea Properties Nillable Description Lists the user attributes, as comma-separated values, that generate a UserProvisioningRequest object during an update.
ReconFilter	Type string Properties Filter, Group, Nillable, Sort Description When collecting and analyzing users on a third-party system, the plug-in uses this filter to limit the scope of the collection.
UserAccountMapping	Type textarea Properties Nillable Description Stores the attributes used to link the Salesforce user to the account on the third-party system, in JSON format. For example: <pre>{ "linkingSalesforceUserAttribute": "Username", "linkingTargetUserAttribute": "Email" }</pre>

UserProvisioningLog

Represents messages generated during the process of provisioning users for third-party applications.

Some messages for this object are generated automatically by Salesforce, and others are created by the developers of the user provisioning plugin. Developers can use this object to log messages from the flow associated with the user provisioning process or the Apex plugin that calls the target system. Administrators can use this object as a log of all user provisioning activity and as a troubleshooting tool if desired behavior is missing. This object is available as a custom report type.

The UserProvisioningLog object is available in API version 33.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Details	Type textarea Properties Create, Nillable, Update Description The value of this field depends on the log entry. For example, if the target system returns an error, the error message may be recorded in this field.
ExternalUserId	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique identifier for the user in the target system.
ExternalUsername	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The username set in the target system for the associated user account.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The unique name for this object.

Field	Details
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Salesforce ID of the Group or User who owns this object.
Status	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The status of the user provisioning request. Based on the context of the log, it can contain different values, such as an HttpStatusCode.
UserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Salesforce ID of the user making the request.
UserProvisioningRequestId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description A unique identifier for the user provisioning request.

UserProvisioningRequest

The UserProvisioningRequest standard object represents an individual provisioning request for a single user.

Represents an individual provisioning request to create, update or delete a user account in a third-party service system (or another Salesforce organization). A UserProvisioningRequest object is created for each provisioning action (such as creating, updating or deleting a user account) for each user, and for each connected app available to the user. For example, if a user has two connected apps, and a provisioning request is sent to two different services to create an account for the user, Salesforce creates two UserProvisioningRequest objects.

The UserProvisioningRequest object is available in API version 33.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AppName	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the connected app associated with the service provider.
ApprovalStatus	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The status of the approval for the current request. If the user provisioning setup for the connected app does not have an approval process enabled, the status is <code>Not Required</code>. If an approval process is enabled, supported values are: • <code>Required</code>— An approval process is enabled in the user provisioning configuration for the associated connected app, but there is no response to the request yet. • <code>Not Required</code>— An approval process is not enabled in the user provisioning configuration for the associated connected app. • <code>Approved</code> • <code>Denied</code>
ConnectedAppId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The eighteen digit application ID for the connected app.
ExternalUserId	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The unique identifier for the user in the target system.

Field	Details
ManagerId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Salesforce ID of the user who manages the user specified in the <code>SalesforceUserId</code> field. If an approval process is configured for the user provisioning request, this value allows the manager to approve the request. Available in API version 34.0 and later.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The unique name for this object.
Operation	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The Apex method called by the trigger associated with the provisioning request (typically a change to the User object). Supported values are: • Create • Read • Update • Deactivate • Activate • Freeze • Unfreeze • Reconcile • Linking For example, when the User object field <code>isActive</code> is set to <code>false</code>, the UserProvisioningRequest object <code>Operation</code> field value is set to <code>Deactivate</code>.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field	Details
	Description Salesforce ID of the Group or User who owns this object.
SalesforceUserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Salesforce ID of the user making the request.
ScheduleDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description When to send this request to the service provider.  Note: Scheduling is not implemented yet. Currently, provisioning changes are queued immediately to be sent to the service provider.
State	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Status of this request. Supported values are: • New • Requested • Completed • Failed • Collecting • Collected • Analyzing • Analyzed • Committing The State goes from New to Requested to Completed or Failed, unless a reconciliation process is occurring. For details about the reconciliation process State value changes, see Usage .
UserProvAccountId	Type reference

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update
	Description The ID value of the associated UserProvAccount object.
UserProvConfigId	Type reference
	Properties Create, Filter, Group, Nillable, Sort, Update
	Description The ID value of the associated UserProvisioningConfig object. Available in API version 34.0 and later.

Usage

The `State` value changes during a reconciliation process (`Operation = Reconcile`) to gather and compare users on the third-party system to Salesforce users. Typically, when a `UserProvisioningRequest` entry is first created, it has a `State` value of `New`. When a collection process is triggered, the `State` transitions to `Collecting` until that process is finished and the `State` is `Collected`. When an analyze process is triggered, the `State` transitions to `Analyzing` until that process is finished and the `State` is `Analyzed`. If a process commits the request, the `State` then transitions to `Committing`, and the properties move from the `UserProvAccountStaging` object to the `UserProvAccount` object. When those properties are saved in the `UserProvAccount` object, the `State` transitions to `Completed`.

However, the `State` does not necessarily start at `New`. For example, `UserProvAccountStaging` entries can be inserted programmatically. If a process is initiated that triggers linking these rows to accounts on the third-party service, a `UserProvisioningRequest` entry could start with the `Analyzing` `State`.

Also, the `State` cannot go backwards from an active task. For example, a successful `Analyzing` `State` must progress to `Analyzed`; unless the active process fails, and then the `State` must change to `Failed`. Certain `State` transitions cannot be made programmatically and must be triggered by Salesforce.

The following table shows the `State` transitions that can occur for each `State` value. Each row corresponds to a current `State` value and each column corresponds to a new `State` after a potential transition.

-  — the transition to this value is not allowed.
-  — the transition to this value is allowed.
-  — only Salesforce can transition the `State` to this value.

	New	Requested	Collecting	Collected	Analyzing	Analyzed	Committing	Completed	Failed
New									
Requested									
Collecting									
Collected									

	New	Requested	Collecting	Collected	Analyzing	Analyzed	Committing	Completed	Failed
Analyzing	✖	✖	✖		✓				
Analyzed	✖	✖	✖	✖	✖	✓	✓	✓	✓
Committing	✖	✖	✖	✖	✖		✓		
Completed	✖	✖	✖	✖	✖	✖	✖	✓	✖
Failed	✖	✖	✖	✖	✖	✖	✖	✖	✓

UserProvisioningRequestOwnerSharingRule

Represents a rule for sharing a UserProvisioningRequest object with users other than the owner.

The UserProvAccountOwnerSharingRule object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing allowed. The possible values are: - Read - Edit
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description A description of the sharing rule. Maximum size is 1000 characters.
DeveloperName	Type string

Field Name	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization.  Note: When creating large sets of data, always specify a unique <code>DeveloperName</code> for each record. If no <code>DeveloperName</code> is specified, performance may slow while Salesforce generates one for each record.
GroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the source group. UserProvisioningRequest objects owned by users in the source group trigger the rule to give access.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Label of the sharing rule as it appears in the user interface. Limited to 80 characters. Corresponds to Label in the user interface.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID representing the target user or group. Target users or groups have access to the UserProvisioningRequest object.

UserProvisioningRequestShare

Represents a sharing entry on a UserProvisioningRequest record.

This object is available in API version 34.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccessLevel</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description A value that represents the type of sharing allowed. The possible values are: • Read • Edit
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the parent record, if any.
<code>RowCause</code>	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description Reason that this sharing entry exists. Values may include: • <code>Manual</code>—The User or Group has access because a user with “All” access manually shared the <code>UserProvisioningRequest</code> record with them. • <code>Owner</code>—The User is the owner of the <code>UserProvisioningRequest</code> record or is in a role above the <code>UserProvisioningRequest</code> record owner in the role hierarchy.
<code>UserOrGroupId</code>	Type reference Properties Create, Filter, Group, Sort

Field Name	Details
	Description ID of the User or Group that has been given access to the UserProvisioningRequest record.

UserRecordAccess

Represents a user's access to a set of records. This object is read only and is available in API version 24.0 and later.

Supported Calls

`describeSObjects(), query()`

Fields

Field	Details
HasAllAccess	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a user can share the record.
HasDeleteAccess	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a user has delete access to the record (<code>true</code>) or not (<code>false</code>).
HasEditAccess	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a user has edit access to the record (<code>true</code>) or not (<code>false</code>).
HasTransferAccess	Type boolean

Field	Details
	Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a user has transfer access to the record (<code>true</code>) or not (<code>false</code>).
HasReadAccess	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether a user has read access to the record (<code>true</code>) or not (<code>false</code>).
MaxAccessLevel	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Indicates a user's maximum level of access to a record. Valid values are: • None • Read • Edit • Delete • Transfer • All
RecordId	Type picklist Properties Filter, Group, Restricted picklist, Sort Description ID of the record.
UserId	Type reference Properties Filter, Group Description ID of the user.

Usage

Use this object to query a user's access to records. You can't create, delete, or update any records using this object.

Up to 200 record IDs can be queried. You can include an `ORDER BY` clause for any field that is being selected in the query.

The following sample query returns the records, whether the queried user has read and transfer access to each record, and the user's maximum access level to each record.

```
SELECT RecordId, HasReadAccess, HasTransferAccess, MaxAccessLevel
  FROM UserRecordAccess
 WHERE UserId = [single ID]
 AND RecordId = [single ID]           //or Record IN [list of IDs]
```

The following query returns the records to which a queried user has read access.

```
SELECT RecordId
  FROM UserRecordAccess
 WHERE UserId = [single ID]
 AND RecordId = [single ID]           //or Record IN [list of IDs]
 AND HasReadAccess = true
```

Using API version 30.0 and later, `UserRecordAccess` is a foreign key on the records. You can't filter by or provide the `UserId` or `RecordId` fields when using this object as a lookup or foreign key. The previous sample queries can be run as:

```
SELECT Id, Name, UserRecordAccess.HasReadAccess, UserRecordAccess.HasTransferAccess,
       UserRecordAccess.MaxAccessLevel
  FROM Account
```

```
SELECT Id, Name, UserRecordAccess.HasReadAccess
  FROM Account
```

SOQL restrictions for API version 29.0 and earlier:

- When the running user is querying a user's access to a set of records, records that the running user does not have read access to are filtered out of the results.
- When filtering by `UserId` and `RecordId` only, you must use `SELECT RecordId` and optionally one or more of the access level fields: `HasReadAccess`, `HasEditAccess`, `HasDeleteAccess`, `HasTransferAccess`, and `HasAllAccess`. You may include `MaxAccessLevel`.
- When filtering by `UserId`, `RecordId`, and an access level field, you must use `SELECT RecordId` only.

UserRole

Represents a user role in your organization.



Note: This object was called "Role" in previous versions of the API documentation.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
CaseAccessForAccountOwner	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The case access level for the account owner.
ContactAccessForAccountOwner	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The contact access level for the account owner.  Note: When DefaultContactAccess is set to Controlled by Parent, you can't create or update this field.
DeveloperName	Type string Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The unique name of the object in the API. This name can contain only underscores and alphanumeric characters, and must be unique in your organization. It must begin with a letter, not include spaces, not end with an underscore, and not contain two consecutive underscores. In managed packages, this field prevents naming conflicts on package installations. With this field, a developer can change the object's name in a managed package and the changes are reflected in a subscriber's organization. Corresponds to Role Name in the user interface. This field is available in API version 24.0 and later.  Note: When creating large sets of data, always specify a unique DeveloperName for each record. If no DeveloperName is specified, performance may slow while Salesforce generates one for each record.

Field	Details
ForecastUserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the forecast manager associated with this role. Label is User ID.
IsPartner	Type boolean Properties Defaulted on create, Filter Description Indicates whether the user role is a partner who has access to the partner portal (<code>true</code>) or not (<code>false</code>). This field is not available for release 9.0 and later. Instead, use <code>PortalType</code> with the value <code>Partner</code>.
MayForecastManagerShare	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the forecast manager can manually share their own forecast.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name of the role. Corresponds to Label on the user interface.
OpportunityAccessForAccountOwner	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. The opportunity access level for the account owner. Note that you can't set a user role with an opportunity access less than that specified in organization-wide defaults.
ParentRoleId	Type reference

Field	Details
	Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the parent role.
PortalRole	Type picklist Properties Filter, Nillable Description The portal role: Executive, Manager, User, or PersonAccount.
PortalType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description This value indicates the type of portal for the role: • None: Salesforce application role. • CustomerPortal: Customer portal role. • Partner: partner portal role. The field <code>IsPartner</code> used in release 8.0 will map to this value. This field replaces <code>IsPartner</code> beginning with release 9.0.
RollupDescription	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Description of the forecast rollup. Label is Description .

Usage

Use this object to query the set of currently configured user roles in your organization. Use it in your client application to obtain valid UserRole IDs to use when querying or modifying a User record.

All users have access to invoke query or describe this object. If your client application logs in with the “Manage Users” permission, it can query, create, update, or delete UserRole records.

 **Note:** You can’t update any field for a portal role.

For example, the following code finds all roles that are not assigned to any users.

```
SELECT Id, Name, DeveloperName,
FROM UserRole
WHERE Id NOT IN (SELECT UserRoleId
                  FROM User
                  WHERE UserRoleId != '0000000000000000')
```

UserServicePresence

Represents a presence user’s real-time presence status. This object is available in API version 32.0 and later.

Supported Calls

query(), getDeleted(), getUpdated(), retrieve()

Fields

Field	Details
Capacity	Type double Properties Create, Filter, Group, Sort, Update Description The user’s capacity to take on work items.
Name	Type string Properties Create, Filter, Nillable, Sort, Update Description An automatically generated ID number that identifies the record.
ServicePresenceStatusId	Type reference Properties Create, Filter, Nillable, Sort, Update Description The ID of the presence status that’s associated with the presence user that’s specified by the <code>UserId</code>.
UserId	Type string

Field	Details
	Properties Create, Filter, Group, Sort, Update
	Description The ID of the Omni-Channel user.

UserShare

Represents a sharing entry on a user record. This object is available in API version 26.0 and later.

Supported Calls

`create()`, `delete()`, `describeObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

Customer Portal users can't access this object.

Fields

Field	Details
IsActive	Type boolean
	Properties Defaulted on create, Filter, Group, Sort
	Description Read-only. Indicates whether the User has access to log in (<code>true</code>) or not (<code>false</code>). You can modify a User's active status from the user interface or via the API.
RowCause	Type picklist
	Properties Filter, Group, Restricted picklist, Sort
	Description Reason that this sharing entry exists. You can only write to this field when its value is either omitted or set to <code>Manual</code> (default). Possible values include: <code>Manual</code>—The User or Group has access to the user record because a User with “All” access manually shared the User with them. <code>Rule</code>—The User or Group has access to the user record via a User sharing rule.

Field	Details
UserAccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Level of access that the User or Group has to the specified user. The specified user is denoted by the <code>UserId</code>. The possible values are: • Read • Edit This field must be set to an access level that is at least equal to the organization's default <code>UserAccessLevel</code>. <code>UserAccessLevel</code> can be updated only if <code>RowCause</code> is set to <code>Manual Sharing</code>.
UserId	Type reference Properties Create, Filter, Group, Sort Description ID of the User being shared.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the User or Group that has been given access to the User. This field can't be updated.

Usage

This object allows you to determine which users and groups can view or edit User records owned by other users.

UserTeamMember

Represents a single User on the default opportunity team of another User.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- This object is available only in organizations that have enabled the team selling functionality.
- Customer Portal users can't access this object.

Fields

Field	Details
OpportunityAccessLevel	Type picklist Properties Create, Filter, Restricted picklist, Update Description Required. Level of access that the team member has to opportunities for which the user has added his or her default opportunity team. The possible values are: • Read • Edit This field must be set to an access level that is higher than the organization's default access level for opportunities.
OwnerId	Type reference Properties Create, Filter Description Required. ID of the User who owns the default opportunity team. This field can't be updated.
TeamMemberRole	Type picklist Properties Create, Filter, Nillable, Update Description Role that the team member has on opportunities for which the User has added his or her default opportunity team. The valid values are set by the organization's administrator in the Opportunity Team Roles picklist. Label is Team Role.
UserId	Type reference Properties Create, Filter Description Required. ID of the User who is a member of the default opportunity team. This field can't be updated.

Usage

If you attempt to create a record that matches an existing record, the create request updates any modified fields and returns the existing record.

Users can set up their default opportunity team to include other users that typically work with them on opportunities.

UserTerritory

Represents a User who has been assigned to a Territory.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

- Only available if territory management has been enabled for your organization.
- Customer Portal users can't access this object.

Fields

Field	Details
IsActive	Type boolean Properties Defaulted on create, Filter Description Indicates whether the user is active in the given territory (<code>true</code>), or inactive in the given territory (<code>false</code>): • Users who are active in a territory are explicitly assigned to the territory and can have open opportunities, closed opportunities, or no opportunities associated with that territory. • Users who are inactive in a territory are not explicitly assigned to the territory, but own an open or closed opportunity that is associated with the territory. For example, a user may have been transferred out of a territory, but still own opportunities in his or her old territory. Until a user is deleted from a territory (not simply removed from the territory), the record is not returned in a <code>getDeleted()</code> call.
IsDeleted	Type boolean Properties Defaulted on create, Filter

Field	Details
	Description Indicates whether the object has been moved to the Recycle Bin (<code>true</code>) or not (<code>false</code>). Label is Deleted .
TerritoryId	Type reference Properties Create, Filter Description ID of the Territory to which the user has been assigned. This field is required when creating a record in API version 20.0 and later.
UserId	Type reference Properties Create, Filter Description ID of the user. This field is required when creating a record.

Usage

If a user is inactive in a territory, and the opportunities they own that are associated with the territory are all closed, then the user is not returned.

UserTerritory2Association

Represents an association (by assignment) between a territory and a user record. Available only if Enterprise Territory Management has been enabled for your organization.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`

Special Access Rules

If a territory model is in `Active` state, any user can view that model, including its territories and assignment rules. For territories in an active model, any user can view assigned records and assigned users subject to your organization's sharing settings. Users cannot view territory models in other states (such as `Planning` or `Archived`).

Fields

Field Name	Details
IsActive	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Indicates whether the user is active (<code>true</code>) or inactive (<code>false</code>) in the given territory.
RoleInTerritory2	Type picklist Properties Create, Filter, Group, Nillable, Sort, Update Description The role of the user in a territory. Possible values are: Owner, Administrator, Sales Rep. Label is <code>Role in Territory</code>.
Territory2Id	Type reference Properties Create, Filter, Group, Sort Description The ID of the territory that the user is assigned to.
UserId	Type reference Properties Create, Filter, Group, Sort Description The ID of the user who is assigned to the territory.

Vote

Represents a vote that a user has made on an Idea or a Reply.



Note: In API version 16.0 and earlier, SOQL queries on the Vote object only return votes for the Idea object. Starting in API version 17.0, SOQL queries return votes for both Idea and Reply.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field	Details
IsDeleted	Type boolean Properties Defaulted on create, Filter Description Indicates whether the object has been moved to the Recycle Bin (true) or not (false). Label is Deleted.
ParentId	Type reference Properties Group, Sort, Create, Filter Description ID of the Idea or Reply associated with this vote.
Type	Type picklist Properties Group, Sort, Create, Filter, Restricted picklist Description Picklist that indicates the type of vote. The value <code>Up</code> indicates that the vote is a user's positive endorsement of the associated idea or reply. The value <code>Down</code> indicates that the vote is a user's negative endorsement of the associated idea or reply.



Note: If you are importing Vote data into Salesforce and need to set the value for an audit field, such as `CreatedDate`, contact Salesforce. Audit fields are automatically updated during API operations unless you request to set these fields yourself..

Usage

In version 12.0 and later, use this object to track the votes that users made on ideas. For more information on ideas, see “Ideas Overview” in the Salesforce online help.

In version 17.0 and later, use this object to track the votes users made on replies. For more information, see “Answers Overview” in the Salesforce online help.

In version 17.0 and later, you must filter using the following syntax when querying this object in a SOQL query: `ParentId = single ID`, `Parent.Type = single Type`, `Id = single ID`, or `Id IN (list of IDs)`. See Comparison Operators in the [Salesforce SOQL and SOSL Reference Guide](#) for a sample query.

A SOQL query must filter using one of the following Parent or Id clauses.

- `ParentId = [single ID]`
- `Parent.Type = [single type]`
- `Id = [single ID]`
- `Id IN = [list of IDs]`

WebLink

Represents a custom link to a URL or Scontrol.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Special Access Rules

- To create a custom link, the client application must be logged in with the “Customize Application” permission.
- Customer Portal users can’t access this object.

Fields

Field Name	Details
Availability	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description
Description	Type textarea Properties Create, Filter, Nillable, Sort, Update Description Description of the custom link. Limit is 1,000 characters.
DisplayType	Type picklist

Field Name	Details
	Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Type of display: button, link, or mass-action button.
EncodingKey	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. Encoding of parameters on the URL link.
HasMenubar	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the popup window shows a menu bar (<code>true</code>) or not (<code>false</code>).
HasScrollbars	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the popup window shows scroll bars (<code>true</code>) or not (<code>false</code>).
HasToolbar	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the popup window shows browser toolbars (<code>true</code>) or not (<code>false</code>). Toolbars normally contain navigation buttons like Back, Forward, and Print.
Height	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Height of the popup in pixels.

Field Name	Details
IsProtected	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the object is protected (<code>true</code>) or not (<code>false</code>). Protected components that have been installed in other organizations can't be linked to or referenced by components created in the subscriber organization. A developer can easily delete a protected component contained in a managed package in a future release of the package without worrying about failing installations. However, once a component is marked as unprotected and is released globally, the developer can't delete it.
IsResizable	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether users are allowed to resize the popup window (<code>true</code>) or not (<code>false</code>).
LinkType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. Type of link (S-control or URL).
MasterLabel	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description Master label for the link. Limit is 240 characters. This display value is the internal label that is not translated.
Name	Type string Properties Create, Filter, Group, Sort, Update Description Required. Name to display on page.

Field Name	Details
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <i>namespacePrefix__componentName</i> notation. The namespace prefix can have one of the following values: • In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. • In organizations that are not Developer Edition organizations, NamespacePrefix is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects. This field can't be accessed unless the logged-in user has the "Customize Application" permission.
OpenType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Required. How the custom link opens when clicked in a browser—NewWindow, Sidebar, or NoSidebar.
PageOrObjectType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort Description Required. For standard objects, the name of the page on which to display the custom link. For custom objects, the name of the object.
Position	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update

Field Name	Details
	Description Location on the screen where the popup should open—TopLeft, FullScreen, or None.
RequireRowSelection	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the custom link requires a row selection (<code>true</code>) or not (<code>false</code>).
ScontrolId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description ID of the custom s-control object (Scontrol) to link to. Can include fields as tokens within the custom s-control object. Label is Custom S-Control ID .
ShowsLocation	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the popup window shows the browser's address bar containing the URL (<code>true</code>) or not (<code>false</code>).
ShowsStatus	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Show the status bar at the bottom of the browser.
Url	Type textarea Properties Create, Nillable, Update Description Required. URL of the page to link to. Can include fields as tokens within the URL. Limit: 1,024 KB.

Field Name	Details
Width	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description Width of the popup in pixels.

Usage

Use this object to programmatically manage custom links, which allow client applications to integrate data with external URLs, an organization's intranet, or other back-end office systems. A custom link can point to:

- An external URL, such as `www.google.com` or your company's intranet.
- A custom s-control, such as a Java applet or Active-X control.

Custom links can include fields as tokens within the URL or custom s-control.

WebLinkLocalization

When the Translation Workbench is enabled for your organization, the WebLinkLocalization object provides the translation of the field label of a custom link to a URL or s-control. For information on the Translation Workbench, see the Salesforce online help.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `update()`, `upsert()`

Special Access Rules

- Your organization must be using Professional, Enterprise, Developer, Unlimited, or Performance Edition and be enabled for the Translation Workbench.
- To view this object, you must have the "View Setup and Configuration" permission.

Fields

Field	Details
LanguageLocaleKey	Type picklist Properties Create, Filter, Nillable, Restricted picklist

Field	Details
	Description This field is available in API version 16.0 and earlier. It is the same as the <code>Language</code> field.
Language	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description This field is available in API version 17.0 and later. The combined language and locale ISO code, which controls the language for labels displayed in an application. This picklist contains the following fully-supported languages: - Chinese (Simplified): <code>zh_CN</code> - Chinese (Traditional): <code>zh_TW</code> - Danish: <code>da</code> - Dutch: <code>n1_NL</code> - English: <code>en_US</code> - Finnish: <code>fi</code> - French: <code>fr</code> - German: <code>de</code> - Italian: <code>it</code> - Japanese: <code>ja</code> - Korean: <code>ko</code> - Norwegian: <code>no</code> - Portuguese (Brazil): <code>pt_BR</code> - Russian: <code>ru</code> - Spanish: <code>es</code> - Spanish (Mexico): <code>es_MX</code> - Swedish: <code>sv</code> - Thai: <code>th</code> The following end-user only languages are available. - Arabic: <code>ar</code> - Bulgarian: <code>bg</code> - Croatian: <code>hr</code> - Czech: <code>cs</code> - English (UK): <code>en_GB</code> - Greek: <code>el</code> - Hebrew: <code>iw</code>

Field	Details
	• Hungarian: <code>hu</code> • Indonesian: <code>in</code> • Polish: <code>pl</code> • Portuguese (Portugal): <code>pt_PT</code> • Romanian: <code>ro</code> • Slovak: <code>sk</code> • Slovenian: <code>sl</code> • Turkish: <code>tr</code> • Ukrainian: <code>uk</code> • Vietnamese: <code>vi</code> The following platform languages are available for organizations that use Salesforce exclusively as a platform. • Albanian: <code>sq</code> • Arabic (Algeria): <code>ar_DZ</code> • Arabic (Bahrain): <code>ar_BH</code> • Arabic (Egypt): <code>ar_EG</code> • Arabic (Iraq): <code>ar_IQ</code> • Arabic (Jordan): <code>ar_JO</code> • Arabic (Kuwait): <code>ar_KW</code> • Arabic (Lebanon): <code>ar_LB</code> • Arabic (Libya): <code>ar_LY</code> • Arabic (Morocco): <code>ar_MA</code> • Arabic (Oman): <code>ar_OM</code> • Arabic (Qatar): <code>ar_QA</code> • Arabic (Saudi Arabia): <code>ar_SA</code> • Arabic (Sudan): <code>ar_SD</code> • Arabic (Syria): <code>ar_SY</code> • Arabic (Tunisia): <code>ar_TN</code> • Arabic (United Arab Emirates): <code>ar_AE</code> • Arabic (Yemen): <code>ar_YE</code> • Armenian: <code>hy</code> • Basque: <code>eu</code> • Bosnian: <code>bs</code> • Bengali: <code>bn</code> • Chinese (Simplified—Singapore): <code>zh_SG</code> • Chinese (Traditional—Hong Kong): <code>zh_HK</code> • English (Australia): <code>en_AU</code> • English (Canada): <code>en_CA</code>

Field**Details**

-
- English (Hong Kong): en_HK
 - English (India): en_IN
 - English (Ireland): en_IE
 - English (Malaysia): en_MY
 - English (Philippines): en_PH
 - English (Singapore): en_SG
 - English (South Africa): en_ZA
 - Estonian: et
 - French (Belgium): fr_BE
 - French (Canada): fr_CA
 - French (Luxembourg): fr_LU
 - French (Switzerland): fr_CH
 - Georgian: ka
 - German (Austria): de_AT
 - German (Luxembourg): de_LU
 - German (Switzerland): de_CH
 - Hindi: hi
 - Icelandic: is
 - Irish: ga
 - Italian (Switzerland): it_CH
 - Latvian: lv
 - Lithuanian: lt
 - Luxembourgish: lb
 - Macedonian: mk
 - Malay: ms
 - Maltese: mt
 - Romanian (Moldova): ro_MD
 - Montenegrin: sh_ME
 - Romansh: rm
 - Serbian (Cyrillic): sr
 - Serbian (Latin): sh
 - Spanish (Argentina): es_AR
 - Spanish (Bolivia): es_BO
 - Spanish (Chile): es_CL
 - Spanish (Colombia): es_CO
 - Spanish (Costa Rica): es_CR
 - Spanish (Dominican Republic): es_DO
 - Spanish (Ecuador): es_EC
-

Field	Details
	- Spanish (El Salvador): <code>es_SV</code> - Spanish (Guatemala): <code>es_GT</code> - Spanish (Honduras): <code>es_HN</code> - Spanish (Nicaragua): <code>es_NI</code> - Spanish (Panama): <code>es_PA</code> - Spanish (Paraguay): <code>es_PY</code> - Spanish (Peru): <code>es_PE</code> - Spanish (Puerto Rico): <code>es_PR</code> - Spanish (United States): <code>es_US</code> - Spanish (Uruguay): <code>es_UY</code> - Spanish (Venezuela): <code>es_VE</code> - Tagalog: <code>tl</code> - Tamil: <code>ta</code> - Urdu: <code>ur</code> - Welsh: <code>cy</code> The values in this field are not related to the default locale selection.
NamespacePrefix	Type string Properties Filter, Group, Nillable, Sort Description The namespace prefix associated with this object. Each Developer Edition organization that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the <code>namespacePrefix__componentName</code> notation. The namespace prefix can have one of the following values: - In Developer Edition organizations, the namespace prefix is set to the namespace prefix of the organization for all objects that support it. There is an exception if an object is in an installed managed package. In that case, the object has the namespace prefix of the installed managed package. This field's value is the namespace prefix of the Developer Edition organization of the package developer. - In organizations that are not Developer Edition organizations, <code>NamespacePrefix</code> is only set for objects that are part of an installed managed package. There is no namespace prefix for all other objects.
Value	Type string Properties Create, Filter, Nillable, Sort, Update

Field	Details
	Description The actual translated label of the custom link. Label is Translation .
WebLinkId	Type reference
	Properties Create, Filter, Group, Nillable, Sort
	Description The ID of the WebLink that is being translated.

Usage

Use this object to translate your custom links to URLs or s-controls into the different languages supported by Salesforce. Users with the Translation Workbench enabled can view custom link translations, but either the “Customize Application” or “Manage Translation” permission is required to create or update custom link translations.

WorkAccess

Used to grant or restrict user access to give badge definitions. Each badge definition record must have one WorkAccess record.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Additional Considerations and Related Objects

WorkAccess is not available through Schema Builder and is not customizable. A WorkAccess record is **required** for users to **Give** BadgeDefinitions. If a WorkAccess record is not created, BadgeDefinitions will not be available to users.

The sharing of WorkAccess records is through [WorkAccessShare](#) on page 1533 For each WorkBadgeDefinition record, you must create both a WorkAccess record (per WorkBadgeDefinition) and WorkAccessShare records for sharing to users or groups.

Fields

Field Name	Details
AccessType	Type picklist
	Properties Create, Filter, Group, Restricted picklist, Sort, Update
	Description Define the type of Access given to user (“Give”).

Field Name	Details
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Salesforce unique ID for owner of Access record.
ParentId	Type reference Properties Create, Filter, Group, Sort, Update Description Salesforce unique ID for BadgeDefinition record associated with this Access record.

WorkAccessShare

WorkAccessShare is used to control Givers of WorkBadgeDefinition records.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Additional Considerations and Related Objects

Related to [WorkAccess Object](#). WorkAccess is the parent of WorkAccessShare.

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description CRUD Access Level (picklist values: Read Only, Read/Write, Owner).
ParentId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Sort Description ID for WorkAccess record.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Owner or Manual sharing.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description User or Group ID for WorkAccess.

WorkBadge

A WorkBadge record is created for each recipient of a WorkBadgeDefinition. Contains information about who the badge was given to and which badge was given.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Additional Considerations and Related Objects

WorkBadge is a lookup to WorkThanks. Each WorkBadge record must derive a SourceId from WorkThanks. There can be multiple WorkBadge records tied to a single WorkThanks record.

Fields

Field Name	Details
DefinitionId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Sort
	Description Required. Salesforce unique ID for the given WorkBadgeDefinition record given.
Description	Type textarea
	Properties Nillable
	Description The description of the WorkBadgeDefinition.
GiverId	Type reference
	Properties Filter, Group, Nillable, Sort
	Description The ID of the badge giver.
ImageUrl	Type url
	Properties Filter, Group, Nillable, Sort
	Description The URL of the badge image.
LastReferencedDate	Type dateTime
	Properties Filter, Nillable, Sort
	Description The time stamp that indicates when the current user last viewed a record that is related to this WorkBadge.
LastViewedDate	Type dateTime
	Properties Filter, Nillable, Sort
	Description The time stamp that indicates when the current user last viewed this WorkBadge. If this value is null, this record might have been only referenced (LastReferencedDate) and not viewed.

Field Name	Details
Message	Type textarea Properties Nillable Description The message accompanying the thanks badge.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the community that this WorkBadge is associated with. This field is available only if Salesforce Communities is enabled in your organization.
RecipientId	Type reference Properties Create, Filter, Group, Sort Description Required. Salesforce unique ID for User who is the Recipient of Badge.
RewardId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Salesforce unique ID for Reward given with badge (if Reward Badge)
SourceId	Type reference Properties Create, Filter, Group, Sort Description Salesforce unique ID for Thanks record referenced to this badge.

WorkBadgeDefinition

The attributes of a badge including the badge name, description, and image. Each WorkBadge record must have a lookup to a WorkBadgeDefinition as badge attributes, such as badge name, badge description, and badge image, are derived from the WorkBadgeDefinition object.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Additional Considerations and Related Objects

WorkBadgeDefinition has a field called `ImageUrl` that references a DocumentID. This is a required field for creating a Badge.

To grant “giver” access to a WorkBadgeDefinition, you must also create the [WorkAccess](#) (and the related [WorkAccessShare](#)) records.

Each WorkBadgeDefinition has an `ImageUrl` field that must be populated with a DocumentID of the Document record containing the badge image.

Fields

Field Name	Details
Description	Type textarea Properties Create, Update Description Required. Limit: 4000 characters. The description of the badge and what it means to receive this badge.
GivenBadgeCount	Type int Properties Filter, Group, Nillable, Sort Description The number of badges given per user or across all users.  Note: This field can't be added in a list view or referenced in a formula field.
ImageUrl	Type url Properties Create, Filter, Group, Sort, Update Description Required. This is the badge image that will be displayed in the UI. Use DocumentID or ImageURL.
IsActive	Type boolean

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Represents whether a WorkBadgeDefinition is active and available in the UI.
IsCompanyWide	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Represents a special class of badges known as Company Badges. Company badges are visible to the entire company and visible in specific list view filters.  Note: If this field is selected, everyone within the user's network will be able to give the badge automatically. If this field is not selected, people with sharing must be added to the badge's access list in order to give the badge.
IsLimitPerUser	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the badge limit is per user (<code>true</code>) or across all users (<code>false</code>). The default value is <code>false</code>.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed a record that is related to this WorkBadgeDefinition.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed this WorkBadgeDefinition. If this value is null, this record might have been only referenced (<code>LastReferencedDate</code>) and not viewed.

Field Name	Details
LimitNumber	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The badge limit per user or across all users.
LimitStartDate	Type dateTime Properties Create, Filter, Group, Nillable, Sort, Update Description The start date of the badge limit. The date can be reset to the current date.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Required. Name of the Badge. Label: Badge Title.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the community that this WorkBadgeDefinition is associated with. This field is available only if Salesforce Communities is enabled in your organization.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Salesforce User ID for User who is the Owner of the WorkBadgeDefinition record (usually the creator of the record)
RewardFundId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description Salesforce unique ID for the WorkRewardFund that is associated with this WorkBadgeDefinition. WorkBadgeDefinition records with a RewardFundID indicate a Reward Badge.

WorkBadgeDefinitionHistory

Represents the history of changes to the values in the fields of a WorkBadgeDefinition object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Type of change (e.g., created).
NewValue	Type Any Type Properties Nillable, Sort Description Updated value of record.
OldValue	Type Any Type Properties Nillable, Sort Description Previous value of record.
WorkBadgeDefinitionId	Type reference

Field Name	Details
	Properties Filter, Group, Sort
	Description ID of WorkBadgeDefinition record.

WorkBadgeDefinitionShare

Represents a sharing entry on a WorkBadgeDefinition object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccessLevel</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the work badge definition. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records This field must be set to an access level that is higher than the organization's default access level for work badge definitions.
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkBadgeDefinition object that is associated with this sharing entry.
<code>RowCause</code>	Type picklist

Field Name	Details
	Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: - Owner: User is the owner of the WorkBadgeDefinition or is in a user role above the WorkBadgeDefinition owner in the role hierarchy. - Manual: User or group has access, because a user with “All” access manually shared the WorkBadgeDefinition with the user or group. - Rule: User or group has access via a WorkBadgeDefinition sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the work badge definition. This field can’t be updated.

WorkCoaching

Represents a single coaching relationship between two users. One of the users is defined as the coach and the other is defined as a coachee. WorkCoaching is feed-enabled so there is a private feed available to the coach and coachee.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
CoachId	Type reference Properties Create, Filter, Group, Sort, Update Description [Required] The coach in this 1:1 coaching relationship.

Field Name	Details
CoachedId	Type reference Properties Create, Filter, Group, Sort, Update Description [Required] The user being coached in this 1:1 coaching relationship.
IsInactive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the coaching relationship is <i>Inactive</i> (<code>true</code>) or not (<code>false</code>).
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed a record that is related to this coaching relationship.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed this coaching relationship. If this value is null, this record might have been only referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Create, Filter, Group, Sort, Update Description [Required] The record's name. Max length is 255 characters.
OwnerId	Type reference

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update
	Description ID of the contact who owns the WorkCoaching record.

WorkCoachingFeed

Represents a single feed item in the feed on the detail page for a coaching record. A coaching feed shows recent changes to a lead record for any fields that are tracked in feeds, as well as posts and comments about the record. It is a useful way to stay up-to-date with changes made to coaching in Salesforce.

Supported Calls

`delete()`, `describeObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Special Access Rules

You can delete all feed items that you created. To delete feed items that you didn't create, you must have one of these permissions:

- "Modify All Data"
- "Modify All" on the WorkCoachingFeed object
- "Moderate Chatter"

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.

Field Name	Details
ContentData	Type base64 Properties Nillable Description The file that is uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file that is uploaded to the feed. Required if Type is ContentPost. The name of the file that is uploaded to the feed. Setting ContentFileName automatically sets Type to ContentPost.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) that is uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file that is uploaded to the feed.

Field Name	Details
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, InsertedById is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes that are associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. If Salesforce Communities is enabled for your organization, this field is available in API version 28.0 and later. <code>NetworkScope</code> can have the following values. • <code>NetworkId</code>: The ID of the community in which the FeedItem is available. If left empty, the feed item is available only in the default community. • <code>AllNetworks</code>: The feed item is available in all communities. Note the following exceptions for <code>NetworkScope</code>. • Only feed items with a CollaborationGroup or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. • For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>.

Field Name	Details
ParentId	Type reference Properties Filter, Group, Sort Description ID of the WorkCoaching record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of type ContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the FeedItem. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of ContentPost, LinkPost, and TextPost, feed item types should not be created directly from the API • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement.

Field Name	Details
	• <code>AnnouncementPost</code>—Not used. • <code>ApprovalPost</code>—generated when a user submits an approval. • <code>BasicTemplateFeedItem</code>—Not used. • <code>CanvasPost</code>—a post made by a canvas app posts on a feed. • <code>CollaborationGroupCreated</code>—generated when a user creates a public group. • <code>CollaborationGroupUnarchived</code>—Not used. • <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received.

Field Name	Details
	- FacebookPost—generated when a Facebook post is created from a case. Deprecated. - MilestoneEvent—generated when a case milestone is completed or reaches violation status. - SocialPost—generated when a social post is created from a case.  Note: If you set Type to ContentPost, you must specify ContentData and ContentFileName.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The visibility of a FeedItem: - AllUsers: visible to all users - InternalUsers: visible to internal users

WorkCoachingHistory

Represents the history of changes to the values in the fields of a WorkCoaching object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort

Field Name	Details
	Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.
WorkCoachingId	Type reference Properties Filter, Group, Sort Description The ID of the WorkCoaching object.

WorkCoachingShare

Represents a sharing entry on a WorkCoaching object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the coaching relationship. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records.

Field Name	Details
	This field must be set to an access level that is higher than the organization's default access level for coaching relationships.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkCoaching object that is associated with this sharing entry.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: - Owner: User is the owner of the coaching relationship or is in a user role above the coaching relationship owner in the role hierarchy. - Manual: User or group has access, because a user with "All" access manually shared the coaching relationship with the user or group. - Rule: User or group has access via a sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the coaching relationship. This field can't be updated.

WorkFeedback

Answer to a specific question that the person was asked via a request for feedback. Also used to store offered feedback without linking it to a particular question.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Additional Considerations and Related Objects

- Ownership is transferred to the requester on submit for certain types (ad-hoc feedback).
- The record is read-only after the request that it's linked to is Submitted.
- You can't link a feedback object to a request unless you are the recipient.
- The question that the feedback is linked to must be part of the same question set that the request is linked to.

Fields

Field Name	Details
Feedback	Type textarea Properties Create, Nillable, Update Description Contains either the free-form text of the answer, or the choice selected by the user. Max length is 65536.
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The name of the WorkFeedback record.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the WorkFeedback record.
QuestionId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The question this answer applies to. When this feedback is linked to a request of an unsolicited type, the question ID is null.
RequestId	Type reference

Field Name	Details
	Properties Create, Filter, Group, Sort
	Description The ID of the request this response belongs to, in case of offered feedback.

WorkFeedbackHistory

This read-only object contains historical information about changes that have been made to the WorkFeedback object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.
WorkFeedbackId	Type reference

Field Name	Details
	Properties Filter, Group, Sort
	Description ID of the WorkFeedback object.

WorkFeedbackQuestion

Represents a question within a set of questions of either a free form text type, or a multiple choice.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
Choices	Type textarea
	Properties Create, Nillable, Update
	Description New-line separated list of valid choices for multiple choice questions. Maximum length is 1000 characters.
Detail	Type textarea
	Properties Create, Nillable, Update
	Description Detailed instructions on how to answer the question.
IsConfidentialAnswer	Type boolean
	Properties Create, Defaulted on create, Filter, Group, Sort, Update
	Description Answers to questions marked confidential will not be shared with the subject of the review. This field applies only to performance summaries.

Field Name	Details
IsOptional	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If this option is selected, the question is optional and isn't required to be answered. This field applies only to performance summaries.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description A short description of the question, which can be used as a header for reports and Calibration.
Number	Type int Properties Create, Filter, Group, Sort, Update Description The order of the question that is displayed within the question set, such as question number three in a question set that has five questions.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the WorkFeedbackQuestion.
QuestionSetId	Type reference Properties Create, Filter, Group, Sort, Update Description The question set this question is a part of.
Text	Type textarea Properties Create, Update

Field Name	Details
	Description The body of the question. Max length is 16384 characters.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description Allows for either a free-form text answer or a multiple choice question defined by new-line separate choices in the 'Choices' field. Valid picklist values are: - MultipleChoice - FreeText - Rating

WorkFeedbackQuestionHistory

Represents the history of changes to the values in the fields of a WorkFeedbackQuestion.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.

Field Name	Details
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.
WorkFeedbackQuestionId	Type reference Properties Filter, Group, Sort Description ID of the WorkFeedbackQuestion.

WorkFeedbackQuestionSet

Represents a set of questions that are being asked. The question set is used to link all the individual requests where different recipients were asked the same set of questions on the same subject.

In the Work.com performance application, a question set defines the type of summaries and their due dates that will accompany the deployment of a specific performance summary cycle.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
DueDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The date that this specific question set is expected to be submitted by the recipient. This field applies only to performance summaries.
FeedbackType	Type picklist

Field Name	Details
	Properties Create, Filter, Group, Nillable, Restricted picklist, Sort Description The description of the collection of questions that are written in context to the type of recipient answering them, relative to the subject of the summary. This field applies only to performance summaries.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The name of the question set. Maximum length is 225 characters.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the WorkFeedbackQuestionSet.
PerformanceCycleId	Type reference Properties Create, Filter, Group, Nillable, Sort Description If a question set is associated to a performance summary cycle, then that cycle ID is referenced in this field. This field applies only to performance summaries.

WorkFeedbackQuestionSetHistory

This read-only object contains historical information about changes that have been made to the WorkFeedbackQuestionSet object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.
WorkFeedbackQuestionSetId	Type reference Properties Filter, Group, Sort Description ID of the WorkFeedbackQuestionSet object.

WorkFeedbackQuestionSetShare

Represents a sharing entry on a WorkFeedbackQuestionSet.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the feedback question set. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records. This field must be set to an access level that is higher than the organization's default access level for feedback question sets.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkFeedbackQuestionSet object that is associated with this sharing entry.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: • Owner: User is the owner of the WorkFeedbackQuestionSet or is in a user role above the WorkFeedbackQuestionSet owner in the role hierarchy. • Manual: User or group has access, because a user with "All" access manually shared the WorkFeedbackQuestionSet with the user or group. • Rule: User or group has access via a WorkFeedbackQuestionSet sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort

Field Name	Details
	Description ID of the user or group that was given access to the feedback question set. This field can't be updated.

WorkFeedbackQuestionShare

Represents a sharing entry on a WorkFeedbackQuestion.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccessLevel</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the feedback question. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records. This field must be set to an access level that is higher than the organization's default access level for feedback questions.
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkFeedbackQuestion object that is associated with this sharing entry.
<code>RowCause</code>	Type picklist

Field Name	Details
	Properties Filter, Group, Restricted picklist, Sort
	Description Reason that this sharing entry exists. Read-only. Valid values include: - Owner: User is the owner of the WorkFeedbackQuestion or is in a user role above the WorkFeedbackQuestion owner in the role hierarchy. - Manual: User or group has access, because a user with “All” access manually shared the WorkFeedbackQuestion with the user or group. - Rule: User or group has access via a WorkFeedbackQuestion sharing rule.
UserOrGroupId	Type reference
	Properties Create, Filter, Group, Sort
	Description ID of the user or group that was given access to the feedback question. This field can’t be updated.

WorkFeedbackRequest

In the feedback application, WorkFeedbackRequest represents a single feedback request on a subject or topic (question) to a single recipient. In the case of offered feedback, WorkFeedbackRequest represents feedback that is offered about a subject. In the performance application, WorkFeedbackRequest represents a request for feedback on a set of questions from a question set, on a subject—for the recipient to complete and submit.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Additional Considerations and Related Objects

- After a request’s state is changed to Submitted, fields can’t be changed, except for LastSharedDate and IsUnreadByOwner.
- If LastRemindDate is updated, a reminder notification will be sent to the request’s recipient (only possible when request is in Draft state).
- When a new request is created, a notification is sent to the recipient.
- When a recipient of a request submits their feedback (Draft->Submitted), a notification will be sent to requester (except for offered feedback).
- Requester cannot modify the subject of the question set after a request is created.

- For offered feedback (to user, to manager, or both), the person who is offering feedback is both the creator of WorkFeedbackRequest as well as the recipient.

Fields

Field Name	Details
AdHocFeedback	Type textarea Properties Create, Filter, Nillable, Sort Description The content of the feedback.
AdHocQuestion	Type textarea Properties Create, Filter, Nillable, Sort Description The content of the feedback question.
Description	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description The description of the WorkFeedbackRequest.
FeedbackRequestState	Type picklist Properties Create, Defaulted on create, Filter, Group, Restricted picklist, Sort, Update Description The current state of the feedback request. Allowed picklist values are: • Draft • Submitted • Dismissed
FeedbackType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort

Field Name	Details
	Description Specifies the type of request. Picklist values that are used for performance summaries: • Unspecified • Peer Summary • Self Summary • Manager Summary • Skip Level Summary Picklist values that are used for feedback: • Personal • Unsolicited to User • Unsolicited to Manager • Unsolicited to User and Manager • On Topic The type of the feedback determines the sharing and visibility rules that are applied to answers.
IsDeployed	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, the feedback is part of a deployed performance summary cycle.
IsShareWithSubject	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, the feedback is shared with the summary subject.
IsUnreadByOwner	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, the submitted request has not been seen by the requester.
IsUnsolicited	Type boolean

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update Description If <code>true</code>, the feedback request is unsolicited feedback offered to another user.
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed a record that is related to this WorkFeedbackRequest.
LastRemindDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The last time a reminder was sent to the recipient of this draft request.
LastSharedDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The last time this request was shared with another user or group.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed this WorkFeedbackRequest. If this value is null, this record might have been only referenced (LastReferencedDate) and not viewed.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The name of the WorkFeedbackRequest.

Field Name	Details
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the WorkFeedbackRequest.
PerformanceCycleId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Used by performance summaries to link to a summary cycle. This field applies only to performance summaries.
QuestionSetId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Question set associated with the current request.
RecipientId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description User asked to provide feedback on the subject.
RelatedObjectId	Type reference Properties Create, Filter, Group, Nillable, Sort Description Specifies a record in the system that this feedback request is related to. Used by ad-hoc feedback to gather feedback in the context of an opportunity or Work.com goal. Used by performance summaries to link to a summary cycle.
SharingScope	Type picklist

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The users that see the feedback. <code>SharingScope</code> can have the following values: - Nobody - Subject - Manager - SubjectAndManager
SubjectId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the user that this request (or offer) is about.
SubmitFeedbackToId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the person this performance summary feedback request (and its respective answers) is shared with. It's also the ID of the person who owns the requested subject's manager summary request. This field applies only to performance summaries.
SubmittedDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The last time (in case it was reopened by admin) this request was submitted by the recipient. This field applies only to performance summaries.
TemplateId	Type reference Properties Create, Filter, Group, Nillable, Sort Description The ID of the associated feedback template.

WorkFeedbackRequestFeed

Represents a single feed item in the feed displayed on the feedback request detail page. The feedback request feed shows changes to a request for fields that are tracked in feeds, posts and comments about the request.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.

Field Name	Details
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if Type is ContentPost. The name of the file uploaded to the feed. Setting ContentFileName automatically sets Type to ContentPost.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then InsertedById is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.

Field Name	Details
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the goal record that is tracked in the feed. The feed is displayed on the detail page for this record.
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of TypeContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the FeedItem. When the Type is LinkPost, the LinkUrl is the URL and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of ContentPost, LinkPost, and TextPost, feed item types should not be created directly from the API

Field Name	Details
	• ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the Type picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case. • CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event.

Field Name	Details
	• <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.

WorkFeedbackRequestHistory

Represents the history of changes to the values in the fields of a `WorkFeedbackRequest`.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.

Field Name	Details
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.
WorkFeedbackRequestId	Type picklist Properties Filter, Group, Sort Description ID of the WorkFeedbackRequest.

WorkFeedbackRequestShare

Represents a sharing entry on a WorkFeedbackRequest.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the feedback request. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records. This field must be set to an access level that is higher than the organization's default access level for feedback requests.

Field Name	Details
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkFeedbackRequest object that is associated with this sharing entry.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: • Owner: User is the owner of the WorkFeedbackRequest or is in a user role above the WorkFeedbackRequest owner in the role hierarchy. • Manual: User or group has access, because a user with “All” access manually shared the WorkFeedbackRequest with the user or group. • Rule: User or group has access via a WorkFeedbackRequest sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the feedback request. This field can't be updated.

WorkFeedbackShare

Represents a sharing entry on a WorkFeedback object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the feedback. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records. This field must be set to an access level that is higher than the organization's default access level for feedback.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkFeedback object that is associated with this sharing entry.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: • Owner: User is the owner of the WorkFeedback or is in a user role above the WorkFeedback owner in the role hierarchy. • Manual: User or group has access, because a user with "All" access manually shared the WorkFeedback with the user or group. • Rule: User or group has access via a WorkFeedback sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the feedback. This field can't be updated.

WorkFeedbackTemplate

This object is reserved for future use.

WorkFeedbackTemplateShare

This object is reserved for future use.

WorkGoal

The WorkGoal object represents the components of a goal such as its description and associated metrics.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Related

[WorkGoalCollaborator](#), [WorkGoalLink](#), [WorkGoalFeed](#)

Fields

Field Name	Details
ActualValue	Type double Properties Create, Filter, Nillable, Sort, Update Description The actual value of the WorkGoal metric. Applicable only to WorkGoal objects of Type: Metric.
ActualValueExternalUrl	Type url Properties Create, Filter, Group, Nillable, Sort, Update Description Contains a URL that references work.com data synchronization for the actual value of a metric. Applicable only to WorkGoal objects of Type: Metric.
CompletionDate	Type dateTime

Field Name	Details
	Properties Create, Filter, Nillable, Sort, Update Description The completion date of the goal.  Note: Field-level security limits access to only administrators and owners by default, and only they can complete a goal.
Description	Type textarea (max length 4000) Properties Create, Nillable, Update Description The description of the goal.
DueDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The date the WorkGoal object is due (optional). Applicable only to WorkGoal objects of <code>Type: Metric</code>.
FlaggedAs	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The progress of the WorkGoal object. Applicable only to WorkGoal objects of <code>Type: Metric</code>. Possible values: - On Track: Progress on the metric is on track. - Behind: Progress on the metric is behind schedule. - Postponed: The metric is postponed. - Critical: Progress on the metric is critical.
ImageUrl	Type url Properties Create, Filter, Group, Nillable, Sort, Update

Field Name	Details
	Description The URL for the goal image. The image must be stored in Documents and set as externally available. Applicable only to WorkGoal objects of <code>Type: Goal</code> .
InitialValue	Type double Properties Create, Filter, Nillable, Sort, Update Description The initial value of the WorkGoal metric. Applicable only to WorkGoal objects of <code>Type: Metric</code> and <code>MetricType: Progress</code> or <code>Percent</code> .
IsKeyCompanyGoal	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Used to indicate if the goal is a key company goal. Used for the Company Goal Showcase. Applicable only to WorkGoal objects of <code>Type: Goal</code> .
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed a record that is related to this goal.
LastSyncDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The time stamp that indicates when the actual value was last synced with the associated metrics report.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed this goal.

Field Name	Details
MetricType	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The type of metric that is represented. (See values in the following list). Applies only to WorkGoal objects of <code>Type: Metric</code>. Possible values: - Progress: ActualValue / TargetValue as a percentage - Percent: the metric as a percentage only - YesNo: the completed / not completed metric as a milestone - Absolute: Deprecated
MetricTypeDataSource	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description Specifies how the metric (ActualValue and CurrentValue) is updated. Applies only to WorkGoal objects of <code>Type: Goal</code> and <code>Metric</code>. Possible values: - Manual: indicates that the actual and target value of the metric is updated manually by the user - Rollup: indicates that the actual and target value of a goal is rolled up automatically by Work.com Goals - DataSyncActualOnly: indicates that the actual value of the metric is linked to a Salesforce report
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The name of the WorkGoal object. (Maximum length is 255.)
OverallStatus	Type string Properties Filter, Group, Nillable, Sort

Field Name	Details
	Description The overall calculated status of the WorkGoal based on <code>FlaggedAs</code> and <code>CompletionDate</code> .
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the user who owns the WorkGoal.
ParentId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Specifies the structural parent of the WorkGoal. For example, a goal that has a metric is represented by a WorkGoal of <code>Type Metric</code> , which has a parent of WorkGoal of <code>Type Goal</code> .  Note: The root and the parent must be set to the parent goal for any child metrics.
Progress	Type percent Properties Filter, Nillable, Sort Description Read Only. The overall progress of the WorkGoal.
RootId	Type reference to a WorkGoal object Properties Create, Filter, Group, Nillable, Sort, Update Description Specifies the structural root of the WorkGoal. For example, a goal that has a metric is represented by a WorkGoal of <code>Type Metric</code> , which has a root of WorkGoal of <code>Type Goal</code> .
State	Type picklist Properties Create, Defaulted on create, Filter, Group, Restricted picklist, Sort, Update

Field Name	Details
	Description The state of the WorkGoal object. Applies only to WorkGoal objects of <code>Type</code>: Metric. Possible values: • Draft: the draft state for the WorkGoal • Published: published state for the WorkGoal • Archived: archived state for the WorkGoal (for example, goals that no longer apply)
TargetValue	Type double Properties Create, Filter, Nillable, Sort, Update Description The target value of the WorkGoal. Applies only to WorkGoal objects of <code>Type</code>: Metric.
Type	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of the WorkGoal object, used to differentiate between the components of a goal. (This field is used to represent components of a goal such as its description and associated metrics.) Possible values: • Goal: a goal • Metric: a metric (typically associated with goals) • Objective: an objective • KeyResult: a key result (typically associated with objectives) • V2MOM: a V2MOM (pilot feature) • Vision: a vision (pilot feature — typically associated with V2MOM) • Value: a value (pilot feature - typically associated with V2MOM) • Method: a method (pilot feature - typically associated with V2MOM) • Obstacle: an obstacle (pilot feature - typically associated with V2MOM) • Measure: a measure (pilot feature - typically associated with a method)  Note: Administrators can rename goals and metrics to objectives and key results, respectively. If this preference is enabled, use the <code>Type</code> Objective or KeyResult. Otherwise, use the default <code>Type</code> Goal or KeyResult.

Field Name	Details
Weight	Type double Properties Create, Filter, Nillable, Sort, Update Description The weight of the goal or metric. The sum of the weights should equal 100%.

WorkGoalCollaborator

The WorkGoalCollaborator object represents collaborators on a WorkGoal object. Note that this doesn't include WorkGoal followers, which is handled by Chatter Feed Follow functionality.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
InvitationDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description The date that a user was invited to become a collaborator (null if the user was not invited).
State	Type picklist Properties Create, Defaulted on create, Filter, Group, Restricted picklist, Sort, Update Description Indicates the state of the collaborating user. Whether the user has not responded, joined, or declined collaboration. The possible values are: • PendingResponse: a user who was invited to collaborate but hasn't joined or declined • Joined: a user who is collaborating on a goal (joined/commit) • Declined: a user who declined to collaborate on a goal

Field Name	Details
UserId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The collaborating user.
WorkGoalId	Type reference Properties Create, Filter, Group, Sort Description The WorkGoal object that this collaborator is a part of.

WorkGoalCollaboratorHistory

This read-only object contains historical information about changes that were made to the WorkGoalCollaborator object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Name of the standard or custom field.
NewValue	Type anyType Properties Nillable, Sort Description New value of the modified field.

Field Name	Details
OldValue	Type anyType Properties Nillable, Sort Description Previous value of the modified field.
WorkGoalCollaboratorId	Type reference Properties Filter, Group, Sort Description ID of the WorkGoalCollaborator object that is associated with this history entry.

WorkGoalFeed

Represents a single feed item in the feed displayed on the goal page for a Goal record. The goal feed shows changes to a goal for fields that are tracked in feeds, posts, and comments about the goal, as well as updates on metrics.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when Type is TextPost. Optional when Type is ContentPost or LinkPost. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort

Field Name	Details
	Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if Type is ContentPost. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets Type to ContentPost.
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in ContentData.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if Type is ContentPost. The name of the file uploaded to the feed. Setting ContentFileName automatically sets Type to ContentPost.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort

Field Name	Details
	Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then InsertedById is set to the ID of the logged-in user.
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. If Salesforce Communities is enabled for your organization, this field is available in API version 28.0 and later. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope:

Field Name	Details
	- Only feed items with a Group or User parent can set a <code>NetworkId</code> or a null value for <code>NetworkScope</code>. - For feed items with a record parent, users can set <code>NetworkScope</code> only to <code>AllNetworks</code>. - You can't filter a <code>FeedItem</code> on the <code>NetworkScope</code> field.
<code>ParentId</code>	Type reference Properties Filter, Group, Sort Description ID of the goal record that is tracked in the feed. The feed is displayed on the detail page for this record.
<code>RelatedRecordId</code>	Type reference Properties Group, Nillable, Sort Description ID of the <code>ContentVersion</code> object associated with a <code>ContentPost</code>. This field is null for all posts except <code>ContentPost</code>. For example, set this field to an existing <code>ContentVersion</code> and post it to a feed as a <code>FeedItem</code> object of <code>TypeContentPost</code>.
<code>Title</code>	Type string Properties Group, Nillable, Sort Description The title of the <code>FeedItem</code>. When the Type is <code>LinkPost</code>, the <code>LinkUrl</code> is the URL and this field is the link name.
<code>Type</code>	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of <code>ContentPost</code>, <code>LinkPost</code>, and <code>TextPost</code>, feed item types should not be created directly from the API <code>ActivityEvent</code>—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email

Field Name	Details
	tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used. • ContentPost—a post with an attached file. • CreatedRecordEvent—generated when a user creates a record from the publisher. • DashboardComponentAlert—generated when a dashboard metric or gauge exceeds a user-defined threshold. • DashboardComponentSnapshot—created when a user posts a dashboard snapshot on a feed. • LinkPost—a post with an attached URL. • PollPost—a poll posted on a feed. • ProfileSkillPost—generated when a skill is added to a user's Chatter profile. • QuestionPost—generated when a user posts a question. • ReplyPost—generated when Chatter Answers posts a reply. • RypplePost—generated when a user creates a Thanks badge in Work.com. • TextPost—a direct text entry on a feed. • TrackedChange—a change or group of changes to a tracked field. • UserStatus—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • AttachArticleEvent—generated event when a user attaches an article to a case. • CallLogPost—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event.

Field Name	Details
	• <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.
Visibility	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The visibility of a FeedItem: • <code>AllUsers</code>: visible to all users • <code>InternalUsers</code>: visible to internal users

WorkGoalHistory

This read-only object contains historical information about changes that have been made to the WorkGoal object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort

Field Name	Details
	Description The name of the field that was changed.
NewValue	Type Any Type Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type Any Type Properties Nillable, Sort Description The latest value of the field before it was changed.
WorkGoalId	Type reference Properties Filter, Group, Sort Description ID of the Goal. Label is Goal ID.

WorkGoalLink

Represents the relationship between two goals (many to many relationship).

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
IsActive	Type boolean

Field Name	Details
	Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Whether the WorkGoalLink is active (<code>true</code>) or not (<code>false</code>)
LinkType	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The type of link
Name	Type string Properties Autonumber, Defaulted on create, Filter, idLookup, Sort Description The auto-generated name of the goal link
SourceGoalId	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the source WorkGoal object
TargetGoalId	Type reference Properties Create, Filter, Group, Sort, Update Description The ID of the target WorkGoal object

WorkGoalShare

Represents a sharing entry on a WorkGoal object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the goal. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records This field must be set to an access level that is higher than the organization's default access level for goals.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkGoal object that is associated with this sharing entry.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: • Owner: User is the owner of the WorkGoal or is in a user role above the WorkGoal owner in the role hierarchy. • Manual: User or group has access, because a user with "All" access manually shared the WorkGoal with the user or group. • Rule: User or group has access via a WorkGoal sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the goal. This field can't be updated.

WorkPerformanceCycle

WorkPerformanceCycle represents feedback that is gathered for the purpose of assessing the performance of a specific set of employees.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
ActivityFrom	Type date Properties Create, Filter, Group, Sort, Update Description The date that you want to start filtering the work.com objects to help requesters create accurate summaries. The start of the evaluation period.
ActivityTo	Type date Properties Create, Filter, Group, Sort, Update Description The date that you want to stop filtering the work.com objects to help requesters create accurate summaries. The end of the evaluation period.
CurrentTask	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The current task that the performance summary cycle is engaged in, including deploying and sharing.
LastManagerRequestsSharedDate	Type dateTime Properties Create, Filter, Nillable, Sort, Update Description The date when all manager requests are set to be shared.

Field Name	Details
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed a record that is related to this WorkPerformanceCycle.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed this WorkPerformanceCycle. If this value is null, this record might have been only referenced (LastReferencedDate) and not viewed.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The name of the performance summary cycle that employees will participate in. This name is created by the administrator and is visible on all respective notifications and in the UI.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description ID of the owner of the WorkPerformanceCycle.
State	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The state that the performance summary cycle is in. Available pick list values: • Setup: The summary is in draft. • In Progress: The summary is deployed and people are answering the questions that were created.

Field Name	Details
	- Finished: The summary is no longer in progress. - Error: The summary encountered an error.

WorkPerformanceCycleFeed

Represents a single feed item in the feed that is displayed on a Work.com Performance detail page.

Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Body	Type textarea Properties Nillable, Sort Description The content of the FeedItem. Required when <code>Type</code> is <code>TextPost</code>. Optional when <code>Type</code> is <code>ContentPost</code> or <code>LinkPost</code>. This is the message that appears in the feed.
CommentCount	Type int Properties Filter, Group, Sort Description The number of FeedComments associated with this feed item.
ContentData	Type base64 Properties Nillable Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. Encoded file data. Cannot be 0 bytes. Can be any format. Setting this field automatically sets <code>Type</code> to <code>ContentPost</code>.

Field Name	Details
ContentDescription	Type textarea Properties Nillable, Sort Description The description of the file specified in <code>ContentData</code>.
ContentFileName	Type string Properties Group, Nillable, Sort Description The file uploaded to the feed. Required if <code>Type</code> is <code>ContentPost</code>. The name of the file uploaded to the feed. Setting <code>ContentFileName</code> automatically sets <code>Type</code> to <code>ContentPost</code>.
ContentSize	Type int Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The size of the file (in bytes) uploaded to the feed.
ContentType	Type string Properties Group, Nillable, Sort Description Read only. Automatically determined during insert. The MIME type of the file uploaded to the feed.
InsertedById	Type reference Properties Group, Nillable, Sort Description ID of the user who added this object to the feed. For example, if a client application migrates multiple posts and comments from another application into a feed, then <code>InsertedById</code> is set to the ID of the logged-in user.

Field Name	Details
LikeCount	Type int Properties Filter, Group, Sort Description The number of FeedLikes associated with this feed item.
LinkUrl	Type url Properties Nillable, Sort Description The URL of a LinkPost.
NetworkScope	Type picklist Properties Group, Nillable, Restricted picklist, Sort Description Specifies whether this feed item is available in the default community, a specific community, or all communities. If Salesforce Communities is enabled for your organization, this field is available in API version 30.0 and later. NetworkScope can have the following values: • NetworkId—The ID of the community in which the FeedItem is available. If left empty, the feed item is only available in the default community. • AllNetworks—The feed item is available in all communities. Note the following exceptions for NetworkScope: • Only feed items with a Group or User parent can set a NetworkId or a null value for NetworkScope. • For feed items with a record parent, users can set NetworkScope only to AllNetworks. • You can't filter a FeedItem on the NetworkScope field.
ParentId	Type reference Properties Filter, Group, Sort Description ID of the group that is tracked in the feed. The feed is displayed on the detail page for this record.

Field Name	Details
RelatedRecordId	Type reference Properties Group, Nillable, Sort Description ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of Type ContentPost.
Title	Type string Properties Group, Nillable, Sort Description The title of the FeedItem. When the Type is LinkPost, the LinkUrl is the URL, and this field is the link name.
Type	Type picklist Properties Filter, Group, Nillable, Restricted picklist, Sort Description The type of feed item. With the exception of ContentPost, LinkPost, and TextPost, feed item types should not be created directly from the API • ActivityEvent—indirectly generated event when a user or the API adds a Task associated with a feed-enabled parent record (excluding email tasks on cases). Also occurs when a user or the API adds or updates a Task or Event associated with a case record (excluding email and call logging). For a recurring Task with CaseFeed disabled, one event is generated for the series only. For a recurring Task with CaseFeed enabled, events are generated for the series and each occurrence. • AdvancedTextPost—created when a user posts a group announcement. • AnnouncementPost—Not used. • ApprovalPost—generated when a user submits an approval. • BasicTemplateFeedItem—Not used. • CanvasPost—a post made by a canvas app posts on a feed. • CollaborationGroupCreated—generated when a user creates a public group. • CollaborationGroupUnarchived—Not used.

Field Name	Details
	• <code>ContentPost</code>—a post with an attached file. • <code>CreatedRecordEvent</code>—generated when a user creates a record from the publisher. • <code>DashboardComponentAlert</code>—generated when a dashboard metric or gauge exceeds a user-defined threshold. • <code>DashboardComponentSnapshot</code>—created when a user posts a dashboard snapshot on a feed. • <code>LinkPost</code>—a post with an attached URL. • <code>PollPost</code>—a poll posted on a feed. • <code>ProfileSkillPost</code>—generated when a skill is added to a user's Chatter profile. • <code>QuestionPost</code>—generated when a user posts a question. • <code>ReplyPost</code>—generated when Chatter Answers posts a reply. • <code>RypplePost</code>—generated when a user creates a Thanks badge in Work.com. • <code>TextPost</code>—a direct text entry on a feed. • <code>TrackedChange</code>—a change or group of changes to a tracked field. • <code>UserStatus</code>—automatically generated when a user adds a post. Deprecated. The following values appear in the <code>Type</code> picklist for all feed objects but apply only to CaseFeed: • <code>AttachArticleEvent</code>—generated event when a user attaches an article to a case. • <code>CallLogPost</code>—generated event when a user logs a call for a case through the user interface. CTI calls also generate this event. • <code>CaseCommentPost</code>—generated event when a user adds a case comment for a case object. • <code>ChangeStatusPost</code>—generated event when a user changes the status of a case. • <code>ChatTranscriptPost</code>—generated event when Live Agent transcript is saved to a case. • <code>EmailMessageEvent</code>—generated event when an email related to a case object is sent or received. • <code>FacebookPost</code>—generated when a Facebook post is created from a case. Deprecated. • <code>MilestoneEvent</code>—generated when a case milestone is completed or reaches violation status. • <code>SocialPost</code>—generated when a social post is created from a case.
Visibility	Type picklist

Field Name	Details
	Properties Filter, Group, Nillable, Restricted picklist, Sort
	Description The visibility of a FeedItem: • AllUsers: visible to all users • InternalUsers: visible to internal users

WorkPerformanceCycleHistory

Represents the history of changes to the values in the fields of a WorkPerformanceCycle.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed.
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed.
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed.

Field Name	Details
WorkPerformanceCycleId	Type reference Properties Filter, Group, Sort Description The ID of the WorkPerformanceCycle.

WorkPerformanceCycleShare

Represents a sharing entry on a WorkPerformanceCycle object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the work performance cycle. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records. This field must be set to an access level that is higher than the organization's default access level for work performance cycles.
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID of the WorkPerformanceCycle object that is associated with this sharing entry.

Field Name	Details
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Reason that this sharing entry exists. Read-only. Valid values include: - Owner: User is the owner of the WorkPerformanceCycle or is in a user role above the WorkPerformanceCycle owner in the role hierarchy. - Manual: User or group has access, because a user with “All” access manually shared the WorkPerformanceCycle with the user or group. - Rule: User or group has access via a WorkPerformanceCycle sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description ID of the user or group that was given access to the performance cycle share. This field can't be updated.

WorkReward

Used to store reward codes tied to a Reward Fund. Reward Funds must have at least one WorkReward record.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

You must have the Reward permission enabled in order to use the Rewards feature, including WorkRewardFund and WorkReward.

Additional Considerations and Related Objects

WorkReward is a lookup to WorkRewardFund. WorkRewardFund must have at least one WorkReward record to be available for use. Each WorkBadge record with a `RewardId` indicates a reward badge given to a Recipient.

Fields

Field Name	Details
Code	Type string Properties Create, Filter, Group, Sort, Update Description Represents a single reward code tied to a RewardFundId.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Represents the User ID of Owner of WorkReward record
RecipientId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description Salesforce User ID for User associated with this WorkReward record.
RedemptionDisclaimer	Type textarea Properties Nillable Description The disclaimer information about the WorkReward.
RedemptionInfo	Type textarea Properties Nillable Description The instructions for redeeming the WorkReward.
RedemptionUrl	Type textarea Properties Nillable

Field Name	Details
	Description The URL for redeeming the WorkReward.
RewardFundId	Type reference Properties Create, Filter, Group, Sort, Update Description Salesforce unique ID for WorkRewardFund record that is associated with WorkReward record.
RewardFundTypeId	Type reference Properties Create, Filter, Group, Sort, Update Description Salesforce unique ID of the WorkRewardFundType associated with the WorkReward.
Value	Type double Properties Filter, Nillable, Sort Description The value of the WorkReward.

WorkRewardFund

Represents a Reward Fund and describes the Reward Fund attributes.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Special Access Rules

To use the Rewards feature, including WorkRewardFund and WorkReward, you must have the Reward permission enabled. To create Rewards, the user must have Create on WorkRewardFund, which is not a standard permission.

Additional Considerations and Related Objects

WorkReward is a lookup to WorkRewardFund. WorkRewardFund must have at least one WorkReward record available. Each WorkBadgeDefinition with a RewardFundId is a "Reward Badge."

Fields

Field Name	Details
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Indicates whether the WorkRewardFund is active (<code>true</code>) or not (<code>false</code>).
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed a record that is related to this WorkRewardFund.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed this WorkRewardFund. If this value is null, this record might have been only referenced (<code>LastReferencedDate</code>) and not viewed.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description Required. Name of the Reward Fund.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field Name	Details
	Description Salesforce unique ID of User who is the Owner of the WorkRewardFund record.
RewardFundTypeId	Type reference Properties Create, Filter, Group, Sort, Update Description Salesforce unique ID of the WorkRewardFundType that is associated with the WorkRewardFund.
TotalCodeCount	Type int Properties Filter, Group, Nillable, Sort Description Total reward codes that are available in the WorkRewardFund. Derived from WorkReward records that are associated with the WorkRewardFund.
Type	Type string Properties Create, Filter, Group, Nillable, Sort, Update Description RewardType of the WorkRewardFund. Default is Amazon.com.
UsedCodeCount	Type int Properties Filter, Group, Nillable, Sort Description Total reward codes that are used in the WorkRewardFund. Derived from the total assigned WorkReward records that are associated with the WorkRewardFund.
Value	Type currency Properties Create, Filter, Sort, Update Description Value of each of the reward codes in the WorkRewardFund.

WorkRewardFundHistory

Represents the history of changes to the values in the fields of a WorkRewardFund object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Type of change (e.g., created).
NewValue	Type Any Type Properties Nillable, Sort Description Updated value of record.
OldValue	Type Any Type Properties Nillable, Sort Description Previous value of record.
WorkRewardFundId	Type reference Properties Filter, Group, Sort Description ID of WorkRewardFund record.

WorkRewardFundShare

Share records for WorkRewardFund.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description CRUD Access Level (picklist values: Read Only, Read/Write, Owner).
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID for WorkRewardFund record.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Owner or Manual sharing.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description User or Group ID for WorkRewardFund record.

WorkRewardFundType

Represents the type of WorkRewardFund object.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field Name	Details
CreditSystem	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The credit system that is used by the WorkRewardFundType object (gift codes or points). If points are selected, the reward message will not consider the CurrencyCode field.
CurrencyCode	Type picklist Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update Description The currency code of the WorkRewardFundType
IsActive	Type boolean Properties Create, Defaulted on create, Filter, Group, Sort, Update Description Whether the WorkRewardFundType is active and available in the UI
IsPredefined	Type boolean Properties Defaulted on create, Filter, Group, Sort Description Whether the WorkRewardFundType is predefined (<code>true</code>) or not (<code>false</code>)

Field Name	Details
LastReferencedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed a record that is related to this WorkRewardFundType.
LastViewedDate	Type dateTime Properties Filter, Nillable, Sort Description The time stamp that indicates when the current user last viewed this WorkRewardFundType. If this value is null, this record might have been only referenced (LastReferencedDate) and not viewed.
Name	Type string Properties Create, Filter, Group, idLookup, Sort, Update Description The name of the WorkRewardFundType
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update Description The ID of the WorkRewardFundType owner
RedemptionDisclaimer	Type textarea Properties Create, Nillable, Update Description The redemption disclaimer text for the WorkRewardFundType
RedemptionInfo	Type textarea Properties Create, Nillable, Update

Field Name	Details
	Description Redemption text for the WorkRewardFundType
RedemptionUrl	Type textarea Properties Create, Nillable, Update Description The URL that's linked to the redemption
UploadCodeColumn	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The column where the reward code is contained in the CSV file. The upload uses the second value by default.
UploadValueColumn	Type int Properties Create, Filter, Group, Nillable, Sort, Update Description The column where the reward value is contained in the CSV file. The upload uses the third column by default.

WorkRewardFundTypeHistory

Represents the history of changes to the values in the fields of a WorkRewardFundType object.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist

Field Name	Details
	Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed
NewValue	Type anyType Properties Nillable, Sort Description The value of the changed field
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed
WorkRewardFundTypeId	Type reference Properties Filter, Group, Sort Description The ID of the WorkRewardFundType

WorkRewardFundTypeShare

Represents a sharing entry on a WorkRewardFundType.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist

Field Name	Details
	Properties Create, Filter, Group, Restricted picklist, Sort, Update Description The user's or group's level of access to the work reward fund type. The possible values are: • Read • Edit • All: This value is not valid when you create, update, or delete records. This field must be set to an access level that is higher than the organization's default access level for WorkRewardFundType objects.
ParentId	Type reference Properties Create, Filter, Group, Sort Description The ID of the WorkRewardFundType object that is associated with this sharing entry.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The reason that this sharing entry exists. Read-only. Valid values include: • Owner: User is the owner of the WorkRewardFundType or is in a user role above the WorkRewardFundType owner in the role hierarchy. • Manual: User or group has access, because a user with "All" access manually shared the WorkRewardFundType with the user or group. • Rule: User or group has access via a WorkRewardFundType sharing rule.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description The ID of the user or group that was given access to the WorkRewardFundType. This field can't be updated.

WorkRewardHistory

Represents the history of changes to the fields of a WorkReward.

Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Fields

Field Name	Details
Field	Type picklist Properties Filter, Group, Restricted picklist, Sort Description The name of the field that was changed
NewValue	Type anyType Properties Nillable, Sort Description The new value of the field that was changed
OldValue	Type anyType Properties Nillable, Sort Description The latest value of the field before it was changed
WorkRewardId	Type reference Properties Filter, Group, Sort Description The ID of the WorkReward

WorkRewardShare

Share records for WorkReward object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
AccessLevel	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description CRUD Access Level (picklist values: Read Only, Read/Write, Owner).
ParentId	Type reference Properties Create, Filter, Group, Sort Description ID for WorkReward record.
RowCause	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Owner or Manual sharing.
UserOrGroupId	Type reference Properties Create, Filter, Group, Sort Description User or Group ID for WorkReward record.

WorkThanks

Represents the source and message of a thanks post.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Additional Considerations and Related Objects

WorkBadge is a lookup to WorkThanks. Each WorkBadge record must derive a SourceId from WorkThanks.

Fields

Field Name	Details
GiverId	Type reference Properties Create, Filter, Group, Sort Description Salesforce user ID for the giver of the Thanks record.
Message	Type textarea Properties Create Description Required. Message associated with the Thanks record.
NetworkId	Type reference Properties Create, Filter, Group, Nillable, Sort, Update Description The ID of the community that this WorkThanks is associated with. This field is available only if Salesforce Communities is enabled in your organization.
OwnerId	Type reference Properties Create, Defaulted on create, Filter, Group, Sort, Update

Field Name	Details
	Description Salesforce user ID for the owner of the badge record (typically the same user as the giver of the record).

WorkThanksShare

Share records for WorkThanks object.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field Name	Details
<code>AccessLevel</code>	Type picklist Properties Create, Filter, Group, Restricted picklist, Sort, Update Description CRUD Access Level (picklist values: Read Only, Read/Write, Owner).
<code>ParentId</code>	Type reference Properties Create, Filter, Group, Sort Description ID for WorkThanks record.
<code>RowCause</code>	Type picklist Properties Filter, Group, Restricted picklist, Sort Description Owner or Manual sharing.
<code>UserOrGroupId</code>	Type reference

Field Name**Details****Properties**

Create, Filter, Group, Sort

Description

User or Group ID for WorkThanks record.

CHAPTER 3 Data Model


The entity relationship diagrams (ERDs) for standard Salesforce objects in this section illustrate important relationships between objects. The available ERDs are:

- [Sales Objects](#)—includes accounts, contacts, opportunities, leads, campaigns, and other related objects
- [Task and Event Objects](#)—includes tasks and events and their related objects
- [Support Objects](#)—includes cases and solutions and their related objects
- [Salesforce Knowledge Objects](#)—includes view and vote statistics, article versions, and other related objects
- [Document, Note, and Attachment Objects](#)—includes documents, notes, and attachments and their related objects
- [User, Sharing, and Permission Objects](#)—includes users, profiles, and roles
- [Profile and Permission Objects](#)—includes users, profiles, permission sets, and related permission objects
- [Record Type Objects](#)—includes record types and business processes and their related objects
- [Product and Schedule Objects](#)—includes opportunities, products, and schedules
- [Sharing and Team Selling Objects](#)—includes account teams, opportunity teams, and sharing objects
- [Customizable Forecasting Objects](#)—includes forecasts and related objects
- [Forecasts Objects](#)—includes objects for Collaborative Forecasts.
- [Territory Management](#)—includes territories and related objects
- [Process Objects](#)—includes approval processes and related objects
- [Content Objects](#)—includes content and libraries and their related objects
- [Chatter Feed Objects](#)—includes objects related to feeds
- [Work.com Badge and Reward Objects](#)—includes badge and reward objects


Each entity relationship diagram includes links to the topics that describe the fields in objects related to the diagram. The data model for your custom objects depends on what you create.




Task and Event Objects




Support Objects




Document, Note, and Attachment Objects




User, Sharing, and Permission Objects




Profile and Permission Objects



Record Type Objects




Product and Schedule Objects




Create a separate PricebookEntry for each currency and price combination.

Sharing and Team Selling Objects




Customizable Forecasting Objects




Forecasts Objects

 **Note:** This information only applies to Collaborative Forecasts.




Territory Management 2.0 Objects


 **Note:** This information applies to Territory Management 2.0 only, not to previous versions of Territory Management.




Territory Management



Process Objects



Content Objects




Chatter Objects


Diagram showing the relationships between the Chatter objects

The following diagram shows the relationships between the major Chatter objects.

- A feed item is an entry in the feed, such as a change to a record that's being followed, an updated post, or a user status change.
- All feed items have a `ParentId`, which is either:
 - the record that is changed
 - the user who received the post




Chatter Feed Objects




Standard Objects with Feeds

The following standard objects can have Chatter feeds: [Account](#), [Asset](#), [Case](#), [CollaborationGroup](#), [Contact](#), [ContentDocument](#), [Contract](#), [Dashboard](#), [DashboardComponent](#), [Entitlement](#), [Event](#), [KnowledgeArticle](#), [Lead](#), [Opportunity](#), [Product2](#), [Quote](#), [Report](#), [ServiceContract](#), [Site](#), [Solution](#), [Task](#), [Topic](#), and [User](#).

Salesforce Knowledge Objects



Work.com Badge and Reward Objects



INDEX

A

AcceptedEventRelation object 50
Account object 52
AccountCleanInfo object 71
AccountContactRole object 92
AccountFeed object 93
AccountHistory object 100
AccountOwnerSharingRule object 101
AccountPartner object 104
AccountShare object 106
AccountTag object 109
AccountTeamMember object 110
AccountTerritoryAssignmentRule object 112
AccountTerritoryAssignmentRuleItem object 114
ActionLinkGroupTemplate object 118
ActionLinkTemplate object 121
ActivityHistory 125
AdditionalNumber object 133
address 9, 12
AgentWork object 134
AllowedEmailDomain object 136
Announcement object 137
ApexClass object 138
ApexComponent object 140
ApexLog object 143
ApexPage object 145
ApexTestQueueItem object 148
ApexTestResult object 150
ApexTrigger object 152
AppMenuItem object 156
Approval object 160
Article
 DataCategorySelection 163
Article Type__Feed object 164
Asset object 170
AssetFeed object 173
AssetTag object 183
AssignmentRule object 184
AsyncApexJob object 185
AttachedContentDocument object 188
Attachment object 190
AuraDefinition object 194
AuraDefinitionBundle object 195
AuthConfig object 197
AuthConfigProviders object 199

AuthProvider object 200
AuthSession object 205

B

Badge
 data model 1636
Bookmark object 208
BrandTemplate 209
BusinessProcess object 215

C

CallCenter object 217
Campaign object 219
CampaignFeed object 227
CampaignMember object 234
CampaignMemberStatus object 237
CampaignOwnerSharingRule object 238
CampaignShare object 240
CampaignTag object 242
Cascading deletes 22
Case object 243
CaseArticle object 252
CaseComment object 253
CaseContactRole object 256
CaseFeed object 257
CaseHistory object 263
CaseMilestone object 265
CaseOwnerSharingRule object 268
CaseShare object 270
CaseSolution object 271
CaseStatus object 272
CaseTag object 274
CaseTeamMember object 275
CaseTeamRole object 276
CaseTeamTemplate object 277
CaseTeamTemplateMember object 277
CaseTeamTemplateRecord object 278
CategoryData object 279
CategoryNode object 280
CategoryNodeLocalization object 281
Chatter
 objects 1632
ChatterActivity object 286
ChatterAnswersActivity object 288
ChatterAnswersReputationLevel object 292
ChatterConversation object 293

ChatterConversationMember object [294](#)
 ChatterMessage object [294](#)
 ClientBrowser object [296](#)
 CollaborationGroup object [297](#)
 CollaborationGroupFeed object [302](#)
 CollaborationGroupMember object [309](#)
 CollaborationGroupMemberRequest object [311](#)
 CollaborationGroupRecord object [312](#)
 CollaborationInvitation object [313](#)
 CombinedAttachment object [316](#)
 Community (Zone) object [318](#)
 compound fields [9, 11–12](#)
 ConnectedApplication object [319](#)
 Contact object [322](#)
 ContactCleanInfo object [333](#)
 ContactFeed object [342](#)
 ContactHistory object [348](#)
 ContactOwnerSharingRule object [349](#)
 ContactShare object [351](#)
 ContactTag object [353](#)
 ContentDistribution object [354](#)
 ContentDistributionView object [359](#)
 ContentDocument object [360](#)
 ContentDocumentFeed object [365](#)
 ContentDocumentHistory object [372](#)
 ContentDocumentLink object [373](#)
 ContentFolder object [376](#)
 ContentFolderLink object [376](#)
 ContentFolderMember object [377](#)
 ContentHubItem object [378](#)
 ContentHubRepository object [381](#)
 ContentNote object [383](#)
 ContentVersion object [385](#)
 ContentVersionHistory object [395](#)
 ContentWorkspace object [397](#)
 ContentWorkspaceDoc object [399](#)
 Contract object [401](#)
 ContractContactRole object [409](#)
 ContractFeed object [411](#)
 ContractHistory object [417](#)
 ContractLineItem object [418](#)
 ContractLineItemHistory object [422](#)
 ContractStatus object [424](#)
 ContractTag object [425](#)
 CreatedById fields [15](#)
 CreatedDate fields [15](#)
 CronJobDetail object [426](#)
 CronTrigger object [427](#)
 CurrencyType object [430](#)

Custom fields [17](#)
 Custom Metadata Type__mdt object [435](#)
 Custom Object__Feed object [437](#)
 Custom objects [18](#)
 CustomBrand object [432](#)
 CustomBrandAsset object [432](#)
 CustomPermission object [443](#)
 CustomPermissionDependency object [445](#)

D

DandBCompany object [447](#)
 Dashboard object [465](#)
 DashboardComponent object [470](#)
 DashboardComponentFeed object [470](#)
 DashboardFeed object [477](#)
 DashboardTag object [483](#)
 Data access
 standard objects [23](#)
 Data types, mapping API to Salesforce field types [14](#)
 DataCategorySelection article [163](#)
 DataCategorySelection question [1193](#)
 DatacloudCompany object [484](#)
 DatacloudContact object [492](#)
 DatacloudDandBCompany object [496](#)
 DatacloudOwnedEntity object [516](#)
 DatacloudPurchaseUsage object [517](#)
 DatacloudSocialHandle object [519](#)
 DatedConversionRate object [520](#)
 DcSocialProfile object [522](#)
 DcSocialProfileHandle object [524](#)
 DeclinedEventRelation object [525](#)
 Deleting and cascading deletes [22](#)
 Division object [526](#)
 DivisionLocalization object [527](#)
 Document object [529](#)
 DocumentAttachmentMap [533](#)
 DocumentTag object [535](#)
 Domain object [536](#)
 DomainSite object [537](#)
 DuplicateRule [541](#)

E

Effective dated currency [520](#)
 EmailDomainKey object [543](#)
 EmailMessage object [545](#)
 EmailServicesAddress object [549](#)
 EmailServicesFunction object [551](#)
 EmailStatus [556](#)
 EmailTemplate object [533, 557](#)

Entitlement object [562](#)
 EntitlementContact object [565](#)
 EntitlementFeed object [566](#)
 EntitlementHistory object [572](#)
 EntitlementTemplate object [574](#)
 EntityHistory object [576](#)
 EntitySubscription object [577](#)
 EnvironmentHubMember object [579](#)
 Event object [583](#)
 EventFeed object [596](#)
 EventLogFile [602](#)
 EventRelation object [679](#)
 EventTag object [683](#)
 EventWhoRelation object [685](#)
 External objects [21](#)
 ExternalDataSource object [686](#)
 ExternalDataUserAuth object [688](#)

F

FeedComment object [689](#)
 FeedItem object [693](#), [709](#)
 FeedLike object [702](#)
 FeedPollChoice object [703](#)
 FeedPollVote object [704](#)
 FeedPost object [705](#)
 Feeds
 custom [710](#)
 post [705](#), [710](#)
 standard [710](#)
 FeedTrackedChange object [710](#)
 Field types [3](#), [9](#), [11–12](#)
 FieldHistoryArchive object [713](#)
 FieldPermissions object [716](#)
 Fields
 custom fields [17](#)
 system fields [15](#)
 FiscalYearSettings object [719](#)
 FlowInterview object [722](#)
 Folder object [723](#)
 ForecastingAdjustment object [726](#)
 ForecastingFact object [730](#)
 ForecastingItem object [732](#)
 ForecastingOwnerAdjustment object [738](#)
 ForecastingQuota object [742](#)
 ForecastingType object [744](#)
 ForecastShare object [746](#)
 Freeze users [1458](#)

G

geolocation [9](#), [11–12](#)
 Goal object [748](#)
 GoalFeed object [750](#)
 GoalHistory object [755](#)
 GoalLink object [756](#)
 GoalShare object [757](#)
 GoogleDoc object [758](#)
 Group object [759](#)
 GroupMember object [762](#)

H

HashtagDefinition object [763](#)
 Holiday object [764](#)

I

ID fields [15](#)
 Idea object [768](#)
 IdeaComment object [774](#)
 IdeaReputation [776](#)
 IdeaReputationLevel object [778](#)
 IdeaTheme object [779](#)

K

KnowledgeableUser object [781](#)
 KnowledgeArticle object [782](#)
 KnowledgeArticleVersion object [784](#)
 KnowledgeArticleVersionHistory object [791](#)
 KnowledgeArticleViewStat object [794](#)
 KnowledgeArticleVoteStat object [795](#)

L

LastModifiedById fields [15](#)
 LastModifiedDate fields [15](#)
 Lead object [797](#)
 LeadCleanInfo object [813](#)
 LeadFeed object [827](#)
 LeadHistory object [833](#)
 LeadOwnerSharingRule object [835](#)
 LeadShare object [836](#)
 LeadStatus object [838](#)
 LeadTag object [839](#)
 LimitAllocationPerApp object [841](#)
 LineItemOverride object [843](#)
 ListView object [845](#)
 ListViewChart object [847](#)
 ListViewChartInstance object [849](#)
 LiveAgentSession object [853](#)
 LiveAgentSessionHistory object [856](#)

[LiveAgentSessionOwnerSharingRule object 857](#)
[LiveAgentSessionShare object 859](#)
[LiveChatBlockingRule object 860](#)
[LiveChatButton object 862](#)
[LiveChatButtonDeployment object 870](#)
[LiveChatButtonSkill object 871](#)
[LiveChatDeployment object 872](#)
[LiveChatTranscript object 874](#)
[LiveChatTranscriptEvent object 881](#)
[LiveChatTranscriptHistory object 883](#)
[LiveChatTranscriptOwnerSharingRule 884](#)
[LiveChatTranscriptOwnerSharingRule object](#)
 [LiveChatTranscriptOwnerSharingRule 884](#)
[LiveChatTranscriptShare object 886](#)
[LiveChatTranscriptSkill object 887](#)
[LiveChatUserConfig object 888](#)
[LiveChatUserConfigProfile object 894](#)
[LiveChatUserConfigUser object 895](#)
[LiveChatVisitor object 896](#)
[location 9, 11](#)
[LoginGeo object 897](#)
[LoginHistory object 899](#)
[LoginIp object 903](#)
[LookedUpFromActivity object 904](#)
[Lookup relationships 22](#)

M

[MailmergeTemplate object 910](#)
[map 9, 11](#)
[Mapping API data types to Salesforce field types 14](#)
[Master-detail relationships 22](#)
[Metric object 912](#)
[MetricDataLink object 916](#)
[MetricDataLinkHistory object 917](#)
[MetricFeed object 918](#)
[MetricHistory object 922](#)
[MetricsDataFile object 923](#)
[MetricShare object 926](#)
[MilestoneType object 927](#)
[mobile 9, 11](#)

N

[NamedCredential object 932](#)
[Network object 934](#)
[NetworkActivityAudit object 940](#)
[NetworkMember object 943](#)
[NetworkMemberGroup object 948](#)
[NetworkModeration object 949](#)
[NetworkPageOverride object 951](#)

[NetworkSelfRegistration object 952](#)
[NewsFeed object 953](#)
[Note object 959](#)
[NoteAndAttachment object 963](#)
[NoteTag object 965](#)

O

[OAuthToken object 961](#)
[Object_asset 179](#)
[Object_Assets 181](#)
[Object\[PushTopic\] 1174](#)
[Object\[StreamingChannel\] 1347](#)
[ObjectPermissions object 966](#)
[Objects](#)
 [AcceptedEventRelation 50](#)
 [Account 52](#)
 [AccountCleanInfo 71](#)
 [AccountContractRole 92](#)
 [AccountFeed 93](#)
 [AccountHistory 100](#)
 [AccountOwnerSharingRule 101](#)
 [AccountPartner 104](#)
 [AccountShare 106](#)
 [AccountTag 109](#)
 [AccountTeamMember 110](#)
 [AccountTerritoryAssignmentRule 112](#)
 [AccountTerritoryAssignmentRuleItem 114](#)
 [ActionLinkGroupTemplate 118](#)
 [ActionLinkTemplate 121](#)
 [ActivityHistory 125](#)
 [AdditionalNumber 133](#)
 [AgentWork 134](#)
 [AllowedEmailDomain 136](#)
 [Announcement 137](#)
 [ApexClass 138](#)
 [ApexComponent 140](#)
 [ApexLog 143](#)
 [ApexPage 145](#)
 [ApexTestQueueItem 148](#)
 [ApexTestResult 150](#)
 [ApexTrigger 152](#)
 [AppMenuItem 156](#)
 [Approval 160](#)
 [Article Type__Feed 164](#)
 [Asset 170](#)
 [AssetFeed 173](#)
 [Assets 179, 181](#)
 [AssetTag 183](#)
 [AssignmentRule 184](#)

Objects (continued)

AsyncApexJob [185](#)
AttachedContentDocument [188](#)
Attachment [190](#)
AuraDefinition [194](#)
AuraDefinitionBundle [195](#)
AuthConfig [197](#)
AuthConfigProviders [199](#)
AuthProvider [200](#)
AuthSession [205](#)
Bookmark [208](#)
BrandTemplate [209](#)
BusinessProcess [215](#)
CallCenter [217](#)
Campaign [219](#)
CampaignFeed [227](#)
CampaignMember [234](#)
CampaignMemberStatus [237](#)
CampaignOwnerSharingRule [238](#)
CampaignShare [240](#)
CampaignTag [242](#)
Case [243](#)
CaseArticle [252](#)
CaseComment [253](#)
CaseContactRole [256](#)
CaseFeed [257](#)
CaseHistory [263](#)
CaseMilestone [265](#)
CaseOwnerSharingRule [268](#)
CaseShare [270](#)
CaseSolution [271](#)
CaseStatus [272](#)
CaseTag [274](#)
CaseTeamMember [275](#)
CaseTeamRole [276](#)
CaseTeamTemplate [277](#)
CaseTeamTemplateMember [277](#)
CaseTeamTemplateRecord [278](#)
CategoryData [279](#)
CategoryNode [280](#)
CategoryNodeLocalization [281](#)
ChatterActivity [286](#)
ChatterAnswersActivity [288](#)
ChatterAnswersReputationLevel [292](#)
ChatterConversation [293](#)
ChatterConversationMember [294](#)
ChatterMessage [294](#)
ClientBrowser [296](#)
CollaborationGroup [297](#)

Objects (continued)

CollaborationGroupFeed [302](#)
CollaborationGroupMember [309](#)
CollaborationGroupMemberRequest [311](#)
CollaborationGroupRecord [312](#)
CollaborationInvitation [313](#)
CombinedAttachment [316](#)
Community (Zone) [318](#)
ConnectedApplication [319](#)
Contact [322](#)
ContactCleanInfo [333](#)
ContactFeed [342](#)
ContactHistory [348](#)
ContactOwnerSharingRule [349](#)
ContactShare [351](#)
ContactTag [353](#)
ContentDistribution [354](#)
ContentDistributionView [359](#)
ContentDocument [360](#)
ContentDocumentFeed [365](#)
ContentDocumentHistory [372](#)
ContentDocumentLink [373](#)
ContentFolder [376](#)
ContentFolderLink [376](#)
ContentFolderMember [377](#)
ContentHubItem [378](#)
ContentHubRepository [381](#)
ContentNote [383](#)
ContentVersion [385](#)
ContentVersionHistory [395](#)
ContentWorkspace [397](#)
ContentWorkspaceDoc [399](#)
Contract [401](#)
ContractContactRole [409](#)
ContractFeed [411](#)
ContractHistory [417](#)
ContractLineItem [418](#)
ContractLineItemHistory [422](#)
ContractStatus [424](#)
ContractTag [425](#)
CronJobDetail [426](#)
CronTrigger [427](#)
CurrencyType [430](#)
Custom Metadata Type__mdt [435](#)
Custom Object__Feed [437](#)
custom objects [18](#)
CustomBrand [432](#)
CustomBrandAsset [432](#)
CustomPermission [443](#)

Objects (*continued*)

CustomPermissionDependency [445](#)
 DandBCompany [447](#)
 Dashboard [465](#)
 DashboardComponent [470](#)
 DashboardComponentFeed [470](#)
 DashboardFeed [477](#)
 DashboardTag [483](#)
 DatacloudCompany [484](#)
 DatacloudContact [492](#)
 DatacloudDandBCompany [496](#)
 DatacloudOwnedEntity [516](#)
 DatacloudPurchaseUsage [517](#)
 DatacloudSocialHandle [519](#)
 DatedConversionRate [520](#)
 DcSocialProfile [522](#)
 DcSocialProfileHandle [524](#)
 DeclinedEventRelation [525](#)
 Division [526](#)
 DivisionLocalization [527](#)
 Document [529](#)
 DocumentAttachmentMap [533](#)
 DocumentTag [535](#)
 Domain [536](#)
 DomainSite [537](#)
 DuplicateRule [541](#)
 EmailDomainKey [543](#)
 EmailMessage [545](#)
 EmailServicesAddress [549](#)
 EmailServicesFunction [551](#)
 EmailStatus [556](#)
 EmailTemplate [557](#)
 Entitlement [562](#)
 EntitlementContact [565](#)
 EntitlementFeed [566](#)
 EntitlementHistory [572](#)
 EntitlementTemplate [574](#)
 EntityHistory [576](#)
 EntitySubscription [577](#)
 EnvironmentHubMember [579](#)
 Event [583](#)
 EventFeed [596](#)
 EventLogFile [602](#)
 EventRelation [679](#)
 EventTag [683](#)
 EventWhoRelation [685](#)
 external objects [21](#)
 ExternalDataSource [686](#)
 ExternalDataUserAuth [688](#)

Objects (*continued*)

FeedComment [689](#)
 FeedItem [693](#)
 FeedLike [702](#)
 FeedPollChoice [703](#)
 FeedPollVote [704](#)
 FeedPost [705](#)
 FeedRevision [709](#)
 FeedTrackedChange [710](#)
 FieldHistoryArchive [713](#)
 FieldPermissions [716](#)
 FiscalYearSettings [719](#)
 FlowInterview [722](#)
 Folder [723](#)
 ForecastingAdjustment [726](#)
 ForecastingFact [730](#)
 ForecastingItem [732](#)
 ForecastingOwnerAdjustment [738](#)
 ForecastingQuota [742](#)
 ForecastingType [744](#)
 ForecastShare [746](#)
 Goal [748](#)
 GoalFeed [750](#)
 GoalHistory [755](#)
 GoalLink [756](#)
 GoalShare [757](#)
 GoogleDoc [758](#)
 Group [759](#)
 GroupMember [762](#)
 HashtagDefinition [763](#)
 Holiday [764](#)
 Idea [768](#)
 idea comment [774](#)
 IdeaReputation [776](#)
 IdeaReputationLevel [778](#)
 IdeaTheme [779](#)
 KnowledgeableUser [781](#)
 KnowledgeArticle [782](#)
 KnowledgeArticleVersion [784](#)
 KnowledgeArticleVersionHistory [791](#)
 KnowledgeArticleViewStat [794](#)
 KnowledgeArticleVoteStat [795](#)
 Lead [797](#)
 LeadCleanInfo [813](#)
 LeadFeed [827](#)
 LeadHistory [833](#)
 LeadOwnerSharingRule [835](#)
 LeadShare [836](#)
 LeadStatus [838](#)

Objects (*continued*)

- [LeadTag](#) 839
- [LimitAllocationPerApp](#) 841
- [LinItemOverride](#) 843
- [ListView](#) 845
- [ListViewChart](#) 847
- [ListViewChartInstance](#) 849
- [LiveAgentSession](#) 853
- [LiveAgentSessionHistory](#) 856
- [LiveAgentSessionOwnerSharingRule](#) 857
- [LiveAgentSessionShare](#) 859
- [LiveChatBlockingRule](#) 860
- [LiveChatButton](#) 862
- [LiveChatButtonDeployment](#) 870
- [LiveChatButtonSkill](#) 871
- [LiveChatDeployment](#) 872
- [LiveChatTranscript](#) 874
- [LiveChatTranscriptEvent](#) 881
- [LiveChatTranscriptHistory](#) 883
- [LiveChatTranscriptShare](#) 886
- [LiveChatTranscriptSkill](#) 887
- [LiveChatUserConfig](#) 888
- [LiveChatUserConfigProfile](#) 894
- [LiveChatUserConfigUser](#) 895
- [LiveChatVisitor](#) 896
- [LoginGeo](#) 897
- [LoginHistory](#) 899
- [LoginIp](#) 903
- [LookedUpFromActivity](#) 904
- [MailmergeTemplate](#) 910
- [Metric](#) 912
- [MetricDataLink](#) 916
- [MetricDataLinkHistory](#) 917
- [MetricFeed](#) 918
- [MetricHistory](#) 922
- [MetricsDataFile](#) 923
- [MetricShare](#) 926
- [MilestoneType](#) 927
- [NamedCredential](#) 932
- [Network](#) 934
- [NetworkActivityAudit](#) 940
- [NetworkMember](#) 943
- [NetworkMemberGroup](#) 948
- [NetworkModeration](#) 949
- [NetworkPageOverride](#) 951
- [NetworkSelfRegistration](#) 952
- [NewsFeed](#) 953
- [Note](#) 959
- [NoteAndAttachment](#) 963

Objects (*continued*)

- [NoteTag](#) 965
- [OAuthToken](#) 961
- [ObjectPermissions](#) 966
- [ObjectTerritory2AssignmentRule](#) 969
- [ObjectTerritory2AssignmentRuleItem](#) 971
- [ObjectTerritory2Association](#) 973
- [OpenActivity](#) 974
- [Opportunity](#) 981
- [OpportunityCompetitor](#) 991
- [OpportunityContactRole](#) 992
- [OpportunityFeed](#) 993
- [OpportunityFieldHistory](#) 1000
- [OpportunityHistory](#) 1001
- [OpportunityLinItem](#) 1003
- [OpportunityLinItemSchedule](#) 1010
- [OpportunityOverride](#) 1013
- [OpportunityOwnerSharingRule](#) 1016
- [OpportunityPartner](#) 1018
- [OpportunityShare](#) 1020
- [OpportunitySplit](#) 1021
- [OpportunitySplitType](#) 1023
- [OpportunityStage](#) 1025
- [OpportunityTag](#) 1028
- [OpportunityTeamMember](#) 1029
- [Order](#) 1031
- [OrderFeed](#) 1041
- [OrderHistory](#) 1046
- [OrderItem](#) 1048
- [OrderItemFeed](#) 1050
- [OrderItemHistory](#) 1056
- [OrderOwnerSharingRule](#) 1057
- [Organization](#) 1060
- [OrgWideEmailAddress](#) 1078
- [OwnedContentDocument](#) 1079
- [PackageLicense](#) 1081
- [Partner](#) 1083
- [PartnerNetworkConnection](#) 1086
- [PartnerNetworkRecordConnection](#) 1088
- [PartnerNetworkSyncLog](#) 1092
- [PartnerRole](#) 1093
- [Period](#) 1095
- [PermissionSet](#) 1096
- [PermissionSetAssignment](#) 1102
- [PermissionSetLicense](#) 1103
- [PermissionSetLicenseAssign](#) 1106
- [PlatformAction](#) 1107
- [PresenceUserConfig](#) 1112
- [PresenceUserConfigProfile](#) 1114

Objects (*continued*)

PresenceUserConfigUser [1115](#)
 Pricebook2 [1115](#)
 Pricebook2History [1119](#)
 PricebookEntry [1120](#)
 ProcessDefinition [1123](#)
 ProcessInstance [1125](#)
 ProcessInstanceHistory [1127](#)
 ProcessInstanceNode [1132](#)
 ProcessInstanceStep [1130](#)
 ProcessInstanceWorkitem [1134](#)
 ProcessNode [1136](#)
 Product2 [1138](#)
 Product2Feed [1143](#)
 ProductEntitlementTemplate [1150](#)
 Profile [1150](#)
 ProfileSkill [1153](#)
 ProfileSkillEndorsement [1155](#)
 ProfileSkillEndorsementFeed [1156](#)
 ProfileSkillEndorsementHistory [1160](#)
 ProfileSkillFeed [1161](#)
 ProfileSkillHistory [1165](#)
 ProfileSkillShare [1166](#)
 ProfileSkillUser [1168](#)
 ProfileSkillUserFeed [1169](#)
 ProfileSkillUserHistory [1173](#)
 QuantityForecast [1176](#)
 QuantityForecastHistory [1183](#)
 Question [1188](#)
 QuestionReportAbuse [1195](#)
 QuestionSubscription [1195](#)
 QueueRoutingConfig [1186](#)
 QueueSubject [1197](#)
 QuickText [1198](#)
 QuickTextHistory [1200](#)
 QuickTextOwnerSharingRule [1201](#)
 QuickTextShare [1203](#)
 Quote [1204](#)
 QuoteDocument [1217](#)
 QuoteLineItem [1218](#)
 RecentlyViewed [1222](#)
 RecordType [1226](#)
 RecordTypeLocalization [1229](#)
 Reply [1230](#)
 ReplyReportAbuse [1233](#)
 Report [1234](#)
 ReportFeed [1237](#)
 ReportTag [1243](#)
 ReputationLevel [1244](#)

Objects (*continued*)

ReputationPointsRule [1246](#)
 RevenueForecast [1247](#)
 RevenueForecastHistory [1255](#)
 RuleTerritory2Association [1258](#)
 SamISsoConfig [1259](#)
 Scontrol [1264](#)
 ScontrolLocalization [1267](#)
 SearchPromotionRule [1272](#)
 SelfServiceUser [1273](#)
 ServiceChannel [1276](#)
 ServiceChannelStatus [1278](#)
 ServiceContract [1279](#)
 ServiceContractFeed [1286](#)
 ServiceContractHistory [1293](#)
 ServiceContractOwnerSharingRule [1294](#)
 ServiceContractShare [1296](#)
 ServicePresenceStatus [1297](#)
 SetupEntityAccess [1298](#)
 SignupRequest [1300](#)
 Site [1307](#)
 SiteDomain [1312](#)
 SiteHistory [1313](#)
 Skill [1314](#)
 SkillProfile [1315](#)
 SkillUser [1316](#)
 SlaProcess [1317](#)
 Solution [1320](#)
 SolutionFeed [1323](#)
 SolutionHistory [1330](#)
 SolutionStatus [1331](#)
 SolutionTag [1333](#)
 SOSDeployment [1334](#)
 SOSSession [1336](#)
 SOSSessionActivity [1339](#)
 SOSSessionHistory [1340](#)
 SOSSessionOwnerSharingRule [1341](#)
 SOSSessionShare [1343](#)
 standard objects [26](#)
 StaticResource [1344](#)
 TagDefinition [1348](#)
 Task [1350](#)
 TaskFeed [1361](#)
 TaskPriority [1367](#)
 TaskRelation [1369](#)
 TaskStatus [1371](#)
 TaskTag [1372](#)
 TaskWhoRelation [1373](#)
 TenantSecret [1375](#)

Objects (*continued*)

[Territory](#) 1377
[Territory2](#) 1379
[Territory2Model](#) 1382
[Territory2ModelHistory](#) 1384
[Territory2Type](#) 1385
[ThirdPartyAccountLink](#) 1387
[Topic](#) 1389
[TopicAssignment](#) 1390
[TopicFeed](#) 1392
[TopicLocalization](#) 1398
[TwoFactorInfo](#) 1403
[UndecidedEventRelation](#) 1404
[User](#) 1405
[UserAccountTeamMember](#) 1443
[UserConfigTransferButton](#) 1446
[UserConfigTransferSkill](#) 1447
[UserFeed](#) 1447
[UserLicense](#) 1454
[UserLogin](#) 1457
[UserMembershipSharingRule](#) 1458
[UserPackageLicense](#) 1460
[UserPreference](#) 1461
[UserProfile](#) 1462
[UserProfileFeed](#) 1480
[UserProvAccount](#) 1487
[UserProvAccountStaging](#) 1490
[UserProvisioningConfig](#) 1495
[UserProvisioningLog](#) 1498
[UserProvisioningRequest](#) 1500
[UserProvisioningRequestOwnerSharingRule](#) 1505
[UserProvisioningRequestShare](#) 1506
[UserProvMockTarget](#) 1493
[UserRecordAccess](#) 1508
[UserRole](#) 1510
[UserServicePresence](#) 1514
[UserShare](#) 1515
[UserTeamMember](#) 1516
[UserTerritory](#) 1518
[UserTerritory2Association](#) 1519
[vote](#) 1520
[WebLink](#) 1522
[WebLinkLocalization](#) 1527
[WorkAccess](#) 1532
[WorkAccessShare](#) 1533
[WorkBadge](#) 1534
[WorkBadgeDefinition](#) 1536
[WorkBadgeDefinitionHistory](#) 1540
[WorkBadgeDefinitionShare](#) 1541

Objects (*continued*)

[WorkCoaching](#) 1542
[WorkCoachingFeed](#) 1544
[WorkCoachingHistory](#) 1549
[WorkCoachingShare](#) 1550
[WorkFeedback](#) 1551
[WorkFeedbackHistory](#) 1553
[WorkFeedbackQuestion](#) 1554
[WorkFeedbackQuestionHistory](#) 1556
[WorkFeedbackQuestionSet](#) 1557
[WorkFeedbackQuestionSetHistory](#) 1558
[WorkFeedbackQuestionSetShare](#) 1559
[WorkFeedbackQuestionShare](#) 1561
[WorkFeedbackRequest](#) 1562
[WorkFeedbackRequestFeed](#) 1568
[WorkFeedbackRequestHistory](#) 1572
[WorkFeedbackRequestShare](#) 1573
[WorkFeedbackShare](#) 1574
[WorkFeedbackTemplate](#) 1576
[WorkFeedbackTemplateShare](#) 1576
[WorkGoal](#) 1576
[WorkGoalCollaborator](#) 1582
[WorkGoalCollaboratorHistory](#) 1583
[WorkGoalFeed](#) 1584
[WorkGoalHistory](#) 1589
[WorkGoalLink](#) 1590
[WorkGoalShare](#) 1591
[WorkPerformanceCycle](#) 1593
[WorkPerformanceCycleFeed](#) 1595
[WorkPerformanceCycleHistory](#) 1600
[WorkPerformanceCycleShare](#) 1601
[WorkReward](#) 1602
[WorkRewardFund](#) 1604
[WorkRewardFundHistory](#) 1607
[WorkRewardFundShare](#) 1608
[WorkRewardFundType](#) 1609
[WorkRewardFundTypeHistory](#) 1611
[WorkRewardFundTypeShare](#) 1612
[WorkRewardHistory](#) 1614
[WorkRewardShare](#) 1615
[WorkThanks](#) 1616
[WorkThanksShare](#) 1617
[ObjectTerritory2AssignmentRule](#) object 969
[ObjectTerritory2AssignmentRuleItem](#) object 971
[ObjectTerritory2Association](#) object 973
[OpenActivity](#) object 974
[Opportunity](#) object 981
[OpportunityCompetitor](#) object 991
[OpportunityContactRole](#) object 992

OpportunityFeed object [993](#)
 OpportunityFieldHistory object [1000](#)
 OpportunityHistory object [1001](#)
 OpportunityLineItem object [1003](#)
 OpportunityLineItemSchedule object [1010](#)
 OpportunityOverride object [1013](#)
 OpportunityOwnerSharingRule object [1016](#)
 OpportunityPartner object [1018](#)
 OpportunityShare object [1020](#)
 OpportunitySplit object [1021](#)
 OpportunitySplitType object [1023](#)
 OpportunityStage object [1025](#)
 OpportunityTag object [1028](#)
 OpportunityTeamMember object [1029](#)
 Order object [1031](#)
 OrderFeed object [1041](#)
 OrderHistory object [1046](#)
 OrderItem object [1048](#)
 OrderItemFeed object [1050](#)
 OrderItemHistory object [1056](#)
 OrderOwnerSharingRule object [1057](#)
 Organization object [1060](#)
 OrgWideEmailAddress object [1078](#)
 OwnedContentDocument object [1079](#)

P

PackageLicense object [1081](#)
 Partner object [1083](#)
 PartnerNetworkConnection object [1086](#)
 PartnerNetworkRecordConnection object [1088](#)
 PartnerNetworkSyncLog object [1092](#)
 PartnerRole object [1093](#)
 Period object [1095](#)
 PermissionSet object [1096](#)
 PermissionSetAssignment object [1102](#)
 PermissionSetLicense object [1103](#)
 PermissionSetLicenseAssign object [1106](#)
 PlatformAction object [1107](#)
 Posts [705](#), [710](#)
 PresenceUserConfig object [1112](#)
 PresenceUserConfigProfile object [1114–1115](#)
 Pricebook2 object [1115](#)
 Pricebook2History object [1119](#)
 PricebookEntry object [1120](#)
 ProcessDefinition object [1123](#)
 ProcessInstance object [1125](#)
 ProcessInstanceHistory object [1127](#)
 ProcessInstanceNode object [1132](#)
 ProcessInstanceStep object [1130](#)

ProcessInstanceWorkitem [1134](#)
 ProcessNode object [1136](#)
 Product2 object [1138](#)
 Product2Feed object [1143](#)
 ProductEntitlementTemplate object [1150](#)
 Profile object [1150](#)
 ProfileSkill object [1153](#)
 ProfileSkillEndorsement object [1155](#)
 ProfileSkillEndorsementFeed object [1156](#)
 ProfileSkillEndorsementHistory object [1160](#)
 ProfileSkillFeed object [1161](#)
 ProfileSkillHistory object [1165](#)
 ProfileSkillShare object [1166](#)
 ProfileSkillUser object [1168](#)
 ProfileSkillUserFeed object [1169](#)
 ProfileSkillUserHistory object [1173](#)
 PushTopic object [1174](#)

Q

QuantityForecast object [1176](#)
 QuantityForecastHistory object [1183](#)
 Question object [1188](#)
 QuestionDataCategorySelection [1193](#)
 QuestionReportAbuse object [1195](#)
 QuestionSubscription object [1195](#)
 QueueRoutingConfig object [1186](#)
 QueueSubject object [1197](#)
 QuickText object [1198](#)
 QuickTextHistory object [1200](#)
 QuickTextOwnerSharingRule object [1201](#)
 QuickTextShare object [1203](#)
 Quote object [1204](#)
 QuoteDocument object [1217](#)
 QuoteLineItem object [1218](#)

R

RecentlyViewedobject [1222](#)
 RecordType object [1226](#)
 RecordTypeLocalization object [1229](#)
 Relationships
 parent reference fields in child object [16](#)
 Reply object [1230](#)
 ReplyReportAbuse object [1233](#)
 Report object [1234](#)
 ReportFeed object [1237](#)
 ReportTag object [1243](#)
 ReputationLevel object [1244](#)
 ReputationPointsRule object [1246](#)
 RevenueForecast object [1247](#)

RevenueForecastHistory object [1255](#)
 Reward
 data model [1636](#)
 Role, see [UserRole 1510](#)
 RuleTerritory2Association object [1258](#)

S

SamlSsoConfig object [1259](#)
 Scontrol object [1264](#)
 ScontrolLocalization object [1267](#)
 SearchPromotionRule object [1272](#)
 SelfServiceUser object [1273](#)
 ServiceChannel object [1276](#)
 ServiceChannelStatus object [1278](#)
 ServiceContract object [1279](#)
 ServiceContractFeed object [1286](#)
 ServiceContractHistory object [1293](#)
 ServiceContractOwnerSharingRule object [1294](#)
 ServiceContractShare object [1296](#)
 ServicePresenceStatus object [1297](#)
 SetupEntityAccess object [1298](#)
 SignupRequest object [1300](#)
 Site object [1307](#)
 SiteDomain object [1312](#)
 SiteHistory object [1313](#)
 Skill object [1314](#)
 SkillProfile object [1315](#)
 SkillUser object [1316](#)
 SlaProcess object [1317](#)
 Solution object [1320](#)
 SolutionFeed object [1323](#)
 SolutionHistory object [1330](#)
 SolutionStatus object [1331](#)
 SolutionTag object [1333](#)
 SOSDeployment object [1334](#)
 SOSSession object [1336](#)
 SOSSessionActivity object [1339](#)
 SOSSessionHistory object [1340](#)
 SOSSessionOwnerSharingRule object [1341](#)
 SOSSessionShare object [1343](#)
 Standard objects
 data access [23](#)
 StaticResource object [1344](#)
 StreamingChannel object [1347](#)
 System fields [15](#)
 SystemModstamp fields [15](#)

T

TagDefinition object [1348](#)

Task object [1350](#)
 TaskFeed object [1361](#)
 TaskPriority object [1367](#)
 TaskRelation object [1369](#)
 TaskStatus object [1371](#)
 TaskTag object [1372](#)
 TaskWhoRelation object [1373](#)
 TenantSecret object [1375](#)
 Territory object [1377](#)
 Territory2 object [1379](#)
 Territory2Model object [1382](#)
 Territory2ModelHistory object [1384](#)
 Territory2Type object [1385](#)
 ThirdPartyAccountLink object [1387](#)
 Topic object [1389](#)
 TopicAssignment object [1390](#)
 TopicFeed object [1392](#)
 TopicLocalization object [1398](#)
 TwoFactorInfo object [1403](#)
 Types of fields [3, 9, 11–12](#)

U

UndecidedEventRelation object [1404](#)
 User object [1405](#)
 UserAccountTeamMember object [1443](#)
 UserConfigTransferButton object [1446](#)
 UserConfigTransferSkill object [1447](#)
 UserFeed object [1447](#)
 UserLicense object [1454](#)
 UserLogin object [1457](#)
 UserMembershipSharingRule object [1458](#)
 UserPackageLicense object [1460](#)
 UserPreference object [1461](#)
 UserProfile object [1462](#)
 UserProfileFeed object [1480](#)
 UserProvAccount object [1487](#)
 UserProvAccountStaging object [1490](#)
 UserProvisioningConfig object [1495](#)
 UserProvisioningLog object [1498](#)
 UserProvisioningRequest object [1500](#)
 UserProvisioningRequestOwnerSharingRule object [1505](#)
 UserProvisioningRequestShare object [1506](#)
 UserProvMockTarget object [1493](#)
 UserRecordAccess object [1508](#)
 UserRole object [1510](#)
 UserServicePresence object [1514](#)
 UserShare object [1515](#)
 UserTeamMember object [1516](#)
 UserTerritory object [1518](#)

UserTerritory2Association object [1519](#)

V

Vote object [1520](#)

W

WebLink object [1522](#)

WebLinkLocalization object [1527](#)

WorkAccess object [1532](#)

WorkAccessShare object [1533](#)

WorkBadge object [1534](#)

WorkBadgeDefinition object [1536](#)

WorkBadgeDefinitionHistory object [1540](#)

WorkBadgeDefinitionShare object [1541](#)

WorkCoaching object [1542](#)

WorkCoachingFeed object [1544](#)

WorkCoachingHistory object [1549](#)

WorkCoachingShare object [1550](#)

WorkFeedback object [1551](#)

WorkFeedbackHistory object [1553](#)

WorkFeedbackQuestion object [1554](#)

WorkFeedbackQuestionHistory object [1556](#)

WorkFeedbackQuestionSet object [1557](#)

WorkFeedbackQuestionSetHistory object [1558](#)

WorkFeedbackQuestionSetShare object [1559](#)

WorkFeedbackQuestionShare object [1561](#)

WorkFeedbackRequest object [1562](#)

WorkFeedbackRequestFeed object [1568](#)

WorkFeedbackRequestHistory object [1572](#)

WorkFeedbackRequestShare object [1573](#)

WorkFeedbackShare object [1574](#)

WorkFeedbackTemplate object [1576](#)

WorkFeedbackTemplateShare object [1576](#)

WorkGoal object [1576](#)

WorkGoalCollaborator object [1582](#)

WorkGoalCollaboratorHistory object [1583](#)

WorkGoalFeed object [1584](#)

WorkGoalHistory object [1589](#)

WorkGoalLink object [1590](#)

WorkGoalShare object [1591](#)

WorkPerformanceCycle object [1593](#)

WorkPerformanceCycleFeed object [1595](#)

WorkPerformanceCycleHistory object [1600](#)

WorkPerformanceCycleShare object [1601](#)

WorkReward object [1602](#)

WorkRewardFund object [1604](#)

WorkRewardFundHistory object [1607](#)

WorkRewardFundShare object [1608](#)

WorkRewardFundType object [1609](#)

WorkRewardFundTypeHistory object [1611](#)

WorkRewardFundTypeShare object [1612](#)

WorkRewardHistory object [1614](#)

WorkRewardShare object [1615](#)

WorkThanks object [1616](#)

WorkThanksShare object [1617](#)