
Education Cloud Developer Guide

Version 58.0, Summer '23



CONTENTS

Chapter 1: Introduction to Education Cloud	1
Chapter 2: Release Notes	2
Chapter 3: Education Cloud Data Model Overview	3
Chapter 4: Education Cloud Standard Objects	4
AcademicSession	5
AcademicTerm	9
AcademicTermEnrollment	13
AcademicYear	18
ApplicationDecision	20
ApplicationRecommendation	23
ApplicationRecommender	25
ApplicationReview	28
ApplicationTimeline	32
ConstituentRole	36
ContactProfile	39
CourseOfferingParticipant	45
CourseOfferingPtcpResult	49
CourseOfferingSchedule	53
CourseOfferingScheduleTpl	57
EducationalInfoRequest	61
IndividualApplication	64
LearnerProgram	68
LearnerProgramRequirement	71
LearnerProgramRqmtProgress	74
Learning	76
LearningAchievement	80
LearningCourse	84
LearningFoundationItem	88
LearningOutcomeltem	91
LearningProgram	93
LearningProgramPlan	95
LearningProgramPlanRqmt	98
LocationUse	101
PersonDisability	103
ProgramTermApplnTimeline	106
SuccessTeam	109
WorkTypeGroupRole	112

Contents

Chapter 5: Education Cloud Fields on Standard Objects	115
CourseOffering	116
Location	118
PersonEducation	119
PersonEmployment	122
PersonExamination	128
PreliminaryApplicationRef	134
ServiceTerritoryMember	136

CHAPTER 1 Introduction to Education Cloud

Use Education Cloud to support the entire learner experience, including managing applications, scheduling, courses, facilities, and more.

Education Cloud draws on the power of Salesforce to connect insights across recruitment, admissions, and student success for a unified view of every learner's journey. With Salesforce at the center of your institution's information technology solution, important tasks can be completed in less time, at scale, and in collaboration between departments. A single source of truth creates a complete student profile, so your institution can offer personalized experiences that translate into successful lifetime learners — from prospective student to engaged alum.

EDITIONS

Available in: Lightning Experience in **Performance, Enterprise, Developer,** and **Unlimited** editions that have Education Cloud enabled.

CHAPTER 2 Release Notes

View the latest features from Education Cloud.

[Education Cloud Release Notes](#)

CHAPTER 3 Education Cloud Data Model Overview

Learn about the objects and relationships within the Education Cloud data model.

View entity relationship diagrams from Education Cloud on the Salesforce Architects site to understand associations between the objects:

- [Education Cloud Data Model Overview](#)
- [Education Cloud Recruitment and Admissions Data Model](#)
- [Education Cloud Student Success Data Model](#)
- [Education Cloud Appointment Scheduling Data Model](#)

EDITIONS

Available in: Lightning Experience in **Performance, Enterprise, Developer,** and **Unlimited** editions that have Education Cloud enabled.

CHAPTER 4 Education Cloud Standard Objects

In this chapter ...

- [AcademicSession](#)
- [AcademicTerm](#)
- [AcademicTermEnrollment](#)
- [AcademicYear](#)
- [ApplicationDecision](#)
- [ApplicationRecommendation](#)
- [ApplicationRecommender](#)
- [ApplicationReview](#)
- [ApplicationTimeline](#)
- [ConstituentRole](#)
- [ContactProfile](#)
- [CourseOfferingParticipant](#)
- [CourseOfferingPtcpResult](#)
- [CourseOfferingSchedule](#)
- [CourseOfferingScheduleTpl](#)
- [EducationalInfoRequest](#)
- [IndividualApplication](#)
- [LearnerProgram](#)
- [LearnerProgramRequirement](#)
- [LearnerProgramRqmtProgress](#)
- [Learning](#)
- [LearningAchievement](#)
- [LearningCourse](#)
- [LearningFoundationItem](#)
- [LearningOutcomeItem](#)
- [LearningProgram](#)
- [LearningProgramPlan](#)
- [LearningProgramPlanRqmt](#)
- [LocationUse](#)
- [PersonDisability](#)
- [ProgramTermAppTimeline](#)
- [SuccessTeam](#)
- [WorkTypeGroupRole](#)

This section lists standard objects available for use with Education Cloud.

Some fields may not be listed for some objects. To verify the complete list of fields for an object, you can use a describe call from the API, or inspect with an appropriate tool, for example, inspecting the WSDL or using a schema viewer.

EDITIONS

Available in: Lightning Experience in **Performance, Enterprise, Developer,** and **Unlimited** editions that have Education Cloud enabled.

AcademicSession

Records course offering period. Specifies time periods based on an institution's calendar whether that is semesters, quarters, trimesters, or other terms. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicTermId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Academic Term associated with the Academic Session. This field is a relationship field.</p> <p>Relationship Name AcademicTerm</p> <p>Relationship Type Lookup</p> <p>Refers To AcademicTerm</p>
AddDropDeadline	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The last date when a student can add or drop a course, without a record of registration on their academic period.</p>
AuditDueDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The last date for a student to audit a course and take it without seeking a grade or credit.</p>

Field	Details
ClassEndDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when classes end for the Academic Session.</p>
ClassStartDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when classes start for the Academic Session.</p>
CourseWithdrawDeadline	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when withdraw from a course is recorded on the student's academic record.</p>
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The description of the Academic Session.</p>
ExamEndDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when exams for the Academic Session end.</p>
ExamStartDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when exams for the Academic Session start.</p>

Field	Details
IsActive	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the Academic Session is active (true) or not (false). The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>

Field	Details
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
ResultAvailabilityDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when the result of the course offering is announced.</p>
ResultDueDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The last date to submit the result of a course offering, such as grades.</p>
Season	<p>Type restricted picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the season related to the Academic Session.</p>

Field	Details
	<p>Possible values are:</p> <ul style="list-style-type: none"> • Fall • Spring • Summer • Winter
Type	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the type of Academic Session.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • First Semester • MiniTerm • Others • Quarter • Second Semester • Semester • Term 1 • Term 2 • Term 3 • Term 4 • Trimester

AcademicTerm

Defines an academic period which may hold other more defined time periods within it to create a specific time for reporting and offerings. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicYearId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The academic year that's associated with the Academic Term. This field is a relationship field.</p> <p>Relationship Name AcademicYear</p> <p>Relationship Type Lookup</p> <p>Refers To AcademicYear</p>
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The description of the Academic Term.</p>
EndDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when the Academic Term ends.</p>
IsActive	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the Academic Term is active (true) or not (false). The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p>

Field	Details
	<p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LateRegistrationDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date from when the applications are considered as late submissions.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p>

Field	Details
	<p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
RegistrationCloseDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The last date for the students to register for the Academic Term.</p>
RegistrationOpenDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date from when the students can begin to register for the Academic Term.</p>
Season	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the season related to the Academic Term. Possible values are:</p> <ul style="list-style-type: none"> • Fall

Field	Details
	<ul style="list-style-type: none"> • Spring • Summer • Winter
StartDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The date when the Academic Term starts.</p>

AcademicTermEnrollment

Represents information about a student's enrollment in an Academic Term. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicTermId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Academic Term associated with the Academic Term Enrollment. This field is a relationship field.</p> <p>Relationship Name AcademicTerm</p> <p>Relationship Type Lookup</p> <p>Refers To AcademicTerm</p>
EnrollmentDate	<p>Type date</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date that the student enrolled in the Academic Term.</p>
EnrollmentReason	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The reason the student enrolled in the Academic Term. Possible values are:</p> <ul style="list-style-type: none"> • Continuing • First Time • Re-admit • Transfer in
EnrollmentStatus	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the status of a student's enrollment in the Academic Term. Possible values are:</p> <ul style="list-style-type: none"> • Active • Dropout • Expelled • Graduated • No show • Other • Transferred • Withdrawn
ExitDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the student left the institution.</p>

Field	Details
ExitReason	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The reason that the student left the institution.</p>
HoursAttempted	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The number of credit hours or contact hours attempted by a student during the Academic Term.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearnerAccountId	<p>Type reference</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Account of the person associated with the Academic Term Enrollment. This field is a relationship field.</p> <p>Relationship Name LearnerAccount</p> <p>Relationship Type Lookup</p> <p>Refers To Account</p>
LearnerContactId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Contact person associated with the Academic Term Enrollment. This field is a relationship field.</p> <p>Relationship Name LearnerContact</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for this record.</p>

Field	Details
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
StudentAcademicLevel	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the student's applicable point in the education process. Possible values are:</p> <ul style="list-style-type: none"> • Adult Education • Doctoral • Elementary • Graduate • High School • Middle School • Post-Baccalaureate Certificate • Pre-K/Preschool • Professional Education • Undergraduate
StudyYearClassification	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the student's year of study classification. Possible values are:</p>

Field	Details
	<ul style="list-style-type: none"> • Freshman • Junior • Senior • Sophomore
TermGradePointAverage	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The student's cumulative grade point average for the Academic Term.</p>

AcademicYear

Defines an academic year period. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The description of the Academic Year.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>

Field	Details
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (LastReferencedDate) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p>

Field	Details
	<p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
Year	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the Academic Year.</p>

ApplicationDecision

Represents information about the academic standing of an applicant. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ApplicantDecision	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the applicant's decision. Possible values are:</p> <ul style="list-style-type: none"> • Accept • Decline • Defer • Withdraw
ApplicationDecision	<p>Type picklist</p>

Field	Details
	<p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the decision on the application.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Admit • Cancelled • Deny • Enroll • Waitlist
ApplicationId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The application for which the decision is announced. This field is a relationship field.</p> <p>Relationship Name Application</p> <p>Relationship Type Lookup</p> <p>Refers To IndividualApplication</p>
Comment	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The information about the decision provided on the application.</p>
DecisionAuthorityId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Identifier for the decision authority person.</p> <p>Relationship Name DecisionAuthority</p>

Field	Details
	<p>Relationship Type Lookup</p> <p>Refers To User</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p>

Field	Details
	<p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
PreliminaryApplicationRefId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Identifier for the preliminary application reference.</p> <p>Relationship Name PreliminaryApplicationRef</p> <p>Relationship Type Lookup</p> <p>Refers To PreliminaryApplicationRef</p>

ApplicationRecommendation

Represents information about the recommendation for an individual application. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ApplicationRecommenderId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The contact associated with the recommendation as the recommender. This field is a relationship field.</p> <p>Relationship Name ApplicationRecommender</p> <p>Relationship Type Lookup</p> <p>Refers To ApplicationRecommender</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>

Field	Details
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
Recommendation	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The content submitted as the recommendation.</p>

ApplicationRecommender

Represents a junction between an individual application and the recommender of the application. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ApplicationId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The individual application that's associated with the recommender. This field is a relationship field.</p> <p>Relationship Name Application</p> <p>Relationship Type Lookup</p> <p>Refers To IndividualApplication</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p>

Field	Details
	<p>Description</p> <p>The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type</p> <p>boolean</p> <p>Properties</p> <p>Defaulted on create, Filter, Group, Sort</p> <p>Description</p> <p>Indicates whether the record can be edited (true) or not (false).</p> <p>The default value is <code>false</code>.</p>
Name	<p>Type</p> <p>string</p> <p>Properties</p> <p>Create, Filter, Group, idLookup, Sort, Update</p> <p>Description</p> <p>The name for this record.</p>
RecommendationStatus	<p>Type</p> <p>picklist</p> <p>Properties</p> <p>Create, Filter, Restricted picklist, Group, Sort, Update</p> <p>Description</p> <p>Specifies the status of the recommendation.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Requested • Submitted
RecommenderId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Filter, Group, Sort, Update</p> <p>Description</p> <p>The contact associated with the application as a recommender.</p> <p>This field is a relationship field.</p> <p>Relationship Name</p> <p>Recommender</p> <p>Relationship Type</p> <p>Lookup</p>

Field	Details
	Refers To Contact
SubmittedDate	Type date Properties Create, Filter, Group, Nillable, Sort, Update Description Specifies the date on which the recommendation was submitted.

ApplicationReview

Represents a review performed against the specified application. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicTerm	Type string Properties Filter, Group, Nillable, Sort Description Specifies the academic term associated with the application.
ApplicationCategory	Type picklist Properties Filter, Group, Nillable, Sort Description Specifies the category of the application based on the admission decision period. Possible values are: <ul style="list-style-type: none"> • Early Decision • Regular Decision

Field	Details
ApplicationId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The application that is in review. This field is a relationship field.</p> <p>Relationship Name Application</p> <p>Relationship Type Lookup</p> <p>Refers To IndividualApplication</p>
ApplicationRecommendation	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the recommendation provided by the reviewer for the application into the institution. Possible values are:</p> <ul style="list-style-type: none"> • Admit • Admit with Conditions • Deny • Pending
AssignedDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the date on which the application is assigned for review.</p>
Comment	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The information added by the reviewer about the application that's in review.</p>

Field	Details
Condition	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The condition that's applicable to an applicant.</p>
DueDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The last date by which the application review should be completed.</p>
EndDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the application review was completed.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p>

Field	Details
	<p>Description</p> <p>The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type</p> <p>boolean</p> <p>Properties</p> <p>Defaulted on create, Filter, Group, Sort</p> <p>Description</p> <p>Indicates whether the record can be edited (true) or not (false).</p> <p>The default value is <code>false</code>.</p>
Name	<p>Type</p> <p>string</p> <p>Properties</p> <p>Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description</p> <p>The name for this record.</p>
OwnerId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description</p> <p>The user who owns this record.</p> <p>This field is a polymorphic relationship field.</p> <p>Relationship Name</p> <p>Owner</p> <p>Relationship Type</p> <p>Lookup</p> <p>Refers To</p> <p>Group, User</p>
ReviewedById	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Filter, Group, Nillable, Sort, Update</p> <p>Description</p> <p>Identifier of the reviewer of the application.</p>

Field	Details
	<p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To User</p>
StartDate	<p>Type dateTime</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the application review started.</p>
Status	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the status of the application review. Possible values are:</p> <ul style="list-style-type: none"> • Cancelled • Completed • In Progress • Not Started
SubmissionDate	<p>Type dateTime</p> <p>Properties Filter, Group, Nillable, Sort,</p> <p>Description The date when the applicant submitted the application.</p>

ApplicationTimeline

Represents the milestone dates in the application process. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ApplicationCloseDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The last date when domestic applicants can apply for admission.</p>
ApplicationOpenDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when applicants can start to apply for admission.</p>
DecisionReleaseDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the application decision is announced.</p>
EarlyActionCloseDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The last date when applicants can apply for early action admission.</p>
EarlyActionOpenDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when applicants can start to apply for early action admission.</p>

Field	Details
EarlyApplicationCloseDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The last date when applicants can apply early for admission.</p>
EarlyApplicationOpenDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when applicants can start to apply early for admission.</p>
EarlyApplnDecisionRelDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the application decision for early applicants is announced.</p>
GraduationApplnDeadline	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The last date for the students to apply for graduation.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p>

Field	Details
	<p>Description</p> <p>The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type</p> <p>dateTime</p> <p>Properties</p> <p>Filter, Nillable, Sort</p> <p>Description</p> <p>The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type</p> <p>boolean</p> <p>Properties</p> <p>Defaulted on create, Filter, Group, Sort</p> <p>Description</p> <p>Indicates whether the record can be edited (true) or not (false).</p> <p>The default value is <code>false</code>.</p>
Name	<p>Type</p> <p>string</p> <p>Properties</p> <p>Create, Filter, Group, idLookup, Sort, Update</p> <p>Description</p> <p>The name for this record.</p>
OwnerId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description</p> <p>The user who owns this record.</p> <p>This field is a polymorphic relationship field.</p> <p>Relationship Name</p> <p>Owner</p> <p>Relationship Type</p> <p>Lookup</p> <p>Refers To</p> <p>Group, User</p>

Field	Details
Type	<p>Type picklist</p> <p>Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update</p> <p>Description Specifies the type of application timeline. Possible values are:</p> <ul style="list-style-type: none"> • Admissions

ConstituentRole

Contains information about roles associated with the individual. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ContextRecordId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The record of the context that's associated with the constituent. This field is a relationship field.</p> <p>Relationship Name ContextRecord</p> <p>Relationship Type Lookup</p> <p>Refers To Learning</p>
Description	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p>

Field	Details
	<p>Description The short description of the constituent's role in the system.</p>
EffectiveEndDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date from when the constituent role becomes inactive.</p>
EffectiveStartDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date from when the constituent role becomes active.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>

Field	Details
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
PersonId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The individual associated with the constituent role. This field is a polymorphic relationship field.</p> <p>Relationship Name Person</p> <p>Relationship Type Lookup</p>

Field	Details
	<p>Refers To Account, Contact, Individual</p>
RoleType	<p>Type picklist</p> <p>Properties Create, Filter, Restricted picklist, Group, Sort, Update</p> <p>Description Specifies the type of constituent role. Possible values are:</p> <ul style="list-style-type: none"> • Alumni • Applicant • Donor • Faculty • Parent • Prospect • Staff • Student • Suspect
Status	<p>Type picklist</p> <p>Properties Create, Filter, Restricted picklist, Group, Sort, Update</p> <p>Description The status of the constituent role. Possible values are:</p> <ul style="list-style-type: none"> • Active • Admitted • Current • Enrolled • Former

ContactProfile

Represents information about an individual, such as their ethnicity, citizenship, birth place, race, and so on. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
BirthCountryId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The individual's country of birth. This field is a relationship field.</p> <p>Relationship Name BirthCountry</p> <p>Relationship Type Lookup</p> <p>Refers To GeoCountry</p>
BirthPlace	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The individual's place of birth.</p>
ContactId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The contact associated with the contact profile record. This field is a relationship field.</p> <p>Relationship Name Contact</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>

Field	Details
Ethnicity	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the ethnicity of the individual. Possible values are:</p> <ul style="list-style-type: none"> • Hispanic or Latino • Not Hispanic or Latino • Not Selected
HighestEducationLevel	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the highest educational qualification of the individual Possible values are:</p> <ul style="list-style-type: none"> • Graduate • High School • Masters • Other • PhD
IsFirstGenerationStudent	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the individual is the first generation to enroll in education beyond high school. The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>

Field	Details
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
MilitaryBranch	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the military branch if the individual has ever enlisted in the military. Possible values are:</p> <ul style="list-style-type: none"> • Air Force • Army • Coast Guard • Marine Corps • Navy • Other • Space Force

Field	Details
MilitaryService	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the current status of military service. Possible values are:</p> <ul style="list-style-type: none"> • Active Duty • Active Reserve • Full time • Other • Part time • Retired • Unknown • Veteran
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for this record.</p>
PrimaryCitizenshipId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The primary citizenship held by the individual. This field is a relationship field.</p> <p>Relationship Name PrimaryCitizenship</p> <p>Relationship Type Lookup</p> <p>Refers To GeoCountry</p>
PrimaryCitizenshipType	<p>Type picklist</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the type of primary citizenship held by the individual. Possible values are:</p> <ul style="list-style-type: none"> Asylum National Other Refugee
Race	<p>Type multipicklist</p> <p>Properties Create, Filter, Nillable, Update</p> <p>Description Specifies the race of the individual. Possible values are:</p> <ul style="list-style-type: none"> Alaska Native American Indian Asian Black or African American Native Hawaiian or Other Pacific Islander White
SecondaryCitizenshipId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The secondary citizenship of the individual if they hold dual citizenship. This field is a relationship field.</p> <p>Relationship Name SecondaryCitizenship</p> <p>Relationship Type Lookup</p> <p>Refers To GeoCountry</p>
SecondaryCitizenshipType	<p>Type picklist</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the type of secondary citizenship held by the individual.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> Asylum National Other Refugee

CourseOfferingParticipant

Represents information about a student's enrollment in a Course Offering. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicTermEnrollmentId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Academic Term associated with the Course Offering Participant. This field is a relationship field.</p> <p>Relationship Name AcademicTermEnrollment</p> <p>Relationship Type Lookup</p> <p>Refers To AcademicTermEnrollment</p>
CourseOfferingId	<p>Type reference</p>

Field	Details
	<p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Course Offering associated with the Course Offering Participant. This field is a relationship field.</p> <p>Relationship Name CourseOffering</p> <p>Relationship Type Lookup</p> <p>Refers To CourseOffering</p>
EndDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the participant's involvement in the course ended.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
IsRepeatAttempt	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the participant has previously taken the course (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p>

Field	Details
	<p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>

Field	Details
ParticipantAccountId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Account associated with the Course Offering Participant. This field is a relationship field.</p> <p>Relationship Name ParticipantAccount</p> <p>Relationship Type Lookup</p> <p>Refers To Account</p>
ParticipantAffiliation	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The participant's role in the course. Possible values are:</p> <ul style="list-style-type: none"> • Aide • Student • Teacher
ParticipantContactId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Contact record associated with the Course Offering Participant. This field is a relationship field.</p> <p>Relationship Name ParticipantContact</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>

Field	Details
ParticipationStatus	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the participation status of the participant in the course. Possible values are:</p> <ul style="list-style-type: none"> • Audit • Completed • Enrolled • Facilitating • Failed • On Hold • Transfer Credit • Waitlisted • Withdrew
StartDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the participant's involvement in the course began.</p>

CourseOfferingPtcpResult

Represents the outcome of a student's participation in a course. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
CourseOfferingParticipantId	<p>Type reference</p>

Field	Details
	<p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Course Offering Participant associated with the Course Offering Participant Result. This field is a relationship field.</p> <p>Relationship Name CourseOfferingParticipant</p> <p>Relationship Type Lookup</p> <p>Refers To CourseOfferingParticipant</p>
DurationUnit	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The unit of measurement for completion of the course. Possible values are:</p> <ul style="list-style-type: none"> • Clock Hours • Continuing Education Units • Credit Hours • No Credit • Other
EvaluatorContactId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Contact that assigns the result associated with the Course Offering Participant Result. This field is a relationship field.</p> <p>Relationship Name EvaluatorContact</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>

Field	Details
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LetterGrade	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The letter grade awarded to the participant for completing the course.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>

Field	Details
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description Course Offering Participant Result auto-generated name.</p>
NumericGrade	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The value that's assigned to a Letter Grade.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
ParticipantResultStatus	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update</p> <p>Description Specifies the type or status of the participant's result. For example, Pass or Fail. Possible values are:</p> <ul style="list-style-type: none"> • Fail • Incomplete • Pass • Withdraw

Field	Details
UnitsEarned	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Units of value awarded for completing the course.</p>

CourseOfferingSchedule

Represents information about the schedule defined for a Course Offering. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
CourseOfferingId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The Course Offering that's associated with the Course Offering Schedule. This field is a relationship field.</p> <p>Relationship Name CourseOffering</p> <p>Relationship Type Lookup</p> <p>Refers To CourseOffering</p>
CourseOfferingScheduleImplId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p>

Field	Details
	<p>Description The Course Offering Schedule Template associated with the Course Offering Schedule. If a Course Offering Schedule Template is specified, the <code>StartTime</code>, <code>EndTime</code> and <code>Days</code> from the Course Offering Schedule Template are used.</p> <p>This field is a relationship field.</p> <p>Relationship Name CourseOfferingScheduleTpl</p> <p>Relationship Type Lookup</p> <p>Refers To CourseOfferingScheduleTpl</p>
Description	<p>Type string</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The description of the Course Offering Schedule Template.</p>
EndTime	<p>Type time</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The time of day when the Course Offering meeting ends.</p>
IsFriday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Friday. The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>

Field	Details
IsMonday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Monday. The default value is <code>false</code>.</p>
IsSaturday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Saturday. The default value is <code>false</code>.</p>
IsSunday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Sunday. The default value is <code>false</code>.</p>
IsThursday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Thursday. The default value is <code>false</code>.</p>
IsTuesday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Tuesday. The default value is <code>false</code>.</p>

Field	Details
IsWednesday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Wednesday. The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LocationId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The education facility Location that's associated with the Course Offering Schedule. This field is a relationship field.</p> <p>Relationship Name Location</p> <p>Relationship Type Lookup</p> <p>Refers To Location</p>
MayEdit	<p>Type boolean</p>

Field	Details
	<p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for this record.</p>
StartTime	<p>Type time</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The time of day when the Course Offering meeting starts.</p>

CourseOfferingScheduleTpl

Represents a template that can be used to define a course schedule. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	<p>Type textarea</p> <p>Properties Create, Update</p> <p>Description The description of the Course Offering Schedule Template.</p>

Field	Details
EndTime	<p>Type time</p> <p>Properties Create, Filter, Sort, Update</p> <p>Description The time of day when the Course Offering meeting ends.</p>
IsFriday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Friday. The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
IsMonday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Monday. The default value is <code>false</code>.</p>
IsSaturday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Saturday. The default value is <code>false</code>.</p>
IsSunday	<p>Type boolean</p>

Field	Details
	<p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Sunday. The default value is <code>false</code>.</p>
IsThursday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Thursday. The default value is <code>false</code>.</p>
IsTuesday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Tuesday. The default value is <code>false</code>.</p>
IsWednesday	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates that the Course Offering occurs on Wednesday. The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p>

Field	Details
	<p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
StartTime	<p>Type time</p> <p>Properties Create, Filter, Sort, Update</p>

Field	Details
	<p>Description</p> <p>The time of day when the Course Offering meeting starts.</p>

EducationalInfoRequest

Represents details about a request for information (RFI) raised by prospective students, parents, or counselors. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicDurationId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Filter, Group, Nillable, Sort, Update</p> <p>Description</p> <p>The academic term or academic year that's associated with the Educational Information Request.</p> <p>This field is a polymorphic relationship field.</p> <p>Relationship Name</p> <p>AcademicDuration</p> <p>Relationship Type</p> <p>Lookup</p> <p>Refers To</p> <p>AcademicTerm, AcademicYear</p>
CaseId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Filter, Group, Sort</p> <p>Description</p> <p>The case that's associated with the request for information.</p> <p>This field is a relationship field.</p>

Field	Details
	<p>Relationship Name Case</p> <p>Relationship Type Lookup</p> <p>Refers To Case</p>
Category	<p>Type picklist</p> <p>Properties Create, Filter, Restricted picklist, Group, Sort, Update</p> <p>Description Specifies the category for which the Request for Information is raised. Possible values are:</p> <ul style="list-style-type: none"> • Academic • Admission • Financial Aid
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p>

Field	Details
	<p>Description</p> <p>The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearningId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Filter, Group, Nillable, Sort, Update</p> <p>Description</p> <p>The learning that's associated with the request for information.</p> <p>This field is a relationship field.</p> <p>Relationship Name</p> <p>Learning</p> <p>Relationship Type</p> <p>Lookup</p> <p>Refers To</p> <p>Learning</p>
MayEdit	<p>Type</p> <p>boolean</p> <p>Properties</p> <p>Defaulted on create, Filter, Group, Sort</p> <p>Description</p> <p>Indicates whether the record can be edited (true) or not (false).</p> <p>The default value is <code>false</code>.</p>
Name	<p>Type</p> <p>string</p> <p>Properties</p> <p>Create, Filter, Group, idLookup, Sort, Update</p> <p>Description</p> <p>The name for this record.</p>
RequesterId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Filter, Group, Nillable, Sort, Update</p> <p>Description</p> <p>The account of the person associated with the request for information.</p> <p>This field is a relationship field.</p>

Field	Details
	<p>Relationship Name Requester</p> <p>Relationship Type Lookup</p> <p>Refers To Account</p>
SubCategory	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the sub-category for which the Request for Information is raised.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Application Process • Housing • Program Info • Scholarship • Tuition Fee

IndividualApplication

Represents information about the preferences of an applicant during program enrollment. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicTerm	<p>Type string</p> <p>Properties Filter, Group, Nillable, Sort</p> <p>Description The academic term associated with the application</p>

Field	Details
ApplicantEmail	<p>Type email</p> <p>Properties Filter, Group, Nillable, Sort</p> <p>Description The email address of the applicant.</p>
ApplicantPhone	<p>Type phone</p> <p>Properties Filter, Group, Nillable, Sort</p> <p>Description The phone number of the applicant.</p>
ApplicationCategory	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Categorizes the ways an application can be processed. Possible values are:</p> <ul style="list-style-type: none"> • Early Decision • Regular Decision
ApplicationType	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The type of the application. Possible values are:</p> <ul style="list-style-type: none"> • Graduate • International • Transfer • Undergraduate
Category	<p>Type picklist</p> <p>Properties Create, Filter, Group, Sort, Update</p>

Field	Details
	<p>Description The service category of the application.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Education
ContactId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The contact person associated with the application. This field is a relationship field.</p> <p>Relationship Name Contact</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>
DecisionReleaseDate	<p>Type date</p> <p>Properties Filter, Group, Nillable, Sort</p> <p>Description The date when the application decision is announced.</p>
DueDate	<p>Type date</p> <p>Properties Filter, Group, Nillable, Sort</p> <p>Description The last date when applicants can apply for admission.</p>
LearningProgram	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The Learning Program associated with the Individual Application. This field is a relationship field.</p>

Field	Details
	<p>Relationship Name LearningProgram</p> <p>Relationship Type Lookup</p> <p>Refers To LearningProgram</p>
ProgramTermApplnTimelineId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The application timeline of the program term associated with the application. This field is a relationship field.</p> <p>Relationship Name ProgramTermApplnTimeline</p> <p>Relationship Type Lookup</p> <p>Refers To ProgramTermApplnTimeline</p>
Status	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description he submission and approval status of the application. Possible values are:</p> <ul style="list-style-type: none"> • Application Decision • Canceled • In Review • Processing • Ready For Decision • Denied

For more information, see [IndividualApplication in Public Sector Solutions](#).

LearnerProgram

Represents details of a Learning Program Plan that's created for a learner. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description Description of the Learner Program.</p>
EndDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date that the learner exited the program.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>

Field	Details
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearnerAccountId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Account associated with the learner that the Learning Program Plan is assigned to. This field is a relationship field.</p> <p>Relationship Name LearnerAccount</p> <p>Relationship Type Lookup</p> <p>Refers To Account</p>
LearnerContactId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Contact record for the learner that the Learning Program Plan is assigned to. This field is a relationship field.</p> <p>Relationship Name LearnerContact</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>
LearningProgramPlanId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p>

Field	Details
	<p>Description Learning Program Plan that's associated with the Learner Program. This field is a relationship field.</p> <p>Relationship Name LearningProgramPlan</p> <p>Relationship Type Lookup</p> <p>Refers To LearningProgramPlan</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description Name of a Learning Program Plan for an individual learner.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
StartDate	<p>Type date</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date that the learner began the program.</p>
Status	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Status of the learner's participation in the program. Possible values are:</p> <ul style="list-style-type: none"> • Abandoned • Active • Completed • Not Started • Paused

LearnerProgramRequirement

Represents details of the requirement that a learner is required to complete in their assigned Learning Program Plan. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description Description of a Learner Program Requirement.</p>

Field	Details
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearnerProgramId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description Learning Program Plan assigned to a learner. This field is a relationship field.</p> <p>Relationship Name LearnerProgram</p> <p>Relationship Type Lookup</p> <p>Refers To LearnerProgram</p>
LearningProgramPlanRqmtId	<p>Type reference</p>

Field	Details
	<p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Learning Program Plan associated with the Learner Program Requirement. This field is a relationship field.</p> <p>Relationship Name LearningProgramPlanRqmt</p> <p>Relationship Type Lookup</p> <p>Refers To LearningProgramPlanRqmt</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description Name of the Learning Program Requirement that's assigned to an individual.</p>
Status	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Status of the learner's progress towards meeting the requirement. Possible values are:</p> <ul style="list-style-type: none"> • Active • Completed • Exempt

LearnerProgramRqmtProgress

Represents information about the progress of a requirement that a learner is required to complete as a part of the assigned program plan. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description The description of the Learning Program Requirement Progress.</p>
Duration	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The allocated length of time for completion of the Requirement.</p>
DurationUnit	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The unit of measurement for length of time for the completion of the Requirement. Example values include Credit Hour, Contact Hour, Hours, Weeks, Quarters, Semesters, and Years. Possible values are:</p> <ul style="list-style-type: none"> • Clock Hours • Continuing Education Units • Credit Hours • No Credit • Other

Field	Details
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearnerProgramRequirementId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The Learner Program Requirement associated with this Learner Program Requirement Progress. This field is a relationship field.</p> <p>Relationship Name LearnerProgramRequirement</p> <p>Relationship Type Lookup</p> <p>Refers To LearnerProgramRequirement</p>

Field	Details
LearningOutcomeItemId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Learning Outcome Item used to fulfill the requirement. This field is a relationship field.</p> <p>Relationship Name LearningOutcomeItem</p> <p>Relationship Type Lookup</p> <p>Refers To LearningOutcomeItem</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name of the Learning Program Requirement Progress that tracks the completion of a requirement.</p>

Learning

Represents information that defines a training that can be made available as a course, program, or on-site experience, for a contact. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicLevel	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The applicable point in the education process. Possible values are:</p> <ul style="list-style-type: none"> • Adult Education • Doctoral • Elementary • Graduate • High School • Middle School • Post-Baccalaureate Certificate • Pre-K/Preschool • Professional Education • Undergraduate
ActiveFromDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Date the Learning framework became active.</p>
ActiveToDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Date the Learning framework became inactive.</p>
CipCode	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Classification of Instructional Programming code that identifies the program or field of study.</p>

Field	Details
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description Description of the Learning framework.</p>
Duration	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The allocated length of time for completion of the Learning.</p>
DurationUnit	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The unit of measurement for the length of time for completion. Possible values are:</p> <ul style="list-style-type: none"> • Clock Hours • Continuing Education Units • Credit Hours • No Credit • Other
IsActive	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Specifies that the Learning framework is active. The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p>

Field	Details
	<p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description Name of the Learning framework.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p>

Field	Details
	<p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
ProviderId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Account of the institution that provides the Learning. This field is a relationship field.</p> <p>Relationship Name Provider</p> <p>Relationship Type Lookup</p> <p>Refers To Account</p>
Type	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update</p> <p>Description Specifies the type of Learning. Possible values are:</p> <ul style="list-style-type: none"> • LearningCourse • LearningProgram

LearningAchievement

Represents information about the outcome of a learning activity. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Abbreviation	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Short name for a Learning Achievement.</p>
AcademicLevel	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The applicable point in the education process. Possible values are:</p> <ul style="list-style-type: none"> • Adult Education • Doctoral • Elementary • Graduate • High School • Middle School • Post-Baccalaureate Certificate • Pre-K/Preschool • Professional Education • Undergraduate
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description Description of a Learning Achievement.</p>

Field	Details
FieldOfStudy	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The academic subject related to the course of study. Possible values are:</p> <ul style="list-style-type: none"> • Career and Technical Education • Composite • Critical Reading • English • English Language Arts • Fine and Performing Arts • Foreign Language and Literature • Life and Physical Sciences • Mathematics • Military Science • Other • Physical, Health, and Safety Education • Reading • Religious Education and Theology • Science • Social Sciences and History • Social Studies • Writing
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
IssuerId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p>

Field	Details
	<p>Description The institution that grants the credential. This field is a relationship field.</p> <p>Relationship Name Issuer</p> <p>Relationship Type Lookup</p> <p>Refers To Account</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p>

Field	Details
	<p>Description</p> <p>Name of a Learning Achievement that represents a modeled qualification, achievement, or other program outcome. Used to provide a meaningful mapping between Learnings and the result of their successful completion.</p>
OwnerId	<p>Type</p> <p>reference</p> <p>Properties</p> <p>Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description</p> <p>The user who owns this record.</p> <p>This field is a polymorphic relationship field.</p> <p>Relationship Name</p> <p>Owner</p> <p>Relationship Type</p> <p>Lookup</p> <p>Refers To</p> <p>Group, User</p>
Specialization	<p>Type</p> <p>string</p> <p>Properties</p> <p>Create, Filter, Group, Nillable, Sort, Update</p> <p>Description</p> <p>Narrows the category, subject, area of study, discipline, or general branch of knowledge that the achievement was awarded for.</p>

LearningCourse

Represents information about a course that's required in a learning framework. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
CourseLevelDescription	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The general type or level of instruction provided throughout the course. Possible values are:</p> <ul style="list-style-type: none"> • Accepted as high school equivalent • Advanced • Advanced Placement • Basic • Career and Technical Education • College-level • Core Subject • Dual Credit • English Language Learner • General • Gifted and Talented • Graduation Credit • Honors • International Baccalaureate • Other • Remedial • Students with disabilities • Untracked
CourseNumber	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The number that identifies the level of the course and helps organize the course catalog.</p>
FieldOfStudy	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p>

Field	Details
	<p>Description</p> <p>The academic subject related to the course of study.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Career and Technical Education • Composite • Critical Reading • English • English Language Arts • Fine and Performing Arts • Foreign Language and Literature • Life and Physical Sciences • Mathematics • Military Science • Other • Physical, Health, and Safety Education • Reading • Religious Education and Theology • Science • Social Sciences and History • Social Studies • Writing
IsLocked	<p>Type</p> <p>boolean</p> <p>Properties</p> <p>Defaulted on create, Filter, Group, Sort, Update</p> <p>Description</p> <p>Indicates whether the record is locked (true) or not (false).</p> <p>The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type</p> <p>dateTime</p> <p>Properties</p> <p>Filter, Nillable, Sort</p> <p>Description</p> <p>The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>

Field	Details
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearningId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description Learning (unique parent field) associated with a Learning Course. This field is a relationship field.</p> <p>Relationship Name Learning</p> <p>Relationship Type Lookup</p> <p>Refers To Learning</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description Name of a course of study that represents a single unit of teaching that typically lasts one term.</p>
SubjectAbbreviation	<p>Type string</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Abbreviation of the Academic Subject for the course of study. For example, MAT = Mathematics.</p>

LearningFoundationItem

Represents information about the prerequisite, co-requisite, or the recommended learning that's required for a learning outcome. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Duration	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The allocated length of time for completion of the Learning.</p>
DurationUnit	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The unit of measurement for length of time for completion of the Learning. Possible values are:</p> <ul style="list-style-type: none"> • Clock Hours • Continuing Education Units • Credit Hours • No Credit • Other

Field	Details
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearningAchievementId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description A modeled qualification, achievement, or other program outcome used for the Learning Foundation. This field is a relationship field.</p> <p>Relationship Name LearningAchievement</p> <p>Relationship Type Lookup</p> <p>Refers To LearningAchievement</p>

Field	Details
LearningId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description Prerequisite, co-requisite or recommended Learning to attain a Learning Achievement. This field is a relationship field.</p> <p>Relationship Name Learning</p> <p>Relationship Type Lookup</p> <p>Refers To Learning</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description Name of the mapping between the Learning and the Learning Achievement requirements.</p>
Type	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Type of Learning Foundation Item. Possible values are:</p> <ul style="list-style-type: none"> • Co-requisite • Prerequisite • Recommended

LearningOutcomeItem

Represents information about the mapping between the learnings and the related outcome. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Duration	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The allocated length of time for completion of the Learning.</p>
DurationUnit	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The unit of measurement for length of time for the completion of the Learning. Possible values are:</p> <ul style="list-style-type: none"> • Clock Hours • Continuing Education Units • Credit Hours • No Credit • Other
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>

Field	Details
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (LastReferencedDate) but not viewed it.</p>
LearningAchievementId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The Learning Achievement that's granted upon the completion of the Learning. This field is a relationship field.</p> <p>Relationship Name LearningAchievement</p> <p>Relationship Type Lookup</p> <p>Refers To LearningAchievement</p>
LearningId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The Learning framework that's related to the Learning Outcome Item. This field is a relationship field.</p> <p>Relationship Name Learning</p>

Field	Details
	<p>Relationship Type Lookup</p> <p>Refers To Learning</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description Name of the mapping between the Learning and the Learning Achievements that it provides.</p>

LearningProgram

Represents information about one or more trainings in a program that's required to obtain a credential. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false).</p>

Field	Details
	The default value is <code>false</code> .
<code>LastReferencedDate</code>	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
<code>LastViewedDate</code>	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
<code>LearningId</code>	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description Learning (unique parent field) associated with a Learning Program. This field is a relationship field.</p> <p>Relationship Name Learning</p> <p>Relationship Type Lookup</p> <p>Refers To Learning</p>
<code>MayEdit</code>	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>

Field	Details
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description Name of the Learning Program that leads to a Learning Achievement.</p>

LearningProgramPlan

Represents details of a plan that's created to execute a Learning Program. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ActiveFromDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date the Learning Program Plan became active.</p>
ActiveToDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date after which the Learning Program Plan is inactive.</p>
Description	<p>Type textarea</p> <p>Properties Create, Nillable, Update</p> <p>Description Description of the Learning Program Plan.</p>

Field	Details
IsActive	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Specifies whether the Learning Program Plan is active or not. The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearningProgramId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The Learning Program associated with the Learning Program Plan. This field is a relationship field.</p>

Field	Details
	<p>Relationship Name LearningProgram</p> <p>Relationship Type Lookup</p> <p>Refers To LearningProgram</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
MinimumProgramGradePointAvg	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The minimum cumulative GPA that's required to complete the program.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name of the Learning Program Plan.</p>
ProviderId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Account of the institution that provides the Learning Program Plan. This field is a relationship field.</p> <p>Relationship Name Provider</p> <p>Relationship Type Lookup</p>

Field	Details
	Refers To Account
VersionNumber	Type double Properties Create, Filter, Nillable, Sort, Update Description Specifies the version of the Learning Program Plan.

LearningProgramPlanRqmt

Represents information about the requirements of a learning outcome that's included in the learning program plan. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
Description	Type textarea Properties Create, Nillable, Update Description The description of the Learning Program Plan Requirement.
Duration	Type double Properties Create, Filter, Nillable, Sort, Update Description The allocated length of time for completion of the requirement.
DurationUnit	Type picklist

Field	Details
	<p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description The unit of measurement for length of time for completion of the requirement. Example values include Credit Hours, Clock Hours, No Credit, Continuing Education Units, Other.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Clock Hours • Continuing Education Units • Credit Hours • No Credit • Other
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearningAchievementId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p>

Field	Details
	<p>Description The Learning Achievement associated with the Learning Program Plan Requirement. This field is a relationship field.</p> <p>Relationship Name LearningAchievement</p> <p>Relationship Type Lookup</p> <p>Refers To LearningAchievement</p>
LearningProgramPlanId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort</p> <p>Description The Learning Program Plan associated with the Learning Program Plan Requirement. This field is a relationship field.</p> <p>Relationship Name LearningProgramPlan</p> <p>Relationship Type Lookup</p> <p>Refers To LearningProgramPlan</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name of the requirement for a Learning Program Plan.</p>
SequenceNumber	<p>Type int</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The order that the course or other requirement should be taken within a Learning Program Plan.</p>

LocationUse

Records the general purpose of the Location. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

Fields

Field	Details
DeveloperName	<p>Type string</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description Name of the developer of the location.</p>
IsBookable	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates if the location is bookable. The default value is <code>false</code>.</p>
Language	<p>Type picklist</p> <p>Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update</p> <p>Description Specifies the language in use at the location. Possible values are:</p>

Field	Details
	<ul style="list-style-type: none"> • da - Danish • de - German • en_US - English • es - Spanish • es_MX - Spanish (Mexico) • fi - Finnish • fr - French • it - Italian • ja - Japanese • ko - Korean • nl_NL - Dutch • no - Norwegian • pt_BR - Portuguese (Brazil) • ru - Russian • sv - Swedish • th - Thai • zh_CN - Chinese (Simplified) • zh_CN - Chinese (Traditional)
LocationType	<p>Type picklist</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description Specifies the type of the location. Possible values are:</p> <ul style="list-style-type: none"> • Building • Campus • Other • Room
MasterLabel	<p>Type string</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The label that identifies this record throughout the user interface.</p>

Field	Details
Use	<p>Type string</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Specifies what the location is used for.</p>

PersonDisability

Represents information about a person's disability. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
IndividualId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The individual associated with the disability. This field is a polymorphic relationship field.</p> <p>Relationship Name Individual</p> <p>Relationship Type Lookup</p> <p>Refers To Account, Contact, Individual</p>
IsAccommodationRequired	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the individual requires accommodation.</p>

Field	Details
	The default value is <code>false</code> .
<code>IsLocked</code>	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
<code>LastReferencedDate</code>	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
<code>LastViewedDate</code>	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
<code>MayEdit</code>	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
<code>Name</code>	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>

Field	Details
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
Rank	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the level of disability.</p>
Status	<p>Type picklist</p> <p>Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update</p> <p>Description Specifies the status of the disability. Possible values are:</p> <ul style="list-style-type: none"> • Permanent • Temporary <p>The default value is <code>Temporary</code>.</p>
Type	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the type of disability. Possible values are:</p> <ul style="list-style-type: none"> • Blindness

Field	Details
	<ul style="list-style-type: none"> • Cognitive • Hearing impairment
VerificationDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the disability was verified.</p>
VerifiedBy	<p>Type picklist</p> <p>Properties Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update</p> <p>Description Specifies the verifier of the disability in the individual. Possible values are:</p> <ul style="list-style-type: none"> • HealthcareProvider • Other • Physician • Psychologist • SelfReported • SocialWorker • Teacher • Therapist <p>The default value is <code>Physician</code>.</p>
VerifiedByOther	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the verifier of the disability if its other than what is listed in <code>VerifiedBy</code>.</p>

ProgramTermApplnTimeline

Represents a junction between Academic Term, Application Timeline, and Learning Program objects. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AcademicTermId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The associated Academic Term for which the program is being offered. This field is a relationship field.</p> <p>Relationship Name AcademicTerm</p> <p>Relationship Type Lookup</p> <p>Refers To AcademicTerm</p>
ApplicationTimelineId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The associated Application Timeline that determines when admissions to the program for this term are open. This field is a relationship field.</p> <p>Relationship Name ApplicationTimeline</p> <p>Relationship Type Lookup</p> <p>Refers To ApplicationTimeline</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p>

Field	Details
	<p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
LearningProgramId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The associated Learning Program which is accepting students for admission. This field is a relationship field.</p> <p>Relationship Name LearningProgram</p> <p>Relationship Type Lookup</p> <p>Refers To LearningProgram</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false).</p>

Field	Details
	The default value is <code>false</code> .
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>

SuccessTeam

Records details about a success team in Salesforce Scheduler. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AccountId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p>

Field	Details
	<p>Description The account associated with the success team. This field is a relationship field.</p> <p>Relationship Name Account</p> <p>Relationship Type Lookup</p> <p>Refers To Account</p>
CanSelfSchedule	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Specifies whether the success team can be self scheduled (true) or not (false). The default value is <code>false</code>.</p>
CaseRecordTypeId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The case record type associated with the success team. This field is a relationship field.</p> <p>Relationship Name CaseRecordType</p> <p>Relationship Type Lookup</p> <p>Refers To RecordType</p>
DefaultUnassignedCaseTeam	<p>Type string</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The default case team that is unassigned.</p>
IsActive	<p>Type boolean</p>

Field	Details
	<p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Specifies whether the success team is active (true) or not (false). The default value is <code>false</code>.</p>
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p>

Field	Details
	<p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name of the success team.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>

WorkTypeGroupRole

Represents a grouping of work types by roles, used to categorize types of appointments available in Salesforce Scheduler. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
CaseTeamRole	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The role of the case team.</p>

Field	Details
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for the work type group role.</p>

Field	Details
WorkTypeGroupId	<p data-bbox="519 262 584 294">Type</p> <p data-bbox="568 304 665 336">reference</p> <p data-bbox="519 346 649 378">Properties</p> <p data-bbox="568 388 893 420">Create, Filter, Group, Sort, Update</p> <p data-bbox="519 430 665 462">Description</p> <p data-bbox="568 472 1185 504">The work type group associated with this work type group role.</p> <p data-bbox="568 514 860 546">This field is a relationship field.</p> <p data-bbox="519 556 730 588">Relationship Name</p> <p data-bbox="568 598 730 630">WorkTypeGroup</p> <p data-bbox="519 640 730 672">Relationship Type</p> <p data-bbox="568 682 649 714">Lookup</p> <p data-bbox="519 724 633 756">Refers To</p> <p data-bbox="568 766 730 798">WorkTypeGroup</p>

CHAPTER 5 Education Cloud Fields on Standard Objects

In this chapter ...

- [CourseOffering](#)
- [Location](#)
- [PersonEducation](#)
- [PersonEmployment](#)
- [PersonExamination](#)
- [PreliminaryApplicationRef](#)
- [ServiceTerritoryMember](#)

This section lists Education Cloud fields available with standard Salesforce objects. These fields are available only in orgs where Education Cloud is enabled.

EDITIONS

Available in: Lightning Experience in **Performance, Enterprise, Developer,** and **Unlimited** editions that have Education Cloud enabled.

CourseOffering

Represents an instance of a training course with location and date details of training courses. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
<code>AcademicSessionId</code>	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Academic Session associated with the Course Offering. This field is a relationship field.</p> <p>Relationship Name AcademicSession</p> <p>Relationship Type Lookup</p> <p>Refers To AcademicSession</p>
<code>EnrolleeCount</code>	<p>Type int</p> <p>Properties Filter, Group, Nillable, Sort</p> <p>Description The current number of enrollees in the Course Offering.</p>
<code>EnrollmentCapacity</code>	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The maximum number of students that are allowed to enroll for the Course Offering.</p>

Field	Details
LearningCourseId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Learning Course record associated with the Course Offering. This field is a relationship field.</p> <p>Relationship Name LearningCourse</p> <p>Relationship Type Lookup</p> <p>Refers To LearningCourse</p>
PrimaryFacultyId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The Contact associated with the Course Offering as lead instructor. This field is a relationship field.</p> <p>Relationship Name PrimaryFaculty</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>
SectionNumber	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Differentiates a Course Offering from other sections in an academic term.</p>
WaitlistCapacity	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The maximum number of students that can be waitlisted for the Course Offering.</p>

Field	Details
WaitlistCount	<p>Type int</p> <p>Properties Filter, Group, Nillable, Sort</p> <p>Description The current number of people on the waitlist for the Course Offering.</p>

For more information, see [CourseOffering in Public Sector Solutions](#).

Location

Represents details about a facility, building, room, or region. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
MaximumOccupancy	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The maximum occupancy of the location.</p>
OwnershipStatus	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the status of ownership of the facility. Possible values are:</p> <ul style="list-style-type: none"> • Leased • Other • Owned • Rented

For more information, see [Location in Salesforce Platform Objects](#).

PersonEducation

Represents information about the academic standing of an applicant. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ClassRank	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The measure of the applicant's academic performance compared to the other students in their class. This rank is based on the class rank reporting format that's followed by the institute, such as a number or percentage.</p>
ClassRankReportingFormat	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the class rank reporting format followed by the institution to report the applicant's performance.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Decile • Exact • None • Quartile • Quintile
ClassRankWeightingType	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p>

Field	Details
	<p>Description Specifies the GPA weighting type that's used to calculate the applicant's class rank.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Unweighted • Weighted
Comment	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Comments on the applicant's education details.</p>
CumulativeGpa	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The grade point average of all the grades earned by an applicant in all the semesters or terms.</p>
EducationLevel	<p>Type picklist</p> <p>Properties Create, Defaulted on create, Filter, Group, Nillable, Sort, Update</p> <p>Description Level of education achieved.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Graduate • High School • No Formal Education • Post Graduate <p>The default value is Fellowship.</p>
EndDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The end date of the individual's education.</p>

Field	Details
GpaScale	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The scale used when calculating the applicant's grade point average.</p>
GpaWeightingType	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the type of weightage given to the applicant's grades when calculating their grade point average. Possible values are:</p> <ul style="list-style-type: none"> • Unweighted • Weighted
GraduationClassSize	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The number of students who graduated from the same school, in the same academic year, as the applicant.</p>
InstitutionAccountId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The institution associated with the applicant's education. This field is a relationship field.</p> <p>Relationship Name Individual</p> <p>Relationship Type Lookup</p> <p>Refers To Individual</p>

Field	Details
IsActive	<p>Type boolean</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is active. The default value is <code>false</code>.</p>

For more information, see [PersonEducation in Public Sector Solutions](#).

PersonEmployment

Represents information about a person's employment. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
AnnualIncome	<p>Type currency</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description The annual income of the person.</p>
EmployerAddress	<p>Type address</p> <p>Properties Filter, Nillable</p> <p>Description The complete address of the employer.</p>
EmployerCity	<p>Type string</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The city where the employer is located.</p>
EmployerCountry	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The country where the employer is located.</p>
EmployerGeocodeAccuracy	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Restricted picklist, Sort, Update</p> <p>Description The level of accuracy of a location's geographical coordinates compared with its physical address. A geocoding service typically provides this value based on the address's latitude and longitude coordinates.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Address • Block • City • County • ExtendedZip • NearAddress • Neighborhood • State • Street • Unknown • Zip
EmployerLatitude	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Used with Longitude to specify the precise geolocation of the address. Acceptable values are numbers between -90 and 90 with up to 15 decimal places.</p>

Field	Details
EmployerLongitude	<p>Type double</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Used with Latitude to specify the precise geolocation of the address. Acceptable values are numbers between -180 and 180 with up to 15 decimal places.</p>
EmployerPhone	<p>Type phone</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Employer's phone number.</p>
EmployerPostalCode	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The postal code of the employer's address.</p>
EmployerState	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The state of the employer's address.</p>
EmployerStreet	<p>Type textarea</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The street address of the employer.</p>
EmploymentStatus	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p>

Field	Details
	<p>Description</p> <p>Specifies the employment status with the employer.</p> <p>Possible values are:</p> <ul style="list-style-type: none"> • Employed • Retired • Self-Employed • Unemployed
EndDate	<p>Type</p> <p>date</p> <p>Properties</p> <p>Create, Filter, Group, Nillable, Sort, Update</p> <p>Description</p> <p>The last date of employment at this job.</p>
IsLocked	<p>Type</p> <p>boolean</p> <p>Properties</p> <p>Defaulted on create, Filter, Group, Sort, Update</p> <p>Description</p> <p>Indicates whether the record is locked (true) or not (false).</p> <p>The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type</p> <p>dateTime</p> <p>Properties</p> <p>Filter, Nillable, Sort</p> <p>Description</p> <p>The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type</p> <p>dateTime</p> <p>Properties</p> <p>Filter, Nillable, Sort</p> <p>Description</p> <p>The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>

Field	Details
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Create, Filter, Group, idLookup, Sort, Update</p> <p>Description The name for this record.</p>
Occupation	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the person's occupation. Possible values are:</p> <ul style="list-style-type: none"> • Actor or Entertainer • Architect or Urban Planner • Artist • Business (Clerical) • Business Executive (Management, Administrator) • Business Owner or Proprietor • Business Salesperson or Buyer • Clergy (Minister, Priest) • Clergy (Other Religious) • Clinical Psychologist • College Administrator or Staff • College Teacher • Computer Programmer or Analyst • Conservationist or Forester • Dentist (Including Orthodontist) • Dietitian or Nutritionist • Engineer

Field	Details
	<ul style="list-style-type: none"> • Farmer or Rancher • Foreign Service Worker (Including Diplomat) • Homemaker (Full-Time) • Interior Decorator (Including Designer) • Lab Technician or Hygienist • Laborer • Law Enforcement Officer • Lawyer (Attorney) or Judge • Military Service (Career) • Musician (Performer, Composer) • Nurse • Optometrist • Other • Pharmacist • Physician • Policymaker or Government • School Counselor • School Principal or Superintendent • Scientific Researcher • Skilled Trades • Social, Welfare, or Recreation Worker • Teacher or Administrator (Elementary) • Teacher or Administrator (Secondary) • Therapist (Physical, Occupational, Speech) • Veterinarian • Writer or Journalist
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description The user who owns this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p>

Field	Details
	<p>Refers To Group, User</p>
Position	<p>Type string</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The last position of the person at this job.</p>
RelatedPersonId	<p>Type reference</p> <p>Properties Create, Filter, Group, Sort, Update</p> <p>Description The person associated with the employment. This field is a polymorphic relationship field.</p> <p>Relationship Name RelatedPerson</p> <p>Relationship Type Lookup</p> <p>Refers To Account, Contact</p>
StartDate	<p>Type date</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The start date of employment at this job.</p>

PersonExamination

Represents the examinations taken by a person. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ContactId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description ID of the contact related to this record. This field is a relationship field.</p> <p>Relationship Name Contact</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>
EffectiveFrom	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Date from which the examination is effective from.</p>
EffectiveTo	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Date till which the examination is effective.</p>
ExaminationDate	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Date the examination was taken.</p>
ExaminationId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p>

Field	Details
	<p>Description ID of the examination. This field is a relationship field.</p> <p>Relationship Name Examination</p> <p>Relationship Type Lookup</p> <p>Refers To Examination</p>
InstitutionName	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Name of the institution offering the examination. Possible values are:</p> <ul style="list-style-type: none"> • Abitur • Apolytirion • Baccalauréat (BAC) • Cambridge Internation Education Pre-University (CIE Pre-U) • Caribbean Advanced Proficiency Exam II (CAPE) • Center Shiken or Kyotsu Tests • Chinese National Entrance Examination (Gao Kao) or Joint Entrance Examination (JEE) • College Scholastic Ability Test (CSAT) • Concurso Nacional de Acesso ao Ensino Superior (CNA) • Emerites Standardized Test (EmSAT) • Ethiopian School Leaving Certificate Exams (ESLCE) or Ethiopian Higher Education Entrance • European Baccalaureate • GCE-Advanced Level Examinations (GCE-A Levels) • Higher / Level 6 • Higher Secondary Certificate (HSC) • Higher Secondary Education Board Examination (HSEBE) or School Leaving Certificate (SLC) • Higher Secondary School Certificate (HSSC) • Indian Certificate of Secondary Education - Class X (ICSE)

Field	Details
	<ul style="list-style-type: none"> • Indian School Certificate - Class XII (ISC) • Irish Leaving Certificate • Kenya Certificate of Secondary Education (KCSE) • Matriculation and Secondary Education Certificate (MATSEC) • Matura (Maturita) • Other • Prueba de Selección Universitaria (PSU) • Sijil Tinggi Persekolahan Malaysia (STPM) • Te'udat Bagrut • Tertiary Entrance Rank (TER) or Universities Admission Index (UAI) • Thanaweya Amma • Western African Senior School Certificate Examination (WASSCE)
IsLocked	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort, Update</p> <p>Description Indicates whether the record is locked (true) or not (false). The default value is <code>false</code>.</p>
LastReferencedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last accessed this record, a record related to this record, or a list view.</p>
LastViewedDate	<p>Type dateTime</p> <p>Properties Filter, Nillable, Sort</p> <p>Description The timestamp when the current user last viewed this record or list view. If this value is null, the user might have only accessed this record or list view (<code>LastReferencedDate</code>) but not viewed it.</p>

Field	Details
MayEdit	<p>Type boolean</p> <p>Properties Defaulted on create, Filter, Group, Sort</p> <p>Description Indicates whether the record can be edited (true) or not (false). The default value is <code>false</code>.</p>
Name	<p>Type string</p> <p>Properties Autonumber, Defaulted on create, Filter, idLookup, Sort</p> <p>Description The name for this record.</p>
OwnerId	<p>Type reference</p> <p>Properties Create, Defaulted on create, Filter, Group, Sort, Update</p> <p>Description ID of the owner of this record. This field is a polymorphic relationship field.</p> <p>Relationship Name Owner</p> <p>Relationship Type Lookup</p> <p>Refers To Group, User</p>
ParentPersonExaminationId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The parent Person Examination associated with this examination. This field is a relationship field.</p> <p>Relationship Name ParentPersonExamination</p> <p>Relationship Type Lookup</p>

Field	Details
	<p>Refers To PersonExamination</p>
Result	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Result of the examination. Possible values are:</p> <ul style="list-style-type: none"> • Fail • Pass
Score	<p>Type int</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Score secured in the examination.</p>
ScoreType	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the type of examination score. Possible values are:</p> <ul style="list-style-type: none"> • Actual • Predicted
SubjectName	<p>Type picklist</p> <p>Properties Create, Filter, Group, Restricted picklist, Nillable, Sort, Update</p> <p>Description Specifies the academic subject associated with the examination. Possible values are:</p> <ul style="list-style-type: none"> • English • Mathematics • Reading

Field	Details
	<ul style="list-style-type: none"> • Reading and Writing • Science • Writing • Composite
VerificationDateTime	<p>Type dateTime</p> <p>Properties Create, Filter, Nillable, Sort, Update</p> <p>Description Date and time the examination details were verified.</p>
VerificationStatus	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Status of the examination details verification. Possible values are:</p> <ul style="list-style-type: none"> • Accepted • Rejected • Verified • Waived

PreliminaryApplicationRef

Represents details about saved applications. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `undelete()`, `update()`, `upsert()`

Fields

Field	Details
ApplicantId	<p>Type reference</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The contact record associated with the person who submitted the application. This field is a relationship field.</p> <p>Relationship Name Applicant</p> <p>Relationship Type Lookup</p> <p>Refers To Contact</p>
ApplicationCategory	<p>Type picklist</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description Specifies the category of the application based on the admission decision period. Possible values are:</p> <ul style="list-style-type: none"> • Early Decision • Regular Decision
ProgramTermApplnTimelineId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The program term application timeline associated with the preliminary application reference record. This field is a relationship field.</p> <p>Relationship Name ProgramTermApplnTimeline</p> <p>Relationship Type Lookup</p> <p>Refers To ProgramTermApplnTimeline</p>
SubmissionDate	<p>Type date</p>

Field	Details
	<p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The date when the application was submitted.</p>

ServiceTerritoryMember

Represents a service resource who can be assigned in a service territory in Field Service, Salesforce Scheduler, Workforce Engagement, or Education Cloud. This object is available in API version 57.0 and later.

Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`, `update()`, `upsert()`

Fields

Field	Details
LocationId	<p>Type reference</p> <p>Properties Create, Filter, Group, Nillable, Sort, Update</p> <p>Description The location where the service resource takes appointments. This field is a relationship field.</p> <p>Relationship Name Location</p> <p>Relationship Type Lookup</p> <p>Refers To Location</p>

For more information, see [ServiceTerritoryMember in Salesforce Scheduler](#).