# Salesforce Feedback Management Developer Guide

Version 66.0, Spring ’26

Last updated: April 10, 2026

© Copyright 2000–2026 Salesforce, Inc. All rights reserved. Salesforce is a registered trademark of Salesforce, Inc., as are other names and marks. Other marks appearing herein may be trademarks of their respective owners.

# CONTENTS


**Chapter 1:** Introduction to Salesforce Feedback Management . . . . . 1

**Chapter 2:** Salesforce Surveys Object Model . . . . . 2

**Chapter 3:** Salesforce Surveys Standard Objects . . . . . 3

Survey . . . . . 4
SurveyEmailBranding . . . . . 7
SurveyEngagementContext . . . . . 9
SurveyInvitation . . . . . 11
SurveyPage . . . . . 15
SurveyQuestion . . . . . 16
SurveyQuestionChoice . . . . . 20
SurveyQuestionResponse . . . . . 21
SurveyQuestionScore . . . . . 25
SurveyResponse . . . . . 28
SurveySubject . . . . . 36
SurveyVersion . . . . . 39
SurveyVersionAddlInfo . . . . . 41

**Chapter 4:** Salesforce Surveys Translation Resources . . . . . 48

Add or Change the Translation of a Survey Field . . . . . 49
Add or Update the Translated Value of Multiple Survey Fields in One or More Languages . . . . 50
Delete the Translated Value of a Survey Field . . . . . 51
Delete the Translated Value of Multiple Survey Fields in One or More Languages . . . . . 52
Get Translated Value of a Survey Field . . . . . 53
Get the Translated Values of Multiple Survey Fields in One or More Languages . . . . . 54

**Chapter 5:** Salesforce Surveys Business APIs . . . . . 57

Surveys for Authenticated Participants . . . . . 58
- Surveys Resources . . . . . 58
- Connect REST API Request Bodies . . . . . 69
- Connect REST API Response Bodies . . . . . 79

Surveys for Unauthenticated Participants . . . . . 88
- Set Up Your Environment . . . . . 89
- Access Token . . . . . 89
- Resources . . . . . 90
- Request Bodies . . . . . 93
- Response Bodies . . . . . 98
- Error Code Details . . . . . 106

**Chapter 6:** Salesforce Surveys Apex Classes . . . . . 109

sfdc_surveys Namespace . . . 110
SurveyInvitationLinkShortener Interface . . . 110
Example Implementation to Associate SurveySubjects with SurveyInvitation and SurveyResponses . . . 112
ConnectApi Namespace . . . 113
Surveys Class . . . 113
ConnectApi Input Classes . . . 114
ConnectApi Output Classes . . . 117
industriesNlpSvc . . . 118
NlpResponse Class . . . 118
NlpSummarizationResult Class . . . 119

**Chapter 7:** Salesforce Surveys Standard Invocable Actions . . . 120

Dynamic Send Survey Invitation Actions . . . 121
Perform Survey Sentiment Analysis . . . 124
Process Data Using Generative AI Action . . . 125
Send Survey Invitation Actions . . . 127
Transform NLP Action Results Action . . . 129

**Chapter 8:** Salesforce Surveys Use Cases . . . 132

Creation of Surveys by Using Salesforce Feedback Management Response APIs . . . 133
In-App Survey Overview . . . 133

# CHAPTER 1 Introduction to Salesforce Feedback Management

Gather customer feedback and gain deeper insights about your products or services through Surveys. Salesforce Feedback Management (SFM) gives you the tools and developer resources to create engaging, personalized surveys.

The developer resources include Connect REST APIs to build surveys, Apex classes to send survey invitations, and REST APIs to translate surveys. With SFM, you can:

- Create surveys with a wide range of question types.
- Achieve faster response times with retained application context as users don't have to switch between multiple applications to complete the survey.
- Define survey user experience with your company's branding and theme.
- Translate surveys and get feedback from a global audience.

SEE ALSO:

Salesforce Help: Salesforce Feedback Management

# CHAPTER 2 Salesforce Surveys Object Model

Learn about how Salesforce Surveys objects relate to one another in Salesforce.




This diagram represents the object model for Salesforce Surveys. For more details and a larger image, visit the Data Model Gallery.

# CHAPTER 3 Salesforce Surveys Standard Objects

In this chapter ...


- Survey
- SurveyEmailBranding
- SurveyEngagementContext
- SurveyInvitation
- SurveyPage
- SurveyQuestion
- SurveyQuestionChoice
- SurveyQuestionResponse
- SurveyQuestionScore
- SurveyResponse
- SurveySubject
- SurveyVersion
- SurveyVersionAddlInfo


Salesforce Feedback Management (SFM) provides you access to a suite of standard objects that you can find in Setup and as tabs in Salesforce. Use the standard objects to work with the core Surveys features.

SFM is available in both Salesforce Classic (not available in all orgs) and Lightning Experience.

SFM is available in Enterprise, Unlimited, and Developer editions.

Here's a list of standard objects available with SFM.

# Survey

Represents a survey.

## Supported Calls

`describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`

Note: You can't define custom fields for the Survey object using the Object Manager.

## Fields

| Field Name | Details |
|---|---|
| `ActiveVersionID` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the survey version currently activated. |
| `Description` | **Type**<br>string<br>**Properties**<br>Nillable<br>**Description**<br>The description of the survey. This field isn't visible in the UI. |
| `DeveloperName` | **Type**<br>string<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The survey's unique API name. |
| `IsPartialSaveEnabled` | **Type**<br>boolean<br>**Properties**<br>Create, Defaulted on create, Filter, Group, Sort<br>**Description**<br>Indicates whether to save the partial responses for the survey (`true`) or not (`false`).<br>The default value is `false`. |

| Field Name | Details |
| --- | --- |
| `LastReferencedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The date and time that the current user last viewed a record related to the survey. |
| `LastViewedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The timestamp for when the current user last viewed the survey. |
| `LatestVersionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the most recent version of this survey. |
| `Name` | **Type**<br>string<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The name of the survey that appears in the UI. This field is read-only from API version 50.0. |
| `NamespacePrefix` | **Type**<br>string<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The namespace prefix that is associated with this object. Each Developer Edition org that creates a managed package has a unique namespace prefix. Limit: 15 characters. You can refer to a component in a managed package by using the ***`namespacePrefix__componentName`*** notation.<br>The namespace prefix can have one of the following values.<br>• In Developer Edition orgs, `NamespacePrefix` is set to the namespace prefix of the org for all objects that support it, unless an object is in an installed managed package. In that case, the object has the namespace prefix of the |

| Field Name | Details |
| --- | --- |
| | installed managed package. This field's value is the namespace prefix of the Developer Edition org of the package developer.<br>• In orgs that are not Developer Edition orgs, `NamespacePrefix` is set only for objects that are part of an installed managed package. All other objects have no namespace prefix. |
| `OwnerId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the user who created the survey. |
| `SurveyType` | **Type**<br>string<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Type of the survey. The default value is Survey.<br>Possible values are:<br>• `ASSESSMENT` — Survey type for sales enablement teams. Available from API version 58.0 and later.<br>• `BASIC` — Survey with a question page with like or dislike, long text, multiple selection, NPS, rating, short text, and single selection questions, and without inserted participant responses, display logic, and page branching logic.<br>• `SURVEY` — Survey with all the available features. |
| `TotalVersionsCount` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The number of versions of the survey. |

## Associated Objects

This object has the following associated objects. Unless noted, they are available in the same API version as this object.

**SurveyChangeEvent**
Change events are available for the object.

**SurveyFeed (API version 42.0)**
Feed tracking is available for the object.

**SurveyOwnerSharingRule**
Sharing rules are available for the object.

**SurveyShare**
Sharing is available for the object.

# SurveyEmailBranding

Represents the configuration settings for invitation emails sent to survey participants for a particular survey.

## Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `query()`, `retrieve()`, `update()`, `upsert()`

## Special Access Rules

As of Spring '20 and later, only users with the View Setup and Configuration permission can access this object.

Note: You can't define custom fields for the SurveyEmailBranding object using the Object Manager.

## Fields

| Field Name | Details |
|---|---|
| `Body` | **Type**<br>textarea<br>**Properties**<br>Create, Update<br>**Description**<br>The body text of the invitation email. |
| `DeveloperName` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, Sort, Update<br>**Description**<br>The unique API name of the email branding configuration.<br>Note: Only users with View DeveloperName OR View Setup and Configuration permission can view, group, sort, and filter this field. |
| `FooterImageId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Nillable, Sort, Update |

| Field Name | Details |
| --- | --- |
| | **Description**<br>The ID of the content asset that appears in the footer of the invitation email. |
| `FromEmailAddress` | **Type**<br>email<br>**Properties**<br>Create, Filter, Group, Nillable, Sort, Update<br>**Description**<br>The email address that appears in the “From” field when the invitation is sent to participants. |
| `HeaderImageId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Nillable, Sort, Update<br>**Description**<br>The ID of the content asset that appears in the header of the invitation email. |
| `Language` | **Type**<br>picklist<br>**Properties**<br>Create, Defaulted on create, Filter, Group, Nillable, Restricted picklist, Sort, Update<br>**Description**<br>The language of the emails. Available languages include:<br>• Chinese (Simplified)<br>• Chinese (Traditional)<br>• Danish<br>• Dutch<br>• English<br>• Finnish<br>• French<br>• German<br>• Italian<br>• Japanese<br>• Korean<br>• Norwegian<br>• Portuguese (Brazilian)<br>• Russian<br>• Spanish<br>• Spanish (Mexican) |

| Field Name | Details |
| --- | --- |
| | • Swedish<br>• Thai |
| `MasterLabel` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, Sort, Update<br>**Description**<br>The label for these email configuration settings. |
| `Subject` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, Sort, Update<br>**Description**<br>The subject of the invitation email. |

# SurveyEngagementContext

Represents the context based on which a survey invitation was sent or a survey response was received. This object is available in API version 49.0 and later.

## Supported Calls

`create()`, `delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

Note: You can't define custom fields for the SurveyEngagementContext object using the Object Manager.

## Fields

| Field | Details |
| --- | --- |
| `ContextType` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, Nillable, Sort, Update<br>**Description**<br>Context type based on which the survey invitation was sent or the response was received. |

| Field | Details |
| --- | --- |
| `ContextValue` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, Nillable, Sort, Update<br>**Description**<br>Context based on which the survey invitation was sent or the response was received. |
| `Name` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, idLookup, Sort, Update<br>**Description**<br>Name of the record. |
| `OwnerId` | **Type**<br>reference<br>**Properties**<br>Create, Defaulted on create, Filter, Group, Sort, Update<br>**Description**<br>ID of the record's owner. |
| `SurveyInvitationId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Nillable, Sort<br>**Description**<br>ID of the survey invitation. |
| `SurveyResponseId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Nillable, Sort<br>**Description**<br>ID of the survey response. |

# Associated Objects

This object has the following associated objects. Unless noted, they are available in the same API version as this object.

**SurveyEngagementContextShare**
Sharing is available for the object.

# SurveyInvitation

Represents the invitation sent to a participant to complete the survey.

## Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

## Fields

| Field Name | Details |
|---|---|
| `CommunityId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the Experience Cloud site that you want to send the survey to. |
| `ContactId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>ID of the contact who received the invitation. This field is available in API v49.0 and later. |
| `EmailBrandingId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the survey email branding object that's associated with this invitation. |
| `InvitationLink` | **Type**<br>url<br>**Properties**<br>Group, Nillable<br>**Description**<br>The URL to the survey that is sent to participants. To query on this field, you need access to the associated Survey record. |

| Field Name | Details |
| --- | --- |
| `InviteExpiryDateTime` | **Type**<br>dateTime<br>**Properties**<br>Create, Filter, Nillable, Sort, Update<br>**Description**<br>The date and time that the survey invitation expires. |
| `IsDefault` | **Type**<br>boolean<br>**Properties**<br>Create, Defaulted on create, Filter, Group, Sort, Update<br>**Description**<br>Determines whether this is the default survey invitation to use when the survey is sent to participants. |
| `LastReferencedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The timestamp for when the current user last viewed a record related to this survey invitation. |
| `LastViewedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The timestamp for when the current user last viewed this survey invitation. |
| `LeadId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>ID of the lead who received the invitation. This field is available in API v49.0 and later. |
| `Name` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, idLookup, Sort, Update |

| Field Name | Details |
| --- | --- |
| | **Description**<br>The name of the survey invitation that appears in the UI. |
| `OptionsAllowGuestUserResponse` | **Type**<br>boolean<br>**Properties**<br>Create, Filter, Update<br>**Description**<br>Determines whether participants who don't have a Salesforce account can complete the survey. |
| `OptionsAllowParticipantAccessTheirResponse` | **Type**<br>boolean<br>**Properties**<br>Create, Filter, Update<br>**Description**<br>Determines whether participants can access a copy of their responses after they complete the survey. |
| `OptionsCollectAnonymousResponse` | **Type**<br>boolean<br>**Properties**<br>Create, Filter, Update<br>**Description**<br>Determines whether participants can complete the survey anonymously. |
| `OwnerId` | **Type**<br>reference<br>**Properties**<br>Create, Defaulted on create, Filter, Group, Sort, Update<br>**Description**<br>ID of the user who created the survey invitation. |
| `ParticipantId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Nillable, Sort<br>**Description**<br>ID of the participant if the participant is a Salesforce contact, user, or lead. |
| `ResponseStatus` | **Type**<br>picklist |

| Field Name | Details |
| --- | --- |
| | **Properties**<br>Filter, Group, Restricted picklist, Sort<br>**Description**<br>The status of a participant's response to the survey that's associated with the survey invitation. Possible values include:<br>• `NotStarted` — For an invitation with a `ParticipantID`, it means that the recipient hasn't opened the survey. For an invitation without the `ParticipantID`, it means that none of the recipients have opened the survey.<br>• `Started` — For an invitation with a `ParticipantID`, it means that the recipient opened the survey. For an invitation without the `ParticipantID`, it means that the survey has been opened by at least one recipient.<br>• `Paused` — For an invitation with a `ParticipantID`, it means that the recipient has paused the survey. For an invitation without the `ParticipantID`, it means that the survey has been paused by any one of the recipients. Paused isn't available for invitations in which either `OptionsAllowParticipantAccessTheirResponse` or `OptionsCollectAnonymousResponse` is true.<br>• `PartiallyCompleted`— For an invitation with a `ParticipantID` field, it means that the recipient has partially completed the survey. For an invitation without the `ParticipantID` field, it means that at least one recipient has partially completed the survey. Available in API version 63.0 and later.<br>• `Completed` — For an invitation with a `ParticipantID`, it means that the recipient has submitted the survey. For an invitation without the `ParticipantID`, it means that the invitation has been submitted by at least one recipient. |
| `SurveyId` | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Sort<br>**Description**<br>ID of the survey that's sent in the invitation. |
| `UUID` | **Type**<br>string<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>A unique user ID that's added to a survey invitation generated for a contact, lead,or user. |

| Field Name | Details |
| --- | --- |
| `UserId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>ID of the user who received the invitation. This field is available in API v49.0 and later. |

## Associated Objects

This object has the following associated objects. Unless noted, they are available in the same API version as this object.

**SurveyInvitationChangeEvent (API version 62.0)**
Change events are available for the object.

**SurveyInvitationOwnerSharingRule**
Sharing rules are available for the object.

**SurveyInvitationShare**
Sharing is available for the object.

# SurveyPage

Represents a page, such as the title page or a question page, in a survey.

## Supported Calls

`getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Note: You can't define custom fields for the SurveyPage object using the Object Manager.

## Fields

| Field | Details |
| --- | --- |
| `DeveloperName` | **Type**<br>string<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The unique API name of this SurveyPage object. |
| `Name` | **Type**<br>string |

| Field | Details |
| --- | --- |
| | **Properties**<br>Filter, Group, idLookup, Sort<br>**Description**<br>The name of the survey page that appears in the UI. |
| `SurveyVersionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The version of the survey that the page belongs to. |

## Associated Objects

This object has the following associated objects. If the API version isn't specified, they're available in the same API versions as this object. Otherwise, they're available in the specified API version and later.

**SurveyPageChangeEvent**
Change events are available for the object.

# SurveyQuestion

Represents a question in a survey.

## Supported Calls

`describeLayout()` `describeSObjects()` `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Note: You can't define custom fields for the SurveyQuestion object using the Object Manager.

## Fields

| Field | Details |
| --- | --- |
| `DeveloperName` | **Type**<br>string<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The API name of the SurveyQuestion. The API name must be unique within a particular version of the survey. |

| Field | Details |
| --- | --- |
| `IsDeprecated` | **Type**<br>boolean<br>**Properties**<br>Defaulted on create, Filter, Group, Sort<br>**Description**<br>Indicates whether the question was deleted from the survey. |
| `Name` | **Type**<br>string<br>**Properties**<br>Filter, Group, idLookup, Sort<br>**Description**<br>Up to the first 250 characters of the label for the question. |
| `PageDisplayOrder` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The order in which the page is displayed. This field is available in API version 54.0 and later. |
| `PageName` | **Type**<br>string<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The label for the page. This field is available in API version 52.0 and later. |
| `QuestionChoiceCount` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The number of choices for the question. This field is available in API version 62.0 and later. |
| `QuestionName` | **Type**<br>textarea<br>**Properties**<br>Nillable<br>**Description**<br>The label for the question. |

| Field | Details |
| --- | --- |
| `QuestionOrder` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The order in which the question is displayed.<br>The label for the page. This field is available in API version 52.0 and later. |
| `QuestionType` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Restricted picklist, Sort<br>**Description**<br>The type of question. Possible values include:<br>• `Boolean`—This value is available in API v49.0 and later.<br>• `CSAT`<br>• `Currency`<br>• `Date`<br>• `DateTime`<br>• `FreeText`<br>• `Image`<br>• `Matrix`—This value is available in API v55.0 and later.<br>• `MultipleChoice`<br>• `MultiSelectPicklist`<br>• `NPS`<br>• `Number`<br>• `Picklist`<br>• `RadioButton`<br>• `StackRank`<br>• `Rating`<br>• `ShortText`—This value is available in API v49.0 and later.<br>• `Slider`<br>• `Toggle` |
| `RelatedQuestionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort |

| Field | Details |
| --- | --- |
| | **Description**<br>The ID of the parent question. This field is blank when the question itself is the parent question. This field is available in API v55.0 and later, with Feedback Management - Starter and Feedback Management - Growth licenses. |
| `SubQuestionDisplayOrder` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The order in which the question is displayed within the parent question. This field is available in API v55.0 and later, with Feedback Management - Starter and Feedback Management - Growth licenses. |
| `SurveyPageId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>Lookup to the SurveyPage that contains the question. |
| `SurveyVersionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the SurveyVersion that the question belongs to. |
| `ValidationType` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>The validations available for the short-text question. Possible values include:<br>• Custom - Cu<br>• Number - Nu |

## Associated Objects

This object has the following associated objects. If the API version isn't specified, they're available in the same API versions as this object. Otherwise, they're available in the specified API version and later.

**SurveyQuestionChangeEvent**
Change events are available for the object.

# SurveyQuestionChoice

Represents an answer choice that a participant can select for a survey question.

## Supported Calls

`describeLayout()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Note: You can't define custom fields for the SurveyQuestionChoice object using the Object Manager.

## Fields

| Field | Details |
|---|---|
| `DeveloperName` | **Type**<br>string<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The unique API name of the SurveyQuestionChoice object. |
| `DisplayOrder` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The order in which the question choice is displayed within the parent question. This field is available in API v55.0 and later, with Feedback Management - Starter and Feedback Management - Growth licenses. |
| `IsDeprecated` | **Type**<br>boolean<br>**Properties**<br>Defaulted on create, Filter, Group, Sort<br>**Description**<br>Indicates whether a question choice was deleted from the survey. |
| `Name` | **Type**<br>string |

| Field | Details |
| --- | --- |
| | **Properties**<br>Filter, Group, idLookup, Sort<br>**Description**<br>A label for the question choice that appears in the UI. |
| `QuestionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the SurveyQuestion object that this choice belongs to. |
| `SurveyVersionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The version of the survey that this question choice belongs to. |

## Associated Objects

This object has the following associated objects. If the API version isn't specified, they're available in the same API versions as this object. Otherwise, they're available in the specified API version and later.

**SurveyQuestionChoiceChangeEvent**
Change events are available for the object.

# SurveyQuestionResponse

Represents a participant's answer to a specific question.

## Supported Calls

`describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

Note: You can't define custom fields for the SurveyQuestionResponse object using the Object Manager.

# Fields

| Field | Details |
| --- | --- |
| `ChoiceValue` | **Type**<br>textarea<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>Response provided by a participant for the following question types:<br>• Multiple choice<br>• Picklist<br>• Radio<br>• Ranking |
| `Datatype` | **Type**<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>The data type of the question response. Possible values are:<br>• `Boolean` This value is available in API v49.0 and later.<br>• `Date`<br>• `Double`<br>• `Int`<br>• `Number`<br>• `String` |
| `DateTimeValue` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>Response provided by a participant for a question of the type date time. |
| `DateValue` | **Type**<br>date<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Response provided by a participant for a question of the type date. |

| Field | Details |
| --- | --- |
| `InvitationId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the SurveyInvitation that was sent to the survey participant. |
| `IsTrueOrFalse` | **Type**<br>boolean<br>**Properties**<br>Defaulted on create, Filter, Group, Sort<br>**Description**<br>Response provided by a participant for a question type which has only two possible values: True and False. |
| `NumberValue` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Response provided by a participant for the following question types:<br>• Net Promoter Score (NPS)<br>• Rating<br>• Score<br>• Slider |
| `QuestionChoiceId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The ID of SurveyQuestionChoice that a participant chose in response to a question. |
| `QuestionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the SurveyQuestion that a participant provided an answer for. |

| Field | Details |
| --- | --- |
| `Rank` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Rank provided by a participant for an answer choice for the ranking question type. |
| `ResponseId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the SurveyResponse that is the parent of this SurveyQuestionResponse. |
| `ResponseShortText` | **Type**<br>string<br>**Properties**<br>Filter, Group, idLookup, Sort<br>**Description**<br>Up to the first 250 characters of the response provided by a participant for a text type question. |
| `ResponseValue` | **Type**<br>textarea<br>**Properties**<br>Nillable<br>**Description**<br>Response provided by a participant for a question. |
| `SurveyVersionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the SurveyVersion that the response belongs to. |

# Associated Objects

This object has the following associated objects. If the API version isn't specified, they're available in the same API versions as this object. Otherwise, they're available in the specified API version and later.

**SurveyQuestionResponseChangeEvent**
Change events are available for the object.

# SurveyQuestionScore

Represents the aggregate of responses for the following question types: date, multiple choice, picklist, radio, ranking, rating, scoring, slider, and Net Promoter Score® (NPS®).

## Supported Calls

`delete()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`

Note: You can't define custom fields for the SurveyQuestionScore object using the Object Manager.

## Fields

| Field | Details |
|---|---|
| `CumulativeScore` | **Type**<br>double<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>Sum of the responses provided by all the participants for a question of the following types: rating, scoring, and slider. For a question of the type ranking, sum of the weights provided by all the participants for each item.<br>Note: This field is only applicable for the overall score type. |
| `DateResponse` | **Type**<br>date<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The date selected by one or more participants for a question of the type date.<br>Note: This field is only applicable for the individual score type. |
| `Name` | **Type**<br>string<br>**Properties**<br>Filter, Group, idLookup, Sort<br>**Description**<br>For an overall score type record:<br>• Name of a question.<br>• Name of an item in a question of the type ranking.<br>For an individual score type record: |

| Field | Details |
| --- | --- |
| | • Name of an item in a question of the type ranking.<br>• Name of a question of the type date.<br>• Response provided by one or more participants for questions of the following types: picklist, multiple choice, rating, ranking, score, slider, NPS. |
| `QuestionChoiceId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Unique identifier of the answer choice selected by one or more participants. For an individual score type record, this field is applicable for questions of the following types: picklist, radio, multi choice, ranking and rating. For an overall score type record, this field is applicable for questions of the type ranking. |
| `QuestionDeveloperName` | **Type**<br>string<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The API name of the question for which response is recorded. The API name must be unique within a particular version of the survey. |
| `QuestionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Unique identifier of the question for which response is recorded. |
| `QuestionName` | **Type**<br>textarea<br>**Properties**<br>Nillable<br>**Description**<br>Name of the question for which response is recorded. |
| `QuestionSkippedCount` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort |

| Field | Details |
| --- | --- |
| | **Description**<br>Number of participants who didn't respond to the question.<br>Note: This field is only applicable for the overall score type. |
| `ResponseCount` | **Type**<br>int<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>For an overall score type record, number of participants who responded to the question. For an individual score type record, number of participants who selected a particular answer choice. |
| `ResponseValue` | **Type**<br>double<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>Answer choice selected by one or more participants for a question of the following types: rating, slider, score, NPS. Rank provided by the participant for an item in a question of the type ranking.<br>Note: This field is only applicable for the individual score type. |
| `Score` | **Type**<br>double<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>For an individual score type record, percentage of participants who selected a particular answer choice.<br>Note: For questions of the type ranking, the percentage of participants who have provided the same rank to an item.<br>For overall score type record:<br>• Average score of questions of the following question types: rating, scoring, and slider.<br>• Score of an NPS type question.<br>• Average weight provided by all participants for each item in question of the type ranking.<br>• Number of participants who responded to the question for the following question types: date, radio, multi choice, and picklist. |

| Field | Details |
| --- | --- |
| `ScoreType` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>Type of the score calculated for a record. Possible values are:<br>• `Individual`<br>• `Overall` |
| `SurveyId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>Unique identifier of the survey that contains the question for which scores are calculated. |
| `SurveyInvitationId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Unique identifier of the survey invitation for which scores are calculated. |
| `SurveyVersionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>Unique identifier of the survey version for which scores are calculated. |

# SurveyResponse

Represents information about a participant's response to a survey, such as the status of the response, the participant's location, and when the survey was completed.

## Supported Calls

`describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`

Note: You can't define custom fields for the SurveyResponse object using the Object Manager.

# Fields

| Field Name | Details |
| --- | --- |
| `CompletionDateTime` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The date and time that the participant completed the survey. |
| `DataMapperExecutionStatus` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>Status of all the survey data maps after a response is received. This field is available in API v49.0 and later, with Feedback Management - Starter and Feedback Management - Growth licenses.<br>Possible values are:<br>• `Pending`<br>• `InProgress`<br>• `Success`<br>• `Error` |
| `InterviewGuid` | **Type**<br>string<br>**Properties**<br>Filter, Group, idLookup, Nillable<br>**Description**<br>An automatically-generated, unique ID for a saved survey response. |
| `InterviewId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the FlowInterview object that's associated with this response. |
| `InvitationId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort |

| Field Name | Details |
| --- | --- |
| | **Description**<br>The ID of the SurveyInvitation object that's associated with this response. |
| `IpAddress` | **Type**<br>string<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The IP address of the device the participant used to take the survey. |
| `Language` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>The language that the participant used to complete the survey.<br>Possible values are:<br>• `af`—Afrikaans<br>• `ar`—Arabic<br>• `ar_AE`—Arabic (United Arab Emirates)<br>• `ar_BH`—Arabic (Bahrain)<br>• `ar_DZ`—Arabic (Algeria)<br>• `ar_EG`—Arabic (Egypt)<br>• `ar_IQ`—Arabic (Iraq)<br>• `ar_JO`—Arabic (Jordan)<br>• `ar_KW`—Arabic (Kuwait)<br>• `ar_LB`—Arabic (Lebanon)<br>• `ar_LY`—Arabic (Libya)<br>• `ar_MA`—Arabic (Morocco)<br>• `ar_OM`—Arabic (Oman)<br>• `ar_QA`—Arabic (Qatar)<br>• `ar_SA`—Arabic (Saudi Arabia)<br>• `ar_SD`—Arabic (Sudan)<br>• `ar_SY`—Arabic (Syria)<br>• `ar_TN`—Arabic (Tunisia)<br>• `ar_YE`—Arabic (Yemen)<br>• `bg`—Bulgarian<br>• `bn`—Bengali<br>• `bs`—Bosnian |

| Field Name | Details |
| --- | --- |
| | • ca—Catalan<br>• cs—Czech<br>• cy—Welsh<br>• da—Danish<br>• de—German<br>• de_AT—German (Austria)<br>• de_BE—German (Belgium)<br>• de_CH—German (Switzerland)<br>• de_LU—German (Luxembourg)<br>• el—Greek<br>• en_AU—English (Australian)<br>• en_CA—English (Canadian)<br>• en_GB—English (UK)<br>• en_HK—English (Hong Kong)<br>• en_IE—English (Ireland)<br>• en_IN—English (Indian)<br>• en_MY—English (Malaysian)<br>• en_NZ—English (New Zealand)<br>• en_PH—English (Philippines)<br>• en_SG—English (Singapore)<br>• en_US—English<br>• en_ZA—English (South Africa)<br>• es—Spanish<br>• es_AR—Spanish (Argentina)<br>• es_BO—Spanish (Bolivia)<br>• es_CL—Spanish (Chile)<br>• es_CO—Spanish (Colombia)<br>• es_CR—Spanish (Costa Rica)<br>• es_DO—Spanish (Dominican Republic)<br>• es_EC—Spanish (Ecuador)<br>• es_GT—Spanish (Guatemala)<br>• es_HN—Spanish (Honduras)<br>• es_MX—Spanish (Mexico)<br>• es_NI—Spanish (Nicaragua)<br>• es_PA—Spanish (Panama)<br>• es_PE—Spanish (Peru)<br>• es_PR—Spanish (Puerto Rico)<br>• es_PY—Spanish (Paraguay) |

| Field Name | Details |
| --- | --- |
| | • es_SV—Spanish (El Salvador)<br>• es_US—Spanish (United States)<br>• es_UY—Spanish (Uruguay)<br>• es_VE—Spanish (Venezuela)<br>• et—Estonian<br>• eu—Basque<br>• fa—Farsi<br>• fi—Finnish<br>• fr—French<br>• fr_BE—French (Belgium)<br>• fr_CA—French (Canadian)<br>• fr_CH—French (Switzerland)<br>• fr_LU—French (Luxembourg)<br>• ga—Irish<br>• gu—Gujarati<br>• hi—Hindi<br>• hr—Croatian<br>• hu—Hungarian<br>• hy—Armenian<br>• in—Indonesian<br>• is—Icelandic<br>• it—Italian<br>• it_CH—Italian (Switzerland)<br>• iw—Hebrew<br>• ja—Japanese<br>• ka—Georgian<br>• kn—Kannada<br>• ko—Korean<br>• lb—Luxembourgish<br>• lt—Lithuanian<br>• lv—Latvian<br>• mi—Te reo<br>• mk—Macedonian<br>• ml—Malayalam<br>• mr—Marathi<br>• ms—Malay<br>• mt—Maltese<br>• my—Burmese |

| Field Name | Details |
| --- | --- |
| | • nl_BE—Dutch (Belgium)<br>• nl_NL—Dutch<br>• no—Norwegian<br>• pl—Polish<br>• pt_BR—Portuguese (Brazil)<br>• pt_PT—Portuguese (European)<br>• rm—Romansh<br>• ro—Romanian<br>• ro_MD—Romanian (Moldova)<br>• ru—Russian<br>• sh—Serbian (Latin)<br>• sh_ME—Montenegrin<br>• sk—Slovak<br>• sl—Slovene<br>• sq—Albanian<br>• sr—Serbian (Cyrillic)<br>• sv—Swedish<br>• sw—Swahili<br>• ta—Tamil<br>• te—Telugu<br>• th—Thai<br>• tl—Tagalog<br>• tr—Turkish<br>• uk—Ukrainian<br>• ur—Urdu<br>• vi—Vietnamese<br>• xh—Xhosa<br>• zh_CN—Chinese (Simplified)<br>• zh_HK—Chinese (Hong Kong)<br>• zh_SG—Chinese (Singapore)<br>• zh_TW—Chinese (Traditional)<br>• zu—Zulu |
| LastReferencedDate | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort |

| Field Name | Details |
| --- | --- |
| | **Description**<br>The date and time that another Salesforce object last referenced this SurveyResponse object. |
| `LastViewedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The date and time that someone last viewed this SurveyResponse object. |
| `Latitude` | **Type**<br>double<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The latitude of the participant's location. |
| `Location` | **Type**<br>location<br>**Properties**<br>Nillable<br>**Description**<br>The latitude and longitude coordinates of the participant's location. |
| `Longitude` | **Type**<br>double<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The longitude of the participant's location. |
| `Name` | **Type**<br>string<br>**Properties**<br>Filter, Group, idLookup, Sort<br>**Description**<br>The name of the participant. |
| `Status` | **Type**<br>picklist |

| Field Name | Details |
| --- | --- |
| | **Properties**<br>Filter, Group, Restricted picklist, Sort<br>**Description**<br>The status of the survey. Possible values include:<br>• NotStarted — The participant hasn't opened the survey.<br>• Started — The participant has opened the survey.<br>• Paused — The participant has paused the survey. Paused isn't available for invitations in which either `OptionsAllowParticipantAccessTheirResponse` or `OptionsCollectAnonymousResponse` is true.<br>• PartiallyCompleted — The participant has partially completed the survey. Available in API version 63.0 and later.<br>• Completed — The participant has completed the survey. |
| `SubmitterId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the Salesforce user, contact, or lead who completed the survey.<br>**Relationship Name**<br>Submitter<br>**Relationship Type**<br>Lookup<br>**Refers To**<br>Contact, Lead, User |
| `SurveyId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the survey that the participant completed. |
| `SurveyVersionId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the version of the survey that the participant completed. |

## Associated Objects

This object has the following associated objects. If the API version isn't specified, they're available in the same API versions as this object. Otherwise, they're available in the specified API version and later.

**SurveyResponseChangeEvent**
Change events are available for the object.

# SurveySubject

Represents a relationship between a survey and another object, such as an account or a case.

## Supported Calls

`create()`, `delete()`, `describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `undelete()`, `update()`, `upsert()`

## Fields

| Field Name | Details |
|---|---|
| `LastReferencedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The timestamp for when the SurveySubject record was last referenced by another object. |
| `LastViewedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The timestamp for when the current user last viewed the SurveySubject record. |
| `Name` | **Type**<br>string<br>**Properties**<br>Create, Filter, Group, idLookup, Sort, Update<br>**Description**<br>The name of the SurveySubject record. |
| `ParentId` | **Type**<br>reference |

| Field Name | Details |
| --- | --- |
| | **Properties**<br>Create, Filter, Group, Sort<br>**Description**<br>Unique identifier of the SurveyInvitation object or SurveyResponse object that is associated with this survey-object relationship.<br>**Relationship Name**<br>Parent<br>**Relationship Type**<br>Lookup<br>**Refers To**<br>SurveyInvitation, SurveyResponse |
| `SubjectEntityType` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>Object that the survey is associated with. Possible values include:<br>• *`Account`*<br>• *`Asset`*<br>• *`Banker`*<br>• *`BranchUnit`*<br>• *`BranchUnitBusinessMember`*<br>• *`BranchUnitCustomer`*<br>• *`BusinessLicenseApplication`*<br>• *`BusinessMilestone`*<br>• *`Campaign`*<br>• *`CareProgram`*<br>• *`Case`*<br>• *`Claim`*<br>• *`ClaimParticipant`*<br>• *`Contact`*<br>• *`Employee`*<br>• *`Event`*<br>• *`Incident`*<br>• *`IndividualApplication`*<br>• *`InsurancePolicy`*<br>• *`InsurancePolicyParticipant`*<br>• *`Lead`* |

| Field Name | Details |
| --- | --- |
| | • *LearningItemSubmission*—Available in API version 58.0 and later.<br>• *LiveChatTranscript*<br>• *LoyaltyProgram*<br>• *LoyaltyProgramMember*<br>• *LoyaltyProgramPartner*<br>• *MaterialityStakeholder*<br>• *MessagingSession*<br>• *Opportunity*<br>• *Order*<br>• *PersonalLifeEvent*<br>• *Producer*<br>• *Product2*<br>• *Promotion*<br>• *RebateProgram*<br>• *RetailStore*<br>• *ServiceAppointment*<br>• *ServiceResource*<br>• *Solution*<br>• *Task*<br>• *TransactionJournal*<br>• *User*<br>• *VideoCall*<br>• *Visit*<br>• *VoiceCall*<br>• *VolunteerProject*<br>• *WorkOrder*<br>• Custom Objects |
| SubjectId | **Type**<br>reference<br>**Properties**<br>Create, Filter, Group, Sort, Update<br>**Description**<br>The ID of the object that's associated with the survey. |
| SurveyId | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort |

| Field Name | Details |
| --- | --- |
| | **Description**<br>Unique identifier of the survey that's associated with the record that's represented by `SubjectId`. |
| `SurveyInvitationId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Unique identifier of the survey invitation that's associated with another object. |
| `SurveyResponseId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>Unique identifier of the survey response that's associated with another object. |

## Associated Objects

This object has the following associated objects. If the API version isn't specified, they're available in the same API versions as this object. Otherwise, they're available in the specified API version and later.

**SurveySubjectChangeEvent (API version 62.0)**
Change events are available for the object.

# SurveyVersion

Represents a version of a survey.

## Supported Calls

`describeLayout()`, `describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`, `search()`

Note: You can't define custom fields for the SurveyVersion object using the Object Manager.

## Fields

| Field Name | Details |
| --- | --- |
| `BrandingSetId` | **Type**<br>reference |

| Field Name | Details |
| --- | --- |
| | **Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The ID of the branding set associated with the survey version. |
| `Description` | **Type**<br>textarea<br>**Properties**<br>Nillable<br>**Description**<br>The description of this survey version. |
| `IsTemplate` | **Type**<br>boolean<br>**Properties**<br>Defaulted on create, Filter, Group, Sort<br>**Description**<br>Indicates whether the survey version is a template. Template surveys are automatically shared with all users in your Salesforce org. |
| `LastReferencedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The date and time that the current user last viewed a record related to the survey version. |
| `LastViewedDate` | **Type**<br>dateTime<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The timestamp for when the current user last viewed the survey version. |
| `Name` | **Type**<br>string<br>**Properties**<br>Filter, Group, Sort<br>Filter, Group, Sort<br>Filter, Group, idLookup, Sort |

| Field Name | Details |
| --- | --- |
| | **Description**<br>The name of the survey that appears in the UI. |
| `SurveyId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The ID of the survey associated with the survey version. |
| `SurveyStatus` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>The status of the survey. Possible values include:<br>• `Active`<br>• `Draft`<br>• `Obsolete`<br>• `InvalidDraft` |
| `VersionNumber` | **Type**<br>int<br>**Properties**<br>Filter, Group, Sort<br>**Description**<br>The version number of the survey. |

## Associated Objects

This object has the following associated objects. If the API version isn't specified, they're available in the same API versions as this object. Otherwise, they're available in the specified API version and later.

**SurveyVersionChangeEvent**
Change events are available for the object.

# SurveyVersionAddlInfo

Represents additional information about a survey version. This information defines the default settings of a survey version. This object is available in API version 49.0 and later.

## Supported Calls

`describeSObjects()`, `getDeleted()`, `getUpdated()`, `query()`, `retrieve()`

## Fields

| Field | Details |
|---|---|
| `EmailSender` | **Type**<br>textarea<br>**Properties**<br>Filter, Nillable, Sort<br>**Description**<br>The organization-wide email address used to send a survey invitation. |
| `EmailTemplateId` | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>ID of the email template that's used to send an automated survey invitation. |
| `EngagementContextMetadata` | **Type**<br>string<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>The custom metadata created to get the engagement context from the participants. |
| `InvitationSharingRole` | **Type**<br>picklist<br>**Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>Indicates the users that share edit access to a survey invitation.<br>Possible values are:<br>• `InvitationRecordCreator`— Owner of the record that's associated with a survey invitation.<br>• `SurveyOwner` |
| `Language` | **Type**<br>picklist |

| Field | Details |
| --- | --- |
| | **Properties**<br>Filter, Group, Nillable, Restricted picklist, Sort<br>**Description**<br>Language used to create the survey.<br>Possible values are:<br>• af—Afrikaans<br>• ar—Arabic<br>• ar_AE—Arabic (United Arab Emirates)<br>• ar_BH—Arabic (Bahrain)<br>• ar_DZ—Arabic (Algeria)<br>• ar_EG—Arabic (Egypt)<br>• ar_IQ—Arabic (Iraq)<br>• ar_JO—Arabic (Jordan)<br>• ar_KW—Arabic (Kuwait)<br>• ar_LB—Arabic (Lebanon)<br>• ar_LY—Arabic (Libya)<br>• ar_MA—Arabic (Morocco)<br>• ar_OM—Arabic (Oman)<br>• ar_QA—Arabic (Qatar)<br>• ar_SA—Arabic (Saudi Arabia)<br>• ar_SD—Arabic (Sudan)<br>• ar_SY—Arabic (Syria)<br>• ar_TN—Arabic (Tunisia)<br>• ar_YE—Arabic (Yemen)<br>• bg—Bulgarian<br>• bn—Bengali<br>• bs—Bosnian<br>• ca—Catalan<br>• cs—Czech<br>• cy—Welsh<br>• da—Danish<br>• de—German<br>• de_AT—German (Austria)<br>• de_BE—German (Belgium)<br>• de_CH—German (Switzerland)<br>• de_LU—German (Luxembourg)<br>• el—Greek<br>• en_AU—English (Australian) |

| Field | Details |
| --- | --- |
| | • en_CA—English (Canadian)<br>• en_GB—English (UK)<br>• en_HK—English (Hong Kong)<br>• en_IE—English (Ireland)<br>• en_IN—English (Indian)<br>• en_MY—English (Malaysian)<br>• en_NZ—English (New Zealand)<br>• en_PH—English (Philippines)<br>• en_SG—English (Singapore)<br>• en_US—English<br>• en_ZA—English (South Africa)<br>• es—Spanish<br>• es_AR—Spanish (Argentina)<br>• es_BO—Spanish (Bolivia)<br>• es_CL—Spanish (Chile)<br>• es_CO—Spanish (Colombia)<br>• es_CR—Spanish (Costa Rica)<br>• es_DO—Spanish (Dominican Republic)<br>• es_EC—Spanish (Ecuador)<br>• es_GT—Spanish (Guatemala)<br>• es_HN—Spanish (Honduras)<br>• es_MX—Spanish (Mexico)<br>• es_NI—Spanish (Nicaragua)<br>• es_PA—Spanish (Panama)<br>• es_PE—Spanish (Peru)<br>• es_PR—Spanish (Puerto Rico)<br>• es_PY—Spanish (Paraguay)<br>• es_SV—Spanish (El Salvador)<br>• es_US—Spanish (United States)<br>• es_UY—Spanish (Uruguay)<br>• es_VE—Spanish (Venezuela)<br>• et—Estonian<br>• eu—Basque<br>• fa—Farsi<br>• fi—Finnish<br>• fr—French<br>• fr_BE—French (Belgium)<br>• fr_CA—French (Canadian) |

| Field | Details |
| --- | --- |
| | • `fr_CH`—French (Switzerland)<br>• `fr_LU`—French (Luxembourg)<br>• `ga`—Irish<br>• `gu`—Gujarati<br>• `hi`—Hindi<br>• `hr`—Croatian<br>• `hu`—Hungarian<br>• `hy`—Armenian<br>• `in`—Indonesian<br>• `is`—Icelandic<br>• `it`—Italian<br>• `it_CH`—Italian (Switzerland)<br>• `iw`—Hebrew<br>• `ja`—Japanese<br>• `ka`—Georgian<br>• `kn`—Kannada<br>• `ko`—Korean<br>• `lb`—Luxembourgish<br>• `lt`—Lithuanian<br>• `lv`—Latvian<br>• `mi`—Te reo<br>• `mk`—Macedonian<br>• `ml`—Malayalam<br>• `mr`—Marathi<br>• `ms`—Malay<br>• `mt`—Maltese<br>• `my`—Burmese<br>• `nl_BE`—Dutch (Belgium)<br>• `nl_NL`—Dutch<br>• `no`—Norwegian<br>• `pl`—Polish<br>• `pt_BR`—Portuguese (Brazil)<br>• `pt_PT`—Portuguese (European)<br>• `rm`—Romansh<br>• `ro`—Romanian<br>• `ro_MD`—Romanian (Moldova)<br>• `ru`—Russian<br>• `sh`—Serbian (Latin) |

| Field | Details |
| --- | --- |
| | • sh_ME—Montenegrin<br>• sk—Slovak<br>• sl—Slovene<br>• sq—Albanian<br>• sr—Serbian (Cyrillic)<br>• sv—Swedish<br>• sw—Swahili<br>• ta—Tamil<br>• te—Telugu<br>• th—Thai<br>• tl—Tagalog<br>• tr—Turkish<br>• uk—Ukrainian<br>• ur—Urdu<br>• vi—Vietnamese<br>• xh—Xhosa<br>• zh_CN—Chinese (Simplified)<br>• zh_HK—Chinese (Hong Kong)<br>• zh_SG—Chinese (Singapore)<br>• zh_TW—Chinese (Traditional)<br>• zu—Zulu |
| Name | **Type**<br>string<br>**Properties**<br>Filter, Group, idLookup, Sort<br>**Description**<br>Name of the record. |
| SurveyQuestionId | **Type**<br>reference<br>**Properties**<br>Filter, Group, Nillable, Sort<br>**Description**<br>ID of the survey question embedded in the email template used to send automated survey invitations. |
| SurveyVersionId | **Type**<br>reference |

| Field | Details |
| --- | --- |
| | **Properties**<br>Filter, Group, Sort<br>**Description**<br>ID of the survey version. This field is unique within your organization |

# CHAPTER 4 Salesforce Surveys Translation Resources

In this chapter ...


- Add or Change the Translation of a Survey Field
- Add or Update the Translated Value of Multiple Survey Fields in One or More Languages
- Delete the Translated Value of a Survey Field
- Delete the Translated Value of Multiple Survey Fields in One or More Languages
- Get Translated Value of a Survey Field
- Get the Translated Values of Multiple Survey Fields in One or More Languages


Use REST APIs to translate survey fields, view, update, or delete translated survey fields. The translated values of surveys fields are stored in Flow fields.

The following survey fields can be translated:

- Survey name
- Pause message
- Welcome message
- Questions
- Answer choices and ranking items
- Thank you message

# Add or Change the Translation of a Survey Field

If a survey field can be translated or is already translated into a particular language, you can add or change the translated value of the survey field. This resource is available in REST API version 48.0 and later.

Note: This URI can only be used for the flow process type `Survey`.

## Syntax

**URI**

`/services/data/v`***`XX.X`***`/localizedvalue/record/`***`developerName`***`/`***`language`***

**Formats**

JSON

**HTTP methods**

POST

**Authentication**

`Authorization: Bearer` ***`token`***

**Request body JSON example**

```
{
"value": "China"
}
```

**Request parameters**

| Parameter | Description |
|---|---|
| `developerName` | Optional. Developer name of the flow field. |
| `language` | Optional Translated language of the flow field. |
| `value` | Required. Translated value of the flow field. |

**Response parameters**

| Parameter | Description |
|---|---|
| `createdBy` | ID of the user who translated the flow field. |
| `createdDate` | Date and time the flow field was translated. |
| `developerName` | Developer name of the flow field. |
| `language` | Language into which the flow field was translated. |
| `value` | Translated value of the flow field. |
| `isOutofDate` | Indicates if the flow field is out of date. |

## Example

```
{
  "createdBy": "005xxx",
  "createdDate": "2018-09-14T00:10:30Z",
  "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
  "language": "zh_CN",
  "value": "□□",
  "isOutOfDate": true
}
```

# Add or Update the Translated Value of Multiple Survey Fields in One or More Languages

If one or more survey fields can be translated or are already translated, you can add or update the translated values of the survey fields in the languages into which survey fields can be translated. This resource is available in REST API version 48.0 and later.

Note: This URI can only be used for the flow process type `Survey`.

## Syntax

**URI**

`/services/data/v`***`XX.X`***`/localizedvalue/records/upsert`

**Formats**

JSON

**HTTP methods**

POST

**Request body JSON example**

```
[
  {
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "en_US",
    "value": "China"
  },
  {
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "zh_CN",
    "value": "□□"
  }
]
```

**Request parameters**

| Parameter | Description |
| --- | --- |
| `developerName` | Required. Developer name of the flow field. |

| Parameter | Description |
|---|---|
| `language` | Required. Language into which the flow field is translated. |
| `value` | Required. New or updated value of the flow field. |

**Response parameters**

| Parameter | Description |
|---|---|
| `createdBy` | ID of the user who translated the flow field. |
| `createdDate` | Date and time the flow field was translated. |
| `developerName` | Developer name of the flow field. |
| `language` | Language into which the flow field was translated. |
| `value` | Updated value of the flow field. |
| `isOutofDate` | Indicates if the flow field is out of date. |

## Example

```
[
  {
    "createdBy": "005xxx",
    "createdDate": "2018-09-14T00:10:30Z",
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "en_US",
    "value": "China",
    "isOutOfDate": false
  },
  {
    "createdBy": "005xxx",
    "createdDate": "2018-09-14T00:10:30Z",
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "zh_CN",
    "value": "□□",
    "isOutOfDate": false
  }
]
```

# Delete the Translated Value of a Survey Field

After a survey field is translated into a particular language, you can delete the translated value of the survey field. This resource is available in REST API version 48.0 and later.

Note: This URI can only be used for the flow process type `Survey`.

## Syntax

**URI**

`/services/data/v`***XX.X***`/localizedvalue/record/`***developerName***`/`***language***

**Formats**

JSON

**HTTP methods**

DELETE

**Request parameters**

| Parameter | Description |
|---|---|
| `developerName` | The developer name of the flow field. For example, *`Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel`* |
| `language` | Language of the translated field. Possible values are:<br>• `da`<br>• `nl_NL`<br>• `fi`<br>• `fr`<br>• `de` |

# Delete the Translated Value of Multiple Survey Fields in One or More Languages

After survey fields are translated into one or more languages, you can delete the translated values of multiple survey fields. This resource is available in REST API version 48.0 and later.

Note: This URI can only be used for the flow process type `Survey`.

## Syntax

**URI**

`/services/data/v`***XX.X***`/localizedvalue/records/delete`

**Formats**

JSON

**HTTP methods**

POST

**Request body JSON example**

```
[
  {
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "en_US"
```

```
  },
  {
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "zh_CN"
  }
]
```

**Request parameters**

| Parameter | Description |
|---|---|
| `developerName` | Required. Developer name of the flow field. |
| `language` | Required. Language into which the flow field was translated. |

# Get Translated Value of a Survey Field

After a survey field is translated into a particular language, you can use this resource to get the translated value of the survey field. This resource is available in REST API version 48.0 and later.

Note: This URI can only be used for the flow process type `Survey`.

## Syntax

**URI**

`/services/data/v`***`XX.X`***`/localizedvalue/record/`***`developerName`***`/`***`language`***

**Formats**

JSON

**HTTP methods**

GET

**Authentication**

`Authorization: Bearer` ***`token`***

**Request body**

None

**Request parameters**

| Path Parameter | Description |
|---|---|
| `developerName` | Required. The developer name of the flow field. For example, *`Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel`* |
| `language` | Required. Language of the translated field. Possible values are:<br>• `da`<br>• `nl_NL`<br>• `fi`<br>• `fr` |

| Path Parameter | Description |
| --- | --- |
| | • `de` |

**Response parameters**

| Parameter | Description |
| --- | --- |
| `createdBy` | ID of the user who translated the flow field. |
| `createdDate` | Date and time the flow field was translated. |
| `developerName` | Developer name of the flow field. |
| `language` | Language into which the flow field was translated. |
| `value` | Translated value of the flow field. |
| `isOutofDate` | Indicates if the flow field is out of date. |

## Example

```
{
  "createdBy": "005xxx",
  "createdDate": "2018-09-14T00:10:30Z",
  "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
  "language": "zh_CN",
  "value": "□□",
  "isOutOfDate": true
}
```

# Get the Translated Values of Multiple Survey Fields in One or More Languages

After survey fields are translated into one or more languages, you can view the translated values of multiple survey fields in the translated languages. This resource is available in REST API versions 48.0 and later.

Note: This URI can only be used for the flow process type `Survey`.

## Syntax

**URI**

`/services/data/v`***XX.X***`/localizedvalue/records/get`

**Formats**

JSON

**HTTP methods**

POST

**Request body JSON example**

```
[
  {
     "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
     "language": "en_US"
  },
  {
     "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
     "language": "zh_CN"
  }
]
```

**Request parameters**

| Parameter | Description |
|---|---|
| `developerName` | Required. Developer name of the flow field. |
| `language` | Required. Language into which the flow field was translated. |

**Response parameters**

| Parameter | Description |
|---|---|
| `createdBy` | ID of the user who translated the flow field. |
| `createdDate` | Date and time the flow field was translated. |
| `developerName` | Developer name of the flow field. |
| `language` | Language into which the flow field was translated. |
| `value` | Translated value of the flow field. |
| `isOutofDate` | Indicates if the flow field is out of date. |

# Example

```
[
  {
    "createdBy": "005xxx",
    "createdDate": "2018-09-14T00:10:30Z",
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "en_US",
    "value": "China",
    "isOutOfDate": true
  },
  {
    "createdBy": "005xxx",
    "createdDate": "2018-09-14T00:10:30Z",
    "developerName": "Flow.Flow.MyFlow.1.Choice.Choice_1_Master.InputLabel",
    "language": "zh_CN",
```

```
    "value": "□□",
    "isOutOfDate": true
  }
]
```

# CHAPTER 5 Salesforce Surveys Business APIs

In this chapter ...


- Surveys for Authenticated Participants
- Surveys for Unauthenticated Participants


Salesforce Feedback Management (SFM) developer resources include Connect REST APIs that you can use to create engaging, personalized surveys in Salesforce.

Use the SFM Connect REST APIs to build in-app surveys in Salesforce Lightning pages, such as the home page or record pages for users to respond in Salesforce.

# Surveys for Authenticated Participants

Use Salesforce Feedback Management (SFM) Response APIs to create survey invitations and to enable survey responses from authenticated participants.

Surveys Resources
Understand customer feedback as it evolves over time by engaging customers and users with relevant, personalized surveys. Incorporate survey data into your feedback management process and gain actionable insights at every stage of the customer lifecycle.

Connect REST API Request Bodies
To perform a POST, PATCH, or PUT request, pass query parameters or create a request body formatted in either XML or JSON. This chapter lists the request bodies. The query parameters are listed with each resource.

Connect REST API Response Bodies
The successful execution of a request to a Connect REST API resource can return a response body in either JSON or XML format.

## Surveys Resources

Understand customer feedback as it evolves over time by engaging customers and users with relevant, personalized surveys. Incorporate survey data into your feedback management process and gain actionable insights at every stage of the customer lifecycle.

Note: Salesforce Feedback Management (SFM) Business API performance can be impacted if a POST request exceeds 5,400 calls per minute and if a PATCH request exceeds 2,700 calls per minute at the org level. For more rate limit information, see Connect REST API Limits.

Available resources are:

| Resource | Description |
|---|---|
| `/connect/surveys/surveyId/survey-invitation-emails` | Email survey invitations to up to 300 participants. You can email leads, contacts, or users in your org. Either a link to launch the survey or a question can be embedded in the email invitations. |
| `/connect/surveys/surveyId/survey-response` | Create responses using the invitation configuration details and initiate the process of submitting the survey responses by making a POST request. Submit the survey responses using the PATCH request. |
| `/connect/surveys/surveyId/invitation/surveyInvitationId/survey-response` | Initialize the process of submitting survey responses and return the details of the first page of the survey by making a POST request. Submit the survey responses using the PATCH request. |

Salesforce Surveys Invitation Emails Resource
Email survey invitations to up to 300 participants. You can email leads, contacts, or users in your org. Either a link to launch the survey or a question can be embedded in the email invitations.

Survey Responses Using Invitation Configurations (POST, PATCH)
Create responses using the invitation configuration details and initiate the process of submitting the survey responses by making a POST request. Submit the survey responses using the PATCH request. You can create a survey to collect data from customers, employees, or other people whose feedback you need. The survey responses are stored in the SurveyResponse object and the responses to individual questions in the SurveyQuestionResponse object.

Surveys Responses Using Invitation ID (POST, PATCH)

Initialize the process of submitting survey responses and return the details of the first page of the survey by making a POST request. Submit the survey responses using the PATCH request. You can create a survey to collect data from customers, employees, or other people whose feedback you need. The survey responses are stored in the SurveyResponse object and the responses to individual questions in the SurveyQuestionResponse object.

SEE ALSO:

Salesforce Platform Connect API rate limits

## Salesforce Surveys Invitation Emails Resource

Email survey invitations to up to 300 participants. You can email leads, contacts, or users in your org. Either a link to launch the survey or a question can be embedded in the email invitations.

**Resource**

```
/connect/surveys/surveyId/survey-invitation-emails
```

**Available version**

50.0

**HTTP methods**

POST

**Request body for POST**

**Root XML tag**

```
<SurveyInvitationEmailInput>
```

**JSON example**

```
{
 "recipients":["003x0000003j8CEAAY"],
 "collectAnonymousResponse":false,
 "allowParticipantsAccessTheirResponse":false,
 "allowGuestUserResponse":true,
 "isPersonalInvitation":true,
 "emailTemplateId":"00Xx0000000LwAuEAK",
 "surveyQuestionIds":["0Kux000000003yBCAQ"],
 "invitationExpirationDate":"2020-07-31T21:32:54",
 "fromEmailAddress":"abeeram@salesforce.com",
 "invitationOwner":"0054V00000FZTjJ",
 "shareInvitationsWith":["0054V00000FZTjJ"],

"associateRecordsWithRecipients":[{"recipientId":"003x0000003j8CEAAY","associateRecordIds":["001x0000004EWIZAA4"]}],

 "recipientEngagementContexts":[{"recipientId" :
"003x0000003j8CEAAY","recipientEngagementContext":{"TestKey" :"TestValue"}}]
}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `allowGuestUserResponse` | Boolean | Specifies whether participants who don't have a Salesforce account can respond (`true`) or not (`false`). | Required | 50.0 |
| `allowParticipantsAccessTheirResponse` | Boolean | Specifies whether participants can see their responses (`true`) or not (`false`). | Required | 50.0 |
| `associateRecordsWithRecipients` | Survey Recipient Survey Subjects Input[] | Maps each recipient with another record that must be associated with the recipient's survey invitation. | Optional | 50.0 |
| `body` | String | Content of the email. Specify the email body in case you don't specify an email template. The email body must contain one of these merge fields:<br>• To embed a link to launch the survey: [[SURVEY_INVITATION_URL]]<br>• To embed a survey question: {{{SurveyQuestion.QuestionName}}} and {{{SurveyQuestion.QuestionHtmlContent}}} | Optional | 50.0 |
| `collectAnonymousResponse` | Boolean | Specifies whether participants can respond anonymously (`true`) or not (`false`). | Required | 50.0 |
| `communityId` | String | ID of the site that's used to open the survey for users outside your org. | Optional | 50.0 |
| `emailTemplateId` | String | ID of the Lightning email template that's used to send the survey invitation. The template must contain the required merge fields that embed either the survey link or a question in the email. Only Lightning email templates are used to send survey invitations. | Optional | 50.0 |
| `fromEmailAddress` | String | Email ID of the user or the org-wide email address associated with the user's profile. | Required | 50.0 |
| `invitationExpirationDate` | String | Date on which the survey invitation expires. | Optional | 50.0 |
| `invitationOwner` | String | ID of the owner of the survey invitation records. | Optional | 50.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `isPersonalInvitation` | Boolean | Specifies whether a unique invitation is created for each participant (`true`) or not (`false`). When a participant responds using a personal invitation, the response record is associated with the participant's Salesforce record. | Required | 50.0 |
| `recipientEngagementContexts` | Survey Recipient Engagement Context Input[] | Maps each recipient with the context based on which the survey invitation is emailed. | Optional | 50.0 |
| `recipients` | String[] | List of up to 300 IDs of leads, contacts, or users to whom the survey invitation is emailed. | Required | 50.0 |
| `sendEmailThroughUma` | Boolean | Specifies whether to send the email through Marketing Cloud (`true`) or not (`false`). If unspecified, defaults to `false`. | Optional | 65.0 |
| `shareInvitationsWith` | String[] | IDs of the users with whom the survey invitation records must be shared. The invitation records are shared with Read access. | Optional | 50.0 |
| `subject` | String | Subject of the email. Specify the subject in case you don't specify an email template. | Optional | 50.0 |
| `surveyQuestionIds` | String[] | IDs of the questions that are embedded in the email. You can send an email invitation for questions of these types: Net Promoter Score (NPS), rating, and score. | Optional | 50.0 |

**Response body for POST**

Survey Email

## Survey Responses Using Invitation Configurations (POST, PATCH)

Create responses using the invitation configuration details and initiate the process of submitting the survey responses by making a POST request. Submit the survey responses using the PATCH request. You can create a survey to collect data from customers, employees, or other people whose feedback you need. The survey responses are stored in the SurveyResponse object and the responses to individual questions in the SurveyQuestionResponse object.

Note: Salesforce Feedback Management (SFM) Business API performance can be impacted if a POST request exceeds 5,400 calls per minute and if a PATCH request exceeds 2,700 calls per minute at the org level. For more rate limit information, see Connect REST API Limits.

## Special Access Rules

The Feedback Management - Starter and Feedback Management - Growth licenses are required to use this resource.

**Resource**

```
/connect/surveys/surveyId/survey-response
```

**Example**

```
https://yourInstance.salesforce.com/services/data/56.0/connect
/surveys/0Kdx00000000H46CAE/survey-response
```

**Available version**

56.0

**HTTP methods**

PATCH, POST

Note: The HTTP header request format only accepts `Content-Type: application/json`.

**Request body for POST**

**JSON example**

```
{
  "languageCode": "",
  "relatedRecordIds": [
    "500xx000000bo3dAAA"
  ],
  "recipientEngagementContext": {
    "test_key1": "test_value1",
    "test_key2": "test_value1"
  },
  "invitationSettings": {
    "recipientId": "005xx000001X7ibAAC",
    "allowGuestUserResponse": false,
    "allowParticipantsAccessTheirResponse": false,
    "collectAnonymousResponse": false,
    "invitationExpirationDate": "2022-07-31T21:32:54",
    "communityId": "",
    "invitationOwner": ""
  }
}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| invitationSettings | Survey Invitation Settings Input | Invitation settings of the survey.<br>Note: The Invitation ID API doesn't require the invitation configuration settings to be passed with the Survey Invitations. | Required | 56.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `languageCode` | String | Code of the language in which the survey is created. | Optional | 56.0 |
| `recipientEngagementContext` | Map<String, String> | Engagement context settings for a recipient of the survey. | Optional | 56.0 |
| `relatedRecordIds` | String[] | IDs of the records that are related to the survey. | Optional | 56.0 |
| `shouldLoadPartiallyCmplSurvey` | Boolean | Indicates whether to load partially completed surveys when a partially completed survey is selected (`true`), or to start a new survey (`false`). The default value is `false`. | Optional | 63.0 |
| `staticMergeFields` | Map<String, String> | Map of static merge field values. | Optional | 56.0 |

**Response body for POST**

Survey Description Output

**Request body for PATCH**

**JSON example**

Here's an example for multiple questions.

```
{
  "invitationId": "0Kixx0000004DbMCAU",
  "languageCode": "en",
  "flowInterviewState": "ewqJgw",
  "navigationAction" : "Next",
  "surveyPageResponses": {
    "name" :  "p_ff794819_c0f0_4e0d_b357_29ca1694cfc4",
    "questionResponses": [
      {
        "name": "q_d217f330_05a6_4e2b_859b_1f1ef210bf84",
        "questionType": "NPS",
        "responseValue": 5
      },
      {
        "name": "q_ab781617_3665_4a41_b4ff_f236d73ecb30",
        "questionType": "FreeText",
        "responseValue": "Free Text Question Response"
      },
      {
        "name": "q_b1cdfe4c_9c7d_4c2f_ad9d_1915d301d780",
        "questionType": "ShortText",
        "responseValue": "Short Text Question Response"
      },
      {
```

```
        "name": "q_f84a6a3c_683c_4ed5_864e_5b486baed308",
        "questionType": "Boolean",
        "responses": [
          {
            "name": "choice1"
          }
        ]
      },
      {
        "name": "q_113419b1_5d29_4bb9_8b10_e3fe324ae040",
        "questionType": "MultiChoice",
        "responses": [
          {
            "name": "c_9775c2e5_9086_44a8_a5c9_89fdc886c99a"
          },
          {
            "name": "c_0f1f63cc_608a_4560_9d29_72b203f195f2"
          }
        ]
      },
      {
        "name": "q_1d8690a9_ae95_4e7c_86be_b8057205facc",
        "questionType": "RadioButton",
        "responses": [
          {
            "name": "c_4867edc8_e9a6_4e86_9fea_b80758e90caf"
          }
        ]
      },
      {
        "name": "q_8946f212_25ff_43a8_a507_d267637eee1f",
        "questionType": "Rating",
        "responses": [
          {
            "name": "c_f51c509a_9643_4a05_89f1_42464de618a6"
          }
        ]
      }
    ]
  }
}
```

Here's an example for a single question.

```
{
  "invitationId": "0Kixx0000004EdsCAE",
  "languageCode": "en",
  "navigationAction" : "Next",
  "surveyPageResponses": {
    "questionResponses": [
      {
        "name": "q_3e501184_bb93_4a9c_a66b_6f2d81c92316",
        "questionType": "FreeText",
        "responseValue": "Answer for text question"
      }
```

```
    ]
  },
  "flowInterviewState": "eg"
}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `flowInterviewState` | String | State of the flow interview. | Required | 56.0 |
| `invitationId` | String | ID of the survey invitation. | Required | 56.0 |
| `languageCode` | String | Code of the language that the survey is created in. | Optional | 56.0 |
| `navigationAction` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Navigate to the previous survey page.<br>• `Next`—Navigate to the next survey page. | Required | 57.0 |
| `surveyPageResponses` | Survey Page Response Input | Responses to the survey questions on a page. | Required | 56.0 |

**Response body for PATCH**

Survey Response Output

SEE ALSO:

Salesforce Platform Connect API rate limits

## Surveys Responses Using Invitation ID (POST, PATCH)

Initialize the process of submitting survey responses and return the details of the first page of the survey by making a POST request. Submit the survey responses using the PATCH request. You can create a survey to collect data from customers, employees, or other people whose feedback you need. The survey responses are stored in the SurveyResponse object and the responses to individual questions in the SurveyQuestionResponse object.

Note: Salesforce Feedback Management (SFM) Business API performance can be impacted if a POST request exceeds 5,400 calls per minute and if a PATCH request exceeds 2,700 calls per minute at the org level. For more rate limit information, see Connect REST API Limits.

### Special Access Rules

The Feedback Management - Starter and Feedback Management - Growth licenses are required to use this resource.

### Resource

```
/connect/surveys/surveyId/invitation/surveyInvitationId/survey-response
```

### Example

```
https://yourInstance.salesforce.com/services/data/56.0/connect
/surveys/0Kdx00000000H46CAE/invitation/0Kixx0000004EsOCAU/survey-response
```

### Available version

56.0

### HTTP methods

POST, PATCH

Note: The HTTP header request format only accepts `Content-Type: application/json`.

### Request body for POST

#### JSON example

```
{
  "languageCode": "",
  "relatedRecordIds": [
    "500xx000000bo3dAAA"
  ],
  "recipientEngagementContext": {
    "test_key1": "test_value1",
    "test_key2": "test_value1"
  }
}
```

#### Properties

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `invitationSettings` | Survey Invitation Settings Input | Invitation settings of the survey.<br>Note: The Invitation ID API doesn't require the invitation configuration settings to be passed with the Survey Invitations. | Required | 56.0 |
| `languageCode` | String | Code of the language in which the survey is created. | Optional | 56.0 |
| `recipientEngagementContext` | Map<String, String> | Engagement context settings for a recipient of the survey. | Optional | 56.0 |
| `relatedRecordIds` | String[] | IDs of the records that are related to the survey. | Optional | 56.0 |
| `shouldLoadPartiallyCmplSurvey` | Boolean | Indicates whether to load partially completed surveys when a partially completed survey is selected (`true`), or | Optional | 63.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| | | to start a new survey (`false`). The default value is `false`. | | |
| `staticMergeFields` | Map<String, String> | Map of static merge field values. | Optional | 56.0 |

**Response body for POST**

Survey Description Output

**Request body for PATCH**

**JSON example**

Here's an example for multiple questions.

```
{
  "invitationId": "0Kixx0000004DbMCAU",
  "languageCode": "en",
  "flowInterviewState": "ewqJgw",
  "navigationAction" : "Next",
  "surveyPageResponses": {
    "name" :  "p_ff794819_c0f0_4e0d_b357_29ca1694cfc4",
    "questionResponses": [
      {
        "name": "q_d217f330_05a6_4e2b_859b_1f1ef210bf84",
        "questionType": "NPS",
        "responseValue": 5
      },
      {
        "name": "q_ab781617_3665_4a41_b4ff_f236d73ecb30",
        "questionType": "FreeText",
        "responseValue": "Free Text Question Response"
      },
      {
        "name": "q_b1cdfe4c_9c7d_4c2f_ad9d_1915d301d780",
        "questionType": "ShortText",
        "responseValue": "Short Text Question Response"
      },
      {
        "name": "q_f84a6a3c_683c_4ed5_864e_5b486baed308",
        "questionType": "Boolean",
        "responses": [
          {
            "name": "choice1"
          }
        ]
      },
      {
        "name": "q_113419b1_5d29_4bb9_8b10_e3fe324ae040",
        "questionType": "MultiChoice",
        "responses": [
          {
```

```
            "name": "c_9775c2e5_9086_44a8_a5c9_89fdc886c99a"
          },
          {
            "name": "c_0f1f63cc_608a_4560_9d29_72b203f195f2"
          }
        ]
      },
      {
        "name": "q_1d8690a9_ae95_4e7c_86be_b8057205facc",
        "questionType": "RadioButton",
        "responses": [
          {
            "name": "c_4867edc8_e9a6_4e86_9fea_b80758e90caf"
          }
        ]
      },
      {
        "name": "q_8946f212_25ff_43a8_a507_d267637eee1f",
        "questionType": "Rating",
        "responses": [
          {
            "name": "c_f51c509a_9643_4a05_89f1_42464de618a6"
          }
        ]
      }
    ]
  }
}
```

Here's an example for a single question.

```
{
  "invitationId": "0Kixx0000004EdsCAE",
  "languageCode": "en",
  "navigationAction" : "Next",
  "surveyPageResponses": {
    "questionResponses": [
      {
        "name": "q_3e501184_bb93_4a9c_a66b_6f2d81c92316",
        "questionType": "FreeText",
        "responseValue": "Answer for text question"
      }
    ]
  },
  "flowInterviewState": "eg"
}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `flowInterviewState` | String | State of the flow interview. | Required | 56.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `invitationId` | String | ID of the survey invitation. | Required | 56.0 |
| `languageCode` | String | Code of the language that the survey is created in. | Optional | 56.0 |
| `navigationAction` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Navigate to the previous survey page.<br>• `Next`—Navigate to the next survey page. | Required | 57.0 |
| `surveyPage Responses` | Survey Page Response Input | Responses to the survey questions on a page. | Required | 56.0 |

**Response body for PATCH**

Survey Response Output

# Connect REST API Request Bodies

To perform a POST, PATCH, or PUT request, pass query parameters or create a request body formatted in either XML or JSON. This chapter lists the request bodies. The query parameters are listed with each resource.

To create a JSON request body, specify the properties of the request body in JSON format.

This is an example of a Comment request body.

```
{
 "body" : "Let's look for a new solution."
}
```

If a request body is top-level, it has a root XML tag listed. To create an XML request body, nest the properties as XML tags inside the root XML tag.

This is the same Connect request body in XML format:

```
<comment>
 <body>Let's look for a new solution.</body>
</comment>
```

Survey Description Input

Input representation of the details of the survey recipient and their engagement context, and the language, related records, and invitation settings of the survey.

Survey Email Input

Survey email.

Survey Integer Question Response Input

Input representation of the details of the response to an NPS question on the survey page.

Survey Invitation Settings Input

Input representation of the settings of the survey invitation that define the participants who can respond to the survey, its expiration, and other related configurations.

Survey Page Response Input

Input representation of the details of the response to a survey page.

Survey Question Response Input

Input representation of the details of the response to a question on the survey page.

Survey Recipient Engagement Context Input

Context based on which the survey invitation is sent to a participant.

Survey Recipient Survey Subjects Input

Records associated with the survey invitation.

Survey Response Input

Input representation of the details of a survey response.

Survey Selection Question Choice Input

The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

Survey Selection Question Response Input

Input representation of the details of the response to a boolean, rating, single selection, or a multiple selection question on the survey page.

Survey Text Question Response Input

The details of the response to a short-text or a long-text question on the survey page.

## Survey Description Input

Input representation of the details of the survey recipient and their engagement context, and the language, related records, and invitation settings of the survey.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `invitationSettings` | Survey Invitation Settings Input | Invitation settings of the survey.<br>Note: The Invitation ID API doesn't require the invitation configuration settings to be passed with the Survey Invitations. | Required | 56.0 |
| `languageCode` | String | Code of the language in which the survey is created. | Optional | 56.0 |
| `recipientEngagementContext` | Map<String, String> | Engagement context settings for a recipient of the survey. | Optional | 56.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| relatedRecordIds | String[] | IDs of the records that are related to the survey. | Optional | 56.0 |
| shouldLoadPartiallyCmplSurvey | Boolean | Indicates whether to load partially completed surveys when a partially completed survey is selected (true), or to start a new survey (false). The default value is false. | Optional | 63.0 |
| staticMergeFields | Map<String, String> | Map of static merge field values. | Optional | 56.0 |

## Survey Email Input

Survey email.

**Root XML tag**

<SurveyInvitationEmailInput>

**JSON example**

```
{
 "recipients":["003x0000003j8CEAAY"],
 "collectAnonymousResponse":false,
 "allowParticipantsAccessTheirResponse":false,
 "allowGuestUserResponse":true,
 "isPersonalInvitation":true,
 "emailTemplateId":"00Xx0000000LwAuEAK",
 "surveyQuestionIds":["0Kux000000003yBCAQ"],
 "invitationExpirationDate":"2020-07-31T21:32:54",
 "fromEmailAddress":"abeeram@salesforce.com",
 "invitationOwner":"0054V00000FZTjJ",
 "shareInvitationsWith":["0054V00000FZTjJ"],

"associateRecordsWithRecipients":[{"recipientId":"003x0000003j8CEAAY","associateRecordIds":["001x0000004EWIZAA4"]}],

 "recipientEngagementContexts":[{"recipientId" :
"003x0000003j8CEAAY","recipientEngagementContext":{"TestKey" :"TestValue"}}]
}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| allowGuestUserResponse | Boolean | Specifies whether participants who don't have a Salesforce account can respond (true) or not (false). | Required | 50.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `allowParticipantsAccessTheirResponse` | Boolean | Specifies whether participants can see their responses (`true`) or not (`false`). | Required | 50.0 |
| `associateRecordsWithRecipients` | Survey Recipient Survey Subjects Input[] | Maps each recipient with another record that must be associated with the recipient's survey invitation. | Optional | 50.0 |
| `body` | String | Content of the email. Specify the email body in case you don't specify an email template. The email body must contain one of these merge fields:<br>• To embed a link to launch the survey: [[SURVEY_INVITATION_URL]]<br>• To embed a survey question: {{{SurveyQuestion.QuestionName}}} and {{{SurveyQuestion.QuestionHtmlContent}}} | Optional | 50.0 |
| `collectAnonymousResponse` | Boolean | Specifies whether participants can respond anonymously (`true`) or not (`false`). | Required | 50.0 |
| `communityId` | String | ID of the site that's used to open the survey for users outside your org. | Optional | 50.0 |
| `emailTemplateId` | String | ID of the Lightning email template that's used to send the survey invitation. The template must contain the required merge fields that embed either the survey link or a question in the email. Only Lightning email templates are used to send survey invitations. | Optional | 50.0 |
| `fromEmailAddress` | String | Email ID of the user or the org-wide email address associated with the user's profile. | Required | 50.0 |
| `invitationExpirationDate` | String | Date on which the survey invitation expires. | Optional | 50.0 |
| `invitationOwner` | String | ID of the owner of the survey invitation records. | Optional | 50.0 |
| `isPersonalInvitation` | Boolean | Specifies whether a unique invitation is created for each participant (`true`) or not (`false`). When a participant responds using a personal invitation, the response record is associated with the participant's Salesforce record. | Required | 50.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `recipientEngagementContexts` | Survey Recipient Engagement Context Input[] | Maps each recipient with the context based on which the survey invitation is emailed. | Optional | 50.0 |
| `recipients` | String[] | List of up to 300 IDs of leads, contacts, or users to whom the survey invitation is emailed. | Required | 50.0 |
| `sendEmailThroughUma` | Boolean | Specifies whether to send the email through Marketing Cloud (`true`) or not (`false`). If unspecified, defaults to `false`. | Optional | 65.0 |
| `shareInvitationsWith` | String[] | IDs of the users with whom the survey invitation records must be shared. The invitation records are shared with Read access. | Optional | 50.0 |
| `subject` | String | Subject of the email. Specify the subject in case you don't specify an email template. | Optional | 50.0 |
| `surveyQuestionIds` | String[] | IDs of the questions that are embedded in the email. You can send an email invitation for questions of these types: Net Promoter Score (NPS), rating, and score. | Optional | 50.0 |

## Survey Integer Question Response Input

Input representation of the details of the response to an NPS question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | 56.0 |
| `questionType` | String | The type of survey question. | Required | 56.0 |
| `responseValue` | Integer | The value of a response to an NPS question in a survey. | Required | 56.0 |

## Survey Invitation Settings Input

Input representation of the settings of the survey invitation that define the participants who can respond to the survey, its expiration, and other related configurations.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `allowGuestUserResponse` | Boolean | Indicates whether a guest user can respond to the survey (`true`) or not (`false`). | Required | 56.0 |
| `allowParticipantsAccessTheirResponse` | Boolean | Indicates whether participants with Salesforce accounts can access their responses (`true`) or not (`false`). | Required | 56.0 |
| `collectAnonymousResponse` | Boolean | Indicates whether participants can take the survey without revealing their name or other identifying information (`true`) or not (`false`). | Required | 56.0 |
| `communityId` | String | The ID of the Experience Cloud site related to the survey. | Optional | 56.0 |
| `invitationExpirationDate` | String | The date when the survey invitation expires. | Optional | 56.0 |
| `invitationOwner` | String | The ID of the survey invitation's owner. The default value is the ID of the user running the API request. | Optional | 56.0 |
| `recipientId` | String | The ID of the survey recipient. | Optional | 56.0 |

## Survey Page Response Input

Input representation of the details of the response to a survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of the survey page.<br>Note: Reserved for future use. | Optional | 56.0 |
| `questionResponses` | Various | The responses to the survey questions on the page.<br>• NPS Question Type—See Survey Integer Question Response Input.<br>• Selection Question Type—See Survey Selection Question Response Input.<br>• Short Text or Long Text Question Type—See Survey Text Question Response Input. | Required | 56.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| | | • Other Question Type—See Survey Question Response Input. | | |

## Survey Question Response Input

Input representation of the details of the response to a question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | 56.0 |
| `questionType` | String | The type of survey question. | Required | 56.0 |

## Survey Recipient Engagement Context Input

Context based on which the survey invitation is sent to a participant.

**Root XML tag**

```
<SurveyRecipientEngagementContextInput>
```

**JSON example**

```
{"recipientId" : "003x0000003j8CEAAY","recipientEngagementContext":{"TestKey"
:"TestValue"}}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `recipient Engagement Context` | Map<String, String> | Map each recipient with the context based on which the survey invitation is emailed. | Required | 50.0 |
| `recipientId` | String | Participant ID with whom the engagement context should be associated. | Required | 50.0 |

## Survey Recipient Survey Subjects Input

Records associated with the survey invitation.

**Root XML tag**

```
<SurveyRecipientSurveySubjectsInput>
```

**JSON example**

```
{"recipientId":"003x0000003j8CEAAY","associateRecordIds":["001x0000004EWIZAA4"]}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `associateRecordIds` | String[] | ID of the associated records. | Required | 50.0 |
| `recipientId` | String | Participant ID with whose invitation the record should be associated. | Required | 50.0 |

## Survey Response Input

Input representation of the details of a survey response.

**JSON example**

Here's an example for multiple questions.

```
{
  "invitationId": "0Kixx0000004DbMCAU",
  "languageCode": "en",
  "flowInterviewState": "ewqJgw",
  "navigationAction" : "Next",
  "surveyPageResponses": {
    "name" :  "p_ff794819_c0f0_4e0d_b357_29ca1694cfc4",
    "questionResponses": [
      {
        "name": "q_d217f330_05a6_4e2b_859b_1f1ef210bf84",
        "questionType": "NPS",
        "responseValue": 5
      },
      {
        "name": "q_ab781617_3665_4a41_b4ff_f236d73ecb30",
        "questionType": "FreeText",
        "responseValue": "Free Text Question Response"
      },
      {
        "name": "q_b1cdfe4c_9c7d_4c2f_ad9d_1915d301d780",
        "questionType": "ShortText",
        "responseValue": "Short Text Question Response"
      },
      {
        "name": "q_f84a6a3c_683c_4ed5_864e_5b486baed308",
        "questionType": "Boolean",
        "responses": [
          {
            "name": "choice1"
          }
        ]
      },
      {
        "name": "q_113419b1_5d29_4bb9_8b10_e3fe324ae040",
        "questionType": "MultiChoice",
```

```
        "responses": [
          {
            "name": "c_9775c2e5_9086_44a8_a5c9_89fdc886c99a"
          },
          {
            "name": "c_0f1f63cc_608a_4560_9d29_72b203f195f2"
          }
        ]
      },
      {
        "name": "q_1d8690a9_ae95_4e7c_86be_b8057205facc",
        "questionType": "RadioButton",
        "responses": [
          {
            "name": "c_4867edc8_e9a6_4e86_9fea_b80758e90caf"
          }
        ]
      },
      {
        "name": "q_8946f212_25ff_43a8_a507_d267637eee1f",
        "questionType": "Rating",
        "responses": [
          {
            "name": "c_f51c509a_9643_4a05_89f1_42464de618a6"
          }
        ]
      }
    ]
  }
}
```

Here's an example for a single question.

```
{
  "invitationId": "0Kixx0000004EdsCAE",
  "languageCode": "en",
  "navigationAction" : "Next",
  "surveyPageResponses": {
    "questionResponses": [
      {
        "name": "q_3e501184_bb93_4a9c_a66b_6f2d81c92316",
        "questionType": "FreeText",
        "responseValue": "Answer for text question"
      }
    ]
  },
  "flowInterviewState": "eg"
}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `flowInterviewState` | String | State of the flow interview. | Required | 56.0 |
| `invitationId` | String | ID of the survey invitation. | Required | 56.0 |
| `languageCode` | String | Code of the language that the survey is created in. | Optional | 56.0 |
| `navigationAction` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Navigate to the previous survey page.<br>• `Next`—Navigate to the next survey page. | Required | 57.0 |
| `surveyPageResponses` | Survey Page Response Input | Responses to the survey questions on a page. | Required | 56.0 |

## Survey Selection Question Choice Input

The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of selected choice to a Boolean, rating, single selection, or multiple selection question in a survey. | Required | 56.0 |

## Survey Selection Question Response Input

Input representation of the details of the response to a boolean, rating, single selection, or a multiple selection question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | 56.0 |
| `questionType` | String | The type of survey question. | Required | 56.0 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `responses` | Survey Selection Question Choice Input[] | The responses to a Boolean, rating, single selection, or multiple selection question in a survey. | Required | 56.0 |

## Survey Text Question Response Input

The details of the response to a short-text or a long-text question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | 56.0 |
| `questionType` | String | The type of survey question. | Required | 56.0 |
| `responseValue` | String | The value of a response to a short-text or long-text question in a survey. | Required | 56.0 |

# Connect REST API Response Bodies

The successful execution of a request to a Connect REST API resource can return a response body in either JSON or XML format.

A request to a Connect REST API resource always returns an HTTP response code, whether the request was successful or not.

Survey Description Output
Output representation of the response to the Start Survey request.

Survey Detail Output
Output representation of the details of the survey.

Survey Email
Survey invitation email response.

Survey NPS Question Output
Output representation of the details of the NPS question on the survey page.

Survey Question Output
Output representation of the details of the question on the survey page.

Survey Question Page Output
The details of the question page in the survey.

Survey Response Output
Output representation of the response to the Submit Survey request. The response includes the status of the survey response API and the Thank You page details in the survey.

Survey Selection Question Choice Output
The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

Survey Selection Question Output

Output representation of the details of the boolean, rating, single-selection, or multiple-selection question on the survey page.

Survey Short-Text Question Output

Output representation of the details of the short-text question on the survey page.

Survey Text Question Output

Output representation of the details of the text question on the survey page.

Survey Thank You Page Output

Output representation of the details of the Thank You page in the survey.

Survey URL Buttons Output

Output representation of the details of the URL buttons on the Thank You page in the survey.

## Survey Description Output

Output representation of the response to the Start Survey request.

**JSON example**

```
{
  "languageCode": "en",
  "invitationId": "0Kixx0000004MWaCAM",
  "flowInterviewState": "state1",
  "status": "Success",
  "isPartiallyCmplSurveyLoaded": false,
  "surveyDetail": {
    "label": "Survey01",
    "name": "Survey01",
    "surveyPage": {
      "label": "Page 1",
      "name": "p_d84afb73_3a30_4a3f_aae7_b0478b3bb4ed",
      "surveyQuestions": [
        {
          "name": "q_856a997e_be2c_4ea3_b70d_7f6fb9cfbf4f",
          "label": "Good so Far !",
          "questionType": "ShortText",
          "responseDataType": "STRING",
          "isResponseRequired": false
        }
      ]
    }
  },
  "navigationActions": [
    "Next"
  ],
  "responseId": "0Myxx0000004CYqCAM",
  "errors": [],
  "warnings": []
}
```

**Properties**

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `errors` | String[] | Error messages for a failed request. | Small, 56.0 | 56.0 |
| `flowInterviewState` | String | State of the flow interview. | Small, 56.0 | 56.0 |
| `invitationId` | String | ID of the survey invitation that's related to the request. | Small, 56.0 | 56.0 |
| `isPartiallyCmplSurveyLoaded` | Boolean | Indicates whether a partially completed survey is loaded (`true`) or a new survey is started (`false`). | Small, 63.0 | 63.0 |
| `languageCode` | String | Code of the language that the survey is created in. | Small, 56.0 | 56.0 |
| `navigationActions` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Go to the previous survey page.<br>• `Next`—Go to the next survey page. | Small, 57.0 | 57.0 |
| `responseId` | String | ID of the survey response. | Small, 57.0 | 57.0 |
| `status` | String | Status of the API request.<br>Possible values are:<br>• `Failure`—Survey Response API isn't successfully run.<br>• `Success`—Survey Response API is successfully run. | Small, 56.0 | 56.0 |
| `surveyDetail` | Survey Detail Output | All details of the page in the survey. | Small, 56.0 | 56.0 |
| `warnings` | String[] | Warnings for a request. | Small, 56.0 | 56.0 |

## Survey Detail Output

Output representation of the details of the survey.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `label` | String | The label of the survey. | Small, 56.0 | 56.0 |
| `name` | String | The API name of the survey. | Small, 56.0 | 56.0 |

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `surveyPage` | Survey Question Page Output<br>OR<br>Survey Thank You Page Output | The details of the question or thank you page in the survey. | Small, 56.0 | 56.0 |
| `versionLabel` | String | The label of the survey version. | Small, 56.0 | 56.0 |
| `versionNumber` | Integer | The version number of the survey. | Small, 56.0 | 56.0 |

## Survey Email

Survey invitation email response.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `errorCode` | Integer | Error code for the failed call. | Small, 50.0 | 50.0 |
| `errorMessage` | String | Details explaining why the call failed. | Small, 50.0 | 50.0 |
| `status` | String | Status of a survey invitation email. Values are:<br>• `Failed`—The survey invitation email wasn't sent.<br>• `Queued`—The survey invitation email is queued for sending. | Small, 50.0 | 50.0 |

## Survey NPS Question Output

Output representation of the details of the NPS question on the survey page.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `description` | String | Description for the survey question. | Small, 56.0 | 56.0 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory. | Small, 56.0 | 56.0 |
| `label` | String | Label of the survey question. | Small, 56.0 | 56.0 |
| `maxScale` | Integer | Maximum score that participants can select for an NPS question in the survey. | Small, 56.0 | 56.0 |
| `minScale` | Integer | Minimum score that participants can select for an NPS question in the survey. | Small, 56.0 | 56.0 |

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `name` | String | API name of the survey question. | Small, 56.0 | 56.0 |
| `questionType` | String | Type of survey question. | Small, 56.0 | 56.0 |
| `responseDataType` | String | Data type of the survey question. | Small, 56.0 | 56.0 |
| `responseValue` | Integer | Value of the response to an NPS question in a survey. | Small, 57.0 | 57.0 |

## Survey Question Output

Output representation of the details of the question on the survey page.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `description` | String | The description for the survey question. | Small, 56.0 | 56.0 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory (`true`) or not (`false`). | Small, 56.0 | 56.0 |
| `label` | String | The label of the survey question. | Small, 56.0 | 56.0 |
| `name` | String | The API name of the survey question. | Small, 56.0 | 56.0 |
| `questionType` | String | The type of survey question. | Small, 56.0 | 56.0 |
| `responseDataType` | String | The data type of the survey question. | Small, 56.0 | 56.0 |

## Survey Question Page Output

The details of the question page in the survey.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `label` | String | The label of the survey page. | Small, 56.0 | 56.0 |
| `name` | String | The API name of the survey page. | Small, 56.0 | 56.0 |
| `surveyQuestions` | NPS Question Type<br>Selection Question Type<br>ShortText Question Type<br>Text Question Type | List of survey questions. | Small, 56.0 | 56.0 |

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| | Other Question Type | | | |

## Survey Response Output

Output representation of the response to the Submit Survey request. The response includes the status of the survey response API and the Thank You page details in the survey.

**JSON example**

```
{
  "languageCode": "en",
  "invitationId": "0Kixx0000004MWaCAM",
  "flowInterviewState": "state1",
  "status": "Success",
  "surveyPage": {
    "label": "Page 1",
    "name": "p_d84afb73_3a30_4a3f_aae7_b0478b3bb4ed",
    "surveyQuestions": [
      {
        "name": "q_856a997e_be2c_4ea3_b70d_7f6fb9cfbf4f",
        "label": "Good so Far !",
        "questionType": "ShortText",
        "responseDataType": "STRING",
        "isResponseRequired": false
      }
    ]
  },
  "navigationActions": [
    "Next",
    "Back"
  ],
  "responseId": "0Myxx0000004CYqCAM",
  "errors": []
}
```

**Properties**

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `errors` | String[] | Error messages for a failed request. | Small, 56.0 | 56.0 |
| `flowInterviewState` | String | State of the flow interview. | Small, 57.0 | 57.0 |
| `invitationId` | String | ID of the survey invitation that's related to the request. | Small, 57.0 | 57.0 |
| `languageCode` | String | Code of the language that the survey is created in. | Small, 56.0 | 56.0 |

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `navigationActions` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Go to the previous survey page.<br>• `Next`—Go to the next survey page. | Small, 57.0 | 57.0 |
| `responseId` | String | ID of the survey response. | Small, 57.0 | 57.0 |
| `status` | String | Status of the API request.<br>Possible values are:<br>• `Failure`—Survey Response API isn't successfully run.<br>• `Success`—Survey Response API is successfully run. | Small, 56.0 | 56.0 |
| `surveyPage` | Survey Question Page Output<br>OR<br>Survey Thank You Page Output | Details of the question or the Thank You page. | Small, 56.0 | 56.0 |

## Survey Selection Question Choice Output

The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `label` | String | The label of a choice for a Boolean, rating, single selection, or multiple selection question in a survey. | Small, 56.0 | 56.0 |
| `name` | String | The name of a choice for a Boolean, rating, single selection, or multiple selection question in a survey. | Small, 56.0 | 56.0 |

## Survey Selection Question Output

Output representation of the details of the boolean, rating, single-selection, or multiple-selection question on the survey page.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `description` | String | Description for the survey question. | Small, 56.0 | 56.0 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory. | Small, 56.0 | 56.0 |
| `label` | String | Label of the survey question. | Small, 56.0 | 56.0 |
| `maxChoicesAllowed` | Integer | Maximum number of choices for a multiple-choice question. | Small, 65.0 | 65.0 |
| `name` | String | API name of the survey question. | Small, 56.0 | 56.0 |
| `questionChoices` | Survey Selection Question Choice Output[] | Choices that are available for a boolean, rating, single-selection, or multiple-selection question in a survey. | Small, 56.0 | 56.0 |
| `questionType` | String | Type of survey question. | Small, 56.0 | 56.0 |
| `responseDataType` | String | Data type of the survey question. | Small, 56.0 | 56.0 |
| `responseValues` | String[] | List of survey response values for a selected question. | Small, 57.0 | 57.0 |

## Survey Short-Text Question Output

Output representation of the details of the short-text question on the survey page.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `description` | String | Description for the survey question. | Small, 56.0 | 56.0 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory (`true`) or not (`false`). | Small, 56.0 | 56.0 |
| `label` | String | Label of the survey question. | Small, 56.0 | 56.0 |
| `name` | String | API name of the survey question. | Small, 56.0 | 56.0 |
| `questionType` | String | Type of survey question. | Small, 56.0 | 56.0 |
| `responseDataType` | String | Data type of the survey question. | Small, 56.0 | 56.0 |
| `responseValue` | String | Value of the response to a short-text question in a survey. | Small, 57.0 | 57.0 |
| `validationFormula` | String | Validation regex for the short text question. | Small, 56.0 | 56.0 |

## Survey Text Question Output

Output representation of the details of the text question on the survey page.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `description` | String | Description for the survey question. | Small, 56.0 | 56.0 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory (`true`) or not (`false`). | Small, 56.0 | 56.0 |
| `label` | String | Label of the survey question. | Small, 56.0 | 56.0 |
| `name` | String | API name of the survey question. | Small, 56.0 | 56.0 |
| `questionType` | String | Type of survey question. | Small, 56.0 | 56.0 |
| `responseDataType` | String | Data type of the survey question. | Small, 56.0 | 56.0 |
| `responseValue` | String | Value of the response to a long-text question in a survey. | Small, 57.0 | 57.0 |

## Survey Thank You Page Output

Output representation of the details of the Thank You page in the survey.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `label` | String | The label of the survey page. | Small, 56.0 | 56.0 |
| `messageDescription` | String | The description for a message on the Thank You page in the survey. | Small, 56.0 | 56.0 |
| `name` | String | The API name of the survey page. | Small, 56.0 | 56.0 |
| `redirectUrl` | String | The URL that respondents are automatically redirected to after completing the survey. | Small, 56.0 | 56.0 |
| `thankYouMessage` | String | The thank you message of the Thank You page in the survey. | Small, 56.0 | 56.0 |
| `urlButtons` | Survey URL Buttons Output[] | The buttons on the Thank You page which respondents select to navigate to URLs. | Small, 56.0 | 56.0 |

## Survey URL Buttons Output

Output representation of the details of the URL buttons on the Thank You page in the survey.

| Property Name | Type | Description | Filter Group and Version | Available Version |
|---|---|---|---|---|
| `label` | String | The label specified for a button on the Thank You page. | Small, 56.0 | 56.0 |
| `url` | String | The URL specified for a button on the Thank You page. | Small, 56.0 | 56.0 |

# Surveys for Unauthenticated Participants

Use Salesforce Feedback Management (SFM) unAuth Response APIs to create survey invitations and to enable survey responses from unauthenticated participants.

For unauthenticated survey participation, the recipient must be a Contact or a Lead.

Set Up Your Environment

Get your Salesforce environment ready before you create a survey invitation by using the Salesforce Feedback Management (SFM) unAuth Response APIs.

Access Token

Create an access token to enable survey invitation creation, and gather feedback from unauthenticated participants.

Resources

Use the developer resources for the Salesforce Feedback Management (SFM) unAuth Response APIs to create survey invitation, enable survey responses, and gather feedback from unauthenticated participants.

Request Bodies

Get to know the request bodies for the Salesforce Feedback Management (SFM) unAuth Response APIs.

Response Bodies

Get to know the response bodies for the Salesforce Feedback Management (SFM) unAuth Response APIs.

Error Code Details

Get to know the error codes and messages for the Salesforce Feedback Management (SFM) unAuth Response APIs.

# Set Up Your Environment

Get your Salesforce environment ready before you create a survey invitation by using the Salesforce Feedback Management (SFM) unAuth Response APIs.

1. From Setup, in the Quick Find box, enter *Survey*, and then select **Survey Settings**.
2. Turn on Unauthenticated Survey Participation.
3. To create surveys that are available to external unauthenticated participants, select an Experience Cloud site by clicking your site name.
4. Get the My Domain URL that's used to invoke the SFM unAuth Response APIs for your org. The format is `https://`***`OmniChannelEngagementURL`***`/`***`AppPrefix`***
   a. From Setup, in the Quick Find box, enter *My Domain*, and then select **My Domain**.
   b. Find your org's My Domain URL in the Current My Domain URL field.
   c. To get your org's Omni-Channel Engagement URL, append `-scrt` to the My Domain login URL before `.com`.
   For example, if the My Domain URL is `https://exampleCompany.my.salesforce.com`, then the Omni-Channel Engagement URL is `https://exampleCompany.my.salesforce-scrt.com`.
   d. To get the full URL, append the app prefix `surveys/v1` to the Omni-Channel Engagement URL.
   For example, if the Omni-Channel Engagement URL is `https://exampleCompany.my.salesforce-scrt.com`, then the full URL to invoke the SFM unAuth Response APIs is `https://exampleCompany.my.salesforce-scrt.com/surveys/v1`.

EDITIONS

Available in: Salesforce Classic (not available in all orgs) and Lightning Experience with Surveys enabled

Available in: **Developer**, **Enterprise**, and **Unlimited** Editions

Available with the Feedback Management - Growth license

USER PERMISSIONS

To create a basic survey:
- Permissions to create surveys

SEE ALSO:

Salesforce Help: Enable Surveys and Configure Survey Settings

Salesforce Help: Feedback Management Licenses

# Access Token

Create an access token to enable survey invitation creation, and gather feedback from unauthenticated participants.

**Resource**

```
/<MyDomainURL>/<AppPrefix>/accessToken
```

**Example**

```
https://yourInstance.salesforce-scrt.com/surveys/v1/accessToken
```

**HTTP methods**

POST

**Request body for POST**

Pass the 18 digit `orgId` in the request. Make a `Query()` request on the Organization object to fetch the organization ID. See Execute a SOQL Query.

```
{
"orgId": "00DSB00000026pJ2AQ"
}
```

**Response body for POST**

**JSON example**

```
{
    "accessToken": "eyJraWQiOiIwM2ZiN......-UA",
    "expiresIn": 3600,
    "tokenType": "Bearer"
}
```

# Resources

Use the developer resources for the Salesforce Feedback Management (SFM) unAuth Response APIs to create survey invitation, enable survey responses, and gather feedback from unauthenticated participants.

Note: Salesforce Feedback Management Business API performance can be impacted if a POST request exceeds 3600 calls per minute and if a PATCH request exceeds 1800 calls per minute at the organization level.

Survey Responses Using Invitation Configurations (POST, PATCH)

Create responses using the invitation configuration details and initiate the process of submitting the survey responses by making a POST request. Submit the survey responses using the PATCH request.

## Survey Responses Using Invitation Configurations (POST, PATCH)

Create responses using the invitation configuration details and initiate the process of submitting the survey responses by making a POST request. Submit the survey responses using the PATCH request.

Note: Salesforce Feedback Management Business API performance can be impacted if a POST request exceeds 3600 calls per minute and if a PATCH request exceeds 1800 calls per minute at the organization level.

You can create a survey to collect data from customers, employees, or other people whose feedback you need. The survey responses are stored in the SurveyResponse object and the responses to individual questions in the SurveyQuestionResponse object.

**Resource**

```
/<MyDomainURL>/<AppPrefix>/survey-response
```

**Example**

```
https://yourInstance.salesforce-scrt.com/surveys/v1/survey-response
```

**Available version**

v1

**Requires Chatter**

No

### HTTP methods

PATCH, POST

Note: The HTTP header request format only accepts `Content-Type: application/json`.

### Special Access Rules

The Feedback Management - Growth license is required to use this resource.

Note: Ensure the survey is shared to the guest profile from Sharing Settings in Salesforce Setup.

### Authorization

Use the bearer token from the accessToken request.

```
Authorization: Bearer <accessToken>
```

### Merge fields setup

To use the participant or associated record merge fields, ensure these prerequisites are met.

- Access level for merge fields is set to System Context - Enforce record-level access. See Select the Access Level for Merge Fields.
- Share the records used in merge fields to the guest profile from Sharing Settings in Salesforce Setup.

### Request body for POST

#### JSON example

```
{
    "languageCode": "en",
    "surveyDeveloperName": "sample_survey",
    "invitationSettings" : {
      "recipientId": "003RM000008DecmYAC",
      "collectAnonymousResponse" : false,
      "invitationExpirationDate":"2023-07-31T21:32:54Z"
    }
}
```

#### Properties

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `invitationSettings` | Survey Invitation Settings Input | Invitation settings of the survey. | Required | v1 |
| `languageCode` | String | Code of the language to get the survey page or question details.<br>Note: Ensure the survey is shared to the participant in this specified language. | Optional | v1 |
| `surveyDeveloperName` | String | Name of the survey. | Required | v1 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `recipientEngagementContext` | Map<String, String> | Engagement context settings for a recipient of the survey. | Optional | v1 |
| `relatedRecordIds` | String[] | IDs of the records that are related to the survey. | Optional | v1 |
| `staticMergeFields` | Map<String, String> | Map of static merge field values. | Optional | v1 |

### Response body for POST

Survey Description Output

### Request body for PATCH

#### JSON example

Here's an example for a single question.

```
{
 "invitationId": "0Kixx0000004MWaCAM",
 "invitationUuid": "11845-39854594-3438",
 "surveyDeveloperName": "sample_survey",
 "languageCode": "en",
 "flowInterviewState" : "state1",
 "navigationAction" : "Next",
 "surveyPageResponses" : {
        "name" :  "p_ff794819_c0f0_4e0d_b357_29ca1694cfc4",
        "questionResponses" : [
            {
                "name": "q_113419b1_5d29_4bb9_8b10_e3fe324ae040",
                "questionType" : "MultiChoice",
                "responses" : [{"name" : "c_9775c2e5_9086_44a8_a5c9_89fdc886c99a"},

                                {"name" : "c_0f1f63cc_608a_4560_9d29_72b203f195f2"}]

            }
         ]
   }
}
```

#### Properties

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `flowInterviewState` | String | State of the flow interview. | Required | v1 |
| `invitationId` | String | ID of the survey invitation. | Required | v1 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `invitationUuid` | String | Random ID of the survey invitation that's generated for enhanced security. | Required | v1 |
| `languageCode` | String | Code of the language to get the survey page or question details.<br>Note: Ensure the survey is shared to the participant in this specified language. | Optional | v1 |
| `navigationAction` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Navigate to the previous survey page.<br>• `Next`—Navigate to the next survey page. | Required | v1 |
| `surveyDeveloperName` | String | Name of the survey. | Required | v1 |
| `surveyPageResponses` | Survey Page Response Input | Responses to the survey questions on a page. | Required | v1 |

**Response body for PATCH**

Survey Response Output

SEE ALSO:

Salesforce Help: Assign Permissions to Guest Users to Respond to Surveys

# Request Bodies

Get to know the request bodies for the Salesforce Feedback Management (SFM) unAuth Response APIs.

Survey Description Input

Input representation of the details of the survey recipient and their engagement context, the language, related records, and invitation settings of the survey.

Survey Integer Question Response Input

Input representation of the details of the response to an NPS question on the survey page.

Survey Invitation Settings Input

Input representation of the settings of the survey invitation that define the participants who can respond to the survey, its expiration, and other related configurations.

Survey Page Response Input

Input representation of the details of the response to a survey page.

Survey Question Response Input

Input representation of the details of the response to a question on the survey page.

Survey Response Input

Input representation of the details of a survey response.

Survey Selection Question Choice Input

The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

Survey Selection Question Response Input

Input representation of the details of the response to a boolean, rating, single selection, or a multiple selection question on the survey page.

Survey Text Question Response Input

The details of the response to a short-text or a long-text question on the survey page.

## Survey Description Input

Input representation of the details of the survey recipient and their engagement context, the language, related records, and invitation settings of the survey.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `invitationSettings` | Survey Invitation Settings Input | Invitation settings of the survey. | Required | v1 |
| `languageCode` | String | Code of the language to get the survey page or question details.<br>Note: Ensure the survey is shared to the participant in this specified language. | Optional | v1 |
| `surveyDeveloperName` | String | Name of the survey. | Required | v1 |
| `recipientEngagementContext` | Map<String, String> | Engagement context settings for a recipient of the survey. | Optional | v1 |
| `relatedRecordIds` | String[] | IDs of the records that are related to the survey. | Optional | v1 |
| `staticMergeFields` | Map<String, String> | Map of static merge field values. | Optional | v1 |

## Survey Integer Question Response Input

Input representation of the details of the response to an NPS question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | v1 |
| `questionType` | String | The type of survey question. | Required | v1 |
| `responseValue` | Integer | The value of a response to an NPS question in a survey. | Required | v1 |

## Survey Invitation Settings Input

Input representation of the settings of the survey invitation that define the participants who can respond to the survey, its expiration, and other related configurations.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `collectAnonymousResponse` | Boolean | Indicates whether participants can take the survey without revealing their name or other identifying information (`true`) or not (`false`). | Required | v1 |
| `invitationExpirationDate` | String | The date in ISO 8601 format when the survey invitation expires. | Optional | v1 |
| `recipientId` | String | The ID of the survey recipient.<br>Note: For unauthenticated survey participation, the recipient must be a Contact or a Lead. | Optional | v1 |

## Survey Page Response Input

Input representation of the details of the response to a survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of the survey page.<br>Note: Reserved for future use. | Optional | v1 |

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `questionResponses` | Various | The responses to the survey questions on the page.<br>• NPS Question Type—See Survey Integer Question Response Input.<br>• Selection Question Type—See Survey Selection Question Response Input.<br>• Short Text or Long Text Question Type—See Survey Text Question Response Input.<br>• Other Question Type—See Survey Question Response Input. | Required | v1 |

## Survey Question Response Input

Input representation of the details of the response to a question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | v1 |
| `questionType` | String | The type of survey question. | Required | v1 |

## Survey Response Input

Input representation of the details of a survey response.

**JSON example**

Here's an example for a single question.

```
{
 "invitationId": "0Kixx0000004MWaCAM",
 "invitationUuid": "11845-39854594-3438",
 "surveyDeveloperName": "sample_survey",
 "languageCode": "en",
 "flowInterviewState" : "state1",
 "navigationAction" : "Next",
 "surveyPageResponses" : {
        "name" :  "p_ff794819_c0f0_4e0d_b357_29ca1694cfc4",
        "questionResponses" : [
            {
                "name": "q_113419b1_5d29_4bb9_8b10_e3fe324ae040",
                "questionType" : "MultiChoice",
                "responses" : [{"name" : "c_9775c2e5_9086_44a8_a5c9_89fdc886c99a"},
                               {"name" : "c_0f1f63cc_608a_4560_9d29_72b203f195f2"}]
```

```
            }
        ]
    }
}
```

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `flowInterviewState` | String | State of the flow interview. | Required | v1 |
| `invitationId` | String | ID of the survey invitation. | Required | v1 |
| `invitationUuid` | String | Random ID of the survey invitation that's generated for enhanced security. | Required | v1 |
| `languageCode` | String | Code of the language to get the survey page or question details.<br>Note: Ensure the survey is shared to the participant in this specified language. | Optional | v1 |
| `navigationAction` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Navigate to the previous survey page.<br>• `Next`—Navigate to the next survey page. | Required | v1 |
| `surveyDeveloperName` | String | Name of the survey. | Required | v1 |
| `surveyPageResponses` | Survey Page Response Input | Responses to the survey questions on a page. | Required | v1 |

## Survey Selection Question Choice Input

The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of selected choice to a Boolean, rating, single selection, or multiple selection question in a survey. | Required | v1 |

## Survey Selection Question Response Input

Input representation of the details of the response to a boolean, rating, single selection, or a multiple selection question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | v1 |
| `questionType` | String | The type of survey question. | Required | v1 |
| `responses` | Survey Selection Question Choice Input[] | The responses to a Boolean, rating, single selection, or multiple selection question in a survey. | Required | v1 |

## Survey Text Question Response Input

The details of the response to a short-text or a long-text question on the survey page.

**Properties**

| Name | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `name` | String | The API name of survey question. | Required | v1 |
| `questionType` | String | The type of survey question. | Required | v1 |
| `responseValue` | String | The value of a response to a short-text or long-text question in a survey. | Required | v1 |

# Response Bodies

Get to know the response bodies for the Salesforce Feedback Management (SFM) unAuth Response APIs.

Survey Description Output
Output representation of the response to the Start Survey request.

Survey Detail Output
Output representation of the details of the survey.

Survey NPS Question Output
Output representation of the details of the NPS question on the survey page.

Survey Question Output
Output representation of the details of the question on the survey page.

Survey Question Page Output
The details of the question page in the survey.

Survey Response Output

Output representation of the response to the Submit Survey request. The response includes the status of the survey unAuth response API and the Thank You page details in the survey.

Survey Selection Question Choice Output

The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

Survey Selection Question Output

Output representation of the details of the boolean, rating, single-selection, or multiple-selection question on the survey page.

Survey Short-Text Question Output

Output representation of the details of the short-text question on the survey page.

Survey Text Question Output

Output representation of the details of the text question on the survey page.

Survey Thank You Page Output

Output representation of the details of the Thank You page in the survey.

Survey URL Buttons Output

Output representation of the details of the URL buttons on the Thank You page in the survey.

## Survey Description Output

Output representation of the response to the Start Survey request.

**JSON example**

```
{
  "languageCode": "en",
  "invitationId": "0Kixx0000004MWaCAM",
  "invitationUuid": "11845-39854594-3439",
  "flowInterviewState": "state1",
  "status": "Success",
  "surveyDetail": {
    "label": "Survey01",
    "name": "Survey01",
    "surveyPage": {
      "label": "Page 1",
      "name": "p_d84afb73_3a30_4a3f_aae7_b0478b3bb4ed",
      "surveyQuestions": [
        {
          "name": "q_856a997e_be2c_4ea3_b70d_7f6fb9cfbf4f",
          "label": "Good so Far !",
          "questionType": "ShortText",
          "responseDataType": "STRING",
          "isResponseRequired": false
        }
      ]
    }
  },
  "navigationActions": [
    "Next"
  ],
  "responseId": "0Myxx0000004CYqCAM",
  "errors": [],
```

```
  "warnings": []
}
```

**Properties**

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `errors` | String[] | Error messages for a failed request. | v1 |
| `flowInterviewState` | String | State of the flow interview. | v1 |
| `invitationId` | String | ID of the survey invitation that's related to the request. | v1 |
| `invitationUuid` | String | Random ID of the survey invitation that's generated for enhanced security. | v1 |
| `languageCode` | String | Code of the language to get the survey page or question details. | v1 |
| `navigationActions` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Go to the previous survey page.<br>• `Next`—Go to the next survey page. | v1 |
| `responseId` | String | ID of the survey response. | v1 |
| `status` | String | Status of the API request.<br>Possible values are:<br>• `Failure`—Survey unAuth Response API isn't successfully run.<br>• `Success`—Survey unAuth Response API is successfully run. | v1 |
| `surveyDetail` | Survey Detail Output | All details of the page in the survey. | v1 |
| `warnings` | String[] | Warnings for a request. | v1 |

## Survey Detail Output

Output representation of the details of the survey.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `label` | String | The label of the survey. | v1 |
| `name` | String | The API name of the survey. | v1 |

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `surveyPage` | Survey Question Page Output<br>OR<br>Survey Thank You Page Output | The details of the question or thank you page in the survey. | v1 |
| `versionLabel` | String | The label of the survey version. | v1 |
| `versionNumber` | Integer | The version number of the survey. | v1 |

## Survey NPS Question Output

Output representation of the details of the NPS question on the survey page.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `description` | String | Description for the survey question. | v1 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory. | v1 |
| `label` | String | Label of the survey question. | v1 |
| `maxScale` | Integer | Maximum score that participants can select for an NPS question in the survey. | v1 |
| `minScale` | Integer | Minimum score that participants can select for an NPS question in the survey. | v1 |
| `name` | String | API name of the survey question. | v1 |
| `questionType` | String | Type of survey question. | v1 |
| `responseDataType` | String | Data type of the survey question. | v1 |
| `responseValue` | Integer | Value of the response to an NPS question in a survey. | v1 |

## Survey Question Output

Output representation of the details of the question on the survey page.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `description` | String | The description for the survey question. | v1 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory (`true`) or not (`false`). | v1 |
| `label` | String | The label of the survey question. | v1 |
| `name` | String | The API name of the survey question. | v1 |

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `questionType` | String | The type of survey question. | v1 |
| `responseDataType` | String | The data type of the survey question. | v1 |

## Survey Question Page Output

The details of the question page in the survey.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `label` | String | The label of the survey page. | v1 |
| `name` | String | The API name of the survey page. | v1 |
| `surveyQuestions` | NPS Question Type<br>Selection Question Type<br>ShortText Question Type<br>Text Question Type<br>Other Question Type | List of survey questions. | v1 |

## Survey Response Output

Output representation of the response to the Submit Survey request. The response includes the status of the survey unAuth response API and the Thank You page details in the survey.

**JSON example**

```
{
    "languageCode": "en",
    "invitationId": "0Kixx0000004MWaCAM",
    "invitationUuid": "11845-39854594-3438",
    "flowInterviewState": "state1",
    "status": "Success",
    "surveyPage": {
        "label": "Page 2",
        "name": "p_d84afb73_3a30_4a3f_aae7_b0478b3bb4ed",
        "surveyQuestions": [
            {
                "name": "q_856a997e_be2c_4ea3_b70d_7f6fb9cfbf4f",
                "label": "Good so Far !",
                "questionType": "ShortText",
                "responseDataType": "STRING",
                "isResponseRequired": false
            }
        ]
    },
    "navigationActions": [
        "Next",
```

```
        "Back"
    ],
  "responseId": "0Myxx0000004CYqCAM",
    "errors": []
}
```

**Properties**

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `errors` | String[] | Error messages for a failed request. | v1 |
| `flowInterviewState` | String | State of the flow interview. | v1 |
| `invitationId` | String | ID of the survey invitation that's related to the request. | v1 |
| `invitationUuid` | String | Random ID of the survey invitation that's generated for enhanced security. | v1 |
| `languageCode` | String | Code of the language to get the survey page or question details. | v1 |
| `navigationActions` | String | Available navigation actions on the survey page.<br>Possible values are:<br>• `Back`—Go to the previous survey page.<br>• `Next`—Go to the next survey page. | v1 |
| `responseId` | String | ID of the survey response. | v1 |
| `status` | String | Status of the API request.<br>Possible values are:<br>• `Failure`—Survey unAuth Response API isn't successfully run.<br>• `Success`—Survey unAuth Response API is successfully run. | v1 |
| `surveyPage` | Survey Question Page Output<br>OR<br>Survey Thank You Page Output | Details of the question or the Thank You page. | v1 |

## Survey Selection Question Choice Output

The details of a boolean, rating, single selection, or a multiple selection question's choice on the survey page.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `label` | String | The label of a choice for a Boolean, rating, single selection, or multiple selection question in a survey. | v1 |
| `name` | String | The name of a choice for a Boolean, rating, single selection, or multiple selection question in a survey. | v1 |

## Survey Selection Question Output

Output representation of the details of the boolean, rating, single-selection, or multiple-selection question on the survey page.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `description` | String | Description for the survey question. | v1 |
| `isResponse Required` | Boolean | Indicates whether the response to the question is mandatory. | v1 |
| `label` | String | Label of the survey question. | v1 |
| `name` | String | API name of the survey question. | v1 |
| `questionChoices` | Survey Selection Question Choice Output[] | Choices that are available for a boolean, rating, single-selection, or multiple-selection question in a survey. | v1 |
| `questionType` | String | Type of survey question. | v1 |
| `responseDataType` | String | Data type of the survey question. | v1 |
| `responseValues` | String[] | List of survey response values for a selected question. | v1 |

## Survey Short-Text Question Output

Output representation of the details of the short-text question on the survey page.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `description` | String | Description for the survey question. | v1 |
| `isResponse Required` | Boolean | Indicates whether the response to the question is mandatory (`true`) or not (`false`). | v1 |
| `label` | String | Label of the survey question. | v1 |
| `name` | String | API name of the survey question. | v1 |
| `questionType` | String | Type of survey question. | v1 |
| `responseDataType` | String | Data type of the survey question. | v1 |
| `responseValue` | String | Value of the response to a short-text question in a survey. | v1 |

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `validationFormula` | String | Validation regex for the short text question. | v1 |

## Survey Text Question Output

Output representation of the details of the text question on the survey page.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `description` | String | Description for the survey question. | v1 |
| `isResponseRequired` | Boolean | Indicates whether the response to the question is mandatory (`true`) or not (`false`). | v1 |
| `label` | String | Label of the survey question. | v1 |
| `name` | String | API name of the survey question. | v1 |
| `questionType` | String | Type of survey question. | v1 |
| `responseDataType` | String | Data type of the survey question. | v1 |
| `responseValue` | String | Value of the response to a long-text question in a survey. | v1 |

## Survey Thank You Page Output

Output representation of the details of the Thank You page in the survey.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `label` | String | The label of the survey page. | v1 |
| `messageDescription` | String | The description for a message on the Thank You page in the survey. | v1 |
| `name` | String | The API name of the survey page. | v1 |
| `redirectUrl` | String | The URL that respondents are automatically redirected to after completing the survey. | v1 |
| `thankYouMessage` | String | The thank you message of the Thank You page in the survey. | v1 |
| `urlButtons` | Survey URL Buttons Output[] | The buttons on the Thank You page which respondents select to navigate to URLs. | v1 |

## Survey URL Buttons Output

Output representation of the details of the URL buttons on the Thank You page in the survey.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `label` | String | The label specified for a button on the Thank You page. | v1 |
| `url` | String | The URL specified for a button on the Thank You page. | v1 |

# Error Code Details

Get to know the error codes and messages for the Salesforce Feedback Management (SFM) unAuth Response APIs.

accessToken
Listed are the error codes and error code messages associated with the Salesforce Feedback Management (SFM) UnAuth Response APIs for the `accessToken` resource.

survey-response (PATCH)
Listed are the error codes and error code messages associated with the Salesforce Feedback Management (SFM) unAuth Response APIs for the `survey-response` PATCH resource.

survey-response (POST)
Listed are the error codes and error code messages associated with the Salesforce Feedback Management (SFM) unAuth Response APIs for the `survey-response` (POST) resource.

## `accessToken`

Listed are the error codes and error code messages associated with the Salesforce Feedback Management (SFM) UnAuth Response APIs for the `accessToken` resource.

### Error Codes and Responses for the `accessToken` Resource

This table lists the HTTP response code descriptions that are unique to this resource.

| HTTP Response Code | Error Code | Description |
|---|---|---|
| 400 | `INVALID_API_INPUT` | {orgId} isn't valid. Specify a valid orgId value and try again. |
| 400 | `INVALID_API_INPUT` | You can't access the specified org. Specify a different orgId value and try again. |
| 400 | `API_CURRENTLY_DISABLED` | The UnauthenticatedSurveyParticipation API isn't enabled in your Salesforce org. Ask your Salesforce admin for help. |

## `survey-response` (PATCH)

Listed are the error codes and error code messages associated with the Salesforce Feedback Management (SFM) unAuth Response APIs for the `survey-response` PATCH resource.

### Error Codes and Responses for the `survey-response` PATCH Resource

This table lists the HTTP response code descriptions that are unique to this resource.

| HTTP Response Code | Error Code | Description |
|---|---|---|
| 400 | `API_CURRENTLY_DISABLED` | The UnauthenticatedSurveyParticipation API setting isn't enabled in your Salesforce org. Ask your Salesforce admin for help. |
| 400 | `API_CURRENTLY_DISABLED` | Your Salesforce org doesn't have a default Experience Cloud site. Select the default Experience Cloud site from the Survey Settings page in Salesforce, or contact your Salesforce admin. |
| 400 | `MISSING_RECORD` | Specify an existing survey, or ensure that the survey is shared with a guest user, and try again. |
| 400 | `INVALID_API_INPUT` | Specify a valid invitation configuration, and try again. |
| 400 | `INVALID_API_INPUT` | We couldn't process the request. Specify valid inputs, and try again. |
| 401 | `UNAUTHORIZED` | The access token has expired or isn't authorized to access the SFM unAuth Response APIs. |
| 500 | `UNKOWN_EXCEPTION` | We couldn't process the request because of an internal server error. Contact your Salesforce admin. |

## `survey-response` (POST)

Listed are the error codes and error code messages associated with the Salesforce Feedback Management (SFM) unAuth Response APIs for the `survey-response` (POST) resource.

### Error Codes and Responses for the `survey-response` POST Resource

This table lists the HTTP response code descriptions that are unique to this resource.

| HTTP Response Code | Error Code | Description |
|---|---|---|
| 400 | `INVALID_API_INPUT` | {recipientID} is invalid. Specify a recipientId of the type lead or contact, and try again. |
| 400 | `API_CURRENTLY_DISABLED` | The UnauthenticatedSurveyParticipation API isn't enabled in your Salesforce org. Ask your Salesforce admin for help. |
| 400 | `API_CURRENTLY_DISABLED` | Your Salesforce org doesn't have a default Experience Cloud site. Select the default Experience Cloud site from the Survey Settings page in Salesforce, or contact your Salesforce admin. |
| 400 | `MISSING_RECORD` | Specify an existing survey, or ensure that the survey is shared with a guest user, and try again. |
| 400 | `INVALID_INPUT_COMBINATION` | Specify a basic survey, and try again. |
| 400 | `INVALID_API_INPUT` | Either activate the specified survey, or specify an active survey, and try again. |

| HTTP Response Code | Error Code | Description |
|---|---|---|
| 400 | INVALID_API_INPUT | The specified merge field access level isn't supported. Specify a different merge field access level, and try again. |
| 400 | INVALID_API_INPUT | We couldn't process the request. Specify valid inputs, and try again. |
| 400 | MISSING_ARGUMENT | The collectAnonymousResponse property is a required property. Specify the collectAnonymousResponse property, and try again. |
| 400 | MISSING_RECORD | The recipient ID provided in the survey doesn't exist in your org. {recipientId} or the related record isn't shared with you. |
| 401 | UNAUTHORIZED | The access token has expired or isn't authorized to access the SFM unAuth Response APIs. |
| 500 | UNKOWN_EXCEPTION | We couldn't process the request because of an internal server error. Contact your Salesforce admin. |

# CHAPTER 6 Salesforce Surveys Apex Classes

In this chapter ...


- sfdc_surveys Namespace
- ConnectApi Namespace
- industriesNlpSvc


Salesforce Surveys provides the `ConnectApi` namespace (also called Connect in Apex) and `sfdc_surveys` namespace that contains classes for creating and sending survey invitations.

# sfdc_surveys Namespace

The `sfdc_surveys` namespace provides an interface for shortening survey invitations.

The following are the classes in the `sfdc_surveys` namespace.

SurveyInvitationLinkShortener Interface
Use this interface to provide a class factory that Salesforce can call to create instances of your custom `SurveyInvitationLinkShortener`.

Example Implementation to Associate SurveySubjects with SurveyInvitation and SurveyResponses
If no survey responses are populated, create a custom code to associate SurveySubjects with SurveyInvitation and SurveyResponses.

## SurveyInvitationLinkShortener Interface

Use this interface to provide a class factory that Salesforce can call to create instances of your custom `SurveyInvitationLinkShortener`.

### Namespace

sfdc_surveys

### Usage

Implement an instance of the `SurveyInvitationLinkShortener` interface to shorten the survey invitation that can be distributed as short URLs over customer engaged channels, such as SMS, WhatsApp, or Facebook Messenger.

### Special access rules

To implement this interface, you must have the Salesforce Feedback Management license enabled in your Salesforce organization.

SurveyInvitationLinkShortener Methods

SurveyInvitationLinkShortener Example Implementation

### SurveyInvitationLinkShortener Methods

The following are methods for `SurveyInvitationLinkShortener`.

getShortenedURL(var1)
Returns a shortened URL for a given survey invitation.

#### `getShortenedURL(var1)`

Returns a shortened URL for a given survey invitation.

### Signature

```
public String getShortenedURL(String var1)
```

### Parameters

*var1*
Type: String

### Return Value

Type: String

## SurveyInvitationLinkShortener Example Implementation

This is an example implementation of the `sfdc_surveys.SurveyInvitationLinkShortener` interface.

This sample code uses Named Credentials for authentication. For more information on Named Credentials, see Named Credentials as Callout Endpoints.

```
public class SurveyInvitationLinkShortenerImpl implements
sfdc_surveys.SurveyInvitationLinkShortener {
   public String getShortenedURL(String invitationURL) {
      return shortenUrlUsingBitlyService(invitationURL);
   }
   public String shortenUrlUsingBitlyService(String invitationURL) {
      HttpRequest request = new HttpRequest();
      request.setEndpoint('callout:bitly/v4/shorten');
      request.setMethod('POST');
      request.setHeader('Authorization', 'Bearer {!$Credential.Password}');
      request.setHeader('Accept', 'application/json');
      request.setHeader('Content-Type', 'application/json');
      request.setBody(JSON.serialize(new Map<String, Object>{
      'group_guid' => '{!$Credential.UserName}',
      'long_url' => invitationURL
      }));

      Http http = new Http();
      HttpResponse res = http.send(request);

      Object result = JSON.deserializeUntyped(res.getBody());
      if (result instanceof Map<String, Object>) {
         Map<String, Object> resultMap = (Map<String, Object>) result;
         Object shortenedLinkVal = resultMap.get('link');
         if(shortenedLinkVal != null && shortenedLinkVal instanceof String) {
            return (String) shortenedLinkVal;
         }
      }
      return invitationURL;
   }
}
```

# Example Implementation to Associate SurveySubjects with SurveyInvitation and SurveyResponses

If no survey responses are populated, create a custom code to associate SurveySubjects with SurveyInvitation and SurveyResponses.

This example shows how to associate SurveySubjects with SurveyInvitation and SurveyResponses.

```
public class CreateEntriesInSurveyInvitationRespRL {
    // Utility to create SurveyInvitation and SurveySubject record
    public static void addEntry(String associatedRecordId, String surveyId, String
participantId) {
        String invitationId = createSurveyInvitation(surveyId, participantId);

        createSurveySubject(invitationId, associatedRecordId);
    }

    // Create an unauthenticated invitation by setting the surveyId and participantId
    private static String createSurveyInvitation(String surveyId, String participantId) {

        SurveyInvitation surveyInv = new SurveyInvitation();
        surveyInv.Name = 'SurveyInvitationForCase'; // add your survey invitation name
here
        surveyInv.ParticipantId = participantId;
        surveyInv.CommunityId = '0DBRM0000004n4y'; //add your community id here
        surveyInv.OptionsAllowGuestUserResponse = true;
        surveyInv.SurveyId = surveyId;

        // Insert the SurveyInvitation Record
        insert surveyInv;

        return surveyInv.Id;
    }

    // Associate the above invitation to the required record (eg: Case, Opportunity...)
   private static void createSurveySubject(String invitationId, String associatedRecordId)
 {
        SurveySubject subj = new SurveySubject();
        subj.Name = 'Sur_Subject_for_invitation';
       subj.ParentId = invitationId; // similary you can use survey response id to associate
 survey subject to a response record.
        subj.SubjectId = associatedRecordId;

        // Insert the SurveySubject Record
        insert subj;
    }
}



//Use this trigger to create a survey subject record associated to
//the Survey Response record

trigger SurveyResponseForCaseTrigger on SurveyResponse (after insert) {
```

```
    System.debug('Inside Survey response trigger ');
     for(SurveyResponse sr: Trigger.New)
    {
      SurveySubject subj = new SurveySubject();
        subj.Name = 'Sur_Subject_for_response';
        subj.ParentId = sr.id; //Associating survey response id

       //Get the associatedRecordId recordId (like Case, Opportunity etc) using the
SurveyInvitation Id and
       //assigning it to SubjectId, assuming we inserted SurveySubject record for the
associated invitation
       //using the previous code

       List<SurveySubject> SurSubj=[select subjectid from SurveySubject where parentid =
:sr.invitationId];
        for(SurveySubject sub:SurSubj){
            String ids=String.valueOf(sub.subjectid).substring(0,3);
            if('500'.equals(ids)){

                subj.SubjectId =sub.subjectid;
        // Insert the SurveySubject Record
            insert subj;
                break;

            }

}
```

# `ConnectApi` Namespace

The `ConnectApi` namespace (also called Connect in Apex) provides classes for creating surveys.

The following are the classes and the interface in the `ConnectApi` namespace.

Surveys Class
Send survey invitations by email.

ConnectApi Input Classes
Some `ConnectApi` methods take arguments that are instances of `ConnectApi` input classes.

ConnectApi Output Classes
Most `ConnectApi` methods return instances of `ConnectApi` output classes.

## Surveys Class

Send survey invitations by email.

### Namespace

ConnectApi

## Surveys Methods

These methods are for `Surveys`. All methods are static.

sendSurveyInvitationEmail(surveyID, SurveyEmailInput)
Email survey invitations to up to 300 participants. You can email either leads, contacts, or users in your org. Either a link to launch the survey or a question can be embedded in the email invitations.

### `sendSurveyInvitationEmail(surveyID, SurveyEmailInput)`

Email survey invitations to up to 300 participants. You can email either leads, contacts, or users in your org. Either a link to launch the survey or a question can be embedded in the email invitations.

#### API Version

50.0

#### Requires Chatter

No

#### Signature

```
public static ConnectApi.SurveyInvitationEmailOutput sendSurveyInvitationEmail(String surveyID, ConnectApi.SurveyInvitationEmailInput SurveyEmailInput)
```

#### Parameters

*`surveyID`*
Type: String

ID of the survey.

*`SurveyEmailInput`*
Type: `ConnectApi.SurveyInvitationEmailInput`

A `ConnectApi.SurveyInvitationEmailInput` object.

#### Return Value

Type: `ConnectApi.SurveyInvitationEmailOutput`

# `ConnectApi` Input Classes

Some `ConnectApi` methods take arguments that are instances of `ConnectApi` input classes.

Input classes are concrete unless marked abstract in this documentation. Concrete input classes have public constructors that have no parameters.

Some methods have parameters that are typed with an abstract class. You must pass in an instance of a concrete child class for these parameters.

Most input class properties can be set. Read-only properties are noted in this documentation.

ConnectApi.SurveyInvitationEmailInput
Survey invitation email.

ConnectApi.RecipientEngagementContextInput
Context based on which the survey invitation is sent to a participant.

ConnectApi.AssociateRecordsWithRecipientInput
Records associated with the survey invitation.

## ConnectApi.SurveyInvitationEmailInput

Survey invitation email.

| Property | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `allowGuestUserResponse` | Boolean | Specifies whether participants who don't have a Salesforce account can respond (`true`) or not (`false`). | Required | 50.0 |
| `allowParticipantsAccessTheirResponse` | Boolean | Specifies whether participants can see their responses (`true`) or not (`false`). | Required | 50.0 |
| `associateRecordsWithRecipients` | List<`ConnectApi.AssociateRecordsWithRecipientInput`> | Maps each recipient with another record that must be associated with the recipient's survey invitation. | Optional | 50.0 |
| `body` | String | Content of the email. Specify the email body in case you don't specify an email template. The email body must contain one of these merge fields:<br>• To embed a link to launch the survey: [[SURVEY_INVITATION_URL]]<br>• To embed a survey question: {{{SurveyQuestion.QuestionName}}} and {{{SurveyQuestion.QuestionHtmlContent}}} | Optional | 50.0 |
| `collectAnonymousResponse` | Boolean | Specifies whether participants can respond anonymously (`true`) or not (`false`). | Required | 50.0 |
| `communityId` | String | ID of the site that's used to open the survey for users outside your org. | Optional | 50.0 |
| `emailTemplateId` | String | ID of the Lightning email template that's used to send the survey invitation. The template must contain the required merge fields that embed either the survey link or a question in the email. Only Lightning email templates are used to send survey invitations. | Optional | 50.0 |

| Property | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `fromEmailAddress` | String | Email ID of the user or the org-wide email address associated with the user's profile. | Required | 50.0 |
| `invitationExpirationDate` | Datetime | Date on which the survey invitation expires. | Optional | 50.0 |
| `invitationOwner` | String | ID of the owner of the survey invitation records. | Optional | 50.0 |
| `isPersonalInvitation` | Boolean | Specifies whether a unique invitation is created for each participant (`true`) or not (`false`). When a participant responds using a personal invitation, the response record is associated with the participant's Salesforce record. | Required | 50.0 |
| `recipientEngagementContexts` | List<`ConnectApi.RecipientEngagementContextInput`> | Maps each recipient with the context based on which the survey invitation is emailed. | Optional | 50.0 |
| `recipients` | List<String> | List of up to 300 IDs of leads, contacts, or users to whom the survey invitation is emailed. | Required | 50.0 |
| `sendEmailThroughUma` | Boolean | Specifies whether to send the email through Marketing Cloud (`true`) or not (`false`). If unspecified, defaults to `false`. | Optional | 65.0 |
| `shareInvitationsWith` | List<String> | IDs of the users with whom the survey invitation records must be shared. The invitation records are shared with Read access. | Optional | 50.0 |
| `subject` | String | Subject of the email. Specify the subject in case you don't specify an email template. | Optional | 50.0 |
| `surveyQuestionIds` | List<String> | IDs of the questions that are embedded in the email. You can send an email invitation for questions of these types: Net Promoter Score (NPS), rating, and score. | Optional | 50.0 |

## ConnectApi.RecipientEngagementContextInput

Context based on which the survey invitation is sent to a participant.

| Property | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `recipientEngagementContext` | Map<String, String> | Map each recipient with the context based on which the survey invitation is emailed. | Required | 50.0 |
| `recipientId` | String | Participant ID with whom the engagement context should be associated. | Required | 50.0 |

## ConnectApi.AssociateRecordsWithRecipientInput

Records associated with the survey invitation.

| Property | Type | Description | Required or Optional | Available Version |
|---|---|---|---|---|
| `associateRecordIds` | List<String> | ID of the associated records. | Required | 50.0 |
| `recipientId` | String | Participant ID with whose invitation the record should be associated. | Required | 50.0 |

# `ConnectApi` Output Classes

Most `ConnectApi` methods return instances of `ConnectApi` output classes.

All properties are read-only, except for instances of output classes created within test code.

All output classes are concrete unless marked abstract in this documentation.

All concrete output classes have no-argument constructors that you can invoke only from test code. See Testing ConnectApi Code.

ConnectApi.SurveyInvitationEmailOutput
Survey invitation email.

## ConnectApi.SurveyInvitationEmailOutput

Survey invitation email.

| Property Name | Type | Description | Available Version |
|---|---|---|---|
| `errorCode` | Integer | Error code for the failed call. | 50.0 |
| `errorMessage` | String | Details explaining why the call failed. | 50.0 |
| `status` | `ConnectApi.SurveyEmailStatusEnum` | Status of a survey invitation email. Values are:<br>• `Failed`—The survey invitation email wasn't sent.<br>• `Queued`—The survey invitation email is queued for sending. | 50.0 |

# industriesNlpSvc

Stores the objects used in Industries Einstein Natural Language Processing (NLP) services.

The industriesNlpSvc namespace contains these classes that are the outputs for the transformNlpActionResult on page 129 Invocable action.

- `NlpResponse` — Stores the NLP Summarization result performed for an NLP Operation involving summarization use cases such as SurveyLongSummarization and SurveyShortSummarization.
- `NlpSummarizationResult` — Provides the summary obtained as result of NLP Operation.

NlpResponse Class
Stores the result for an NLP Operation. NLP operation can be SurveyLongSummarization and SurveyShortSummarization.

NlpSummarizationResult Class
Provides the summary obtained as result of NLP Operation.

## NlpResponse Class

Stores the result for an NLP Operation. NLP operation can be SurveyLongSummarization and SurveyShortSummarization.

### Namespace

industriesNlpSvc

NlpResponse Properties

### NlpResponse Properties

The following are properties for `NlpResponse`.

summarizationResult
Represents the property that stores the NLP Summarization result performed for an NLP Operation. NLP operation can be SurveyLongSummarization and SurveyShortSummarization.

errors
Represents the property to store errors that occurred as a result of the NLP Operation.

#### `summarizationResult`

Represents the property that stores the NLP Summarization result performed for an NLP Operation. NLP operation can be SurveyLongSummarization and SurveyShortSummarization.

#### Signature

```
public industriesNlpSvc.NlpSummarizationResult summarizationResult {get; set;}
```

### Property Value

Type: List<industriesNlpSvc.NlpSummarizationResult on page 119>

#### `errors`

Represents the property to store errors that occurred as a result of the NLP Operation.

### Signature

```
public List<String> errors {get; set;}
```

### Property Value

Type: List<String>

# NlpSummarizationResult Class

Provides the summary obtained as result of NLP Operation.

## Namespace

industriesNlpSvc

NlpSummarizationResult Properties

## NlpSummarizationResult Properties

The following are properties for `NlpSummarizationResult`:

summary
Represents the field that captures the summary obtained as result of NLP Operation.

#### `summary`

Represents the field that captures the summary obtained as result of NLP Operation.

### Signature

```
public String summary {get; set;}
```

### Property Value

Type: List<String>

# CHAPTER 7 Salesforce Surveys Standard Invocable Actions

In this chapter ...


- Dynamic Send Survey Invitation Actions
- Perform Survey Sentiment Analysis
- Process Data Using Generative AI Action
- Send Survey Invitation Actions
- Transform NLP Action Results Action


Send email survey invitations to leads, contacts, and users in your org based on an action. Also, send customized notifications to users about important events or updates to the records that they're working on.

# Dynamic Send Survey Invitation Actions

Send customized notifications to users about important events or updates to the records that they're working on. For example, notify account owners when a case is created.

This action is available in API version 51.0 and later.

## Special Access Rules

To access the Dynamic Send Survey Invitation action, you must have the Feedback Management Survey Response Pack and the Salesforce org enabled with Surveys.

## Supported REST HTTP Methods

**URI**

Get the list of invocable actions for each available survey.

`/services/data/v51.0/actions/custom/dynamicSendSurveyInvitation`

Send survey invitation by email by using the invocable action.

`/services/data/v51.0/actions/custom/dynamicSendSurveyInvitation/{surveyName}`

**Formats**

JSON, XML

**HTTP Methods**

GET, HEAD, POST

**Authentication**

`Authorization: Bearer token`

## Inputs

| Input | Details |
| --- | --- |
| `anonymousResponse` | **Type**<br>boolean<br>**Description**<br>Indicates whether the participant's name is recorded in the response record (`true`) or not (`false`). |
| `autoExpiryDays` | **Type**<br>integer<br>**Description**<br>Number of days remaining for the survey invitation to expire. |
| `emailTemplateName` | **Type**<br>string |

| Input | Details |
| --- | --- |
| | **Description**<br>Developer name of the template that contains either the question or the survey link. |
| `isUnauthenticatedResponse` | **Type**<br>boolean<br>**Description**<br>Indicates whether the participant is required to authenticate before starting the survey (`true`) or not (`false`). |
| `personalInvitation` | **Type**<br>boolean<br>**Description**<br>Indicates whether the invitation is specific to the recipient (`true`) or not (`false`). |
| `recipient` | **Type**<br>reference<br>**Description**<br>Required. Salesforce ID of the record that the survey invitation is sent to. |
| `recipientType` | **Type**<br>string<br>**Description**<br>Type of the survey recipient. |
| `surveyQuestionName` | **Type**<br>string<br>**Description**<br>Developer name of the question that's sent by using the invitation. |
| `surveySubjectEntity` | **Type**<br>reference<br>**Description**<br>ID of the record that associates the invitation record with another record. |

## Outputs

None.

# Example

**GET**

This example shows how to get information about the Dynamic Send Survey Invitation action type.

```
curl --include --request GET \
--header "Authorization: Authorization: Bearer 00DR...xyz" \
--header "Content-Type: application/json" \
"https://instance.salesforce.com/services/data/v51.0/actions/custom/dynamicSendSurveyInvitation"
```

Here's a response that returns the list of invocable actions for each survey.

```
{
  "actions" : [ {
    "label" : "flowsend",
    "name" : "flowsend",
    "type" : "SEND_SURVEY_DYNAMIC_INVOCABLE_ACTION",
    "url" : "/services/data/v51.0/actions/custom/dynamicSendSurveyInvitation/flowsend"
  }, {
    "label" : "survey2",
    "name" : "survey2",
    "type" : "SEND_SURVEY_DYNAMIC_INVOCABLE_ACTION",
    "url" : "/services/data/v51.0/actions/custom/dynamicSendSurveyInvitation/survey2"
  }, {
    "label" : "survey",
    "name" : "survey",
    "type" : "SEND_SURVEY_DYNAMIC_INVOCABLE_ACTION",
    "url" : "/services/data/v51.0/actions/custom/dynamicSendSurveyInvitation/survey"
  } ]
}
```

**POST**

Here's a request for the Dynamic Send Survey Invitation action.

```
{
   "inputs":[{
      "recipient" : "003xx000004WpemAAC",
      "isUnauthenticatedResponse" : false,
      "autoExpiryDays" : 6
   }]
}
```

Here's a response for the Dynamic Send Survey Invitation action.

```
[
   {
      "actionName" : "survey",
      "errors" : null,
      "isSuccess" : true,
      "outputValues" : null
   }
]
```

# Perform Survey Sentiment Analysis

Create or update the AI Sentiment Result records. You can get insights into the sentiments underlying survey responses and save the sentiment analysis in the SentimentAnalysisResult object.

This action is available in API version 55.0 and later.

## Special Access Rules

To access the Perform Survey Sentiment Analysis action, you must have the Feedback Management - Starter and Feedback Management - Growth licenses.

## Supported REST HTTP Methods

**URI**

`/services/data/v55.0/actions/standard/performSurveySentimentAnalysis`

**Formats**

JSON

**HTTP Methods**

POST

**Authentication**

`Authorization: Bearer token`

## Inputs

| Input | Details |
| --- | --- |
| `surveyId` | **Type**<br>ID<br>**Description**<br>Required. The ID of the survey containing the questions for whose responses you want to get sentiment insights. |
| `surveyQuestionIds` | **Type**<br>ID<br>**Description**<br>Required. The IDs of the questions for whose responses you want to get sentiment insights. |
| `startDate` | **Type**<br>Datetime<br>**Description**<br>Required. The date from when participant responses are processed to get sentiment insights. |
| `endDate` | **Type**<br>Datetime |

| Input | Details |
| --- | --- |
| | **Description**<br>Required. The date until when participant responses are processed to get sentiment insights. |
| `typeOfOperation` | **Type**<br>String<br>**Description**<br>Required. The type of operation to be performed on the survey responses.<br>Possible values are:<br>• `create`—Bulk process survey responses. After the processing is completed, the AI Sentiment Result records are created with the Submitted status.<br>• `update`—Bulk process survey responses that have associated AI Sentiment Result records in the Draft status. After the processing is completed, the AI Sentiment Result records are updated and their status is changed to Submitted.<br>You can only update a sentiment analysis result record with the Draft status. |

## Outputs

None.

## Example

**Sample Request**

Here's an example POST request to create or update the AI Sentiment Result records:

```
{
   "inputs":[{
      "surveyId":"0Kdx00000000GYeCAM",
      "surveyQuestionIds":["0Kux00000000xDgCAI","0Kux00000000xDiCAI"],
      "startDate":"1-07-2022",
      "endDate":"12-07-2022",
      "typeOfOperation":"create"
   }]
}
```

# Process Data Using Generative AI Action

Using Einstein Generative AI, perform Natural Language Processing (NLP) to summarize text, extract key phrases, analyze sentiment, and unlock valuable insights.

This action is available in API version 61.0 and later.

To access the Process Data Using Generative AI action, you must have the Salesforce Feedback Management Starter or Growth License and the Salesforce org enabled with Surveys along with Generative AI Surveys feature.

## Supported REST HTTP Methods

**URI**

`/services/data/v61.0/actions/standard/processDataUsingGenAi`

**Formats**

JSON, XML

**HTTP Methods**

POST

**Authentication**

`Authorization: Bearer token`

## Inputs

| Input | Details |
| --- | --- |
| `additionalParameterIds` | **Type**<br>String<br>**Description**<br>Collection of additional record IDs on which NLP is performed. |
| `feature` | **Type**<br>String (Picklist)<br>Required<br>**Description**<br>Purpose of applying NLP to the target record. Valid values are:<br>• `SurveyLongSummarization`<br>• `SurveyShortSummarization` |
| `targetRecordId` | **Type**<br>String<br>Required<br>**Description**<br>ID of the record on which NLP is performed. |

## Outputs

| Output | Details |
| --- | --- |
| `nlpRecordId` | **Type**<br>string<br>**Description**<br>ID of the created NLP record. |

## Example

**POST**

This example shows a sample request for the Process Data Using Generative AI action.

```
{
   "inputs":[{
      "targetRecordId": "0MySM00000007eD0xx",
      "additionalParameterIds": [
 "0KuSM0000000JM10xx","0KuSM0000000JM20xx","0KuSM0000000JM30xx","0KuSM0000000JM40xx"
      ],
      "feature": "SurveyLongSummarization"   }]
}
```

This example shows a sample response for the Process Data Using Generative AI action.

```
[
   {
      "nlpRecordId" : "7NPSM0000000K5B4xx"
   }
]
```

# Send Survey Invitation Actions

Send email survey invitations to leads, contacts, and users in your org based on an action. For example, send a survey invitation when a customer support case closes.

This action is available in API version 47.0 and later.

## Special Access Rules

To access the Send Survey Invitation action, you must have the Feedback Management Survey Response Pack and the Salesforce org enabled with Surveys.

## Supported REST HTTP Methods

**URI**

`/services/data/v47.0/actions/standard/sendSurveyInvitation`

**Formats**

JSON, XML

**HTTP Methods**

GET, HEAD, POST

**Authentication**

`Authorization: Bearer token`

# Inputs

| Input | Details |
| --- | --- |
| `anonymousResponse` | **Type**<br>boolean<br>**Description**<br>Indicates whether the participant's name is recorded in the response record (`true`) or not (`false`). |
| `autoExpiryDays` | **Type**<br>integer<br>**Description**<br>Number of days remaining for the survey invitation to expire. |
| `emailTemplateName` | **Type**<br>string<br>**Description**<br>Developer name of the template that contains either the question or the survey link. |
| `isUnauthenticatedResponse` | **Type**<br>boolean<br>**Description**<br>Indicates whether the participant is required to authenticate before starting the survey (`true`) or not (`false`). |
| `personalInvitation` | **Type**<br>boolean<br>**Description**<br>Indicates whether the invitation is specific to the recipient (`true`) or not (`false`). |
| `recipient` | **Type**<br>reference<br>**Description**<br>Required. Salesforce ID of the record that the survey invitation is sent to. The record can be a user (internal invitation) or a contact or a lead (external invitation via community). |
| `surveyName` | **Type**<br>string<br>**Description**<br>Required. Developer name of the survey that the invitation is sent for. |
| `surveyQuestionName` | **Type**<br>string |

| Input | Details |
| --- | --- |
| | **Description**<br>Developer name of the question that's sent using the invitation. |
| `surveySubjectEntity` | **Type**<br>reference<br>**Description**<br>ID of the record that associates the invitation record with another record. |

## Outputs

None.

## Example

**GET**

This example shows how to get information about the Send Survey Invitation action type.

```
curl --include --request GET \
--header "Authorization: Authorization: Bearer 00DR...xyz" \
--header "Content-Type: application/json" \
"https://instance.salesforce.com/services/data/v47.0/actions/standard/sendSurveyInvitation"
```

**POST**

Here's a request for the send survey invitation action.

```
{
   "inputs":[{
      "surveyName" : "FlowActionSend",
      "recipient"  : "003RO0000037IRvYAM",
      "autoExpiryDays" : 6
   }]
}
```

Here's a response for the send survey invitation action.

```
[
   {
      "actionName" : "sendSurveyInvitation",
      "errors" : null,
      "isSuccess" : true,
      "outputValues" : null
   }
]
```

# Transform NLP Action Results Action

Transform an AI Natural Language Processing (NLP) result created by using Einstein Generative AI into an Apex Object record.

This action is available in API version 61.0 and later.

To access the Transform NLP Action Results action, you must have the Salesforce Feedback Management Starter or Growth License and the Salesforce org enabled with Surveys along with Generative AI Surveys feature.

## Supported REST HTTP Methods

**URI**

Get the list of invocable actions for each available survey.

`/services/data/v61.0/actions/standard/transformNlpActionResult`

**Formats**

JSON, XML

**HTTP Methods**

POST

**Authentication**

`Authorization: Bearer token`

## Inputs

| Input | Details |
| --- | --- |
| `nlpRecordId` | **Type**<br>String<br>Required<br>**Description**<br>ID of the AI natural language process result (type `AiNaturalLangProcessRslt`) record to perform natural language processing on. |
| `feature` | **Type**<br>String<br>Required<br>**Description**<br>Purpose that the NLP response is used for. Valid values are:<br>• `SurveyLongSummarization`<br>• `SurveyShortSummarization` |

## Outputs

| Output | Details |
| --- | --- |
| `nlpResponse` | **Type**<br>string |

| Output | Details |
| --- | --- |
| | **Description**<br>Apex industries NLP response record that contains the action output. |
| `status` | **Type**<br>string<br>**Description**<br>Status of the NLP operation. Valid values are:<br>• `completed`<br>• `failure`<br>• `notStarted`<br>• `pending` |

# Example

**POST**

This example shows a sample request for the Transform NLP Action Result action.

```
{
  "inputs": [
    {
      "nlpRecordId": "7NPSM0000000K5B4xx",
      "feature": "SurveyLongSummarization"
    }
  ]
}
```

This example shows a sample response for the Transform NLP Action Result action.

```
  {
    "nlpResponse": {
      "summarizationResult": {
        "summary": "The majority of respondents found the process cumbersome and
experienced issues with the payment web page. There were no specific suggestions provided
 for improving the product."
      },
      "status": "completed"
    }
  }
```

# CHAPTER 8 Salesforce Surveys Use Cases

In this chapter ...


- Creation of Surveys by Using Salesforce Feedback Management Response APIs


Learn more about surveys through use cases and usage examples.

Refer to the use cases and usage examples in this section to deepen your knowledge about using surveys. Learn how to:

- Create in-app surveys.
- Use Lightning Web Components (LWCs) for Surveys.

# Creation of Surveys by Using Salesforce Feedback Management Response APIs

Learn how you can create surveys using the Salesforce Feedback Management Response APIs.

Customer experience is the cornerstone of any company's success. Understanding customer sentiment through feedback is critical to a company's growth lifecycle. Get to know customer satisfaction levels and gain deeper insights about your products or services through Surveys.

Surveys enable you to gather continuous feedback, and then to work towards meeting customer expectations. You can invest further to enhance customer experience in areas where you find positive feedback, or pivot by using alternate plans to address negative feedback.

Use Salesforce Feedback Management (SFM) Response APIs to build in-app surveys. In-app surveys retain the application context as survey participants don't have to switch to other applications to complete the survey. In-app surveys also provide a user-friendly and intuitive experience that can be customized to reflect your company's theme and branding, thus, increasing survey response rates.

Let's look at a scenario that uses the capabilities of SFM Response APIs to build in-app surveys.

Consider a scenario wherein a company, Dream House, wants to get employee feedback on their new hire onboarding process.

Note: The API endpoints mentioned later in this scenario apply to authenticated users only.

In-App Survey Overview
Get your environment ready before you create a sample in-app survey. With the Surveys setup ready in Salesforce, prepare survey details, create and send invitations, and collect survey responses.

## In-App Survey Overview

Get your environment ready before you create a sample in-app survey. With the Surveys setup ready in Salesforce, prepare survey details, create and send invitations, and collect survey responses.

Here's a high-level overview of how you can create an in-app survey.




Set Up Your Environment
Get your Salesforce environment ready before you create your first in-app survey.
Lightning Web Components for Surveys
Lightning Web Components (LWCs) for Surveys provide a variety of question types that you can use in a survey.
Survey Questionnaire
Create a basic survey by using Survey Builder and prepare the questionnaire by using various types of survey questions.

Survey Invitations

Learn how to create survey invitations through API requests that are invoked from an Apex class.

Survey Responses

Use API responses to show survey questions in Salesforce.

## Set Up Your Environment

Get your Salesforce environment ready before you create your first in-app survey.

To create an in-app survey, set up your environment with these prerequisites.

- Enable users to create surveys and send them to the participants by enabling the Surveys feature in Salesforce Setup. See Enable Surveys and Configure Survey Settings.
- Create a named credential with a callout endpoint by using your credentials and then use it in an Apex class that makes Connect REST API calls by using SFM APIs. See Named Credentials as Callout Endpoints.
- Configure the sample LWCs that are available with the package along with an Apex class to integrate the LWCs. Embed the LWCs in Salesforce Lightning pages, such as the home page or record pages to help the participants respond to the survey in Salesforce. See LWCs for Surveys.
  1. Specify a valid `SurveyId` value and the details of named credentials in the SurveyApi Apex class (`SurveyApi.cls` file) from the package.
  2. Deploy your LWCs in Salesforce. See Deploy LWCs in Salesforce.
  3. Configure the LWCs provided with the package for Lightning App Builder. See Configure a Component for Lightning App Builder.

EDITIONS

Available in: Salesforce Classic (not available in all orgs) and Lightning Experience

Available in: **Developer**, **Enterprise**, and **Unlimited** Editions

Available with the Feedback Management - Growth or Feedback Management - Starter license

USER PERMISSIONS

To create a basic survey:

- Permissions to create surveys

SEE ALSO:

Salesforce Help: Feedback Management Licenses

## Lightning Web Components for Surveys

Lightning Web Components (LWCs) for Surveys provide a variety of question types that you can use in a survey.

EDITIONS

Available in: **Developer**, **Enterprise**, and **Unlimited** Editions

### LWCs for Surveys

Lightning Web Components—a Salesforce recommended framework—enable participants to respond to any type of Feedback Management survey. LWCs can be added to standard or custom lightning pages to show the survey to the participants and to enable the participants to submit their response.

Here's the list of LWCs from the package that show a specific question type in a survey.

| LWC Name | Description |
|---|---|
| SurveyContainer | Interacts with the Apex class and shows the survey contents. |
| SurveyQuestion | Invokes the question-specific component. |
| surveyBooleanQuestion | Shows the boolean type of questions |

| LWC Name | Description |
| --- | --- |
| surveyShortTextQuestion | Shows the short text type of questions. |
| surveySingleSelectQuestion | Shows the single selection type of questions. |
| surveyMultiSelectQuestion, surveyNpsQuestion, surveyRatingQuestion, and surveyFreeTextQuestion | Shows other supported question types, such as multi-select type of questions, Net Promoter Score (NPS) questions, rating questions, or free-text questions. |

SEE ALSO:

*Lightning Web Components Developer Guide*: Configure a Component for Lightning App Builder

## Survey Questionnaire

Create a basic survey by using Survey Builder and prepare the questionnaire by using various types of survey questions.

Use Survey Builder to create a basic survey that has these questions.

- Rating question: How do you rate the onboarding process?
- Short text question: Would you recommend this process to your colleagues?
- Long text question: Describe your experience in a few words.

Note: Only basic surveys support the SFM APIs.

See Create a Basic Survey.

Here's how the survey appears in the Survey Builder after the Lightning Web Components (LWCs) are built and integrated.



## Survey Invitations

Learn how to create survey invitations through API requests that are invoked from an Apex class.

Survey invitations are created using these steps.

1. The SurveyApi Apex class (SurveyApi.cls file) is available within a package. The POST method from the SurveyApi Apex class calls the API endpoint having the required payload to create the survey invitation.

   **Resource**

   ```
   /services/data/vXX.X/connect/surveys/surveyId/survey-response
   ```

   **Request body for POST**

   ```
   {
     "languageCode": "",
     "invitationSettings": {
       "allowGuestUserResponse": false,
       "allowParticipantsAccessTheirResponse": false,
       "collectAnonymousResponse": false,
       "invitationExpirationDate": "2022-07-31T21:32:54",
       "communityId": "",
       "invitationOwner": ""
     }
   }
   ```

   See Survey Responses Using Invitation Configurations for details of the request properties.

2. The response to the previous POST request fetches the survey and its questions.

   **Response**

   ```
   {
     "languageCode": "en",
     "invitationId": "0Kixx0000004MWaCAM",
     "flowInterviewState": "state1",
     "status": "Success",
     "surveyDetail": {
       "label": "Survey01",
       "name": "Survey01",
       "surveyPage": {
         "label": "Page 1",
         "name": "p_d84afb73_3a30_4a3f_aae7_b0478b3bb4ed",
         "surveyQuestions": [
           {
             "name": "q_856a997e_be2c_4ea3_b70d_7f6fb9cfbf4f",
             "label": "Good so Far!",
             "questionType": "ShortText",
             "responseDataType": "STRING",
             "validationFormula": <Formula if any custom validation is added>,
             "isResponseRequired": false
           }
         ]
       "versionLabel":"<Survey name>",
       "versionNumber": <Survey version>
       }
     },
   ```

```
  "errors": [],
  "warnings": []
}
```

3. The SurveyApi Apex class also has the code to parse the API response, which returns the survey details and questions to the Lightning Web Component (LWC).

   See Survey Description Output for details of the response properties.

   Here's how the survey appears on the Salesforce home page.




## Survey Responses

Use API responses to show survey questions in Salesforce.

Create a submit button or enable a trigger to call the Apex class for submitting the responses.

The SurveyApi Apex class uses the PATCH request endpoint to submit the survey responses using this format:

**Resource**

```
/services/data/vXX.X/connect/surveys/<surveyId>/invitation/<invitationId>/survey-response
```

Note: The invitationId property is retrieved from the POST API request. The flowInterviewState property is retrieved from the first POST API request and later from subsequent PATCH API requests.

### Request body for PATCH

Here's an example for multiple questions.

```
{
  "invitationId": "0Kixx0000004DbMCAU",
  "flowInterviewState": "<FlowInterviewState>",
  "surveyPageResponses": {
    "questionResponses": [
      {
        "name": "q_d217f330_05a6_4e2b_859b_1f1ef210bf84",
        "questionType": "NPS",
        "responseValue": 5
      },
      {
        "name": "q_ab781617_3665_4a41_b4ff_f236d73ecb30",
        "questionType": "FreeText",
        "responseValue": "Free Text Question Response"
      },
      {
        "name": "q_b1cdfe4c_9c7d_4c2f_ad9d_1915d301d780",
        "questionType": "ShortText",
        "responseValue": "Short Text Question Response"
      },
      {
        "name": "q_f84a6a3c_683c_4ed5_864e_5b486baed308",
        "questionType": "Boolean",
        "responses": [
          {
            "name": "choice1"
          }
        ]
      },
      {
        "name": "q_113419b1_5d29_4bb9_8b10_e3fe324ae040",
        "questionType": "MultiChoice",
        "responses": [
          {
            "name": "c_9775c2e5_9086_44a8_a5c9_89fdc886c99a"
          },
          {
            "name": "c_0f1f63cc_608a_4560_9d29_72b203f195f2"
          }
        ]
      },
      {
        "name": "q_1d8690a9_ae95_4e7c_86be_b8057205facc",
        "questionType": "RadioButton",
        "responses": [
          {
            "name": "c_4867edc8_e9a6_4e86_9fea_b80758e90caf"
          }
        ]
      },
      {
```

```
        "name": "q_8946f212_25ff_43a8_a507_d267637eee1f",
        "questionType": "Rating",
        "responses": [
          {
            "name": "c_f51c509a_9643_4a05_89f1_42464de618a6"
          }
        ]
      }
    ]
  }
}
```

**Response**

```
{
   "errors":[],
   "status":"Success",
   "surveyPage":{
     "label": null,
     "messageDescription":"",
     "name": null,
     "redirectUrl": "<URL of the page to be redirected>",
     "thankYouMessage":"<Thank you message to be displayed>",
     "urlButtons":[ // List of URL text and URL for buttons to be displayed
]
   }
}
```

If the PATCH API request is successful, the feedback is submitted and a Thank You page is displayed.